

2006trans1\_a .doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Transmission Control Module Read Only Memory	P0601	EPROM/Flash memory corruption (Incorrect program/calibrations checksum)	ROM fail count $\geq 5$	None	Immediate  Type A
Transmission Control Module Not Programmed	P0602	Non-programmed TCM (calibrations)	KbCOND_NoStartCal = TRUE	None	Immediate  Type A
Transmission Control Module Long-Term Memory Reset	P0603	Wrong copy of Non-volatile Memory to RAM	Non-volatile memory (static or dynamic) checksum failure	None	Immediate  Type A
Transmission Control Module Random Access Memory	P0604	RAM failure	RAM read/write failure (single word)  RAM fail count $\geq 5$	None	Immediate  Type A
Trans Fluid Temp Sensor Circuit Range/ Performance	P0711	The DTC detects the following failure modes of the TFT:  1) A sensor that remains at a value. (Stuck Sensor)  2) A sensor that remains at a value. (Stuck Sensor)  4) Transmission Temperature remains below 20° C for a calibrated time dependant on startup transmission temperature.	<u>Fail Case 1</u> $\Delta TFT < 2^{\circ}C$ . TCC Slip $\geq 120$ RPM for 300 sec cumul. $-39^{\circ}C \leq TFT$ at startup $\leq 20^{\circ}C$ .  <u>Fail Case 2</u> $\Delta TFT < 2^{\circ}C$ . $129^{\circ}C \leq TFT$ at startup $\leq 149^{\circ}C$ .  <u>Fail Case 4</u> $TFT \leq 20^{\circ}C$ after a calibrated amount of time based on a 2D lookup table.	<u>For fail case 1, 2, and 4:</u> Common ignition voltage enable, Common engine speed enable, No Engine Coolant DTC's, No OSS P0722, P0723 DTCs, No ISS P0716, P0717 DTCs, P0711 has not passed this ignition cycle, $-39^{\circ}C \leq$ trans fluid temp $\leq 149^{\circ}C$  <u>Fail case 1:</u> $-39^{\circ}C \leq$ trans fluid temp $\leq 20^{\circ}C$ at startup, Engine coolant $\geq 70^{\circ}C$ , Engine Coolant has changed $\geq 55^{\circ}C$ since startup, Vehicle speed $\geq 8$ kph for $> 300$ seconds (cumulative timer)  <u>Fail case 2:</u> $129^{\circ}C \leq$ trans fluid temp $\leq 149^{\circ}C$ at startup, Engine coolant $\geq 70^{\circ}C$ Engine Coolant has changed $\geq 55^{\circ}C$ since startup, Vehicle speed $\geq 8$ kph for $\geq 300$ seconds (cumulative timer)  <u>Fail case 4:</u> Valid TPS, Torque signal, and Crank Signals. $50 \text{ Nm} \leq$ Engine Torque $\leq 1492 \text{ Nm}$ $2\% \leq$ Throttle Position $\leq 90\%$ $8 \text{ kph} \leq$ Vehicle Speed $\leq 511 \text{ kph}$ $500 \text{ rpm} \leq$ Engine Speed $\leq 6500 \text{ rpm}$ $-39^{\circ}C \leq$ Coolant Temperature $\leq 149^{\circ}C$	<u>Fail case 1:</u> 80.0 seconds  <u>Fail case 2:</u> 80.0 seconds  <u>Fail case 4:</u> Between 200 & 1900 seconds dependant on startup trans temperature.  Type C-

2006trans1\_a .doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Transmission Fluid Temperature Sensor Circuit Low Voltage	P0712	Continuous Short-to-Ground in Trans Fluid Temperature sensor or TFT signal circuit	Trans Temp Sensor $\leq 43.19$ ohm Trans Temp $> 150C$	$8V \leq$ Ignition Voltage $\leq 18V$ for 5 sec $500 \leq$ Engine RPM $\leq 6500$ for 5.0 sec	12.0 sec  Type C-
Transmission Fluid Temperature Sensor Circuit High Voltage	P0713	Continuous Open of Short to Voltage in Transmission Fluid Temperature sensor or TFT signal circuit	Trans Temp Sensor $\geq 171862$ ohm Trans Temp $< -40C$ (-40F)	No P0716, P0717, P0722, P0723 DTCs $500 \leq$ Engine RPM $\geq 6500$ for 5.0 sec $8.0 \leq$ Ignition Voltage $\leq 18.0 V$ OSS $\geq 64.3^*$ RPM for 200 sec cumul. TCC Slip $\geq 120$ RPM for 200 sec cumul.	80.0 sec  Type C-
Input Speed Sensor Performance	P0716	0 – 6500 RPM  Unrealistically large drop in Input Speed in a very period of time that remains	Input Speed drop $\geq 1000$ RPM	No P0717, P0722, P0723, P0752, P0973, P0974 DTCs $8V \leq$ Ignition Voltage $\leq 18V$ $500 \leq$ Engine RPM $\leq 6500$ for 5 sec No TP malfunction No Engine Torque malfunction $50 \leq$ Engine Torque $\leq 1492$ N-m TPS $\geq 8.0\%$ Vehicle Speed $\geq 16.0$ kph ISS $\geq 1050$ RPM for 2.0 sec $\Delta$ ISS $\leq 500$ RPM for 2.0 sec	3.25 sec  Type B
Input Speed Sensor Circuit Low Voltage	P0717	0 – 6500 RPM  Low Input Speed with large vehicle speed	Input Speed $< 100.0$ RPM	No P0717, P0722, P0723 DTCs No Engine Torque malfunction $500 \leq$ Engine RPM $\leq 6500$ for 5 sec $8V \leq$ Ignition Voltage $\leq 18V$ Vehicle Speed $\geq 16.0$ kph $50 \leq$ Engine Torque $\leq 1492$ N-m	4.5 sec  Type B
Output Speed Sensor Circuit Low Voltage	P0722	0 - 6500 RPM  Low vehicle speed with large engine speed in Drive range	<u>Drive</u> $50 \leq$ Engine Torque $\leq 1492$ N-m Output Speed $\leq 64.3^*$ RPM  <u>Park/Neutral</u> $1492 \leq$ Engine Torque $\leq 1492$ N-m	No, P0716, P0717, P0723 No TPS malfunction No Engine Torque malfunction $8V \leq$ Ignition Voltage $\leq 18V$ $500 \leq$ Engine RPM $\leq 6500$ for 5.0 sec Range $\neq$ P/N TCC Slip $\geq -20$ RPM Trans Temp $\geq -40^\circ C$ . $1500$ RPM $\leq$ Input Speed $\leq 6500$ RPM TPS $\geq 8.0\%$	4.5 sec  Type B
Output Speed Sensor Circuit Intermittent	P0723	0 - 6500 RPM  Loss of vehicle speed when vehicle is moving	Drop in Output Speed $> 385.8^*$ RPM in any Drive range	No P0716, P0717, P0974 DTC $8V \leq$ Ignition Voltage $\leq 18V$ $500 \leq$ Engine RPM $\geq 6500$ for 5 sec Range $\neq$ P/N $50$ Nm $\leq$ Engine Torque $\leq 1492$ Nm Time since last range change $\geq 6.0$ sec $+\Delta$ VSS, loop-to-loop, $\leq 160.8^*$ RPM for 2.0 sec $\Delta$ ISS $\leq 500$ RPM for 2.0 sec Output Speed $\geq 321.5^*$ RPM for 2.0 sec	3.25 sec  Type B

2006trans1\_a .doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Torque Converter Clutch System - Stuck Off	P0741	High TCC slip with TCC commanded on	TCC slip Error $\geq$ 125 RPM  Count = 2	No P0716, P0717, P0722, P0723, P0742 No TPS malfunction No Engine Torque and Speed malfunctions $8V \leq$ Ignition Voltage $\leq$ 18V $500 \leq$ Engine RPM $\leq$ 6500 for 5.0 sec $50 \leq$ Engine Torque $\leq$ 1492 N-m $2.0\% \leq$ TPS $\leq$ 90% $20^\circ C. \leq$ Trans Temp $\leq$ 130° C. TCC Capacity $\geq$ 65% for 2.0 sec Commanded Gear > 2 TCC Mode = On or Locked On	8 sec  Type B
Torque Converter Clutch System - Stuck On	P0742	Low TCC slip with TCC commanded off	-20 rpm $\leq$ TCC Slip Speed $\leq$ 40 rpm  Count = 4	No P0716, P0717, P0722, P0723, P0741 No TPS malfunction No Engine Torque and Speed malfunctions $8V \leq$ Ignition Voltage $\leq$ 18V $500 \leq$ Engine RPM $\leq$ 6500 for 5.0 sec TCC commanded OFF $50 \leq$ Engine Torque $\leq$ 1492 N-m $20^\circ C. \leq$ Trans Temp $\leq$ 130° C. $8\% \leq$ TPS $\leq$ 90% $16 \text{ kph} \leq$ VSS $\leq$ 511 kph $1.07 \geq$ Gear Ratio $\geq$ 0.6324	4.0 sec  Type B
1-2 Shift Solenoid Valve Performance - No First or Fourth Gear	P0751	2-2-3-3 shift pattern	<u>Fail Case 1</u> Commanded 1st $1.5483 <$ Ratio $<$ 1.7115  <u>Fail Case 2</u> Commanded 4th $0.95 <$ Ratio $<$ 1.05  Count = 2	No P0716, P0717, P0722, P0723, P0742, P0973, P0974, P0976, P0977, or TPS DTCs (see below) No Engine Torque malfunction $500 \leq$ Engine RPM $\leq$ 6500 for 5.0 sec $8V \leq$ Ignition Voltage $\leq$ 18V TPS $\geq$ 8.0% $20^\circ C. <$ Trans Temp $<$ 130° C. 1.0 sec. after gear change $150 \leq$ Input Speed $\leq$ 6500 RPM $50 \leq$ Engine Torque $\leq$ 1492 N-m Output Speed $\geq$ 64.3* RPM	<u>Fail Case 1</u> 2.0 sec  <u>Fail Case 2</u> 4.0 sec  Type B
1-2 Shift Solenoid Valve Performance - No Second or Third Gear	P0752	1-1-4-4 shift pattern	<u>Fail Case 3</u> Commanded 2nd $2.8120 <$ Ratio $<$ 3.1080  <u>Fail Case 4</u> Commanded 3 <sup>rd</sup> $0.6458 <$ Ratio $<$ 0.7137  Count = 2	See P0751	<u>Fail Case 3</u> 2.0 sec  <u>Fail Case 4</u> 3.0 sec  Type B

2006trans1\_a .doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
2-3 Shift Solenoid Valve Performance - No First or Second Gear	P0756	4-3-3-4 shift pattern	<p><u>Fail Case 5</u>  <math>-20 \leq \text{TCC Slip} \leq 8191 \text{ RPM}</math>  <math>\text{VSS} \geq 64.3^* \text{ RPM}</math>                      Commanded 1st  <math>0.6458 \leq \text{Ratio} \leq 0.7137</math></p> <p><u>Fail Case 6</u>                      Commanded 2nd  <math>0.95 \leq \text{Ratio} \leq 1.05</math></p> <p>Count = 2</p>	See P0751	<p><u>Fail Case 5</u>                      2.0 sec</p> <p><u>Fail Case 6</u>                      3.0 sec</p> <p>Type A</p>
2-3 Shift Solenoid Valve Performance - No Third or Fourth Gear	P0757	1-2-2-1 shift pattern	<p><u>Fail Case 7</u>  <math>50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}</math>                      Commanded 3rd  <math>1.5483 &lt; \text{Ratio} &lt; 1.7115</math></p> <p><u>Fail Case 8</u>  <math>5 \leq \text{Engine Torque} \leq 1492 \text{ N-m}</math>                      Commanded 4<sup>th</sup>  <math>2.8120 &lt; \text{Ratio} &lt; 3.1080</math></p> <p>Count = 2</p>	See P0751	<p><u>Fail Case 7</u>                      2.0 sec</p> <p><u>Fail Case 8</u>                      2.0 sec</p> <p>Type A</p>
1-2 Shift Solenoid Control Circuit Low Voltage	P0973	0 – 12 V  Continuous Short-to-Ground OR Open in Shift Solenoid A or SSA circuit (ODM)	SSA ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec)  Type B
1-2 Shift Solenoid Control Circuit High Voltage	P0974	0 – 12 V  Continuous Short-to-Power in Shift Solenoid A or SSA circuit (ODM)	SSA ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec)  Type B
2-3 Shift Solenoid Control Circuit Low Voltage	P0976	0 – 12 V  Continuous Short-to-Ground OR Open in Shift Solenoid B or SSB circuit (ODM)	SSB ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec)  Type A
2-3 Shift Solenoid Control Circuit High Voltage	P0977	0 – 12 V  Continuous Short-to-Power in Shift Solenoid B or SSB circuit (ODM)	SSB ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec)  Type A
Transmission Control Module Long Term Memory Performance	P1621	NVM write error at key-down	TCM Non-Volatile Memory Incorrect flag = 1	$8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$ Ignition ON	Immediate  Type A

2006trans1\_a.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Internal Mode Switch A Circuit Low Voltage	P1820	0 – 12 V IMS A Signal is Low in Park and Drive	IMS Input A = Low in Drive (Range = Transitional 1)	8V ≤ Ignition Voltage ≤ 18V 500 ≤ Engine RPM ≤ 6500 for 5.0 sec Has not passed this key cycle IMS Input A = Low in Park for 1 sec No Engine Torque Malfunction 50 ≤ Engine Torque ≤ 1492 N-m	8.0 sec Type B
Internal Mode Switch B Circuit High Voltage	P1822	0 – 12 V IMS B Signal is High in Park and Drive	IMS Input B = High/Open in Drive (Range = Transitional13)	8V ≤ Ignition Voltage ≤ 18V 500 < Engine RPM < 6500 for 5.0 sec Has not passed this key cycle IMS Input B = High in Park for 1 sec No Engine Torque Malfunction 50 ≤ Engine Torque ≤ 1492 N-m	8.0 sec Type B
IMS Mode 'P' Ckt Low	P1823	0 – 12 V IMS P Signal is High in Park and Drive	IMS Input P = Low in Drive (Range = Transitional 8)	8V ≤ Ignition Voltage ≤ 18V 500 ≤ Engine RPM ≤ 6500 for 5.0 sec Has not passed this key cycle IMS Input P = Low in Park for 1 sec No Engine Torque Malfunction 50 ≤ Engine Torque ≤ 1492 N-m	8.0 sec Type B
Trans Internal Mode Switch Illegal Range	P1825	0 - 12V	Range is Illegal	8V ≤ Ignition Voltage ≤ 18V 500 ≤ Engine RPM ≤ 6500 for 5.0 sec	8.0 sec Type B
Internal Mode Switch C Circuit High Voltage	P1826	0 – 12 V IMS C Signal is High in Drive	IMS Input C = High/Open in Drive (Range = Transitional)	No P0722 or P0723 DTC's 8V ≤ Ignition Voltage ≤ 18V Has not passed this key cycle Engine Torque ≥ 50 Nm Vehicle Speed ≥ 16 kph 3.1672 ≥ Gear Ratio ≥ 2.7528 or 1.7441 ≥ Gear Ratio ≥ 1.5157 or 1.0699 ≥ Gear Ratio ≥ 0.9301 or 0.7275 ≥ Gear Ratio ≥ 0.6324	8.0 sec Type B
Internal Mode Switch Does Not Indicate P/N During Start	P1915	0 – 12 V	IMS Not Equal to Park/Neutral During Crank	6V ≤ Ignition Voltage ≤ 18V Engine Speed ≥ 450 rpm Crank Requested ≥ 2.5 sec	2.0 sec Type B
Ignition 1 Switch Circuit Low Voltage	P2534	Continuous Open/Short-to-Ground in TCM Ignition 1 Switch circuit	Every 25 msec, the FAIL counter is incremented if an open or a short to ground is detected	Engine running	Fail Counts ≥ 200 out of 220 Samples (Time ≈ 5 sec)  Continuous Type A

2006trans1\_a.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Torque Converter Clutch Pressure Control Solenoid Control Circuit High Voltage	P2763	Continuous Short-to-Voltage in TCC PWM circuit	Every 100 msec, the FAIL counter is incremented if a short to voltage is detected	Ignition ON 8V ≤ Ignition Voltage ≤ 18V 500 ≤ Engine RPM ≤ 6500 for 5.0 sec TCC Commanded ON	Fail Count = 44 out of 50 (Time ≈ 4.4 sec)  Continuous  Type B
Torque Converter Clutch Pressure Control Solenoid Control Circuit Low Voltage	P2764	Continuous Open/Short-to-Ground in TCC PWM circuit or TCC PWM solenoid	Every 100 msec, the FAIL counter is incremented if an open or a short to ground is detected	Ignition ON 8V ≤ Ignition Voltage ≤ 18V 500 ≤ Engine RPM ≤ 6500 for 5.0 sec	Fail Count = 44 out of 50 (Time ≈ 4.4 sec)  Continuous  Type B
Controller Area Network Bus Communication Error	U0073	TCM cannot communicate on the CAN Bus	GetCNDD_b_BusOffSt() = TRUE	Ignition ON  8V ≤ Ignition Voltage ≤ 18V for 5 seconds	Fail Count = 5 out of 5 (Time ≈ 5 sec)    Type B
Lost Communications with Engine Control System	U0100	Communication between TCM & Engine Control System Lost	CAN Bus ECM Error flag = 1	Ignition ON  8V ≤ Ignition Voltage ≤ 18V for 5 seconds	Fail Count = 12 out of 12 (Time ≈ 12 sec)    Type B