

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Transmission Control Module Read Only Memory	P0601	EPROM/Flash memory corruption (Incorrect program/calibrations checksum)	ROM fail count $\geq 5$	None	Immediate Type A
Transmission Control Module Not Programmed	P0602	Non-programmed TCM (calibrations)	KbCOND_NoStartCal = TRUE	None	Immediate Type A
Transmission Control Module Long-Term Memory Reset	P0603	Wrong copy of Non-volatile Memory to RAM	Non-volatile memory (static or dynamic) checksum failure	None	Immediate Type A
Transmission Control Module Random Access Memory	P0604	RAM failure	RAM read/write failure (single word) RAM fail count $\geq 5$	None	Immediate Type A
Powertrain Internal Control Module EEPROM Error	P062F	NVM write error at key-down	TCM Non-Volatile Memory Incorrect flag = 1	$8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$ Ignition ON	Immediate Type A

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Trans Fluid Temp Sensor Circuit Range/ Performance	P0711	<p>The DTC detects the following failure modes of the TFT:</p> <p>1) A sensor that remains at a value. (Stuck Sensor)</p> <p>2) A sensor that remains at a value. (Stuck Sensor)</p> <p>4) Transmission Temperature remains below 20° C for a calibrated time dependant on startup transmission temperature.</p>	<p><u>Fail Case 1</u>  <math>\Delta TFT &lt; 2^{\circ}C</math>.                      TCC Slip <math>\geq 120</math> RPM for 300 sec cumul.  <math>-39^{\circ}C \leq TFT</math> at startup <math>\leq 20^{\circ}C</math>.</p> <p><u>Fail Case 2</u>  <math>\Delta TFT &lt; 2^{\circ}C</math>.  <math>129^{\circ}C \leq TFT</math> at startup <math>\leq 149^{\circ}C</math>.</p> <p><u>Fail Case 4</u>  <math>TFT \leq 20^{\circ}C</math> after a calibrated amount of time based on a 2D lookup table.</p>	<p>For fail case 1, 2, and 4:                      Common ignition voltage enable,                      Common engine speed enable,                      No Engine Coolant DTC's,                      No OSS P0722, P0723 DTCs,                      No ISS P0716, P0717 DTCs,                      P0711 has not passed this ignition cycle,  <math>-39^{\circ}C \leq</math> trans fluid temp <math>\leq 149^{\circ}C</math></p> <p><u>Fail case 1:</u>  <math>-39^{\circ}C \leq</math> trans fluid temp <math>\leq 20^{\circ}C</math> at startup,                      Engine coolant <math>\geq 70^{\circ}C</math>,                      Engine Coolant has changed <math>\geq 55^{\circ}C</math> since startup,                      Vehicle speed <math>\geq 8</math> kph for <math>&gt; 300</math> seconds (cumulative timer)</p> <p><u>Fail case 2:</u>  <math>129^{\circ}C \leq</math> trans fluid temp <math>\leq 149^{\circ}C</math> at startup,                      Engine coolant <math>\geq 70^{\circ}C</math>                      Engine Coolant has changed <math>\geq 55^{\circ}C</math> since startup,                      Vehicle speed <math>\geq 8</math> kph for <math>\geq 300</math> seconds (cumulative timer)</p> <p><u>Fail case 4:</u>                      Valid TPS, Torque signal, and Crank Signals.  <math>50 \text{ Nm} \leq</math> Engine Torque <math>\leq 1492 \text{ Nm}</math>  <math>2\% \leq</math> Throttle Position <math>\leq 90\%</math>  <math>8 \text{ kph} \leq</math> Vehicle Speed <math>\leq 511 \text{ kph}</math>  <math>500 \text{ rpm} \leq</math> Engine Speed <math>\leq 6500 \text{ rpm}</math>  <math>-39^{\circ}C \leq</math> Coolant Temperature <math>\leq 149^{\circ}C</math></p>	<p><u>Fail case 1:</u>                      80.0 seconds                      Continuous</p> <p><u>Fail case 2:</u>                      80.0 seconds                      Continuous</p> <p><u>Fail case 4:</u>                      Between 200 &amp; 1900 seconds dependant on startup trans temperature.                      Continuous                      Type C-</p>
Transmission Fluid Temperature Sensor Circuit Low Voltage	P0712	Continuous Short-to-Ground in Trans Fluid Temperature sensor or TFT signal circuit	Trans Temp Sensor $\leq 43.19$ ohm Trans Temp $> 150C$	$8V \leq$ Ignition Voltage $\leq 18V$ for 5 sec $500 \leq$ Engine RPM $\leq 6500$ for 5.0 sec	12.0 sec Continuous Type C-
Transmission Fluid Temperature Sensor Circuit High Voltage	P0713	Continuous Open of Short to Voltage in Transmission Fluid Temperature sensor or TFT signal circuit	Trans Temp Sensor $\geq 171862$ ohm Trans Temp $< -40C$ (-40F)	No P0716, P0717, P0722, P0723 DTCs $500 \leq$ Engine RPM $\geq 6500$ for 5.0 sec $8.0 \leq$ Ignition Voltage $\leq 18.0 V$ OSS $\geq 64.3^{\circ}$ RPM for 200 sec cumul. TCC Slip $\geq 120$ RPM for 200 sec cumul.	80.0 sec Type C- Continuous

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Input Speed Sensor Performance	P0716	0 – 6500 RPM  Unrealistically large drop in Input Speed in a very period of time that remains	Input Speed drop $\geq$ 1000 RPM	No P0717, P0722, P0723, P0752, P0973, P0974 DTCs 8V $\leq$ Ignition Voltage $\leq$ 18V 500 $\leq$ Engine RPM $\leq$ 6500 for 5 sec No TP malfunction No Engine Torque malfunction 50 $\leq$ Engine Torque $\leq$ 1492 N-m TPS $\geq$ 8.0% Vehicle Speed $\geq$ 16.0 kph ISS $\geq$ 1050 RPM for 2.0 sec $\Delta$ ISS $\leq$ 500 RPM for 2.0 sec	3.25 sec  Type B Continuous
Input Speed Sensor Circuit Low Voltage	P0717	0 – 6500 RPM  Low Input Speed with large vehicle speed	Input Speed < 100.0 RPM	No P0717, P0722, P0723 DTCs No Engine Torque malfunction 500 $\leq$ Engine RPM $\leq$ 6500 for 5 sec 8V $\leq$ Ignition Voltage $\leq$ 18V Vehicle Speed $\geq$ 16.0 kph 50 $\leq$ Engine Torque $\leq$ 1492 N-m	4.5 sec Continuous Type B
Output Speed Sensor Circuit Low Voltage	P0722	0 - 6500 RPM  Low vehicle speed with large engine speed in Drive range	<u>Drive</u> 50 $\leq$ Engine Torque $\leq$ 1492 N-m Output Speed $\leq$ 64.3* RPM  <u>Park/Neutral</u> 1492 $\leq$ Engine Torque $\leq$ 1492 N-m	No, P0716, P0717, P0723 No TPS malfunction No Engine Torque malfunction 8V $\leq$ Ignition Voltage $\leq$ 18V 500 $\leq$ Engine RPM $\leq$ 6500 for 5.0 sec Range $\neq$ P/N TCC Slip $\geq$ -20 RPM Trans Temp $\geq$ -40° C. 1500 RPM $\leq$ Input Speed $\leq$ 6500 RPM TPS $\geq$ 8.0%	4.5 sec  Continuous Type B
Output Speed Sensor Circuit Intermittent	P0723	0 - 6500 RPM  Loss of vehicle speed when vehicle is moving	Drop in Output Speed > 385.8* RPM in any Drive range	No P0716, P0717, P0974 DTC 8V $\leq$ Ignition Voltage $\leq$ 18V 500 $\leq$ Engine RPM $\geq$ 6500 for 5 sec Range $\neq$ P/N 50 Nm $\leq$ Engine Torque $\leq$ 1492 Nm Time since last range change $\geq$ 6.0 sec + $\Delta$ VSS, loop-to-loop, $\leq$ 160.8* RPM for 2.0 sec $\Delta$ ISS $\leq$ 500 RPM for 2.0 sec Output Speed $\geq$ 321.5* RPM for 2.0 sec	3.25 sec  Continuous Type B
Torque Converter Clutch System - Stuck Off	P0741	High TCC slip with TCC commanded on	TCC slip Error $\geq$ 125 RPM  Count = 2	No P0716, P0717, P0722, P0723, P0742 No TPS malfunction No Engine Torque and Speed malfunctions 8V $\leq$ Ignition Voltage $\leq$ 18V 500 $\leq$ Engine RPM $\leq$ 6500 for 5.0 sec 50 $\leq$ Engine Torque $\leq$ 1492 N-m 2.0% $\leq$ TPS $\leq$ 90% 20° C. $\leq$ Trans Temp $\leq$ 130° C. TCC Capacity $\geq$ 65% for 2.0 sec Commanded Gear > 2 TCC Mode = On or Locked On	8 sec  Continuous Type B

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Torque Converter Clutch System - Stuck On	P0742	Low TCC slip with TCC commanded off	$-20 \text{ rpm} \leq \text{TCC Slip Speed} \leq 40 \text{ rpm}$  Count = 4	No P0716, P0717, P0722, P0723, P0741 No TPS malfunction No Engine Torque and Speed malfunctions $8\text{V} \leq \text{Ignition Voltage} \leq 18\text{V}$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec TCC commanded OFF $50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}$ $20^\circ \text{ C.} \leq \text{Trans Temp} \leq 130^\circ \text{ C.}$ $8\% \leq \text{TPS} \leq 90\%$ $16 \text{ kph} \leq \text{VSS} \leq 511 \text{ kph}$ $1.07 \geq \text{Gear Ratio} \geq 0.6324$	4.0 sec  Type B Continuous
1-2 Shift Solenoid Valve Performance - No First or Fourth Gear	P0751	2-2-3-3 shift pattern	<u>Fail Case 1</u> Commanded 1st $1.5483 < \text{Ratio} < 1.7115$  <u>Fail Case 2</u> Commanded 4th $0.95 < \text{Ratio} < 1.05$  Count = 2	No P0716, P0717, P0722, P0723, P0742, P0973, P0974, P0976, P0977, or TPS DTCs (see below) No Engine Torque malfunction $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec $8\text{V} \leq \text{Ignition Voltage} \leq 18\text{V}$ $\text{TPS} \geq 8.0\%$ $20^\circ \text{ C.} < \text{Trans Temp} < 130^\circ \text{ C.}$ 1.0 sec. after gear change $150 \leq \text{Input Speed} \leq 6500 \text{ RPM}$ $50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}$ $\text{Output Speed} \geq 64.3^* \text{ RPM}$	<u>Fail Case 1</u> 2.0 sec  <u>Fail Case 2</u> 4.0 sec  Continuous Type B
1-2 Shift Solenoid Valve Performance - No Second or Third Gear	P0752	1-1-4-4 shift pattern	<u>Fail Case 3</u> Commanded 2nd $2.8120 < \text{Ratio} < 3.1080$  <u>Fail Case 4</u> Commanded 3 <sup>rd</sup> $0.6458 < \text{Ratio} < 0.7137$  Count = 2	See P0751	<u>Fail Case 3</u> 2.0 sec  <u>Fail Case 4</u> 3.0 sec  Continuous Type B
2-3 Shift Solenoid Valve Performance - No First or Second Gear	P0756	4-3-3-4 shift pattern	<u>Fail Case 5</u> $-20 \leq \text{TCC Slip} \leq 8191 \text{ RPM}$ $\text{VSS} \geq 64.3^* \text{ RPM}$ Commanded 1st $0.6458 \leq \text{Ratio} \leq 0.7137$  <u>Fail Case 6</u> Commanded 2nd $0.95 \leq \text{Ratio} \leq 1.05$  Count = 2	See P0751	<u>Fail Case 5</u> 2.0 sec  <u>Fail Case 6</u> 3.0 sec  Continuous Type A

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
2-3 Shift Solenoid Valve Performance - No Third or Fourth Gear	P0757	1-2-2-1 shift pattern	<p><u>Fail Case 7</u>  <math>50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}</math>            Commanded 3rd  <math>1.5483 &lt; \text{Ratio} &lt; 1.7115</math></p> <p><u>Fail Case 8</u>  <math>5 \leq \text{Engine Torque} \leq 1492 \text{ N-m}</math>            Commanded 4<sup>th</sup>  <math>2.8120 &lt; \text{Ratio} &lt; 3.1080</math></p> <p>Count = 2</p>	See P0751	<p><u>Fail Case 7</u>            2.0 sec</p> <p><u>Fail Case 8</u>            2.0 sec</p> <p>Continuous            Type A</p>
1-2 Shift Solenoid Control Circuit Low Voltage	P0973	0 – 12 V  Continuous Short-to-Ground OR Open in Shift Solenoid A or SSA circuit (ODM)	SSA ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec) Continuous Type B
1-2 Shift Solenoid Control Circuit High Voltage	P0974	0 – 12 V  Continuous Short-to-Power in Shift Solenoid A or SSA circuit (ODM)	SSA ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec) Continuous Type B
2-3 Shift Solenoid Control Circuit Low Voltage	P0976	0 – 12 V  Continuous Short-to-Ground OR Open in Shift Solenoid B or SSB circuit (ODM)	SSB ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec)  Type A
2-3 Shift Solenoid Control Circuit High Voltage	P0977	0 – 12 V  Continuous Short-to-Power in Shift Solenoid B or SSB circuit (ODM)	SSB ODM feedback circuit state $\neq$ PCM commanded state	Ignition ON $8.0 \leq \text{Ignition Voltage} \leq 18.0 \text{ V}$	Fail count = 44 out of 50 (Time $\approx$ 4.4 sec) Continuous Type A
Internal Mode Switch A Circuit Low Voltage	P1820	0 – 12 V  IMS A Signal is Low in Park and Drive	IMS Input A = Low in Drive (Range = Transitional 1)	$8\text{V} \leq \text{Ignition Voltage} \leq 18\text{V}$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec Has not passed this key cycle IMS Input A = Low in Park for 1 sec No Engine Torque Malfunction $50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}$	8.0 sec Continuous Type B
Internal Mode Switch B Circuit High Voltage	P1822	0 – 12 V  IMS B Signal is High in Park and Drive	IMS Input B = High/Open in Drive (Range = Transitional13)	$8\text{V} \leq \text{Ignition Voltage} \leq 18\text{V}$ $500 < \text{Engine RPM} < 6500$ for 5.0 sec Has not passed this key cycle IMS Input B = High in Park for 1 sec No Engine Torque Malfunction $50 \leq \text{Engine Torque} < 1492 \text{ N-m}$	8.0 sec Continuous Type B
IMS Mode 'P' Ckt Low	P1823	0 – 12 V  IMS P Signal is High in Park and Drive	IMS Input P = Low in Drive (Range = Transitional 8)	$8\text{V} \leq \text{Ignition Voltage} \leq 18\text{V}$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec Has not passed this key cycle IMS Input P = Low in Park for 1 sec No Engine Torque Malfunction $50 \leq \text{Engine Torque} \leq 1492 \text{ N-m}$	8.0 sec Continuous Type B

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Trans Internal Mode Switch Illegal Range	P1825	0 - 12V	Range is Illegal	$8V \leq \text{Ignition Voltage} \leq 18V$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec	8.0 sec Continuous Type B
Internal Mode Switch C Circuit High Voltage	P1826	0 – 12 V  IMS C Signal is High in Drive	IMS Input C = High/Open in Drive (Range = Transitional)	No P0722 or P0723 DTC's $8V \leq \text{Ignition Voltage} \leq 18V$ Has not passed this key cycle Engine Torque $\geq 50$ Nm Vehicle Speed $\geq 16$ kph $3.1672 \geq \text{Gear Ratio} \geq 2.7528$ or $1.7441 \geq \text{Gear Ratio} \geq 1.5157$ or $1.0699 \geq \text{Gear Ratio} \geq 0.9301$ or $0.7275 \geq \text{Gear Ratio} \geq 0.6324$	8.0 sec Continuous Type B
Internal Mode Switch Does Not Indicate P/N During Start	P1915	0 – 12 V	IMS Not Equal to Park/Neutral During Crank	$6V \leq \text{Ignition Voltage} \leq 18V$ Engine Speed $\geq 450$ rpm Crank Requested $\geq 2.5$ sec	2.0 sec Continuous Type B
Ignition 1 Switch Circuit Low Voltage	P2534	Continuous Open/Short-to-Ground in TCM Ignition 1 Switch circuit	Every 25 msec, the FAIL counter is incremented if an open or a short to ground is detected	Engine running	Fail Counts $\geq 200$ out of 220 Samples (Time $\approx 5$ sec)  Continuous  Type A
Torque Converter Clutch Pressure Control Solenoid Control Circuit High Voltage	P2763	Continuous Short-to-Voltage in TCC PWM circuit	Every 100 msec, the FAIL counter is incremented if a short to voltage is detected	Ignition ON $8V \leq \text{Ignition Voltage} \leq 18V$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec TCC Commanded ON	Fail Count = 44 out of 50 (Time $\approx 4.4$ sec)  Continuous  Type B
Torque Converter Clutch Pressure Control Solenoid Control Circuit Low Voltage	P2764	Continuous Open/Short-to-Ground in TCC PWM circuit or TCC PWM solenoid	Every 100 msec, the FAIL counter is incremented if an open or a short to ground is detected	Ignition ON $8V \leq \text{Ignition Voltage} \leq 18V$ $500 \leq \text{Engine RPM} \leq 6500$ for 5.0 sec	Fail Count = 44 out of 50 (Time $\approx 4.4$ sec)  Continuous  Type B
Controller Area Network Bus Communication Error	<b>U0073</b>	TCM cannot communicate on the CAN Bus	GetCNDD_b_BusOffSt() = TRUE	Ignition ON  $8V \leq \text{Ignition Voltage} \leq 18V$ for 5 seconds	Fail Count = 5 out of 5 (Time $\approx 5$ sec)  Continuous  Type B

07 GRP13\_4T80E LD8\_L37.doc

SENSED PARAMETER	FAULT CODE	ACCEPTABLE OPERATING RANGE AND RATIONALITY	PRIMARY MALF DETECTION PARAMETERS	SECONDARY PARAMETERS AND CONDITIONS	MONITORING TIME & DTC TYPE
Lost Communications with Engine Control System	<b>U0100</b>	Communication between TCM & Engine Control System Lost	CAN Bus ECM Error flag = 1	Ignition ON 8V ≤ Ignition Voltage ≤ 18V for 5 seconds	Fail Count = 12 out of 12 (Time ≈ 12 sec)  Continuous Type B