

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Intake Camshaft Position Actuator Solenoid Control Circuit Bank 1	P0010	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Output driver commanded on Ignition switch is in crank or run 11 volts < Ignition Voltage < 18 volts	100 failures out of 100 samples  250ms loop continuous	DTC Type B
Intake Camshaft Position System Performance Bank 1	P0011	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)]: 4 degrees at 104C oil temp - varies with Oil Temp  Table is a function of Engine RPM and Oil Temperature	Engine is running VVT is enabled Desired camshaft position > 0 $\Delta$ Desired Camshaft position > 3.5 for 3 seconds 11 volts $\leq$ System voltage $\leq$ 18 volts Power Take Off (PTO) not active DTCs not active for the following sub-systems: Cam sensors Crank sensors Cam to crank rationality Cam phase output drivers	100 fail counts out of 300 sample counts  100ms loop Continuous	DTC Type B
Exhaust Camshaft Position Actuator Solenoid Control Circuit Bank 1	P0013	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Output driver commanded on Ignition switch is in crank or run 11 volts < Ignition Voltage < 18 volts	100 failures out of 100 samples 250ms loop continuous	DTC Type B
Exhaust Camshaft Position System Performance Bank 1	P0014	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)]: 4 degrees at 104C oil temp - varies with Oil Temp  Table is a function of Engine RPM and Oil Temperature	Engine is running VVT is enabled Desired camshaft position > 0 $\Delta$ Desired Camshaft position > 3.5 for 3 seconds 11 volts $\leq$ System voltage $\leq$ 18 volts Power Take Off (PTO) not active DTCs not active for the following sub-systems: Cam sensors Crank sensors Cam to crank rationality	100 fail counts out of 300 sample counts  100ms loop Continuous	DTC Type B
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 1 Sensor A	P0016	This diagnostic will determine if the Cam sensor and cam timing have been installed correctly compared to the crank timing.	Cam signal falling edge out of phase -10 or + 11 degrees from corresponding crank falling edge.	Engine is running – run flag is true No crank position sensor circuit or performance DTC's No Fault Pending CAM Circuit DTC's	1 Test failure is counted when all 4 cam pulses (4x cam sensor) are more than the allowed crank degrees.  25 test failures within a 35 test sample size.  Time necessary to complete sample: Varies with engine speed  1 Sample = 1 engine cycle.	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 1 Sensor B	P0017	This diagnostic will determine if the Cam sensor and cam timing have been installed correctly compared to the crank timing.	Cam signal falling edge out of phase -10 or + 11 degrees from corresponding crank falling edge.	Engine is running – run flag is true No crank position sensor circuit or performance DTC's <ul style="list-style-type: none"> <li>No Fault Pending CAM Circuit DTC's</li> </ul>	1 Test failure is counted when all 4 cam pulses (4x cam sensor) are more than the allowed crank degrees.  25 test failures within a 35 test sample size.  Time necessary to complete sample: Varies with engine speed  1 Sample = 1 engine cycle.	DTC Type B
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 2 Sensor A	P0018	This diagnostic will determine if the Cam sensor and cam timing have been installed correctly compared to the crank timing.	Cam signal falling edge out of phase -10 or + 11 degrees from corresponding crank falling edge.	Engine is running – run flag is true No crank position sensor circuit or performance DTC's <ul style="list-style-type: none"> <li>No Fault Pending CAM Circuit DTC's</li> </ul>	1 Test failure is counted when all 4 cam pulses (4x cam sensor) are more than the allowed crank degrees.  25 test failures within a 35 test sample size.  Time necessary to complete sample: Varies with engine speed  1 Sample = 1 engine cycle.	DTC Type B
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 2 Sensor B	P0019	This diagnostic will determine if the Cam sensor and cam timing have been installed correctly compared to the crank timing.	Cam signal falling edge out of phase -10 or + 11 degrees from corresponding crank falling edge.	Engine is running – run flag is true No crank position sensor circuit or performance DTC's <ul style="list-style-type: none"> <li>No Fault Pending CAM Circuit DTC's</li> </ul>	1 Test failure is counted when all 4 cam pulses (4x cam sensor) are more than the allowed crank degrees.  25 test failures within a 35 test sample size.  Time necessary to complete sample: Varies with engine speed  1 Sample = 1 engine cycle.	DTC Type B
Intake Camshaft Position (CMP) Actuator Solenoid Control Circuit Bank 2	P0020	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Output driver commanded on Ignition switch is in crank or run <ul style="list-style-type: none"> <li>11 volts &lt; Ignition Voltage &lt; 18 volts</li> </ul>	100 failures out of 100 samples  250ms loop continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Intake Camshaft Position System Performance - Bank 2	P0021	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)]: 4 degrees at 104C oil temp - varies with Oil Temp  Table is a function of Engine RPM and Oil Temperature	Engine is running VVT is enabled Desired camshaft position > 0 Δ Desired Camshaft position > 3.5 for 3 seconds System voltage ≥ 11 volts Power Take Off (PTO) not active DTC's not active for the following sub-systems: Cam sensors Crank sensors Cam to crank rationality • Cam phase output drivers	100 fail counts out of 300sample counts  100ms loop Continuous	DTC Type B
Exhaust Camshaft Position (CMP) Actuator Solenoid Control Circuit Bank 2	P0023	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Output driver commanded on Ignition switch is in crank or run • 11 volts < Ignition Voltage < 18 volts	100 failures out of 100 samples  250ms loop continuous	DTC Type B
Exhaust Camshaft Position System Performance - Bank 2	P0024	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)]: 4 degrees at 104C oil temp - varies with Oil Temp  Table is a function of Engine RPM and Oil Temperature	Engine is running VVT is enabled Desired camshaft position > 0 Δ Desired Camshaft position > 3.5 for 3 seconds System voltage ≥ 11 volts Power Take Off (PTO) not active DTC's not active for the following sub-systems: Cam sensors Crank sensors Cam to crank rationality Cam phase output drivers •	100 fail counts out of 300 sample counts  100ms loop Continuous	DTC Type B
O2S Heater Control Circuit Bank 1 Sensor 1	P0030	This DTC checks the Heater Output Driver circuit for electrical integrity	Voltage low during driver open state (indicates short-to-ground or open circuit) or voltage high during driver closed state (indicates short to voltage).	• Ignition switch is in crank or run • 11 volts < Ignition Voltage < 18 volts • RPM > 425	20 failures out of 25 samples  Frequency: 250ms loop Continuous	DTC Type B
Turbo/Super Charger Bypass Valve Control Circuit	P0033	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts) • Engine speed > 0 RPM	20 failures in a 25 sample test 250 msec / sample	DTC Type B
O2S Heater Control Circuit Bank 1 Sensor 2	P0036	This DTC checks the Heater Output Driver circuit for electrical integrity	Voltage low during driver open state (indicates short-to-ground or open circuit) or voltage high during driver closed state (indicates short to voltage).	• Ignition switch is in crank or run • 11 volts < Ignition Voltage < 18 volts • RPM > 425	20 failures out of 25 samples  Frequency: 250ms loop Continuous	DTC Type B
O2S Heater Control Circuit Bank 2 Sensor 1	P0050	This DTC checks the Heater Output Driver circuit for electrical integrity	Voltage low during driver open state (indicates short-to-ground or open circuit) or voltage high during driver closed state (indicates short to voltage).	• Ignition switch is in crank or run • 11 volts < Ignition Voltage < 18 volts • RPM > 425	20 failures out of 25 samples  Frequency: 250ms loop Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
HO2S Heater Resistance Bank 1 Sensor 1	P0053	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	3.13 < Calculated Heater resistance < 9.31	<ul style="list-style-type: none"> <li>Coolant – IAT &lt; 8°C</li> <li>Engine Soak Time &gt; 28800 Seconds</li> <li>-30 °C &lt; Coolant Temp &lt; 45°C</li> <li>Coolant Fault = Not Active</li> <li>Ignition Off Timer Fault = Not Active</li> <li>Intake Air Temp Fault = Not Active</li> <li>Ignition Voltage &lt; 18</li> </ul>	Once per valid cold start.	DTC Type B
HO2S Heater Resistance Bank 1 Sensor 2	P0054	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	3.13 < Calculated Heater resistance < 9.31	<ul style="list-style-type: none"> <li>Coolant – IAT &lt; 8°C</li> <li>Engine Soak Time &gt; 28800 Seconds</li> <li>-30 °C &lt; Coolant Temp &lt; 45°C</li> <li>Coolant Fault = Not Active</li> <li>Ignition Off Timer Fault = Not Active</li> <li>Intake Air Temp Fault = Not Active</li> <li>Ignition Voltage &lt; 18</li> </ul>	Once per valid cold start.	DTC Type B
B2S2 Oxygen Sensor Heater Circuit (ODM)	P0056	This DTC checks the Heater Output Driver circuit for electrical integrity	Output state shorted or open	Output driver commanded on Ignition switch is in crank or run 10 volts < Ignition Voltage < 18 volts RPM > 425	20 failures out of 25 samples  Frequency: 250ms loop Continuous	DTC Type B 4 Sensor Systems
HO2S Heater Resistance Bank 2 Sensor 1	P0059	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	3.13 < Calculated Heater resistance < 9.31	<ul style="list-style-type: none"> <li>Coolant – IAT &lt; 8°C</li> <li>Engine Soak Time &gt; 28800 Seconds</li> <li>-30 °C &lt; Coolant Temp &lt; 45°C</li> <li>Coolant Fault = Not Active</li> <li>Ignition Off Timer Fault = Not Active</li> <li>Intake Air Temp Fault = Not Active</li> <li>Ignition Voltage &lt; 18</li> </ul>	Once per valid cold start.	DTC Type B
B2S2 Oxygen Sensor Heater Resistance	P0060	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	3.13 < Calculated Heater resistance < 9.31	<ul style="list-style-type: none"> <li>Coolant – IAT &lt; 8°C</li> <li>Engine Soak Time &gt; 28800 Seconds</li> <li>-30 °C &lt; Coolant Temp &lt; 45°C</li> <li>Coolant Fault = Not Active</li> <li>Ignition Off Timer Fault = Not Active</li> <li>Intake Air Temp Fault = Not Active</li> <li>Ignition Voltage &lt; 18</li> </ul>	Frequency: Once per valid cold start	DTC Type B 4 Sensor Systems

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE																																							
MAP/MAF/Throttle Position Correlation	P0068	Detect when manifold absolute pressure and measured airflow do not match estimated engine airflow as established by the TPS	<p>1. Difference between measured MAP and estimated MAP &gt; MAP_Lim kPa OR V5B OOR OR After Throt Blade MAP sensor TFTKO, then MAP leg failed</p> <p>2. Difference between measured MAF and estimated MAF &gt; MAF_Lim grams/sec OR MAF sensor TFTKO OR Vbatt &lt; 10 volts, then MAF leg failed.</p> <table border="1"> <thead> <tr> <th>TPS</th> <th>MAP_Lim</th> <th>MAF_Lim</th> </tr> </thead> <tbody> <tr><td>1</td><td>5%</td><td>17.31</td><td>12.20</td></tr> <tr><td>2</td><td>10%</td><td>14.96</td><td>12.84</td></tr> <tr><td>3</td><td>15%</td><td>17.68</td><td>14.36</td></tr> <tr><td>4</td><td>20%</td><td>15.57</td><td>17.57</td></tr> <tr><td>5</td><td>25%</td><td>12.30</td><td>20.53</td></tr> <tr><td>6</td><td>30%</td><td>11.59</td><td>21.81</td></tr> <tr><td>7</td><td>35%</td><td>100.00</td><td>255.00</td></tr> <tr><td>8</td><td>40%</td><td>100.00</td><td>255.00</td></tr> <tr><td>9</td><td>100%</td><td>100.00</td><td>255.00</td></tr> </tbody> </table>	TPS	MAP_Lim	MAF_Lim	1	5%	17.31	12.20	2	10%	14.96	12.84	3	15%	17.68	14.36	4	20%	15.57	17.57	5	25%	12.30	20.53	6	30%	11.59	21.81	7	35%	100.00	255.00	8	40%	100.00	255.00	9	100%	100.00	255.00	Engine running, engine speed > 800 rpm	<p>Continuously fail MAP AND MAF legs for longer than 0.1875 msec</p> <p>Continuous in the main processor</p>	DTC Type A
TPS	MAP_Lim	MAF_Lim																																											
1	5%	17.31	12.20																																										
2	10%	14.96	12.84																																										
3	15%	17.68	14.36																																										
4	20%	15.57	17.57																																										
5	25%	12.30	20.53																																										
6	30%	11.59	21.81																																										
7	35%	100.00	255.00																																										
8	40%	100.00	255.00																																										
9	100%	100.00	255.00																																										
Manifold Absolute Pressure – Barometric Pressure Correlation	# P0069	Compares baro sensor to the calculated baro estimate (part throttle calculated or unthrottled MAP)	<p>If the difference between baro read from sensor and calculated baro is exceeded, the code is set</p> <p>Calculated &gt; 20 when the distance traveled since wide open throttle baro update while Vehicle Speed &gt;17.5 kph is &gt;10meters</p> <p>Map &gt; 15 when the distance traveled since wide open throttle baro update while Vehicle Speed &gt;17.5 kph is &lt;10meters</p>	<p>No circuit fault on the baro sensor</p> <p>No fault (circuit or performance) on the CLT sensor</p> <p>No fault (circuit or performance) on the IAT sensor</p> <p>No fault (circuit or performance) on the MAF sensor</p> <p>No fault (circuit or performance) on the ATP sensor (SCIAP on supercharged applications)</p> <p>No fault (circuit or performance) on the Throttle Position sensor</p> <p>No fault (circuit or performance) on vehicle speed</p>	20 failures in a 25 sample test 250 msec / sample	DTC Type B																																							
Intake Air Temperature Sensor 2 Circuit Range/Performance	# P0096	Detects IAT and IAT2 temp sensors stuck in mid range	<p>A failure will be reported if any of the following occur:</p> <p>The delta between IAT and IAT2 is greater than 20 degrees C after a minimum 8 hour soak (fast fail) and P0116 is passing.</p>	<p>No VSS DTC's</p> <p>No ECT DTC's</p> <p>No ECT sensor shorted DTC's</p> <p>Non-volatile memory failure has not been detected on power-up.</p> <p>Engine off time &gt; 8 hours</p> <p>No stall</p> <p>Test run this trip = false</p> <p>Test aborted this trip = false</p>	<p>1 failure</p> <p>500 ms loop</p>	DTC Type B																																							

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Intake Air Temperature Sensor 2 Circuit Low	# P0097	This DTC detects a continuous short to ground in the IAT2 signal circuit or the IAT2 sensor.	Raw IAT2 < 25 ohms	Engine run time > 10 seconds, or Coolant ≤ 150°C Vehicle speed > 0 MAF < 512 g/s	50 test failures in a 63 sample test for short  1 sec / sample	DTC Type B
Intake Air Temperature Sensor 2 Circuit High	# P0098	This DTC detects a continuous short to high or open in the IAT2 signal circuit or the IAT2 sensor.	Raw IAT2 > 1,800,000 ohms	Engine run time > 10 seconds, or Coolant ≥ -40°C Vehicle speed > 0 MAF < 512 g/s	50 test failures in a 63 sample test for short  1 sec / sample	DTC Type B
MASS AIR FLOW SYSTEM PERFORMANCE (RATIONALITY)	P0101	This DTC determines if the MAF sensor is stuck within the normal operating range	(Measured Flow – Modeled air Flow) Filtered > 25 AND (Measured Manifold Air Pressure – Manifold Model 2 pressure) Filtered > 30	Engine rpm =>550 and <= 5000  MAP sensor high/low DTC's not active  EGR DTC's P0401, P0405, and P1404 not active MAF sensor high/low DTC's not active Crank sensor DTC's not active Engine Coolant DTC's not active Intake Air Temp. DTC's not active Engine Coolant > 70 deg C and < 129 deg C Intake Air Temp > -7 deg C and < 60 deg C  Refer to "IFRD weight factors" attached at bottom Minimum total weight factor (all factors multiplied together) >.26	Continuous  The Mass Air Flow reading and Mass Air Flow calculation are performed during the same 12.5 ms loop	DTC Type B
MASS AIR FLOW SENSOR CIRCUIT LOW FREQUENCY	P0102	Detects a continuous short to low or a open in either the signal circuit or the MAF sensor	MAF ≤ 850 Hz (approximately 1.5g/s)	Engine Running ≥ 1 second Engine Speed ≥ 300 RPM RunCrank Voltage ≥ 8 volts Above must be true ≥ 1 second	50 failures in a 63 sample test 1 sample every LoRes event	DTC Type B
MASS AIR FLOW SENSOR CIRCUIT HIGH FREQUENCY	P0103	Detects a continuous short to high in either the signal circuit or the MAF sensor	MAF ≥ 14500 Hz Hz (approximately 866g/s)	Engine Running ≥ 1 second Engine Speed ≥ 300 RPM RunCrank Voltage ≥ 8 volts Above must be true ≥ 1 second	50 failures in a 63 sample test 1 sample every LoRes event	DTC Type B
MAP SENSOR RANGE/ PERFORMANCE (RATIONALITY)	P0106	This DTC determines if the MAP sensor is stuck within the normal operation range	(Measured MAP - Manifold Model 1 pressure) filtered > 20 AND (Measured MAP – Manifold Model 2 pressure) filtered > 20	Engine rpm =>550 and <= 5000 MAP sensor high/low DTC's not active EGR DTC's P0401, P0405, and P1404 not active MAF sensor high/low DTC's not active Crank sensor DTC's not active Engine Coolant DTC's not active Intake Air Temp. DTC's not active Engine Coolant > 70 deg C and < 129 deg C Intake Air Temp > -7 deg C and < 60 deg C  Refer to "IFRD weight factors" attached at bottom Minimum total weight factor (all factors multiplied together) >.26	Continuous  The MAP reading and the Manifold Model calculations are performed in the same LoRes loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
MANIFOLD ABSOLUTE PRESSURE SENSOR CIRCUIT LOW	P0107	This DTC detects a continuous short to low or open in either the signal circuit or the MAP sensor.	MAP voltage < 2% of Vref (0.1 volts)	Key-On test: Engine speed ≤ 400 RPM Run Test: No TPS failures present TPS ≥ 0%, and Engine Speed ≤ 800 RPM, or TPS ≥ 12.5%, Engine Speed > 800 RPM)	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B
MANIFOLD ABSOLUTE PRESSURE SENSOR CIRCUIT HIGH	P0108	This DTC detects an open sensor ground or continuous short to high in either the signal circuit or the MAP sensor	MAP voltage > 98% of Vref (4.9 volts)	No TPS failures present Engine running Engine run time > Min based on power-up coolant temp (-30°C = 242 seconds, -15°C = 188 seconds, 0°C = 144 seconds, 15°C = 80 seconds, 30°C = 0 seconds) TPS < 1%, and Engine Speed ≤ 1200 RPM, or TPS < 20%, and Engine Speed > 1200 RPM	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B
Intake Air Temperature (IAT) Sensor Performance	# P0111	Detects IAT sensor stuck in range	A failure will be reported if any of the following occur:  The delta between IAT and IAT2 is greater than 20 degrees C after a minimum 8 hour soak (fast fail) and P0116 is failing.	No VSS DTC's No ECT DTC's No ECT sensor shorted DTC's Non-volatile memory failure has not been detected on power-up. Engine off time > 8 hours No stall Test run this trip = false Test aborted this trip = false	1 failure  500 ms loop	DTC Type B
INTAKE AIR TEMP SENSOR CIRCUIT LOW (HIGH TEMP)	P0112	This DTC detects a continuous short to ground in the IAT signal circuit or the IAT sensor	Raw IAT < 45 ohms (approximately 150 DegC)	No ECT failures present No Vehicle Speed failures present Coolant Temp < 150°C Vehicle speed ≥ 0 kph Engine run time > 10 seconds	50 failures in a 63 sample test 100 msec / sample	DTC Type B
INTAKE AIR TEMP SENSOR CIRCUIT HIGH (LOW TEMP)	P0113	This DTC detects a continuous open or short to high in the IAT signal circuit or the IAT sensor	Raw IAT > 163000 ohms (approximately -60 DegC)	No ECT failures present No MAF failures present No Vehicle Speed failures present Coolant Temp ≥ -40°C Mass Airflow < 512 g/s Vehicle speed < 512 kph Engine run time > 10 seconds	50 failures in a 63 sample test 100 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
ENGINE COOLANT TEMP SENSOR RATIONALITY (HIGH-SIDED)	P0116	Detects coolant temp sensor stuck in mid range	<p>A failure will be reported if any of the following occur:</p> <p>ECT at powerup &gt; IAT at powerup by an IAT based table lookup value after a minimum 8 hour soak (fast fail) table attached at bottom.</p> <p>ECT at powerup &gt; IAT at powerup by 10C after a minimum 8 hour soak and a block heater has not been detected.</p> <p>ECT at powerup &gt; IAT at powerup by 10C after a minimum 8 hour soak and the time spent cranking the engine without starting is greater than 5 seconds with the fuel level being above a minimum level of 5%.</p>	<p>No VSS DTC's No IAT DTC's No ECT sensor shorted DTC's ECM/PCM Internal Engine Off Timer Performance DTC not active Non-volatile memory failure has not been detected on power-up. Engine off time &gt; 8 hours Test run this trip = false Test aborted this trip = false</p> <p>Block heater detection: ECT at powerup &gt; IAT at powerup by 20C Powerup IAT &gt; -7C Vehicle driven a minimum of 400 seconds above 15 kph and IAT drops more than 4C from powerup IAT.</p>	<p>1 failure</p> <p>500 ms loop</p>	DTC Type B
ENGINE COOLANT TEMP SENSOR CIRCUIT LOW (HIGH TEMP)	P0117	This DTC detects a continuous short to ground in the ECT signal circuit or the ECT sensor.	OHMS < 45 ohms (approximate temperature 150 deg C)	Engine run time > 10 seconds, or IAT ≤ 50°C	5 test failures in a 6 sample test. 1 sec / sample	DTC Type B
ENGINE COOLANT TEMP SENSOR CIRCUIT HIGH (LOW TEMP)	P0118	This DTC detects a continuous short to high or open in the ECT signal circuit or the ECT sensor.	OHMS > 450,000 ohms (approximate temperature -60 deg C)	Engine run time > 10 seconds, or IAT ≥ 0°C	5 failures in a 6 sample test 1 sec / sample	DTC Type B
Throttle Position (TP) Sensor 1 Circuit	P0120	Detects a continuous or intermittent short or open in TP sensor #1 circuit	0.325 Volts > TPS > 4.75 Volts	Ignition in unlock/accessory, run or crank System voltage>5.23 V No 5 V reference DTCs	79/159 counts; 52 counts continuous; 3.125 msec /count in the ECM main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Throttle Position (TP) Sensor 1 Circuit Lo	P0122	Detects a continuous or intermittent OOR lo TPS	TPS < 0.325 Volts	Ignition in unlock/accessory, run or crank System voltage>5.23 V No 5 V reference DTCs	79/159 counts; 52 counts continuous; 3.125 msec /count in the ECM main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Throttle Position (TP) Sensor 1 Circuit Lo	P0122	Detects a continuous or intermittent OOR lo TPS	TPS < 0.35V	Ignition in unlock/accessory, run or crank System voltage>5.23 V No PCM processor, 5 V reference DTCs	79/159 counts; 55 counts continuous; 3.125 msec /count in the ECM main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Throttle Position (TP) Sensor 1 Circuit Hi	P0123	Detects a continuous or intermittent OOR lo TPS	TPS > 4.58 V	Ignition in unlock/accessory, run or crank System voltage>5.23 V No PCM processor, 5 V reference DTCs	79/159 counts; 55counts continuous; 3.125 msec /count in the ecm main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
COOLANT TEMPERATURE BELOW STAT REGULATING TEMPERATURE	P0128	Under driving conditions, target coolant temperature should be achieved based on amount of cumulative airflow ingested, and based on startup coolant temperature	A table attached at bottom defines maximum cumulative airflow based on startup coolant temperature and IAT at which target coolant temperature must have been reached For -7C < IAT < 10C, Target = 75C For IAT > 10C, Target = 75C	10 gps < Airflow < 35 gps Engine runtime <1370seconds before test completes Engine runtime > 60 seconds Minimum IAT > -7C Vehicle speed > 8 kph for 0.5 kilometers For -7C < IAT < 10C, Startup ECT< 70 For IAT > 10C, Startup ECT<70 No ECT, Throttle, IAT, VSS, MAF or MAP faults	Once per trip  Time based on flow	DTC Type B
Supercharger Inlet Pressure Sensor Performance	# P012B	This DTC determines if the SCIAP sensor is stuck within the normal operation range	(Measured SCIAP - SCIAP Model 1 pressure) filtered > 17 AND (Measured SCIAP – SCIAP 2 pressure) filtered > 24	Engine rpm =>550 and <= 5000 MAP sensor high/low DTC's not active EGR DTC's P0401, P0405, and P1404 not active MAF sensor high/low DTC's not active Crank sensor DTC's not active Engine Coolant DTC's not active Intake Air Temp. DTC's not active Engine Coolant > 70 deg C and < 129 deg C Intake Air Temp > -7 deg C and < 60 deg C IAT_2 fault Not Active SCIAP Circuit Fault Not Active Ambient Air Pressure Estimate not Defaulted all the way to a calibration  Refer to "IFRD weight factors" attached at bottom Minimum total weight factor (all factors multiplied together) >.26	Continuous  The SCIAP reading and the Manifold Model calculations are performed in the same LoRes loop	DTC Type B
Supercharger Inlet Pressure Sensor Circuit Low Voltage	# P012C	This DTC detects a continuous short to low or open in either the signal circuit or the SCIAP sensor.	SCIAP voltage < 2% of Vref (0.1 volts)	Key-On test: Engine speed ≤ 400 RPM Run Test: No TPS failures present TPS ≥ 0%, and Engine Speed ≤ 800 RPM, or TPS >= 12.5%, Engine Speed > 800 RPM)	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Supercharger Inlet Pressure Sensor Circuit High Voltage	# P012D	This DTC detects an open sensor ground or continuous short to high in either the signal circuit or the SCIAP sensor	SCIAP voltage > 98% of Vref (4.9 volts)	No TPS failures present Engine running Engine run time > Min based on power-up coolant temp (-30°C = 242 seconds, -15°C = 188 seconds, 0°C = 144 seconds, 15°C = 80 seconds, 30°C = 0 seconds) TPS < 1%, and Engine Speed ≤ 1200 RPM, or TPS < 20%, and Engine Speed > 1200 RPM	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B
O2S Circuit Low Voltage Bank 1 Sensor 1	P0131	This DTC determines if the O2 sensor circuit is shorted to low.	O2 sensor voltage < 25 millivolts (B*S1) O2 sensor voltage < 10 millivolts (B1S2)	<u>Common Enable Criteria</u> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <u>Specific Enable Criteria</u> <ul style="list-style-type: none"> <li>0.99 ≤ Equivalence ratio ≤ 1.01</li> <li>0 % ≤ throttle position ≤ 50 %</li> <li>Fuel state = closed loop with no fault pending</li> <li>All fuel injectors = ON</li> <li>Traction Control = not active</li> </ul> All of the above met for at least 3 seconds	160 test failures in a 200 sample test for 2 consecutive tests  <u>Frequency:</u> Continuous 100 ms loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit High Voltage Bank 1 Sensor 1	P0132	This DTC determines if the O2 sensor or circuit is shorted to high.	O2 sensor voltage > 1050 millivolts to go fault pending  O2 sensor voltage > 1050 millivolts to set DTC	<u>Common Enable Criteria</u> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <u>Specific Enable Criteria</u> <ul style="list-style-type: none"> <li>• <math>0.99 \leq \text{Equivalence Ratio} \leq 1.01</math></li> <li>• <math>0\% \leq \text{throttle position} \leq 60\%</math></li> <li>• Fuel State = Closed loop</li> </ul> All of the above met for at least 1 seconds	40 test failures in a 50 sample test for 2 consecutive tests  <u>Frequency:</u> Continuous 100 ms loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Slow Response Bank 1 Sensor 1	P0133	This DTC determines if the O2 sensor response time is degraded	Refer to "O2S Slow Response Bank 1 Sensor 1 (P0133), O2S Slow Response Bank 2 Sensor 1 (P0153) Pass/Fail Thresholds." In Lookup Tables section.	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• O2 Heater on for <math>\geq 0</math> seconds</li> <li>• B1S1 DTCs = Not Active</li> <li>• Learned heater resistance is valid</li> <li>• Misfire DTC = Not Active</li> <li>• ECT &gt; 70 °C</li> <li>• IAT &gt; -40 °C</li> <li>• Engine run time &gt; 202 seconds</li> <li>• EVAP Canister purge duty cycle <math>\geq 0</math> %</li> <li>• 25 gps <math>\leq</math> MAF <math>\leq</math> 40 gps</li> <li>• 1100 <math>\leq</math> RPM <math>\leq</math> 2500</li> <li>• Ethanol percentage &lt; 85 %</li> <li>• Baro &gt; 70 kPa</li> <li>• Throttle position <math>\geq 3</math> %</li> <li>• Fuel Level &gt; 10 %</li> <li>• Fuel state = closed loop</li> <li>• No fuel level data faults</li> <li>• Transmission (automatic) not in Park, Reverse or Neutral</li> <li>• Transmission gear selection is not defaulted</li> <li>• Baro is not defaulted</li> </ul> <p>All of the above met for at least 1 second.</p>	60 seconds  <u>Frequency:</u> Once per trip	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Insufficient Activity Bank 1 Sensor 1	P0134	This DTC determines if the O2 sensor circuit is open.	500 millivolts < O2 sensor < 400 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>Engine run time &gt; 101 seconds</li> <li>Ethanol percentage &lt; 85 %</li> <li>No B1S1 heater related DTCs</li> </ul>	<p>480 test failures in a 600 test samples</p> <p>Minimum of 0 occurrences of a delta TP sensor <math>\geq</math> 5 % during diagnostic test</p> <p><u>Frequency:</u> Continuous for pre catalyst sensors 100 ms loop rate</p>	DTC Type B
O2S Heater Performance Bank 1 Sensor 1	P0135	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	O2 sensor heater current is < 0.25 amps or > 3.125 amps	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>Engine Run Time <math>\geq</math> 180 seconds</li> <li>ECT <math>\geq</math> 60° C</li> <li>500 <math>\leq</math> Engine Rpm <math>\leq</math> 3000</li> <li>5 gps <math>\leq</math> Mass Airflow <math>\leq</math> 45 gps</li> <li>O2 heater not in Device control</li> <li>B1S1 O2 heater resistance DTC not active</li> </ul> <p>All of the above met for at least 2 seconds</p>	<p>8 test failures in 10 test samples</p> <p>Frequency: 2 tests per trip 120 seconds delay between tests 1 second execution rate</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Low Voltage Bank 1 Sensor 2	P0137	This DTC determines if the O2 sensor circuit is shorted to low by checking for a lean condition during steady throttle.	O2 sensor voltage < 10 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>0.99 ≤ Equivalence ratio ≤ 1.01</li> <li>0 % ≤ throttle position ≤ 50 %</li> <li>Fuel state = closed loop</li> <li>All fuel injectors = ON</li> <li>Traction Control = not active</li> </ul> <p>All of the above met for at least 3 seconds</p>	<p>320 test failures in a 400 sample test for 1 consecutive test</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B
O2S Circuit High Voltage Bank 1 Sensor 2	P0138	This DTC determines if the O2 sensor or circuit is shorted to high	<p>O2 sensor voltage &gt; 1050 millivolts to go fault pending</p> <p>O2 sensor voltage &gt; 1050 millivolts to set DTC</p>	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>0.99 ≤ Equivalence Ratio ≤ 1.01</li> <li>0 % ≤ throttle position ≤ 50 %</li> <li>Fuel State = Closed loop</li> </ul> <p>All of the above met for at least 3 seconds</p>	<p>320 test failures in a 400 sample test for 1 consecutive test</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Insufficient Activity Bank 1 Sensor 2	P0140	This DTC determines if the O2 sensor circuit is open.	<p>400 millivolts &lt; O2 sensor &lt; 500 millivolts for regular open test</p> <p>300 millivolts &lt; O2 sensor &lt; 600 millivolts to fail the fast pass open test (must fail the regular open test in order to fail the DTC; regular open test is run if fast pass is not run or if fast pass fails)</p>	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• Ethanol percentage &gt; 85 %</li> <li>• No B1S2 heater related DTCs</li> <li>• PCM State = run</li> </ul> <p><u>Fast Pass:</u></p> <ul style="list-style-type: none"> <li>• Engine run time ≤ 100 seconds</li> </ul> <p>(Fast pass cannot report a fail; if Fastpass fails, the regular open test is run)</p> <p><u>Regular Open Test</u></p> <ul style="list-style-type: none"> <li>• Engine run time &gt; 101 seconds</li> <li>• Fuel state = closed loop</li> </ul>	<p>1200 test failures in a 1500 test samples</p> <p>Minimum of 5 occurrences of a delta TP sensor ≥ 5 % during diagnostic test</p> <p>(sample counts – failure counts) &lt; 400 within 100 seconds of engine run time to fail the fast pass test (regular open test is run when fast pass fails; to fail DTC the regular open test must fail)</p> <p><u>Frequency:</u> Once/trip for post catalyst sensors 100 ms loop</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Heater Performance Bank 1 Sensor 2	P0141	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	O2 sensor heater current is < 0.25 amps or > 3.125 amps	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>Engine Run Time ≥ 180 seconds</li> <li>ECT ≥ 60° C</li> <li>500 ≤ Engine Rpm ≤ 3000</li> <li>5 gps ≤ Mass Airflow ≤ 45 gps</li> <li>O2 heater not in Device control</li> <li>B1S2 O2 heater resistance DTC not active</li> </ul> <p>All of the above met for at least 2 seconds</p>	8 test failures in 10 test samples Frequency: 2 tests per trip 120 seconds delay between tests 1 second execution rate	DTC Type B
O2S Circuit Low Voltage Bank 2 Sensor 1	P0151	This DTC determines if the O2 sensor circuit is shorted to low	O2 sensor voltage < 25 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>0.99 ≤ Equivalence ratio ≤ 1.01</li> <li>0 % ≤ throttle position ≤ 50 %</li> <li>Fuel state = closed loop with no fault pending</li> <li>All fuel injectors = ON</li> <li>Traction Control = not active</li> </ul> <p>All of the above met for at least 3 seconds</p>	80 test failures in a 100 sample test for 2 consecutive tests  <u>Frequency:</u> Continuous 100 ms loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit High Voltage Bank 2 Sensor 1	P0152	This DTC determines if the O2 sensor or circuit is shorted to high.	O2 sensor voltage > 1050 millivolts to go fault pending  O2 sensor voltage > 1050 millivolts to set DTC	<u>Common Enable Criteria</u> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <u>Specific Enable Criteria</u> <ul style="list-style-type: none"> <li>• <math>0.99 \leq \text{Equivalence Ratio} \leq 1.01</math></li> <li>• <math>0\% \leq \text{throttle position} \leq 60\%</math></li> <li>• Fuel State = Closed loop</li> </ul> <p style="text-align: center;">All of the above met for at least 1 seconds</p>	80 test failures in a 100 sample test for 2 consecutive tests  <u>Frequency:</u> Continuous 100 ms loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Slow Response Bank 2 Sensor 1	P0153	This DTC determines if the O2 sensor response time is degraded	Refer to "O2S Slow Response Bank 1 Sensor 1 (P0133), O2S Slow Response Bank 2 Sensor 1 (P0153) Pass/Fail Thresholds." In Lookup Tables section.	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• O2 Heater on for <math>\geq 0</math> seconds</li> <li>• B2S1 DTCs = Not Active</li> <li>• Learned heater resistance is valid</li> <li>• Misfire DTC = Not Active</li> <li>• ECT &gt; 70 °C</li> <li>• IAT &gt; -40 °C</li> <li>• Engine run time &gt; 202 seconds</li> <li>• EVAP Canister purge duty cycle <math>\geq 0</math> %</li> <li>• 25 gps <math>\leq</math> MAF <math>\leq</math> 40 gps</li> <li>• 1100 <math>\leq</math> RPM <math>\leq</math> 2500</li> <li>• Ethanol percentage &lt; 85 %</li> <li>• Baro &gt; 70 kPa</li> <li>• Throttle position <math>\geq 3</math> %</li> <li>• Fuel Level &gt; 10 %</li> <li>• Fuel state = closed loop</li> <li>• No fuel level data faults</li> <li>• Transmission (automatic) not in Park, Reverse or Neutral</li> <li>• Transmission gear selection is not defaulted</li> <li>• Baro is not defaulted</li> </ul> <p>All of the above met for at least 1 second.</p>	60 seconds  <u>Frequency:</u> Once per trip	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Insufficient Activity Bank 2 Sensor 1	P0154	This DTC determines if the O2 sensor circuit is open.	400 millivolts < O2 sensor < 500 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>Engine run time &gt; 101 seconds</li> <li>Ethanol percentage &lt; 85 %</li> <li>No B1S1 heater related DTCs</li> </ul>	<p>480 test failures in a 600 test samples</p> <p>Minimum of 0 occurrences of a delta TP sensor <math>\geq</math> 5 % during diagnostic test</p> <p><u>Frequency:</u> Continuous for pre catalyst sensors 100 ms loop rate</p>	DTC Type B
O2S Heater Performance Bank 2 Sensor 1	P0155	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	O2 sensor heater current is < 0.25 amps or > 3.125 amps	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>Engine Run Time <math>\geq</math> 180 seconds</li> <li>ECT <math>\geq</math> 60° C</li> <li>500 <math>\leq</math> Engine Rpm <math>\leq</math> 3000</li> <li>5 gps <math>\leq</math> Mass Airflow <math>\leq</math> 45 gps</li> <li>O2 heater not in Device control</li> <li>B2S1 O2 heater resistance DTC not active</li> </ul> <p>All of the above met for at least 2 seconds</p>	<p>8 test failures in 10 test samples</p> <p>Frequency: 2 tests per trip 120 seconds delay between tests 1 second execution rate</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Low Voltage Bank 2 Sensor 12	P0157	This DTC determines if the O2 sensor circuit is shorted to low by checking for a lean condition during steady throttle.	O2 sensor voltage < 10 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• <math>0.99 \leq</math> Equivalence ratio <math>\leq 1.01</math></li> <li>• <math>0\% \leq</math> throttle position <math>\leq 50\%</math></li> <li>• Fuel state = closed loop</li> <li>• All fuel injectors = ON</li> <li>• Traction Control = not active</li> </ul> <p>All of the above met for at least 3 seconds</p>	<p>320 test failures in a 400 sample test for 1 consecutive test</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B 4 Sensor systems
O2S Circuit High Voltage Bank 2 Sensor 2	P0158	This DTC determines if the O2 sensor or circuit is shorted to high	<p>O2 sensor voltage &gt; 1050 millivolts to go fault pending</p> <p>O2 sensor voltage &gt; 1050 millivolts to set DTC</p>	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• <math>0.99 \leq</math> Equivalence Ratio <math>\leq 1.01</math></li> <li>• <math>0\% \leq</math> throttle position <math>\leq 50\%</math></li> <li>• Fuel State = Closed loop</li> </ul> <p>All of the above met for at least 3 seconds</p>	<p>320 test failures in a 400 sample test for 1 consecutive test</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B 4 Sensor Systems

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Circuit Insufficient Activity Bank 1 Sensor 2	P0140	This DTC determines if the O2 sensor circuit is open.	<p>400 millivolts &lt; O2 sensor &lt; 500 millivolts for regular open test</p> <p>300 millivolts &lt; O2 sensor &lt; 600 millivolts to fail the fast pass open test (must fail the regular open test in order to fail the DTC; regular open test is run if fast pass is not run or if fast pass fails)</p>	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• Ethanol percentage &gt; 85 %</li> <li>• No B1S2 heater related DTCs</li> <li>• PCM State = run</li> </ul> <p><u>Fast Pass:</u></p> <ul style="list-style-type: none"> <li>• Engine run time ≤ 100 seconds</li> </ul> <p>(Fast pass cannot report a fail; if Fastpass fails, the regular open test is run)</p> <p><u>Regular Open Test</u></p> <ul style="list-style-type: none"> <li>• Engine run time &gt; 101 seconds</li> <li>• Fuel state = closed loop</li> </ul>	<p>1200 test failures in a 1500 test samples</p> <p>Minimum of 5 occurrences of a delta TP sensor ≥ 5 % during diagnostic test</p> <p>(sample counts – failure counts) &lt; 400 within 100 seconds of engine run time to fail the fast pass test (regular open test is run when fast pass fails; to fail DTC the regular open test must fail)</p> <p><u>Frequency:</u> Once/trip for post catalyst sensors 100 ms loop</p>	<p>DTC Type B</p> <p>4 Sensor Systems</p>

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Heater Performance Bank 2 Sensor 2	P0161	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	O2 sensor heater current is < 0.25 amps or > 3.125 amps	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <p><u>Specific Enable Criteria</u></p> <ul style="list-style-type: none"> <li>• Engine Run Time ≥ 180 seconds</li> <li>• ECT ≥ 60° C</li> <li>• 500 ≤ Engine Rpm ≤ 3000</li> <li>• 5 gps ≤ Mass Airflow ≤ 45 gps</li> <li>• O2 heater not in Device control</li> <li>• B1S2 O2 heater resistance DTC not active</li> </ul> <p>All of the above met for at least 2 seconds</p>	8 test failures in 10 test samples Frequency: 2 tests per trip 120 seconds delay between tests 1 second execution rate	DTC Type B 4 Sensor Systems

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel System Too Lean Bank 1	P0171	<p>Determines if the fuel control system is in a lean condition, based on the EWMA of long-term fuel trim (LTM).</p> <p>(Note: EWMA stands for “Exponentially Weighted Moving Average”)</p>	<p>The EWMA of long term fuel trim (LTM) samples <math>\geq 1.24</math></p>	<ul style="list-style-type: none"> <li>• No Misfire, pre-cat O2 Sensor, or EVAP DTC's</li> <li>• No Fuel Injector or Composition (Ethanol) DTC's</li> <li>• No IAC, MAF, MAP, ECT, EGR, or A.I.R. DTC's</li> <li>• No TP Sensor or TAC System DTC's</li> <li>• Engine speed &gt; 400 rpm but &lt; 6000 rpm</li> <li>• BARO &gt; 70 kpa</li> <li>• ECT &gt; -38 °C but &lt; 150 °C</li> <li>• MAP &gt; 5 kpa but &lt; 255 kpa</li> <li>• IAT &gt; -38 °C but &lt; 150 °C</li> <li>• Mass Airflow &gt; 0.5 g/s but &lt; 510 g/s</li> <li>• Vehicle speed &lt; 134 kph</li> <li>• Closed Loop and Long Term Fuel Trim Learning enabled</li> <li>• Not in Device Control</li> <li>• EGR Flow Diagnostic Intrusive Test = Not Active</li> <li>• Catalyst Monitor Diagnostic Intrusive Test = Not Active</li> <li>• Post O2 Diagnostic Intrusive Test = Not Active</li> <li>• Evap diagnostic is at any stage except the “tank pull down” portion of the test.</li> </ul> <p>General Notes:</p> <ul style="list-style-type: none"> <li>• At least 55 seconds of LTM data must accumulate on each trip, with at least 45 seconds of data in the current fuel trim cell before a pass or fail decision can be made</li> </ul>	<p>The EWMA of long term fuel trim (LTM) samples <math>\geq 1.24</math> for <math>\geq 100</math> ms</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	<p>DTC Type B</p>

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel System Too Rich Bank 1	P0172	<p>Determines if the fuel control system is in a rich condition, based on the EWMA of long-term fuel trim (LTM).</p> <p>(Note: EWMA stands for “Exponentially Weighted Moving Average”)</p>	<p>There exists both a Passive and, if needed, Intrusive rich test.</p> <p>Passive: The EWMA of long term purge-off fuel trim (LTM) samples <math>\leq 0.79</math></p> <p>Intrusive: If a passive decision cannot be made, and the EWMA of long term purge-on fuel trim (LTM) samples <math>\leq 0.78</math>, purge is ramped off to determine if excess purge is the cause. Therefore, the following must also occur to report a failure:</p> <p>The EWMA of LTM samples with purge off <math>\leq 0.79</math> for at least 10 seconds during each of 3 intrusive segments.</p> <p>Intrusive Notes:</p> <ol style="list-style-type: none"> <li>Segments can last up to 60 seconds, and are separated by the smaller of a 10 second purge-on time or enough time to purge 5 grams of vapor.</li> <li>A maximum of 5 completed segments or 20 intrusive attempts are allowed for each intrusive test.</li> <li>After an intrusive test report is completed, another intrusive test cannot occur for 300 seconds to allow sufficient time to purge excess vapors from the canister. During this period, fuel trim will pass if the EWMA of LTM samples <math>&gt; .79</math> and at least 60 seconds of extended purging has occurred indicating that the canister has been purged.</li> </ol> <p>Performing intrusive tests too frequently may also affect EVAP and FTP emissions, and the execution frequency of other diagnostics.</p>	<ul style="list-style-type: none"> <li>No Misfire, pre-cat O2 Sensor, or EVAP DTC's</li> <li>No Fuel Injector or Composition (Ethanol) DTC's</li> <li>No IAC, MAF, MAP, ECT, EGR, or A.I.R. DTC's</li> <li>No TP Sensor or TAC System DTC's</li> <li>Engine speed <math>&gt; 400</math> rpm but <math>&lt; 6000</math> rpm</li> <li>BARO <math>&gt; 70</math> kpa</li> <li>ECT <math>&gt; -38</math> °C but <math>&lt; 150</math> °C</li> <li>MAP <math>&gt; 5</math> kpa but <math>&lt; 255</math> kpa</li> <li>IAT <math>&gt; -38</math> C but <math>&lt; 150</math> °C</li> <li>Mass Airflow <math>&gt; 2.89</math> g/s but <math>&lt; 510</math> g/s</li> <li>Vehicle speed <math>&lt; 134</math> kph</li> <li>Closed Loop and Long Term Fuel Trim Learning enabled</li> <li>Not in Device Control</li> <li>EGR Flow Diagnostic Intrusive Test = Not Active</li> <li>Catalyst Monitor Diagnostic Intrusive Test = Not Active</li> <li>Post O2 Diagnostic Intrusive Test = Not Active</li> <li>Evap diagnostic is at any stage except the “tank pull down” portion of the test.</li> </ul> <p>General Notes:</p> <p>At least 105 seconds of LTM data must accumulate on each trip, with at least 45 seconds of data in the current fuel trim cell before a pass or fail decision can be made.</p> <p>Intrusive Enable Criteria</p> <ul style="list-style-type: none"> <li>Insufficient purge-off data prior to purge-on .</li> <li>The EWMA of long term purge-on fuel trim (LTM) samples <math>\leq .79</math></li> <li>RPM <math>&gt; 400</math></li> <li>Mass Airflow <math>&gt; 2.89</math> g/s but <math>&lt; 510</math> g/s</li> <li>MAP <math>&gt; 5</math> kpa but <math>&lt; 255</math> kpa</li> </ul>	<p>Passive: The EWMA of long term purge-off fuel trim (LTM) samples <math>\leq .79</math> for <math>\geq 100</math>ms</p> <p>Intrusive: If rich fail counter is <math>\geq 3</math> before pass counter <math>\geq 3</math>, diagnostic fails.</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel System Too Lean Bank 2	P0174	<p>Determines if the fuel control system is in a lean condition, based on the EWMA of long-term fuel trim (LTM).</p> <p>(Note: EWMA stands for “Exponentially Weighted Moving Average”)</p>	<p>The EWMA of long term fuel trim (LTM) samples <math>\geq 1.24</math></p>	<ul style="list-style-type: none"> <li>• No Misfire, pre-cat O2 Sensor, or EVAP DTC's</li> <li>• No Fuel Injector or Composition (Ethanol) DTC's</li> <li>• No IAC, MAF, MAP, ECT, EGR, or A.I.R. DTC's</li> <li>• No TP Sensor or TAC System DTC's</li> <li>• Engine speed &gt; 400 rpm but &lt; 6000 rpm</li> <li>• BARO &gt; 70 kpa</li> <li>• ECT &gt; -38 °C but &lt; 150 °C</li> <li>• MAP &gt; 5 kpa but &lt; 255 kpa</li> <li>• IAT &gt; -38 °C but &lt; 150 °C</li> <li>• Mass Airflow &gt; 0.5 g/s but &lt; 510 g/s</li> <li>• Vehicle speed &lt; 134 kph</li> <li>• Closed Loop and Long Term Fuel Trim Learning enabled</li> <li>• Not in Device Control</li> <li>• EGR Flow Diagnostic Intrusive Test = Not Active</li> <li>• Catalyst Monitor Diagnostic Intrusive Test = Not Active</li> <li>• Post O2 Diagnostic Intrusive Test = Not Active</li> <li>• Evap diagnostic is at any stage except the “tank pull down” portion of the test.</li> </ul> <p>General Notes:</p> <ul style="list-style-type: none"> <li>• At least 55 seconds of LTM data must accumulate on each trip, with at least 45 seconds of data in the current fuel trim cell before a pass or fail decision can be made</li> </ul>	<p>The EWMA of long term fuel trim (LTM) samples <math>\geq 1.24</math> for <math>\geq 100</math> ms</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	<p>DTC Type B</p>

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel System Too Rich Bank 2	P0175	<p>Determines if the fuel control system is in a rich condition, based on the EWMA of long-term fuel trim (LTM).</p> <p>(Note: EWMA stands for “Exponentially Weighted Moving Average”)</p>	<p>There exists both a Passive and, if needed, Intrusive rich test.</p> <p>Passive: The EWMA of long term purge-off fuel trim (LTM) samples <math>\leq 0.79</math></p> <p>Intrusive: If a passive decision cannot be made, and the EWMA of long term purge-on fuel trim (LTM) samples <math>\leq 0.79</math>, purge is ramped off to determine if excess purge is the cause. Therefore, the following must also occur to report a failure:</p> <p>The EWMA of LTM samples with purge off <math>\leq 0.79</math> for at least 10 seconds during each of 3 intrusive segments.</p> <p>Intrusive Notes:</p> <ol style="list-style-type: none"> <li>1. Segments can last up to 60 seconds, and are separated by the smaller of a 10 second purge-on time or enough time to purge 5 grams of vapor.</li> <li>2. A maximum of 5 completed segments or 20 intrusive attempts are allowed for each intrusive test.</li> <li>3. After an intrusive test report is completed, another intrusive test cannot occur for 300 seconds to allow sufficient time to purge excess vapors from the canister. During this period, fuel trim will pass if the EWMA of LTM samples <math>&gt; .79</math> and at least 60 seconds of extended purging has occurred indicating that the canister has been purged.</li> </ol> <p>Performing intrusive tests too frequently may also affect EVAP and FTP emissions, and the execution frequency of other diagnostics.</p>	<ul style="list-style-type: none"> <li>• No Misfire, pre-cat O2 Sensor, or EVAP DTC's</li> <li>• No Fuel Injector or Composition (Ethanol) DTC's</li> <li>• No IAC, MAF, MAP, ECT, EGR, or A.I.R. DTC's</li> <li>• No TP Sensor or TAC System DTC's</li> <li>• Engine speed <math>&gt; 400</math> rpm but <math>&lt; 6000</math> rpm</li> <li>• BARO <math>&gt; 70</math> kpa</li> <li>• ECT <math>&gt; -38</math> °C but <math>&lt; 150</math> °C</li> <li>• MAP <math>&gt; 5</math> kpa but <math>&lt; 255</math> kpa</li> <li>• IAT <math>&gt; -38</math> C but <math>&lt; 150</math> °C</li> <li>• Mass Airflow <math>&gt; 2.89</math> g/s but <math>&lt; 510</math> g/s</li> <li>• Vehicle speed <math>&lt; 134</math> kph</li> <li>• Closed Loop and Long Term Fuel Trim Learning enabled</li> <li>• Not in Device Control</li> <li>• EGR Flow Diagnostic Intrusive Test = Not Active</li> <li>• Catalyst Monitor Diagnostic Intrusive Test = Not Active</li> <li>• Post O2 Diagnostic Intrusive Test = Not Active</li> <li>• Evap diagnostic is at any stage except the “tank pull down” portion of the test.</li> </ul> <p>General Notes:</p> <p>General Notes:</p> <p>At least 105 seconds of LTM data must accumulate on each trip, with at least 45 seconds of data in the current fuel trim cell before a pass or fail decision can be made.</p> <p>Intrusive Enable Criteria</p> <ul style="list-style-type: none"> <li>• Insufficient purge-off data prior to purge-on operation .</li> <li>• The EWMA of long term purge-on fuel trim (LTM) samples <math>\leq .79</math></li> <li>• RPM <math>&gt; 400</math></li> <li>• Mass Airflow <math>&gt; 2.89</math> g/s but <math>&lt; 510</math> g/s</li> <li>• MAP <math>&gt; 5</math> kpa but <math>&lt; 255</math> kpa</li> </ul>	<p>Passive: The EWMA of long term purge-off fuel trim (LTM) samples <math>\leq .79</math> for <math>\geq 100</math>ms</p> <p>Intrusive: If rich fail counter is <math>\geq 3</math> before pass counter <math>\geq 3</math>, diagnostic fails.</p> <p><u>Frequency:</u> Continuous 100 ms loop</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Engine Oil Temperature Sensor Performance	# P0196	Determines if the oil temperature sensor is stuck/biased in range.	<p>Cold Start Fast Fail: Delta between powerup oil temp and coolant temp &gt; 30° C &amp; Delta between powerup ECT and IAT &lt;= 15.75 ° C OR Cold Start Block Heater Test Enable is True Delta between powerup ECT and IAT &lt;= 15.75 ° C &amp; Delta between powerup ECT and minimum observed IAT &lt;= 15.75 ° C</p> <p>Cold Start Fast Pass: Delta between powerup oil temp and coolant temp &lt;= 15.75 ° C &amp; Delta between powerup oil temp and inlet air temp &lt;= 15.75 ° C OR If Cold Start Driving EOTD Enable is True Delta between powerup oil temp and coolant temp &lt;= 15.75 ° C &amp; Delta between powerup oil temp and minimum observed inlet air temp &lt;= 15.75 ° C OR</p>	<p>Oil Temp Diagnostics Enabled (KeEOTD_b_DiagnosticsEnable) == TRUE</p> <p>Continuous Model Diagnostic Enabled: (KeEOTD_b_ContinuousDiagEnbl) == TRUE Engine Running == TRUE Engine Oil Model Temp State == Equilibrium (KeEOTL_b_QuickTransToEquilState) == TRUE Modeled Oil Temp &gt;= 70.0° C -7° C &gt;= Powerup Coolant Temp &lt;= 105° C 45° C &gt;= Coolant Temp &lt;= 95° C</p> <p>Oil Temp Cold Start Diagnostic Enabled: (KeEOTD_b_ColdStartDiagEnbl) == TRUE Engine Off Time &gt; 540 seconds</p> <p>EOTD Diagnostic Disable Fault Detected: Engine Coolant DTC's not active Intake Air Temp DTC's not active Vehicle Speed error not present Engine Oil Temp Sensor Circuit DTC's not active Mass Airflow Sensor DTC's not active ECM Internal Eng Off Timer DTC's not active</p> <p>Cold Start Driving EOTD Enable Test: Vehicle Speed &gt; 15 kph for 400 seconds</p> <p>Cold Start Block Heater Enable Test: 10.25 ° C &gt; Minimum observed inlet air temp OR -10 ° C &gt; Minimum observed inlet air temp &amp; Delta between powerup IAT and minimum observed IAT &lt; 5.25 ° C</p>	<p>Cold Start Fast Fail: 1 sample at 1 second Cold Start Fast Pass: 1 sample at 1 second Continuous Pass Test: 1 sample every 1 second Continuous Fail Test: 1 sample every 1 second</p> <p><b>Increment Rate Based Numerator when:</b> EOT Performance Fault is detected or when Cold Start Fail Criteria Met == TRUE</p> <p>Cold Start Fail Criteria is True when the following three conditions are True: 1. Delta between powerup EOT and ECT &gt; 15.75 ° C or Delta between powerup EOT and minimum observed IAT &gt; 15.75 ° C 2. either a or b 2a. Delta between powerup EOT and ECT &lt; 15.75 ° C or {Minimum observed IAT &gt; 10.25 ° C &amp; Minimum observed IAT &gt; -10 ° C } 2b. Delta between powerup EOT and ECT &lt; 15.75 ° C or {Minimum observed IAT &gt; 10.25 ° C &amp; Delta between powerup IAT and minimum observed IAT &gt; 5.25 ° C }</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
	# P0196 Continued		<p>Cold Start Block Heater Test Enable is True  Delta between powerup oil temp and powerup IAT <math>\leq 15.75^{\circ}\text{C}</math>  &amp;  Delta between powerup oil temp and minimum observed inlet air temp <math>\leq 15.75^{\circ}\text{C}</math></p> <p>Continuous Pass Test:  Oil temp sensed minus oil temp model <math>\geq 0.0^{\circ}\text{C}</math>  &amp;  Delta between oil temp model and oil temp sensed <math>\leq 40.0^{\circ}\text{C}</math>  <b>OR</b>  Oil temp sensed minus oil temp model <math>&lt; 0^{\circ}\text{C}</math>  &amp;  Delta between oil temp sensed and oil temp model <math>\leq 40.0^{\circ}\text{C}</math></p> <p>Continuous Fail Test:  Oil temp sensed minus oil temp model <math>\geq 0.0^{\circ}\text{C}</math>  &amp;  Delta between oil temp model and oil temp sensed <math>\geq 40.0^{\circ}\text{C}</math>  <b>OR</b>  Oil temp sensed minus oil temp model <math>&lt; 0^{\circ}\text{C}</math>  &amp;  Delta between oil temp sensed and oil temp model <math>\geq 40.0^{\circ}\text{C}</math></p>		<p>3. either a or b  3a. Delta between powerup EOT and ECT <math>&gt; 15.75^{\circ}\text{C}</math> &amp; {Delta between powerup EOT and IAT <math>\leq 15.75^{\circ}\text{C}</math> &amp; Delta between powerup EOT and minimum observed IAT <math>\leq 15.75^{\circ}\text{C}</math> }  3b. Delta between powerup EOT and ECT <math>&gt; 15.75^{\circ}\text{C}</math> &amp; {Delta between powerup ECT and IAT <math>\leq 15.75^{\circ}\text{C}</math> &amp; Delta between powerup ECT and minimum observed IAT <math>\leq 15.75^{\circ}\text{C}</math> }</p> <p><b>Increment Rate Based Denominator when:</b>  KeEOTI_b_DiagEnable = True</p>	
Engine Oil Temperature Circuit Low	# P0197	Determines if the oil temperature sensor circuit has low voltage.	OHMS $< 25$ ohms (approximate temperature greater than $169.2^{\circ}\text{deg C}$ )	KeEOTI_b_DiagEnable = True & Engine Run Time $> 20$ seconds Or Coolant Resistance $\leq 25$ ohms	Fail Counts $> 25$ counts In 50 sample counts Performed every 1 second	DTC Type B
Engine Oil Temperature Circuit High	# P0198	Determines if the oil temperature sensor circuit has high voltage.	OHMS $> 450,000$ ohms (approximate temperature $-60^{\circ}\text{deg C}$ )	KeEOTI_b_DiagEnable = True & Engine Run Time $> 20$ seconds Or Coolant Resistance $\geq 1.8\text{e}6$ ohms	Fail Counts $> 25$ counts In 50 sample counts Performed every 1 second	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Injector Control Circuit (Cylinders 1-8) (ODM)	P0201 – P0208	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Engine running PT_RelayInRange (9 volts < Ignition < 18 volts) Ignition voltage in range > 1 seconds	20 failures in a 25 sample test 250 msec / sample	DTC Type B
Throttle Position (TP) Sensor 2 Circuit	P0220	Detects a continuous or intermittent short or open in TP sensor #2 circuit	0.25 Volts > TPS > 4.59 Volts	Ignition in Unlock/accessory, run, crank System voltage > 5.23 V No 5 V reference DTCs	79/159 counts; 52 counts continuous; 3.125 msec/count in the motor processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Throttle Position (TP) Sensor 2 Lo	P0222	Detects a continuous or intermittent short or open in TP sensor #2 circuit	TPS < 0.25 Volts	Ignition in Unlock/accessory, run, crank System voltage > 5.23 V No 5 V reference DTCs	79/159 counts ; 52 counts continuous; 3.125 msec /count in the ecm main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Throttle Position (TP) Sensor 2 Circuit Hi	P0223	Detects a continuous or intermittent short or open in TP sensor #2 circuit	TPS > 4.59 Volts	Ignition in Unlock/accessory, run, crank System voltage > 5.23 V No 5 V reference DTCs	79/159 counts ; 52 counts continuous; 3.125 msec /count in the ecm main processor  19/39 counts or 13 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
FUEL PUMP CONTROL CIRCUIT (ODM)	P0230	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (11 volts < Ignition < 18 volts) Engine speed >= 0 RPM	8 failures in a 10 sample test 250 msec / sample	DTC Type B
Turbo/Supercharger Intercooler Coolant Pump Control Circuit	P023A	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts) • Engine speed > 0 RPM	20 failures in a 25 sample test 250 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Random Misfire Detected	P0300	These DTC 's will determine if a random misfire or a cylinder specific misfire is occurring by monitoring crankshaft velocity.	Deceleration index Vs Engine Speed Vs Load and Camshaft Position  Emission Failure Threshold =1.0% (Kt_MISF_Emission_Misfire), depending on engine speed and engine load  Catalyst Damage Threshold = 5 – 11.25% (Kt_MISF_Catalyst_Misfire), depending on engine speed and engine load	<ul style="list-style-type: none"> <li>• Engine run time &gt; 2 crankshaft revolutions</li> <li>• DTCs not active for VSS, CKP, TP, MAP, ECT, MAF, and IAT sensors .</li> <li>• No engine protection faults.</li> <li>• P0315 (Crankshaft Position System Variation Not Learned) not active or engine speed &lt; 1000 RPM</li> <li>• Deceleration Fuel and Clutch cutoff not active.</li> <li>• Power management is not active.</li> <li>• Not an automatic transmission shift with a throttle position &gt;95%.</li> <li>• Brake torque management not active.</li> <li>• Fuel level &gt; 10% (disablement ends 500 engine cycles, after a low fuel level condition ceases, and fuel disable does not occur with a fuel sensor DTC).</li> <li>• -7°C &lt; ECT &lt; 129 ° C.</li> <li>• If ECT at startup &lt; -7 °C, then disable until ECT &gt; 21 °C.</li> <li>• 150 RPM below minimum hot idle &lt; Engine speed &lt; 400 RPM below Engine Over Speed Protection..</li> <li>• 9 volts &lt; System voltage 18 volts.</li> <li>• + Throttle position delta &lt; 50 % per 100 ms.</li> <li>• - Throttle position delta &lt;50% per 100 ms.</li> <li>• Abnormal engine speed is not present.</li> <li>• ABS rough road not detected.</li> <li>• ABS / TCS / VSES is not active.</li> <li>• Not an abusive engine speed condition, 500 RPM above maximum engine over speed protection. Abusive engine speed delay = 1250 cycles (Manual Transmission Only)</li> <li>• Positive and zero torque (except the CARB approved 3000 rpm to redline triangle). Positive and zero torque is detected when both is true: 1) engine load &gt; zero torque cal (cal a function of engine speed and temperature), and 2) Throttle open or VSS &lt; 48 KPH.</li> <li>• EGR Intrusive test not active.</li> <li>• Misfire Diag is not requesting to disable TCC when transmission is in hot mode.</li> <li>• Crankshaft Ring Filter inactive (after a low level misfire, another misfire may not be detectable until crankshaft ringing ceases)</li> </ul>	Emission Exceedence = (5) failed 200 revolution blocks of 16. Failure reported with (1) Exceedence in 1st (16) 200 revolution block, or (4) Exceedences thereafter.  1st Catalyst Exceedence = Number of 200 revolution blocks as data supports for catalyst damage. 2nd and subsequent Catalyst Exceedences = (1) 200 revolution block with catalyst damage. Failure reported with (3) Exceedences in FTP, or (1) Exceedence outside FTP.  Frequency: Continuous	DTC Type B  (MIL Flashes with Catalyst Damaging Misfire)
Cylinder 1 Misfire Detected	P0301					
Cylinder 2 Misfire Detected	P0302					
Cylinder 3 Misfire Detected	P0303					
Cylinder 4 Misfire Detected	P0304					
Cylinder 5 Misfire Detected	P0305					
Cylinder 6 Misfire Detected	P0306					
Cylinder 7 Misfire Detected	P0307					
Cylinder 8 Misfire Detected	P0308					
Crankshaft Position System Variation Not Learned	P0315	The DTC will determine if the Crankshaft Position System Variation has not been learned	Sum of compensation factors not within range	<ul style="list-style-type: none"> <li>• PCM State =Run</li> <li>• Manufacturers enable counter must be Zero.</li> </ul>	100 ms loop continuous	DTC Type A

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Knock Sensor (KS) Module Performance	P0324	This diagnostic will detect a failed internal ECM component associated with knock control	Any Cylinder's Avg Gain Signal > 4.5 if RPM>2000 OR All Cylinder's Actual Signals < 0.2 if RPM>1500	APC >300	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit Bank 1	P0325	This diagnostic checks for an open to the knock sensor	Gated Low Pass Filter Voltage > 4V or < 1.24 V	Coolant>75 and Engine Run Time > 90 PTO not active  Temporarily disabled ('Indeterminate' state reported) for samples in which P0327 or P0328 report 'Failed' state.	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Performance Bank 1	P0326	This diagnostic checks for an overactive knock sensor caused by noisy engine components (e.g. lifters)	Fast Retard $\geq$ 12	Engine Speed $\geq$ 1200 MAP $\geq$ 80 No throttle fault No PTO active Fast spark retard active	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit Low Bank 1	P0327	This diagnostic checks for an out of range low knock sensor signal	Sensor Input Signal Line > 2.86 V or Sensor Return Signal Line < 1.48 V	Coolant>75and Engine Run Time > 90 PTO not active	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit High Bank 1	P0328	This diagnostic checks for an out of range high knock sensor signal	Sensor Input Signal Line < 2.02 V or Sensor Return Signal Line > 3.76 V	Coolant>75 and Engine Run Time > 90 PTO not active	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit Bank 2	P0330	This diagnostic checks for an open to the knock sensor	Gated Low Pass Filter Voltage > 4V or < 1.24 V	Coolant>75 and Engine Run Time > 90 PTO not active.  Temporarily disabled ('Indeterminate' state reported) for samples in which P032 or P0333 report 'Failed' state.	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit Low Bank 2	P0332	This diagnostic checks for an out of range low knock sensor signal	Sensor Input Signal Line > 2.86 V or Sensor Return Signal Line < 1.48 V	Coolant>75and Engine Run Time > 90 PTO not active	50 out of 100  100ms sample rate Continuous	DTC Type B
Knock Sensor (KS) Circuit High Bank 2	P0333	This diagnostic checks for an out of range high knock sensor signal	Sensor Input Signal Line < 2.02 V or Sensor Return Signal Line > 3.76 V	Coolant>75 and Engine Run Time > 90 PTO not active	50 out of 100  100ms sample rate Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Crankshaft Position (CKP) Sensor A Circuit	P0335	This diagnostic determines whether a fault exists with crank position sensor signal	<ol style="list-style-type: none"> <li>1. No crankshaft position sensor pulses received for 4 seconds</li> <li>2. No crankshaft position sync</li> <li>3. No crankshaft position sensor pulses received</li> </ol>	<ol style="list-style-type: none"> <li>1. Engine cranking and either CMP pulses being received or MAF &gt; 3 grams per second</li> <li>2. Engine is spinning and no 5V reference DTCs set</li> <li>3. Engine is spinning and no 5V reference or cam position sensor DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous - 12.5 ms</li> <li>2. Continuous - 12.5 ms</li> <li>3. Continuous - 12.5 ms 2 test failures out of 10 samples</li> </ol>	DTC Type B
Crankshaft Position (CKP) Sensor A Performance	P0336	This diagnostic determines whether a performance fault exists with crank position sensor signal	<ol style="list-style-type: none"> <li>1. Twenty crank resyncs occur within 25 seconds</li> <li>2. 55 &gt; number of crank pulses received in one engine revolution &gt;61</li> </ol>	<ol style="list-style-type: none"> <li>1. Engine speed &gt; 450 RPM</li> <li>2. Engine is spinning and no 5V reference or cam position sensor DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous – 2 test failures</li> <li>2. Continuous – 8 test failures out of 10 samples</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor A	P0340	This diagnostic will detect if a fault exists on the camshaft position sensor signal.	<ol style="list-style-type: none"> <li>1. No Cam pulses received during first 24 MEDRES events</li> <li>2. No Cam pulses received for 100 engine cycles</li> <li>3. No Cam pulses received</li> <li>4. No Cam pulses received</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> <li>3. Engine is cranking and either crank pulses are received or MAF &gt; 3 grams per second</li> <li>4. Engine is spinning and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> <li>3. Continuous – 4 seconds</li> <li>4. Continuous – 1.5 seconds</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor A	P0341	Detects cam sensor performance malfunctions by monitoring for the incorrect number of cam sensor pulses in a given number of crank sensor pulses	<ol style="list-style-type: none"> <li>1. 4 &gt; number of cam pulses received in 24 MEDRES events &gt; 10</li> <li>2. 397 &gt; number of cam pulses received in 100 engine cycles &gt; 403</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Circuit Bank 2 Sensor A	P0345	This diagnostic will detect if a fault exists on the camshaft position sensor signal.	<ol style="list-style-type: none"> <li>1. No Cam pulses received during first 24 MEDRES events</li> <li>2. No Cam pulses received for 100 engine cycles</li> <li>3. No Cam pulses received</li> <li>4. No Cam pulses received</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> <li>3. Engine is cranking and either crank pulses are received or MAF &gt; 3 grams per second</li> <li>4. Engine is spinning and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> <li>3. Continuous – 4 seconds</li> <li>4. Continuous – 1.5 seconds</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Performance Bank 2 Sensor A	P0346	Detects cam sensor performance malfunctions by monitoring for the incorrect number of cam sensor pulses in a given number of crank sensor pulses	<ol style="list-style-type: none"> <li>1. 4 &gt; number of cam pulses received in 24 MEDRES events &gt; 10</li> <li>2. 397 &gt; number of cam pulses received in 100 engine cycles &gt; 403</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> </ol>	DTC Type B
IGNITION CONTROL (Cylinders 1-8)	P0351 – P0358	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	Engine cranking or Engine Running RunCrank Active (Ignition > 6 volts)	50 failures in a 63 sample test 100 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor B	P0365	This diagnostic will detect if a fault exists on the camshaft position sensor signal.	<ol style="list-style-type: none"> <li>1. No Cam pulses received during first 24 MEDRES events</li> <li>2. No Cam pulses received for 100 engine cycles</li> <li>3. No Cam pulses received</li> <li>4. No Cam pulses received</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> <li>3. Engine is cranking and either crank pulses are received or MAF &gt; 3 grams per second</li> <li>4. Engine is spinning and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> <li>3. Continuous – 4 seconds</li> <li>4. Continuous – 1.5 seconds</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor B	P0366	Detects cam sensor performance malfunctions by monitoring for the incorrect number of cam sensor pulses in a given number of crank sensor pulses	<ol style="list-style-type: none"> <li>1. 4 &gt; number of cam pulses received in 24 MEDRES events &gt; 10</li> <li>2. 397 &gt; number of cam pulses received in 100 engine cycles &gt; 403</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Circuit Bank 2 Sensor B	P0390	This diagnostic will detect if a fault exists on the camshaft position sensor signal.	<ol style="list-style-type: none"> <li>1. No Cam pulses received during first 24 MEDRES events</li> <li>2. No Cam pulses received for 100 engine cycles</li> <li>3. No Cam pulses received</li> <li>4. No Cam pulses received</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>2. Crank is synchronized and no 5V ref DTCs set</li> <li>3. Engine is cranking and either crank pulses are received or MAF &gt; 3 grams per second</li> <li>4. Engine is spinning and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> <li>3. Continuous – 4 seconds</li> <li>4. Continuous – 1.5 seconds</li> </ol>	DTC Type B
Camshaft Position (CMP) Sensor Performance Bank 2 Sensor B	P0391	Detects cam sensor performance malfunctions by monitoring for the incorrect number of cam sensor pulses in a given number of crank sensor pulses	<ol style="list-style-type: none"> <li>1. 4 &gt; number of cam pulses received in 24 MEDRES events &gt; 10</li> <li>2. 397 &gt; number of cam pulses received in 100 engine cycles &gt; 403</li> </ol>	<ol style="list-style-type: none"> <li>1. Crank is synchronized and no 5V ref DTCs set</li> <li>4. Crank is synchronized and no 5V ref DTCs set</li> </ol>	<ol style="list-style-type: none"> <li>1. Continuous</li> <li>2. Continuous – 8 test failures out of 10 samples</li> </ol>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Exhaust Gas Recirculation (EGR) Flow Insufficient	# P0401	During a closed throttle decel condition, the EGR valve is normally closed. This diagnostic opens the valve to a pre-determined position, and the change in MAP is computed. This change in MAP correlates to the flow rate of the EGR system.	With EGR valve open, the peak + MAP Δ is monitored over a period of time. This value is compared with a threshold from Engine Speed vs Baro table and the difference computed. The result is statistically filtered (EWMA) and compared to a decision limit. DTC is set when the filtered result exceeds the decision limit of 0.897 kpa	<p><u>Test Enables</u>                      No fuel injector DTCs set                      No CKP DTCs set                      No TP sensor DTC's set                      No MAP DTC's set                      No VSS DTC's set                      No ETC DTC's set                      No 5 volt reference DTC's set                      No IAT sensor DTC's set                      No ECT sensor DTC's set                      No IAC DTC's set                      No EGR Pintle Position DTC set                      No Misfire DTC's set                      No MAF DTC's set                      No CPP (Clutch) DTC's set                      No PCM DTC's set                      No Engine Metal Overtemperature Protection                      Not in Power Take Off (PTO) Mode                      Not in device control                      Traction control not active                      EGR valve icing not occurring                      EGR valve over temperature not occurring                      EGR Engine run time expired                      Not in Power Enrichment                      Not in Catalyst protection mode                      ECT &gt; 5°C                      ECT &lt; 150°C                      BARO &gt; 74Kpa                      BARO data is valid                      IAT &lt; 100°C                      IAT &gt; NA                      Ignition Voltage &lt; 18V                      Ignition Voltage &gt; 11V                      Transmission is in 3 or 4gear                      In decel fuel cut off                      decel fuel cut off status is unchanged                      Vehicle speed &lt; 130 kph                      Vehicle Speed &gt; 32 kph                      Throttle Position is virtually closed                      Transmission status is unchanged</p> <p><u>Stability Mode Enables</u>                      EGR Position &lt; 1%                      1000_RPM &lt; Engine Speed &lt; 1800                      MAP Δ &lt; 1.1 kpa                      5 kPa &lt; Compensated MAP 45 kpa                      Throttle Area Delta &lt; 1.1%                      Difference between desired &amp; actual airflow &lt; 2 g/s</p> <p><u>Intrusive Mode Enables</u>                      Vehicle Speed Δ &lt; 5.6 kph                      + RPM Δ &lt; 100 rpm                      - RPM Δ &lt; 200 rpm</p>	<p><u>Test Time</u>                      0.5 sec. + 0.3 sec = 0.8 sec</p> <p><u>Frequency</u>                      6.26 ms loop                      Once per trip (typically)</p> <p><b>Rapid Step Response feature will initiate multiple tests:</b>                      IF                      the difference between the current EWMA and the current map diff &gt; 3.19 kPa                      AND current map diff &gt; -0.039 kPa                      THEN                      7 tests will be run per trip until 42 tests have been completed</p> <p>Fast Initial Response feature will initiate multiple tests upon code clear or a non-volatile memory failure:                      Several tests per trip will run until 10 tests have been completed.</p>	DTC Type A

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Exhaust Gas Recirculation (EGR) Solenoid Control Circuit	# P0403	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	20 failures in a 25 sample test 250 msec / sample	DTC Type B
Exhaust Gas Recirculation (EGR) Open Position Performance	# P0404	This diagnostic detects if the pintle position error is too large	Pintle position error [absolute value of (desired position - actual position)] > 15 %	5 Volt reference DTC's not active P1258 not active Engine is running Off-board device not active Power Take Off (PTO) not active P0401 not intrusive Ignition voltage ≥ 11V EGR is enabled Desired EGR position > 0% Δ Desired EGR position < 14.5 % for 2 sec.	336 counts out of 420 counts  100ms loop Continuous	DTC Type B
Exhaust Gas Recirculation (EGR) Position Sensor A Circuit Low Voltage	# P0405	This diagnostic detects if the pintle position feedback circuit is open or shorted to ground	EGR feedback sensor signal < 4 % of A/D reference voltage	5 Volt reference DTC's not active Engine is running Off-board device not active Power Take Off (PTO) not active P0401 not intrusive Ignition voltage ≥ 11 volts	50 counts out of 55 counts  100ms loop Continuous	DTC Type B
Exhaust Gas Recirculation (EGR) Position Sensor A Circuit High Voltage	# P0406	This diagnostic detects if the pintle position feedback circuit is shorted to high voltage or the 5V return is open.	EGR feedback sensor signal > 94.7 % of A/D reference voltage	5 Volt reference DTC's not active Engine is running Off-board device not active Power Take Off (PTO) not active P0401 not intrusive Ignition voltage ≥ 11 volts Enable conditions met for	180 counts out of 200 counts  100ms loop Continuous	DTC Type B
AIR System Incorrect Flow	# P0411	Detects an AIR system insufficient flow condition.  This test is run during the phase 1 (pump on, control valve open) portion of the Secondary Air Injection Diagnostic (SAI D).	AIR normalized pressure error > 5 kPa (higher than predicted pressure) during SAID phase 1 test OR AIR normalized pressure error < -5kPa (lower than predicted pressure) during SAID phase 1 test	No active AIR pressure sensor circuit DTCs set. No active AIR pressure sensor performance DTCs set. No active MAP sensor DTCs set. No active AIR pump relay circuit DTC set. No active AIR control valve relay circuit DTC set. No active MAF sensor DTCs set. No active 5 volt reference DTCs set. No active IAT sensor DTCs set. No active ECT sensor DTCs set. No active Misfire DTCs set. No active catalyst monitor DTCs set. No active fuel injector DTCs set. No active EST DTCs set. No active DTC P0606 set. AIR pressure sensor circuit fault pending = False. AIR operation is allowed this start.. IAT > 5° C 18 volts > System voltage > 9 volts.	SAID phase 1 conditional test weight > 7 seconds  Conditional test weight is based on Baro, Mass air flow & System voltage.  Once per trip where AIR pump operation is requested at startup.	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Secondary Air Injection (AIR) Solenoid Control Circuit Bank 1	# P0412	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	20 failures in a 25 sample test 250 msec / sample	DTC Type B
Secondary Air Injection (AIR) Pump Control Circuit Bank 1	# P0418	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	20 failures in a 25 sample test 250 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Catalyst System Low Efficiency Bank 1	P0420	Oxygen Storage	<p>Normalized Ratio OSC Value <math>\leq 0.38</math> (EWMA filtered)</p> <p>Normalized Ratio OSC Value Calculation Information and Definitions =</p> <p>1. Raw OSC Calculation = (post cat O2 Resp time - pre cat O2 Resp time)</p> <p>2. BestFailing OSC value from a calibration table (based on temp and exhaust gas flow)</p> <p>3. WorstPassing OSC value (based on temp and exhaust gas flow)</p> <p>Normalized Ratio Calculation = <math>(1-2) / (3-2)</math></p> <p>A Normalized Ratio of 1 essentially represents a good part and a ratio of 0 essentially represents a very bad part.</p>	<p><u>General Enable</u></p> <ul style="list-style-type: none"> <li>No EVAP, PTO not active, TAC system, MAF, CAM, ECT, CKP, EGR, BARO, AIR, EST, Fuel Injector, Fuel Trim, Idle Air, MAP, IAT, Misfire, O2 Sensor, TP Sensor, VSS or Engine Overtemp Protection Mode DTCs</li> </ul> <p><u>Valid Idle Period Criteria</u></p> <ul style="list-style-type: none"> <li>Throttle Position <math>&lt; 2\%</math></li> <li>Vehicle Speed <math>\leq 3.2\text{kph}</math></li> <li>Engine speed <math>\geq 1000\text{ RPM}</math> for a minimum of 20 seconds since end of last idle period.</li> <li>Engine run time <math>\geq 350\text{ seconds}</math>.</li> <li>Tests attempted this trip <math>&lt; 18.00</math>.</li> <li>The catalyst diagnostic has not yet completed for the current trip.</li> </ul> <p><u>Catalyst Idle Conditions Met Criteria</u></p> <p>General Enable met and the Valid Idle Period Criteria met</p> <ul style="list-style-type: none"> <li>Green Converter Delay = Not Active</li> <li>Induction Air <math>&gt; -20^\circ\text{ C}</math></li> <li>Induction Air <math>&lt; 250^\circ\text{ C}</math></li> <li>FASD and/ or POS Diagnostic Intrusive Test and/or AIR Diagnostic Intrusive Test not Active</li> <li>RunCrank Voltage <math>&gt; 10.7\text{ volts}</math></li> <li>Ethanol Estimation Is NOT in Progress</li> <li>ECT <math>\geq 70^\circ\text{ C}</math></li> <li>ECT <math>\leq 129^\circ\text{ C}</math></li> <li>Barometric Pressure <math>&gt; 70\text{ KPA}</math></li> <li>Idle Time is <math>\leq 60\text{ seconds}</math></li> <li><math>\Rightarrow</math> Idle time is incremented if the vehicle speed <math>\leq</math> vehicle speed cal and the throttle position <math>\leq</math> TPS cal as identified in the Valid Idle Period Criteria section.</li> <li>Short Term Fuel Trim <math>&lt; 1.10</math></li> <li>Short Term Fuel Trim <math>&gt; 0.90</math></li> <li>Predicted catalyst temp <math>\geq 385^\circ\text{C}</math> for at least 75 seconds with a closed throttle time <math>\leq 180\text{ seconds}</math> consecutively (closed throttle consideration involves having the TPS <math>&lt;</math> the value as stated in the Valid Idle Period Criteria Section)</li> </ul>	<p>1 test attempted per valid idle period</p> <p>Minimum of 1 test per trip</p> <p>Maximum of 6 tests per trip</p> <p><u>Frequency:</u></p> <ul style="list-style-type: none"> <li>Fueling Related : 12.5 ms</li> <li>OSC Measurements: 100 ms</li> <li>Temp Prediction: 1000ms</li> </ul> <p>Rapid Step Response (RSR) feature will initiate multiple tests:</p> <ul style="list-style-type: none"> <li>If the difference between current EWMA value and the current OSC Normalized Ratio value is <math>\geq 0.64</math></li> <li>The current OSC Normalized Ratio value is <math>\leq 0.38</math></li> </ul> <p>Maximum of 6 tests per trip. Maximum of 18 tests to detect failure when RSR is enabled.</p> <p><u>Green Converter Delay Criteria</u></p> <p>This is part of the check for the Catalyst Idle Conditions Met Criteria section</p> <ul style="list-style-type: none"> <li>The diagnostic will not be enabled until the following has been met: Predicted catalyst temperature <math>\geq 500^\circ\text{ C}</math> for 3600 seconds non-continuously.</li> <li>Note: this feature is only enabled when the vehicle is new and cannot be enabled in service</li> </ul>	<p>DTC Type A</p>

Comment [G1]:

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Exhaust Gas Recirculation (EGR) Closed Position Performance	# P042E	This diagnostic detects if the valve is stuck open when commanded closed.	Actual pintle position $\geq$ 5.5 % of reference voltage from learned closed position	5 Volt reference DTC's not active Engine is running Off-board device not active Power Take Off (PTO) not active P0401 not intrusive Ignition voltage $\geq$ 11 volts EGR is enabled EGR stroke is enabled Desired EGR position = 0, for 1 sec.	4 detections of:  240 counts out of 300 counts  with pintle movement between failure detections of 30 % for at least 5 seconds open time  100ms loop Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
CATALYTIC CONVERTER LOW OXYGEN STORAGE	P0430	Oxygen Storage.	<p>Normalized Ratio OSC Value <math>\leq 0.38</math> (EWMA filtered)</p> <p>Normalized Ratio OSC Value Calculation Information and Definitions =</p> <p>1. Raw OSC Calculation = (post cat O2 Resp time - pre cat O2 Resp time)</p> <p>2. BestFailing OSC value from a calibration table (based on temp and exhaust gas flow)</p> <p>3. WorstPassing OSC value (based on temp and exhaust gas flow)</p> <p>Normalized Ratio Calculation = <math>(1-2) / (3-2)</math></p> <p>A Normalized Ratio of 1 essentially represents a good part and a ratio of 0 essentially represents a very bad part.</p>	<p><u>General Enable</u></p> <ul style="list-style-type: none"> <li>No EVAP, PTO not active, TAC system, MAF, CAM, ECT, CKP, EGR, BARO, AIR, EST, Fuel Injector, Fuel Trim, Idle Air, MAP, IAT, Misfire, O2 Sensor, TP Sensor, VSS or Engine Overtemp Protection Mode DTCs</li> </ul> <p><u>Valid Idle Period Criteria</u></p> <ul style="list-style-type: none"> <li>Throttle Position <math>&lt; 2\%</math></li> <li>Vehicle Speed <math>\leq 3.2\text{kph}</math></li> <li>Engine speed <math>\geq 1000\text{ RPM}</math> for a minimum of 20 seconds since end of last idle period.</li> <li>Engine run time <math>\geq 350\text{ seconds}</math>.</li> <li>Tests attempted this trip <math>&lt; 18.00</math>.</li> <li>The catalyst diagnostic has not yet completed for the current trip.</li> </ul> <p><u>Catalyst Idle Conditions Met Criteria</u></p> <p>General Enable met and the Valid Idle Period Criteria met</p> <ul style="list-style-type: none"> <li>Green Converter Delay = Not Active</li> <li>Induction Air <math>&gt; -20^\circ\text{C}</math></li> <li>Induction Air <math>&lt; 250^\circ\text{C}</math></li> <li>FASD and/ or POS Diagnostic Intrusive Test and/or AIR Diagnostic Intrusive Test not Active</li> <li>RunCrank Voltage <math>&gt; 10.7\text{ volts}</math></li> <li>Ethanol Estimation Is NOT in Progress</li> <li>ECT <math>\geq 70^\circ\text{C}</math></li> <li>ECT <math>\leq 129^\circ\text{C}</math></li> <li>Barometric Pressure <math>&gt; 70\text{ KPA}</math></li> <li>Idle Time is <math>\leq 60\text{ seconds}</math></li> <li><math>\Rightarrow</math> Idle time is incremented if the vehicle speed <math>\leq</math> vehicle speed cal and the throttle position <math>\leq</math> TPS cal as identified in the Valid Idle Period Criteria section.</li> <li>Short Term Fuel Trim <math>&lt; 1.10</math></li> <li>Short Term Fuel Trim <math>&gt; 0.90</math></li> <li>Predicted catalyst temp <math>\geq 385^\circ\text{C}</math> for at least 75 seconds with a closed throttle time <math>\leq 180\text{ seconds}</math> consecutively (closed throttle consideration involves having the TPS <math>&lt;</math> the value as stated in the Valid Idle Period Criteria Section)</li> </ul>	<p>1 test attempted per valid idle period</p> <p>Minimum of 1 test per trip</p> <p>Maximum of 6 tests per trip</p> <p><u>Frequency:</u></p> <ul style="list-style-type: none"> <li>Fueling Related : 12.5 ms</li> <li>OSC Measurements: 100 ms</li> <li>Temp Prediction: 1000ms</li> </ul> <p>Rapid Step Response (RSR) feature will initiate multiple tests:</p> <ul style="list-style-type: none"> <li>If the difference between current EWMA value and the current OSC Normalized Ratio value is <math>\geq 0.64</math></li> <li>The current OSC Normalized Ratio value is <math>\leq 0.38</math></li> </ul> <p>Maximum of 6 tests per trip. Maximum of 18 tests to detect failure when RSR is enabled.</p> <p><u>Green Converter Delay Criteria</u></p> <p>This is part of the check for the Catalyst Idle Conditions Met Criteria section</p> <ul style="list-style-type: none"> <li>The diagnostic will not be enabled until the following has been met: Predicted catalyst temperature <math>\geq 500^\circ\text{C}</math> for 3600 seconds non-continuously.</li> <li>Note: this feature is only enabled when the vehicle is new and cannot be enabled in service</li> </ul>	<p>DTC Type A</p> <p>Dual Bank Systems</p>

Comment [G2]:

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Evaporative Emission (EVAP) System Small Leak Detected	P0442	This DTC will detect a small leak ( $\geq 0.020''$ ) in the EVAP system between the fuel fill cap and the purge solenoid. The engine off natural vacuum method (EONV) is used.	<p><b><u>SMALL LEAK TEST FAIL:</u></b>                      Engine Off Natural Vacuum (EONV) while the engine is off.                      The total pressure change achieved during the test is normalized against a target value that is based upon fuel level and ambient temperature. (value of 1.60" to 2.50" water). The normalized value is entered into EWMA (with 0= perfect pass and 1=perfect fail). Once EWMA exceeds the fail threshold, the DTC light is illuminated. The DTC light can be turned off if the EWMA falls below the re-pass threshold for 3 consecutive trips.</p> <p>Fail threshold = 0.65 265</p> <p>Re-Pass threshold = <b>0.35</b></p>	<p><b><u>TEST ENABLE :</u></b>                      No MAP DTC's                      No Thermostat Rationality DTC's                      VS Sensor DTC's not active                      No Fuel Tank Pressure Sensor circuit DTC's                      No EVAP Canister Purge Solenoid circuit DTC's                      No EVAP Canister Vent Solenoid circuit DTC's                      No Fuel Level DTC's                      Coolant Sensor DTC's not active                      IAT Sensor DTC's not active                      EVAP CCP stuck open DTC not active.                      EVAP large leak DTC not active.                      Ignition off timer DTC not active.                      Canister Vent restriction DTC is not active                      Fuel Level <math>&gt;15.0\%</math> but <math>&lt; 85.0\%</math>                      Drive time <math>\geq 600</math> seconds.                      Drive length <math>\geq 8</math> kilometers.                      Coolant <math>\geq 70^{\circ}\text{C}</math>.                      No fuel filling (fuel level increment <math>\geq 10\%</math>) During EONV test.                      BARO <math>&gt; 74.0\text{kPa}</math>                      Estimated ambient temperature at end of drive <math>&gt;0^{\circ}\text{C}</math> but <math>&lt; 34^{\circ}\text{C}</math>.</p> <p>Estimate of Ambient Air Temperature Valid                      Conditions to be valid</p> <ol style="list-style-type: none"> <li>Cold Start                          Startup <math>\Delta^{\circ}\text{C}(\text{ECT-IAT}) &lt; 8^{\circ}\text{C}</math> if ECT <math>&gt; \text{IAT}</math>                          OR</li> <li>Hot Restart                          Sufficient drive length to get accurate estimate of ambient air temperature (at least a minimum of 3 minutes and 5 kilometers)</li> </ol>	<p>Once per trip, during hot soak (up to <b>2400</b> sec.).                      Time since last complete test <math>\geq 17</math> hours if EWMA is passing, or <math>\geq 10</math> hours if EWMA is failing.                      No more than 2 attempts per day.</p>	<p>DTC Type A                      EWMA</p> <p>Average run length is 9. under normal conditions</p> <p>Run length is 2 to 6 trips after code clear or non-volatile reset</p>
EVAP CANISTER PURGE SOLENOID VALVE CIRCUIT (ODM)	P0443	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	20 failures in a 25 sample test 250 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Evaporative Emission (EVAP) Vent System Performance	P0446	This DTC will determine if a restriction is present in the vent solenoid, vent filler, vent hose or EVAP canister	Tank Vacuum > 12.00 "H2O for 5 seconds BEFORE Purge Volume > 6 liters  OR Vented Vacuum < -2.5 in. H2O or Vented Vacuum > 5 in. H2O for 15 seconds  2 liters of fuel must be consumed after setting the DTC active the first time to set the DTC active the second time.	General Test Enable No MAP DTC's No TP Sensor DTC's No VSS DTC's No IAT DTC's No ECT DTC's No Fuel Tank Pressure Sensor circuit DTC's No Evap Canister Purge solenoid circuit DTC's No EVAP Canister Vent Solenoid circuit DTC's No Thermostat Rationality DTC's 15 % < Fuel Level < 85. % 10.00 V < System Voltage < 18.00 V 4 °C < IAT < 30°C ECT < 30 °C BARO > 74.00 kPa (8000 ft)	Once per Cold Start  Time is dependent on driving conditions  Max. before test abort is 1000 seconds	DTC Type B
EVAP VENT SOLENOID CONTROL CIRCUIT (ODM)	P0449	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	20 failures in a 25 sample test 250 msec / sample	DTC Type B
Fuel Tank Pressure (FTP) Sensor Circuit Performance	P0451	The DTC will be set if the fuel tank vacuum sensor is out of range when it tries to re-zero prior to the phase-1 or phase-2 portions of the engine-off natural vacuum small leak test.	The tank vacuum sensor voltage is compared to a window about the nominal sensor voltage offset (~1.5 volts)  upper voltage threshold (voltage addition above the nominal voltage): 0.2 volts  lower voltage threshold (voltage subtraction below the nominal voltage): 0.2 volts  The difference between tank vacuum sensor voltage and the nominal offset voltage is then normalized against the appropriate threshold listed above to produce a ratio between 0.0 and 1.0. This normalized re-zero ratio is then filtered with a EWMA (with 0= perfect pass and 1=perfect fail). Once EWMA exceeds the fail threshold, the DTC light is illuminated. The DTC light can be turned off if the EWMA falls below the re-pass threshold for 3 consecutive trips.  Fail threshold = 0.73 Re-Pass threshold = 0.40	This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes	This test is executed during an engine-off natural vacuum small leak test. The number of times that it executes can range from zero to two per engine-off period.  The length of the test is determined by the refueling rationality test which can take up to 600 seconds to complete.	DTC Type A EWMA  average run length: 6  Used on EONV Applications

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel Tank Pressure (FTP) Sensor Circuit Low Voltage	P0452	This DTC will detect a fuel tank pressure sensor signal that is too low out of range.	Fuel tank pressure sensor signal < 0.1 volts produces a failing sample. Otherwise, the sample is considered passing.  If 80 samples fail out of 100 samples total, then a fail will be reported to the DTC.	<ul style="list-style-type: none"> <li>0.10 second delay after sensor power up for sensor warm-up</li> <li>ECM State &lt;&gt; crank</li> </ul>	<u>Frequency:</u> Continuous 100ms loop	DTC Type B
Fuel Tank Pressure (FTP) Sensor Circuit High Voltage	P0453	This DTC will detect a fuel tank pressure sensor signal that is too high out of range.	Fuel tank pressure sensor signal > 4.9 volts produces a failing sample. Otherwise, the sample is considered passing.  If 80 samples fail out of 100 samples total, then a fail will be reported to the DTC.	<ul style="list-style-type: none"> <li>0.10 second delay after sensor power up for sensor warm-up</li> <li>ECM state &lt;&gt; crank</li> </ul>	<u>Frequency:</u> Continuous 100ms loop	DTC Type B
Fuel Tank Pressure (FTP) Sensor Circuit Intermittent	P0454	This DTC will detect intermittent tank vacuum sensor signals that would have caused the engine-off natural vacuum small leak test to abort due to an apparent re-fueling event.	If an abrupt change in tank vacuum is detected the engine-off natural vacuum test is aborted due to an apparent refueling event. Subsequent to the abort, a refueling rationality test is executed to confirm that a refueling event occurred. If a refueling is confirmed, then the test sample is considered passing. Otherwise, the sample is considered failing indicating an intermittent signal problem.  The abrupt change is defined as a change > 0.45 and < 1.0 "H2O vacuum in the span of 1.0 seconds.  A refueling event is confirmed if the fuel level has a persistent change of 10.0 % for 30 seconds.  The test will report a failure if 2 out of 3 samples are failures.	This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes	This test is executed during an engine-off natural vacuum small leak test. The test can only execute up to once per engine-off period.  The length of the test is determined by the refueling rationality test which can take up to 600 seconds to complete.	DTC Type A  Used on EONV Applications

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Evaporative Emission (EVAP) System Large Leak Detected	P0455	This DTC will detect a weak vacuum condition (large leak or purge blockage) in the Evap system.	<p>Purge volume &gt; 25.00 liters BEFORE</p> <p>Tank vacuum &lt; 10 "H<sub>2</sub>O</p> <p>2 liters of fuel must be consumed after setting the DTC active the first time to set the DTC active the second time.</p> <p><u>Weak Vacuum Follow-up Test</u> (fuel cap replacement test) Weak Vacuum Test failed previous trip and this trip. Passes if tank vacuum &gt; 10 " H<sub>2</sub>O.</p> <p>Note: Weak Vacuum Follow-up Test can only report a pass.</p>	<p><u>General Test Enable</u></p> <ul style="list-style-type: none"> <li>• No MAP DTC's</li> <li>• No TP Sensor DTC's</li> <li>• No VSS DTC's</li> <li>• No IAT DTC's</li> <li>• No ECT DTC's</li> <li>• No Fuel Tank Pressure circuit Sensor DTC's</li> <li>• No Evap Canister Purge solenoid circuit DTC's</li> <li>• No EVAP Canister Vent Solenoid circuit DTC's</li> <li>• No Thermostat Rationality DTC's</li> <li>• 15 % &lt; Fuel Level &lt; 85. %</li> <li>• 10.00 V &lt; System Voltage &lt; 18.00 V</li> <li>• 4 °C &lt; IAT &lt; 30°C</li> <li>• ECT &lt; 30 °C</li> <li>• BARO &gt; 74.00 kPa (8000 ft)</li> </ul> <p style="text-align: center;">Cold Start Test</p> <ul style="list-style-type: none"> <li>• IAT &lt; 30°C</li> <li>• Cold temperature Δ(ECT-IAT): &lt; 8 °C if ECT &gt; IAT</li> <li>• Cold Test Timer &lt; 1000 seconds</li> </ul>	<p>Once per cold start</p> <p>Time is dependent on driving conditions</p> <p>Max. before test abort is 1000 seconds</p> <p><u>Weak Vacuum Follow-up Test</u> On 2<sup>nd</sup> trip with large leak detected, the follow-up test is limited to 600 seconds. Once the MIL is on, the follow-up test runs indefinitely.</p>	DTC Type B
Fuel Level No Change, Stuck in Range Primary Tank	P0461	This DTC will detect a fuel sender stuck in range .	IF Delta Fuel Volume change less than 3 liters over a accumulated 200 Kilometers.	No VSS DTC's set Engine Running	Continuous	DTC Type B
Fuel Level Stuck Low Primary Tank	P0462	This DTC will detect a fuel sender stuck out of range low	Fuel level Sender % of 5V range less than 10 %	runs continuously	240 failures out of 300 samples 1 sample = 100 ms  Continuous	DTC Type B
Fuel Level Stuck High Primary Tank	P0463	This DTC will detect a fuel sender stuck out of range high	Fuel level Sender % of 5V range > than 70%	runs continuously	240 failures out of 300 samples 1 sample = 100 ms  Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Fuel Level Sensor 1 Circuit Intermittent	P0464	This DTC will detect intermittent fuel level sensor signals that would have caused the engine-off natural vacuum small leak test to abort due to an apparent re-fueling event.	<p>If a change in fuel level is detected the engine-off natural vacuum test is aborted due to an apparent refueling event. Subsequent to the abort, a refueling rationality test is executed to confirm that a refueling event occurred. If a refueling is confirmed, then the test sample is considered passing. Otherwise, the sample is considered failing indicating an intermittent signal problem.</p> <p>The refuel event is defined as a change of 15% fuel level during the engine-off test.</p> <p>A refueling event is confirmed if the fuel level has a persistent change of 15% for 30 seconds.</p> <p>The test will report a failure if 2 out of 3 samples are failures.</p>	This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes	<p>This test is executed during an engine-off natural vacuum small leak test. The test can only execute up to once per engine-off period.</p> <p>The length of the test is determined by the refueling rationality test which can take up to 600 seconds to complete.</p>	<p>DTC Type A</p> <p>Used on EONV Applications</p>
PRIMARY COOLING FAN RELAY CONTROL CIRCUIT MALF (ODM)	P0480	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match	RunCrankIgnInRange (9 volts < Ignition < 18 volts) Engine speed greater than 400 rpm	20 failures in a 25 sample test 250 msec / sample	DTC Type B
SECONDARY COOLING FAN RELAY CONTROL CIRCUIT MALF (ODM)	P0481	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match	RunCrankIgnInRange (9 volts < Ignition < 18 volts) Engine speed greater than 400 rpm	20 failures in a 25 sample test 250 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE																				
Evaporative Emission (EVAP) System Flow During Non-Purge	P0496	This DTC will determine if the purge solenoid is leaking to engine manifold vacuum.	Tank Vacuum > 10 "H2O for 5.00 sec BEFORE Test time > 60 seconds (cold start)	<u>General Test Enable</u> <ul style="list-style-type: none"> <li>• No MAP DTC's</li> <li>• No TP Sensor DTC's</li> <li>• No VSS DTC's</li> <li>• No IAT DTC's</li> <li>• No ECT DTC's</li> <li>• No Fuel Tank Pressure Sensor circuit DTC's</li> <li>• No EVAP canister purge solenoid circuit DTC's</li> <li>• No EVAP Canister Vent Solenoid circuit DTC's</li> <li>• No Thermostat Rationality DTC's</li> <li>• 15 % &lt; Fuel Level &lt; 85. %</li> <li>• 10.00 V &lt; System Voltage &lt; 18.00 V</li> <li>• 4 °C &lt; IAT &lt; 30°C</li> <li>• ECT &lt; 30 °C</li> <li>• BARO &gt; 74.00 kPa (8000 ft)</li> </ul> <p style="text-align: center;">Cold Start Test</p> <ul style="list-style-type: none"> <li>• IAT &lt; 30°C</li> <li>• Cold temperature Δ(ECT-IAT): &lt; 8 °C if ECT &gt; IAT</li> <li>• Cold Test Timer &lt; 1000 seconds</li> </ul>	Once per cold start.  Cold start: max time is 1000 seconds	DTC Type B																				
IDLE SYSTEM - LOW ENGINE SPEED	P0506	This DTC will determine if a low idle exists.	RPM < Desired RPM by an amount determined in a look up table based on engine coolant  <table border="0"> <thead> <tr> <th><u>ECT</u></th> <th><u>value</u></th> </tr> </thead> <tbody> <tr><td>56</td><td>-100</td></tr> <tr><td>68</td><td>-100</td></tr> <tr><td>80</td><td>-100</td></tr> <tr><td>92</td><td>-100</td></tr> <tr><td>104</td><td>-100</td></tr> <tr><td>116</td><td>-100</td></tr> <tr><td>128</td><td>-100</td></tr> <tr><td>140</td><td>-3200</td></tr> <tr><td>152</td><td>-3200</td></tr> </tbody> </table>	<u>ECT</u>	<u>value</u>	56	-100	68	-100	80	-100	92	-100	104	-100	116	-100	128	-100	140	-3200	152	-3200	No MAF, MAP, IAT, ECT, TP, Injector, Fuel System, Misfire, , VSS or Purge DTC Engine Run > 60 sec. ECT ≥ 60 ° C BARO > 65 kPa IGN. voltage > 10.5 volts but < 18 volts IAT > -10 ° C Time since a gear state change > 3 seconds Time since a TCC mode change is > 3 seconds Idle control logic indicates that the engine is in an idle condition Idle conditions present for > 2 seconds to enable diagnostic test	<p><b>Time for each test:</b> Within pass criteria continuously for 12 seconds Outside of fail criteria continuously for 8 seconds</p> <p>3 tests to fail; must leave enable criteria between each test</p> <p><u>Frequency:</u> Continuous after enable 100ms loop</p>	DTC Type B
<u>ECT</u>	<u>value</u>																									
56	-100																									
68	-100																									
80	-100																									
92	-100																									
104	-100																									
116	-100																									
128	-100																									
140	-3200																									
152	-3200																									

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE																				
IDLE SYSTEM - HIGH ENGINE SPEED	P0507	This DTC will determine if a high idle exists	RPM > Desired RPM by an amount determined in a look up table based on engine coolant  <table border="1"> <thead> <tr> <th>ECT</th> <th>value</th> </tr> </thead> <tbody> <tr><td>56</td><td>200</td></tr> <tr><td>68</td><td>200</td></tr> <tr><td>80</td><td>200</td></tr> <tr><td>92</td><td>200</td></tr> <tr><td>104</td><td>200</td></tr> <tr><td>116</td><td>200</td></tr> <tr><td>128</td><td>200</td></tr> <tr><td>140</td><td>3200</td></tr> <tr><td>152</td><td>3200</td></tr> </tbody> </table>	ECT	value	56	200	68	200	80	200	92	200	104	200	116	200	128	200	140	3200	152	3200	No MAF, MAP, IAT, ECT, TP, Injector, Fuel System, Misfire, VSS or Purge DTC Engine Run > 60 sec. ECT ≥ 60 ° C BARO > 65 kPa IGN. voltage > 10.5 volts but < 18 volts IAT > -10 ° C Time since a gear state change > 3 seconds Time since a TCC mode change is > 3 seconds Idle control logic indicates that the engine is in an idle condition Idle conditions present for > 2 seconds to enable diagnostic test	<b>Time for each test:</b> Within pass criteria continuously for 12 seconds Outside of fail criteria continuously for 12 seconds  3 tests to fail; must leave enable criteria between each test  <u>Frequency:</u> Continuous after enable 100ms loop	DTC Type B
ECT	value																									
56	200																									
68	200																									
80	200																									
92	200																									
104	200																									
116	200																									
128	200																									
140	3200																									
152	3200																									
Control Module Read Only Memory (ROM)	P0601	This DTC will be stored if the calibration check sum is incorrect	Output state invalid	<ul style="list-style-type: none"> <li>PCM state = crank or run</li> <li>Ignition voltage ≥ 5 volts</li> </ul>	1 failure if it occurs on the first pass, 5 failures after the first pass has completed successfully  <u>Frequency:</u> Runs continuously in the background	DTC Type A																				
Control Module Not Programmed	P0602	This DTC will be stored if the PCM is a service PCM that has not been programmed.	Output state invalid	<ul style="list-style-type: none"> <li>PCM state = crank or run</li> <li>PCM is identified through calibration as a Service PCM</li> </ul>	Test is run at Powerup  Test also runs: <u>Frequency:</u> 100ms loop Continuous	DTC Type A																				
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error at controller power-up	Checksum at power-up does not match checksum at power-down		1 failure  Once at power-up	DTC Type A																				
ECM RAM FAILURE	P0604	Indicates that ECM is unable to correctly write and read data to and from RAM	Data read does not match data written	Ignition in Run or Crank	Should finish within 30 seconds at all engine conditions.	DTC Type A																				

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
PCM Processor 1. Processor Performance Check - Throttle limiting Fault 2. Processor Performance Check - ETC software is not executed in proper order 3. Processor Performance Check 4. Processor Performance Check - SPI failed 5. Processor Performance Check - motor processor state of health (Main) 6. Processor Performance Check - Learn Corruption Fault (Main&motor processor) 7. Processor Performance Check - Learn Corruption Fault MAIN & motor processor 8. Processor Performance Check - motor processor state of health (Main) Processor Performance Check - MAIN state of health (motor processor)	P0606	Indicates that the ECM has detected an ETC internal processor integrity fault	1. MHC processor detects throttle limiting fault 2. Software tasks loops > schedule tasks loop 3. Loss of SPI communication from the motor processor 4. 1.5 msec < Average motor processor state of health toggle > 2.5 msec 5. TPS or APPS minimum learned values fail compliment check 6. TPS or APPS minimum learned values fail range check 7. Motor processor integrity check error occurs  Motor processor integrity check error of main processor occurs	Ignition in unlock/accessory, run or crank System voltage>5.23 V	1. 187.5 ms in the MHC processor 2. Error > 5 times of loop time; loop time are 12.5, 25,50,100 and 250 ms in the main processor 3. In the main processor, 159/400 counts intermittent or 15 counts continuous; 39 counts continuous @ initialization 4. In the MHC processor 475 ms at initialization, 175 msec continuous or 20/200 intermittent. 5. 187.5ms continuous/100 ms intermittent in the main processor 6. 187.5ms continuous/100 msec intermittent in the main processor	DTC Type A

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Control Module Accelerator Pedal Position (APP) System Performance	P060D	Verify that the indicated accelerator pedal position calculation is correct	<ol style="list-style-type: none"> <li>PPS sensor switch fault</li> <li>Difference between Main processor indicated accelerator pedal position and MHC processor indicated accelerator pedal position &gt; 2.5%</li> </ol> <p>If your program does not have equal slope pedal sensors, delete number one above as it does not apply.</p>	<ol style="list-style-type: none"> <li>Ignitions in unlock/ accessory and run, System voltage &gt; 5.23 V No PCM processor DTC</li> </ol> <p>Ignition in unlock, accessory, run or crank System voltage &gt; 5.23 V No PCM processor DTC, No Comm Fault w/ Main</p>	39 counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Control Module EEPROM Error	P062F	Indicates that the NVM Error flag has not been cleared	Last EEPROM write did not complete	Ignition on.	1 test failure Once on controller power-up	DTC Type A
5 Volt Reference 1 Circuit	P0641	Detects a continuous or intermittent short on the #1 5 V sensor reference circuit	Vref1 < 4.43 or > 4.66 volts	Ignition in unlock/accessory, run or crank System voltage > 5.23 V No ECM processor DTCs	19/39 counts or 187.5 msec continuous; 12.5 msec/count in main /MHC processor	DTC Type A
Malfunction Indicator Lamp Control Circuit MALF (ODM)	P0650	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts) Remove Vehicle Start is not active	20 failures in a 25 sample test 250 msec / sample	DTC Type B, No MIL
5 Volt Reference 2 Circuit	P0651	Detects a continuous or intermittent short on the #2 5 V sensor reference circuit	Vref1 < 4.43 or > 4.66 volts	Ignition in unlock/accessory, run or crank System voltage > 5.23 V No ECM processor DTCs	19/39counts or 187.5 msec continuous; 12.5 msec/count in main/MHC processor	DTC Type A
Powertrain Relay Control (ODM)	P0685	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.	RunCrankIgnInRange (9 volts < Ignition < 18 volts)	8 failures in a 10 sample test 1 second / sample	DTC Type B
Transmission Control Module (TCM) Requested MIL Illumination	P0700	Monitors the TCM MIL request line to determine when the TCM has detected a MIL illuminating fault.	Transmission Emissions-Related DTC set	Time since power-up > 3 seconds	Continuous	DTC Type A  No MIL

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Traction Control Torque Request Circuit	P0856	Determines if torque request from the EBTCM is valid	<p>For PPEI3</p> <p>1. Serial Communication 2's complement not equal for message \$1C9 (PPEI3)</p> <p>2. Serial Communication rolling count value shall be + 1 from previous \$1C9 message (PPEI3)</p> <p>or for PPEI2</p> <p>1. Serial Communication 2's complement not equal for message \$140 (PPEI2)</p> <p>2. Serial Communication rolling count value shall be + 1 from previous \$140 message (PPEI2)</p> <p>or for Class2 w/ PWM</p> <p>4% &lt;= PWM or 95% &gt;= PWM set a fail coun</p>	<p>Torque Reduction Signal Diagnostic Enabled</p> <p>For GMLAN PPEI2 or PPEI3 (KeTCSD_b_GMLAN_DiagEnable == TRUE)</p> <p>No Serial communication loss to TCM (U0108)</p> <p>Engine Running == TRUE</p> <p>Power Mode = Run</p> <p>Traction Control System == Present for GMLAN \$380 (PPEI2) or \$4E9 (PPEI3) message</p> <p>or for Class2 w/ PWM Systems:</p> <p>KbTCSD_NoFreqDiagEnbl == TRUE</p> <p>Traction/Drage Control System == Present for PWM \$2B3C (Class2) message</p>	<p>1.# of Protect Errors &gt;= 10</p> <p>2. # of Alive Rolling Errors &gt;= 10 in 10 SampleSize # of Samples performed in the 25ms loop</p> <p>or for Class2 w/ PWM Systems:</p> <p>Fail Counts =&gt; 10 in 10 # of samples performed in the 50ms loop</p>	Special DTC Type C
Inlet Airflow System Performance	P1101	This DTC detects flaws with all Inlet Airflow sensors suggesting a major inlet flow problem.	<p>(Measured Flow – Modeled air Flow) Filtered &gt; 25</p> <p>or</p> <p>(Measured MAP - Manifold Model 1 pressure) filtered &gt; 20</p> <p>and</p> <p>(Measured MAP – Manifold Model 2 pressure) filtered &gt; 20</p> <p>and</p> <p>(The calculated throttle residual from the MAF model and the Manifold Model) filtered &gt; 300</p>	<p>Engine rpm =&gt;500 and &lt;= 5000</p> <p>MAP sensor high/low DTC's not active</p> <p>EGR DTC's P0401,.P0405, and P1404 not active</p> <p>MAF sensor high/low DTC's not active</p> <p>Crank sensor DTC's not active</p> <p>Engine Coolant DTC's not active</p> <p>Intake Air Temp. DTC's not active</p> <p>Engine Coolant &gt; 70 deg C and &lt; 129 deg C</p> <p>Intake Air Temp &gt; -7 deg C and &lt; 60 deg C</p> <p>Refer to "IFRD weight factors" attached at bottomMinimum total weight factor (all factors multiplied together) &gt;.26</p>	<p>Continuous</p> <p>Evaluated every 12.5 ms</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Insufficient Switching Bank 1 Sensor 1	P1133	This DTC determines if the O2 sensor is no longer sufficiently switching.	Half cycle L/R switches < 43 OR Half cycle R/L switches < 43  OR  Slope Time L/R switches < 1 OR Slope Time R/L switches < 1	<u>Common Enable Criteria</u> <ul style="list-style-type: none"> <li>• No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>• Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>• Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>• Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>• 10 volts &lt; system voltage &lt; 18 volts</li> <li>• EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <u>Specific Enable Criteria</u> <ul style="list-style-type: none"> <li>• O2 Heater on for <math>\geq 0</math> seconds</li> <li>• B1S1 DTCs = Not Active</li> <li>• Learned heater resistance is valid</li> <li>• Misfire DTC = Not Active</li> <li>• ECT &gt; 70 °C</li> <li>• IAT &gt; -40 °C</li> <li>• Engine run time &gt; 202 seconds</li> <li>• EVAP Canister purge duty cycle <math>\geq 0</math> %</li> <li>• 20 gps <math>\leq</math> MAF <math>\leq</math> 40 gps</li> <li>• 1100 <math>\leq</math> RPM <math>\leq</math> 2500</li> <li>• Ethanol percentage &lt; 85 %</li> <li>• Baro &gt; 70 kPa</li> <li>• Throttle position <math>\geq 3</math> %</li> <li>• Fuel Level &gt; 10 %</li> <li>• Fuel state = closed loop</li> <li>• No fuel level data faults</li> <li>• Transmission (automatic) not in Park, Reverse or Neutral</li> <li>• Transmission gear selection is not defaulted</li> <li>• Baro is not defaulted</li> </ul> All of the above met for at least 1 second.	60 seconds  <u>Frequency:</u> Once per trip	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2S Insufficient Switching Bank 2 Sensor 1	P1153	This DTC determines if the O2 sensor is no longer sufficiently switching.	Half cycle L/R switches < 43 OR Half cycle R/L switches < 43  OR Slope Time L/R switches < 1 OR Slope Time R/L switches < 1	<u>Common Enable Criteria</u> <ul style="list-style-type: none"> <li>No TP Sensor, MAP, ECT, MAF, IAT, Evap, Fuel Injector DTC's</li> <li>Catalyst monitor diagnostic Intrusive Test = Not Active</li> <li>Post Oxygen Sensor Diagnostic Intrusive Test = Not Active</li> <li>Traction Control, AIR, Fuel, Idle, EGR, and Engine Not Overspeed Intrusive Tests = Not Active</li> <li>10 volts &lt; system voltage &lt; 18 volts</li> <li>EGR, Idle, Fuel Inj, and AIR Device controls = Not Active</li> </ul> <u>Specific Enable Criteria</u> <ul style="list-style-type: none"> <li>O2 Heater on for ≥ 0 seconds</li> <li>B2S1 DTCs = Not Active</li> <li>Learned heater resistance is valid</li> <li>Misfire DTC = Not Active</li> <li>ECT &gt; 70 °C</li> <li>IAT &gt; -40 °C</li> <li>Engine run time &gt; 202 seconds</li> <li>EVAP Canister purge duty cycle ≥ 0 %</li> <li>20 gps ≤ MAF ≤ 40 gps</li> <li>1100 ≤ RPM ≤ 2500</li> <li>Ethanol percentage &lt; 85 %</li> <li>Baro &gt; 70</li> <li>Throttle position ≥ 3 %</li> <li>Fuel Level &gt; 10</li> <li>Fuel state = closed loop</li> <li>No fuel level data faults</li> <li>Transmission (automatic) not in Park, Reverse or Neutral</li> <li>Transmission gear selection is not defaulted</li> <li>Baro is not defaulted</li> </ul> All of the above met for at least 1 second.	60 seconds  <u>Frequency:</u> Once per trip	DTC Type B
ENGINE PROTECTION MODE ACTIVE	P1258	Monitor for engine protection mode active.	Coolant temperature ≥ 131°C Condition exists ≥ 2 seconds.	No coolant sensor failures	Set immediately upon engine protection mode active.	DTC Type A
ABS Rough Road Malfunction	P1380	This diagnostic detects if the ABS Controller is indicating a fault. When this occurs, misfire will continue to run.	ABS Controller sends a message to the ECM indicating that a failure has occurred in the ABS Module.	<ul style="list-style-type: none"> <li>VS ≥ 0 kph</li> </ul>	40 failures out of 80 samples 100 msec loop continuous	DTC Type C  (DTC can only set when a P0300 Light Request is True)

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
ABS System Rough Road Detection Communication Fault	P1381	This diagnostic detects if the rough road information is no longer being received from the ABS Module. When this occurs, misfire will continue to run.	Serial data messages are lost.	<ul style="list-style-type: none"> <li>None</li> </ul>	40 failures out of 80 samples 100 msec loop continuous	DTC Type C  (DTC can only set when a P0300 Light Request is True)
Cold Start Emissions Reduction System Fault	P1400	Model based test computes power from exhaust flow and thermal energy resulting from the elevated idle speed and retarded spark advance. Detects if the cold start emission reduction system has failed resulting in the delivered power being out of range.	<p>If RPM in Park/Neutral &lt; 1004 - 1145 {f(ECT and engine run time)} or If RPM in Gear &lt; 650 - 750 {f(ECT and engine run time)}, then the model tends to make a fail decision.</p> <p>If Spark Advance in Park/Neutral &gt; 5 {f(RPM and air per cylinder)} or If Spark Advance in Gear &gt; 5 {f(RPM and air per cylinder)}, then the model tends to make a fail decision.</p> <p>The DTC will set when: (Average desired accumulated power - Average estimated accumulated power) &gt; .25 Or (Average desired accumulated power - Average estimated accumulated power) &lt; -11</p>	<p>Cold start emission reduction strategy is active. VS &lt; 2 kph Airflow per cylinder &gt; 40 mg/cyl TP(area w/o idle) &lt; .05 % Engine run time &gt; 0 Sec.</p> <p>No DTC's set for the following systems: MAP, MAF, IAT, ECT, Misfire, Electronic Spark Timing, Crank sensor, Idle, Fuel Injection, TP sensor, VS sensor, 5 volt reference, ECM/PCM Memory, Intake Flow Rationality</p>	100ms loop  Runs once per trip when the cold start emission reduction strategy is active.  Test completes after 10 seconds of accumulated qualified data	DTC Type A
Cooling Fan Speed Output Circuit	P1482	Control circuit voltage is monitored during operation. It should be low during operation and near B+ when "off"	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match	Engine speed greater than 400 rpm Ignition voltage > 10 volts, but < 18 volts	5 seconds  Continuous	DTC Type B For use on vehicles with PWM Fan

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Throttle Actuator Control (TAC) Module - Throttle Actuator Position Performance	P1516	1. Detect a throttle positioning error. Determine if the actuator has been miswired.	1.  throttle error  >=  2.00%  after > 0.4875 sec stability with no change in error sign,  OR GMX215  throttle error  > 6.401 % GMX265  throttle error  > 6.441 % GMX295  throttle error  > 6.151 %  TPS1 < 1.91 Volts	Ignition in run or crank [(RPM>0 and system voltage > 5.4 Volts) OR (RPM=0 and not in battery saver mode and System voltage > 11 Volts)] No comm. Fault w/ Main TPS min learn not active  No ignition correlation DTC active.	187.5ms in the MHC processor	DTC Type A
Ignition Correlation	P1682	Detect a continuous or intermittent OOC between the Run/Crank Ignition Voltage & ETC Run/Crank Ignition Voltage	Run/Crank – ETC Run/Crank  > 3.00 V	Ignition in unlock/accessory, run or crank System voltage > 5.23 V & Powertrain Relay Commanded on.  Run/Crank Ignition ≥ voltage required to engage relay at the current IAT temperature, or ETC Run/Crank > voltage required to hold relay in once engaged.  <u>Pull-In Voltage</u> 23° C = 7.00 volts 85° C = 8.70 volts 95° C = 9.00 volts 105° C = 9.20 volts 125° C = 10.00 volts  <u>Hold-In Voltage</u> 5.50 volts	14 / 14 counts , 12.5msec loop time, in main processor	DTC Type A
Fuel Level No Change, Stuck in Range Secondary Tank	P2066	This DTC will detect a fuel sender stuck in range .	IF Delta Fuel Volume change less than 3 liters over a accumulated 100 Kilometers.	No VSS DTC's set Engine Running	Continuous	DTC Type B
Fuel Level Stuck Low Secondary Tank	P2067	This DTC will detect a fuel sender stuck out of range low	Fuel level Sender % of 5V range less than 10 %	runs continuously	240 failures out of 300 samples 1 sample = 100 ms  Continuous	DTC Type B
Fuel Level Stuck High Secondary Tank	P2068	This DTC will detect a fuel sender stuck out of range high	Fuel level Sender % of 5V range > than 70%	runs continuously	240 failures out of 300 samples 1 sample = 100 ms  Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Control Module Throttle Actuator Position Performance	P2101	<ol style="list-style-type: none"> <li>Detect a throttle positioning error</li> <li>Detect excessive motor driver current (PWM)</li> </ol>	Difference between measured throttle position and modeled throttle position > <ol style="list-style-type: none"> <li>GMX215 6.401 %</li> <li>GMX265 6.441 %</li> <li>GMX295 6.151 %</li> </ol> Motor driver PWM output > Thresh. Thresh based on system voltage.	<ol style="list-style-type: none"> <li>Ignition in run or crank [(RPM&gt;0 and system voltage &gt; 5.5 Volts) OR (RPM=0 and not in battery saver mode and System voltage &gt; 11.0 Volts)] Throttle not at default position</li> <li>NA</li> </ol> No ignition correlation DTC active.	<ol style="list-style-type: none"> <li>15/15 counts continuous</li> </ol> Check runs every 12.5 msec in the main processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 1	P2120	<ol style="list-style-type: none"> <li>Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor</li> <li>Detect a continuous or intermittent short or open in the APP sensor #1 on MHC processor</li> </ol>	<ol style="list-style-type: none"> <li>APP1 &lt; 0.325 OR APP1 &gt; 4.75</li> <li>APP1 &lt; 0.325 OR APP1 &gt; 4.75</li> </ol>	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	<ol style="list-style-type: none"> <li>19/39counts or 13counts continuous; 12.5 msec/count in the main processor</li> </ol> 19/39counts or 13counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 1 Lo	P2122	Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor	APP 1 < 0.325	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	19/39counts or 13 counts continuous; 12.5 msec/count in the Main processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 1 Hi	P2123	Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor	APP 1 > 0.325	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	19/39counts or 13 counts continuous; 12.5 msec/count in the Main processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 2	P2125	<ol style="list-style-type: none"> <li>Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor</li> <li>Detect a continuous or intermittent short or open in the APP sensor #1 on MHC processor</li> </ol>	<ol style="list-style-type: none"> <li>APP2 &lt; 0.325 OR APP2 &gt; 4.75</li> <li>APP2 &lt; 0.325 OR APP2 &gt; 4.75</li> </ol>	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	<ol style="list-style-type: none"> <li>19/39counts or 13counts continuous; 12.5 msec/count in the main processor</li> </ol> 19/39counts or 13counts continuous; 12.5 msec/count in the MHC processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 2 Lo	P2127	Detect a continuous or intermittent short or open in the APP sensor #2 on Main processor	APP 2 < 0.325	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	19/39counts or 13 counts continuous; 12.5 msec/count in the Main processor	DTC Type A
Accelerator Pedal Position (APP) Sensor 2 Hi	P2128	Detect a continuous or intermittent short or open in the APP sensor #2 on Main processor	APP 2 > 4.75	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	19/39counts or 13 counts continuous; 12.5 msec/count in the Main processor	DTC Type A

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Throttle Position (TP) Sensor 1-2 Correlation	P2135	<ol style="list-style-type: none"> <li>1. Detects a continuous or intermittent correlation fault between TP sensors #1 and #2 on Main processor</li> <li>2. Detects a continuous or intermittent correlation fault between TP sensors #1 and #2 on MHC processor</li> </ol>	<ol style="list-style-type: none"> <li>1. Difference between TPS1 displaced and TPS2 displaced &gt; 7.00 % offset at min. throttle position with an increasing to 10% at max. throttle position</li> <li>2. Different between (raw min TPS1 ) and (raw_min TPS2) &gt; 4.99 % of Vref</li> </ol>	Ignition in unlock/accessory, run or crank System voltage >5.23 V No 5 Volt reference DTCs	<ol style="list-style-type: none"> <li>1. 79/159 counts or 63 counts continuous; 3.125 msec/count in the main processor</li> <li>19/39 counts or 15 counts continuous; 12.5 msec/count in the MHCprocessor</li> </ol>	DTC Type A
Accelerator Pedal Position (APP) Sensor 1-2 Correlation	P2138	Detect an invalid minimum mechanical position correlation between APP sensor #1 and #2	<ol style="list-style-type: none"> <li>1. Difference between (raw min. learned PPS#1 voltage-raw min. PPS#1 voltage) and (raw PPS#2 voltage - raw min. learned PPS#2 voltage) &gt;5.00 % offset at min. throttle position with an increasing to 10% (0.5v)at max. throttle position for Main processor.</li> </ol> OR <ol style="list-style-type: none"> <li>2. Difference between the learned PPS1 min and PPS2 min &gt; 5.00 % Vref</li> </ol>	<ol style="list-style-type: none"> <li>1. Ignition in unlock/accessory, run or crank System voltage &gt;5.23 V No 5 Volt reference DTC's</li> <li>2. Ignition in unlock/accessory, run or crank System voltage &gt;5.23 V No 5 Volt reference DTC's</li> </ol>	<ol style="list-style-type: none"> <li>1. 19/39 counts intermittent or 15 counts continuous, 12.5 msec/count in the main processor</li> <li>2. 19/39 counts intermittent or 15 counts continuous, 12.5 msec/count in the MHC processor</li> </ol>	DTC Type A
Minimum Throttle Position Not Learned	P2176	TP minimum learning not completed	<ol style="list-style-type: none"> <li>1. TPS &gt; 0.935 Volts during TPS min learn on the Main processor</li> </ol> OR <ol style="list-style-type: none"> <li>TPS &gt; 0.935 Volts during TPS min learn on the MHC processor</li> </ol>	Minimum TPS learn active state Stable throttle position reading for 40 msec Ignition in run or crank No TPS circuit DTCs No ignition correlation DTC active.	1.8secs	DTC Type A
Barometric Pressure (BARO) Sensor Performance	#P2227	This DTC determines if the Baro sensor is stuck within the normal operation range	(Measured Baro – Previous Baro) > 10	Engine rpm =>550 and <= 5000 MAP sensor high/low DTC's not active EGR DTC's P0401, P0405, and P1404 not active MAF sensor high/low DTC's not active Crank sensor DTC's not active Engine Coolant DTC's not active Intake Air Temp. DTC's not active Engine Coolant > 70 deg C and < 129 deg C Intake Air Temp > -7 deg C and < 60 deg C	20 failures in a 25 sample test 250 msec / sample	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Barometric Pressure (BARO) Sensor Low Voltage	#P2228	This DTC detects a continuous short to low or open in either the signal circuit or the Baro sensor.	Baro voltage < 2% of Vref (0.1 volts)	Key-On test: Engine speed ≤ 400 RPM Run Test: No TPS failures present TPS ≥ 0%, and Engine Speed ≤ 800 RPM, or TPS ≥ 12.5%, Engine Speed > 800 RPM)	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B
Barometric Pressure (BARO) Sensor High Voltage	#P2229	This DTC detects an open sensor ground or continuous short to high in either the signal circuit or the Baro sensor	Baro voltage > 98% of Vref (4.9 volts)	No TPS failures present Engine running Engine run time > Min based on power-up coolant temp (-30°C = 242 seconds, -15°C = 188 seconds, 0°C = 144 seconds, 15°C = 80 seconds, 30°C = 0 seconds) TPS < 1%, and Engine Speed ≤ 1200 RPM, or TPS < 20%, and Engine Speed > 1200 RPM	320 failures in a 400 sample test 12.5 msec / sample	DTC Type B
Turbo/Supercharger Bypass Valve – Mechanical	#P2261	This DTC will determine if the bypass valve is stuck closed	Calculated bypass valve residuals  BP Stuck Closed 1 Resid > Cal AND/OR BP Stuck Open Resid 1 > Calibration  AND  BP Stuck Closed 2 Resid > Cal AND/OR BP Stuck Open Resid 2 > Calibration	Engine rpm =>550 and <= 5000 MAP sensor high/low DTC's not active EGR DTC's P0401..P0405, and P1404 not active MAF sensor high/low DTC's not active Crank sensor DTC's not active Engine Coolant DTC's not active Intake Air Temp. DTC's not active Engine Coolant > 70 deg C and < 129 deg C Intake Air Temp > -7 deg C and < 60 deg C	Continuous  The SCIAP reading and the Manifold Model calculations are performed in the same LoRes loop	DTC Type B
AIR System Pressure Sensor A Circuit	# P2430	Detects a stuck-in-range AIR pressure sensor signal.	Stuck in Range Average Error < 0.5 AND Stuck in Range Variance < 1.0	No active DTC P0412 set. No active DTC P0418 set. No active DTC P0606 set. No active DTC P2432 set. No active DTC P2433 set. No active 5 volt reference DTCs set. AIR pressure sensor circuit fault pending = False. AIR pump is commanded ON	Stuck in Range Cumulative Info > 5 sec.  Once per trip where AIR pump operation is requested at startup.	DTC Type B
AIR System Pressure Sensor A Performance	# P2431	Detects significant errors in the comparison of the AIR pressure sensor signal and estimated BARO as well as evaluates the quality of the comparison.	Cumulative Error < -500 or > 500 Test quality is based on BARO and the distance traveled since the last unthrottled BARO update.	No active DTC P0412 set. No active DTC P0418 set. No active DTC P0606 set. No active DTC P2432 set. No active DTC P2433 set. No active 5 volt reference DTCs set. AIR pressure sensor circuit fault pending = False. AIR pump is commanded OFF	Performance Cumulative Info > 30 sec.  Continuous, 100ms loop	DTC Type B
AIR System Pressure Sensor A Circuit Low	# P2432	Detects a low out-of-range AIR pressure sensor signal	AIR Pressure Sensor signal < 5% of 5V ref.	No active DTC P0606 set. No active 5 volt reference DTCs set.	50 fail counts out of 63sample counts.  Continuous, 12.5 ms loop.	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE																				
AIR System Pressure Sensor A Circuit High	# P2433	Detects a high out-of-range AIR pressure sensor signal	AIR Pressure Sensor signal > 94% of 5V ref.	No active DTC P0606 set. No active 5 volt reference DTCs set.	50 fail counts out of 63 sample counts.  Continuous, 12.5 ms loop.	DTC Type B																				
AIR System Switch / Valve Stuck Open	# P2440	Detects an AIR system control valve stuck open condition.  This test is run during the phase 2 (pump on, control valve shut) portion of the SAI diagnostic.	AIR normalized pressure error < a table value (lower than predicted pressure) during SAID phase 2 test  <table border="1"> <thead> <tr> <th>Cumul. Wght. time</th> <th>Pres. Err.</th> </tr> </thead> <tbody> <tr><td>0</td><td>-2</td></tr> <tr><td>1</td><td>-2</td></tr> <tr><td>2</td><td>-2</td></tr> <tr><td>3</td><td>-1.5</td></tr> <tr><td>4</td><td>-1.5</td></tr> <tr><td>5</td><td>-1.5</td></tr> <tr><td>6</td><td>-1.5</td></tr> <tr><td>7</td><td>-1.5</td></tr> <tr><td>8</td><td>-1.5</td></tr> </tbody> </table>	Cumul. Wght. time	Pres. Err.	0	-2	1	-2	2	-2	3	-1.5	4	-1.5	5	-1.5	6	-1.5	7	-1.5	8	-1.5	No active AIR pressure sensor circuit DTCs set. No active AIR pressure sensor performance DTCs set. No active MAP sensor DTCs set. No active AIR pump relay circuit DTC set. No active AIR control valve relay circuit DTC set. No active MAF sensor DTCs set. No active 5 volt reference DTCs set. No active IAT sensor DTCs set. No active ECT sensor DTCs set. No active Misfire DTCs set. No active catalyst monitor DTCs set. No active fuel injector DTCs set. No active EST DTCs set. No active DTC P0411 set. No active DTC P0606 set. AIR pressure sensor circuit fault pending = False. AIR operation is allowed this start. 18 volts > System voltage > 9 volts.	SAID phase 2 conditional test weight > 1.5 seconds  Conditional test weight is based on Baro, Mass air flow & System voltage.  Once per trip where AIR pump operation is requested at startup.	DTC Type B
Cumul. Wght. time	Pres. Err.																									
0	-2																									
1	-2																									
2	-2																									
3	-1.5																									
4	-1.5																									
5	-1.5																									
6	-1.5																									
7	-1.5																									
8	-1.5																									
AIR System Pump Stuck On	# P2444	Detects an AIR pump stuck ON condition.  This test is run during the phase 3 (pump off) portion of the SAI diagnostic.	AIR normalized pressure error > 4.2 kPa (higher than predicted pressure) during SAID phase 3 test	No active AIR pressure sensor circuit DTCs set. No active AIR pressure sensor performance DTCs set. No active MAP sensor DTCs set. No active AIR pump relay circuit DTC set. No active AIR control valve relay circuit DTC set. No active MAF sensor DTCs set. No active 5 volt reference DTCs set. No active IAT sensor DTCs set. No active ECT sensor DTCs set. No active Misfire DTCs set. No active catalyst monitor DTCs set. No active fuel injector DTCs set. No active EST DTCs set. No active DTC P0411 set. No active DTC P0606 set.bb No active DTC P2440 set. AIR pressure sensor circuit fault pending = False. AIR operation is allowed this start. SAID post control time < 14 seconds	Within 10 seconds of the AIR pump being commanded OFF.  Once per trip where AIR pump operation is requested at startup.	DTC Type A																				

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Transmission Control Torque Request Circuit	P2544	Determines if torque request from the TCM is valid	<ol style="list-style-type: none"> <li>1. Serial Communication 2's complement not equal for message \$199 (PTEI3)</li> <li>2. Serial Communication rolling count value shall be + 1 from previous \$199 message (PTEI3)</li> <li>3. 2's complement not equal of torque requested value or torque requested type when stored in ECM</li> <li>4. If TCM Requested Torque in message \$199 (PTEI3) &gt; 400</li> </ol>	No Serial communication loss to TCM (U0101) Engine Running == TRUE Power Mode = Run Crank Active	<ol style="list-style-type: none"> <li>1. # of Protect Errors &gt;= 16</li> <li>2. # of Alive Rolling Errors &gt;= 6 in 10 samples</li> <li>3. # of RAM errors &gt;= 3</li> <li>4. # of range errors &gt;= 3 in 10 samples</li> </ol> <p>If any the above exist for &gt; 2 seconds then increment fail counter else fail counter is reset</p> <p>If the fail counter is =&gt; 2 fault is active</p> <p>Pass diagnostic if none of the above conditions are present for =&gt; 2 seconds</p> <p>12.5ms loop</p>	DTC Type B
ECM/PCM Internal Engine Off Timer Performance	P2610	This DTC determines if the engine off timer does not initialize or count properly.  Clock rate test: Checks the accuracy of the 1 second timer by comparing it with the 12.5 msec timer	<p>Initial value test: 1 second ≤ Initial Value ≤ 10 seconds</p> <p>Clock rate test: .8 sec ≤ 1 second accuracy &lt; 1.2 sec</p>	ECM is powered down DTC sets on next key cycle if failure detected -40°C ≤ IAT ≤ 125°C	<p>Initial value test: 3 failures 1.375 sec / sample</p> <p>Clock rate test: 8 failures in a 10 sample test 1 second / sample test runs once each key-off</p>	DTC Type B
Fuel Pump 2 Flow Insufficient	P2636 XLR only	DTC monitors that enough fuel is transferred from the secondary fuel tank to the primary fuel tank	Both primary and secondary fuel levels are in the readable range for more then 300 seconds.	runs continuously	Continuous	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2 Sensor Circuit Range/Performance Bank 1 Sensor 1	P2A00	This DTC determines if the O2 sensor voltage is not meeting the voltage criteria to enable closed loop fueling.	Closed loop fuel control O2 sensor Ready flag set to "Not Ready."  O2 sensor voltage must be > 650 millivolts or < 250 millivolts to set closed loop fuel O2 Ready flag. Once set to "Ready," the O2 sensor voltage cannot be > 250 millivolts and < 650 millivolts for > 10 seconds or the O2 Ready flag will be reset to "Not Ready."	<ul style="list-style-type: none"> <li>No TP Sensor, MAF, MAP, IAT, ECT, EVAP, Secondary Air, Injector DTC's</li> <li>No B1S1 or B2S1 O2 DTC's</li> <li>Engine Run Time ≥ 100 seconds</li> <li>ECT ≥ 70° C</li> <li>Engine Metal Overtemp = Not Active</li> <li>Traction Control = Not Active</li> <li>No default throttle action</li> <li>Not in Catalyst Protection Mode</li> <li>10 volts ≤ Ignition Voltage ≤ 18 volts</li> <li>500 ≤ Engine Speed ≤ 5000</li> <li>3 gps ≤ Mass Airflow ≤ 30 gps</li> <li>Not in Decel Fuel Cutoff Mode</li> <li>Not in Power Enrichment</li> <li>Predicted O2 temp ≥ 0°C</li> </ul> <p>All of the above met for 5 seconds.</p>	250 test failures in a 300 test sample  <u>Frequency:</u> Continuous 100ms loop	DTC Type B
O2 Sensor Circuit Range/Performance Bank 1 Sensor 2	P2A01	This DTC determines if the post catalyst O2 sensor is stuck in a normal voltage range and thereby can no longer be used for post oxygen sensor fuel control or for catalyst monitoring. The diagnostic includes a passive (stage 1) test and an intrusive (stage 2) test. The stage 2 increases or reduces delivered fuel to achieve the required rich or lean threshold.	Post catalyst O2 sensor cannot achieve voltage ≥ 751 millivolts and voltage ≤ 200 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No O2 circuit, heater, response or heater driver DTC's active</li> <li>No TP Sensor, ETC, MAF, ECT, MAP, IAT, EVAP, Secondary Air, Fuel Injector DTC's</li> <li>Engine Runtime ≥ 280 seconds</li> <li>Post catalyst O2s have a valid resistance learn</li> </ul> <p><u>Stage 2 Specific Enable Criteria:</u></p> <ul style="list-style-type: none"> <li>Stage 1 portion of test not passed</li> <li>No Fuel Trim or Misfire DTC's active</li> <li>Engine Runtime &gt; 281 seconds</li> <li>500 rpm ≤ Engine Speed ≤ 5000 rpm</li> <li>3 gps ≤ Airflow ≤ 50 gps</li> <li>5 kph ≤ Vehicle Speed ≤ 132 kph</li> </ul> <p>All of the above met for at least 2 seconds, and then:</p> <ul style="list-style-type: none"> <li>1.05 ≤ Short term fuel trim ≤ 0.95</li> <li>Fuel state = closed loop</li> <li>Drive state = decel</li> <li>EVAP diagnostic not in control of purge</li> </ul>	<p><u>Stage 1:</u> Runs until pass or fail reporting.</p> <p><u>Stage 2:</u> Up to 475 grams of accumulated airflow for each threshold</p> <p><u>Frequency:</u> Once per trip</p>	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
O2 Sensor Circuit Range/Performance Bank 2 Sensor 1	P2A03	This DTC determines if the O2 sensor voltage is not meeting the voltage criteria to enable closed loop fueling.	Closed loop fuel control O2 sensor Ready flag set to "Not Ready."  O2 sensor voltage must be > 650 millivolts or < 250 millivolts to set closed loop fuel O2 Ready flag. Once set to "Ready," the O2 sensor voltage cannot be > 250 millivolts and < 650 millivolts for > 10 seconds or the O2 Ready flag will be reset to "Not Ready."	<ul style="list-style-type: none"> <li>No TP Sensor, MAF, MAP, IAT, ECT, EVAP, Secondary Air, Injector DTC's</li> <li>No B1S1 or B2S1 O2 DTC's</li> <li>Engine Run Time ≥ 100 seconds</li> <li>ECT ≥ 70° C</li> <li>Engine Metal Overtemp = Not Active</li> <li>Traction Control = Not Active</li> <li>No default throttle action</li> <li>Not in Catalyst Protection Mode</li> <li>10 volts ≤ Ignition Voltage ≤ 18 volts</li> <li>500 ≤ Engine Speed ≤ 5000</li> <li>3 gps ≤ Mass Airflow ≤ 30 gps</li> <li>Not in Decel Fuel Cutoff Mode</li> <li>Not in Power Enrichment</li> <li>Predicted O2 temp ≥ 0°C</li> </ul> <p>All of the above met for 5 seconds.</p>	250 test failures in a 300 test sample  <u>Frequency:</u> Continuous 100ms loop	DTC Type B
O2 Sensor Circuit Range/Performance Bank 2 Sensor 2	P2A04	This DTC determines if the post catalyst O2 sensor is stuck in a normal voltage range and thereby can no longer be used for post oxygen sensor fuel control or for catalyst monitoring. The diagnostic includes a passive (stage 1) test and an intrusive (stage 2) test. The stage 2 increases or reduces delivered fuel to achieve the required rich or lean threshold.	Post catalyst O2 sensor cannot achieve voltage ≥ 751 millivolts and voltage ≤ 200 millivolts	<p><u>Common Enable Criteria</u></p> <ul style="list-style-type: none"> <li>No O2 circuit, heater, response or heater driver DTC's active</li> <li>No TP Sensor, ETC, MAF, ECT, MAP, IAT, EVAP, Secondary Air, Fuel Injector DTC's</li> <li>Engine Runtime ≥ 280 seconds</li> <li>Post catalyst O2s have a valid resistance learn</li> </ul> <p><u>Stage 2 Specific Enable Criteria:</u></p> <ul style="list-style-type: none"> <li>Stage 1 portion of test not passed</li> <li>No Fuel Trim or Misfire DTC's active</li> <li>Engine Runtime &gt; 281 seconds</li> <li>500 rpm ≤ Engine Speed ≤ 5000 rpm</li> <li>3 gps ≤ Airflow ≤ 50 gps</li> <li>5 kph ≤ Vehicle Speed ≤ 132 kph</li> </ul> <p>All of the above met for at least 2 seconds, and then:</p> <ul style="list-style-type: none"> <li>1.05 ≤ Short term fuel trim ≤ 0.95</li> <li>Fuel state = closed loop</li> <li>Drive state = decel</li> <li>EVAP diagnostic not in control of purge</li> </ul>	<p><u>Stage 1:</u> Runs until pass or fail reporting.</p> <p><u>Stage 2:</u> Up to 475 grams of accumulated airflow for each threshold</p> <p><u>Frequency:</u> Once per trip</p>	DTC Type B  4 Sensor Systems
Control Module Communication Bus Off  (Automatic transmission)	U0073	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state.	CAN device driver has reported that it has entered a bus-off state.		5 seconds  <u>Frequency:</u> Continuous 1 second loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
Lost Communication with TCM  (Automatic transmission)	U0101	Detects that CAN serial data communication has been lost with the TCM.	Lost communication with the TCM while the ignition switch is in the RUN power mode.		12 seconds  <u>Frequency:</u> Continuous 1 second loop	DTC Type B

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
------------------	------------	------------------------------	---	--	---------------------------	-----------------------

**TABLE - O2S Slow Response Bank 1 Sensor 1 (P0133), O2S Slow Response Bank 2 Sensor 1 (P0153)**  
Lean-Rich Ave

Seconds	Rich-Lean Ave																
	0.000	0.015	0.030	0.045	0.060	0.075	0.085	0.095	0.105	0.115	0.125	0.135	0.140	0.141	0.150	0.160	1.000
0.000	PASS	PASS	PASS	PASS	PASS	PASS	FAIL										
0.015	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL								
0.030	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL							
0.045	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
0.060	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
0.075	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
0.085	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
0.095	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL									
0.105	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL								
0.115	FAIL	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL							
0.125	FAIL	FAIL	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL						
0.135	FAIL	FAIL	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL						
0.140	FAIL	FAIL	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL						
0.141	FAIL	FAIL	FAIL	FAIL	PASS	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL						
0.150	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
0.160	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL
1.0	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL	FAIL

TABLE - IFRD weight factors	RPM																
	0	1500	1700	1790	1800	3100	3200	3300	3500	3700	4000	4200	4500	5000	5500	6500	8000
MAF residual weight (RPM)	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.9	0.9

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)										SECONDARY PARAMETERS AND ENABLE CONDITIONS					TIME LENGTH AND FREQUENCY			MIL ILLUMINATION TYPE	
MAP1 residual weight			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.9	0.9		
MAP2 residual weight			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
TPS residual weight			1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1		
		MAF g/s																				
			0	50	70	73	76	79	82	85	89	95	100	110	150	170	180	200	350			
MAF residual weight (MAF)			1	1	1	1	1	1	1	1	1	1	1	1	1	1	0.9	0.9	0.9			

MAP and MAF Delta Criterion based on TPS % for P0068 code

Throtte position %	5.000	10.000	15.000	20.000	25.000	30.000	35.000	40.000	100.000
Max MAP delta	26.812	33.210	28.565	26.197	24.854	21.853	100.000	100.000	100.000
Max MAF delta	16.762	21.395	20.522	22.716	30.465	37.660	255.000	255.000	255.000

P0116

Induction Air Temperature at Powerup Powertrain (VeEITI_T_InductAirCvrtedPwrUp)	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
The minimum temperature difference required to allow a gross failure of the ECT to bypass the engine block heater algorithm and promptly fail the diagnostic (KtECTD_T_HSC_FastFailTempDiff)	110	98	86	74	62	50	38	26	19	19	19	19	20	30	42	53	65

P0128

For IAT > 10C, Threshold = 75C

Coolant Temp at Begin Run Transition (SfECTI_T_EngCoolBRn)	-40	-28	-16	-4	8	20	32	44	56	68	80
Calculated minimum total air threshold as a function of Coolant Temp (KaECTD_m_EngTotAirGramsStartRun)	16553	15983	15162	14091	12769	11196	9372	7298	4974	2398	2398

07\_GRP13b LH2\_LC3.doc

SENSED PARAMETER	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA AND THRESHOLD VALUE(S)	SECONDARY PARAMETERS AND ENABLE CONDITIONS	TIME LENGTH AND FREQUENCY	MIL ILLUMINATION TYPE
------------------	------------	------------------------------	---	--	---------------------------	-----------------------

P0128

For  $-7C < IAT < 10C$ , Threshold = 75C

Coolant Temp at Begin Run Transition (SfECTI_T_EngCoolBRn)	-40	-28	-16	-4	8	20	32	44	56	68	80
Calculated minimum total air threshold as a function of Coolant Temp (KaECTD_m_EngTotAirGramsStartRun)	19560	18623	17465	16085	14485	12663	10621	8358	5873	3167	3168