

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Intake Camshaft Actuator Solenoid Circuit – Bank 1	P0010	Detects a VVT system error by monitoring the circuit for electrical integrity	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		System supply voltage is within limits Output driver is commanded on, Ignition switch is in crank or run position	> 11 Volts, and < 32 Volts	20 failures out of 25 samples 250 ms /sample, continuous	Trips 2 B Type
Intake Camshaft System Performance – Bank 1	P0011	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive	(Intake cam Bank 1)Cam Position Error > KtPHSD_phi_CamPosErrorLimlc1 Deg (see Supporting Table)	DTC's are NOT active: P0010 IntkCMP B1 Circuit IntakeCamSensorTFTKO CrankSensorTFTKO CrankIntakeCamCorrelationFA Engine is running VVT is enabled Desired camshaft position > 0 Power Take Off (PTO) not active	System Voltage > 11 Volts, and System Voltage < 32 Volts Both Desired & Measured cam positions cannot be < KtPHSD_phi_CamPosErrorLimlc1 or > than (25.0 - KtPHSD_phi_CamPosErrorLimlc1). Desired cam position cannot vary more than 3.0 Cam Deg for at least KtPHSD_t_StablePositionTime1c1 seconds (see Supporting Tables)	135 failures out of 150 samples 100 ms /sample	Trips 2 B Type
Exhaust Camshaft Actuator Solenoid Circuit – Bank 1	P0013	Detects a VVT system error by monitoring the circuit for electrical integrity	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		System supply voltage is within limits Output driver is commanded on, Ignition switch is in crank or run position	> 11 Volts, and < 32 Volts	20 failures out of 25 samples 250 ms /sample, continuous	Trips 2 B Type

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Exhaust Camshaft System Performance – Bank 1	P0014	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive	(Exhaust cam Bank 1)Cam Position Error > KtPHSD_phi_CamPosErrorLimEc1 Deg (see Supporting Table)	DTC's are NOT active: P0013 IntkCMP B1 Circuit ExhaustCamSensorTFTKO CrankSensorTFTKO CrankExhaustCamCorrelationFA Engine is running VVT is enabled Desired camshaft position > 0 Power Take Off (PTO) not active	System Voltage > 11 Volts, and System Voltage < 32 Volts Both Desired & Measured cam positions cannot be < KtPHSD_phi_CamPosErrorLimEc1 or > than (Exh25.0 - KtPHSD_phi_CamPosErrorLimEc1). Desired cam position cannot vary more than 3.0 Cam Deg for at least KtPHSD_t_StablePositionTimeEc1 seconds (see Supporting Tables)	135 failures out of 150 samples 100 ms /sample	Trips 2 B Type
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 1 Sensor A	P0016	Detects cam to crank misalignment by monitoring if cam sensor pulse for bank 1 sensor A occurs during the incorrect crank position	4 cam sensor pulses more than -9 crank degrees before or 12 crank degrees after nominal position in one cam revolution.		Crankshaft and camshaft position signals are synchronized Engine is Spinning Cam phaser is in "parked" position		2 failures out of 3 tests. A failed test is 4 failures out of 5 samples. There is a delay after the first failed test to allow the camshaft position to return to the park position. This time is defined by the table "Cam Correlation Oil Temperature Threshold".	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					No Active DTCs: Time since last execution of diagnostic	P0335, P0336 P0340, P0341 5VoltReferenceA_FA 5VoltReferenceB_FA < 1.0 seconds	One sample per cam rotation	
Crankshaft Position (CKP)-Camshaft Position (CMP) Correlation Bank 1 Sensor B	P0017	Detects cam to crank misalignment by monitoring if cam sensor pulse for bank 1 sensor B occurs during the incorrect crank position	4 cam sensor pulses more than -9 crank degrees before or 12 crank degrees after nominal position in one cam revolution.		Crankshaft and camshaft position signals are synchronized Engine is Spinning Cam phaser is in "parked" position No Active DTCs:	P0335, P0336 P0365, P0366	2 failures out of 3 tests. A failed test is 4 failures out of 5 samples. There is a delay after the first failed test to allow the camshaft position to return to the park position. This time is defined by the table "Cam Correlation Oil Temperature Threshold".	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Time since last execution of diagnostic	5VoltReferenceA_FA 5VoltReferenceB_FA < 1.0 seconds	One sample per cam rotation	
O2S Heater Control Circuit Bank 1 Sensor 1	P0030	This DTC checks the Heater Output Driver circuit for electrical integrity.	Voltage low during driver open state (indicates short-to-ground or open circuit) or voltage high during driver closed state (indicates short to voltage).		Ignition = Crank or Run Ignition Voltage Engine Speed	11.0 < Volts < 32.0 > 400 RPM	20 failures out of 25 samples 250 ms / sample Continuous	2 trips Type B
Turbo/Super Charger Bypass Valve Control Circuit	P0033	Detect Turbocharger Bypass Valve - Open Circuit	ECM detects that commanded and actual states of output driver do not match because the output is open circuit		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts <= 32.00 Volts >= 2.00 Volts <= 6.00 Volts	20 failures out of 100 samples 1 sample every 100ms	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Turbo/Super Charger Bypass Valve Control Circuit Low	P0034	Detect Turbocharger Bypass Valve - Shorted to Ground	ECM detects that commanded and actual states of output driver do not match because the output is shorted to ground		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts <= 32.00 Volts >= 2.00 Volts <= 6.00 Volts	20 failures out of 100 samples 1 sample every 100ms	Type B 2 trips
Turbo/Super Charger Bypass Valve Control Circuit High	P0035	Detect Turbocharger Bypass Valve - Shorted to Power	ECM detects that commanded and actual states of output driver do not match because the output is shorted to power		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts <= 32.00 Volts >= 2.00 Volts <= 6.00 Volts	20 failures out of 100 samples 1 sample every 100ms	Type B 2 trips
O2S Heater Control Circuit Bank 1 Sensor 2	P0036	This DTC checks the Heater Output Driver circuit for electrical integrity.	Voltage low during driver open state (indicates short-to-ground or open circuit) or voltage high during driver closed state (indicates short to voltage).		Ignition = Crank or Run Ignition Voltage Engine Speed	11.0 < Volts < 32.0 > 400 RPM	20 failures out of 25 samples 250 ms / sample Continuous	2 trips Type B
HO2S Heater Resistance Bank 1 Sensor 1	P0053	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	Heater Resistance	3.7 < Ω < 8.7	No Active DTC's Coolant – IAT Engine Soak Time Coolant Temp Ignition Voltage	ECT_Sensor_FA P2610 IAT_SensorFA < 8.0 °C > 28800 seconds -30.0 < °C < 45.0 < 32.0 volts	Once per valid cold start	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Engine Run time	< 0.00 seconds		
HO2S Heater Resistance Bank 1 Sensor 2	P0054	Detects an oxygen sensor heater having an incorrect or out of range resistance value.	Heater Resistance	$3.6 < \Omega < 10.3$	No Active DTC's Coolant – IAT Engine Soak Time Coolant Temp Ignition Voltage Engine Run time	ECT_Sensor_FA P2610 IAT_SensorFA < 8.0 °C > 28800 seconds > -30.0 < °C < 45.0 < 32.0 volts < 0.10 seconds	Once per valid cold start	2 trips Type B
MAP / MAF / Throttle Position Correlation	P0068	Detect when MAP and MAF do not match estimated engine airflow as established by the TPS	Difference between MAP and estimated MAP exceeds threshold (kPa), or P0651 (5 Volt Ref), or P0107 (MAP circuit low), or P0108 (MAP circuit high) have failed this key cycle, then MAP portion of diagnostic fails	Table, f(TPS). See supporting tables	Engine Speed	> 800 RPM Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	Continuously fail MAP and MAF portions of diagnostic for 0.1875 s Continuous in MAIN processor	Trips: 1
			Absolute difference between MAF and estimated MAF exceed threshold (grams/sec), or P0102 (MAF circuit low), or P0103 (MAF circuit hi) have failed this key cycle, or maximum MAF versus RPM (Table) is greater than or equal to maximum MAF versus battery voltage, then MAF portion of diagnostic fails	Table, f(TPS). See supporting tables				Type: A MIL: YES

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
				Table, f(RPM). See supporting tables Table, f(Volts). See supporting tables				
Internal Control Module SIDI High Pressure Pump min/max authority	P0089	This DTC Detects pump control windup to its max or min authority	High Pressure Fuel Pump Delivery Angle High Pressure Fuel Pump Delivery Angle	$\geq 132^\circ$ Or $\leq 0^\circ$	Battery Voltage Low Side Fuel Pressure Engine Run Time Barometric Pressure Inlet Air Temp Fuel Temp	$11 \leq \text{Volts} \leq 32$ $> 0.250 \text{ MPa}$ \geq KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Engine is not cranking ≥ 70.0 ≥ -10.0 $-10 \leq \text{Temp degC} \leq 100$	Windup High - 750 failures out of 938 samples Windup Low - 750 failures out of 938 Samples	2 trips Type B
					Additional Enable Conditions:			
						High Pressure Pump is enabled Estimate fuel rail pressure is valid Green Engine (In assembly plant) is not enabled		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTC's not active:	Not LowFuelConditionDiagnostic Low side Fuel Pump is on Injector Flow Test is not active Device control commanded pressure is false Device control pump ckt enabled on is false Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0 FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA Ethanol Composition Sensor FA PowertrainRelayFault FHPR_b_PumpCkt_FA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
High Pressure Pump Cntrl Solenoid Enable Low Side Open Circuit	P0090	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the high pressure fuel pump solenoid low side is open circuit		Engine Speed Battery Voltage	>= 50 RPM 11 <= volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A
High Pressure Pump Cntrl Solenoid Enable Low Side Short to Ground	P0091	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the high pressure fuel pump solenoid low side is short to ground		Engine Speed Battery Voltage	>= 50 RPM 11 <= volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A
High Pressure Pump Cntrl Solenoid Enable Low Side Short to Power P0092	P0092	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the high pressure fuel pump solenoid low side is short to power		Engine Speed Battery Voltage	>= 50 RPM 11 <= volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A
Intake Air Temperature Sensor 2 Circuit Performance	P0096	Detects an IAT2 sensor that has stuck in range by comparing to IAT and engine coolant temperature at startup	ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up ECT - Power Up IAT2) >= ABS(Power Up ECT - Power Up IAT)	> 20 deg C	Time between current ignition cycle and the last time the engine was running No Active DTCs:	> 28800 seconds ECT_Sensor_Ckt_FA IAT_SensorCircuitFA IAT2_SensorCircuitFA	Executes once at the beginning of each ignition cycle if enable conditions are met	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
Intake Air Temperature Sensor Circuit 2 Low (High Temperature)	P0097	Detects a continuous short to ground in the IAT 2 signal circuit or the IAT 2 sensor	Raw IAT 2 Input	< 57 Ohms (~150 deg C)	Engine Run Time	> 0.0 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B 2 trips	
Intake Air Temperature Sensor Circuit 2 High (Low Temperature)	P0098	Detects a continuous open circuit in the IAT 2 signal circuit or the IAT 2 sensor	Raw IAT 2 Input	> 162529 Ohms (~-60 deg C)	Engine Run Time	> 0.0 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B 2 trips	
High Pressure Start Diagnostic	P00C6	This DTC checks the high side fuel pressure during engine cranking	The ECM detects that the fuel pressure is not rising or has fallen beyond acceptable limits during engine cranking	Pressure Fall Test: High Side Fuel Rail Pressure <= Supporting Table KtFHPC_p_HPS_PressFallLoThresh Pressure Rise Test: High Side Fuel Pressure < Supporting Table KtFHPC_p_HighPressStart	Low side feed fuel pressure Engine Run Time >= 0 Run/Crank Voltage <= 0 Engine Coolant > 8 Volts Barometric Pressure -100 <= °C <= 80 Inlet Air Temp >= 70.0 >= -10.0 For each engine start, only 1 diagnostic is performed. The pressure rise test will run if High side fuel pressure is less than KtFHPC_p_HighPressStart, otherwise, the pressure fall diagnostic will run The pressure fall runs when the engine is cranking	Pressure Fall Test: Injected cylinder events >= Supporting Table KtFHPC_Cnt_HPS_PressFallLoThresh Pressure Rise Test: Time >= Supporting Table KtFHPC_t_HighPressStartTmout	2 trips Type B		
								Additional Enable Conditions:	
								High Pressure Pump is enabled	
Estimate fuel rail pressure is valid									
Green Engine (In assembly plant) is not enabled									

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTC's not active:	Not LowFuelConditionDiagnostic Low side Fuel Pump is on Injector Flow Test is not active Device control commanded pressure is false Device control pump ckt enabled on is false Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0 FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA Ethanol Composition Sensor FA PowertrainRelayFault FHPR_b_PumpCkt_FA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Intake Air Pressure Measurement System - Multiple Sensor Correlation	P00C7	Detects an inconsistency between pressure sensors in the induction system in which a particular sensor cannot be identified as the failed sensor	ABS(Manifold Pressure - Baro Pressure) AND ABS(Turbocharger Boost Pressure - Manifold Pressure) AND ABS(Turbocharger Boost Pressure - Baro Pressure) OR ABS(Manifold Pressure - Baro Pressure) AND ABS(Turbocharger Boost Pressure - Manifold Pressure) AND ABS(Turbocharger Boost Pressure - Baro Pressure) OR ABS(Manifold Pressure - Baro Pressure)	> 10.0 kPa <= 10.0 kPa <= 10.0 kPa <= 10.0 kPa <= 10.0 kPa > 10.0 kPa <= 10.0 kPa <= 10.0 kPa	Time between current ignition cycle and the last time the engine was running Engine is not rotating Manifold Pressure Manifold Pressure Baro Pressure Baro Pressure Turbocharger Boost Pressure Turbocharger Boost Pressure No Active DTCs: No Pending DTCs:	> 10.0 seconds >= 50.0 kPa <= 115.0 kPa >= 50.0 kPa <= 115.0 kPa >= 50.0 kPa <= 115.0 kPa EngModeNotRunTmErr MAP_SensorFA AAP_SnsrFA AAP2_SnsrFA MAP_SensorCircuitFP AAP_SnsrCktFP AAP2_SnsrCktFP	4 failures out of 5 samples 1 sample every 12.5 msec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			AND ABS(Turbocharger Boost Pressure - Manifold Pressure)	<= 10.0 kPa				
			AND ABS(Turbocharger Boost Pressure - Baro Pressure)	> 10.0 kPa				
			OR ABS(Manifold Pressure - Baro Pressure)	> 10.0 kPa				
			AND ABS(Turbocharger Boost Pressure - Manifold Pressure)	> 10.0 kPa				
			AND ABS(Turbocharger Boost Pressure - Baro Pressure)	> 10.0 kPa				
Fuel Press Regulator Solenoid Supply Voltage Control Circuit/Open	P00C8	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the Fuel Press Regulator Solenoid Supply Voltage Control Circuit/Open		Engine Speed Battery Voltage	>= 50 RPM 11 <= Volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Press Regulator Solenoid Supply Voltage Control Circuit Low	P00C9	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the Fuel Press Regulator Solenoid Supply Voltage Control short to ground		Engine Speed Battery Voltage	>= 50 RPM 11 <= Volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A
Fuel Press Regulator Solenoid Supply Voltage Control Circuit High	P00CA	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the Fuel Press Regulator Solenoid Supply Voltage Control short to power		Engine Speed Battery Voltage	>= 50 RPM 11 <= Volts <= 32 Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	1 trips Type A
Mass Air Flow System Performance	P0101	Determines if the MAF sensor is stuck within the normal operating range	See table "Turbocharger Intake Flow Rationality Diagnostic Failure Matrix" for combinations of model failures that can set this DTC. MAF model fails when ABS(Measured Flow – Modeled Air Flow) Filtered MAP1 model fails when ABS(Measured MAP – MAP Model 1) Filtered	> 20 grams/sec	Engine Speed Engine Speed Coolant Temp Coolant Temp Intake Air Temp Intake Air Temp Minimum total weight factor (all factors multiplied together)	>= 400 RPM <= 6000 RPM > -7 Deg C < 125 Deg C > -20 Deg C < 125 Deg C >= 0.00 Modeled Air Flow Error multiplied by MAF Residual Weight Factor based on RPM and MAF Residual Weight Factor Based on MAF Est	Continuous Calculation are performed every 12.5 msec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			MAP2 model fails when ABS(Measured MAP – MAP Model 2) Filtered	> 24.0 kPa > 22.0 kPa		MAP Model 1 Error multiplied by MAP1 Residual Weight Factor based on RPM MAP Model 2 Error multiplied by MAP2 Residual Weight Factor based on RPM		
			MAP3 model fails when ABS(Measured MAP – MAP Model 3) Filtered	> 22.0 kPa		MAP Model 3 Error multiplied by MAP Residual Weight Factor based on RPM		
			TIAP1 model fails when ABS(Measured TIAP – TIAP Model 1) Filtered	> 24.0 kPa		TIAP Model 1 Error multiplied by TIAP Residual Weight Factor based on RPM		
			TPS model fails when Filtered Throttle Model Error	> 200 kPa*(g/s)		Filtered Throttle Model Error multiplied by TPS Residual Weight Factor based on RPM		
			TIAP Correlation model fails when High Engine Air Flow is TRUE AND Measured TIAP - measured MAP offset as a function of engine speed		No Active DTCs:	See table "IFRD Residual Weighting Factors". MAP_SensorCircuitFA EGRValve_FP EGRValvePerformance_FA MAF_SensorCircuitFA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>See table "TIAP-MAP Correlation Offset"</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured Baro offset as a function of engine speed</p>	> 24.0 kPa		<p>CrankSensor_FA</p> <p>ECT_Sensor_FA</p> <p>ECT_Sensor_Ckt_FP</p> <p>IAT_SensorFA</p> <p>IAT_SensorCircuitFP</p> <p>IAT2_SensorFA</p> <p>IAT2_SensorCircuitFP</p> <p>TC_BoostPresSnsrCkt FA</p> <p>AmbientAirDefault</p>		
			<p>See table "TIAP-Baro Correlation Offset"</p> <p>TIAP Correlation is valid when</p> <p>High Engine Air Flow has been TRUE for a period of time</p>	> 24.0 kPa				
			<p>OR</p> <p>High Engine Air Flow has been TRUE for a period of time</p>	> 1.0 seconds				
			<p>High Engine Air Flow is TRUE when</p>	> 1.0 seconds				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
			Mass Air Flow AND Manifold Pressure AND Filtered Mass Air Flow - Mass Air Flow Low Engine Air Flow is TRUE when Mass Air Flow	> a threshold in gm/sec as a function of engine speed See table "TIAP-MAP Correlation Min Air Flow" > a threshold in kPa as a function of engine speed See table "TIAP-MAP Correlation Min MAP" < 3.0 gm/sec < a threshold in gm/sec as a function of engine speed See table "TIAP-Baro Correlation Max Air Flow"					

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			AND Manifold Pressure AND Mass Air Flow - Filtered Mass Air Flow	< a threshold in kPa as a function of engine speed See table "TIAP-Baro Correlation Max MAP" < 2.0 gm/sec				
Mass Air Flow Sensor Circuit Low Frequency	P0102	Detects a continuous short to low or a open in either the signal circuit or the MAF sensor	MAF Output	<= 750 Hertz (~ 0.92 gm/sec)	Engine Run Time Engine Speed Ignition Voltage Above criteria present for a period of time	> 1.0 seconds >= 300 RPM >= 11.0 Volts >= 1.0 seconds	200 failures out of 250 samples 1 sample every cylinder firing event	Type B 2 trips
Mass Air Flow Sensor Circuit High Frequency	P0103	Detects a high frequency output from the MAF sensor	MAF Output	>= 13350 Hertz (~ 542 gm/sec)	Engine Run Time Engine Speed Ignition Voltage Above criteria present for a period of time	> 1.0 seconds >= 300 RPM >= 11.0 Volts >= 1.0 seconds	200 failures out of 250 samples 1 sample every cylinder firing event	Type B 2 trips
Manifold Absolute Pressure Sensor Performance	P0106	Determines if the MAP sensor is stuck within the normal operating range	See table "Turbocharger Intake Flow Rationality Diagnostic Failure Matrix" for combinations of model failures that can set this DTC.		Engine Speed Engine Speed Coolant Temp Coolant Temp	>= 400 RPM <= 6000 RPM > -7 Deg C < 125 Deg C	Continuous Calculation are performed every 12.5 msec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Intake Air Temp Intake Air Temp Minimum total weight factor (all factors multiplied together)	> -20 Deg C < 125 Deg C		
			MAF model fails when			>= 0.00		
			ABS(Measured Flow – Modeled Air Flow) Filtered	> 20 grams/sec		Modeled Air Flow Error multiplied by MAF Residual Weight Factor based on RPM and MAF Residual Weight Factor Based on MAF Est		
			MAP1 model fails when					
			ABS(Measured MAP – MAP Model 1) Filtered	> 24.0 kPa		MAP Model 1 Error multiplied by MAP1 Residual Weight Factor based on RPM		
			MAP2 model fails when					
			ABS(Measured MAP – MAP Model 2) Filtered	> 22.0 kPa		MAP Model 2 Error multiplied by MAP2 Residual Weight Factor based on RPM		
			MAP3 model fails when					
			ABS(Measured MAP – MAP Model 3) Filtered	> 22.0 kPa		MAP Model 3 Error multiplied by MAP Residual Weight Factor based on RPM		
			TIAP1 model fails when			TIAP Model 1 Error multiplied by TIAP		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>ABS(Measured TIAP – TIAP Model 1) Filtered</p> <p>TPS model fails when</p> <p>Filtered Throttle Model Error</p> <p>TIAP Correlation model fails when</p> <p>High Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured MAP offset as a function of engine speed</p> <p>See table "TIAP-MAP Correlation Offset"</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured Baro offset as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Offset"</p>	<p>> 24.0 kPa</p> <p>> 200 kPa*(g/s)</p> <p>> 24.0 kPa</p> <p>> 24.0 kPa</p>	<p>No Active DTCs:</p>	<p>multiplied by TIAP Residual Weight Factor based on RPM</p> <p>Filtered Throttle Model Error multiplied by TPS Residual Weight Factor based on RPM</p> <p>See table "IFRD Residual Weighting Factors".</p> <p>MAP_SensorCircuitFA</p> <p>EGRValve_FP</p> <p>EGRValvePerformance_FA</p> <p>MAF_SensorCircuitFA</p> <p>CrankSensor_FA</p> <p>ECT_Sensor_FA</p> <p>ECT_Sensor_Ckt_FP</p> <p>IAT_SensorFA</p> <p>IAT_SensorCircuitFP</p> <p>IAT2_SensorFA</p> <p>IAT2_SensorCircuitFP</p> <p>TC_BoostPresSnsrCkt FA</p> <p>AmbientAirDefault</p>		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			TIAP Correlation is valid when High Engine Air Flow has been TRUE for a period of time OR High Engine Air Flow has been TRUE for a period of time High Engine Air Flow is TRUE when Mass Air Flow AND Manifold Pressure	> 1.0 seconds > 1.0 seconds > a threshold in gm/sec as a function of engine speed See table "TIAP-MAP Correlation Min Air Flow" > a threshold in kPa as a function of engine speed				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>AND</p> <p>Filtered Mass Air Flow - Mass Air Flow</p> <p>Low Engine Air Flow is TRUE when</p> <p>Mass Air Flow</p>	<p>See table "TIAP-MAP Correlation Min MAP"</p> <p>< 3.0 gm/sec</p> <p>< a threshold in gm/sec as a function of engine speed</p>				
			<p>AND</p> <p>Manifold Pressure</p>	<p>See table "TIAP-Baro Correlation Max Air Flow"</p> <p>< a threshold in kPa as a function of engine speed</p>				
			<p>AND</p> <p>Mass Air Flow - Filtered Mass Air Flow</p>	<p>See table "TIAP-Baro Correlation Max MAP"</p>				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p><u>Engine Not Rotating Case:</u></p> <p>Manifold Pressure OR Manifold Pressure</p>	<p>< 2.0 gm/sec</p> <p>< 50.0 kPa</p> <p>> 115.0 kPa</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Engine is not rotating</p> <p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>> 10.0 seconds</p> <p>EngModeNotRunTmErr MAP_SensorFA TC_BoostPresSnsrCktFA AAP2_SnsrFA MAP_SensorCircuitFP AAP_SnsrCktFP AAP2_SnsrCktFP</p>	<p>4 failures out of 5 samples</p> <p>1 sample every 12.5 msec</p>	
Manifold Absolute Pressure Sensor Circuit Low	P0107	Detects a continuous short to low or open in either the signal circuit or the MAP sensor.	MAP Voltage	< 9.0 % of 5 Volt Range (0.5 Volts = 5.8 kPa)	Continuous		<p>320 failures out of 400 samples</p> <p>1 sample every 12.5 msec</p>	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Manifold Absolute Pressure Sensor Circuit High	P0108	Detects an open sensor ground or continuous short to high in either the signal circuit or the MAP sensor.	MAP Voltage	> 78.0 % of 5 Volt Range (3.9 Volts = 299.0 kPa)	Continuous		320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Intake Air Temperature Sensor Circuit Performance	P0111	Detects an IAT sensor that has stuck in range by comparing to IAT2 and engine coolant temperature at startup	ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up ECT – Power Up IAT) > ABS(Power Up ECT – Power Up IAT2)	> 20 deg C	Time between current ignition cycle and the last time the engine was running No Active DTCs:	> 28800 seconds ECT_Sensor_Ckt_FA IAT_SensorCircuitFA IAT2_SensorCircuitFA	Executes once at the beginning of each ignition cycle if enable conditions are met	Type B 2 trips
Intake Air Temperature Sensor Circuit Low (High Temperature)	P0112	Detects a continuous short to ground in the IAT signal circuit or the IAT sensor	Raw IAT Input	< 58 Ohms (~150 deg C)	Engine Run Time	> 0.0 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B 2 trips
Intake Air Temperature Sensor Circuit High (Low Temperature)	P0113	Detects a continuous open circuit in the IAT signal circuit or the IAT sensor	Raw IAT Input	> 142438 Ohms (~-60 deg C)	Engine Run Time	> 0.0 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B 2 trips
Intake Air Temperature Sensor Intermittent In-Range	P0114	Detects a noisy or erratic IAT signal circuit or IAT sensor	Change in IAT reading between consecutive 100 millisecond samples	> 10 DegC	Continuous		20 failures out of 200 samples 1 sample every 100 msec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Change in IAT is multiplied by IAT Intermittent Weight Factor based on Filtered IAT. Filtered IAT = 0.10 * Current IAT + 0.90 * Filtered IAT from 100 milliseconds before					
Engine Coolant Temperature (ECT) Sensor Performance	P0116	This DTC detects ECT temp sensor stuck in mid range.	A failure will be reported if any of the following occur: 1) ECT at power up > IAT at power up by an IAT based table lookup value after a minimum 25200 second soak (fast fail). 2) ECT at power up > IAT at power up by 15.8 C after a minimum 25200 second soak and a block heater has not been detected.	See "P0116: Fail if power up ECT exceeds IAT by these values" in the Supporting tables section	No Active DTC's Non-volatile memory initialization Test complete this trip Test aborted this trip LowFuelCondition Diag	VehicleSpeedSensor_F A IAT_SensorFA ECT_Sensor_Ckt_FA IgnitionOffTimeValid TimeSinceEngineRunningValid = Not occurred = False = False IAT ≥ -7 °C = False	1 failure 500 msec/ sample Once per valid cold start	2 trips Type B
						Block Heater detection is enabled when either of the following occurs:		
						1) ECT at power up > IAT at power up by > 15.8 °C		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			3) ECT at power up > IAT at power up by 15.8 C after a minimum 25200 seconds soak and the time spent cranking the engine without starting is greater than 10.0 seconds with the LowFuelConditionDiag	= False	2) Cranking time Block Heater is detected and diagnostic is aborted when 1) or 2) occurs. Diagnostic is aborted when 3) or 4) occurs: 1a) Vehicle drive time 1b) Vehicle speed 1c) Additional Vehicle drive time is provided to 1a when Vehicle speed is below 1b as follows: 1d) IAT drops from power up IAT 2a) ECT drops from power up ECT 2b) Engine run time 3) Engine run time with vehicle speed below 1b 4) Minimum IAT during test	< 10.0 Seconds > 400 Seconds with > 14.9 MPH 0.50 times the seconds with vehicle speed below 1b ≥ 5.3 °C > 5 °C Within > 30 Seconds > 1800 Seconds ≤ -7 °C		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Engine Coolant Temp Sensor Circuit Low	P0117	Circuit Continuity This DTC detects a short to ground in the ECT signal circuit or the ECT sensor.	ECT Resistance (@ 150°C)	< 46 Ohms			5 failures out of 6 samples 1 sec/ sample Continuous	2 trips Type B
Engine Coolant Temp Sensor Circuit High	P0118	Circuit Continuity This DTC detects a short to high or open in the ECT signal circuit or the ECT sensor.	ECT Resistance (@ -60°C)	> 419000 Ohms	Engine run time	> 10.0 seconds	5 failures out of 6 samples 1 sec/ sample Continuous	2 trips Type B
					Or IAT min	≥ -7.0 °C		
Engine Coolant Temperature (ECT) Sensor Circuit Intermittent	P0119	Circuit Continuity This DTC detects large step changes in the ECT signal circuit or the ECT sensor. Allowable high and low limits are calculated for the next sample based on the previous sample.	ECT temperature step change: 1) positive step change is greater than high limit OR 2) negative step change is lower than low limit.		No Active DTC's	P0117 P0118	3 failures out of 4 samples 1 sec/ sample Continuous	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			TIAP1 model fails when ABS(Measured TIAP – TIAP Model 1) Filtered TPS model fails when Filtered Throttle Model Error TIAP Correlation model fails when High Engine Air Flow is TRUE AND Measured TIAP - measured MAP offset as a function of engine speed See table "TIAP-MAP Correlation Offset" OR Low Engine Air Flow is TRUE AND Measured TIAP - measured Baro offset as a function of engine speed	> 24.0 kPa > 200 kPa*(g/s) > 24.0 kPa	No Active DTCs:	TIAP Model 1 Error multiplied by TIAP Residual Weight Factor based on RPM Filtered Throttle Model Error multiplied by TPS Residual Weight Factor based on RPM See table "IFRD Residual Weighting Factors". MAP_SensorCircuitFA EGRValve_FP EGRValvePerformance_FA MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA ECT_Sensor_Ckt_FP IAT_SensorFA IAT_SensorCircuitFP IAT2_SensorFA IAT2_SensorCircuitFP TC_BoostPresSnsrCkt FA AmbientAirDefault		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>See table "TIAP-Baro Correlation Offset"</p> <p>TIAP Correlation is valid when</p> <p>High Engine Air Flow has been TRUE for a period of time</p> <p>OR</p> <p>High Engine Air Flow has been TRUE for a period of time</p> <p>High Engine Air Flow is TRUE when</p> <p>Mass Air Flow</p> <p>> a threshold in gm/sec as a function of engine speed</p> <p>See table "TIAP-MAP Correlation Min Air Flow"</p> <p>AND</p> <p>Manifold Pressure</p>	<p>> 24.0 kPa</p> <p>> 1.0 seconds</p> <p>> 1.0 seconds</p>				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>AND</p> <p>Filtered Mass Air Flow - Mass Air Flow</p> <p>Low Engine Air Flow is TRUE when</p> <p>Mass Air Flow</p> <p>AND</p> <p>Manifold Pressure</p>	<p>> a threshold in kPa as a function of engine speed</p> <p>See table "TIAP-MAP Correlation Min MAP"</p> <p>< 3.0 gm/sec</p> <p>< a threshold in gm/sec as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Max Air Flow"</p> <p>< a threshold in kPa as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Max MAP"</p>				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			AND Mass Air Flow - Filtered Mass Air Flow	< 2.0 gm/sec				
TPS1 Circuit Low	P0122	Detects a continuous or intermittent short or open in TPS1 circuit	TPS1 Voltage <	0.325		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No 5V reference error or fault for # 4 5V reference circuit (P06A3)	79/159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Trips: 1
								Type: A
								MIL: YES
TPS1 Circuit High	P0123	Detects a continuous or intermittent short or open in TPS1 circuit	TPS1 Voltage >	4.75		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No 5V reference error or fault for # 4 5V reference circuit (P06A3)	79/159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Trips: 1
								Type: A
								MIL: YES
Engine Coolant Temperature Below Stat Regulating Temperature	P0128	This DTC detects if the engine coolant temperature rises too slowly due to an ECT or Cooling system fault.	Total energy transferred to the engine cooling system is greater than the predicted energy before:	See "P0128: Maximum Total Energy transferred to Cooling System for IAT and Start-up ECT conditions" in the Supporting tables section.	No Active DTC's	MAP_SensorFA MAF_SensorFA TPS_Performance_FA TPS_FA TPS_ThrottleAuthority Defaulted	30 failures to set DTC. 1 sec/ sample	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p><u>Range #1 (Primary)</u></p> <p>ECT reaches 69.0 °C when IAT min is < 52.0°C and ≥ 10.0°C.</p>			<p>IAT_SensorFA</p> <p>ECT_Sensor_Ckt_FA</p> <p>ECT_Sensor_Perf_FA</p> <p>VehicleSpeedSensor_FA</p> <p>EngineTorqueInaccuracy</p>	Once per ignition key cycle	
			<p><u>Range #2 (Alternate)</u></p> <p>ECT reaches 55.0 °C when IAT min is < 10.0°C and ≥ -7.0°C.</p>		<p>Engine not run time ≥ 1800 seconds</p> <p>Engine run time ≥ 120 seconds</p> <p>Fuel Condition Ethanol ≤ 87%</p>			
					<p><u>Range #1 (Primary) Test</u></p> <p>ECT at start run ≤ 64.0 °C</p> <p>Average Cooling System Energy ≥ 5.0 kW</p> <p>Vehicle Speed > 5 mph for at least 0.9 miles</p>			
					<p><u>Range #2 (Alternate) Test</u></p> <p>ECT at start run ≤ 50.0 °C</p> <p>Average Cooling System Energy ≥ 5.0 kW</p> <p>Vehicle Speed > 5 mph for at least 0.9 miles</p>			
					<p>Cooling System Energy Adjustments</p> <p>1) Max. cooling system power when accumulating energy</p>			
						30.0 kW		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					2) When Cooling system power is < 8.0 kW then it is set to 3) With Decel Fuel Cut Off active, Cooling System energy is reduced by multiplying actual power by 4) With Hybrid Engine Off Active, Cooling System Energy is reduced by Diagnostic will restart (using the lower value) if ECT drops	0.0 kW 0.20 times 1.00 kW each second ≥ 5.0°C below previous minimum ECT		
O2S Circuit Low Voltage Bank 1 Sensor 1	P0131	This DTC determines if the O2 sensor circuit is shorted to low.	Oxygen Sensor Signal	< 50 mVolts	No Active DTC's	TPS_ThrottleAuthority Defaulted MAP_SensorFA AIR System FA Ethanol Composition Sensor FA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA	300 failures out of 375 samples Frequency: Continuous in 100 milli - second loop	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
					EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsrCkt_FA FuelInjectorCircuit_FA AIR intrusive test = Not active Fuel intrusive test = Not active Idle intrusive test = Not active EGR intrusive test = Not active System Voltage 10.0 < Volts < 32.0 EGR Device Control = Not active Idle Device Control = Not active Fuel Device Control = Not active AIR Device Control = Not active Low Fuel Condition Diag = False Equivalence Ratio 0.9912 < ratio < 1.0400 Air Per Cylinder 20 < mgram < 1000 Fuel Control State = Closed Loop Closed Loop Active = TRUE All Fuel Injectors for active Cylinders Enabled (On) Fuel Condition Ethanol ≤ 87% Fuel State DFCO not active				
					All of the above met for	> 5.0 seconds			
O2S Circuit High Voltage Bank 1 Sensor 1	P0132	This DTC determines if the O2 sensor circuit is shorted to high.	Oxygen Sensor Signal	> 1050 mvolts	Open Test Criteria No Active DTC's	TPS_ThrottleAuthority Defaulted MAF_SensorFA	100 failures out of 125 samples	2 trips Type B	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					EthanolCompositionSensor_FA System Voltage AFM Status Heater Warm-up delay Engine Run Time Engine Run Accum Fuel Condition No Active DTC's	EthanolCompositionSensor_FA 10.0 < Volts < 32.0 = All Cylinders active = Complete > 5 seconds > 150 seconds ≤ 87 % Ethanol MAP_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR System FA = False ≤ 87 % Ethanol > 40.0 seconds when engine soak time > 28800 seconds > 40.0 seconds when engine soak time ≤ 28800 seconds 0.9912 ≤ ratio ≤ 1.0400 20.0 ≤ mgram ≤ 1200.0 not = Power Enrichment	Frequency: Continuous in 100 milli - second loop	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					All of the above met for > 5.0 seconds			
O2S Slow Response Bank 1 Sensor 1	P0133	This DTC determines if the O2 sensor response time is degraded.	The average response time is calculated over the test time, and compared to the threshold. Refer to "P0133 - O2S Slow Response Bank 1 Sensor 1" Pass/Fail Threshold table in the Supporting Tables tab.		No Active DTC's	TPS_ThrottleAuthority Defaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR System FA EthanolCompositionSensor_FA EngineMisfireDetected_FA P0131 P0132 P0134 System Voltage 10.0 < Volts < 32.0 EGR Device Control = Not active Idle Device Control = Not active Fuel Device Control = Not active AIR Device Control = Not active Low Fuel Condition Diag = False	Sample time is 60 seconds Frequency: Once per trip	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						= Not Valid. See definition of Green Sensor Delay Criteria (B1S1) in Supporting Tables tab. Green O2S Condition O2 Heater on for ≥ 40 seconds Learned Htr resistance = Valid Engine Coolant > 69 °C IAT > -40 °C Engine run Accum > 60 seconds Time since any AFM status change > 2.0 seconds Time since Purge On to Off change > 0.0 seconds Time since Purge Off to On change > 1.5 seconds Purge duty cycle ≥ 0 % duty cycle $10 \leq$ grams per second ≤ 50 Engine airflow Engine speed $1000 \leq$ RPM ≤ 3500 Fuel < 87 % Ethanol Baro > 70 kpa Air Per Cylinder ≥ 100 mGrams Low Fuel Condition Diag = False Fuel Control State = Closed Loop Closed Loop Active = TRUE LTM fuel cell = Enabled Transient Fuel Mass ≤ 100.0 mgrams Baro = Not Defaulted not = Power Fuel Control State Enrichment Fuel State DFCO not active Commanded Proportional Gain ≥ 0.0 % All of the above met for > 3.0 seconds		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
O2S Circuit Insufficient Activity Bank 1 Sensor 1	P0134	This DTC determines if the O2 sensor circuit is open.	Oxygen Sensor Signal	> 1700 mvolts	No Active DTC's	TPS_ThrottleAuthority Defaulted MAF_SensorFA EthanolCompositionSensor_FA System Voltage = 10.0 < Volts < 32.0 AFM Status = All Cylinders active Heater Warm-up delay = Complete Engine Run Time > 5 seconds Engine Run Accum > 150 seconds Fuel ≤ 87 % Ethanol	100 failures out of 125 samples. Frequency: Continuous 100msec loop	2 trips Type B
O2S Heater Performance Bank 1 Sensor 1	P0135	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	Heater Current	0.3 < Amps < 2.5	No Active DTC's	ECT_Sensor_FA System Voltage = 10.0 < Volts < 32.0 Heater Warm-up delay = Complete O2S Heater device control B1S1 O2S Heater Duty Cycle = Not active > zero	8 failures out of 10 samples Frequency: 2 tests per trip 30 seconds delay between tests and 1 second execution rate	2 trips Type B
					<u>All of the above met for</u>	> 120 seconds		
O2S Circuit Low Voltage Bank 1 Sensor 2	P0137	This DTC determines if the O2 sensor circuit is shorted to low.	Oxygen Sensor Signal	< 50 mvolts	No Active DTC's	TPS_ThrottleAuthority Defaulted MAP_SensorFA AIR System FA Ethanol Composition Sensor FA EvapPurgeSolenoidCircuit_FA	350 failures out of 437 samples Frequency: Continuous in 100 milli - second loop	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR intrusive test = Not active Fuel intrusive test = Not active Idle intrusive test = Not active EGR intrusive test = Not active System Voltage 10.0 < Volts < 32.0 EGR Device Control = Not active Idle Device Control = Not active Fuel Device Control = Not active AIR Device Control = Not active Low Fuel Condition Diag = False Equivalence Ratio 0.9912 ≤ ratio ≤ 1.0400 Air Per Cylinder 20 ≤ mgrams ≤ 1000 Fuel Control State = Closed Loop Closed Loop Active = TRUE All Fuel Injectors for active Cylinders Enabled (On) Fuel Condition Ethanol ≤ 87% Fuel State DFCO not active			
					All of the above met for	> 5.0 seconds		
O2S Circuit High Voltage Bank 1 Sensor 2	P0138	This DTC determines if the O2 sensor circuit is shorted to high.	Oxygen Sensor Signal	> 1050 mvolts	Open Test Criteria No Active DTC's	TPS_ThrottleAuthority Defaulted MAF_SensorFA	100 failures out of 125 samples	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					EthanolCompositionSensor_FA System Voltage AFM Status Heater Warm-up delay Engine Run Time Fuel Condition No Active DTC's	10.0 < Volts < 32.0 = All Cylinders active = Complete > 5 seconds ≤ 87 % Ethanol	Frequency: Continuous in 100 milli - second loop	
					MAP_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR System FA Low Fuel Condition Diag Fuel Condition Initial delay after Open Test Criteria met (cold start condition) Initial delay after Open Test Criteria met (not cold start condition) Equivalence Ratio Air Per Cylinder Fuel Control State	= False ≤ 87 % Ethanol > 40.0 seconds when engine soak time > 28800 seconds > 40.0 seconds when engine soak time ≤ 28800 seconds 0.9912 ≤ ratio ≤ 1.0400 20 ≤ mgrams ≤ 1200 not = Power Enrichment		
					<u>All of the above met for</u>	> 5.0 seconds		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTC's Passed	P013E (and P014A if applicable)		
					After above conditions are met: DFCO mode is continued (wo driver initiated pedal input).			
O2 Sensor Slow Response Lean to Rich Bank 1 Sensor 2	P013B	This DTC determines if the post catalyst O2 sensor has Slow Response in a predefined Lean to Rich voltages range during Lean to Rich transition. The diagnostic is an intrusive test which increases the delivered A/F ratio to achieve the required rich threshold.	The EWMA of the Post O2 sensor normalized integral value OR The Accumulated mass air flow monitored during the Slow Response Test (between the upper and lower voltage thresholds)	> 8.0 units > 148 grams (lower threshold is 350 mvolts and upper threshold is 600 mvolts)	No Active DTC's	TPS_ThrottleAuthority Defaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA EthanolCompositionSensor_FA P013A, P013E, P013F, P2270 or P2271	Frequency: Once per trip Note: if NaPOPD_b_ResetFastRespFunc= FALSE for the given Fuel Bank OR NaPOPD_b_RapidResponseActive = TRUE, multiple tests per trip are allowed.	1 trips Type A EWMA
					B1S2 Failed this key cycle	System Voltage 10.0 < Volts < 32.0 Learned heater resistance = Valid ICAT MAT Burnoff delay = Not Valid = Not Valid, See definition of Green Sensor Delay Criteria (B1S2) in Supporting Tables tab.		
					Green O2S Condition			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Low Fuel Condition Diag Post fuel cell DTC's Passed	= False = enabled P2270 (and P2272 if applicable) P013E (and P014A if applicable) P013A (and P013C if applicable) P2271 (and P2273 if applicable) P013F (and P014B if applicable)		
					After above conditions are met: Fuel Enrich mode continued.			
O2 Sensor Delayed Response Rich to Lean Bank 1 Sensor 2	P013E	This DTC determines if the post catalyst O2 sensor has an initial delayed response to an A/F change from Rich to Lean. The diagnostic is an intrusive test which runs in a DFCO mode to achieve the required response.	Post O2 sensor voltage AND The Accumulated mass air flow monitored during the Delayed Response Test	> 450 mvolts > 26 grams	No Active DTC's	TPS_ThrottleAuthority Defaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA EthanolCompositionSensor_FA	Frequency: Once per trip Note: if NaPOPD_b_Reset FastRespFunc= FALSE for the given Fuel Bank OR NaPOPD_b_Rapid ResponseActive = TRUE, multiple tests per trip are allowed.	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					B1S2 Failed this key cycle System Voltage Learned heater resistance ICAT MAT Burnoff delay Green O2S Condition Low Fuel Condition Diag Post fuel cell DTC's Passed	P013A, P013B, P013F, P2270 or P2271 10.0 < Volts < 32.0 = Valid = Not Valid = Not Valid, See definition of Green Sensor Delay Criteria (B1S2) in Supporting Tables tab. = False = enabled P2270 (and P2272 if applicable)		
					After above conditions are met: DFCO mode entered (wo driver initiated pedal input).			
O2 Sensor Delayed Response Lean to Rich Bank 1 Sensor 2	P013F	This DTC determines if the post catalyst O2 sensor has an initial delayed response to an A/F change from Lean to Rich. The diagnostic is an intrusive test which increases the delivered A/F ratio to achieve the required rich threshold.	Post O2 sensor voltage AND The Accumulated mass air flow monitored during the Delayed Response Test	< 350 mvolts > 94 grams	No Active DTC's	TPS_ThrottleAuthority Defaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA	Frequency: Once per trip Note: if NaPOPD_b_Reset FastRespFunc= FALSE for the given Fuel Bank OR NaPOPD_b_Rapid ResponseActive = TRUE, multiple tests per trip are allowed	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					B1S2 Failed this key cycle System Voltage Learned heater resistance ICAT MAT Burnoff delay Green O2S Condition Low Fuel Condition Diag Post fuel cell DTC's Passed	EngineMisfireDetected_FA EthanolCompositionSensor_FA P013A, P013B, P013E, P2270 or P2271 10.0 < Volts < 32.0 = Valid = Not Valid = Not Valid, See definition of Green Sensor Delay Criteria (B1S2) in Supporting Tables tab. = False = enabled P2270 (and P2272 if applicable) P013E (and P014A if applicable) P013A (and P013C if applicable) P2271 (and P2273 if applicable)		
O2S Circuit Insufficient Activity Bank 1 Sensor 2	P0140	This DTC determines if the O2 sensor circuit is open.	Oxygen Sensor Signal	> 1700 mvolts	No Active DTC's	After above conditions are met: Fuel Enrich mode entered. TPS_ThrottleAuthority Defaulted MAF_SensorFA	100 failures out of 125 samples.	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						EthanolCompositionSensor_FA System Voltage = 10.0 <Volts < 32.0 AFM Status = All Cylinders active Heater Warm-up delay = Complete Engine Run Time > 5 seconds Engine Run Accum Fuel > 150 seconds ≤ 87 % Ethanol	Frequency: Continuous 100msec loop	
O2S Heater Performance Bank 1 Sensor 2	P0141	This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit.	Heater Current	0.3 > amps > 2.5	No Active DTC's System Voltage Heater Warm-up delay O2S Heater device control B1S1 O2S Heater Duty Cycle <u>All of the above met for</u> Time	ECT_Sensor_FA 10.0 < Volts < 32.0 = Complete = Not active > zero > 120 seconds	8 failures out of 10 samples Frequency: 2 tests per trip 30 seconds delay between tests and 1 second execution rate.	2 trips Type B
Fuel System Too Lean Bank 1	P0171	Determines if the fuel control system is in a lean condition, based on the filtered long-term fuel trim.	The filtered long-term fuel trim metric	>= 1.295	Engine speed BARO Coolant Temp MAP Inlet Air Temp MAF Fuel Level Long Term Fuel Trim data accumulation:	450 <rpm< 6500 > 70 kPa -20 <°C< 150 10 <kPa< 255 -20 <°C< 150 1.0 <g/s< 512.0 > 10 % or if fuel sender is faulty > 40.0 seconds of data must accumulate on	Frequency: 100 ms Continuous Loop Development data indicates that the Fuel Adjustment System Diagnostic (FASD) is typically enabled during 62% of the EPAIII drive cycle. This is also typical of real-	2 Trip(s) Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						each trip, with at least 30.0 seconds of data in the current fuel trim cell before a pass or fail decision can be made.	world driving, however values will vary (higher or lower) based on the actual conditions present during the drive cycle.	
					fuel trim diagnosed during decels? No			
					Long-Term Fuel Trim Cell Usage			
					Sometimes, certain Long-Term Fuel Trim Cells are not utilized for control or diagnosis. Please see "Supporting Tables" Tab for a list of cells utilized for diagnosis.			
					Fuel Control Status			
					Closed Loop	Enabled		
					Long Term FT	Enabled		
					Please see "Closed Loop Enable Criteria" and "Long Term FT Enable Criteria" in Supporting Tables.			
					Fuel Consumed	> 0.0 liters of fuel consumed after a fuel fill event		
					EGR Flow Diag. Intrusive Test Not Active			
					Catalyst Monitor Intrusive Test Not Active			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Post O2 Diag. Intrusive Test Not Active Device Control Not Active EVAP Diag. "tank pull down" Not Active			
					No active DTCs:			
					IAC_SystemRPM_FA MAP_SensorFA MAF_SensorFA MAF_SensorTFTKO AIR System FA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSensorCircuit_FA Ethanol Composition Sensor FA FuelInjectorCircuit_FA EngineMisfireDetected_FA EGRValvePerformance_FA EGRValveCircuit_FA MAP_EngineVacuumStatus AmbientAirDefault O2S_Bank_1_Sensor_1_FA			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel System Too Rich Bank 1	P0172	<p>Determines if the fuel control system is in a rich condition, based on the filtered long-term fuel trim metric.</p> <p>There are two methods to determine a Rich fault. They are Passive and Intrusive. The Intrusive test is described below:</p>	Passive Test:			Secondary Parameters and Enable Conditions are identical to those for P0171, with the exception that fuel level is not considered.	Frequency: 100 ms Continuous Loop	2 Trip(s) Type B
			The filtered Non-Purge Long Term Fuel Trim metric	<= 0.705 (a Passive Test decision cannot be made when Purge is enabled)				
			Intrusive Test:					
			The filtered Purge Long Term Fuel Trim metric	<= 0.710				
			AND					
		The filtered Non-Purge Long Term Fuel Trim metric	<= 0.705 for 3 out of 5 intrusive segments					
		<p>Intrusive Test: When the filtered Purge Long Term Fuel Trim metric is <= 0.710, purge is ramped off to determine if excess purge vapor is the cause of the rich condition. If the filtered Purge Long Term Fuel Trim metric > 0.710, the test passes without checking the filtered Non-Purge Long Term Fuel Trim metric.</p> <p>Performing intrusive tests too frequently may also affect EVAP and EPAIII emissions, and the execution frequency of other diagnostics.</p>	<p>Segment Def'n: Segments can last up to 42 seconds and are separated by the lesser of 10 seconds of purge-on time or enough time to purge 11 grams of vapor.</p> <p>A maximum of 5 completed segments or 15 attempts are allowed for each intrusive test.</p> <p>After an intrusive test report is completed, another intrusive test cannot occur for 300 seconds to allow sufficient time to purge excess vapors from the canister. During this period, fuel trim will pass if the filtered Purge-on Long Term fuel trim > Purge Rich Limit Table for at least 120 seconds, indicating that the canister has been purged.</p>					

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Composition Sensor Circuit Low	P0178	Detects Out of Range Low Frequency Signal	Flex Fuel Sensor Output Frequency	< 45 Hertz	Powertrain Relay	> 11.0 Volts < 32.0 Volts	50 failures out of 63 samples 100 ms loop Continuous	2 trip(s) Type B
Fuel Composition Sensor Circuit High	P0179	Detects Out of Range High Frequency Signal	Flex Fuel Sensor Output Frequency	> 155 Hertz <= 185 Hertz	Powertrain Relay	> 11.0 Volts < 32.0 Volts	50 failures out of 63 samples 100 ms loop Continuous	2 trip(s) Type B
SIDI High Pressure Sensor Performance	P0191	This DTC detects a skewed fuel rail sensor via a comparison of measured pressure and commanded/modeled pressure	Idle test (Low Side Fuel Pressure - High Side Fuel Pressure)	Enabled ≤ -0.600 MPa OR ≥ 0.300 MPa	Vehicle Speed Pedal Position = 0 for Battery Voltage Low Pressure Fuel Pump Pressure Engine Run Time	Enabled when a code clear is not active or not exiting device control Engine is not cranking ≤ 3.11 MPH 200 Counts (12.5ms per count) 11 ≤ Volts ≤ 32 ≥ 0.250 MPa ≥ KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Delay counts after pump is turned off Engine is not cranking ≥ KtFHPD_Cnt_SnsPrfIdlePumpOffDly(see supporting tables)	Idle Test ≥ 240 counts (12.5ms per count) KtFHPD_Cnt_SnsPrfIdlePumpOffDly runs in 12.5 ms loop	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>High Drive Test (Relief Pressure - Measured high Pressure)</p>	<p>Enabled ≤ -4.70 MPa</p>	<p>Engine Speed Desired High Side Pressure Vehicle Speed Battery Voltage Low Pressure Fuel Pump Pressure Engine Run Time</p>	<p>1000 ≤ RPM ≤ 3000 3 ≤ MPa ≤ 6 ≥ 18.64 MPH 11 ≤ Volts ≤ 32 ≥ 0.250 MPa ≥ KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Engine is not cranking</p>	<p>High Drive Test ≥ 160 counts (12.5ms per count)</p>	
			<p>Low Drive Test (Commanded high Pressure - Measured high Pressure) AND Modeled Injection Pressure</p>	<p>Enabled ≥ 1.567 MPa ≥ 1.57 MPa</p>	<p>Engine Speed Desired High Side Pressure Vehicle Speed Battery Voltage Low Pressure Fuel Pump Pressure Engine Run Time</p>	<p>1000 ≤ RPM ≤ 3000 3.00 ≤ MPa ≤ 6.00 ≥ 18.64 MPH 11 ≤ Volts ≤ 32 ≥ 0.250 MPa ≥ KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Engine is not cranking</p>	<p>LoDrive Test ≥ 240 counts (12.5ms per count)</p>	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>Sensor Stuck Test Measured High Pressure (max - min)</p>	<p>Enabled ≤ 0.100 MPa</p>	<p>Engine Speed Vehicle Speed</p>	<p>≥ 2000 ≥ 18.64 MPH</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>Engine is not cranking</p>	<p>Stuck Test Engine Run Time ≥ KtFHPD_t_PumpCntrlEngRunThrsH(See Supporting Tables) or Accumulating engine crank time ≥ KtFHPD_t_SnsPrfStuckCrankTmout(See Supporting Tables)</p>	
					<p>Additional Enable Conditions:</p> <p>High Pressure Pump is enabled</p> <p>Barometric Pressure ≥ 70.0</p> <p>Inlet Air Temp ≥ -10.0</p> <p>Fuel Temp -10 ≤ Temp degC ≤ 100</p> <p>Estimate fuel rail pressure is valid</p> <p>Green Engine (In assembly plant) is not enabled</p> <p>Not LowFuelConditionDiagnostic</p> <p>Low side Fuel Pump is on</p> <p>Injector Flow Test is not active</p> <p>Device control commanded pressure is false</p> <p>Device control pump ckt enabled on is false</p>			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTC's not Active	Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0) Clutch Disengaged (See Supporting Tables) or vehicle has automatic transmission All cylinder are fuel enabled FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA FHPR_b_PumpCkt_FA Ethanol Composition Sensor FA PowertrainRelayFault FuelInjectorCircuit_FA FuelInjectorCircuit_TFTKO IgnitionOutputDriver_FA EngineMisfireDetected_FA MAF_SensorFA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						MAP_SensorFA AcceleratorPedalFailure TPS_FA VehicleSpeedSensor_FA IAC_SystemRPM_FA		
High Pressure Sensor Out of Range Low	P0192	This DTC checks the circuit for electrical integrity during operation.	High Pressure Fuel Sensor	$\leq 4\%$ of 5Vref	Battery Voltage	11 \leq Volts \leq 32 Engine Running	Both Run Continuously Engine Synchronouse Mode 800 failures out of 1000 samples Time Based Mode 400 failures out of 500 samples 6.25 ms Sample Continuous	1 trips Type A
High Pressure Sensor Out of Range High	P0193	This DTC checks the circuit for electrical integrity during operation.	High Pressure Fuel Sensor	$\geq 96\%$ of 5Vref	Battery Voltage	11 \leq Volts \leq 32 Engine Running	Both Run Continuously Engine Synchronouse Mode 800 failures out of 1000 samples Time Based Mode 400 failures out of 500 samples 6.25 ms Sample Continuous	1 trips Type A
Injector 1 Open Circuit	P0201	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector 1 has determined to be an open circuit		Battery Voltage Engine Run Time	11 \leq Volts \leq 32 ≥ 5 Sec	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Injector 2 Open Circuit	P0202	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector 2 has determined to be an open circuit		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 3 Open Circuit	P0203	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector has determined to be an open circuit		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 4 Open Circuit	P0204	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector has determined to be an open circuit		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
TPS2 Circuit Low	P0222	Detects a continuous or intermittent short or open in TPS2 circuit	TPS2 Voltage <	0.25		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No 5V reference error or fault for # 4 5V reference circuit (P06A3)	79/159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Trips:
								1
								Type:
								A
MIL:								
YES								
TPS2 Circuit High	P0223	Detects a continuous or intermittent short or open in TPS2 circuit	TPS2 Voltage >	4.59		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No 5V reference error or fault for # 4 5V reference circuit (P06A3)	79/159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Trips:
								1
								Type:
								A
MIL:								
YES								

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Turbo/Super Charger Engine Overboost	P0234	Detect Negative Boost Pressure Control Deviation	Desired Boost Pressure - Actual Boost Pressure	< (KtBSTD_p_CntrlDevNegLim - KtBSTD_p_CntrlDevAmbAirCorr) See Tables in Supporting Tables Sheet	Diagnosis Enabled Engine Speed Engine Speed Desired Boost Pressure Desired Boost Pressure Desired Boost Pressure Derivative Desired Boost Pressure Derivative Ambient Pressure Ambient Pressure Coolant Temp Coolant Temp Intake Air Temp Intake Air Temp Wait for steady state: No Active DTCs:	Enabled > 1600 rpm < 6000 rpm > 140.0 kPa < 300.0 kPa > -75.0 kPa/s < 75.0 kPa/s > 60.0 kPa < 120.0 kPa > -40.0 Deg C < 120.0 Deg C > -40.0 Deg C < 80.0 Deg C 0.8 seconds Desired Boost Pressure > Basic Pressure AmbientAirDefault BSTR_b_PCA_CktFA BSTR_b_TurboBypass CktFA ECT_Sensor_FA IAT_SensorFA BSTR_b_ExcsvBstTFT KO BSTR_b_PCA_CktTFT KO TC_BoostPresSnsrFA	15 failures out of 15 samples 1 sample every 100ms	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			ABS(Measured MAP – MAP Model 2) Filtered	> 22.0 kPa		MAP Model 2 Error multiplied by MAP2 Residual Weight Factor based on RPM		
			MAP3 model fails when			MAP Model 3 Error multiplied by MAP Residual Weight Factor based on RPM		
			ABS(Measured MAP – MAP Model 3) Filtered	> 22.0 kPa				
			TIAP1 model fails when			TIAP Model 1 Error multiplied by TIAP Residual Weight Factor based on RPM		
			ABS(Measured TIAP – TIAP Model 1) Filtered	> 24.0 kPa				
			TPS model fails when			Filtered Throttle Model Error multiplied by TPS Residual Weight Factor based on RPM		
			Filtered Throttle Model Error	> 200 kPa*(g/s)				
			TIAP Correlation model fails when			See table "IFRD Residual Weighting Factors".		
			High Engine Air Flow is TRUE AND		No Active DTCs:	MAP_SensorCircuitFA EGRValve_FP		
			Measured TIAP - measured MAP offset as a function of engine speed			EGRValvePerformance_FA MAF_SensorCircuitFA CrankSensor_FA		
			See table "TIAP-MAP Correlation Offset"	> 24.0 kPa		ECT_Sensor_FA ECT_Sensor_Ckt_FP		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>Onset</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured Baro - offset as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Offset"</p> <p>TIAP Correlation is valid when</p> <p>High Engine Air Flow has been TRUE for a period of time</p> <p>OR</p> <p>High Engine Air Flow has been TRUE for a period of time</p> <p>High Engine Air Flow is TRUE when</p> <p>Mass Air Flow</p>	<p>> 24.0 kPa</p> <p>> 1.0 seconds</p> <p>> 1.0 seconds</p> <p>> a threshold in gm/sec as a function of engine speed</p>		<p>IAT_SensorFA</p> <p>IAT_SensorCircuitFP</p> <p>IAT2_SensorFA</p> <p>IAT2_SensorCircuitFP</p> <p>TC_BoostPresSnsrCkt FA</p> <p>AmbientAirDefault</p>		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			AND Manifold Pressure	See table "TIAP-MAP Correlation Min Air Flow" > a threshold in kPa as a function of engine speed				
			AND Filtered Mass Air Flow - Mass Air Flow	See table "TIAP-MAP Correlation Min MAP" < 3.0 gm/sec				
			Low Engine Air Flow is TRUE when Mass Air Flow	< a threshold in gm/sec as a function of engine speed				
			AND Manifold Pressure	See table "TIAP-Baro Correlation Max Air Flow"				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>< a threshold in kPa as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Max MAP"</p> <p>AND</p> <p>Mass Air Flow - Filtered Mass Air Flow</p> <p>< 2.0 gm/sec</p> <p><u>Engine Not Rotating Case:</u></p> <p>Turbocharger Boost Pressure</p> <p>OR</p> <p>Turbocharger Bosst Pressure</p>	<p>< 50.0 kPa</p> <p>> 115.0 kPa</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Engine is not rotating</p> <p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>> 10.0 seconds</p> <p>EngModeNotRunTmErr</p> <p>MAP_SensorFA</p> <p>TC_BoostPresSnsrCktFA</p> <p>AAP2_SnsrFA</p> <p>MAP_SensorCircuitFP</p> <p>AAP_SnsrCktFP</p> <p>AAP2_SnsrCktFP</p>	<p>4 failures out of 5 samples</p> <p>1 sample every 12.5 msec</p>	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Turbocharger Boost Pressure Sensor Circuit Low	P0237	Detects a continuous short to low or open in either the signal circuit or the turbocharger boost pressure sensor.	Turbocharger Boost Pressure Voltage	< 18.0 % of 5 Volt Range (0.9 Volts = 44.0 kPa)	Engine Run Time	> 0.00 seconds	320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Turbocharger Boost Pressure Sensor Circuit High	P0238	Detects an open sensor ground or continuous short to high in either the signal circuit or the turbocharger boost pressure sensor.	Turbocharger Boost Pressure Voltage	> 78.0 % of 5 Volt Range (3.9 Volts = 299.0 kPa)	Engine Run Time	> 0.00 seconds	320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit	P0243	Detect Turbocharger Boost Solenoid -Open Circuit	ECM detects that commanded and actual states of output driver do not match because the output is open circuit		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts <= 32.00 Volts >= 2.00 Volts <= 6.00 Volts	10 failures out of 20 samples 1 sample every 100ms	Type B 2 trips
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit Low	P0245	Detect Turbocharger Boost Solenoid - Shorted to ground	ECM detects that commanded and actual states of output driver do not match because the output is shorted to ground		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts <= 32.00 Volts >= 2.00 Volts <= 6.00 Volts	10 failures out of 20 samples 1 sample every 100ms	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit High	P0246	Detect Turbocharger Boost Solenoid - Shorted to Power	ECM detects that commanded and actual states of output driver do not match because the output is shorted to power		Diagnosis Enabled Powertrain relay Voltage Powertrain relay Voltage Ignition run crank voltage Ignition run crank voltage Engine is not cranking	Enabled >= 11.00 Volts ≤ 32.00 Volts ≥ 2.00 Volts ≤ 6.00 Volts	10 failures out of 20 samples 1 sample every 100ms	Type B 2 trips
Injector 1 Low side circuit shorted to ground	P0261	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 1 Low side circuit shorted to power	P0262	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 2 Low side circuit shorted to ground	P0264	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector 2 low side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 2 Low side circuit shorted to power	P0265	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 3 Low side circuit shorted to ground	P0267	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 3 Low side circuit shorted to power	P0268	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 4 Low side circuit shorted to ground	P0270	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Injector 4 Low side circuit shorted to power	P0271	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector low side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Turbo/Super Charger Engine Underboost	P0299	Detect Positive Boost Pressure Control Deviation	Desired Boost Pressure - Actual Boost Pressure	> (KtBSTD_p_CntrlDevPosLim + KtBSTD_p_CntrlDevAmbAirCorr) See Tables in Supporting Tables Sheet	Diagnosis Enabled Engine Speed Engine Speed Desired Boost Pressure Desired Boost Pressure Desired Boost Pressure Derivative Desired Boost Pressure Derivative Ambient Pressure Ambient Pressure Coolant Temp Coolant Temp Intake Air Temp Intake Air Temp Wait for steady state: No Active DTCs:	Enabled > 1600 rpm < 6000 rpm > 140.0 kPa < 300.0 kPa > -75.0 kPa/s < 75.0 kPa/s > 60.0 kPa < 120.0 kPa > -40.0 Deg C < 120.0 Deg C > -40.0 Deg C < 80.0 Deg C 0.8 seconds Desired Boost Pressure > Basic Pressure AmbientAirDefault BSTR_b_PCA_CktFA BSTR_b_TurboBypass CktFA	15 failures out of 15 samples 1 sample every 100ms	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						ECT_Sensor_FA IAT_SensorFA BSTR_b_ExcsvBstTFTKO BSTR_b_PCA_CktTFTKO TC_BoostPresSnsrFA AnyCamPhaser_FA BSTR_b_PresCntrlTooLoTFTKO BSTR_b_PresCntrlTooHiTFTKO EnginePowerLimited Not in Device Control for: Wastegate Control Bypass Control		
Random Misfire Detected	P0300	These DTC's will determine if a random or a cylinder specific misfire is occurring by monitoring crankshaft velocity	Deceleration index vs. Engine Speed Vs Engine load	(>Idle SCD AND > Idle SCD ddt Tables) OR (>SCD Delta AND > SCD Delta ddt Tables)	Engine Run Time	> 2 crankshaft revolutions	Emission Exceedence = any (5) failed 200 rev blocks out of (16) 200 rev block tests	2 Trips
Cylinder 1 Misfire Detected	P0301		Deceleration index calculation is tailored to specific veh. Tables used are 1st tables encountered that are not max of range.	OR (>Idle Cyl Mode AND > Idle Cyl Mode ddt Tables)	ECT	-7°C < ECT < 130°C	Failure reported for (1) Exceedence in 1st (16) 200 rev block tests, or (4) Exceedences thereafter.	Type B (Mil Flashes with Catalyst Damaging Misfire)
Cylinder 2 Misfire Detected	P0302		Undetectable region at a given speed/load point is where all tables are max of range point. see Algorithm Description Document for additional details.	OR (>Cyl Mode AND > Cyl Mode ddt Tables)	If ECT at startup	< -7°C		
Cylinder 3 Misfire Detected	P0303			OR (>Rev Mode Table)	ECT	21°C < ECT < 130°C		
Cylinder 4 Misfire Detected	P0304			OR (> AFM Table in Cyl Deact mode)	System Voltage + Throttle delta - Throttle delta	9.00<volts<32.00 < 95.00% per 25 ms < 95.00% per 25 ms		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Cylinder 5 Misfire Detected	P0306							
Cylinder 6 Misfire Detected	P0307							
Cylinder 7 Misfire Detected	P0308							
Cylinder 8 Misfire Detected								
			Misfire Percent Emission Failure Threshold	≥ 0.70% P0300 ≥ 0.70% emission				
			Misfire Percent Catalyst Damage	>"Catalyst Damaging Misfire Percentage" Table whenever secondary conditions are met.	Engine Speed Engine Load Misfire counts (at low speed/loads, one cylinder may not cause cat damage)	> 1400 rpm AND > 20 % load AND < 180 counts on one cylinder		
			When engine speed and load are less than the FTP calcs (3) catalyst damage exceedences are allowed.	≤ 0 FTP rpm AND ≤ 0 FTP % load				
					Engine Speed	650 < rpm < (Engine Speed Limit) - 400 Engine speed limit is a function of inputs like Gear and temperature typical Engine Speed Limit = 6200 rpm	Continuous 4 cycle delay	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
				disable conditions:	No active DTCs:	TPS_FA EnginePowerLimited MAF_SensorTFTKO MAP_SensorTFTKO IAT_SensorTFTKO ECT_Sensor_Ckt_TFTKO 5VoltReferenceB_FA CrankSensorTestFailedTKO CrankSensorFaultActive CrankIntakeCamCorrelationFA CrankExhaustCamCorrelationFA CrankCamCorrelationTFTKO AnyCamPhaser_FA AnyCamPhaser_TFTKO If Monitor Rough Road=1 and RoughRoadSource="TOSS" Transmission Output Shaft Angular Velocity Validity (Auto Trans only) Clutch Sensor FA (Manual Trans only) TransEngagedState_FA (Auto Trans only)	4 cycle delay	
					P0315 & engine speed	> 1000 rpm		
					Fuel Level Low	LowFuelConditionDiagnostic	500 cycle delay	
					Cam and Crank Sensors	in sync with each other	4 cycle delay	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Misfire requests TCC unlock	Not honored because Transmission in hot mode or Post O2 intrusive diagnostic running	4 cycle delay	
					Fuel System Status	≠ Fuel Cut	4 cycle delay	
					Active Fuel Management	Transition in progress	0 cycle delay	
					Undetectable engine speed and engine load region	invalid speed load range in decel index tables	4 cycle delay	
					Abusive Engine Over Speed	> 6800 rpm	1250 cycle delay	
					Below zero torque (except CARB approved 3000 rpm to redline triangle.)	<" Zero torque engine load" in Supporting Tables tab	4 cycle delay	
					Below zero torque: TPS Veh Speed	≤ 1% > 30 mph	4 cycle delay	
					EGR Intrusive test	Active	0 cycle delay	
					Manual Trans	Clutch shift	4 cycle delay	
					Throttle Position	> 98.00%	7 cycle delay	
					AND Automatic transmission shift			
					Driveline Ring Filter active After a low level misfire, another misfire may not be detectable until driveline ringing ceases. If no ringing seen, stop filter early.			
					Filter Driveline ring: Stop filter early:			
						4 engine cycles after misfire 3 Engine cycles after misfire		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Abnormal engine speed oscillations: (Rough road etc) Off Idle, number of consecutive decelerating cylinders after accelerating.: (Number of decels can vary with misfire detection equation) TPS Engine Speed Veh Speed SCD Cyl Mode Rev Mode	> 3 % > 950 rpm > 3 mph = 4 consecutive cyls = 4 consecutive cyls = 4 consecutive cyls 1 (1 = Enabled)		
					Misfire Pattern Recognition Enabled: Validates misfire vs. false detection Engine Speed Veh Speed Final fail conditions within:	Between > 700 RPM and < 3000 RPM > 1 kph > 0.8 < 2.0 of misfire threshold for a given engine speed and load		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Rough Road Section: Monitor Rough Road RoughRoadSource IF Rough Road is monitored, then ONE of the following Rough Road Sources will be used: Rough Road Source = "TOSS" Rough Road detected Rough Road Source = "WheelSpeedInECM" ABS/TCS system active RoughRoad detected VSES active Rough Road Source = "FromABS" ABS/TCS system active RoughRoad detected VSES active	0 (1=Yes) WheelSpeedInECM		
Crankshaft Position System Variation Not Learned	P0315	Monitor for valid crankshaft error compensation factors	Sum of Compensation factors	≥ 2.0040 OR ≤ 1.9960	OBD Manufacturer Enable Counter	=0	0.50 seconds Frequency Continuous 100 msec	1 Trips Type A
Knock Sensor (KS) Performance Per Cylinder	P0324	This diagnostic checks for knock sensor performance out of the normal expected range due to: 1) Excessive knock and 2) Abnormal engine noise on a per cylinder basis	Common Enable Criteria		Diagnostic Enabled? Engine Speed	Disabled ≤ 8500 RPM	First Order Lag Filter with Weight Coefficient	Type: B MIL: YES Trips: 2

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Engine Air Flow	≥ 0 mg/cylinder and ≤ 2000 mg/cylinder		
					ECT	≥ -40 deg's C		
					IAT	≥ -40 deg's C		
			Specific Enable Criteria and Thresholds					
			1. Filtered Knock Intensity (for Excessive Knock) VaKNKD_k_PerfCylKnockIntFilt	> 1.5000	Engine Speed Engine running	≥ 400 RPM ≥ 7.5 seconds	Weight Coefficient = 0.0300 Updated each engine event	
			2. Filtered FFT Intensity: (for Abnormal Noise) VaKNKD_k_PerfCylAbnFiltIntnsity	< Abnormal Noise Threshold (see supporting tables)	Engine Speed Engine running	≥ 2000 RPM ≥ 1.5 seconds	Weight Coefficient = 0.0025 Updated each engine event	
Knock Sensor (KS) Circuit Bank 1	P0325	This diagnostic checks for an open in the knock sensor circuit	Filtered FFT Output (VaKNKD_k_OpenFiltIntensity[0])	> OpenCktThrshMin and < OpenCktThrshMax See Supporting Tables for OpenCktThrshMin & Max	Diagnostic Enabled? Engine Speed Engine Air Flow ECT IAT Engine running	Enabled ≥ 400 RPM and ≤ 8500 RPM ≥ 20 mg/cylinder and ≤ 2000 mg/cylinder ≥ -40 deg's C ≥ -40 deg's C ≥ 7.5 seconds	First Order Lag Filter with Weight Coefficient Weight Coefficient = 0.0100 Updated each engine event	Type: B MIL: YES Trips: 2

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Knock Sensor (KS) Performance Bank 1	P0326	This diagnostic checks for knock sensor performance out of the normal expected range due to 1. Excessive knock or 2. Abnormal engine noise on a per bank/sensor basis	Common Enable Criteria		Diagnostic Enabled?	Enabled	First Order Lag Filter with Weight Coefficient	Type: B MIL: YES Trips: 2
					Engine Speed	≤ 8500 RPM		
					Engine Air Flow	≥ 0 mg/cylinder and ≤ 2000 mg/cylinder		
					ECT	≥ -40 deg's C		
					IAT	≥ -40 deg's C		
			1. Filtered Knock Intensity (for Excessive Knock) VaKNKD_k_PerfKnockIntFilt	> 1.5000	Engine Speed Engine running	≥ 400 RPM ≥ 7.5 seconds	Weight Coefficient = 0.0150 Updated each engine event	
			2. Filtered FFT Intensity: (for Abnormal Noise) VaKNKD_k_PerfAbnFiltIntnsity	< Abnormal Noise Threshold (see supporting tables)	Engine Speed Engine running	≥ 2000 RPM ≥ 6.0 seconds	Weight Coefficient = 0.0100 Updated each engine event	
Knock Sensor (KS) Circuit Low Bank 1	P0327	This diagnostic checks for an out of range low knock sensor signal	Sensor Input Signal Line	< 0.57 Volts	Diagnostic Enabled?	Enabled	50 Failures out of 63 Samples	Type: B MIL: YES Trips: 2
			or			Engine Speed	> 400 RPM and < 8500 RPM	
			Sensor Return Signal Line	< 0.40 Volts				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Knock Sensor (KS) Circuit High Bank 1	P0328	This diagnostic checks for an out of range high knock sensor signal	Sensor Input Signal Line	> 2.76 Volts	Diagnostic Enabled?	Enabled	50 Failures out of 63 Samples 100 msec rate	Type: B MIL: YES Trips: 2
			or		Engine Speed	> 400 RPM and < 8500 RPM		
			Sensor Return Signal Line	> 1.95 Volts				
Knock Sensor (KS) Circuit Bank 2	P0330	This diagnostic checks for an open in the knock sensor circuit	Filtered FFT Output (VaKNKD_k_OpenFiltIntensity[1]) See Supporting Tables for OpenCktThrshMin & Max	> OpenCktThrshMin and < OpenCktThrshMax	Diagnostic Enabled?	Enabled	First Order Lag Filter with Weight Coefficient Weight Coefficient = 0.0100 Updated each engine event	Type: B MIL: YES Trips: 2
					Engine Speed	≥ 400 RPM and ≤ 8500 RPM		
					Engine Air Flow	≥ 20 mg/cylinder and ≤ 2000 mg/cylinder		
					ECT	≥ -40 deg's C		
					IAT	≥ -40 deg's C		
					Engine running	≥ 7.5 seconds		
Knock Sensor (KS) Performance Bank 2	P0331	This diagnostic checks for knock sensor performance out of the normal expected range due to 1. Excessive knock or 2. Abnormal engine noise on a per bank basis			Diagnostic Enabled?	Enabled	First Order Lag Filter with Weight Coefficient	Type: B MIL: YES Trips: 2
					Engine Speed	≤ 8500 RPM		
					Engine Air Flow	≥ 0 mg/cylinder and ≤ 2000 mg/cylinder		
					ECT	≥ -40 deg's C		
					IAT	≥ -40 deg's C		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			1. Filtered Knock Intensity (for Excessive Knock) VaKNKD_k_PerfKnockIntFilt	> 1.5000	Engine Speed Engine running	≥ 400 RPM ≥ 7.5 seconds	Weight Coefficient = 0.0150 Updated each engine event	
			2. Filtered FFT Intensity: (for Abnormal Noise) VaKNKD_k_PerfAbnFiltIntnsity	< Abnormal Noise Threshold (see supporting tables)	Engine Speed Engine running	≥ 2000 RPM ≥ 6.0 seconds	Weight Coefficient = 0.0100 Updated each engine event	
Knock Sensor (KS) Circuit Low Bank 2	P0332	This diagnostic checks for an out of range low knock sensor signal	Sensor Input Signal Line	< 0.57 Volts	Diagnostic Enabled?	Enabled	50 Failures out of 63 Samples 100 msec rate	Type: B MIL: YES Trips: 2
			or		Engine Speed	> 400 RPM and < 8500 RPM		
			Sensor Return Signal Line	< 0.40 Volts				
Knock Sensor (KS) Circuit High Bank 2	P0333	This diagnostic checks for an out of range high knock sensor signal	Sensor Input Signal Line	> 2.76 Volts	Diagnostic Enabled?	Enabled	50 Failures out of 63 Samples 100 msec rate	Type: B MIL: YES Trips: 2
			or		Engine Speed	> 400 RPM and < 8500 RPM		
			Sensor Return Signal Line	> 1.95 Volts				
Crankshaft Position (CKP) Sensor A Circuit	P0335	Determines if a fault exists with the crank position sensor signal	<u>Engine-Cranking Crankshaft Test:</u>		<u>Engine-Cranking Crankshaft Test:</u>		<u>Engine-Cranking Crankshaft Test:</u>	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Circuit			Time since last crankshaft position sensor pulse received	>= 4.0 seconds	Starter engaged	= FALSE = FALSE = FALSE > 3.0 grams/second))	Continuous every 100 msec	
					AND (cam pulses being received			
					OR (DTC P0101 AND DTC P0102 AND DTC P0103 AND Engine Air Flow			
		<u>Time-Based Crankshaft Test:</u>			<u>Time-Based Crankshaft Test:</u>	<u>Time-Based Crankshaft Test:</u>		
		No crankshaft pulses received	>= 1.0 seconds	Engine is Running	5VoltReferenceB_FA	Continuous every 12.5 msec		
				Starter is not engaged				
				No DTC Active:				
		<u>Event-Based Crankshaft Test:</u>		<u>Event-Based Crankshaft Test:</u>				<u>Event-Based Crankshaft Test:</u>
		No crankshaft pulses received		Engine is Running		2 failures out of 10 samples		
				OR Starter is engaged				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					No DTC Active:	5VoltReferenceA_FA 5VoltReferenceB_FA P0365 P0366	One sample per engine revolution	
Crankshaft Position (CKP) Sensor A Performance	P0336	Determines if a performance fault exists with the crank position sensor signal	<p><u>Crank Re-synchronization Test:</u></p> <p>Time in which 10 or more crank re-synchronizations occur</p> <p><u>Time-Based Crankshaft Test:</u></p> <p>No crankshaft synchronization gap found</p> <p><u>Engine Start Test during Crank:</u></p> <p>Time since starter engaged without detecting crankshaft synchronization gap</p>	<p>< 10.0 seconds</p> <p>>= 0.4 seconds</p> <p>>= 1.5 seconds</p>	<p><u>Crank Re-synchronization Test:</u></p> <p>Engine Air Flow Cam-based engine speed</p> <p>No DTC Active:</p> <p><u>Time-Based Crankshaft Test:</u></p> <p>Engine is Running Starter is not engaged</p> <p>No DTC Active:</p> <p><u>Engine Start Test during Crank:</u></p> <p>Starter engaged</p> <p>AND (cam pulses being received)</p> <p>OR</p>	<p>>= 3.0 grams/second</p> <p>> 450 RPM 5VoltReferenceB_FA P0335</p> <p>5VoltReferenceB_FA</p>	<p><u>Crank Re-synchronization Test:</u></p> <p>Continuous every 250 msec</p> <p><u>Time-Based Crankshaft Test:</u></p> <p>Continuous every 12.5 msec</p> <p><u>Engine Start Test during Crank:</u></p> <p>Continuous every 100 msec</p>	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p><u>Event-Based Crankshaft Test:</u></p> <p>Crank Pulses received in one engine revolution</p> <p>OR</p> <p>Crank Pulses received in one engine revolution</p>	<p>< 51</p> <p>> 65</p>	<p>(DTC P0101 AND DTC P0102 AND DTC P0103 AND Engine Air Flow</p> <p><u>Event-Based Crankshaft Test:</u></p> <p>Engine is Running</p> <p>OR</p> <p>Starter is engaged</p> <p>No DTC Active:</p>	<p>= FALSE</p> <p>= FALSE</p> <p>= FALSE</p> <p>> 3.0 grams/second))</p> <p>5VoltReferenceA_FA 5VoltReferenceB_FA P0365 P0366</p>	<p><u>Event-Based Crankshaft Test:</u></p> <p>8 failures out of 10 samples</p> <p>One sample per engine revolution</p>	
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor A	P0340	Determines if a fault exists with the cam position bank 1 sensor A signal	<p><u>Engine Cranking Camshaft Test:</u></p> <p>Time since last camshaft position sensor pulse received</p> <p>OR</p>	<p>>= 5.5 seconds</p>	<p><u>Engine Cranking Camshaft Test:</u></p> <p>Starter engaged</p> <p>AND</p> <p>(cam pulses being received</p>		<p><u>Engine Cranking Camshaft Test:</u></p> <p>Continuous every 100 msec</p>	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Time that starter has been engaged without a camshaft sensor pulse	>= 4.0 seconds	OR (DTC P0101 AND DTC P0102 AND DTC P0103 AND Engine Air Flow	= FALSE = FALSE = FALSE > 3.0 grams/second))		
			<u>Time-Based Camshaft Test:</u> Fewer than 4 camshaft pulses received in a time	> 3.0 seconds	<u>Time-Based Camshaft Test:</u> Engine is Running Starter is not engaged	 5VoltReferenceA_FA	<u>Time-Based Camshaft Test:</u> Continuous every 100 msec	
			<u>Fast Event-Based Camshaft Test:</u> No camshaft pulses received during first 12 MEDRES events (There are 12 MEDRES events per engine cycle)		<u>Fast Event-Based Camshaft Test:</u> Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged	 5VoltReferenceA_FA 5VoltReferenceB_FA CrankSensor_FA	<u>Fast Event-Based Camshaft Test:</u> Continuous every MEDRES event	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<u>Slow Event-Based Camshaft Test:</u> The number of camshaft pulses received during 100 engine cycles	= 0	<u>Slow Event-Based Camshaft Test:</u> Crankshaft is synchronized No DTC Active:	5VoltReferenceA_FA 5VoltReferenceB_FA CrankSensor_FA	<u>Slow Event-Based Camshaft Test:</u> 8 failures out of 10 samples Continuous every engine cycle	
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor A	P0341	Determines if a performance fault exists with the cam position bank 1 sensor A signal	<u>Fast Event-Based Camshaft Test:</u> The number of camshaft pulses received during first 12 MEDRES events is less than 4 or greater than 10 (There are 12 MEDRES events per engine cycle) <u>Slow Event-Based Camshaft Test:</u> The number of camshaft pulses received during 100 engine cycles		<u>Fast Event-Based Camshaft Test:</u> Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged No DTC Active:	5VoltReferenceA_FA 5VoltReferenceB_FA CrankSensor_FA	<u>Fast Event-Based Camshaft Test:</u> Continuous every MEDRES event <u>Slow Event-Based Camshaft Test:</u> 8 failures out of 10 samples	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			OR	< 398 > 402		5VoltReferenceB_FA CrankSensor_FA	Continuous every engine cycle	
IGNITION CONTROL #1 CIRCUIT	P0351	This diagnostic checks the circuit for electrical integrity during operation. Monitors EST for Cylinder 1	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Engine running	> 6.00 Volts	50 Failures out of 63 Samples	Type: B MIL: YES Trips: 2
					Ignition Voltage		100 msec rate	
IGNITION CONTROL #2 CIRCUIT	P0352	This diagnostic checks the circuit for electrical integrity during operation. Monitors EST for Cylinder 2	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Engine running	> 6.00 Volts	50 Failures out of 63 Samples	Type: B MIL: YES Trips: 2
					Ignition Voltage		100 msec rate	
IGNITION CONTROL #3 CIRCUIT	P0353	This diagnostic checks the circuit for electrical integrity during operation. Monitors EST for Cylinder 3	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Engine running	> 6.00 Volts	50 Failures out of 63 Samples	Type: B MIL: YES Trips: 2
					Ignition Voltage		100 msec rate	
IGNITION CONTROL #4 CIRCUIT	P0354	This diagnostic checks the circuit for electrical integrity during operation. Monitors EST for Cylinder 4	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Engine running	> 6.00 Volts	50 Failures out of 63Samples	Type: B MIL: YES Trips: 2
					Ignition Voltage		100 msec rate	
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor B	P0365	Determines if a fault exists with the cam position bank 1 sensor B signal	<u>Engine Cranking Camshaft Test:</u> Time since last camshaft position sensor pulse received		<u>Engine Cranking Camshaft Test:</u> Starter engaged		<u>Engine Cranking Camshaft Test:</u> Continuous every 100 msec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>OR</p> <p>Time that starter has been engaged without a camshaft sensor pulse</p> <p><u>Time-Based Camshaft Test:</u></p> <p>Fewer than 4 camshaft pulses received in a time</p> <p><u>Fast Event-Based Camshaft Test:</u></p> <p>No camshaft pulses received during first 12 MEDRES events</p> <p>(There are 12 MEDRES events per engine cycle)</p>	<p>>= 5.5 seconds</p> <p>>= 4.0 seconds</p> <p>> 3.0 seconds</p>	<p>AND</p> <p>(cam pulses being received</p> <p>OR</p> <p>(DTC P0101</p> <p>AND DTC P0102</p> <p>AND DTC P0103</p> <p>AND</p> <p>Engine Air Flow</p> <p><u>Time-Based Camshaft Test:</u></p> <p>Engine is Running</p> <p>Starter is not engaged</p> <p>No DTC Active:</p> <p><u>Fast Event-Based Camshaft Test:</u></p> <p>Crankshaft is synchronized</p> <p>Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged</p>	<p>= FALSE</p> <p>= FALSE</p> <p>= FALSE</p> <p>> 3.0 grams/second))</p> <p>5VoltReferenceA_FA</p>	<p>Continuous every 100 msec</p> <p>Continuous every MEDRES event</p>	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p><u>Slow Event-Based Camshaft Test:</u></p> <p>The number of camshaft pulses received during 100 engine cycles</p>	= 0	<p>No DTC Active:</p> <p><u>Slow Event-Based Camshaft Test:</u></p> <p>Crankshaft is synchronized</p> <p>No DTC Active:</p>	<p>5VoltReferenceA_FA 5VoltReferenceB_FA CrankSensor_FA</p> <p>5VoltReferenceA_FA 5VoltReferenceB_FA CrankSensor_FA</p>	<p><u>Slow Event-Based Camshaft Test:</u></p> <p>8 failures out of 10 samples</p> <p>Continuous every engine cycle</p>	
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor B	P0366	Determines if a performance fault exists with the cam position bank 1 sensor B signal	<p><u>Fast Event-Based Camshaft Test:</u></p> <p>The number of camshaft pulses received during first 12 MEDRES events is less than 4 or greater than 10</p> <p>(There are 12 MEDRES events per engine cycle)</p>		<p><u>Fast Event-Based Camshaft Test:</u></p> <p>Crankshaft is synchronized</p> <p>Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged</p>		<p><u>Fast Event-Based Camshaft Test:</u></p> <p>Continuous every MEDRES event</p>	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p><u>Slow Event-Based Camshaft Test:</u></p> <p>The number of camshaft pulses received during 100 engine cycles</p> <p>OR</p>	<p>< 398</p> <p>> 402</p>	<p>No DTC Active:</p> <p><u>Slow Event-Based Camshaft Test:</u></p> <p>Crankshaft is synchronized</p> <p>No DTC Active:</p>	<p>5VoltReferenceA_FA</p> <p>5VoltReferenceB_FA</p> <p>CrankSensor_FA</p> <p>5VoltReferenceA_FA</p> <p>5VoltReferenceB_FA</p> <p>CrankSensor_FA</p>	<p><u>Slow Event-Based Camshaft Test:</u></p> <p>8 failures out of 10 samples</p> <p>Continuous every engine cycle</p>	
Catalyst System Low Efficiency Bank 1	P0420	Oxygen Storage	Normalized Ratio OSC Value (EWMA filtered)	< 0.350	<u>Valid Idle Period Criteria</u>		1 test attempted per valid idle period	Type A 1 Trip(s)
		<p>The catalyst washcoat contains Cerium Oxide. Cerium Oxide reacts with NO and O2 during lean A/F excursions to store the excess oxygen (I.e. Cerium Oxidation). During rich A/F excursions, Cerium Oxide reacts with CO and H2 to release this stored oxygen (I.e. Cerium Reduction). This is referred to as the Oxygen Storage Capacity, or OSC. CatMon's strategy is to "measure" the OSC of the catalyst through forced Lean and Rich A/F excursions</p> <p>Normalized Ratio OSC Value Calculation Information and Definitions =</p> <p>1. Raw OSC Calculation = (post cat O2 Resp time - pre cat O2 Resp time)</p> <p>2. BestFailing OSC value from a calibration table (based on temp and exhaust gas flow)</p> <p>3. WorstPassing OSC value (based on temp and exhaust gas flow)</p> <p>Normalized Ratio Calculation = (1-2) / (3-2)</p> <p>A Normalized Ratio of 1 essentially represents a good part and a ratio of 0 essentially represents a very bad part.</p>		<p>Driver must be off the accel pedal. This checks that the final accel pedal position (comprehending deadband and hysteresis) is essentially zero.</p>	<p>Vehicle Speed < 1.24 MPH</p> <p>Engine speed > 1125 RPM for a minimum of 20 seconds since end of last idle period.</p> <p>Engine run time ≥ MinimumEngineRunTime, This is a function of Coolant Temperature, please see Supporting Tables</p>	<p>Minimum of 1 test per trip</p> <p>Maximum of 8 tests per trip</p> <p>Frequency: Fueling Related : 12.5 ms</p> <p>OSC Measurements: 100 ms</p> <p>Temp Prediction: 1000ms</p>		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Tests attempted this trip	< 255		
					The catalyst diagnostic has not yet completed for the current trip.			
					Catalyst Idle Conditions Met Criteria			
					General Enable met and the Valid Idle Period Criteria met			
					Green Converter Delay	Not Active		
					Induction Air	-20 < ° C < 250		
					Intrusive test(s): Fueltrim Post O2 EVAP EGR	Not Active		
					Other vehicle functions: Power Take Off	Not Active		
					RunCrank Voltage	> 10.90 Volts		
					Ethanol Estimation	NOT in Progress		
					ECT	40 < ° C < 140		
					Barometric Pressure	> 70 KPA		
					Idle Time before going intrusive is	< 50 Seconds		
					Idle time is incremented if Vehicle speed	< 1.24 MPH and the drivers foot is off accel pedal and the idle speed control system is active as identified in the Valid Idle Period Criteria section.		
					Short Term Fuel Trim	0.80 < ST FT < 1.20		
					Predicted catalyst temp > 400 degC AND Engine Airflow > MinAirflowToWarmCatalyst table (g/s) (refer to "Supporting Tables" tab)			
		The Catalyst Monitoring Test is done during idle. Several conditions must be meet in order to execute this test. These conditions and their related values are listed in the secondary parameters area of this document.						

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
					<p>(Based on engine coolant at the time the WarmedUpEvents counter resets to 0.)</p> <p>for at least 40 seconds with a closed throttle time < 60 seconds consecutively (closed throttle consideration involves having the driver off the accel pedal as stated in the Valid Idle Period Criteria Section) .</p> <p>Also, in order to increment the WarmedUpEvents counter (counter must exceed 40 cal value), either the vehicle speed must exceed the vehicle speed cal or the driver must NOT be off the accel pedal as stated in the Valid Idle Period Criteria section above.</p> <hr/> <p style="text-align: center;">Closed loop fueling Enabled</p> <p>Please see "Closed Loop Enable Criteria" section of the "Supporting Tables" tab for details.</p> <hr/> <p style="text-align: center;">PRNDL</p> <p>is in Drive Range on an Auto Transmission vehicle.</p> <hr/> <p><i>Idle Stable Criteria :: Must hold true from after Catalyst Idle Conditions Met to the end of test</i></p>				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					MAF	2.00 < g/s < 12.00		
					Predicted catalyst temperature	< 750 degC		
					Engine Fueling Criteria at Beginning of Idle Period			
					The following fueling related must also be met from between 4 and 7 seconds after the Catalyst Idle Conditions Met Criteria has been met for at least 4 seconds prior to allowing intrusive control			
					Number of pre-O2 switches	>= 2		
					Short Term Fuel Trim Avg	0.850 < ST FT Avg < 1.100		
					Rapid Step Response (RSR) feature will initiate multiple tests:			
					If the difference between current EWMA value and the current OSC Normalized Ratio value is > 0.530 and the current OSC Normalized Ratio value is < 0.100			
					Maximum of 23 RSR tests to detect failure when RSR is enabled.			
					Green Converter Delay Criteria			
					This is part of the check for the Catalyst Idle Conditions Met Criteria section			
					The diagnostic will not be enabled until the following has been met:			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Predicted catalyst temperature > 0 ° C for 0 seconds non-continuously. Note: this feature is only enabled when the vehicle is new and cannot be enabled in service			
					PTO Not Active			
					General Enable			
					DTC's Not Set			
					MAF_SensorFA			
					MAF_SensorTFTKO			
					AmbPresDfItDStatus			
					IAT_SensorCircuitFA			
					IAT_SensorCircuitTFTKO			
					ECT_Sensor_FA			
					O2S_Bank_1_Sensor_1_FA			
					O2S_Bank_1_Sensor_2_FA			
					O2S_Bank_2_Sensor_1_FA			
					O2S_Bank_2_Sensor_2_FA			
					FuelTrimSystemB1_FA			
					FuelTrimSystemB1_TFTKO			
					FuelTrimSystemB2_FA			
					FuelTrimSystemB2_TFTKO			
					EngineMisfireDetected_FA			
					EvapPurgeSolenoidCircuit_FA			
					IAC_SystemRPM_FA			
					EGRValvePerformance_FA			
					EGRValveCircuit_FA			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					CamSensorAnyLocationFA			
					CrankSensor_FA			
					TPS_Performance_FA			
					EnginePowerLimited			
					VehicleSpeedSensor_FA			
Evaporative Emission (EVAP) System Small Leak Detected	P0442	This DTC will detect a small leak (≥ 0.020 "") in the EVAP system between the fuel fill cap and the purge solenoid. The engine off natural vacuum method (EONV) is used. EONV is an evaporative system leak detection diagnostic that runs when the vehicle is shut off when enable conditions are met. Prior to sealing the system and performing the diagnostic, the fuel volatility is analyzed. In an open system (Canister Vent Solenoid [CVS] open) high volatility fuel creates enough flow to generate a measurable pressure differential relative to atmospheric.	The total delta from peak pressure to peak vacuum during the test is normalized against a calibration pressure threshold table that is based upon fuel level and ambient temperature. (See P0442: EONV Pressure Threshold Table on Supporting Tables Tab). The normalized value is calculated by the following equation: $1 - (\text{peak pressure} - \text{peak vacuum}) / \text{pressure threshold}$. The normalized value is entered into EWMA (with 0= perfect pass and 1= perfect fail).		Fuel Level Drive Time Drive length ECT Baro Odometer Engine not run time before key off must be Time since last complete test if normalized result and EWMA is passing OR Time since last complete test if normalized result or EWMA is failing Estimated ambient temperature at end of drive	$10\% \leq \text{Percent} \leq 90\%$ ≥ 600 seconds ≥ 3.1 miles ≥ 70 °C ≥ 70 kPa ≥ 10.0 miles \leq refer to "P0442: Engine Off Time Before Vehicle Off Maximum as a Function of Estimated Ambient Temperature table" in Supporting Tables.	Once per trip, during hot soak (up to 2400 sec.). No more than 2 unsuccessful attempts between completed tests.	1 trip Type A EWMA Average run length is 6 under normal conditions Run length is 3 to 6 trips after code clear or non-volatile reset

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					<p>Ambient Temperature Valid Conditioning Time" in Supporting Tables Tab.</p> <p>OR</p> <p>4. Not a Cold Start and greater than a Short Soak</p> <p>Previous time since engine off</p> <p>AND</p> <p>Must expire maximum value in Estimate of Ambient Temperature Valid Conditioning Time. Please see "P0442: Estimate of Ambient Temperature Valid Conditioning Time" in Supporting Tables Tab.</p>	<p>Mass Air Flow \geq 8 g/sec</p> <p>> 7200 seconds</p> <p>Vehicle Speed \geq 14.3 mph AND Mass Air Flow \geq 8 g/sec</p>		
				<p>Abort Conditions:</p>	<p>1. High Fuel Volatility</p> <p>During the volatility phase, pressure in the fuel tank is integrated vs. time. If the integrated pressure is</p> <p>< -5</p> <p>then test aborts and unsuccessful attempts is incremented.</p> <p>OR</p> <p>2. Vacuum Refueling Detected</p> <p>See P0454 Fault Code for information on vacuum refueling algorithm.</p>			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					<p>OR</p> <p>3. Fuel Level Refueling Detected</p> <p>See P0464 Fault Code for information on fuel level refueling.</p> <p>OR</p> <p>4. Vacuum Out of Range and No Refueling</p> <p>See P0451 Fault Code for information on vacuum sensor out of range and P0464 Fault Code for information on fuel level refueling.</p> <p>OR</p> <p>5. Vacuum Out of Range and Refueling Detected</p> <p>See P0451 Fault Code for information on vacuum sensor out of range and P0464 Fault Code for information on fuel level refueling.</p> <p>OR</p> <p>6. Vent Valve Override Failed</p> <p>Device control using an off-board tool to control the vent solenoid, cannot exceed during the EONV test</p>	0.50 seconds		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					OR 7. Key up during EONV test No active DTCs:	FuelLevelDataFault MAF_SensorFA ECT_Sensor_FA IAT_SensorFA VehicleSpeedSensor_F A IgnitionOffTimeValid AmbientAirDefault P0443 P0446 P0449 P0452 P0453 P0455 P0496		
Evaporative Emission (EVAP) Canister Purge Solenoid Valve Circuit (ODM)	P0443	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		PT Relay Voltage	11 volts ≤ Voltage ≤ 32 volts	20 failures out of 25 samples 250 ms / sample Continuous with solenoid operation	2 trips Type B
Evaporative Emission (EVAP) Vent System	P0446	This DTC will determine if a restriction is present in the vent solenoid, vent filler, vent hose or EVAP canister.	Vent Restriction Prep Test:		Fuel Level System Voltage	10% ≤ Percent ≤ 90% 11 volts ≤ Voltage ≤ 32 volts	Once per Cold Start	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Performance		This test runs with normal purge and vent valve is open.	Vented Vacuum OR Vented Vacuum for 60 seconds Vent Restriction Test: Tank Vacuum for 5 seconds BEFORE Purge Volume After setting the DTC for the first time, 2 liters of fuel must be consumed before setting the DTC for the second time.	$< -623 \text{ Pa}$ $> 1245 \text{ Pa}$ $> 2989 \text{ Pa}$ $\geq 10 \text{ liters}$	Startup IAT Startup ECT BARO No active DTCs:	volts $4 \text{ }^\circ\text{C} \leq \text{Temperature} \leq 30 \text{ }^\circ\text{C}$ $\leq 35 \text{ }^\circ\text{C}$ $\geq 70 \text{ kPa}$ MAP_SensorFA TPS_FA VehicleSpeedSensor_FA IAT_SensorCircuitFA ECT_Sensor_FA AmbientAirDefault EnginePowerLimited P0443 P0449 P0452 P0453 P0454	Time is dependent on driving conditions Maximum time before test abort is 1000 seconds	
Evaporative Emission (EVAP) Vent Solenoid Control Circuit (ODM)	P0449	This DTC checks the circuit for electrical integrity during operation. If the P0449 is active, an intrusive test is performed with the vent solenoid commanded closed for 15 seconds.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Run/Crank voltage goes to 0 volts at key off	$11 \text{ volts} \leq \text{Voltage} \leq 32 \text{ volts}$	20 failures out of 25 samples 250 ms / sample Continuous with solenoid operation	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
							Solenoild operation	
Fuel Tank Pressure (FTP) Sensor Circuit Performance	P0451	The DTC will be set if the fuel tank vacuum sensor is out of range when it tries to re-zero prior to the phase-1 or phase-2 portions of the engine-off natural vacuum small leak test.	<p>The tank vacuum sensor voltage is compared to a window about the nominal sensor voltage offset (~1.5 volts)</p> <p>Upper voltage threshold (voltage addition above the nominal voltage)</p> <p>Lower voltage threshold (voltage subtraction below the nominal voltage)</p> <p>The difference between tank vacuum sensor voltage and the nominal offset voltage is then normalized against the appropriate threshold listed above to produce a ratio between 0.0 and 1.0. This normalized re-zero ratio is then filtered with a EWMA (with 0= perfect pass and 1=perfect fail).</p> <p>When EWMA is</p>	<p>0.2 volts</p> <p>0.2 volts</p> <p>> 0.73 (EWMA Fail Threshold)</p>	This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes		<p>This test is executed during an engine-off natural vacuum small leak test. The number of times that it executes can range from zero to two per engine-off period.</p> <p>The length of the test is determined by the refueling rationality test, which can take up to 600 seconds to complete.</p>	<p>1 trip Type A EWMA</p> <p>Average run length: 6</p> <p>Run length is 2 trips after code clear or non-volatile reset</p>

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>, the DTC light is illuminated.</p> <p>The DTC light can be turned off if the EWMA is</p> <p>≤ 0.40 (EWMA Re-Pass Threshold)</p> <p>and stays below the EWMA fail threshold for 2 additional consecutive trips.</p>					
Fuel Tank Pressure (FTP) Sensor Circuit Low Voltage	P0452	This DTC will detect a fuel tank pressure sensor signal that is too low out of range.	<p>Fuel tank pressure sensor signal</p> <p>The normal operating range of the fuel tank pressure sensor is 0.5 volts (~1245 Pa) to 4.5 volts (~ -3736 Pa).</p>	< 0.15 volts (3 % of Vref or ~ 1681 Pa)	<p>Time delay after sensor power up for sensor warm-up</p> <p>ECM State \neq crank</p> <p>Stops 6.0 seconds after key-off</p>	is 0.10 seconds	<p>80 failures out of 100 samples</p> <p>100 ms / sample</p> <p>Continuous</p>	2 trips Type B
Fuel Tank Pressure (FTP) Sensor Circuit High Voltage	P0453	This DTC will detect a fuel tank pressure sensor signal that is too high out of range.	<p>Fuel tank pressure sensor signal</p> <p>The normal operating range of the fuel tank pressure sensor is 0.5 volts (~1245 Pa) to 4.5 volts (~ -3736 Pa).</p>	> 4.85 volts (97% of Vref or ~ - 4172 Pa)	<p>Time delay after sensor power up for sensor warm-up</p> <p>ECM State \neq crank</p> <p>Stops 6.0 seconds after key-off</p>	is 0.10 seconds	<p>80 failures out of 100 samples</p> <p>100 ms / sample</p> <p>Continuous</p>	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Tank Pressure (FTP) Sensor Circuit Intermittent	P0454	This DTC will detect intermittent tank vacuum sensor signals that would have caused the engine-off natural vacuum small leak test to abort due to an apparent refueling event.	<p>If an abrupt change in tank vacuum is detected the engine-off natural vacuum test is aborted due to an apparent refueling event. Subsequent to the abort, a refueling rationality test is executed to confirm that a refueling event occurred. If a refueling is confirmed, then the test sample is considered passing. Otherwise, the sample is considered failing indicating an intermittent signal problem.</p> <p>An abrupt change is defined as a change in vacuum:</p> <p>in the span of 1.0 seconds.</p> <p>But in 12.5 msec.</p>	<p>>112 Pa</p> <p>< 249 Pa</p>	This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes		<p>This test is executed during an engine-off natural vacuum small leak test. The test can only execute up to once per engine-off period.</p> <p>The length of the test is determined by the refueling rationality test, which can take up to 600 seconds to complete.</p> <p>The test will report a failure if 2 out of 3 samples are failures.</p> <p>12.5 ms / sample</p>	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					If ECT > IAT, Startup temperature delta (ECT-IAT): Cold Test Timer Startup IAT Startup ECT <u>Weak Vacuum Follow-up Test</u> This test can run following a weak vacuum failure or on a hot restart.	$\leq 8\text{ }^{\circ}\text{C}$ $\leq 1000\text{ seconds}$ $4\text{ }^{\circ}\text{C} \leq \text{Temperature} \leq 30\text{ }^{\circ}\text{C}$ $\leq 35\text{ }^{\circ}\text{C}$	limited to 1300 seconds. Once the MIL is on, the follow-up test runs indefinitely.	
Fuel Level Sensor 1 Performance	P0461	This DTC will detect a fuel sender stuck in range in the primary fuel tank.	Delta Fuel Volume change over an accumulated 186 miles.	< 3 liters	Engine Running No active DTCs:	VehicleSpeedSensor_F A	250 ms / sample Continuous	2 trips Type B
Fuel Level Sensor 1 Circuit Low Voltage	P0462	This DTC will detect a fuel sender stuck out of range low in the primary fuel tank.	Fuel level Sender % of 5V range	< 10 %	Run/Crank Voltage Run/Crank voltage goes to 0 volts at key off	$11\text{ volts} \leq \text{Voltage} \leq 32\text{ volts}$	100 failures out of 125 samples 100 ms / sample Continuous	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Level Sensor 1 Circuit High Voltage	P0463	This DTC will detect a fuel sender stuck out of range high in the primary fuel tank.	Fuel level Sender % of 5V range	> 60 %	Run/Crank Voltage Run/Crank voltage goes to 0 volts at key off	11 volts ≤ Voltage ≤ 32 volts	100 failures out of 125 samples 100 ms / sample Continuous	2 trips Type B
Fuel Level Sensor 1 Circuit Intermittent	P0464	This DTC will detect intermittent fuel level sensor signals that would have caused the engine-off natural vacuum small leak test to abort due to an apparent re-fueling event.	If a change in fuel level is detected, the engine-off natural vacuum test is aborted due to an apparent refueling event. Subsequent to the abort, a refueling rationality test is executed to confirm that an actual refueling event occurred. If a refueling event is confirmed, then the test sample is considered passing. Otherwise, the sample is considered failing indicating an intermittent signal problem. An intermittent change in fuel level is defined as:		This test will execute whenever the engine-off natural vacuum small leak test (P0442) executes		This test is executed during an engine-off natural vacuum small leak test. The test can only execute up to once per engine-off period. The length of the test is determined by the refueling rationality test, which can take up to 600 seconds to complete. The test will report a failure if 2 out of 3 samples are	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			The fuel level changes and does not remain for 30 seconds during a 600 second refueling rationality test.	by 10 % > 10 %			failures. 100 ms / sample	
Cooling Fan 1 Relay Control Circuit (ODM)	P0480	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Engine Speed	11 volts ≤ Voltage ≤ 32 volts ≥ 400 RPM	50 failures out of 63 samples 100 ms / sample Continuous with fan operation	2 trips Type B Not used on systems with Mechanical Fan)
Cooling Fan 2 Relay Control Circuit (ODM)	P0481	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Engine Speed	11 volts ≤ Voltage ≤ 32 volts ≥ 400 RPM	50 failures out of 63 samples 100 ms / sample Continuous with fan operation	2 trips Type B Not used on systems with Mechanical Fan)

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Evaporative Emission (EVAP) System Flow During Non-Purge	P0496	This DTC will determine if the purge solenoid is leaking to engine manifold vacuum. This test will run with the purge valve closed and the vent valve closed.	Tank Vacuum for 5 seconds BEFORE Test time	> 2491 Pa ≥ refer to "P0496: Purge Valve Leak Test Engine Vacuum Test Time (Cold Start) as a Function of Fuel Level table" in Supporting Tables Tab.	Fuel Level System Voltage BARO Startup IAT Startup ECT Engine Off Time No active DTCs:	10% ≤ Percent ≤ 90% 11 volts ≤ Voltage ≤ 32 volts ≥ 70 kPa 4 °C ≤ Temperature ≤ 30 °C ≤ 35 °C ≥ 28800.0 seconds MAP_SensorFA TPS_FA VehicleSpeedSensor_FA IAT_SensorCircuitFA ECT_Sensor_FA AmbientAirDefault EnginePowerLimited P0443 P0449 P0452 P0453 P0454	Once per cold start Cold start: max time is 1000 seconds	2 trips Type B
Transmission Output Speed Sensor (TOSS)	P0502	No activity in the TOSS circuit	TOSS Raw Speed	≤ 60 RPM	Engine Torque Minimum Throttle opening Engine Speed Ignition voltage PTO	90.0 ≤ N-M ≤ 8191.8 ≥ 8.0 % 1500 ≤ RPM ≤ 6500 11.0 ≤ Volts ≤ 32.0 not active	≥ 4.5 sec	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					EngineTorqueEstInaccurate OR If KeETQC_b_MinTransRemedial = 1 (KeETQC_b_MinTransRemedial = 0)	FALSE Not MAF_SensorTFTKO Not MAP_SensorTFTKO Not EngineMisfireDetected_FA		
					P0503	Not failed this key cycle		
Transmission Output Speed Sensor (TOSS)	P0503	TOSS Signal Intermittent	Loop-to-Loop change in TOSS	≥ 350 RPM	Raw Output Speed Output Speed change Time since transfer case range change Ignition voltage Engine Speed Vehicle Speed PTO	> 300 RPM for ≥ 2.0 sec ≤ 150 RPM for ≥ 2.0 sec ≥ 6.0 sec 11.0 ≤ Volts ≤ 32.0 200 ≤ RPM ≤ 7500 for ≥ 5.0 seconds ≤ 318 MPH for ≥ 5.0 sec not active	≥ 3.3 sec	Type B 2 trips
Low Engine Speed Idle System	P0506	This DTC will determine if a low idle exists	Filtered Engine Speed Error	> 95.00 rpm	Baro	> 70 kPa	Diagnostic runs in every 12.5 ms loop	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			filter coefficient	0.00375	Coolant Temp	> 60 °C and < 120 °C Must verify KfECTI_T_EngCoolHot LoThresh is less than KfECTI_T_EngCoolHot HiThresh	Diagnostic reports pass or fail in 10 seconds once all enable conditions are met	
					Engine run time	≥ 60 sec		
					Ignition voltage	32 ≥ volts ≥ 11		
					Time since gear change	≥ 3 sec		
					Time since a TCC mode change	> 3 sec		
					IAT	> -20 °C		
					Vehicle speed	≤ 2 mph		
					Commanded RPM delta	≤ 25 rpm		
					Idle time	> 10 sec		
					For manual transmissions: Clutch Pedal Position or Clutch Pedal Position	> 88.00 pct < 25.00 pct		
						PTO not active		
						Transfer Case not in 4WD LowState		
						Off-vehicle device control (service bay control) must not be active.		
						following conditions not TRUE: (VeTESR_e_EngSpdR eqIntvType = CeTESR_e_EngSpdMi nLimit AND VeTESR_e_EngSpdRe qRespType = CeTESR_e_NoSugges tion)		
						Clutch is not depressed		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					No active DTCs	TC_BoostPresSnsrFA		
						ECT_Sensor_FA		
						EnginePowerLimited		
						EGRValveCircuit_FA		
						EGRValvePerformance_FA		
						IAT_SensorCircuitFA		
						EvapFlowDuringNonPurge_FA		
						FuelTrimSystemB1_FA		
						FuelTrimSystemB2_FA		
						FuelInjectorCircuit_FA		
						MAF_SensorFA		
						EngineMisfireDetected_FA		
						IgnitionOutputDriver_FA		
						TPS_FA		
						TPS_Performance_FA		
						VehicleSpeedSensor_FA		
						FuelLevelDataFault		
						LowFuelConditionDiagnostic		
						Clutch_Sensor_FA		
						AmbPresDfItDStatus		
						P2771		
					All of the above met for Idle time			
						> 10 sec		
High Engine Speed Idle System	P0507	This DTC will determine if a high idle exists	Filtered Engine Speed Error	< -190.00 rpm	Baro	> 70 kPa	Diagnostic runs in every 12.5 ms loop	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			filter coefficient	0.00375	Coolant Temp	> 60 °C and < 120 °C Must verify KfECTI_T_EngCoolHot LoThresh is less than KfECTI_T_EngCoolHot HiThresh	Diagnostic reports pass or fail in 10 seconds once all enable conditions are met	
					Engine run time	≥ 60 sec		
					Ignition voltage	32 ≥ volts ≥ 11		
					Time since gear change	≥ 3 sec		
					Time since a TCC mode change	> 3 sec		
					IAT	> -20 °C		
					Vehicle speed	≤ 2 mph		
					Commanded RPM delta	≤ 25 rpm		
					For manual transmissions: Clutch Pedal Position or Clutch Pedal Position	> 88.00 pct or < 25.00 pct		
						PTO not active		
						Transfer Case not in 4WD LowState		
						Off-vehicle device control (service bay control) must not be active.		
						following conditions not TRUE: (VeTESR_e_EngSpdR eqIntvType = CeTESR_e_EngSpdMi nLimit AND VeTESR_e_EngSpdRe qRespType = CeTESR_e_NoSugges tion)		
						Clutch is not depressed		
					No active DTCs	TC_BoostPresSnsrFA		
						ECT_Sensor_FA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						EnginePowerLimited		
						EGRValveCircuit_FA		
						EGRValvePerformance_FA		
						IAT_SensorCircuitFA		
						EvapFlowDuringNonPurge_FA		
						FuelTrimSystemB1_FA		
						FuelTrimSystemB2_FA		
						FuelInjectorCircuit_FA		
						MAF_SensorFA		
						EngineMisfireDetected_FA		
						IgnitionOutputDriver_FA		
						TPS_FA		
						TPS_Performance_FA		
						VehicleSpeedSensor_FA		
						FuelLevelDataFault		
						LowFuelConditionDiagnostic		
						Clutch Sensor FA		
						AmbPresDfItDStatus		
						P2771		
					All of the above met for Idle time	> 10 sec		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Cold Start Rough Idle	P050D	Monitors the combustion performance when the cold start emission reduction strategy is active by accumulating and determining the percentage of engine cycles that have less than complete combustion relative to the total number of engine cycles in which Dual Pulse is active.	Deceleration index vs. Engine Speed Vs Engine load Deceleration index calculation is tailored to specific veh. Tables used are 1st tables encountered that are not max of range. Undetectable region at a given speed/load point is where all tables are max of range point. see Algorithm Description Document for additional details.	Incomplete combustion identified by P0300 threshold tables: (>Idle SCD AND >Idle SCD ddt Tables) OR (>Idle Cyl Mode AND > Idle Cyl Mode ddt Tables)	Misfire Algorithm Enabled (Refer to P0300 for Enablement Requirements)		Runs once per trip when the cold start emission reduction strategy is active and Dual Pulse is enabled and active. Frequency: Engine Cycle Test completes after Dual Pulse is no longer active OR The first 500 engine cycles have been reached	Type B 2 Trip(s)
					OBD Manufacturer Enable Counter 0 To enable the diagnostic, the Cold Start Emission Reduction Strategy Must Be Active per the following: Catalyst Temperature < 300.00 degC AND Engine Coolant > -10.00 degC In addition, Dual Pulse Strategy Is Enabled and Active Per the following: Engine Speed > 250.00 RPM Engine Speed <= 2600.00 RPM Barometric Pressure >= 70.00 KPa For the engine speeds and loads in which Dual Pulse is active:			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Dual Pulse Error induced misfires percentage	>= catalyst damaging misfire		
					Dual Pulse Error induced misfires percentage	< 90% of the maximum achievable catalyst damaging misfire.		
					Engine Cycles	>= 50		
					Engine Cycles	< 501		
					<p>The Cold Start Emission Reduction strategy must not be exiting. The strategy will exit per the following:</p>			
					Catalyst Temperature	>= 800.00 degC		
					AND			
					Engine Run Time	>= 22.00 seconds		
					OR			
					Engine Run Time	> "KtCSEC_t_ExtendedEngineExit" in Supporting Tables Tab.		
					OR			
					Engine Coolant	>= 56.00 degC		
					<p>Dual Pulse Strategy will exit per the following:</p>			
					Engine Speed	> 2800.00 RPM		
					OR			
					Barometric Pressure	< 70.00 Kpa		
					Pedal position	<= 1.00 Pct		
					<p>Dual Pulse Strategy will also exit if the any of the "Additional Dual Pulse Enabling Criteria" from below are not satisfied.</p>			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Additional Dual Pulse Enabling Criteria: Green Engine Enrichment Not Enabled Misfire Converter Protection strategy not being requested Engine Metal Overtemp strategy not being requested Fuel control state Open Loop Output State Control Not being requested for fuel DOD Or DFCO Not Active Power Enrichment Not Active Piston Protection Not Active Hot Coolant Enrichment Not Active Injector Flow Test Not Active General Enable DTC's Not Set AcceleratorPedalFailure ECT_Sensor_FA IAT_SensorCircuitFA IAT2_SensorCircuitFA CrankSensorFaultActive FuelInjectorCircuit_FA MAF_SensorFA MAP_SensorFA AnyCamPhaser_TFTKO Clutch Sensor FA IAC_SystemRPM_FA IgnitionOutputDriver_FA TPS_FA VehicleSpeedSensor_FA TransmissionEngagedState_FA EngineTorqueInaccurate			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					FuelInjectorCircuit_TFTKO			
					FuelPumpRlyCktFA			
					FuelInjectorCircuit_FA			
					FRP_SnsrCkt_FA			
					FRP_SnsrCkt_TFTKO			
					HighPressPumpCkt_TFTKO			
					HighPressPumpCkt_FA			
Cruise Control Mutil- Functon Switch Circuit	P0564	Detect when cruise control multi- function switch circuit (analog) voltage is in an illegal range	Cruise Control analog circuit voltage must be in an "illegal range" for greater than a calibratable period of time for cruise switch states that are received over serial data		CAN cruise switch diagnostic enable in ECM	Enabled	fail continuously for greater than 0.700 seconds	Type: C MIL: NO Trips: 1
Cruise Control Resume Circuit	P0567	Detects a failure of the cruise resume switch in a continously applied state	Cruise Control Resume switch remains applied for greater than a calibratable period of time for architecture where cruise switch states are received over serial data		CAN cruise switch diagnostic enable in ECM	Enabled	fail continuously for greater than 90.000 seconds	Type: C MIL: NO Trips: 1

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Cruise Control Set Circuit	P0568	Detects a failure of the cruise set switch in a continuously applied state	Cruise Control Set switch remains applied for greater than a calibratable period of time for architecture where cruise switch states are received over serial data		CAN cruise switch diagnostic enable in ECM	Enabled	fail continuously for greater than 90.000 seconds	Type: C MIL: NO
							fail continuously for greater than 90.000 seconds	Trips: 1
Cruise Control Input Circuit	P0575	Detects rolling count or protection value errors in Cruise Control Switch Status serial data signal	If x of y rolling count / protection value faults occur, disable cruise for duration of fault		Cruise Control Switch Serial Data Error Diagnostic Enable	Enabled	10/16 counts	Type: C MIL: NO
								Trips: 1
Control Module Read Only Memory (ROM)	P0601	This DTC will be stored if the calibration check sum is incorrect or the flash memory detects an uncorrectable error via the Error Correcting Code.	The Primary Processor's calculated checksum does not match the stored checksum value. Covers all software and calibrations.	1 failure if the fault is detected during the first pass. 5 failures if the fault occurs after the first pass is complete.			Diagnostic runs continuously in the background	Trips: 1 Type: A MIL: YES
			The Primary Processor's Error Correcting Code hardware in the flash memory detects an error. Covers all software and calibrations.	254 failures detected via Error Correcting Code		Diagnostic runs continuously via the flash hardware		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			The Primary Processor's calculated checksum does not match the stored checksum value for a selected subset of the calibrations.	2 consecutive failures detected or 5 total failures detected.			Diagnostic runs continuously. Will report a detected fault within 200 ms.	
			The Secondary Processor's calculated checksum does not match the stored checksum value. Covers all software and calibrations.	1 failure if the fault is detected during the first pass. 5 failures if the fault occurs after the first pass is complete.			Diagnostic runs continuously in the background	
				In all cases, the failure count is cleared when controller shuts down				
Control Module Not Programmed	P0602	This DTC will be stored if the PCM is a service PCM that has not been programmed.	Output state invalid			PCM State = crank or run	Diagnostic runs at powerup and once per second continuously after that	Type A 1 trips
						PCM is identified through calibration as a Service PCM		
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error at controller power-up	Checksum at power-up does not match checksum at power-down				Diagnostic runs at powerup	Type A 1 trips
							Diagnostic reports a fault if 1 failure occurs	
ECM RAM Failure	P0604	Indicates that the ECM has detected a RAM fault:						Trips: 1
								Type: A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		Primary Processor System RAM Fault	Indicates that the primary processor is unable to correctly read data from or write data to system RAM. Detects data read does not match data written >=	254 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	MIL: YES
		Primary Processor Cache RAM Fault	Indicates that the primary processor is unable to correctly read data from or write data to cached RAM. Detects data read does not match data written >=	254 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	
		Primary Processor TPU RAM Fault	Indicates that the primary processor is unable to correctly read data from or write data to TPU RAM. Detects data read does not match data written >=	5 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	
		Primary Processor Update Dual Store RAM Fault	Indicates that the primary processor detects a mismatch between the data and dual data is				When dual store updates occur.	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			found during RAM updates. Detects a mismatch in data and dual data updates >	0.46250 seconds				
		Primary Processor Write Protected RAM Fault	Indicates that the primary processor detects an illegal write attempt to protected RAM. Number of illegal writes are >	65534 counts			Diagnostic runs continuously (background loop)	
		Secondary Processor RAM Fault	Indicates that the secondary processor is unable to correctly read data from or write data to system RAM. Detects data read does not match data written >=	254 counts			Will finish first memory scan within 30 seconds at all engine conditions, diagnostic runs continuously (background loop)	
Internal ECM Processor Integrity Fault	P0606	Indicates that the ECM has detected an internal processor integrity fault:						Trips: 1
							Type: A	
		Primary Processor SPI Fault Detected	Loss or invalid message of SPI communication from the Secondary Processor at initialization detected by the Primary Processor or loss or invalid message of SPI communication from the Secondary Processor after a valid message was received by the Primary Processor	Loss or invalid message at initialization detected or loss or invalid message after a valid message was received		Run/Crank voltage >= 6.40 or Run/Crank voltage >= 11.00, else the failure will be reported for all conditions	In the primary processor, 159/399 counts intermittent or 39 counts continuous; 39 counts continuous @ initialization. 12.5 ms /count in the ECM main processor	MIL: YES

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		Secondary Processor SPI Fault Detected	Loss or invalid message of SPI communication from the Primary Processor at initialization detected by the Secondary Processor or loss or invalid message of SPI communication from the Primary Processor after a valid message was recieved by the Secondary Processor	Loss or invalid message at initialization detected or loss or invalid message after a valid message was recieved			In the secondary processor, 159/399 counts intermittent or 0 counts continuous; 0 counts continuous @ initialization. 12.5 ms /count in the ECM main processor	
		Secondary Processor Stack Fault	Checks for stack over or underflow in secondary processorby looking for corruption of known pattern at stack boundaries. Checks number of stack over/under flow since last powerup reset >=	5		KeMEMD_b_StackLimitTestEnbl == 1 Value of KeMEMD_b_StackLimitTestEnbl is: 1.	variable, depends on length of time to corrupt stack	
		Secondary processor received incorrect Keys	MAIN processor is verified by responding to a seed sent from the secondary with a key response to secondary. Checks number of incorrect keys received > or Secondary processor has not received a new within time limit	2 incorrect seeds within 8 messages		Ignition in Run or Crank	150 ms for one seed continually failing	
		MAIN processor did not receive seed within time limit	Time new seed not received exceeded			always running	0.450 seconds	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		MAIN processor test for seeds to arrive in a known sequence	MAIN processor receives seed in wrong order			always running	3 / 17 counts intermittent. 50 ms/count in the ECM main	
		Secondary processor ALU check	2 fails in a row in the Secondary processor's ALU check			KePISD_b_ALU_TestEnbld == 1 Value of KePISD_b_ALU_TestEnbld is: 1.	25 ms	
		Secondary processor register configuration check	2 fails in a row in the Secondary processor's configuration register masks versus known good data			KePISD_b_ConfigRegTestEnbld == 1 Value of KePISD_b_ConfigRegTestEnbld is: 1.	12.5 to 25 ms	
		MAIN processor discrete fault:	Secondary processor detects an error in the toggling of a hardware discrete line controlled by the MAIN processor			KePISD_b_MainCPU_SOH_FltEnbld == 1 Value of KePISD_b_ConfigRegTestEnbld is: 1.	50 ms	
		MAIN detected corruption in throttle or pedal critical RAM data	memory and complement memory do not agree				0.19 seconds	
		MAIN Processor Performance Check	1. Software tasks loops > schedule tasks loop 2. 12.5ms task loop sequence does not complete >=	See supporting tables 0.19 seconds		KePISD_b_SeedUpdKeyStorFltEnbld== 1 Value of KePISD_b_SeedUpdKeyStorFltEnbld is: 1. KePISD_b_12p5msSeqTestEnbld== 1 Value of KePISD_b_12p5msSeqTestEnbld is: 1.	Error > 5 times of loop time; loop times are 6.25, 12.5, 25 ms in the main processor	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		MAIN Processor Performance Check	Software background task first pass time to complete exceeds		Powertrain relay	> 6.41 V	360.000 seconds	
		MAIN processor ALU check	2 fails in a row in the MAIN processor's ALU check			KePISD_b_ALU_TestEnbl == 1 Value of KePISD_b_ALU_TestEnbl is: 1.	25 ms	
		MAIN processor configuration register check	2 fails in a row in the MAIN processor's configuration register masks versus known good data			KePISD_b_ConfigRegTestEnbl == 1 Value of KePISD_b_ConfigRegTestEnbl is: 1.	12.5 to 25 ms	
		MAIN Stack Fault	Checks number of stack over/under flow since last powerup reset >=	5		KeMEMD_b_StackLimitTestEnbl == 1 Value of KeMEMD_b_StackLimitTestEnbl is: 1.	variable, depends on length of time to corrupt stack	
		MAIN processor ADC test	Voltage deviation >	0.495		KePISD_b_A2D_CnvrtrTestEnbl == 1 Value of KePISD_b_A2D_CnvrtrTestEnbl is: 1.	3 / 8 counts or 0.150 seconds continuous; 50 ms/count in main processor	
		Flash ECC Fault	Checks for ECC (error correcting code) circuit test errors reported by the hardware for flash memory. Increments counter during controller initialization if ECC error occurred since last controller initialization. Counter >=	3 (results in MIL), 5 (results in MIL and remedial action)		KeMEMD_b_FlashECC_CktTestEnbl == 1 Value of KeMEMD_b_FlashECC_CktTestEnbl is: 1.	variable, depends on length of time to access flash with corrupted memory	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		RAM ECC Fault	Checks for ECC (error correcting code) circuit test errors reported by the hardware for RAM memory circuit. Increments counter during controller initialization if ECC error occurred since last controller initialization. Counter >=	3 (results in MIL), 5 (results in MIL and remedial action)		KeMEMD_b_RAM_EC C_CktTestEnbl == 1 Value of KeMEMD_b_RAM_EC C_CktTestEnbl is: 1.	variable, depends on length of time to access flash with corrupted memory	
Fuel Pump Relay Control Circuit Open	P0627	This DTC checks for an open and shorted high circuit while the device is commanded off.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Engine Speed	11 volts ≤ Voltage ≤ 32 volts ≥ 0 RPM	8 failures out of 10 samples 250 ms / sample Continuous with device off	2 trips Type B
Fuel Pump Relay Control Circuit Low Voltage	P0628	This DTC checks for a shorted low circuit while the device is commanded on.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Engine Speed	11 volts ≤ Voltage ≤ 32 volts ≥ 0 RPM	8 failures out of 10 samples 250 ms / sample Continuous with device on	2 trips Type B
Fuel Pump Relay Control Circuit High Voltage	P0629	This DTC checks for an open and shorted high circuit while the device is commanded off.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Engine Speed	11 volts ≤ Voltage ≤ 32 volts ≥ 0 RPM	8 failures out of 10 samples 250 ms / sample	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
							Continuous with device off	
Internal Control Module Fuel Injector Control Performance	P062B	This DTC checks the circuit for electrical integrity during operation.	Internal ECU Boost Voltage OR Internal ECU Boost Voltage OR Driver Status OR Driver Status	≥ 90 Volts ≤ 40 Volts = Not Ready = Uninitialized	Battery Voltage	$8.0 \leq \text{Volts} \leq 32.0$ Enabled when a code clear is not active or not exiting device control Engine is not cranking	High Voltage - 160 failures out of 200 samples Low Voltage - 160 failures out of 200 samples Driver Status Not Ready- 160 failures out of 200 samples Driver Status Uninitialized - Uninitialized state for ≥ 100 counts All at 12.5ms per sample	1 trips Type A
Control Module EEPROM Error	P062F	Indicates that the NVM Error flag has not been cleared	The next write to NVM will not succeed or the assembly calibration integrity check failed.		Ignition State	= unlock/acesory, run, or crank	1 test failure Diagnostic runs once at powerup	Type A 1 trips
VIN Not Programmed or Mismatched - Engine Control Module (ECM)	P0630	This DTC checks VIN is correctly written	At least one of programed VIN's digit	= 00 or FF	OBD Manufacturer Enable Counter	= 0	250 ms / test Continuous	Type A 1 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
5 Volt Reference #1 Circuit	P0641	Detects a continuous or intermittent short on th 5 volt reference circuit #1	ECM Vref1 < 4.875 or ECM Vref1 > 5.125 or the difference between ECM filtered Vref1 and Vref1 > 0.05			Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 0.1875 sec continuous; 12.5 ms/count in main processor	Trips: 1
								Type: A
								MIL: YES
Malfunction Indicator Lamp (MIL) Control Circuit (ODM)	P0650	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage Remote Vehicle Start is not active	11 volts ≤ Voltage ≤ 32 volts	20 failures out of 25 samples	2 trip Type B
							250 ms / sample	NO MIL
							Continuous	
5 Volt Reference #2 Circuit	P0651	Detects a continuous or intermittent short on th 5 volt reference circuit #2	ECM Vref2 < 4.875 or ECM Vref2 > 5.125 or the difference between ECM filtered Vref2 and Vref2 > 0.05			Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 0.1875 sec continuous; 12.5 ms/count in main processor	Trips: 1
								Type: A
								MIL: YES
Powertrain Relay Control (ODM)	P0685	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match.		Run/Crank Voltage	11 volts ≤ Voltage ≤ 32 volts	8 failures out of 10 samples	2 trips Type B
							250 ms / sample	
							Continuous	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Powertrain Relay Feedback Circuit High	P0690	This DTC is a check to determine if the Powertrain relay is functioning properly.	PT Relay feedback voltage is Stuck Test: PT Relay feedback voltage is when commanded 'OFF'	≥ 18 volts > 2 volts	Powertrain relay commanded "ON" No active DTCs:	PowertrainRelayStateOn_FA	5 failures out of 6 samples 1 second / sample Stuck Test: 100 ms/ sample Continuous failures ≥ 4 seconds	2 trips Type B
5 Volt Reference #3 Circuit	P0697	Detects a continuous or intermittent short on the 5 volt reference circuit #1	ECM Vref3 < or ECM Vref3 > or the difference between ECM filtered Vref3 and Vref3 >	4.875 5.125 0.05		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 0.1875 sec continuous; 12.5 ms/count in main processor	Trips: 1 Type: A MIL: YES
Fuel Pump Control Module (FPCM) Requested MIL Illumination	P069E	Monitors the FPCM MIL request line to determine when the FPCM has detected a MIL illuminating fault.	Fuel Pump Control Module Emissions-Related DTC set			Time since power-up > 3 seconds	Continuous	Type A 1 trips MIL: NO
5 Volt Reference #4 Circuit	P06A3	Detects a continuous or intermittent short on the 5 volt reference circuit #2	ECM Vref4 < or ECM Vref4 > or the difference between ECM filtered Vref3 and Vref3 >	4.875 5.125		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be	19/39 counts or 0.1875 sec continuous; 12.5 ms/count in main processor	Trips: 1 Type:

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
				0.05		reported for all conditions		A MIL: YES
Internal Control Module Knock Sensor Processor 1 Performance	P06B6	This diagnostic checks for a fault with the internal test circuit used only for the '20 kHz' method of the Open Circuit Diagnostic	Gated FFT Diagnostic Output (VaKNKD_k_OpenTestCktIntFilter[0])	> OpenTestThreshLo and < OpenTestThreshHi See Supporting Tables	Diagnostic Enabled?	Enabled	First Order Lag Filter with Weight Coefficient	Type: B MIL: YES Trips: 2
					Engine Speed	> 400 RPM and < 5000 RPM		
					Engine Air Flow	≥ 0 mg/cylinder and ≤ 2000 mg/cylinder	Weight Coefficient = 0.0100	
					Engine running	≥ 7.5 seconds	Updated each engine event	
Internal Control Module Knock Sensor Processor 2 Performance	P06B7	This diagnostic checks for a fault with the internal test circuit used only for the '20 kHz' method of the Open Circuit Diagnostic	Gated FFT Diagnostic Output (VaKNKD_k_OpenTestCktIntFilter[1])	> OpenTestThreshLo and < OpenTestThreshHi See Supporting Tables	Diagnostic Enabled?	Enabled	First Order Lag Filter with Weight Coefficient	Type: B MIL: YES Trips: 2
					Engine Speed	> 400 RPM and < 5000 RPM		
					Engine Air Flow	≥ 0 mg/cylinder and ≤ 2000 mg/cylinder	Weight Coefficient = 0.0100	
					Engine running	≥ 7.5 seconds	Updated each engine event	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
Transmission Control Module (TCM) Requested MIL Illumination	P0700	Monitors the TCM MIL request line to determine when the TCM has detected a MIL illuminating fault.	Transmission Emissions-Related DTC set			Time since power-up > 3 seconds	Continuous	Type A 1 trips MIL: NO	
Clutch Pedal Position Sensor Circuit Range / Performance	P0806	Detects if Clutch Pedal Position Sensor is Stuck in a range indicative of a vehicle NOT in gear, when the vehicle is determined to be in gear. Gear determination is made by verifying that engine RPM/ Trans Output Speed (N/TOS) ratio represents a valid gear.	Filtered Clutch Pedal Position Error when the vehicle is determined to be in gear	> 4 %	N/TOS Ratio	Must match actual gear (i.e. vehicle in gear)	25 ms loop	1 Trip(s) Type A	
					Transfer Case vehicle speed	Not in 4WD Low range > 10 MPH	Continuous		
					Engine Torque	> EngTorqueThreshold Table			
					Clutch Pedal Position	< ResidualErrEnableLow Table			
					OR				
					Clutch Pedal Position	> ResidualErrEnableHigh Table			
					No Active DTCs:				
					ClutchPositionSensorCktLo FA ClutchPositionSensorCkitHi FA CrankSensorFA Trans Output Shaft Angular Velocity Validity VehicleSpeedSensor_FA				
Clutch Pedal Position Sensor Circuit Low	P0807	Detects Continuous Circuit Short to Low or Open	Clutch Position Sensor Circuit	< 4 % of Vref for 200 counts out of 250 samples	Engine Not Cranking System Voltage	> 11.0 Volts	25 ms loop Continuous	1 Trip(s)	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>OR</p> <p>Too many minimum limit torque request transitions occur from TRUE to FALSE to TRUE within a time period</p> <p>Torque request greater than torque request diagnostic maximum threshold</p>	<p>Requested torque intervention type toggles from not increasing request to increasing request</p> <p>> 250 Nm for engine based traction torque system, > 4000 Nm for axle based traction torque system</p>			<p>12.5 msec</p> <p>>= 3 multi-transitions out of 5 samples. Performed every 200 ms</p> <p>>= 4 out of 10 samples Performed every 12.5 msec</p>	<p>1 trip(s)</p> <p>Special Type C</p>
Inlet Airflow System Performance	P1101	Determines if there are multiple air induction problems affecting airflow and/or manifold pressure.	See table "Turbocharger Intake Flow Rationality Diagnostic Failure Matrix" for combinations of model failures that can set this DTC.		<p>Engine Speed</p> <p>Engine Speed</p> <p>Coolant Temp</p> <p>Coolant Temp</p> <p>Intake Air Temp</p> <p>Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p>	<p>>= 400 RPM</p> <p><= 6000 RPM</p> <p>> -7 Deg C</p> <p>< 125 Deg C</p> <p>> -20 Deg C</p> <p>< 125 Deg C</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	<p>Type B</p> <p>2 trips</p>

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			MAF model fails when			>= 0.00		
			ABS(Measured Flow – Modeled Air Flow) Filtered	> 20 grams/sec		Modeled Air Flow Error multiplied by MAF Residual Weight Factor based on RPM and MAF Residual Weight Factor Based on MAF Est		
			MAP1 model fails when					
			ABS(Measured MAP – MAP Model 1) Filtered	> 24.0 kPa		MAP Model 1 Error multiplied by MAP1 Residual Weight Factor based on RPM		
			MAP2 model fails when					
			ABS(Measured MAP – MAP Model 2) Filtered	> 22.0 kPa		MAP Model 2 Error multiplied by MAP2 Residual Weight Factor based on RPM		
			MAP3 model fails when					
			ABS(Measured MAP – MAP Model 3) Filtered	> 22.0 kPa		MAP Model 3 Error multiplied by MAP Residual Weight Factor based on RPM		
			TIAP1 model fails when					
			ABS(Measured TIAP – TIAP Model 1) Filtered	> 24.0 kPa		TIAP Model 1 Error multiplied by TIAP Residual Weight Factor based on RPM		
			TPS model fails when			Filtered Throttle Model Error multiplied by TPS Residual Weight Factor based on RPM		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			<p>Filtered Throttle Model Error</p> <p>TIAP Correlation model fails when</p> <p>High Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured MAP offset as a function of engine speed</p> <p>See table "TIAP-MAP Correlation Offset"</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND</p> <p>Measured TIAP - measured Baro offset as a function of engine speed</p> <p>See table "TIAP-Baro Correlation Offset"</p> <p>TIAP Correlation is valid when</p> <p>High Engine Air Flow has been TRUE for a period of time</p>	<p>> 200 kPa*(g/s)</p> <p>> 24.0 kPa</p> <p>> 24.0 kPa</p>	<p>No Active DTCs:</p>	<p>See table "IFRD Residual Weighting Factors".</p> <p>MAP_SensorCircuitFA</p> <p>EGRValve_FP</p> <p>EGRValvePerformance_FA</p> <p>MAF_SensorCircuitFA</p> <p>CrankSensor_FA</p> <p>ECT_Sensor_FA</p> <p>ECT_Sensor_Ckt_FP</p> <p>IAT_SensorFA</p> <p>IAT_SensorCircuitFP</p> <p>IAT2_SensorFA</p> <p>IAT2_SensorCircuitFP</p> <p>TC_BoostPresSnsrCkt FA</p> <p>AmbientAirDefault</p>		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			OR High Engine Air Flow has been TRUE for a period of time High Engine Air Flow is TRUE when Mass Air Flow AND Manifold Pressure	> 1.0 seconds > 1.0 seconds > a threshold in gm/sec as a function of engine speed See table "TIAP-MAP Correlation Min Air Flow" > a threshold in kPa as a function of engine speed See table "TIAP-MAP Correlation Min MAP" < 3.0 gm/sec				
			Filtered Mass Air Flow - Mass Air Flow Low Engine Air Flow is TRUE when					

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			when Mass Air Flow AND Manifold Pressure AND Mass Air Flow - Filtered Mass Air Flow	< a threshold in gm/sec as a function of engine speed See table "TIAP-Baro Correlation Max Air Flow" < a threshold in kPa as a function of engine speed See table "TIAP-Baro Correlation Max MAP" < 2.0 gm/sec				
O2S Insufficient Switching Bank 1 Sensor 1	P1133	This DTC determines if the O2 sensor is no longer sufficiently switching.	Fault condition present if Half Cycle L/R or R/L Switches are below the threshold. OR Slope Time L/R Switches OR	H/C L/R switches < Threshold, or H/C R/L switches < Threshold, (refer to table named "P1133 - O2S HC L to R Switches Limit Bank 1 Sensor 1" Pass/Fail Threshold table & "P1133 - O2S HC R to L Switches Limit Bank 1 Sensor 1" Pass/Fail Threshold table in Supporting tables tab) < 5 < 5	No Active DTC's	TPS_ThrottleAuthority Defaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsr Ckt_FA FuelInjectorCircuit_FA	Sample time is 60 seconds Frequency: Once per trip	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Slope Time R/L Switches		Bank 1 Sensor 1 DTC's not active System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control Low Fuel Condition Diag Green O2S Condition O2 Heater on for Learned Htr resistance Engine Coolant IAT Engine run Accum Time since any AFM status change Time since Purge On to Off change Time since Purge Off to On change Purge duty cycle Engine airflow	AIR System FA EthanolCompositionSensor_FA EngineMisfireDetected_FA = P0131, P0132 or P0134 10.0 < Volts < 32.0 = Not active = Not active = Not active = Not active = False = Not Valid, See definition of Green Sensor Delay Criteria (B1S1) in Supporting Tables tab. ≥ 40 seconds = Valid > 69 °C > -40 °C > 60 seconds > 2.0 seconds > 0.0 seconds > 1.5 seconds ≥ 0 % duty cycle 10 ≤ gps ≤ 50		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Engine speed Fuel Baro Air Per Cylinder Low Fuel Condition Diag Fuel Control State Closed Loop Active LTM fuel cell Transient Fuel Mass Baro Fuel Control State Fuel State Commanded Proportional Gain <u>All of the above met for</u> Time	$1000 \leq \text{RPM} \leq 3500$ $< 87\% \text{ Ethanol}$ $> 70 \text{ kpa}$ $\geq 100 \text{ mgrams}$ = False = Closed Loop = TRUE = Enabled $\leq 100.0 \text{ mgrams}$ = Not Defaulted not = Power Enrichment DFCO not active $\geq 0.0\%$ $> 3.0 \text{ seconds}$		
Injector 1 low side circuit shorted to high side circuit	P1248	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to low side		Battery Voltage Engine Run Time	$11 \leq \text{Volts} \leq 32$ $\geq 5 \text{ Sec}$ P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 2 low side circuit shorted to high side circuit	P1249	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to low side		Battery Voltage Engine Run Time	$11 \leq \text{Volts} \leq 32$ $\geq 5 \text{ Sec}$ P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Injector 3 low side circuit shorted to high side circuit	P124A	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to low side		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 4 low side circuit shorted to high side circuit	P124B	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to low side		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Ignition Coil Positive Voltage Circuit Group 1	P135A	This diagnostic checks for voltage supply to the Ignition Coils	Ignition Module Supply Voltage.	< 2.5 Volts	Diagnostic Enabled/Disabled	Enabled	50 Failures out of 63 Samples 6.25 msec rate	Type: A MIL: YES Trips: 1
			Three possible power supply sources for Ignition Coils (1. Battery, 2. Ignition Run/Crank, or 3. PT Relay).	Ignition Coil Power Source:	PT_Relay			
				Additional enable criteria if Ignition Coil Power Source is 'Battery' (does <u>not</u> apply if Ignition Coil Power Source is either 'Run/Crank' or 'PT Relay' voltage).	PT Relay Voltage	> 11.0 (volts) and < 32.0 (volts)		
					Delay time starting at Key-On	0 (msec)		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
Cold Start Emissions Reduction System Fault	P1400	Model based test computes power from exhaust flow and thermal energy resulting from elevated idle speed and retarded spark advance. Detects if the cold start emission reduction system has failed resulting in the delivered power being out of range.	Average desired accumulated exhaust power - Average estimated accumulated exhaust power OR Average desired accumulated exhaust power - Average estimated accumulated exhaust power (EWMA filtered)	< -32.00 KJ/s (high RPM failure mode) > 4.00 KJ/s (low RPM failure mode)	<p>To enable the diagnostic, the Cold Start Emission Reduction Strategy must be Active per the following:</p>		Runs once per trip when the cold start emission reduction strategy is active	1 Trip(s)	
							Frequency: 100ms Loop		
							Test completes after 10 seconds of accumulated qualified data.		
							Catalyst Temperature < 300.00 degC		
							AND		
							Engine Coolant > -10.00 degC		
							<p>The Cold Start Emission Reduction strategy must not be exiting. The strategy will exit per the following:</p>		
							Catalyst Temperature >= 800.00 degC		
							AND		
							Engine Run Time >= 22.00 seconds		
OR									
Engine Run Time > "KtCSEC_t_ExtendedEngineExit" in Supporting Tables Tab.									
OR									
Engine Coolant >= 56.00 degC									
Other Enable Criteria									
Vehicle Speed < 1.24 MPH									
Driver must be off the accel pedal. This checks that the final accel pedal position (comprehending deadband and hysteresis) is essentially zero.									

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.						
					<p>A change in throttle position (tip-in/tip-out) will initiate a delay in the calculation of the average qualified residual value. When the</p> <table border="1"> <tr> <td>OBD Manufacturer Enable Counter</td> <td>0</td> </tr> <tr> <td>Pedal Close Delay Timer</td> <td>> 2.00 seconds</td> </tr> </table> <p>the diagnostic will continue the calculation.</p> <p>Clutch Pedal Top of Travel Achieved and Clutch Pedal Bottom of Travel Achieved. Refer to the "Clutch Pedal Top of Travel Achieved criteria" and "Clutch Pedal Bottom of Travel Achieved criteria" section of the "Supporting Tables" tab criteria</p> <table border="1"> <tr> <td>Idle Speed Control System</td> <td>Active</td> </tr> </table> <p>General Enable</p> <p>DTC's Not Set</p> <p>AcceleratorPedalFailure</p> <p>ECT_Sensor_FA</p> <p>IAT_SensorCircuitFA</p> <p>IAT2_SensorCircuitFA</p> <p>CrankSensorFaultActive</p> <p>FuelInjectorCircuit_FA</p> <p>MAF_SensorFA</p> <p>MAP_SensorFA</p> <p>EngineMisfireDetected_FA</p> <p>Clutch Sensor FA</p> <p>IAC_SystemRPM_FA</p> <p>IgnitionOutputDriver_FA</p> <p>P050A (ColdStrt_IAC_SysPerf)</p> <p>P050B (ColdStrtIgnTmngPerf)</p>		OBD Manufacturer Enable Counter	0	Pedal Close Delay Timer	> 2.00 seconds	Idle Speed Control System	Active		
OBD Manufacturer Enable Counter	0													
Pedal Close Delay Timer	> 2.00 seconds													
Idle Speed Control System	Active													

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					TPS_FA			
					VehicleSpeedSensor_FA			
					5VoltReferenceMAP_OOR_Fit			
					TransmissionEngagedState_FA			
					EngineTorqueInaccurate			
Transmission Engine Speed Request Circuit	P150C	Determines if engine speed request from the TCM is valid	Serial Communication rolling count value	+ 1 from previous \$19D message (PTEI3)	Diagnostic enable bit	1	Diagnostic runs in 12.5 ms loop	2 trips Type B
			Transmission engine speed protection	not equal to 2's complement of transmission engine speed request + Transmission alive rolling count	Engine run time	0.50 sec		
					# of Protect Errors	10 protect errors out of 10 samples		
					# of Alive Rolling Errors	6 rolling count errors out of 10 samples		
					No idle diagnostic 506/507 code	IAC_SystemRPM_FA		
					No Serial communication loss to TCM	(U0101)		
					Engine Running	= TRUE		
					Power mode	Run Crank Active		
Steady State Actuation Fault	P1516	Detect an inability to maintain a steady state throttle position	Throttle is considered to be steady state when: Change in throttle position over 12.5 msec is <	0.25 percent			0.49 ms	Trips: 1
				4.00 seconds				Type: A
								MIL: YES
					Run/crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
Internal Control Module SIDI High Pressure Pump current monitor	P163A	This DTC checks the current from the control area and compares it with calibrated thresholds to set current high and low flags	SIDI fuel pump High Current Test	Current	≥ 11.00 Amps	Battery Voltage	11 <= Volts <= 32	Current High - 750 failures out of 938 samples	2 trips Type B
			SIDI fuel pump Low Current Test	Current	≤ 0.10 Amps	Low Side Fuel Pressure			
Additional Enable Criteria:						High Pressure Pump is enabled			
					Barometric Pressure	≥ 70.0			
					Inlet Air Temp	≥ -10.0			
					Fuel Temp	$-10 \leq \text{Temp degC} \leq 100$			
						Estimate fuel rail pressure is valid			
						Green Engine (In assembly plant) is not enabled			
						Not LowFuelConditionDiagnostic			
						Low side Fuel Pump is on			
						Injector Flow Test is not active			
						Device control commanded pressure is false			
						Device control pump ckt enabled on is false			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTCs not Active:	Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0 FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA FHPR_b_PumpCkt_FA Ethanol Composition Sensor FA PowertrainRelayFault		
Ignition Voltage Correlation	P1682	Detect a continuous or intermittent out of correlation between the Run/Crank Ignition Voltage & the Powertrain Relay Ignition Voltage	$ Run/Crank - ETC Run/Crank >$	3.00 Volts	Powertrain commanded on and Run/crank voltage > or ETC Run/crank voltage > and Run/crank voltage >	Table, f(IAT). See supporting tables 5.5 5.5	240/480 counts or 0.1750sec continuous; 12.5 ms/count in main processor	Trips: 1 Type: A MIL: YES

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Internal Control Module Redundant Memory Performance	P16F3	Detect Processor Calculation faults due to RAM corruptions, ALU failures and ROM failures						Trips: 1
							Type: A	
							MIL: YES	
			Desired engine torque request greater than redundant calculation plus threshold	52.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Cylinders active greater than commanded	1 cylinder		Engine speed greater than 0rpm and less than 3200rpm	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Difference between Cruise Axle Torque Arbitrated Request and Cruise Axle Torque Request exceeds threshold	97.62 Nm		Cruise has been engaged for more than 4.00 seconds	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Engine min capacity above threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 100 ms continuous, 0.5 down time multiplier	
No fast unmanaged retarded spark above the applied spark plus the threshold	Table, f(Erpm). See supporting tables		Engine speed greater than 0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Absolute difference of adjustment factor based on temperature and its dual store above threshold	2.76 m/s		Ignition in unlock/accessory, run or crank	Up/down timer 138 ms continuous, 0.5 down time multiplier	
			1) Absolute difference of redundant calculated engine speed above threshold 2)Time between lores events and its dual store do not match	KeEPSD_n_LoresSecurBndry 500 RPM		Engine speed greater than 0 RPM	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			After throttle blade pressure and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Speed Control's Predicted Torque Request and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Engine oil temperature and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 325 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Desired throttle position greater than redundant calculation plus threshold	10.00 percent		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Absolute difference of the rate limited pre-throttle pressure and its redundant calculation greater than threshold	0.83 kpa		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Throttle desired torque above desired torque plus threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Desired filtered throttle torque exceeds the threshold plus the higher of desired throttle torque or modeled throttle torque	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Torque feedback proportional term is out of allowable range or its dual store copy does not match	High Threshold 26.50 Nm Low Threshold -26.50 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Torque feedback integral term magnitude or rate of change is out of allowable range or its dual store copy do not match	High Threshold 49.69 Nm Low Threshold -53.00 Nm Rate of change threshold 3.31 Nm/loop		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of Final Torque feedback proportional plus integral term and its redundant calculation is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold -53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of torque desired throttle area and its redundant calculation is out of bounds given by threshold range	High Threshold 0.50% Low Threshold -0.50%		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of torque model coefficients and its redundant calculation is out of bounds given by threshold range	High Threshold 0.0000270 Low Threshold -0.0000270		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Difference of base friction torque and its redundant calculation is out of bounds given by threshold range	High Threshold 53.00Nm Low Threshold -53.00Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Accessory drive friction torque is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			AC friction torque is greater than commanded by AC control software or less than threshold limit	High Threshold 39.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of Oil temperature delta friction torque and its redundant calculation is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold -53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Generator friction torque is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Supercharger friction torque is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Filtered Torque error magnitude or its increase rate of change is out of allowable range or its dual store copy do not match	High Threshold 53.00 Nm Low Threshold -53.00 Nm Rate of change threshold 3.31 Nm/loop		Engine speed >0rpm MAF, MAP and Baro DTCs are false	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Torque error compensation is out of bounds given by threshold range	High Threshold 53.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Delta Torque Baro compensation is out of bounds given by threshold range	High Threshold 7.98 Nm Low Threshold -2.72 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			1) Difference of reserve torque value and its redundant calculation exceed threshold 2) Reserve request does not agree with operating conditions or Difference of final predicted torque and its redundant calculation exceed threshold 3) Rate of change of reserve torque exceeds threshold, increasing direction only 4) Reserve engine torque above allowable capacity threshold	1) 52.00 Nm 2) NA 3) 52.00 Nm 4) 52.00 Nm		1&2) Torque reserve (condition when spark control greater than optimum to allow fast transitions for torque disturbances) > 53.00 Nm 3&4) Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			AC friction torque is greater than commanded by AC control software	39.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Absolute difference of the calculated spark offset for equivalence ratio and its redundant calculation greater than threshold	5.52 degrees		Engine speed >0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Engine Vacuum and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Absolute difference of the calculated Intake Manifold Pressure during engine event versus during time event is greater than threshold	Table, f(Engine Torque). See supporting tables		Engine speed >0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Min. Axle Torque Capacity is greater than threshold	0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Predicted torque for zero pedal determination is greater than calc'ed limit.	Table, f(Engine, Oil Temp). See supporting tables + 53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Commanded Predicted Axle Torque and its dual store do not match	1 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Steady State Estimated Engine Torque and its dual store are not equal	N/A		AFM not changing from Active to Inactive and preload torque not changing and one loop after React command Engine speed >0rpm	Up/down timer 1988 ms continuous, 0.5 down time multiplier	
			Difference of Weighting factor for number of cylinders fueled and its redundant calculation is above threshold	0.26		Engine run flag = TRUE > 10.00s	Up/down timer 175 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Difference of minimum spark advance limit and its redundant calculation is out of bounds given by threshold range	5.52 degrees		Ignition in unlock/accessory, run or crank	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Difference of commanded spark advance and adjusted delivered is out of bounds given by threshold range	5.52 degrees		Engine speed >0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Estimated Engine Torque and its dual store do not match	53.00 Nm		Engine speed >0rpm	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Estimated Engine Torque without reductions due to torque control and its dual store are not match	53.00 Nm		Engine speed >0rpm	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of desired spark advance for managed torque and its redundant calculation is out of bounds given by threshold range	5.52 degrees		Torque reserve (condition when spark control greater than optimum to allow fast transitions for torque disturbances) > 53.00 Nm	Up/down timer 450 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Absolute difference of Engine Capacity Minimum Running Immediate Brake Torque Excluding Cylinder Sensitivity and its redundant calculation is out of bounds given by threshold range	53.00 Nm		Engine speed >0rpm	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			One step ahead calculation of air-per-cylinder greater than two step ahead calculation by threshold for time	Threshold: Dynamically calculated based on current engine conditions Fault Pending Threshold: 100 ms		Engine speed > 800rpm	Up/down timer 450 ms continuous, 0.5 down time multiplier	
			Rate limited cruise axle torque request and its dual store do not match	97.62 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 163 ms continuous, 0.5 down time multiplier	
			1) Absolute difference of Calculated accelerator pedal position compensated for carpet learn and error conditions and its redundant calculation is out of bounds given by threshold range 2) Absolute difference of Calculated accelerator pedal position compensated for carpet learn and error conditions and its dual store do not equal 3) Absolute difference of Calculated accelerator pedal position and its dual store do not equal	1) 5.00 % 2) NA 3) NA		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Commanded axle torque is greater than its redundant calculation by threshold	780.99 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded axle torque is less than its redundant calculation by threshold	-65535.00 Nm		Ignition in unlock/accessory, run or crank Redundant commanded axle torque < --65535.00 Nm	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded engine torque due to fast actuators and its dual store do not equal	NA		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded engine torque due to slow actuators and its dual store do not equal	NA		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Arbitrated Air-Per-Cylinder filter coefficient is out of bounds given by threshold range	High Threshold 1.000 Low Threshold 0.074		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Launch spark is active but the launch spark redundant path indicates it should not be active	NA		Engine speed < 7000.00 or 7200.00 rpm (hysteresis pair)	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Rate limited vehicle speed and its dual store do not equal	NA		Time since first CAN message with vehicle speed >= 0.500sec	10/20 counts; 25.0msec/count	
			transfer case neutral request from four wheel drive logic does not match with operating conditions	NA		Ignition in unlock/accessory, run or crank Transfer case range valid and not overridden	32/400 counts; 25.0msec/count	
			transfer case neutral and its dual store do not equal	NA		Ignition in unlock/accessory, run or crank	255/6 counts; 25.0msec/count	
			Throttle progression mode and its dual store do not equal	NA		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			TOS to wheel speed conversion factor is out of bounds given by threshold range	High Threshold 1.10 T/C Range Hi 0.10 T/C Range Lo Low Threshold 1.10 T/C Range Hi 0.10 T/C Range Lo		Ignition in unlock/accessory, run or crank	255/6 counts; 25.0msec/count	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			TOS to wheel speed conversion factor and its dual store do not equal	NA		Ignition in unlock/accessory, run or crank	255/6 counts; 25.0msec/count	
			Cylinders active greater than commanded	2 cylinders		Engine run flag = TRUE > 2.00s Number of cylinder events since engine run > 24 No fuel injector faults active	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Absolute difference of Friction torque and its redundant calculation is out of bounds given by threshold range	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Absolute difference of Accessory torque and its redundant calculation is out of bounds given by threshold range	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Absolute difference of Filtered Air-per-cylinder and its redundant calculation is out of bounds given by threshold range	79.12 mg		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Absolute difference between the previous Final Advance and the current Final Advance not Adjusted for Equivalence Ratio is out of bounds given by threshold range	5.52 degrees		Engine speed >0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Desired Throttle Area calculated does not equal its redundant calculation	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Equivalence Ratio torque compensation exceeds threshold	-53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Absolute difference between Equivalence Ratio torque compensation and its dual store out of bounds given bt threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Commanded Predicted Engine Torque and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Zero pedal axle torque is out of bounds given by threshold range	High Threshold 780.99 Nm Low Threshold -65535.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Creep Coast Axle Torque is out of bounds given by threshold range	High Threshold 780.99 Nm Low Threshold -65535.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Torque Learn offset is out of bounds given by threshold range	High Threshold 0.00 Nm Low Threshold 0.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			One step ahead calculation of air-per-cylinder and two step ahead is greater than threshold	80.00 mg		Engine speed >800rpm	Up/down timer 450 ms continuous, 0.5 down time multiplier	
			Difference between Unmanaged Spark and PACS Spark is greater than threshold	5.51 degrees		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Predicted torque for uncorrected zero pedal determination is greater than calc'ed limit.	Table, f(Engine, Oil Temp). See supporting tables + 53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Idle speed control calculated predicted minimum torque request exceeds calculated torque limit	Table, f(Engine, Oil Temp). See supporting tables + 53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Idle speed control calculated predicted minimum torque without reserves exceeds calculated torque limit	Table, f(Engine, Oil Temp). See supporting tables + 53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Difference between Driver Requested Immediate Torque primary path and its secondary exceeds threshold	780.99 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			PTO Torque Request exceeds allowed rate limited PRO Torque Request	6.81 Nm/25ms		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Engine Speed Lores Intake Firing (event based) calculation does not equal its redundant calculation	N/A		Engine speed greater than 0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Engine Speed Lores Intake Firing timing (event based) calculation does not equal its redundant calculation	N/A		Engine speed greater than 0rpm	Up/down timer 150 ms continuous, 0.5 down time multiplier	
			Engine Speed Lores Intake Firing (12.5ms based) calculation does not equal its redundant calculation	N/A		Engine speed greater than 0rpm	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Cold Delta Friction Torque and its dual store do not match	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			1. Driver Predicted Request is greater than its redundant calculation plus threshold 2. Driver Predicted Request is less than its redundant calculation minus threshold	780.99 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Driver Immediate Request is less than its redundant calculation minus threshold	780.99 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			1. Commanded Immediate Request is greater than its redundant calculation plus threshold 2. Commanded Immediate Request is less than its redundant calculation minus threshold	780.99 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Commanded Immediate Response Type is set to Inactive	N/A		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Commanded Immediate Engine Request is greater than its redundant calculation plus threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Commanded Predicted Engine Request is greater than its redundant calculation plus threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded Hybrid Predicted Crankshaft Request is greater than its redundant calculation plus threshold	4096.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Commanded Hybrid Immediate Crankshaft Request is less than its redundant calculation minus threshold	4096.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Engine Predicted Request Without Motor is greater than its redundant calculation plus threshold	52.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Engine Immediate Request Without Motor is greater than its redundant calculation plus threshold	52.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			1. Positive Torque Offset is greater than its redundant calculation plus threshold 2. Positive Torque Offset is less than its redundant calculation minus threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Engine Capacity Minimum Immediate Without Motor is greater than its dual store plus threshold	53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Engine Capacity Minimum Engine Off is greater than threshold	0 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Engine Capacity Minimum Engine Immediate Without Motor is greater than threshold	0 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Regeneration Brake Assist is not within a specified range	Brake Regen Assist < 0 Nm or Brake Regen Assist > 1000.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 2048 ms continuous, 0.5 down time multiplier	Not used Series 11
			Cylinder Spark Delta Correction exceeds the absolute difference as compared to Unadjusted Cylinder Spark Delta	5.51 degrees		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			1. Cylinder Torque Offset exceeds step size threshold 2. Sum of Cylinder Torque Offset exceeds sum threshold	1. 53.00 Nm 2. 53.00 Nm		Ignition in unlock/accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
Control Module Throttle Actuator Position Performance	P2101	1) Detect a throttle positioning error	Difference between measured throttle position and modeled throttle position >	10.00 percent	TPS minimum learn is not active and Throttle is being Controlled and (Engine Running or Ignition Voltage > or Ignition Voltage >)	Run/crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	1. 15 counts; 12.5 ms/count in the primary processor	Trips: 1 Type: A MIL: YES
						11		
						5.5		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Difference between modeled throttle position and measured throttle position >	10.00 percent	Ignition voltage failure is false (P1682)			
		2) Detect throttle control is driving the throttle in the incorrect direction or exceed the reduced power limit	Throttle Position >	46.87 percent	TPS minimum learn is active		2. 11 counts; 12.5 ms/count in the primary processor	
			Throttle Position >	45.87 percent	Reduced Power is True			
					Powertrain relay voltage	> 6.41 Volts		
Throttle return to default	P2119	Throttle unable to return to default throttle position after de-energizing ETC motor.	TPS1 Voltage > AND TPS2 Voltage >	1.977 2.087	Throttle de-energized No TPS circuit faults	Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No 5V reference error or fault for # 4 5V reference circuit (P06A3)	0.4969 sec	Trips: 1 Type: C MIL: NO
Accelerator Pedal Position (APP) Sensor 1 Lo	P2122	Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor	APP1 Voltage <	0.463		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 14 counts continuous; 12.5 ms/count in the main processor	Trips: 1 Type: A MIL: YES

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						No 5V reference error or fault for # 4 5V reference circuit (P06A3)		
Accelerator Pedal Position (APP) Sensor 1 Hi	P2123	Detect a continuous or intermittent short or open in the APP sensor #1 on Main processor	APP1 Voltage >	4.75		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 14 counts continuous; 12.5 ms/count in the main processor	Trips: 1
								Type: A
								MIL: YES
Accelerator Pedal Position (APP) Sensor 2 Lo	P2127	Detect a continuous or intermittent short or open in the APP sensor #2 on Main processor	APP2 Voltage <	0.325		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	19/39 counts or 14 counts continuous; 12.5 ms/count in the main processor	Trips: 1
								Type: A
								MIL: YES
Accelerator Pedal Position (APP) Sensor 2 Hi	P2128	Detect a continuous or intermittent short or open in the APP sensor #2 on Main processor	APP2 Voltage >	2.6		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all	19/39 counts or 14 counts continuous; 12.5 ms/count in the main processor	Trips: 1
								Type: A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						conditions No 5V reference error or fault for # 4 5V reference circuit (P0697)		MIL: YES
Throttle Position (TP) Sensor 1-2 Correlation	P2135	1. Detects a continuous or intermittent correlation fault between TPS sensors #1 and #2 on Main processor	1. Difference between TPS1 displaced and TPS2 displaced > 2. Difference between (normalized min TPS1) and (normalized min TPS2) >	1. 7.022% offset at min. throttle position with a linear threshold to 9.622% at max. throttle position 2. 5.000 % Vref		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions No TPS sensor faults (P0122, P0123, P0222, P0223) No 5V reference error or fault for # 4 5V reference circuit (P06A3)	1 & 2: 79/159 counts or 58 counts continuous; 3.125 ms/count in the main processor	Trips: 1 Type: A MIL: YES
Accelerator Pedal Position (APP) Sensor 1-2 Correlation	P2138	Detects a continuous or intermittent correlation fault between APP sensors #1 and #2 on Main processor	1. Difference between APP1 displaced and APP2 displaced >	1. 5.000% offset at min. pedal position with a linear threshold to 10.000% at max. pedal position		Run/Crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	1 & 2: 19/39 counts intermittent or 15 counts continuous, 12.5 ms/count in the main processor	Trips: 1 Type: A MIL: YES

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			2. Difference between (normalized min APP1) and (normalized min APP2) >	2. 5.000% Vref		No APP sensor faults (P2122, P2123,P2127, P2128) No 5V reference errors or fault for # 3 & # 4 5V reference circuits (P06A3, P0697)		
Injector 1 high side circuit shorted to ground	P2147	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 1 high side circuit shorted to power	P2148	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 2 high side circuit shorted to ground	P2150	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 2 high side circuit shorted to power	P2151	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 3 high side circuit shorted to ground	P2153	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A
Injector 3 high side circuit shorted to power	P2154	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.				
Injector 4 high side circuit shorted to ground	P2156	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to ground		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A				
Injector 4 high side circuit shorted to power	P2157	This DTC checks the circuit for electrical integrity during operation.	The ECM detects that the fuel injector high side is shorted to power		Battery Voltage Engine Run Time	11 ≤ Volts ≤ 32 ≥ 5 Sec P062B not FA or TFTKO	10 failures out of 20 samples 100 ms /sample Continuous	1 trips Type A				
Minimum Throttle Position Not Learned	P2176	TP sensors were not in the minnum learn window after multiple attempts to learn the minimum.	During TPS min learn on the Main processor, TPS Voltage >	0.955		Run/crank voltage or Powertrain relay voltage > 6.41 and reduced power is false, else the failure will be reported for all conditions	2.0 secs	Trips: 1				
								Type: A				
								MIL: YES				
Air Fuel Imbalance Bank 1	P219A	Determines if a cylinder-to-cylinder air-fuel imbalance is present by monitoring the pre and post catalyst O2 sensor voltage characteristics. The pre voltage is used to generate a ratio metric. A normal system will generally result in a negative ratio while a failing system will generally result in a positive ratio. The post voltage is used to generate an X out of Y metric, where Y represents the number of samples and X represents the number of those samples that failed.	Bank 1		System Voltage is NOT < for >=	11.0 Volts 0.2 seconds	Minimum of 1 test per trip Maximum of 10 tests per trip The front O2 sensor voltage is sampled once per cylinder event. Therefore, the time required to complete a single test (when all enable conditions are met) decreases as engine speed increases. For example, 9.0 seconds of data is required at	1 Trip(s) Type A				
			The following criteria apply to:									
			Filtered Ratio	> 2.3					Fuel Level	10.0 percent AND no fuel level sensor fault		
			Exclude AFM (DoD) Ratio data from Ratio value								Yes	Cumulative engine run time
			AFM (DoD) operation required in order to report: AND AFM (DoD) Filtered Ratio						No	Diagnostic runs at Idle regardless of speed, load, air flow, spark advance, and phaser angle:	Engine speed always	< 6500.0 rpm
									> 0.50			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
							1000 rpm while double this time is required at 500 rpm and half this time is required at 2000 rpm.		
					Engine speed during:				
			AND		Normal operation	900 <= rpm <= 6000			
			Post O2 Feature Enabled: AND Filtered Post catalyst O2 voltage is NOT between for more than out of during non-AFM	No 651 and 650 mV 62.5 125 seconds	Intrusive cam	1800 <= rpm <= 2400			
					AFM (DoD)	1000 <= rpm <= 3000			
					AFM (DoD) and intrusive cam	1200 <= rpm <= 2800			
					Post O2 testing	1200 <= rpm <= 3100			
					Engine speed range is less than: during a short term sample	150 rpm			
			OR		Mass Airflow During:				
			for more than out of during AFM	62.5 125 seconds	Normal operation	10 <= g/s <= 500			
					Intrusive cam	1000000 <= g/s <= 0			
					AFM (DoD)	0 <= g/s <= 10000			
		Monitor Strategy Notes: The AFIM Filtered Ratio is derived from the pre-O2 sensor voltage metric known as Variance. Variance is the statistical variation of the O2 sensor voltage over one engine cycle. The reason we use Variance is because it comprehends O2 signal deviation from nominal on a cylinder firing event basis. This metric is representative of the air/fuel imbalance.	NOTE: The Post O2 Logic is enabled only when operating in an enabled Post O2 Cell. The following Post O2 Cells are enabled:	Decel:	No	AFM (DoD) and intrusive cam		0 <= g/s <= 10000	
				Idle:	No	Post O2 testing		0 <= g/s <= 10000	
				Cruise:	No	Cumulative delta mass air flow does not exceed: during a short term sample		2 g/s	
				Light Accel:	No				
				Heavy Accel:	No				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
				No	Filtered Mass Airflow does not change by more than: every 12.5 ms Note: first order lag filter coefficient applied to MAF:	0.25 g/s 0.150	The post catalyst O2 sensor voltage is sampled every 12.5 ms. The cumulative time required for the post O2 portion of the diagnostic to report is 125 seconds.	
			NOTE: The "filtered Post catalyst O2 voltage" referred to above is the result of applying a first order lag filter to the Post O2 voltage used by the closed loop fuel control system. The filter coefficient is:	0.001	Air Per Cylinder During: Normal operation Intrusive cam	250 <= mg/cylinder <= 1200 0 <= mg/cylinder <= 600		
			Note: Injusive phaser control is active, allowing a specified phaser angle during certain operating conditions:		AFM (DoD) AFM (DoD) and intrusive cam	0 <= mg/cylinder <= 700 0 <= mg/cylinder <= 600	Note: If the post O2 feature is enabled, both the front and post portions of the diagnostic must complete before reporting. If the post O2 feature is not enabled, only the front portion must complete before reporting.	
				No	Post O2 testing	0 <= mg/cylinder <= 700		
			The AFIM Filtered Ratio metric is the difference between the current, measured Variance metric and a 17x17 table lookup value (the threshold), divided by a second 17 x 17 table lookup value (the normalizer), and finally multiplied by a Quality Factor, also a 17 x 17 table lookup value (the latter ranges between 0 and 1, based on robustness to false diagnosis in the current operating region). The reason we use a ratio of the Variance is so that we can normalize the failure metric over various engine speed and load regions since engine speed and load directly impact the magnitude of the Variance metric.	The Quality Factor (QF) calibrations are located in a 17x17 lookup table versus engine speed and load (see Supporting Tables). A QF of "1" is an indication that we were able to achieve at least 4sigma/2sigma robustness in that speed/load region. QF values less than "1" indicate that we don't have 4sigma/2sigma robustness in that region. The quality of the data is determined via statistical analysis of Variance data. QF values less than 0.99 identify regions where diagnosis is not possible.	Filtered APC shall not change by more than: between 12.5 ms samples. Note: first order lag filter coefficient applied to APC:	0.30 percent 0.100		
					APC range during short term sample shall not exceed:	60 mg/cylinder		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Spark Advance During: Normal operation $5 \leq \text{degrees} \leq 55$ Intrusive cam $5 \leq \text{degrees} \leq 55$ AFM (DoD) $5 \leq \text{degrees} \leq 55$ AFM (DoD) and intrusive cam $5 \leq \text{degrees} \leq 55$			
					Throttle Area (percent of max) During: Normal operation $3 \leq \text{percent} \leq 200$ Intrusive cam $0 \leq \text{percent} \leq 200$ AFM (DoD) $0 \leq \text{percent} \leq 200$ AFM (DoD) and intrusive cam $0 \leq \text{percent} \leq 200$			
					Intake Cam Phaser Angle During: Normal operation $0 \leq \text{degrees} \leq 25$ Intrusive cam $20 \leq \text{degrees} \leq 100$ AFM (DoD) $0 \leq \text{degrees} \leq 100$ AFM (DoD) and intrusive cam $0 \leq \text{degrees} \leq 100$			
					Exhaust Cam Phaser Angle During: Normal operation $0 \leq \text{degrees} \leq 25$ Intrusive cam $15 \leq \text{degrees} \leq 100$			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					AFM (DoD)	$0 \leq \text{degrees} \leq 100$		
					AFM (DoD) and intrusive cam	$0 \leq \text{degrees} \leq 100$		
					Average O2 voltage change since last sample	< 2 millivolts		
					An AFM (DoD) state change will cause the current sample to be discarded:	No		
					Quality Factor	≥ 0.99 in the current operating region		
					AIR pump not on			
					CASE learn not active			
					EGR - no device control, no intrusive diagnostics			
					EVAP - no device control, no intrusive diagnostics			
					Engine OverSpeed Protection Not Active			
					Idle speed control normal			
					No EngineMisfireDetected_FA			
					No MAP_SensorFA			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					No MAF_SensorFA No ECT_Sensor_FA No TPS_ThrottleAuthorityDefaulted No FuelInjectorCircuit_FA No AIR System FA No EvapPurgeSolenoidCircuit_FA No EvapFlowDuringNonPurge_FA No EvapVentSolenoidCircuit_FA No EvapSmallLeak_FA No EvapEmissionSystem_FA PTO Not Active Injector base pulse width above min limit Fuel Control Status			
					Closed Loop Long Term FT Enabled	for >= 1.2 seconds Please see "Closed Loop Enable Criteria" and "Long Term FT Enable Criteria" in Supporting Tables.		
					Rapid Step Response (RSR):			
					RSR will trigger if the ratio result from the last test is or for AFM (DoD) is AND it exceeds the last filtered ratio by at least: or for AFM (DoD) by at least: Once triggered, the filtered ratio is reset to: or for AFM (DoD) is reset to:	>= 1.5 >= 0.5 2.0 1.0	For RSR or FIR, 10 tests must complete before the diagnostic can report.	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			OR		Engine Run Time	> 0.00 seconds		
			Difference between baro sensor reading and estimated baro	> 20.0 kPa				
			when distance since last estimated baro update	> 0.06 miles				
			<u>Engine Not Rotating Case:</u>					
			Barometric Pressure OR	< 50.0 kPa	Time between current ignition cycle and the last time the engine was running		4 failures out of 5 samples	
			Barometric Pressure	> 115.0 kPa			1 sample every 12.5 msec	
					Engine is not rotating	> 10.0 seconds		
					No Active DTCs:	EngModeNotRunTmErr MAP_SensorFA AAP_SnsrFA SCIAP_SensorFA AAP2_SnsrFA		
					No Pending DTCs:	MAP_SensorCircuitFP AAP_SnsrCktFP SCIAP_SensorCircuitFP		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						AAP2_SnsrCktFP		
Barometric Pressure (BARO) Sensor Circuit Low	P2228	Detects a continuous short to low or open in either the signal circuit or the BARO sensor.	BARO Voltage	< 34.5 % of 5 Volt Range (1.7 Volts = 43.9 kPa)	Engine Run Time	> 0.00 seconds	320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Barometric Pressure (BARO) Sensor Circuit High	P2229	Detects an open sensor ground or continuous short to high in either the signal circuit or the BARO sensor.	BARO Voltage	> 90.0 % of 5 Volt Range (4.5 Volts = 115.0 kPa)	Engine Run Time	> 0.00 seconds	320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Barometric Pressure (BARO) Sensor Circuit Intermittent	P2230	Detects a noisy or erratic barometric pressure input	Difference between the current Baro sensor reading and the previous Baro sensor reading	> 10.0 kPa	Vehicle Speed No Active DTCs:	< 512 KPH AmbientAirPressCktFA ECT_Sensor_FA IAT_SensorFA MAF_SensorFA AfterThrottlePressure_NA TPS_FA TPS_Performance_FA VehicleSpeedSensorError	320 failures out of 400 samples 1 sample every 12.5 msec	Type B 2 trips
Turbo/Super Charger Bypass Valve - Mechanical	P2261	Detect Stuck Closed Bypass Valve	Between start and end time is high pass filtered accumulated Air mass Flow or Boost Pressure larger then Thresholds	0.25 Second < Accumulation time < 1.00 Second	Diagnosis Enabled Engine Speed Pressure ratio over the compressor	Enabled >= 1500 rpm > KtBSTD_r_ExcvsBstPr esLim Enable condition kept true for 0.8 seconds extra	7 Failed tests out of 10 Tests 1 sample every 25ms	Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			Filter Frequency Filtered Air Mass Flow Filtered Boost Pressure	10.00 Hz > 40.000 g/s > 40.00 kPa	Relative Boost Pressure (Boost - Ambient) and Negative Transient in Manifold Air Pressure Bypass Valve Commanded Opened No Active DTCs:	See Tables in Supporting Tables Sheet IF (RelativeBoost < 0.0 kPa OR DerivativeMAP > 10.00 kPa/s) [FALSE] Else (RelativeBoost >= 25.0 kPa AND DerivativeMAP <= - 150.00 kPa) [TRUE] TC_BoostPresSnsrFA MAF_SensorFA BSTR_b_TurboBypassCktFA		
Fuel Conductivity Out Of Range (water in fuel)	P2269	Detects Sensor Frequency Signal	Flex Fuel Sensor Output Frequency	> 185 Hertz	Powertrain Relay	> 11.0 Volts < 32.0 Volts	50 failures out of 63 samples 100 ms loop Continuous	2 trip(s) Type B
O2 Sensor Signal Stuck Lean Bank 1 Sensor 2	P2270	This DTC determines if the post catalyst O2 sensor is stuck in a normal lean voltage range and thereby can no longer be used for post oxygen sensor fuel control or for catalyst monitoring. The diagnostic is an intrusive test (during coast) which increases the delivered fuel to achieve the required rich threshold.	Post O2 sensor signal AND The Accumulated mass air flow monitored during the Stuck Lean Voltage Test	< 825 mvolts > 66 grams	No Active DTC's	TPS_ThrottleAuthority Defaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA	Frequency: Once per trip Note: if NaPOPD_b_Reset FastRespFunc= FALSE for the given Fuel Bank OR NaPOPD_b_Rapid ResponseActive = TRUE, multiple tests per trip are	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA EthanolCompositionSensor_FA B1S2 Failed this key cycle P013A, P013B, P013E, P013F, P2270 or P2271 System Voltage 10.0 < Volts < 32.0 ICAT MAT Burnoff delay = Not Valid = Not Valid, See definition of Green Sensor Delay Criteria (B1S2) in Supporting Tables tab. Green O2S Condition Low Fuel Condition Diag = False Engine Speed to initially enable test 1175 ≤ RPM ≤ 2200 Engine Speed range to keep test enabled (after initially enabled) Engine Airflow 1100 ≤ RPM ≤ 2300 2 ≤ gps ≤ 10 Vehicle Speed to initially enable test 40.4 ≤ MPH ≤ 74.6 Vehicle Speed range to keep test enabled (after initially enabled) 35.4 ≤ MPH ≤ 82.0 mph Closed loop integral 0.80 ≤ C/L Int ≤ 1.07	allowed.	

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Closed Loop Active = TRUE Evap not in control of purge Ethanol not in estimate mode Post fuel cell = enabled EGR Intrusive diagnostic = not active All post sensor heater delays = not active O2S Heater on Time ≥ 180.0 sec Predicted Catalyst temp $500 \leq \text{°C} \leq 900$ Fuel State = DFCO possible			
					All of the above met for at least 3.0 seconds, and then the Force Cat Rich intrusive stage is requested.			
O2 Sensor Signal Stuck Rich Bank 1 Sensor 2	P2271	This DTC determines if the post catalyst O2 sensor is stuck in a normal rich voltage range and thereby can no longer be used for post oxygen sensor fuel control or for catalyst monitoring. The diagnostic is an intrusive test which requests the DFCO mode to achieve the required lean threshold.	Post O2 sensor signal AND The Accumulated mass air flow monitored during the Stuck Rich Voltage Test	> 100 mvolts > 31 grams	No Active DTC's	TPS_ThrottleAuthority Defaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA	Frequency: Once per trip Note: if NaPOPD_b_Reset FastRespFunc= FALSE for the given Fuel Bank OR NaPOPD_b_Rapid ResponseActive = TRUE, multiple tests per trip are allowed.	2 trips Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					B1S2 Failed this key cycle System Voltage ICAT MAT Burnoff delay Green O2S Condition Low Fuel Condition Diag Engine Speed Engine Airflow Vehicle Speed Closed loop integral Closed Loop Active Evap Ethanol Post fuel cell Power Take Off EGR Intrusive diagnostic All post sensor heater delays O2S Heater on Time Predicted Catalyst temp Fuel State	EthanolCompositionSensor_FA P013A, P013B, P013E, P013F or P2270 10.0 < Volts < 32.0 = Not Valid = Not Valid, See definition of Green Sensor Delay Criteria (B1S2) in Supporting Tables tab. = False 1175 ≤ RPM ≤ 2200 2 ≤ gps ≤ 10 40.4 ≤ MPH ≤ 74.6 0.80 ≤ C/L Int ≤ 1.07 = TRUE not in control of purge not in estimate mode = enabled = not active = not active = not active ≥ 180.0 sec 500 ≤ °C ≤ 900 = DFCO possible		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					DTC's Passed = P2270 (and P2272 if applicable) DTC's Passed = P013E (and P014A if applicable) DTC's Passed = P013A (and P013C if applicable)			
					After above conditions are met: DFCO mode is continued (wo driver initiated pedal input).			
SIDI High Pressure Pump	P228C	Detects measured fuel rail pressure bias too low from desired fuel pressure.	Desired Pressure - Measure Pressure	≥ 3.00 Mpa	Battery Voltage Low Side Fuel Pressure Engine Run Time	11 <= Volts <= 32 > 0.250 MPa >= KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Engine is not cranking	Pressure Error - 750 failures out of 938 samples	1 trips Type A
					Additional Enable Conditions: High Pressure Pump is enabled Estimate fuel rail pressure is valid Green Engine (In assembly plant) is not enabled			

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Barometric Pressure Inlet Air Temp Fuel Temp DTCs not Active:	Not LowFuelConditionDiagnostic Low side Fuel Pump is on Injector Flow Test is not active Device control commanded pressure is false Device control pump ckt enabled on is false Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0 >= 70.0 >= -10.0 -10 ≤ Temp degC ≤ 100 FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA FHPR_b_PumpCkt_FA		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
						Ethanol Composition Sensor FA PowertrainRelayFault		
SIDI High Pressure Pump	P228D	Detects measured fuel rail pressure bias too high from desired fuel pressure	Desired Pressure - Measure Pressure	≤ -3.00 Mpa	Battery Voltage	11 <= Volts <= 32	Pressure Error - 750 failures out of 938 samples	1 trips Type A
					Low Side Fuel Pressure	> 0.250 MPa		
					Engine Run Time	>= KtFHPD_t_PumpCntrlEngRunThrsh(see supporting tables) Enabled when a code clear is not active or not exiting device control Engine is not cranking		
Additional Enable Conditions:								
						High Pressure Pump is enabled Estimate fuel rail pressure is valid Green Engine (In assembly plant) is not enabled Not LowFuelConditionDiagnostic Low side Fuel Pump is on Injector Flow Test is not active Device control commanded pressure is false Device control pump ckt enabled on is false		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					Barometric Pressure Inlet Air Temp Fuel Temp DTCs not Active:	Engine movement detected is true (Function of crankshaft and camshaft position) Manufacturers enable counter is 0 >= 70.0 >= -10.0 -10 ≤ Temp degC ≤ 100 FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO CrankSensorFA CamSensorFA IAT_SensorFA IAT2_SensorFA ECT_Sensor_FA FHPR_b_PumpCkt_FA Ethanol Composition Sensor FA PowertrainRelayFault		
Transmission Control Torque Request Circuit	P2544	Determines if the torque request from the TCM is valid	<u>Protect error</u> - Serial Communication message - (\$199 PTEI3) OR <u>Rolling count error</u> - Serial Communication message (\$199 - PPEI3) rolling count value	Message <> two's complement of message Message <> previous message rolling count value + one	Diagnostic enabled/ disabled	Enabled	>= 16 Protect errors during key cycle. Performed every 12.5 msec >= 6 Rolling count errors out of ten samples.	2 trip(s) Type B

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
							Performed every 12.5 msec	
			OR					
			RAM error - Serial Communication message (\$199 - PPEI3)	Transmission torque request value or request type dual store not equal	Power Mode	= Run		
					Engine Running	= True	>= 3 RAM errors out of 6 samples. Performed every 12.5 msec	
					Run/Crank Active	> 0.50 Sec		
			OR					
			Range Error - Serial Communication message - (\$199 - PTEI3) TCM Requested Torque Increase	> 337 Nm			>= 3 out of 10 samples. Performed every 12.5 msec	
			OR					
			Multi-transition error - Trans torque intervention type request change				>= 3 multi-transitions out of 5 samples. Performed every 200 msec	
				Requested torque intervention type toggles from not increasing request to increasing request				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
ECM/PCM Internal Engine Off Timer Performance	P2610	<p>This DTC determines if the engine mode not running timer does not initialize or count properly. There are two tests to ensure proper functioning of the timer: Count Up Test (CUT) and Range Test (RaTe).</p> <p>Count Up Test (CUT): Verifies that the HWIO timer is counting up with the proper increment.</p> <p>Range Test (RaTe): Runs a mirror timer to the HWIO timer. The mirror timer is started when the Engine Mode Not Run Timer is started. When the engine starts or when a controller shutdown is</p>	<p>Count Up Test:</p> <p>Time difference between the current read and the previous read of the Timer</p> <p>Range Test:</p> <p>The variation of the HWIO timer and mirror timer is</p> <p>at controller shutdown.</p>	<p>> 1.50 seconds</p> <p>> 25 %</p>	<p>IAT Temperature</p> <p>No active DTCs:</p> <p>Count Up Test:</p> <p>Ignition key off OR Engine off</p> <p>Range Test:</p> <p>ECM is powering down</p>	<p>-256 °C ≤ Temperature ≤ 256 °C</p> <p>IAT_SensorFA</p>	<p>Count Up Test:</p> <p>8 failures out of 40 samples</p> <p>1 sec / sample</p> <p>Continuous from key off or engine off until controller shutdown.</p> <p>Range Test:</p> <p>One time when the controller is powered down.</p>	<p>2 trips Type B</p> <p>DTC sets on next key cycle if failure detected.</p>

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
		requested, the HWIO timer and mirror timer are compared.						
O2Sensor Circuit Range/ Performance Bank 1 Sensor 1	P2A00	This DTC determines if the O2 sensor voltage is not meeting the voltage criteria to enable closed loop fueling.	Closed Loop O2S ready flag	= False	No Active DTC's System Voltage Engine Speed Engine Airflow Engine Coolant Engine Metal Overtemp Active Converter Overtemp Active Fuel State AFM Status Predicted Exhaust Temp (B1S1) Engine run time Fuel Enrichment <u>All of the above met for</u>	TPS_ThrottleAuthority Defaulted MAP_SensorFA ECT_Sensor_FA FuelInjectorCircuit_FA P0131, P0151 P0132, P0152 10.0 < Volts < 32.0 700 ≤ RPM ≤ 3000 3.0 ≤ gps ≤ 45.0 ≥ 70.0 °C = False = False DFCO not active = All Cylinders active ≥ 0.0 °C > 100 seconds = Not Active > 5 seconds	200 failures out of 250 samples. Frequency: Continuous 100msec loop	2 trips Type B
			A) O2S signal must be	< 1100 mvolts				
			To set Closed Loop ready flag	= True				
			Closed Loop O2S ready flag	= True				
			B) Once set to ready O2S cannot be	> 1100 mvolts > 5.0 seconds				
			Then set Closed Loop ready flag	= False				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.	
Control Module Communication Bus A Off	U0073	This DTC monitors for a BUS A off condition	Bus off failures	≥ 5 counts	CAN hardware is bus OFF for	> 0.5000 seconds	Diagnostic runs in 12.5 ms loop	2 Trip(s)	
			out of these samples	≥ 5 counts	Diagnostic enable timer	> 3.0000 seconds		Type B	
Lost Communication With TCM	U0101	This DTC monitors for a loss of communication with the transmission control module	Message is not received from controller for this amount of time.	Type B time = 10s Type C time = 12s Torque Security Ucode = varied and possibly much shorter time.	Run/Crank Voltage	11 volts ≤ Voltage ≤ 32 volts	The fail diagnostic runs in the 6.25 ms loop with pass conditions reported to the DFIR in the 1000ms loop.	2 Trip(s)	
					Power mode is RUN			Type B	
					Communication bus is not OFF				
					or is typed as a C code				
					Normal Communication is enabled				
					Normal Transmit capability is TRUE				
					The diagnostic system is not disabled				
					The bus has been on for		> 3.0000 seconds		
Lost Communication With Fuel Pump Control Module	U0109	This DTC monitors for a loss of communication with the fuel pump control module	Message is not received from controller for this amount of time.	Type B time = 10s Type C time = 12s Torque Security Ucode = varied and possibly much shorter time.	Run/Crank Voltage	11 volts ≤ Voltage ≤ 32 volts	The fail diagnostic runs in the 6.25 ms loop with pass conditions reported to the DFIR in the 1000ms loop.	2 Trip(s)	
					Power mode is RUN			Type B	
					Communication bus is not OFF				
					or is typed as a C code				
					Normal Communication is enabled				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.		
					Normal Transmit capability is TRUE					
					The diagnostic system is not disabled					
					The bus has been on for	> 3.0000 seconds				
					A message has been selected to monitor.					
Lost Communication With Body Control Module	U0140	This DTC monitors for a loss of communication with the Body Control Module.	Message is not received from controller for this amount of time.	Type B time = 10s Type C time = 12s Torque Security Ucode = varied and possibly much shorter time.	Run/Crank Voltage	11 volts ≤ Voltage ≤ 32 volts	The fail diagnostic runs in the 6.25 ms loop with pass conditions reported to the DFIR in the 1000ms loop.	1 Trip(s)		
						Power mode is RUN			Type C	
						Communication bus is not OFF				
						or is typed as a C code				
						Normal Communication is enabled				
						Normal Transmit capability is TRUE				
						The diagnostic system is not disabled				
						The bus has been on for		> 3.0000 seconds		
						A message has been selected to monitor.				
Lost Communication With Anti-Lock Brake System (ABS) Control Module	U0121	This DTC monitors for a loss of communication with the ABS control module.	Message is not received from controller for this amount of time.	Type B time = 10s Type C time = 12s Torque Security Ucode = varied and possibly much shorter time.	Run/Crank Voltage	11 volts ≤ Voltage ≤ 32 volts	The fail diagnostic runs in the 6.25 ms loop with pass conditions reported to the DFIR in the 1000ms loop.	1 Trip(s)		
						Power mode is RUN			Type C	
						Communication bus is not OFF				

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					or is typed as a C code			
					Normal Communication is enabled			
					Normal Transmit capability is TRUE			
					The diagnostic system is not disabled			
					The bus has been on for	> 3.0000 seconds		
					A message has been selected to monitor.			

Support Tables

P0300-P0308: Idle Cyl Mode
OR (decil index > Idle Cyl Mode AND > Idle Cyl Mode ddt Tables)

	400	500	600	650	700	800	900	1000	1100	1200	1400	1600	1800
10	3500	3250	3000	2550	2100	1700	1200	900	650	500	300	275	225
12	3250	3000	2750	2375	2000	1600	1050	700	550	450	275	250	200
15	3100	2800	2500	2150	1800	1500	1000	750	600	500	260	250	175
18	3000	2600	2200	2000	1800	1450	1000	800	650	500	250	200	150
22	4000	3200	2400	2150	1900	1500	1000	850	650	500	300	225	160
26	4200	3400	2600	2300	2000	1500	1000	900	700	500	300	250	175
31	4400	3600	2800	2500	2200	1500	1300	1000	750	550	350	300	200
35	4500	3700	2900	2600	2300	1625	1475	1200	875	600	425	350	225
38	4600	3800	3000	2700	2400	1750	1650	1400	1000	600	450	400	250
42	4700	3900	3100	2838	2575	1875	1775	1500	1100	600	475	425	275
45	4800	4000	3200	2975	2750	2000	1900	1600	1200	700	500	450	300
50	4900	4100	3300	3088	2875	2125	2025	1700	1300	800	525	475	325
54	5000	4200	3400	3200	3050	2250	2150	1800	1400	900	550	500	350
60	5100	4300	3500	3313	3125	2375	2275	1900	1500	1000	575	525	375
65	5200	4400	3600	3425	3250	2500	2400	2000	1600	1100	600	550	400
71	5300	4500	3700	3538	3375	2625	2500	2100	1700	1200	750	650	450
77	5400	4600	3800	3650	3500	2750	2600	2200	1800	1300	900	750	500

P0300-P0308: Idle Cyl Mode ddt

	400	500	600	650	700	800	900	1000	1100	1200	1400	1600	1800
10	3500	3250	3000	2550	2100	1900	1400	900	750	500	300	275	225
12	3250	3000	2750	2375	2000	1800	1200	800	650	450	275	250	200
15	3100	2800	2500	2150	1800	1700	1250	900	700	500	250	250	175
18	3000	2600	2200	2000	1800	1600	1400	1000	800	550	250	200	150
22	3200	2800	2400	2150	1900	1600	1500	1200	900	600	300	275	200
26	3400	3000	2600	2300	2000	1600	1600	1400	1000	600	400	300	250
31	3700	3250	2800	2500	2200	1800	1700	1500	1000	600	450	350	300
35	3850	3375	2900	2600	2300	1950	1550	1100	600	500	400	400	325
38	4000	3500	3000	2700	2400	2250	2200	1600	1200	600	500	425	350
42	4150	3625	3100	2838	2575	2375	2225	1700	1300	600	500	450	375
45	4300	3750	3200	2975	2750	2500	2250	1800	1400	700	500	475	400
50	4450	3875	3300	3088	2875	2625	2375	1900	1500	800	525	500	425
54	4600	4000	3400	3200	3050	2750	2500	2000	1600	900	550	525	450
60	4750	4125	3500	3313	3125	2875	2650	2100	1700	1000	575	550	475
65	4900	4250	3600	3425	3250	3000	2800	2200	1800	1100	600	575	500
71	5050	4375	3700	3538	3375	3125	2900	2300	1900	1250	750	650	575
77	5200	4500	3800	3650	3500	3250	3000	2400	2000	1500	900	800	650

P0300-P0308: Cyl Mode
OR (decil index > Cyl Mode AND > Cyl Mode ddt Tables)

	400	500	600	700	800	900	1000	1100	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3500	4000	4500	5000	5500	6000	6500	7000	
9	3750	3500	3250	2200	1800	1400	1000	750	550	350	300	275	160	120	130	95	85	75	60	45	45	35	25	22	22	22	22
10	3500	3250	3000	2100	1700	1200	900	650	500	300	275	225	150	115	120	85	70	65	55	40	40	30	22	20	20	20	20
12	3250	3000	2750	2000	1600	1050	700	550	450	275	250	200	135	110	90	80	65	50	50	35	35	27	20	19	19	19	19
15	3100	2800	2500	1800	1500	1000	750	600	500	260	250	175	130	100	80	80	60	45	45	30	30	24	18	18	18	18	18
18	3000	2600	2200	1800	1450	1000	800	650	500	250	200	150	115	90	85	75	60	45	35	27	25	22	17	17	17	17	17
22	4000	3200	2400	1900	1500	1000	850	650	500	300	225	160	125	80	70	50	45	40	30	25	22	18	16	16	16	16	16
26	4200	3400	2600	2000	1500	1000	900	700	500	300	250	175	125	90	70	55	50	40	30	23	22	18	15	15	15	15	15
31	4400	3600	2800	2200	1500	1300	1000	750	550	350	300	250	200	150	110	80	60	50	40	40	25	22	20	15	14	14	14
38	4600	3800	3000	2400	1750	1650	1400	1000	750	500	400	250	175	120	100	70	55	40	45	32	22	20	16	15	15	15	15
45	4800	4000	3200	2750	2000	1900	1600	1200	1000	600	450	300	250	175	150	125	80	70	60	35	25	21	17	16	16	16	16
54	5000	4200	3400	3000	2250	2150	1800	1400	1100	700	550	400	350	250	200	150	120	90	65	48	32	25	18	18	18	18	18
65	5200	4400	3600	3250	2500	2400	2000	1600	1200	800	650	500	400	300	250	175	150	120	75	55	38	30	23	20	20	20	20
77	5400	4600	3800	3500	2750	2600	2200	1800	1300	900	750	600	450	400	300	225	200	150	100	65	45	37	29	25	25	25	25
91	5600	4800	4000	3750	3000	2800	2400	1850	1400	1000	850	600	500	450	350	350	300	250	175	125	80	55	45	36	30	30	30
107	5750	5000	4250	4000	3250	3000	2600	1900	1500	1100	950	700	600	550	450	350	300	200	150	90	65	50	40	35	35	35	35
135	5900	5200	4500	4250	3500	3250	2800	1950	1600	1200	1000	800	700	650	550	400	350	250	200	110	85	60	50	45	45	45	45
177	6050	5400	4750	4500	3750	3500	3000	2000	1750	1300	1050	900	800	750	650	450	400	275	225	125	100	70	65	55	55	55	55

P0300-P0308: Cyl Mode ddt

	400	500	600	700	800	900	1000	1100	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3500	4000	4500	5000	5500	6000	6500	7000	
9	3750	3500	3250	2200	2000	1600	1000	850	550	350	300	275	160	130	130	95	90	75	65	55	50	40	35	30	30	30	30
10	3500	3250	3000	2100	1900	1400	900	750	500	300	275	225	150	120	120	90	80	65	60	50	45	35	30	25	25	25	25
12	3250	3000	2750	2000	1800	1200	800	650	450	275	250	200	145	110	100	90	75	55	55	40	40	30	25	22	22	22	22
15	3100	2800	2500	1800	1700	1250	900	700	500	250	250	175	140	105	95	90	70	55	50	35	35	30	22	20	20	20	20
18	3000	2600	2200	1800	1650	1400	1000	900	550	300	200	150	125	100	90	80	70	55	45	30	30	25	20	18	18	18	18
22	3200	2800	2400	1900	1600	1500	1200	1100	600	400	300	200	150	120	100	70	60	50	40	30	25	22	18	17	17	17	17
26	3400	3000	2600	2000	1600	1600	1400	1200	750	500	350	250	200	160	120	75	65	50	45	30	25	22	17	16	16	16	16
31	3700	3250	2800	2200	1800	1700	1500	1250	800	600	450	300	250	200	150	90	75	50	45	32	28	24	16	15	15	15	15
38	4000	3500	3000	2400	2250	2200	1600	1300	1000	800	550	350	325	250	200	125	95	70	45	35	32	28	22	18	17	17	17
45	4300	3750	3200	2750	2500	2250	1800	1400	1200	1000	650	500	400	300	250	175	125	100	50	40	33	30	26	22	20	20	20
54	4600	4000	3400	3000	2750	2500	2000	1600	1300	1200	900	700	500	400	300	225	150	120	75	50	38	32	27	25	25	25	25
65	4900	4250	3600	3250	3000	2800	2200	1800	1400	1200	900	600	500	400	300	200	135	110	70	50	43	37	30	30	30	30	30
77	5100	4500	3800	3500	3000	2400	2000	1600	1400	1100	700	600	500	300	225	175	135	95	65	53	45	35	35	35	35	35	35
91	5500	4750	4000	3750	3500	3200	2600	2050	1900	1800	16																

Support Tables

P0300-P0308: Rev Mode Table

OR (decel index > Rev Mode Table)

	1100	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3500	4000	4500	5000	5500	6000	6500	7000
load	9	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	10	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	12	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	15	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	18	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	22	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	26	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	31	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	38	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	45	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	54	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	65	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	77	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	91	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	107	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	135	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	177	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767

P0300-P0308: AFM Mode Table

OR (decel index > AFM Table if active fuel management)

	400	500	600	700	800	900	1000	1100	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3500
load	0	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	6	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
Load	13	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	19	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	25	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	31	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	38	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	44	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	50	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	56	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	63	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	69	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	75	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	81	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	88	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	94	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767
	100	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767	32767

P0300-P0308: Zero torque engine load

Zero Torque: All Cylinders active

RPM	Pct load
400	14.00
500	13.00
600	12.30
700	11.50
800	11.00
900	10.60
1000	10.20
1100	9.90
1200	9.70
1400	9.50
1600	9.50
1800	9.50
2000	9.50
2200	9.80
2400	10.10
2600	10.40
2800	10.70
3000	11.00
3500	14.63
4000	18.26
4500	21.88
5000	25.51
5500	29.14
6000	32.77
6500	36.40
7000	40.03

Baro KPa	Multiplier
65	0.82
70	0.85
75	0.88
80	0.93
85	0.95
90	0.95
95	0.97
100	1.00
105	1.03

Zero Torque: Active Fuel Management (AFM)

RPM	Pct Load
400	14.00
500	13.00
600	12.30
700	11.50
800	11.00
900	10.60
1000	10.20
1100	9.90
1200	9.70
1400	9.50
1600	9.50
1800	9.50
2000	9.50
2200	9.80
2400	10.10
2600	10.40
2800	10.70
3000	11.00
3500	14.63
4000	18.26
4500	21.88
5000	25.51
5500	29.14
6000	32.77
6500	36.40
7000	40.03

Note: Zero torque is adjusted for Baro. Misfire thresholds are relative to (maximum air density PID \$1188 SAE xxx) and do not shift appreciably with altitude compared to (current density as defined PID \$04 SAE 1979)

Catalyst Damaging Misfire Percentage

	0	1000	2000	3000	4000	5000	6000	7000
load	0	22.5	22.5	22.5	20.0	4.7	4.7	4.7
	10	22.5	22.5	22.5	20.0	4.7	4.7	4.7
Load	20	22.5	22.5	20.0	16.7	4.7	4.7	4.7
	30	22.5	22.5	20.0	16.7	14.3	4.7	4.7
	40	22.5	20.0	16.7	14.3	9.1	4.7	4.7
	50	20.0	16.7	14.3	12.5	8.3	4.7	4.7
	60	16.7	14.3	12.5	10.0	7.7	4.7	4.7
	70	14.3	12.5	10.0	7.1	6.3	4.7	4.7
	80	12.5	10.0	8.3	6.3	5.0	4.7	4.7
	90	10.0	8.3	6.3	5.0	4.7	4.7	4.7
	100	8.3	6.3	5.0	4.7	4.7	4.7	4.7

Support Tables

RoughRoadSource = CeRRDR_e_TOSS
Rough Road Threshold

Trans Speed	Engine Speed																		
	600	800	1000	1200	1400	1600	1800	2000	2200	2400	2600	2800	3000	3500	4000	4500	5000	5500	6000
100	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
200	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
300	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
400	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
500	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
600	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
700	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
800	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
900	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1000	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1100	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1200	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1300	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1400	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

RoughRoadSource = CeRRDR_e_WheelSpeedInECM or CeRRDR_e_SerialDataFromABS
Rough Road Threshold

Kph	0	12	24	36	48	60	72	84	96	108	120	132	144	158	170	181	194
Accel	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

P0114: IAT Intermittent Weight Factor

X axis is Filtered Intake Air Temperature in Deg C

Temp	-40	0	40	80	120	160	200
	1.00	1.00	1.00	1.00	1.00	1.00	1.00

P0101, P0106, P0121, P012B, P0236, P1101: IFRD Residual Weighting Factors

RPM	0	400	800	1200	1600	2000	2400	2800	3200	3600	4000	4400	4800	5200	5600	6000	6200
TPS Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
MAF Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
MAF Residual Weight Factor based on MAF Estimate	0.0	15.0	30.0	45.0	60.0	75.0	90.0	105.0	120.0	135.0	150.0	165.0	180.0	195.0	210.0	230.0	250.0
MAP1 Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
MAP2 Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
MAP3 Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
TIAP1 Residual Weight Factor based on RPM	0.750	0.750	0.750	0.750	0.850	1.000	1.000	1.000	1.000	1.000	0.800	0.800	0.800	0.800	0.800	0.800	0.800
SCIA1 Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
SCIA2 Residual Weight Factor based on RPM	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Boost Residual Weight Factor based on % of Boost	0.00	0.06	0.13	0.19	0.25	0.31	0.38	0.44	0.50	0.56	0.63	0.69	0.75	0.81	0.88	0.94	1.00

P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Offset based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min Air Flow based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	17.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0	32.0

P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min MAP based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	110.0	130.0	135.0	140.0	140.0	145.0	150.0	150.0	150.0

P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Offset based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	0.0	1.5	3.5	6.0	9.0	12.0	16.0	20.0	25.0

P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max Air Flow based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	6.0	9.0	13.0	16.0	20.0	24.0	28.0	31.0	32.0

P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max MAP based on RPM

RPM	1000	1750	2500	3250	4000	4750	5500	6250	7000
	55.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0

Support Tables

P0128: Maximum Total Energy transferred to Cooling System for IAT and Start-up ECT conditions

Z axis is the cooling system energy failure threshold (grams)
X axis is ECT Temperature at Power up (° C)
Y axis is IAT min during test (° C)

	IAT Range		-40	-28	-16	-4	8	20	32	44	56	68	80
	Low	Hi											
Primary	10.0 ° C	52.0 ° C	6636	6636	6636	6636	6636	5640	4644	3648	2652	1656	1656
Alternate	-7.0 ° C	10.0 ° C	7280	7280	7280	6320	5360	4400	3440	2480	1520	1520	1520

P0133 - O2S Slow Response Bank 1 Sensor 1* Pass/Fail Threshold table

Z axis is the pass/fail result (see note below)
X axis is Lean to Rich response time (msec)
Y axis is Rich to Lean response time (msec)
Note: If the cell contains a "0" then the fault is not indicated, if it contains a "1" a fault is indicated

	0.000	0.010	0.021	0.033	0.045	0.057	0.068	0.080	0.092	0.104	0.115	0.127	0.139	0.150	0.162	0.174	1.000
0.000	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.010	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.021	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.032	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.043	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.055	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.065	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.077	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.088	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.100	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.110	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.121	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.133	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.144	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.155	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
0.166	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0
1.000	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

P0153 - O2S Slow Response Bank 2 Sensor 1* Pass/Fail Threshold table

Z axis is the pass/fail result (see note below)
X axis is Lean to Rich response time (msec)
Y axis is Rich to Lean response time (msec)
Note: If the cell contains a "0" then the fault is not indicated, if it contains a "1" a fault is indicated

	0.000	0.020	0.030	0.040	0.050	0.060	0.070	0.080	0.090	0.100	0.110	0.120	0.130	0.140	0.150	0.160	1.000
0.000	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.020	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.030	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.040	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.050	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.060	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.070	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.080	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.090	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.100	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.110	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.120	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.130	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.140	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.150	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
0.160	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1.000	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

P1133 - O2S HC L to R Switches Limit Bank 1 Sensor 1* Pass/Fail Threshold table

Z axis is Limit for L/R HC switches
Y axis is Average flow during the response test (gps)
X axis is estimated Ethanol percentage
Note: The cell contains the minimum switches

	0.0	25.0	50.0	75.0	100.0
0.0	26	24	22	21	19
6.3	25	24	22	21	19
12.5	25	23	22	21	20
18.8	24	23	22	21	20
25.0	24	23	22	21	20
31.3	23	22	22	21	20
37.5	22	22	22	21	21
43.8	22	22	21	21	21
50.0	21	21	21	21	21
56.3	21	21	21	21	21
62.5	21	21	21	21	21
68.8	21	21	21	21	21
75.0	21	21	21	21	21
81.3	21	21	21	21	21
87.5	21	21	21	21	21
93.8	21	21	21	21	21
100.0	21	21	21	21	21

Support Tables

P1133 - O2S HC R to L Switches Limit Bank 1 Sensor 1* Pass/Fail Threshold table

Z axis is Limit for R/L HC switches
Y axis is Average flow during the response test (gps)
X axis is estimated Ethanol percentage
Note: The cell contains the minimum switches

	0.0	25.0	50.0	75.0	100.0
0.0	26	24	23	21	19
6.3	26	24	23	21	20
12.5	25	24	22	21	20
18.8	24	23	22	21	20
25.0	24	23	22	21	20
31.3	23	22	22	21	20
37.5	23	22	21	21	20
43.8	22	21	21	21	20
50.0	21	21	21	21	21
56.3	21	21	21	21	21
62.5	21	21	21	21	21
68.8	21	21	21	21	21
75.0	21	21	21	21	21
81.3	21	21	21	21	21
87.5	21	21	21	21	21
93.8	21	21	21	21	21
100.0	21	21	21	21	21

Green Sensor Delay Criteria:

The specific diagnostic (from summary table) will not be enabled until the next ignition cycle after the airflow criteria below (by sensor location) has been met:

- * B1S1 Airflow greater than 22 gps for 100000 grams of accumulated flow non-continuously.
- * B1S2 Airflow greater than 22 gps for 100000 grams of accumulated flow non-continuously.
- * B2S1 Airflow greater than 22 gps for 100000 grams of accumulated flow non-continuously.
- * B2S2 Airflow greater than 22 gps for 100000 grams of accumulated flow non-continuously.

Note that all other enable criteria must be met on the next ignition cycle for the test to run on that ignition cycle.
Note: This feature is only enabled when the vehicle is new and cannot be enabled in service

Eth %	KtFHDP_p_HPS_PressFallLoThresh Coolant Axis																
	-40	-32	-24	-16	-8	0	8	16	20	24	32	40	48	64	80	96	112
0.0000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
12.5000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
25.0000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
37.5000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
50.0000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
62.5000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
75.0000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
87.5000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
100.0000	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5

Eth %	KtFHDP_Cnt_HPS_PressFallLoThresh Coolant Axis																
	-40	-32	-24	-16	-8	0	8	16	20	24	32	40	48	64	80	96	112
0.0000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
12.5000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
25.0000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
37.5000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
50.0000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
62.5000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
75.0000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
87.5000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
100.0000	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

Eth %	KtFHPC_p_HighPressStart Coolant Axis																
	-40	-32	-24	-16	-8	0	8	16	20	24	32	40	48	64	80	96	112
0.0000	6.3	6.3	6.3	5.0	2.5	1.6	1.3	1.0	0.8	0.8	0.8	0.8	0.8	0.7	0.4	0.4	0.4
12.5000	6.3	6.3	6.3	5.0	2.5	1.6	1.3	1.0	0.8	0.8	0.8	0.8	0.8	0.7	0.4	0.4	0.4
25.0000	7.8	7.8	7.8	7.0	4.8	2.5	1.7	1.4	1.1	1.1	1.1	0.9	0.9	0.7	0.4	0.4	0.4
37.5000	10.3	10.3	10.3	9.0	5.8	2.5	2.1	1.7	1.5	1.4	1.4	0.9	0.9	0.7	0.4	0.4	0.4
50.0000	10.3	10.3	10.3	9.0	6.5	4.0	2.4	2.1	1.8	1.7	1.6	1.0	1.0	0.7	0.4	0.4	0.4
62.5000	10.3	10.3	10.3	9.0	6.5	4.0	2.8	2.5	2.1	2.0	1.9	1.1	1.0	0.7	0.4	0.4	0.4
75.0000	10.3	10.3	10.3	10.0	7.0	5.0	3.2	2.8	2.4	2.3	2.2	1.1	1.1	0.7	0.4	0.4	0.4
87.5000	12.3	12.3	12.3	12.0	10.5	7.0	3.2	2.8	2.4	2.3	2.2	1.1	1.1	0.7	0.4	0.4	0.4
100.0000	12.3	12.3	12.3	12.0	10.5	7.0	3.2	2.8	2.4	2.3	2.2	1.1	1.1	0.7	0.4	0.4	0.4

Eth %	KtFHPC_t_HighPressStartTmout Coolant Axis																
	-40	-32	-24	-16	-8	0	8	16	20	24	32	40	48	64	80	96	112
12.8	12.8	11.5	10.0	8.0	5.8	5.3	5.0	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	6.0

P0089
P163A
P228C
P228D
P0191

Eth %	KtFHDP_t_PumpCntrlEngRunThresh Coolant Axis						
	-30	-20	-10	0	10	20	80
30.0	30.0	30.0	20.0	10.0	10.0	20.0	30.0
							110
							100
							80
							20
							10
							0

Support Tables

P0191 KIFHPD_t_SnsPrfStuckCrankTmout

	-30	-20	-10	0	10	20	80	100	110
	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

P0191 KIFHPD_Cnt_SnsPrfIdlePumpOffDly(12.5 ms loop rate)

Eth %	65	70	75	80	85	90	95	100	105
0.0000	240.0	240.0	240.0	240.0	240.0	240.0	240.0	240.0	240.0
12.5000	240.0	240.0	240.0	240.0	240.0	240.0	240.0	240.0	240.0
25.0000	230.0	230.0	230.0	230.0	230.0	230.0	230.0	230.0	230.0
37.5000	220.0	220.0	220.0	220.0	220.0	220.0	220.0	220.0	220.0
50.0000	210.0	210.0	210.0	210.0	210.0	210.0	210.0	210.0	210.0
62.5000	200.0	200.0	200.0	200.0	200.0	200.0	200.0	200.0	200.0
75.0000	190.0	190.0	190.0	190.0	190.0	190.0	190.0	190.0	190.0
87.5000	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0
100.0000	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0	180.0

P0234, P0299

KIBSTD_p_CntrlDevNegLim [kPa] X axis is pressure [kPa]
Y axis is Engine Speed [rpm]

	130.0000	140.0000	160.0000	180.0000	200.0000	220.0000	240.0000	260.0000	280.0000	300.0000
1000.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000	-100.0000
1500.0000	-100.0000	-80.0000	-80.0000	-80.0000	-80.0000	-80.0000	-80.0000	-80.0000	-80.0000	-80.0000
2000.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
2500.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
3000.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
3500.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
4000.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
4500.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
5000.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000
6000.0000	-100.0000	-30.0000	-30.0000	-25.0000	-20.0000	-15.0000	-15.0000	-15.0000	-15.0000	-15.0000

KIBSTD_p_CntrlDevPosLim [kPa] X axis is pressure [kPa]
Y axis is Engine Speed [rpm]

	130.0000	140.0000	160.0000	180.0000	200.0000	220.0000	240.0000	260.0000	280.0000	300.0000
1000.0000	100.0000	100.0000	100.0000	100.0000	100.0000	100.0000	100.0000	100.0000	100.0000	100.0000
1500.0000	100.0000	80.0000	80.0000	80.0000	80.0000	80.0000	80.0000	80.0000	80.0000	80.0000
2000.0000	100.0000	80.0000	80.0000	75.0000	70.0000	65.0000	60.0000	50.0000	30.0000	20.0000
2500.0000	100.0000	75.0000	70.0000	60.0000	55.0000	50.0000	45.0000	30.0000	20.0000	15.0000
3000.0000	100.0000	55.0000	50.0000	45.0000	40.0000	35.0000	30.0000	20.0000	15.0000	15.0000
3500.0000	100.0000	40.0000	30.0000	20.0000	20.0000	20.0000	20.0000	20.0000	15.0000	15.0000
4000.0000	100.0000	30.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	15.0000	15.0000
4500.0000	100.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	15.0000	15.0000
5000.0000	100.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	15.0000	15.0000
6000.0000	100.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	20.0000	15.0000	15.0000

KIBSTD_p_CntrlDevAmbAirCorr [kPa] X axis is pressure [kPa]
Y axis is Ambient Pressure [kPa]

	60.0000	70.0000	80.0000	90.0000	100.0000	110.0000
1500.0000	60.0000	60.0000	60.0000	60.0000	60.0000	60.0000
2500.0000	60.0000	50.0000	40.0000	20.0000	0.0000	0.0000
3000.0000	30.0000	20.0000	10.0000	0.0000	0.0000	0.0000
4000.0000	30.0000	20.0000	10.0000	0.0000	0.0000	0.0000
5000.0000	25.0000	10.0000	5.0000	0.0000	0.0000	0.0000
6000.0000	15.0000	5.0000	5.0000	0.0000	0.0000	0.0000

P00C4, P2261

KIBSTD_r_SurgeLim [-] Axis is Corrected Air Mass Flow [g/s]

	0.0000	1.0000
	38.0890	1.5784
	76.6263	2.4442
	100.0000	2.7000
	143.5191	3.1000
	189.1064	3.4125

P226B

KIBSTD_r_ExcvsBstPresLim [-] Axis is Corrected Air Mass Flow [g/s]

	0.0000	1.0000
	0.0250	1.4000
	0.0500	1.9000
	0.0750	2.4000
	0.1000	2.9500
	0.1250	2.7000
	0.1500	3.1000
	0.1750	3.3000

Support Tables

P0324/P0326 Abnormal Noise Threshold (same table used for both):

Y-axis: Engine Speed (RPM)	X-axis: Engine Air Flow (mg per cylinder)			
	100	300	700	1200
500	0.0337	0.0337	0.0337	0.0337
1000	0.0320	0.0320	0.0320	0.0320
1500	0.0308	0.0308	0.0308	0.0308
2000	0.0300	0.0300	0.0300	0.0300
2500	0.0290	0.0290	0.0290	0.0290
3000	0.0368	0.0368	0.0368	0.0368
3500	0.0527	0.0527	0.0527	0.0527
4000	0.0563	0.0563	0.0563	0.0563
4500	0.0373	0.0373	0.0373	0.0373
5000	0.0546	0.0546	0.0546	0.0546
5500	0.0557	0.0557	0.0557	0.0557
6000	0.0733	0.0733	0.0733	0.0733
6500	0.0895	0.0895	0.0895	0.0895
7000	0.0895	0.0895	0.0895	0.0895
7500	0.0895	0.0895	0.0895	0.0895
8000	0.0895	0.0895	0.0895	0.0895
8500	0.0895	0.0895	0.0895	0.0895

P0325/P0330

Two methods are used for the Knock Sensor Open Circuit Diagnostic:

- 1) 20 kHz Method: 20 kHz signal is internally injected on one sensor line (Signal) and the output of the differential op-amp is checked to verify the 20 kHz travels through the sensor and back to the second sensor
- 2) Normal Noise: The amplitude of the FFT (in the knock frequency range) is checked to verify there is a knock signal within an expected range.

K1KNKD_e_OpenMethod is the cal table used to determine which Open Circuit method is used: '0' = Disabled; '1' = 20 kHz Method; '2' = Normal Noise Method

Y-axis: Engine Speed (RPM)	X-axis: Engine Air Flow (mg per cylinder)			
	100	300	700	1200
500	1	1	1	1
1000	1	1	1	1
1500	1	1	1	1
2000	1	1	1	1
2500	1	1	1	1
3000	1	1	1	1
3500	1	1	1	1
4000	1	1	1	1
4500	1	1	1	1
5000	1	1	1	1
5500	1	1	1	1
6000	1	1	1	1
6500	1	1	1	1
7000	1	1	1	1
7500	1	1	1	1
8000	1	1	1	1
8500	1	1	1	1

Open Circuit Thresholds:

1. 20 kHz Method:

Engine Speed (RPM):	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000	8500
OpenCktThrshMin:	1.3477	1.3242	1.3105	1.3066	1.3066	1.3066	1.3047	1.2949	1.2754	1.2402	1.1855	1.1094	1.0078	0.8750	0.7324	0.7793	0.8320
Engine Speed (RPM):	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000	8500
OpenCktThrshMax:	3.9023	3.8340	3.8086	3.8066	3.8203	3.8320	3.8262	3.7949	3.7188	3.5859	3.3809	3.0938	2.7070	2.2070	1.5820	0.8164	0.0000

2. Normal Noise Method:

Engine Speed (RPM):	2700	2900	3000	3250	3500	3750	4000	4250	4500	4750	5000	5500	6000	6500	7000	7500	8500
OpenCktThrshMin:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Engine Speed (RPM):	2700	2900	3000	3250	3500	3750	4000	4250	4500	4750	5000	5500	6000	6500	7000	7500	8500
OpenCktThrshMax:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

P06B6/P06B7

Engine Speed (RPM):	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000	8500
OpenTestThreshLd	0.0059	0.0117	0.0137	0.0137	0.0137	0.0176	0.0234	0.0352	0.0566	0.0859	0.1289	0.1836	0.2559	0.3438	0.4512	0.5801	0.7324
Engine Speed (RPM):	500	1000	1500	2000	2500	3000	3500	4000	4500	5000	5500	6000	6500	7000	7500	8000	8500
OpenTestThreshH	0.0273	0.0293	0.0293	0.0332	0.0391	0.0547	0.0781	0.1172	0.1719	0.2461	0.3438	0.4648	0.6172	0.7988	1.0156	1.2695	1.5645

P0066: MAP / MAF / TPS Correlation

		X-axis is TPS (%)								
		Data is MAP threshold (kPa)								
X-axis		5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
Data		37.45	44.08	46.55	45.54	46.96	41.86	255.00	255.00	255.00
		X-axis is TPS (%)								
		Data is MAF threshold (grams/sec)								
X-axis		5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
Data		9.38	12.13	16.89	19.20	29.84	49.55	255.00	255.00	255.00

Support Tables

X axis is Engine Speed (RPM)
Data is max MAF vs RPM (grams/sec)

X-axis	600.00	7.00	8.00	9.00	3000.00	3800.00	4600.00	5400.00	6200.00	7000.00
Data	17.90	39.19	63.43	80.91	112.92	138.31	168.70	174.20	174.20	176.70

X axis is Battery Voltage (V)
Data is max MAF vs Voltage (grams/sec)

X-axis	6.00	7.00	8.00	9.00	10.00	11.00	12.00	13.00	14.00
Data	6.50	25.00	65.00	140.00	260.00	300.00	300.70	300.70	300.70

P1682: Ignition Voltage Correlation

X-axis is IAT (DegC)
Data is Voltage threshold (V)

X-axis	23.00	85.00	95.00	105.00	125.00
Data	7.00	8.70	9.00	9.20	10.00

P0606: Processor Performance Check - ETC software is not executed in proper order

X-axis is task loop time
Data is threshold (seconds)

X-axis	CaPRR_k_625msSec	CaPRR_k_125msSec	CaPRR_k_25msSec	CaPRR_k_10RES_C
Data	0.175	0.175	0.175	409.594

X-axis is task loop time
Data indicates if feature is enabled

X-axis	CaPRR_k_625msSec	CaPRR_k_125msSec	CaPRR_k_25msSec	CaPRR_k_10RES_C
Data	1	1	0	0

P16F3: No fast unmanaged retarded spark above the applied spark

X-axis is Erpm
Y-axis is Air per Cylinder (mg)
Data is spark delta threshold (kPa)

APC/Erpm	500.00	980.74	1461.48	1942.23	2422.97	2903.71	3384.45	3865.20	4345.94	4826.68	5307.42	5788.16	6268.91	6749.65	7230.39	7711.13	8191.88
80.00	33.84	33.33	34.78	30.41	29.75	27.42	27.06	27.19	25.36	23.09	23.31	26.23	28.00	28.47	28.47	28.47	28.47
160.00	38.08	37.47	29.19	25.38	25.50	26.58	25.27	23.36	21.47	19.89	23.16	23.67	24.63	24.92	24.92	24.92	24.92
240.00	36.13	34.89	25.00	21.78	21.41	21.73	20.97	19.94	18.63	17.45	20.69	21.56	22.00	22.19	22.19	22.19	22.19
320.00	30.55	29.80	21.81	18.72	18.27	18.36	17.94	17.39	16.44	15.53	18.13	19.33	19.67	19.77	19.77	19.77	19.77
400.00	26.47	26.02	19.34	16.39	15.89	15.88	15.69	15.44	14.72	13.98	16.05	17.25	17.05	17.03	17.03	17.03	17.03
480.00	23.34	23.08	17.38	14.56	14.05	14.00	13.94	13.68	13.33	12.72	14.39	15.17	14.78	14.77	14.77	14.77	14.77
560.00	20.88	20.75	15.78	13.11	12.59	12.52	12.53	12.59	12.17	11.66	13.06	13.56	13.05	13.03	13.03	13.03	13.03
640.00	18.89	18.81	14.42	11.92	11.42	11.31	11.41	11.55	11.20	10.77	11.95	12.25	11.67	11.66	11.66	11.66	11.66
720.00	17.25	17.19	13.30	10.94	10.44	10.31	10.45	10.64	10.38	10.00	10.97	11.14	10.56	10.55	10.55	10.55	10.55
800.00	15.86	15.83	12.22	10.08	9.63	9.48	9.64	9.88	9.66	9.33	10.13	10.19	9.64	9.63	9.63	9.63	9.63
880.00	14.69	14.67	11.27	9.34	8.91	8.75	8.92	9.20	9.03	8.73	9.41	9.41	8.88	8.86	8.86	8.86	8.86
960.00	13.67	13.66	10.45	8.70	8.28	8.05	8.19	8.42	8.36	8.23	8.77	8.72	8.22	8.20	8.20	8.20	8.20
1040.00	12.78	12.78	9.75	8.16	7.73	7.45	7.55	7.75	7.77	7.72	8.20	8.14	7.66	7.64	7.64	7.64	7.64
1120.00	12.02	12.02	9.13	7.67	7.25	6.94	7.02	7.19	7.20	7.20	7.69	7.63	7.16	7.16	7.16	7.16	7.16
1200.00	11.33	11.34	8.59	7.23	6.80	6.48	6.55	6.69	6.73	6.75	7.22	7.17	6.72	6.72	6.72	6.72	6.72
1280.00	10.72	10.73	8.11	6.84	6.38	6.08	6.14	6.27	6.31	6.34	6.81	6.77	6.34	6.33	6.33	6.33	6.33
1360.00	10.16	10.19	7.67	6.50	6.00	5.73	5.77	5.89	5.94	6.00	6.45	6.41	6.00	5.98	5.98	5.98	5.98

P16F3: Absolute difference of the calculated Intake Manifold Pressure during engine event versus during time event

X-axis is engine torque (Nm)
Data is MAP delta threshold (kPa)

X-axis	0.00	50.00	100.00	150.00	200.00	300.00
Data	37.45	37.45	37.45	37.45	37.45	37.45

P16F3: Table to calculate limit for predicted torque for zero pedal determination.

X-axis is engine oil temp in C deg
Y-axis is engine speed RPM
Data is Torque (Nm)

	-40.00	-20.00	-10.00	0.00	50.00	90.00
300.00	150.00	150.00	150.00	150.00	150.00	150.00
500.00	150.00	146.86	146.86	146.86	146.86	150.00
600.00	150.00	145.51	145.51	145.51	145.51	150.00
700.00	150.00	144.62	144.62	144.62	144.62	150.00
800.00	150.00	142.46	142.46	142.46	142.46	150.00
900.00	150.00	140.31	140.31	140.31	140.31	150.00
1000.00	150.00	138.15	138.15	138.15	138.15	150.00
1100.00	150.00	136.00	136.00	136.00	136.00	150.00
1300.00	150.00	133.85	133.85	133.85	133.85	150.00
1500.00	150.00	129.36	129.36	129.36	129.36	150.00
1700.00	150.00	124.87	124.87	124.87	124.87	150.00
2000.00	150.00	120.38	120.38	120.38	120.38	150.00
2500.00	150.00	115.90	115.90	115.90	115.90	150.00
3000.00	150.00	106.92	106.92	106.92	106.92	150.00
4000.00	150.00	97.95	97.95	97.95	97.95	150.00
5000.00	150.00	88.97	88.97	88.97	88.97	150.00
6000.00	150.00	80.00	80.00	80.00	80.00	150.00

Support Tables

P0442: EONV Pressure Threshold Table (in Pascals)

X axis is fuel level in %
Y axis is temperature in deg C

	0.0000	6.2499	12.4998	18.7497	24.9996	31.2495	37.4994	43.7493	49.9992	56.2491	62.4990	68.7490	74.9989	81.2488	87.4987	93.7486	99.9985
-10.0000	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
-4.3750	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
1.2500	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
6.8750	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
12.5000	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
18.1250	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
23.7500	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
29.3750	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
35.0000	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
40.6250	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
46.2500	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
51.8750	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
57.5000	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
63.1250	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
68.7500	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
74.3750	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453
80.0000	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-249.0905	-224.2788	-186.8179	-149.3570	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453	-124.5453

P0442: Estimate of Ambient Temperature Valid Conditioning Time

EAT Valid Conditioning Time (in seconds)
Axis is Ignition Off Time (in seconds)

Axis	Curve
0	350
600	350
1200	450
1800	450
2400	475
3000	475
3600	475
4200	450
4800	450
5400	450
6000	450
6600	450
7200	450
7800	400
8400	350
9000	310
9600	275
10200	225
10800	200
11700	200
12600	200
13500	200
14400	200
15300	185
16200	175
17100	165
18000	150
19200	100
20400	100
21600	100
22800	100
24000	100
25200	100

P0442: Engine Off Time Before Vehicle Off Maximum as a Function of Estimated Ambient Temperature

Engine Off Time Before Vehicle Off Maximum Table (in seconds)
Axis is Estimated Ambient Coolant in Deg C

Axis	-10	-4	1	7	13	18	24	29	35	41	46	52	58	63	69	74	80
Curve	44	44	44	44	68	82	105	153	320	480	480	480	480	480	480	480	480

P0496: Purge Valve Leak Test Engine Vacuum Test Time (Cold Start) as a Function of Fuel Level

Purge Valve Leak Test Engine Vacuum Test Time (in seconds)
Axis is Fuel Level in %

Axis	Curve
0	69
6	67
12	66
19	65
25	63
31	62
37	61
44	60
50	60
56	59
62	59
69	58
75	56
81	53
87	51
94	49
100	47

Support Tables

P0461, P2066, P2636: Transfer Pump Enable

TransferPumpOnTimeLimit (in seconds)

Axis is Fuel Level in %

Axis	Curve
0	30
3	35
6	40
9	45
13	50
16	55
19	60
22	65
25	70
28	85
31	90
34	95
38	135
41	135
44	160
47	160
50	260
53	260
56	360
59	360
63	360
66	360
69	360
72	460
75	460
78	460
81	460
84	460
88	460
91	460
94	460
97	460
100	460

Tables supporting Engine Oil Temperature Sensor

P0196

FastFailTempDiff		AXIS is Engine Coolant Temperature at ECM Power-up, Degrees C															
Axis	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
Curve	80.0	80.0	80.0	60.0	60.0	40.0	40.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0

TotalAccumulatedFlow		AXIS is Power up Engine Oil temperature, Curve is accumulated engine grams airflow															
Axis	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
Curve	15000	14000	13000	12000	11000	10000	9000	8000	7000	6000	5000	4000	5000	4000	3000	3000	3000

P0521

EngSpeedWeightFactorTable		AXIS is Engine RPM, Curve is Weight Factor							
Axis	0	500	900	1000	1500	1750	2300	3500	4000
Curve	0.00	0.00	0.00	0.45	0.45	0.45	0.46	0.44	0.00

EngOilTempWeightFactorTable		AXIS is Engine Oil Temp Deg C, Curve is Weight Factor							
Axis	-40	40	60	80	90	100	120	130	140
Curve	0.58	0.70	0.70	0.70	0.70	0.70	0.70	0.70	0.00

EngLoadStabilityWeightFactorTable		AXIS is Engine RPM, Curve is Weight Factor							
Axis	0	5	10	20	30	50	100	200	399
Curve	1.00	1.00	0.50	0.30	0.10	0.00	0.00	0.00	0.00

EngOilPredictionWeightFactorTable		AXIS is Engine RPM, Curve is Engine Oil Prediction Weight Factor							
Axis	0	170	250	275	360	375	400	500	600
Curve	0.00	0.00	0.10	1.00	1.00	1.00	1.00	0.86	0.00

Tables supporting Clutch Diagnostics

P0806

EngTorqueThreshold Table		axis is Percent Clutch Pedal Position, 0 = bottom of travel															
Axis	0	6.2485	12.497	18.7455	24.994	31.2425	37.491	43.7395	49.988	56.2365	62.485	68.7335	74.982	81.2305	87.479	93.7275	99.976
Curve	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

P0806

ResidualErrorEnableLow Table		axis is Gear							
Axis	1st	2nd	3rd	4th	5th	6th	rev	neutral	
Curve	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

P0806

ResidualErrorEnableHigh Table		axis is Gear							
Axis	1st	2nd	3rd	4th	5th	6th	rev	neutral	
Curve	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Tables supporting Clutch Pedal Position Status (analog Clutch Pedal Position Sensor applications only):

Clutch Pedal Top of Travel Achieved criteria

The clutch pedal Top of Travel state will transition from FALSE to TRUE when the following occurs:

Clutch Pedal Position for

<= 88 %
> 3 counts

 each count is equal to 12.5ms

Support Tables

P219B AvgFlow / AvgRPM	250	500	750	1000	1250	1500	1750	2000	K10XYD K_AFIM_QualFactor	2250	2500	2750	3000	3500	4000	4500	5000	6000
40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
200	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
240	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
280	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
320	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
360	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
400	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
440	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
480	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
520	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
560	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
640	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
720	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
800	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Closed Loop Enable Criteria

Engine run time greater than

KIFSTA_t_ClosedLoopTime																		
Start-Up Coolant	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152	
Close Loop Enable Time	300.0	260.0	225.0	90.0	80.0	32.0	32.0	32.0	32.0	32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

and pre converter O2 sensor voltage less than

KIFULC_U_O2_SensorReadyThrsLo	< 1100
Voltage	milliVolts

for
KcFULC_O2_SensorReadyEvents
(events * 12.5 milliseconds > 40 events)

and
COSC (Converter Oxygen Storage Control) not enabled
and
Consumed AirFuel Ratio is stoichiometry i.e. not in component protection
and
POPD or Catalyst Diagnostic not intrusive
and
Turbo Scavenging Mode not enabled
and
All cylinders whose valves are active also have their injectors enabled
and

O2S_Bank_1_TFTKO, O2S_Bank_2_TFTKO, FuelInjectorCircuit_FA and CylinderDeacDriverTFTKO = False

Long Term FT Enable Criteria

Closed Loop Enable and
Coolant greater than
KIFCLL_T_AdaptiveLoCoolant
> 40 Celcius
Coolant

or less than
KIFCLL_T_AdaptiveHiCoolant
< 720
Coolant Celcius

and
KIFCLL_p_AdaptiveLowMAP_Limit
Barometric Pressure 65 70 75 80 85 90 95 100 105
Manifold Air Pressure 16.0 16.0 16.0 16.0 16.0 17.0 18.0 18.0 18.0

and
TPS_ThrottleAuthorityDefaulted = False
and
Flex Fuel Estimate Algorithm is not active
and
Excessive fuel vapors boiling off from the engine oil algorithm (BOFR) is not enabled
and
Catalyst or EVAP large leak test not intrusive

Secondary Fuel Trim Enable Criteria

Closed Loop Enable and
KIFCLP_U_O2ReadyThrsLo
< 1100
Voltage milliVolts

for
KcFCPLP_Cnt_O2RdyCyclesThrs
(events * 12.5 milliseconds > 80 events)

Long Term Secondary Fuel Trim Enable Criteria

KIFCLP_t_PostIntgDisableTime										X10 Y10	X11 Y11	X12 Y12	X13 Y13	X14 Y14	X15 Y15	X16 Y16	X17 Y17
Start-Up Coolant	-40	-29	-18	-6	5	16	28	39	50	61	73	84	95	106	118	129	140
Post Integral Enable Time	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0	100.0
Plus									X10 Y10	X11 Y11	X12 Y12	X13 Y13	X14 Y14	X15 Y15	X16 Y16	X17 Y17	
KIFCLP_t_PostIntgRampInTime	-40	-29	-18	-6	5	16	28	39	50	61	73	84	95	106	118	129	140
Start-Up Coolant									40.0	30.0	20.0	10.0	10.0	10.0	10.0	10.0	10.0
Post Integral Ramp In Time	50.0	50.0	50.0	50.0	50.0	50.0	50.0	50.0	40.0	30.0	20.0	10.0	10.0	10.0	10.0	10.0	10.0

and
KeFCPLP_T_IntegrationCatalystMax
< 1000
Modeled Catalyst Temper Celcius
and
KeFCPLP_T_IntegrationCatalystMin

Support Tables

> 425
Modeled Catalyst Temper *Celcius*
and
PO2S_Bank_1_Snr_2_FA and PO2S_Bank_2_Snr_2_FA = False

Cold Start Emissions Diagnostic
P050D

Pot Eth Concentration /	KICSEC_1_ExtendedEngineExit				
	0	25	50	75	100
0	45	45	45	45	45
0.125	45	45	45	45	45
0.25	45	45	45	45	45
0.375	45	45	45	45	45
0.5	22	22	22	22	22
0.625	22	22	22	22	22
0.75	22	22	22	22	22
0.875	22	22	22	22	22
1	22	22	22	22	22

AFIM

AvgFlow / AvgRPM	KIFABD_U_VarThresh1																
	700	900	1100	1300	1500	1700	1900	2100	2300	2500	3000	3500	4000	4500	5000	5500	6000
100	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384
150	16	16	18	18	22	22	20	18	16	16	14	13	13	13	15	15	15
200	16	16	18	18	22	22	20	18	16	16	14	13	13	13	15	15	15
250	20	20	25	30	25	22	22	20	20	20	18	16	15	14	14	14	14
300	50	30	35	35	35	30	30	30	30	30	30	30	25	22	22	20	20
350	40	40	40	40	40	40	40	40	40	38	35	35	30	28	25	25	25
400	45	45	50	50	50	50	50	50	50	50	50	50	45	45	45	45	35
450	50	50	65	65	65	65	65	60	60	60	60	60	60	55	50	48	42
500	60	60	65	65	65	65	80	80	80	80	80	80	80	70	53	53	16384
550	65	65	70	65	65	80	85	90	90	90	90	90	85	74	16384	16384	16384
600	66	67	70	80	85	85	95	95	95	95	95	95	95	16384	16384	16384	16384
650	16384	74	80	90	95	95	105	105	105	105	105	105	105	16384	16384	16384	16384
700	16384	82	90	100	100	105	115	115	115	115	115	115	115	16384	16384	16384	16384
750	16384	16384	95	100	100	110	115	115	115	115	115	115	115	16384	16384	16384	16384
800	16384	16384	100	105	110	115	115	115	115	115	115	115	115	16384	16384	16384	16384
1000	16384	16384	16384	115	115	115	115	115	115	115	115	115	115	16384	16384	16384	16384
1200	16384	16384	16384	115	115	115	115	115	115	115	115	115	115	16384	16384	16384	16384

AvgFlow / AvgRPM	KIFABD_K_QualFactor1																
	700	900	1100	1300	1500	1700	1900	2100	2300	2500	3000	3500	4000	4500	5000	5500	6000
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
200	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
250	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
300	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
350	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
400	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
450	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
500	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
550	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00
600	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
650	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
700	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
750	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
800	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
1000	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00
1200	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00

AvgFlow / AvgRPM	KIFABD_U_Normalizer1																
	700	900	1100	1300	1500	1700	1900	2100	2300	2500	3000	3500	4000	4500	5000	5500	6000
100	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384
150	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384	16384
200	20	20	20	20	15	15	15	15	15	15	15	15	15	15	20	20	20
250	20	20	20	20	20	20	20	20	20	20	20	20	20	20	15	15	15
300	20	20	20	20	20	20	20	20	20	20	20	20	20	20	15	10	5
350	20	20	20	20	20	20	20	20	20	20	20	20	30	10	10	10	10
400	20	20	20	20	20	20	20	20	20	20	20	20	30	20	15	12	11
450	30	30	20	25	25	25	25	25	25	25	25	25	25	25	20	16	16384
500	35	35	30	30	30	35	30	30	30	30	30	30	30	10	16384	16384	16384
550	30	30	30	30	30	25	30	30	20	30	30	30	20	16384	16384	16384	16384
600	16384	32	35	30	30	30	30	30	30	30	30	30	30	16384	16384	16384	16384
650	16384	31	30	35	35	30	25	25	25	25	25	25	28	16384	16384	16384	16384
700	16384	16384	30	30	30	20	20	20	20	20	20	20	24	16384	16384	16384	16384
750	16384	16384	30	30	30	20	20	20	20	20	20	20	22	16384	16384	16384	16384
800	16384	16384	16384	30	30	30	30	30	30	30	30	30	25	16384	16384	16384	16384
1000	16384	16384	16384	30	30	30	30	30	30	30	30	30	30	16384	16384	16384	16384
1200	16384	16384	16384	16384	30	30	30	30	30	30	30	30	30	16384	16384	16384	16384

Fault Bundle Definitions

ThrotTempSensorFA	IAT2 Pre P0096 P0097 P0098 IAT2 No P0111 P0112 P0113
SuperchargerBypassValveFA	P2261
CylDeacSystemTFTKO	P3400
MAF_SensorPerfFA	P0101
MAF_SensorPerfTFTKO	P0101
MAP_SensorPerfFA	P0106
MAP_SensorPerfTFTKO	P0106
SCIAP_SensorPerfFA	P012B
SCIAP_SensorPerfTFTKO	P012B
ThrottlePositionSnsrPerfFA	P0121
ThrottlePositionSnsrPerfTFTKO	P0121
TIAP_SensorPerfFA	P0236
MAF_SensorFA	P0101 P0102 P0103
MAF_SensorTFTKO	P0101 P0102 P0103
MAF_SensorFP	P0102 P0103
MAF_SensorCircuitFA	P0102 P0103
MAF_SensorCircuitTFTKO	P0102 P0103
MAP_SensorTFTKO	P0106 P0107 P0108
MAP_SensorFA	P0106 P0107 P0108
MAP_SensorCircuitFP	P0107 P0108
SCIAP_SensorFA	P012B P012C P012D
SCIAP_SensorTFTKO	P012B P012C P012D
SCIAP_SensorCircuitFP	P012C P012D
	naturall y aspirat ed, turboch arged P0106 P0107 P0108 superch:P012B P012C P012D
AfterThrottlePressureFA	
	naturall y aspirat ed, turboch arged P0106 P0107 P0108 superch:P012B P012C P012D
AfterThrottleVacuumTFTKO	
SCIAP_SensorCircuitFA	P012C P012D
	naturall y aspirat ed, turboch arged P0106 P0107 P0108 superch:P012B P012C P012D
AfterThrottlePressTFTKO	
MAP_SensorCircuitFA	P0107 P0108
MAP_EngineVacuumStatus	MAP_SensorFA OR P0107, P0108 Pending

Fault Bundle Definitions

CrankCamCorrelationTFTKO	P0016	P0017	P0018	P0019								
CrankSensorFA	P0335	P0336										
CrankSensorTFTKO	P0335	P0336										
CamSensorFA	P0016	P0017	P0018	P0019	P0340	P0341	P0345	P0346	P0365	P0366	P0390	P0391
CamSensorTFTKO	P0016	P0017	P0018	P0019	P0340	P0341	P0345	P0346	P0365	P0366	P0390	P0391
CrankIntakeCamCorrelationFA	P0016	P0018										
CrankExhaustCamCorrelationFA	P0017	P0019										
IntakeCamSensorTFTKO	P0016	P0018	P0340	P0341	P0345	P0346						
IntakeCamSensorFA	P0016	P0018	P0340	P0341	P0345	P0346						
ExhaustCamSensorTFTKO	P0017	P0019	P0365	P0366	P0390	P0391						
ExhaustCamSensorFA	P0017	P0019	P0365	P0366	P0390	P0391						
IntakeCamSensor_FA	P0016	P0018	P0340	P0341	P0345	P0346						
IntakeCamSensor_TFTKO	P0016	P0018	P0340	P0341	P0345	P0346						
ExhaustCamSensor_FA	P0017	P0019	P0365	P0366	P0390	P0391						
ExhaustCamSensor_TFTKO	P0017	P0019	P0365	P0366	P0390	P0391						
CrankIntakeCamCorrFA	P0016	P0018										
CrankExhaustCamCorrFA	P0017	P0019										
CrankSensorFaultActive	P0335	P0336										
CrankSensor_FA	P0335	P0336										
CrankSensorTestFailedTKO	P0335	P0336										
CrankSensor_TFTKO	P0335	P0336										
CamSensor_FA	P0016	P0017	P0018	P0019	P0340	P0341	P0345	P0346	P0365	P0366	P0390	P0391
CamSensorAnyLocationFA	P0016	P0017	P0018	P0019	P0340	P0341	P0345	P0346	P0365	P0366	P0390	P0391
CamSensor_TFTKO	P0016	P0017	P0018	P0019	P0340	P0341	P0345	P0346	P0365	P0366	P0390	P0391
EngModeNotRunTmErr	P2610											
ECT_Sensor_Ckt_FA	P0117	P0118										
ECT_Sensor_Ckt_TPTKO	P0117	P0118										
ECT_Sensor_Ckt_TFTKO	P0117	P0118										
ECT_Sensor_DefaultDetected	P0117	P0118	P0116	P0119								
ECT_Sensor_FA	P0117	P0118	P0116	P0119	P0128							
ECT_Sensor_TFTKO	P0117	P0118	P0116	P0119								
ECT_Sensor_Perf_FA	P0116											
ECT_Sensor_Ckt_FP	P0117	P0118										
ECT_Sensor_Ckt_High_FP	P0118											
ECT_Sensor_Ckt_Low_FP	P0117											
THMR_Insuff_Flow_FA	P00B7											
THMR_Therm_Control_FA	P0597	P0598	P0599									
THMR_RCT_Sensor_Ckt_FA	P00B3	P00B4										
THMR_ECT_Sensor_Ckt_FA	P0117	P0118	P0116	P00B6								
O2S_Bank_1_TFTKO	P0131	P0132	P0134	P2A00								
O2S_Bank_2_TFTKO	P0151	P0152	P0154	P2A03								
O2S_Bank_1_Sensor_1_FA	P2A00	P0131	P0132	P0133	P0134	P0135	P0053	P1133	P015A	P015B	P0030	
O2S_Bank_1_Sensor_2_FA	P013A	P013B	P013E	P013F	P2270	P2271	P0137	P0138	P0140	P0141	P0054	P0036
O2S_Bank_2_Sensor_1_FA	P2A03	P0151	P0152	P0153	P0154	P0155	P0059	P1153	P015C	P015D	P0050	
O2S_Bank_2_Sensor_2_FA	P013C	P013D	P014A	P014B	P2272	P2273	P0157	P0158	P0160	P0161	P0060	P0056
PO2S_Bank_1_Snsr_2_FA	P0137	P0138	P0140	P0036	P0054	P0141	P2270	P2271				
PO2S_Bank_2_Snsr_2_FA	P0157	P0158	P0160	P0056	P0060	P0161	P2272	P2273				
FuellInjectorCircuit_FA	P0201	P0202	P0203	P0204	P0205	P0206	P0207	P0208				
	P0261	P0264	P0267	P0270	P0273	P0276	P0279	P0282				
	P0262	P0265	P0268	P0271	P0274	P0277	P0280	P0283				
	P2147	P2150	P2153	P2156	P216B	P216E	P217B	P217E				

Fault Bundle Definitions

	P2148	P2151	P2154	P2157	P216C	P216F	P217C	P217F											
	P1248	P1249	P124A	P124B	P124C	P124D	P124E	P124F											
FuellInjectorCircuit_TFTKO	P0201	P0202	P0203	P0204	P0205	P0206	P0207	P0208											
	P0261	P0264	P0267	P0270	P0273	P0276	P0279	P0282											
	P0262	P0265	P0268	P0271	P0274	P0277	P0280	P0283											
	P2147	P2150	P2153	P2156	P216B	P216E	P217B	P217E											
	P2148	P2151	P2154	P2157	P216C	P216F	P217C	P217F											
	P1248	P1249	P124A	P124B	P124C	P124D	P124E	P124F											
FHPR_b_PumpCkt_FA	P0090	P0091	P0092	P00C8	P00C9	P00CA													
FHPR_b_PumpCkt_TFTKO	P0090	P0091	P0092	P00C8	P00C9	P00CA													
FHPR_b_FRP_SnsrCkt_FA	P0192	P0193																	
FHPR_b_FRP_SnsrCkt_TFTKO	P0192	P0193																	
EngineMetalOvertempActive	P1258																		
BSTR_b_PCA_CktFA	P0033	P0034	P0035	P0045	P0047	P0048	P0243	P0245	P0246	P0247	P0249	P0250							
BSTR_b_PCA_CktTFTKO	P0033	P0034	P0035	P0045	P0047	P0048	P0243	P0245	P0246	P0247	P0249	P0250							
BSTR_b_PCA_CktLoTFTKO	P0034	P0047	P0245	P0249															
BSTR_b_PstnCntrlFA	P166D	P166E																	
BSTR_b_PstnCntrlTooLoTFTKO	P166D	P166E																	
BSTR_b_PstnCntrlTooHiTFTKO	P166D	P166E																	
BSTR_b_PCA_PstnSnsrFA	P003A	P2564	P2565																
BSTR_b_PCA_PstnSnsrTFTKO	P003A	P2564	P2565																
BSTR_b_TurboBypassCktFA	P0033	P0034	P0035	P00C0	P00C1	P00C2													
BSTR_b_TurboBypassCktTFTKO	P0033	P0034	P0035	P00C0	P00C1	P00C2													
BSTR_b_IC_PmpCktFA	P023A	P023C																	
BSTR_b_PCA_FA	P0234	P0299	P0033	P0034	P0035	P0045	P0047	P0048	P0243	P0245	P0246	P2261	P0247	P0249	P0250				
BSTR_b_PCA_TFTKO	P0234	P0299	P0033	P0034	P0035	P0045	P0047	P0048	P0243	P0245	P0246	P2261	P0247	P0249	P0250				
BSTR_b_ExcsvBstFA	P226B																		
BSTR_b_ExcsvBstTFTKO	P226B																		
BSTR_b_PresCntrlTooLoTFTKO	P0299																		
BSTR_b_PresCntrlTooHiTFTKO	P0234																		
BSTR_b_TurboBypB_CktFA	P00C0	P00C1	P00C2																
BSTR_b_TurboBypB_CktTFTKO	P00C0	P00C1	P00C2																
KS_Ckt_Perf_B1B2_FA	P0324	P0325	P0326	P0327	P0328	P0330	P0332	P0333	P06B6	P06B7									
IgnitionOutputDriver_FA	P0351	P0352	P0353	P0354	P0355	P0356	P0357	P0358											
IAC_SystemRPM_FA	P0506	P0507																	
TCM_EngSpdReqCkt	P150C																		
PPS1_OutOfRange_Composite	P2122	P2123	P06A3																
PPS2_OutOfRange_Composite	P2127	P2128	P0697																
PPS1_OutOfRange_Composite	P2122	P2123	P06A3																
PPS2_OutOfRange_Composite	P2127	P2128	P0697																
PPS1_OutOfRange	P2122	P2123																	
PPS2_OutOfRange	P2127	P2128																	
PPS1_OutOfRange	P2122	P2123																	
PPS2_OutOfRange	P2127	P2128																	
AcceleratorPedalFailure	P2122	P2123	P2127	P2128	P2138	P0697	P06A3												
ControllerRAM_Error_FA	P0604																		
ControllerProcessorPerf_FA	P0606																		

Fault Bundle Definitions

CylinderDeacDriverTFTKO	P3401 P3409 P3417 P3425 P3433 P3441 P3449
BrakeBoosterSensorFA	P0556 P0557 P0558
BrakeBoosterVacuumValid	P0556 P0557 P0558
BrakeBoosterVacuumValid	VehicleMAP_SensorFA
CylinderDeacDriverTFTKO	P3401 P3409 P3417 P3425 P3433 P3441 P3449
EngineTorqueEstInaccurate	EngineFuelInjFuelInjFuelTrim FuelTrim MAF_ScMAP_ScEGRValuePerforamnce_FA
FuelTrimSystemB1_FA	P0171 P0172
FuelTrimSystemB2_FA	P0174 P0175
FuelTrimSystemB1_TFTKO	P0171 P0172
FuelTrimSystemB2_TFTKO	P0174 P0175
A/F Imbalance Bank1	P219A
A/F Imbalance Bank2	P219B
AIRSystemPressureSensor FA	P2430 P2431 P2432 P2433 P2435 P2436 P2437 P2438
AIR System FA	P0411 P2440 P2444
AIRValveControlCircuit FA	P0412
AIRPumpControlCircuit FA	P0418
Clutch Sensor FA	P0806 P0807 P0808
ClutchPositionSensorCircuitLo FA	P0807
ClutchPositionSensorCircuitHi FA	P0808
Ethanol Composition Sensor FA	P0178 P0179 P2269
LowFuelConditionDiagnostic	Flag set to TRUE if the fuel level < AND No Active DTCs: FuelLevelDataFault P0462 P0463 for at least 30 seconds.
Transfer Pump is Commanded On	Fuel Volume in Primary Fuel Tank < 0.0 liters AND Fuel Volume in Secondary Fuel Tank ≥ 0.0 liters AND Transfer Pump on Time < TransferPumpOnTimeLimit Table AND Transfer Pump had been Off for at least 0.0 seconds AND Evap Diagnostic (Purge Valve Leak Test, AND Engine Running
<u>Long Name</u>	<u>Short Name</u>
Bank	B
Brake	Brk
Circuit	Ckt
Engine	Eng

Fault Bundle Definitions

Fault Active	FA
Intake	Intk
Naturally Aspirated	NA
Performance	Perf
Position	Pstn
Pressure	Press
Sensor	Snsr
Supercharged	SC
System	Sys
Test Failed This Key On	TFTKO
Rough Road	RR

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Rail Pressure (FRP) Sensor Performance (rationality)	P018B	This DTC detects a fuel pressure sensor response stuck within the normal operating range	Absolute value of change in fuel pressure as sensed during intrusive test.	<= 30 kPa	1. FRP Circuit Low DTC (P018C) 2. FRP Circuit High DTC (P018D) 3. FuelPump Circuit Low DTC (P0231) 4. FuelPump Circuit High DTC (P0232) 5. FuelPump Circuit Open DTC (P023F) 6. Reference Voltage DTC (P0641) 7. Fuel Pump Control Module Driver Over-temperature DTC's (P064A, P1255) 8. Control Module Internal Performance DTC (P0606)	not active not active not active not active not active not active not active not active	<p><u>Frequency:</u> Continuous; 12.5 ms loop. 60 seconds between intrusive tests that pass</p> <p>Intrusive test requested if fuel system is clamped for >= 5 seconds or fuel pressure error variance <= typically (0.3 to 0.6) (calculated over a 2.5sec period); otherwise report pass</p> <p>Duration of intrusive test is fueling related (5 to 12 seconds).</p> <p>Intrusive test is run when fuel flow is below Max allowed fuel flow rate (Typical values in the range of 11 to 50 g/s)</p>	DTC Type A 1 trip

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					9. Engine run time 10. Emissions fuel level (PPEI \$3FB) AND Engine Run Time 11. Fuel pump control 12. Fuel pump control state 13. Engine fuel flow 14. ECM fuel control system failure (PPEI \$1ED)	>=5 seconds not low > 30 sec enabled normal or FRP Rationality control > 0.047 g/s failure has not occurred		
Fuel Rail Pressure (FRP) Sensor Circuit Low Voltage	P018C	This DTC detects if the fuel pressure sensor circuit is shorted to low	FRP sensor voltage	< 0.14 V			72 failures out of 80 samples 1 sample/12.5 ms	DTC Type A 1 trip
					Ignition	Run or Crank		
Fuel Rail Pressure (FRP) Sensor Circuit High Voltage	P018D	This DTC detects if the fuel pressure sensor circuit is shorted to high	FRP sensor voltage	> 4.86 V			72 failures out of 80 samples 1 sample/12.5 ms	DTC Type A 1 trip
					Ignition	Run or Crank		
Fuel Pump Control Circuit Low Voltage	P0231	This DTC detects if the fuel pump control circuit is shorted to low	Fuel Pump Current	> 14.48A			72 test failures in 80 test samples if Fuel Pump Current <100A 3 test failures in 15 test samples if Fuel Pump Current >=100A 1 sample/12.5 ms	DTC Type A 1 trip
					Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run/Crank Voltage	Run or Crank enabled enabled 9V < voltage < 32V		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
Fuel Pump Control Circuit High Voltage	P0232	This DTC detects if the fuel pump control circuit is shorted to high	Voltage measured at fuel pump circuit	> 3.86 V	Commanded fuel pump output Fuel pump control enable Time that above conditions are met	0% duty cycle (off) False >=4.0 seconds	36 test failures in 40 test samples; 1 sample/12.5ms Pass/Fail determination made only once per trip	DTC Type A 1 trip
Fuel Pump Control Circuit (Open)	P023F	This DTC detects if the fuel pump control circuit is open	Fuel Pump Current AND Fuel Pump Duty Cycle	<=0.5A □ > 20%	Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run/Crank voltage	Run or Crank Enabled Enabled 9V <voltage< 32V	72 test failures in 80 test samples; 1 sample/12.5ms	DTC Type A 1 trip
Fuel System Control Module Enable Control Circuit	P025A	This DTC detects if there is a fault in the fuel pump control enable circuit	PPEI (PPEI (Powertrain Platform Electrical Interface) Fuel System Request (\$1ED)	≠ Fuel Pump Control Module Enable Control Circuit	Ignition AND PPEI Fuel System Request (\$1ED)	Run or Crank Valid	72 failures out of 80 samples 1 sample/12.5 ms	DTC Type A 1 trip
Control Module Read Only Memory (ROM)	P0601	This DTC will be stored if any software or calibration check sum is incorrect	Calculated Checksum (CRC16)	≠ stored checksum for any of the parts (boot, software, application calibration, system calibration)	Ignition OR	Run or Crank	1 failure if it occurs during the first ROM test of the ignition cycle, otherwise 5 failures Frequency: Runs continuously in the background	DTC Type A 1 trip

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					HS Comm OR Fuel Pump Control	enabled enabled		
Control Module Not Programmed	P0602	Indicates that the FSCM needs to be programmed	This DTC is set via calibration, when KeMEMD_b_NoStartCal	TRUE	 Ignition OR HS Comm OR Fuel Pump Control	 Run or Crank enabled enabled	Runs once at power up	DTC Type A 1 trip
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error at controller power-up	Checksum at power-up	≠ checksum at power-down	 Ignition OR HS Comm OR Fuel Pump Control	 Run or Crank enabled enabled	Frequency: Once at power-up	DTC Type A 1 trip
Control Module Random Access Memory (RAM)	P0604	Indicates that control module is unable to correctly write and read data to and from RAM	Data read	≠ Data written	 Ignition OR HS Comm OR Fuel Pump Control	 Run or Crank enabled enabled	1 failure if it occurs during the first RAM test of the ignition cycle, otherwise 5 failures Frequency: Runs continuously in the background.	DTC Type A 1 trip
Control Module Internal Performance 1. Main Processor Configuration Register Test	P0606	This DTC indicates the FSCM has detected an internal processor fault or external watchdog fault (PID 2032 can tell what causes the fault.)	1. For all I/O configuration register faults: •Register contents	Incorrect value.	Ignition	Run or Crank	Tests 1 and 2 1 failure Frequency: Continuously (12.5ms)	DTC Type A 1 trip

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
2. Processor clock test 3. External watchdog test			2. For Processor Clock Fault: •EE latch flag in EEPROM. OR • RAM latch flag. 3. For External Watchdog Fault: • Software control of fuel pump driver	0x5A5A 0x5A Control Lost	OR HS Comm OR Fuel Pump Control 1. For all I/O configuration register faults: •KeMEMD_b_ProcFitCfgRegEnbl 2. For Processor Clock Fault: •KeMEMD_b_ProcFitCLKDiagEnbl 3. For External Watchdog Fault: •KeFRPD_b_FPExtWDogDiagEnbl 3. For External Watchdog Fault: •Control Module ROM(P0601) 3. For External Watchdog Fault: •Control Module RAM(P0604)	enabled enabled TRUE TRUE TRUE not active not active	Test 3 3 failures out of 15 samples 1 sample/12.5 ms	
Control Module Long Term Memory (EEPROM) Performance	P062F	Indicates that the NVM Error flag has not been cleared	Last EEPROM write	Did not complete	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 test failure Once on controller power-up	DTC Type A 1 trip
5Volt Reference Circuit (Short High/Low)	P0641	Detects continuous short on the #1 5V sensor reference circuit	Reference voltage AND Output OR Reference voltage AND Output	>= 0.5V inactive >= 5.5V active	Ignition	Run or Crank	15 failures out of 20 samples 1 sample/12.5 ms	DTC Type A 1 trip

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
			OR Reference voltage AND Output	<= 4.5V active				
Fuel Pump Control Module - Driver Over-temperature 1	P064A	This DTC detects if an internal fuel pump driver overtemperature condition exists under normal operating conditions (Tier 1 supplier Continental responsibility)	Module Range of Operation AND Fuel pump driver Temp	1. Module is within Acceptable Operation Range (Motorola's responsibility - FSCM is in normal operating range for module voltage versus PWM duty cycle. Linear range from 100% @ 12.5V to 70% @ 18V.) > 190C	Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run / Crank KeFRPD_b_FPOverTempDiagEn bl	Run or Crank Enabled Enabled 9V<voltage<32V TRUE	3 failures out of 15 samples 1 sample/12.5 ms	DTC Type B 2 trips
Fuel Pump Control Module - Driver Over-temperature 2	P1255	This DTC detects if an internal fuel pump driver overtemperature condition exists under extreme operating conditions (GM's responsibility)	Module Range of Operation AND Fuel pump driver Temp	Outside normal range (FSCM is NOT in normal operating range for module voltage versus PWM duty cycle. Linear range from 100% @ 12.5V to 70% @ 18V.) > 190C	Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run / Crank KeFRPD_b_FPOverTempDiagEn bl	Run or Crank Enabled Enabled 9V<voltage<32V TRUE	3 failures out of 15 samples 1 sample/12.5 ms	DTC Type B 2 trips
Ignition 1 Switch Circuit Low Voltage	P2534	This DTC detects if the Ignition1 Switch circuit is shorted to low or open	Ignition 1 voltage	<= 6 V	Engine	Running	279 failures out of 300 samples 1 sample/25.0 ms	DTC Type A 1 trip
Fuel Pump Flow Performance (rationality)	P2635	This DTC detects degradation in the performance of the SIDI electronic return-less fuel system	Filtered fuel rail pressure error	<= Low Threshold (function of desired fuel rail pressure and fuel flow rate. 15% of resultant Target Pressure) OR >= High Threshold (function of desired fuel rail pressure and fuel flow rate. 15% of resultant Target Pressure) (See Supporting Tables tab)	1. FRP Circuit Low DTC (P018C)	not active	Filtered fuel rail pressure error Time Constant = 12.5 seconds Frequency: Continuous 12.5 ms loop	DTC Type B 2 trips

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					2. FRP Circuit High DTC (P018D)	not active		
					3. Fuel Pressure Sensor Performance DTC (P018B)	not active		
					4. FuelPump Circuit Low DTC (P0231)	not active		
					5. FuelPump Circuit High DTC (P0232)	not active		
					6. FuelPump Circuit Open DTC (P023F)	not active		
					7. Reference Voltage DTC (P0641)	not active		
					8. Fuel Pump Control Module Driver Over-temperature DTC's (P064A, P1255)	not active		
					9. Control Module Internal Performance DTC (P0606)	not active		
					10. An ECM fuel control system failure (PPEI \$1ED)	has not occurred		
					11. The Barometric pressure (PPEI \$4C1) signal	valid (for absolute fuel pressure sensor)		
					12. Engine run time	>= 30 seconds		
					13. Emissions fuel level (PPEI \$3FB) AND Engine Run Time	not low > 30 sec		
					14. Fuel pump control	enabled		
					15. Fuel pump control state	normal		
					16. Battery Voltage	11V<=voltage=<32V		
					17. Fuel flow rate (See Supporting Tables tab)	> 0.047 g/s AND <= Max allowed fuel flow rate as a function of desired rail pressure & Vbatt (Typical values in the range of 11 to 50 g/s)		

COMPONENT/ SYSTEM	FAULT CODE	MONITOR STRATEGY DESCRIPTION	MALFUNCTION CRITERIA	THRESHOLD VALUE	SECONDARY PARAMETERS	ENABLE CONDITIONS	TIME REQUIRED	MIL ILLUM.
					18. Fuel Pressure Control System	Is not responding to an over-pressurization due to pressure build during DFCO or a decreasing desired pressure command.		
Control Module Communication Bus "A" Off	U0073	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state	Bus Status	Off	Power mode	Run/Crank	5 failures out of 5 samples (5 seconds)	DTC Type B 2 trips
Lost Communication With ECM/PCM "A"	U0100	Detects that CAN serial data communication has been lost with the ECM	Message \$0C9	Undetected	1. Power mode 2. Ignition Run/Crank Voltage 3. U0073	Run/Crank 11V<=voltage=<32V not active	12 failures out of 12 samples (12 seconds)	DTC Type B 2 trips

X-axis= Desired Fuel Pressure (kiloPascals)
Y-axis= Battery voltage (volts)

	200	250	300	350	400	450	500	550	600	
4.5	19.5	19.5	19.5	19.5	19.5	19.5	19.08594	16.86719	14.6875	12.53906
6	19.5	19.5	19.5	19.5	19.5	19.5	19.08594	16.86719	14.6875	12.53906
7.5	19.5	19.5	19.5	19.5	19.5	19.5	19.08594	16.86719	14.6875	12.53906
9	19.5	19.5	19.5	19.5	19.5	19.5	19.08594	16.86719	14.6875	12.53906
10.5	19.5	19.5	19.5	19.5	19.5	19.5	19.08594	16.86719	14.6875	12.53906
12	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.10938
13.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
15	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
16.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
18	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
21	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
22.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
24	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
25.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
27	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5
28.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5	19.5

P2635 Fuel Pump Performance Filtered Pressure Error Fault Threshold High map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	30	37.5	45	52.5	60	67.5	75	82.5	90
1.5	30	37.5	45	52.5	60	67.5	75	82.5	90
3	30	37.5	45	52.5	60	67.5	75	82.5	90
4.5	30	37.5	45	52.5	60	67.5	75	82.5	90
6	30	37.5	45	52.5	60	67.5	75	82.5	90
7.5	30	37.5	45	52.5	60	67.5	75	82.5	90
9	30	37.5	45	52.5	60	67.5	75	82.5	90
10.5	30	37.5	45	52.5	60	67.5	75	82.5	90
12	30	37.5	45	52.5	60	67.5	75	82.5	90
13.5	30	37.5	45	52.5	60	67.5	75	82.5	90
15	30	37.5	45	52.5	60	67.5	75	82.5	90
16.5	30	37.5	45	52.5	60	67.5	75	82.5	90
18	30	37.5	45	52.5	60	67.5	75	82.5	90
19.5	30	37.5	45	52.5	60	67.5	75	82.5	90
21	30	37.5	45	52.5	60	67.5	75	82.5	90
22.5	30	37.5	45	52.5	60	67.5	75	82.5	90
24	30	37.5	45	52.5	60	67.5	75	82.5	90
25.5	30	37.5	45	52.5	60	67.5	75	82.5	90
27	30	37.5	45	52.5	60	67.5	75	82.5	90
28.5	30	37.5	45	52.5	60	67.5	75	82.5	90
30	30	37.5	45	52.5	60	67.5	75	82.5	90
31.5	30	37.5	45	52.5	60	67.5	75	82.5	90
33	30	37.5	45	52.5	60	67.5	75	82.5	90
34.5	30	37.5	45	52.5	60	67.5	75	82.5	90
36	30	37.5	45	52.5	60	67.5	75	82.5	90
37.5	30	37.5	45	52.5	60	67.5	75	82.5	90
39	30	37.5	45	52.5	60	67.5	75	82.5	90
40.5	30	37.5	45	52.5	60	67.5	75	82.5	90
42	30	37.5	45	52.5	60	67.5	75	82.5	90
43.5	30	37.5	45	52.5	60	67.5	75	82.5	90
45	30	37.5	45	52.5	60	67.5	75	82.5	90
46.5	30	37.5	45	52.5	60	67.5	75	82.5	90
48	30	37.5	45	52.5	60	67.5	75	82.5	90

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold High map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
1.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
3	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
4.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
6	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
7.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
9	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
10.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
12	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
13.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
15	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
16.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
18	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
19.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
21	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
22.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
24	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
25.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
27	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
28.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
30	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
31.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
33	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
34.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
36	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
37.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
39	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
40.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
42	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
43.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
45	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
46.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
48	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5

P2635 Fuel Pump Performance Filtered Pressure Error Fault Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
1.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
3	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
4.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
6	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
7.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
9	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
10.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
12	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
13.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
15	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
16.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
18	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
19.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
21	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
22.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
24	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
25.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
27	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
28.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
30	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
31.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
33	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
34.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
36	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
37.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
39	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
40.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
42	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
43.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
45	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
46.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
48	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
1.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
3	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
4.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
6	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
7.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
9	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
10.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
12	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
13.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
15	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
16.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
18	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
19.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
21	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
22.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
24	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
25.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
27	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
28.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
30	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
31.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
33	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
34.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
36	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
37.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
39	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
40.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
42	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
43.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
45	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
46.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
48	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5