

This document was prepared in the following main sections (worksheets) for MY12 ERF5 Diagnostics in Group 5

Section 1 : S1-C101_Ecotec Inline4_Common

Contains information that is common to all C101-controller ERF5 applications within 12OBDG5 with engine RPOs and VPPCs

- 1) LAF 2.4L Ecotec I-4 SIDI, 2) LEA 2.4L Ecotec I-4 SIDI
- 1) GMT172, GMT177, 2) GMT311, 3) D1SB, D1NC

Section 2 : S2-C202_Ecotec Inline4_Common

Contains information that is common to all C202-controller ERF5 applications within 12OBDG5 with engine RPOs and VPPCs

- 1) LEA 2.4L Ecotec I-4 SIDI, 2) LHU 2.0L Turbocharged Ecotec I-4 SIDI, 3) LUK 2.4L BAS+ Hybrid Ecotec I-4 SIDI
- 1) GMX350, GMX353

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					3) LUK 2.4L BAS+ Hybrid Ecotec I-4 SIDI 10. Emissions fuel level (PPEI \$3FB) 11. Fuel pump control AND Ignition Run/Crank Voltage	not low enabled 9V < voltage < 32V		
Fuel System Control Module Enable Control Circuit	P025A	This DTC detects if there is a fault in the fuel pump control enable circuit	PPEI (PPEI (Powertrain Platform Electrical Interface) Fuel System Request (\$1ED)	≠ Fuel Pump Control Module Enable Control Circuit	Ignition AND PPEI Fuel System Request (\$1ED)	Run or Crank valid	72 failures out of 80 samples 1 sample/12.5 ms	DTC Type A 1 trip
Control Module Read Only Memory (ROM)	P0601	This DTC will be stored if any software or calibration check sum is incorrect	Calculated Checksum (CRC16)	≠ stored checksum for any of the parts (boot, software, application calibration, system calibration)	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 failure if it occurs during the first ROM test of the ignition cycle, otherwise 5 failures Frequency: Runs continuously in the background	DTC Type A 1 trip
Control Module Not Programmed	P0602	Indicates that the FSCM needs to be programmed	This DTC is set via calibration, when KeMEMD_b_NoStar tCal	= TRUE	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	Runs once at power up	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

S1-C101 SECTION
1 OF 2 SECTIONS

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error at controller power-up	Checksum at power- up	≠ checksum at power-down	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 failure Frequency: Once at power-up	DTC Type A 1 trip
Control Module Random Access Memory (RAM)	P0604	Indicates that control module is unable to correctly write and read data to and from RAM	Data read	≠ Data written	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 failure if it occurs during the first RAM test of the ignition cycle, otherwise 5 failures Frequency: Runs continuously in the background.	DTC Type A 1 trip
Control Module Internal Performance 1. Main Processor Configuration Register Test	P0606	This DTC indicates the FSCM has detected an internal processor fault or external watchdog fault (PID 2032 discriminates the source of the fault)	1. For all I/O configuration register faults: •Register contents	Incorrect value.	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	Tests 1 and 2 1 failure Frequency: Continuously (12.5ms)	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
2. Processor clock test 3. External watchdog test			2. For Processor Clock Fault: •EE latch flag in EEPROM. OR • RAM latch flag. 3. For External Watchdog Fault: • Software control of fuel pump driver	0x5A5A 0x5A Control Lost	1. For all I/O configuration register faults: •KeMEMD_b_ProcFitCfgRegEn bl 2. For Processor Clock Fault: •KeMEMD_b_ProcFitCLKDiagE nbl 3. For External Watchdog Fault: •KeFRPD_b_FPExtWDogDiagE nbl 3. For External Watchdog Fault: •Control Module ROM(P0601) 3. For External Watchdog Fault: •Control Module RAM(P0604)	TRUE TRUE TRUE not active not active	Test 3 3 failures out of 15 samples 1 sample/12.5 ms	
Control Module Long Term Memory (EEPROM) Performance	P062F	Indicates that the NVM Error flag has not been cleared	Last EEPROM write	Did not complete	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 test failure Once on controller power-up	DTC Type A 1 trip
5Volt Reference Circuit (Short High/Low/Out of Range)	P0641	Detects continuous short or out of range on the #1 5V sensor reference circuit	Reference voltage AND Output	>= 0.5V inactive	Ignition	Run or Crank	15 failures out of 20 samples 1 sample/12.5 ms	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
			OR Reference voltage AND Output OR Reference voltage AND Output	>= 5.5V active <= 4.5V active				
			OR Reference voltage	> 105% nominal (i.e., 5.25V) OR <95% nominal (i.e., 4.75V)				
Fuel Pump Control Module - Driver Over- temperature 1	P064A	This DTC detects if an internal fuel pump driver overttemperature condition exists under normal operating conditions	Pump Driver Temp	> 150C	Ignition OR HS Comm OR Fuel Pump Control KeFRPD_b_FPOverTempDiagE nbl Ignition Run/Crank	Run or Crank enabled enabled TRUE 9V<voltage<32V	3 failures out of 15 samples 1 sample/12.5 ms	DTC Type B 2 trips
Ignition 1 Switch Circuit Low Voltage	P2534	This DTC detects if the Ignition1 Switch circuit is shorted to low or open	Ignition 1 voltage	<= 6 V	Engine	Running	180 failures out of 200 samples 1 sample/25.0 ms	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Fuel Pump Flow Performance (rationality)	P2635	This DTC detects degradation in the performance of the SIDI electronic return-less fuel system	Filtered fuel rail pressure error	<= Low Threshold (Function of desired fuel rail pressure and fuel flow rate. Margin is 15% of resultant target pressure except at flow <= 1.5g/s and target pressure <= 350kPa where the margin increases continuously at 66.6kPa/g/s as flow decreases) OR >= High Threshold (function of desired fuel rail pressure and fuel flow rate. 15% of resultant Target Pressure) (See Supporting Tables tab)	1. FRP Circuit Low DTC (P018C)	not active	Filtered fuel rail pressure error Time Constant = 12.5 seconds Frequency: Continuous 12.5 ms loop	DTC Type B 2 trips
					2. FRP Circuit High DTC (P018D)	not active		
					3. Fuel Rail Pressure Sensor Performance DTC (P018B)	not active		
					4. FuelPump Circuit Low DTC (P0231)	not active		

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					5. FuelPump Circuit High DTC (P0232)	not active		
					6. FuelPump Circuit Open DTC (P023F)	not active		
					7. Reference Voltage DTC (P0641)	not active		
					8. Fuel Pump Control Module Driver Over-temperature DTC's (P064A)	not active		
					9. Control Module Internal Performance DTC (P0606)	not active		
					10. An ECM fuel control system failure (PPEI \$1ED)	has not occurred		
					11. The Barometric pressure (PPEI \$4C1) signal	valid (for absolute fuel pressure sensor)		
					12. Engine run time	>= 30 seconds		
					13. Emissions fuel level (PPEI \$3FB)	not low		
					14. Fuel pump control	enabled		
					15. Fuel pump control state	normal		
					16. Battery Voltage	11V<=voltage=<32V		
					17. Fuel flow rate (See Supporting Tables tab)	> 0.047 g/s AND <= Max allowed fuel flow rate as a function of desired rail pressure & Vbatt (Typical values in the range of 11 to 50 g/s)		
					18. Fuel Pressure Control System	Is not responding to an over-pressurization due to pressure build during DFCO or a decreasing desired pressure command.		

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Control Module Communication Bus "A" Off	U0073	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state	Bus Status	Off	Power mode	Run/Crank	5 failures out of 5 samples (5 seconds)	DTC Type B 2 trips
Lost Communication With ECM/PCM "A"	U0100	Detects that CAN serial data communication has been lost with the ECM	Message \$0C9	Undetected	1. Power mode 2. Ignition Run/Crank Voltage 3. U0073	Run/Crank 11V<voltage<32V not active	12 failures out of 12 samples (12 seconds)	DTC Type B 2 trips

12 OBDG05A FSCM Diagnostics

Supporting Tables

X-axis= Desired Fuel Pressure (kiloPascals)

Y-axis= Battery voltage (volts)

	200	250	300	350	400	450	500	550	600
4.5	13.89844	13.89844	13.89844	13.89844	12.49219	9.648438	6.882813	4.1875	1.5625
6	13.89844	13.89844	13.89844	13.89844	12.49219	9.648438	6.882813	4.1875	1.5625
7.5	13.89844	13.89844	13.89844	13.89844	12.49219	9.648438	6.882813	4.1875	1.5625
9	13.89844	13.89844	13.89844	13.89844	12.49219	9.648438	6.882813	4.1875	1.5625
10.5	13.89844	13.89844	13.89844	13.89844	12.49219	9.648438	6.882813	4.1875	1.5625
12	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	12.99219	10.21875	7.515625
13.5	13.89844	13.89844	1) LEA 2.4	13.89844	13.89844	13.89844	13.89844	13.89844	13.47656
			3) LUK 2.4L BAS+ Hybrid Ecotec I-4 SIDI						
15	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844
16.5	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844	13.89844
9	30	37.5	45	52.5	60	67.5	75	82.5	90
10.5	30	37.5	45	52.5	60	67.5	75	82.5	90
12	30	37.5	45	52.5	60	67.5	75	82.5	90
13.5	30	37.5	45	52.5	60	67.5	75	82.5	90
15	30	37.5	45	52.5	60	67.5	75	82.5	90
16.5	30	37.5	45	52.5	60	67.5	75	82.5	90
18	30	37.5	45	52.5	60	67.5	75	82.5	90
19.5	30	37.5	45	52.5	60	67.5	75	82.5	90
21	30	37.5	45	52.5	60	67.5	75	82.5	90
22.5	30	37.5	45	52.5	60	67.5	75	82.5	90
24	30	37.5	45	52.5	60	67.5	75	82.5	90
25.5	30	37.5	45	52.5	60	67.5	75	82.5	90
27	30	37.5	45	52.5	60	67.5	75	82.5	90
28.5	30	37.5	45	52.5	60	67.5	75	82.5	90
30	30	37.5	45	52.5	60	67.5	75	82.5	90
31.5	30	37.5	45	52.5	60	67.5	75	82.5	90
33	30	37.5	45	52.5	60	67.5	75	82.5	90
34.5	30	37.5	45	52.5	60	67.5	75	82.5	90
36	30	37.5	45	52.5	60	67.5	75	82.5	90
37.5	30	37.5	45	52.5	60	67.5	75	82.5	90
39	30	37.5	45	52.5	60	67.5	75	82.5	90
40.5	30	37.5	45	52.5	60	67.5	75	82.5	90
42	30	37.5	45	52.5	60	67.5	75	82.5	90
43.5	30	37.5	45	52.5	60	67.5	75	82.5	90
45	30	37.5	45	52.5	60	67.5	75	82.5	90
46.5	30	37.5	45	52.5	60	67.5	75	82.5	90
48	30	37.5	45	52.5	60	67.5	75	82.5	90

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold High map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
1.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
3	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
4.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
6	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
7.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
9	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
10.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
12	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
13.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
15	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
16.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
18	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
19.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
21	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
22.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
24	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
25.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
27	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
28.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
30	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
31.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
33	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
34.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
36	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
37.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
39	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
40.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
42	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
43.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
45	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
46.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
48	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-260	-210	-160	-110	-60	-67.5	-75	-82.5	-90
1.5	-145	-125	-102.5	-81.25	-60	-67.5	-75	-82.5	-90
3	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
4.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
6	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
7.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
9	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
10.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
12	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
13.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
15	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
16.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
18	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
19.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
21	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
22.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
24	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
25.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
27	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
28.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
30	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
31.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
33	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
34.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
36	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
37.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
39	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
40.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
42	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
43.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
45	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
46.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
48	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-221	-178.5	-136	-93.5	-51	-57.375	-63.75	-70.125	-76.5
1.5	-123.25	-106.25	-87.125	-69.0625	-51	-57.375	-63.75	-70.125	-76.5
3	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
4.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
6	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
7.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
9	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
10.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
12	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
13.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
15	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
16.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
18	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
19.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
21	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
22.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
24	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
25.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
27	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
28.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
30	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
31.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
33	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
34.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
36	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
37.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
39	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
40.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
42	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
43.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
45	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
46.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
48	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Fuel Rail Pressure (FRP) Sensor Performance (rationality)	P018B	This DTC detects a fuel pressure sensor response stuck within the normal operating range	Absolute value of change in fuel pressure as sensed during intrusive test.	<= 30 kPa	1. FRP Circuit Low DTC (P018C) 2. FRP Circuit High DTC (P018D) 3. FuelPump Circuit Low DTC (P0231) 4. FuelPump Circuit High DTC (P0232) 5. FuelPump Circuit Open DTC (P023F) 6. Reference Voltage DTC (P0641) 7. Fuel Pump Control Module Driver Over-temperature DTC's (P064A, P1255) 8. Control Module Internal Performance DTC (P0606) 1) LEA 2.4L Ecotec I-4 SIDI, 2) LHU 2.0L Turbocharged Ecotec I-4 SIDI, 3) LUK 2.4L BAS+ Hybrid Ecotec I-4 SIDI	not active not active not active not active not active not active not active >=5 seconds	<u>Frequency:</u> Continuous; 12.5 ms loop. 60 seconds between intrusive tests that pass Intrusive test requested if fuel system is clamped for >= 5 seconds or fuel pressure error variance <= typically (0.3 to 0.6) (calculated over a 2.5sec period); otherwise report pass Duration of intrusive test is fueling related (5 to 12 seconds). Intrusive test is run when fuel flow is below Max allowed fuel flow rate (Typical values in the range of 11 to 50 g/s)	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					10. Emissions fuel level (PPEI \$3FB) AND Engine Run Time 11. Fuel pump control Fuel Pump Control	not low > 30 sec enabled enabled		
Control Module Not Programmed	P0602	Indicates that the FSCM needs to be programmed	This DTC is set via calibration, when KeMEMD_b_NoStart Cal	TRUE	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	Runs once at power up	DTC Type A 1 trip
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error at controller power-up	Checksum at power-up	≠ checksum at power-down	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 failure Frequency: Once at power-up	DTC Type A 1 trip
Control Module Random Access Memory (RAM)	P0604	Indicates that control module is unable to correctly write and read data to and from RAM	Data read	≠ Data written	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	1 failure if it occurs during the first RAM test of the ignition cycle, otherwise 5 failures Frequency: Runs continuously in the background.	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination						
Control Module Internal Performance 1. Main Processor Configuration Register Test	P0606	This DTC indicates the FSCM has detected an internal processor fault or external watchdog fault (PID 2032 differentiates cause of fault.)	1. For all I/O configuration register faults: •Register contents	Incorrect value.	Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled	Tests 1 and 2 1 failure Frequency: Continuously (12.5ms)	DTC Type A 1 trip						
									2. Processor clock test	2. For Processor Clock Fault: •EE latch flag in EEPROM. OR • RAM latch flag.	0x5A5A	1. For all I/O configuration register faults: •KeMEMD_b_ProcFltCfgRegE nbl	TRUE	Test 3 3 failures out of 15 samples 1 sample/12.5 ms
			3. For External Watchdog Fault: •KeFRPD_b_FPExtWDogDiag Enbl	TRUE										
								3. For External Watchdog Fault: •Control Module ROM(P0601)	not active					
			3. For External Watchdog Fault: •Control Module RAM(P0604)	not active										

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Control Module Long Term Memory (EEPROM) Performance	P062F	Indicates that the NVM Error flag has not been cleared	Last EEPROM write	Did not complete			1 test failure Once on controller power- up	DTC Type A 1 trip
					Ignition OR HS Comm OR Fuel Pump Control	Run or Crank enabled enabled		
5Volt Reference Circuit (Short High/Low/Out of Range)	P0641	Detects continuous short or out of range on the #1 5V sensor reference circuit	Reference voltage AND Output OR Reference voltage AND Output OR Reference voltage AND Output OR Reference voltage	>= 0.5V inactive >= 5.5V active <= 4.5V active > 102.5% nominal (i.e., 5.125V) OR <97.5% nominal (i.e., 4.875V)	Ignition	Run or Crank	15 failures out of 20 samples 1 sample/12.5 ms	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Fuel Pump Control Module - Driver Over- temperature 1	P064A	This DTC detects if an internal fuel pump driver overtemperature condition exists under normal operating conditions (Tier 1 supplier Continental responsibility)	Module Range of Operation AND Fuel pump driver Temp	1. Module is within Acceptable Operation Range (Motorola's responsibility - FSCM is in normal operating range for module voltage versus PWM duty cycle. Linear range from 100% @ 12.5V to 70% @ 18V.) > 190C	Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run / Crank KeFRPD_b_FPOverTempDiag Enbl	Run or Crank Enabled Enabled 9V<voltage<32V TRUE	3 failures out of 15 samples 1 sample/12.5 ms	DTC Type B 2 trips
Fuel Pump Control Module - Driver Over- temperature 2	P1255	This DTC detects if an internal fuel pump driver overtemperature condition exists under extreme operating conditions (GM's responsibility)	Module Range of Operation AND Fuel pump driver Temp	Outside normal range (FSCM is NOT in normal operating range for module voltage versus PWM duty cycle. Linear range from 100% @ 12.5V to 70% @ 18V.) > 190C	Ignition OR HS Comm OR Fuel Pump Control AND Ignition Run / Crank KeFRPD_b_FPOverTempDiag Enbl	Run or Crank Enabled Enabled 9V<voltage<32V TRUE	3 failures out of 15 samples 1 sample/12.5 ms	DTC Type B 2 trips
Ignition 1 Switch Circuit Low Voltage	P2534	This DTC detects if the Ignition1 Switch circuit is shorted to low or open	Ignition 1 voltage	<= 6 V	Engine	Running	180 failures out of 200 samples 1 sample/25.0 ms	DTC Type A 1 trip

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Fuel Pump Flow Performance (rationality)	P2635	This DTC detects degradation in the performance of the SIDI electronic return-less fuel system	Filtered fuel rail pressure error	<= Low Threshold (Function of desired fuel rail pressure and fuel flow rate. Margin is 15% of resultant target pressure except at flow <= 1.5g/s and target pressure <= 350kPa where the margin increases continuously at 66.6kPa/g/s as flow decreases) OR >= High Threshold (function of desired fuel rail pressure and fuel flow rate. 15% of resultant Target Pressure) (See Supporting Tables tab)	1. FRP Circuit Low DTC (P018C)	not active	Filtered fuel rail pressure error Time Constant = 12.5 seconds Frequency: Continuous 12.5 ms loop	DTC Type B 2 trips
					2. FRP Circuit High DTC (P018D)	not active		
					3. Fuel Pressure Sensor Performance DTC (P018B)	not active		
					4. FuelPump Circuit Low DTC (P0231)	not active		
					5. FuelPump Circuit High DTC (P0232)	not active		
					6. FuelPump Circuit Open DTC (P023F)	not active		
					7. Reference Voltage DTC (P0641)	not active		

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
					8. Fuel Pump Control Module Driver Over-temperature DTC's (P064A, P1255)	not active		
					9. Control Module Internal Performance DTC (P0606)	not active		
					10. An ECM fuel control system failure (PPEI \$1ED)	has not occurred		
					11. The Barometric pressure (PPEI \$4C1) signal	valid (for absolute fuel pressure sensor)		
					12. Engine run time	>= 30 seconds		
					13. Emissions fuel level (PPEI \$3FB) AND Engine Run Time	not low > 30 sec		
					14. Fuel pump control	enabled		
					15. Fuel pump control state	normal		
					16. Battery Voltage	11V<=voltage=<32 V		
					17. Fuel flow rate (See Supporting Tables tab)	> 0.047 g/s AND <= Max allowed fuel flow rate as a function of desired rail pressure & Vbatt (Typical values in the range of 11 to 50 g/s)		
					18. Fuel Pressure Control System	Is not responding to an over-pressurization due to pressure build during DFCO or a decreasing desired pressure command.		

12 OBDG05A FSCM Diagnostics

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illumination
Control Module Communicati on Bus "A" Off	U0073	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus- off state	Bus Status	Off	Power mode	Run/Crank	5 failures out of 5 samples (5 seconds)	DTC Type B 2 trips
Lost Communicati on With ECM/PCM "A"	U0100	Detects that CAN serial data communication has been lost with the ECM	Message \$0C9	Undetected	1. Power mode 2. Ignition Run/Crank Voltage 3. U0073	Run/Crank 11V<=voltage=<32 V not active	12 failures out of 12 samples (12 seconds)	DTC Type B 2 trips

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Maximum Fuel Flow map (grams / s)

X-axis= Desired Fuel Pressure (kiloPascals)

Y-axis= Battery voltage (volts)

	200	250	300	350	400	450	500	550	600
4.5	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156
6	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156
7.5	17.10156	17.10156	1) LEA 2.4	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156
			3) LUK 2.4L BAS+ Hybrid Ecotec I-4 SIDI						
9	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156
10.5	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156	17.10156
3	30	37.5	45	52.5	60	67.5	75	82.5	90
4.5	30	37.5	45	52.5	60	67.5	75	82.5	90
6	30	37.5	45	52.5	60	67.5	75	82.5	90
7.5	30	37.5	45	52.5	60	67.5	75	82.5	90
9	30	37.5	45	52.5	60	67.5	75	82.5	90
10.5	30	37.5	45	52.5	60	67.5	75	82.5	90
12	30	37.5	45	52.5	60	67.5	75	82.5	90
13.5	30	37.5	45	52.5	60	67.5	75	82.5	90
15	30	37.5	45	52.5	60	67.5	75	82.5	90
16.5	30	37.5	45	52.5	60	67.5	75	82.5	90
18	30	37.5	45	52.5	60	67.5	75	82.5	90
19.5	30	37.5	45	52.5	60	67.5	75	82.5	90
21	30	37.5	45	52.5	60	67.5	75	82.5	90
22.5	30	37.5	45	52.5	60	67.5	75	82.5	90
24	30	37.5	45	52.5	60	67.5	75	82.5	90
25.5	30	37.5	45	52.5	60	67.5	75	82.5	90
27	30	37.5	45	52.5	60	67.5	75	82.5	90
28.5	30	37.5	45	52.5	60	67.5	75	82.5	90
30	30	37.5	45	52.5	60	67.5	75	82.5	90
31.5	30	37.5	45	52.5	60	67.5	75	82.5	90
33	30	37.5	45	52.5	60	67.5	75	82.5	90
34.5	30	37.5	45	52.5	60	67.5	75	82.5	90
36	30	37.5	45	52.5	60	67.5	75	82.5	90
37.5	30	37.5	45	52.5	60	67.5	75	82.5	90
39	30	37.5	45	52.5	60	67.5	75	82.5	90
40.5	30	37.5	45	52.5	60	67.5	75	82.5	90
42	30	37.5	45	52.5	60	67.5	75	82.5	90
43.5	30	37.5	45	52.5	60	67.5	75	82.5	90
45	30	37.5	45	52.5	60	67.5	75	82.5	90
46.5	30	37.5	45	52.5	60	67.5	75	82.5	90
48	30	37.5	45	52.5	60	67.5	75	82.5	90

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold High map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
1.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
3	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
4.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
6	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
7.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
9	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
10.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
12	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
13.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
15	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
16.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
18	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
19.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
21	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
22.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
24	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
25.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
27	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
28.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
30	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
31.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
33	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
34.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
36	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
37.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
39	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
40.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
42	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
43.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
45	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
46.5	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5
48	25.5	31.875	38.25	44.625	51	57.375	63.75	70.125	76.5

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-260	-210	-160	-110	-60	-67.5	-75	-82.5	-90
1.5	-145	-125	-102.5	-81.25	-60	-67.5	-75	-82.5	-90
3	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
4.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
6	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
7.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
9	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
10.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
12	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
13.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
15	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
16.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
18	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
19.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
21	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
22.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
24	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
25.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
27	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
28.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
30	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
31.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
33	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
34.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
36	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
37.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
39	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
40.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
42	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
43.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
45	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
46.5	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90
48	-30	-37.5	-45	-52.5	-60	-67.5	-75	-82.5	-90

12 OBDG05A FSCM Diagnostics

Supporting Tables

P2635 Fuel Pump Performance Filtered Pressure Error Fault RePass Threshold Low map (kiloPascals)

X-axis= Target Fuel Pressure (kiloPascals)
Y-axis= Fuel Flow (grams / s)

	200	250	300	350	400	450	500	550	600
0	-221	-178.5	-136	-93.5	-51	-57.375	-63.75	-70.125	-76.5
1.5	-123.25	-106.25	-87.125	-69.0625	-51	-57.375	-63.75	-70.125	-76.5
3	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
4.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
6	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
7.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
9	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
10.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
12	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
13.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
15	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
16.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
18	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
19.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
21	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
22.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
24	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
25.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
27	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
28.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
30	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
31.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
33	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
34.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
36	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
37.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
39	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
40.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
42	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
43.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
45	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
46.5	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5
48	-25.5	-31.875	-38.25	-44.625	-51	-57.375	-63.75	-70.125	-76.5