

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Camshaft Actuator Solenoid Circuit Open – Bank 1	P0010	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground.	<p>System supply voltage</p> <p>Output driver is commanded on</p> <p>Ignition switch is in crank or run position</p>	> 11.00 Volts	<p>20 failures out of 25 samples</p> <p>250 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Camshaft System Performance – Bank 1	P0011	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated.	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive.	(Intake cam Bank 1) Cam Position Error > (P0011_CamPosErrorLimIc1) deg	Intake Cam Phsr Enable System Voltage Engine Running Power Take Off (PTO) active Desired cam position Desired AND Measured cam position Desired cam position variation No Active DTCs	= TRUE > 11.00 Volts = TRUE = FALSE > 0 deg > (P0011_CamPosErrorLimIc1) deg AND < (CalculatedPerfMaxIc1) deg < 5.00 deg for (P0011_P05CC_StablePositionTimeIc1) seconds P0010 P2088 P2089	300.00 failures out of 400.00 samples 100 ms /sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Camshaft Actuator Solenoid Circuit Open – Bank 1	P0013	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200\text{ K } \Omega$ impedance between signal and controller ground.	System supply voltage Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	20 failures out of 25 samples 250 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Camshaft System Performance – Bank 1	P0014	Detects a VVT system error by comparing the desired and actual cam positions when VVT is activated.	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive.	(Exhaust cam Bank 1) Cam Position Error > (P0014_CamPosErrorLimEc1) deg	Exhaust Cam Phsr Enable System Voltage Engine Running Power Take Off (PTO) active Desired cam position Desired AND Measured cam position Desired cam position variation No Active DTCs	= TRUE > 11.00 Volts = TRUE = FALSE > 0 deg > (P0014_CamPosErrorLimEc1) deg AND < (CalculatedPerfMaxEc1) deg < 5.00 deg for (P0014_P05CE_StablePositionTimeEc1) seconds P0013 P2090 P2091	300.00 failures out of 400.00 samples 100 ms /sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP)- Camshaft Position (CMP) Correlation Bank 1 Sensor A (end-park phaser)	P0016	Detects cam to crank misalignment by monitoring if the cam sensor pulse for bank 1 sensor A occurs during the incorrect crank position, diagnostic passes when the cam sensor pulse is in the expected range	4 cam sensor pulses less than or greater than nominal position in one cam revolution.	-7.1 Crank Degrees 8.3 Crank Degrees	Crankshaft and camshaft position signals are synchronized Engine is Spinning Cam phaser is in "parked" position No Active DTCs: Time since last execution of diagnostic	CrankSensor_FA P0340, P0341 <div>< 1.0 seconds</div>	2 failures out of 3 tests. A failed test is 4 failures out of 5 samples. There is a delay after the first failed test to allow the camshaft position to return to the park position. This time is defined by the table P0016, P0017, P0018, P0019: Cam Correlation Oil Temperature Threshold One sample per cam rotation	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP)- Camshaft Position (CMP) Correlation Bank 1 Sensor B (end-park phaser)	P0017	Detects cam to crank misalignment by monitoring if the cam sensor pulse for bank 1 sensor B occurs during the incorrect crank position, diagnostic passes when the cam sensor pulse is in the expected range	4 cam sensor pulses less than or greater than nominal position in one cam revolution..	-8.4 Crank Degrees 9.2 Crank Degrees	Crankshaft and camshaft position signals are synchronized Engine is Spinning Cam phaser is in "parked" position No Active DTCs: Time since last execution of diagnostic	 CrankSensor_FA P0365, P0366 < 1.0 seconds	2 failures out of 3 tests. A failed test is 4 failures out of 5 samples. There is a delay after the first failed test to allow the camshaft position to return to the park position. This time is defined by the table P0016, P0017, P0018, P0019: Cam Correlation Oil Temperature Threshold One sample per cam rotation	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank 1 Sensor 1	P0030	Controller specific output driver circuit diagnoses the heater output low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	$\geq 200 \text{ K } \Omega$ impedance between output and controller ground.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	<p>20 failures out of 25 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips Note: In certain controllers P0031 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank1 Sensor1	P0031	Controller specific output driver circuit diagnoses the heater output low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	$\leq 0.5 \Omega$ impedance between output and controller ground.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	<p>20 failures out of 25 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips Note: In certain controllers P0030 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank1 Sensor1	P0032	Controller specific output driver circuit diagnoses the heater output low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between output and controller power.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	<p>20 failures out of 25 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank 1 Sensor 2	P0036	Controller specific output driver circuit diagnoses the heater output low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200 \text{ K } \Omega$ impedance between output and controller ground.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	20 failures out of 25 samples 250 ms / sample Continuous	Type B, 2 Trips Note: In certain controllers P0037 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank1 Sensor2	P0037	Controller specific output driver circuit diagnoses the heater output low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	$\leq 0.5 \Omega$ impedance between output and controller ground.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	<p>20 failures out of 25 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips Note: In certain controllers P0036 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Control Circuit Bank1 Sensor2	P0038	Controller specific output driver circuit diagnoses the heater output low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between output and controller power.	Ignition Voltage Engine Speed	= Crank or Run > 11.0 volts > 400 RPM	<p>20 failures out of 25 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HO2S Heater Resistance Bank 1 Sensor 1	P0053	<p>Detects an oxygen sensor heater having an incorrect or out of range resistance value. This test calculates the heater's resistance (using voltage and current) at engine start after a longer soak condition and compares it to the expected values for the released sensor.</p> <p>This fault is set if the heater resistance is outside the expected range.</p>	Heater Resistance outside of the expected range of	3.8 < ohms < 10.5	<p>No Active DTC's</p> <p>Coolant – IAT Engine Soak Time Coolant Temp Ignition Voltage Engine Run time</p>	<p>ECT_Sensor_FA P262B IAT_SensorFA < 8.0 °C > 28,800 seconds ≥ -30.0 °C < 32.0 volts < 0.09 seconds</p>	Once per valid cold start	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HO2S Heater Resistance Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0054	<p>Detects an oxygen sensor heater having an incorrect or out of range resistance value. This test calculates the heater's resistance (using voltage and current) at engine start after a soak condition and compares it to the expected values for the released sensor.</p> <p>This fault is set if the heater resistance is outside the expected range.</p>	Heater Resistance outside of the expected range of	6.7 < ohms < 14.0	<p>No Active DTC's</p> <p>Coolant – IAT Engine Soak Time Coolant Temp Ignition Voltage Engine Run time</p>	<p>ECT_Sensor_FA P262B IAT_SensorFA < 8.0 °C > 28,800 seconds ≥ -30.0 °C < 32.0 volts < 0.06 seconds</p>	Once per valid cold start	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module SIDI High Pressure Pump min/ max authority	P0089	This DTC determines when the high pressure pump control has reached to its max or min authority	High Pressure Fuel Pump Delivery Angle OR High Pressure Fuel Pump Delivery Angle	 >= 92 ° <= 0 °	High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Barometric Pressure Inlet Air Temp Fuel Temp Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) andCam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In	True >= 11 Volts > 0.300 MPa Enabled when a code clear is not active or not exiting device control Engine is not cranking >= 70.0 KPA >= -10.0 degC -10 <= Temp degC <= 132	Windup High/ Low 10.00 seconds failures out of 12.50 Seconds samples	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control commanded pressure is false and Device control pump ckt enabled on is false and Engine movement detected is true andManufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active			

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Pressure Pump Control Solenoid Enable Low Side Open Circuit	P0090	Controller specific output driver circuit diagnoses High Pressure pump Control Solenoid low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	>= 200 KOhms impedance between signal and controller ground	<p>Engine Speed</p> <p>Battery Voltage</p>	<p>>= 50 RPM</p> <p>>= 11 Volts</p> <p>Not in pump device control Enabled when a code clear is not active or not exiting device control</p>	<p>20 failures out of 40 samples</p> <p>100 ms /sample</p> <p>Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Pressure Pump Control Solenoid Enable Low Side Short to Ground	P0091	Controller specific output driver circuit diagnoses High Pressure pump Control Solenoid low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	<= 0.1 Amps between signal and controller ground	<p>Engine Speed</p> <p>Battery Voltage</p>	<p>>= 50 RPM</p> <p>>= 11 Volts</p> <p>Not in pump device control</p> <p>Enabled when a code clear is not active or not exiting device control</p>	<p>20 failures out of 40 samples</p> <p>100 ms /sample</p> <p>Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Pressure Pump Cntrl Solenoid Enable Low Side Short to Power	P0092	Controller specific output driver circuit diagnoses diagnoses High Pressure pump Control Solenoid low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	<= 1.1 or 15 Amps selectable thershold based on High pressure Pump .	Engine Speed Battery Voltage	>= 50 RPM >= 11 Volts Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 2 Circuit Performance (applications with humidity sensor and manifold temperature sensor)	P0096	<p>Detects an Intake Air Temperature 2 (IAT2) sensor value that is stuck in range by comparing the IAT2 sensor value against the IAT and IAT3 sensor values and failing the diagnostic if the IAT2 value is more different than the IAT and IAT3 values than is expected. If the engine has been off for a long enough period of time, the air temperature values in the engine compartment of the vehicle are considered to have equalized, and the diagnostic can be enabled.</p> <p>The diagnostic will fail if the IAT and IAT3 values are similar, and the IAT2 value is not similar to the IAT and IAT3 values. The diagnostic will also fail if none of the three sensor values are similar to each other, and the IAT2 value is furthest from the sensor value that is in the middle of the three sensor values.</p> <p>This diagnostic is executed once per</p>	<p><u>Good Correlation Between IAT and IAT3:</u></p> <p>ABS(Power Up IAT - Power Up IAT2)</p> <p>AND</p> <p>ABS(Power Up IAT - Power Up IAT3)</p> <p>AND</p> <p>ABS(Power Up IAT2 - Power Up IAT3)</p>	<p>> 25 deg C</p> <p><= 25 deg C</p> <p>> 25 deg C</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	Type B, 2 Trips
			<p><u>Not Good Correlation, IAT in middle:</u></p> <p>Power Up IAT is between Power Up IAT2 and Power Up IAT3</p> <p>AND</p> <p>ABS(Power Up IAT2 - Power Up IAT3)</p> <p>AND</p> <p>ABS(Power Up IAT - Power Up IAT2) > ABS(Power Up IAT - Power Up IAT3)</p>	<p>> 25 deg C</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	
			<p><u>Not Good Correlation, IAT3 in middle:</u></p> <p>Power Up IAT3 is between Power Up IAT and Power Up IAT2</p>		<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts >= 0.9 seconds</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ignition cycle if the enable conditions are met.	AND ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT3 - Power Up IAT2) > ABS(Power Up IAT3 - Power Up IAT)	> 25 deg C	No Active DTCs:	PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit 2 Low (applications with humidity)	P0097	<p>Detects a continuous short to ground in the Intake Air Temperature 2 (IAT2) signal circuit or an IAT2 sensor that is outputting a frequency signal that is too low. The diagnostic monitors the IAT2 sensor output frequency and fails the diagnostic when the IAT2 frequency is too low.</p> <p>The IAT2 sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. The temperature value is converted by the sensor to a frequency value in Hertz. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the frequency of the square wave signal and converts that frequency to a temperature value. A lower frequency is equivalent to a lower temperature.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	Raw IAT 2 Input	< 13 Hertz (~-60 deg C)	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>40 failures out of 50 samples</p> <p>1 sample every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit 2 High (applications with humidity)	P0098	<p>Detects an Intake Air Temperature 2 (IAT2) sensor that is outputting a frequency signal that is too high. The diagnostic monitors the IAT2 sensor output frequency and fails the diagnostic when the IAT2 frequency is too high.</p> <p>The IAT2 sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. The temperature value is converted by the sensor to a frequency value in Hertz. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the frequency of the square wave signal and converts that frequency to a temperature value. A higher frequency is equivalent to a higher temperature.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	Raw IAT 2 Input	> 390 Hertz (~150 deg C)	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>40 failures out of 50 samples</p> <p>1 sample every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 2 Intermittent In-Range (applications with humidity)	P0099	<p>Detects a noisy or erratic signal in the Intake Air Temperature 2 (IAT2) circuit by monitoring the IAT2 sensor and failing the diagnostic when the IAT2 signal has a noisier output than is expected.</p> <p>When the value of the IAT2 signal in °C is determined, a delta is calculated between the current reading and the previous reading. The absolute value of these deltas is summed over a number of IAT2 readings. The result of this summation is called a "string length". Since the IAT2 signal is anticipated to be relatively smooth, a string length of a particular magnitude indicates a noisy or erratic IAT2 signal. The diagnostic will fail if the string length is too high.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	<p>String Length</p> <p>Where: "String Length" = sum of "Diff" calculated over</p> <p>And where: "Diff" = ABS(current IAT 2 reading - IAT 2 reading from 100 milliseconds previous)</p>	<p>> 100.00 deg C</p> <p>10 consecutive IAT 2 readings</p>	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>4 failures out of 5 samples</p> <p>Each sample takes 1.0 seconds</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Radiator Coolant Temp Sensor Circuit Low Voltage	P00B3	Circuit Continuity This DTC detects a short to ground in the RCT (Radiator Coolant temperature) signal circuit or the RCT sensor. This is accomplished by monitoring the resistance of the circuit. If the resistance goes out of the expected range the DTC is set.	RCT Resistance (@ 150°C)	< 55 Ohms	Engine run time OR IAT min	> 10.0 seconds ≤ 70.3 °C	5 failures out of 6 samples 1 sec/ sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Radiator Coolant Temp Sensor Circuit High Voltage	P00B4	Circuit Continuity This DTC detects a short to high or open in the RCT (Radiator Coolant temperature) signal circuit or the RCT sensor. This is accomplished by monitoring the resistance of the circuit. If the resistance goes out of the expected range the DTC is set.	RCT Resistance (@ -60°C)	> 134,000 Ohms	Engine run time OR IAT min	> 60.0 seconds ≥ -9.0 °C	5 failures out of 6 samples 1 sec/ sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Flow Insufficient	P00B7	This DTC detects a Insufficient Flow Condition in the main cooling circuit. This check is done when all known restrictions in the system such as a thermostat are open and allowing coolant to flow through the radiator. DTC indication can be caused by a stuck closed thermostat or other unexpected restriction in the cooling system.	<p>Engine Coolant Temp (ECT) is</p> <p>AND</p> <p>Difference between ECT and RCT (Radiator Coolant Temp) is</p> <p>When above is present for fail counts start.</p>	<p>> 116.8 Deg C</p> <p>> 40.0 Deg C</p> <p>> 5 seconds</p>	<p>No Active DTC's</p> <p>Engine run time AND Engine Coolant Temp</p>	<p>THMR_RCT_Sensor_Ckt_FA THMR_ECT_Sensor_Ckt_FA</p> <p>> 30 seconds</p> <p>> 90.0 Deg C</p>	<p>30 failures out of 60 samples</p> <p>1 sec/ sample Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Pressure Start Diagnostic	P00C6	The DTC Diagnoses the high side fuel pressure during engine cranking.	<p>The ECM detects that the fuel pressure is not rising or has fallen beyond acceptable limits during engine cranking</p> <p>Pressure Rise Test: Sensed High Pressure Fuel Rail Pressure value</p> <p>Pressure Fall Test: Sensed High Pressure Fuel Rail Pressure value</p>	<p>< P00C6 - Minimum pressure in MPa that will exit High Pressure Start mode and allow fuel delivery (see Supporting Table)</p> <p><= P00C6 - Minimum acceptable value of fuel rail pressure after High Pressure Start (see Supporting Table)</p>	<p>High Pressure Rise Diagnostic During Start</p> <p>High Pressure Fail Diagnostic During Start</p> <p>Low side feed fuel pressure</p> <p>Engine Run Time Run/Crank Voltage Engine Coolant</p> <p>For each engine start, only 1 diagnostic is performed. The pressure rise test will run if High side fuel pressure is less than KtFHPC_p_HighPressStart, otherwise, the pressure fall diagnostic will run The pressure fall runs when the engine is cranking.</p>	<p>True</p> <p>False</p> <p>>= 0 KPA</p> <p>< = 0 sec > 8 Volts -42 <= °C <= 130</p> <p>All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT, IAT2 and ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control</p>	<p>Pressure Rise Test: Crank Time >= P00C6 - High Pressure Pump Control Mode timeout (see Supporting Table) 6.25 ms per sample</p> <p>Pressure Fall Test: Injected cylinder events >= P00C6 - maximum acceptable counts of fuel rail pressure below KtFHPD_p_HPS_PressFallLoThresh after High Pressure Start (see Supporting Table)</p> <p>4 samples per engine rotation</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Barometric Pressure Inlet Air Temp	commanded pressure is false and Device control pump ckt enabled on is false and Engine movement detected is true and Manufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active >= 70.0 KPA >= -10.0 DegC		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Pressure Measuremen t System - Multiple Sensor Correlation (naturally aspirated with TIAP/ Baro sensor)	P00C7	<p>Detects an inconsistency between pressure sensors in the induction system in which a particular sensor cannot be identified as the failed sensor.</p> <p>If the engine has been off for a sufficient amount of time, the pressure values in the induction system will have equalized. The Manifold Pressure (MAP) and Barometric Pressure (BARO) sensors values are checked to see if they are within the normal expected atmospheric pressure range. If they are, then MAP and BARO are compared to see if their values are similar.</p> <p>If the MAP and BARO values are not similar, there are no other pressure sensors to compare against to identify which sensor is not rational. The Multiple Pressure Sensor Correlation Diagnostic will fail in this case.</p>	ABS(Manifold Pressure - Baro Pressure)	> 10.0 kPa	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Engine is not rotating</p> <p>Manifold Pressure Manifold Pressure Baro Pressure Baro Pressure</p> <p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>> 10.0 seconds</p> <p>>= 50.0 kPa <= 115.0 kPa >= 50.0 kPa <= 115.0 kPa</p> <p>EngineModeNotRunTimer Error MAP_SensorFA AAP_SnsrFA</p> <p>MAP_SensorCircuitFP AAP_SnsrCktFP</p>	<p>4 failures out of 5 samples</p> <p>1 sample every 12.5 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Press Regulator Solenoid Supply Voltage Control High Side Circuit Short to ground	P00C9	Controller specific output driver circuit diagnoses High Pressure pump Control Solenoid high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	 ≤ 1.1 or 15 Amps selectable threshold based on High pressure Pump.	Engine Speed Battery Voltage	≥ 50 RPM ≥ 11 Volts Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Press Regulator Solenoid Supply Voltage Control High Side Circuit Short to power	P00CA	Controller specific output driver circuit diagnoses High Pressure pump Control Solenoid high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	<= 0.1 Amps between signal and controller power	Engine Speed Battery Voltage	>= 50 RPM >= 11 Volts Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Humidity Sensor Circuit Low	P00F4	<p>Detects a continuous short to ground in the humidity signal circuit or a humidity sensor that is outputting a duty cycle that is too low. The diagnostic monitors the humidity sensor duty cycle output and fails the diagnostic when the humidity duty cycle is too low.</p> <p>The humidity sensor converts the capacitance across the sensor to a relative humidity. The relative humidity value is converted by the sensor to a duty cycle value in %. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the duty cycle of the square wave signal and converts that duty cycle to a relative humidity value in % through a transfer function.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	Humidity Duty Cycle	<= 5.0 %	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>40 failures out of 50 samples</p> <p>1 sample every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Humidity Sensor Circuit High	P00F5	<p>Detects a humidity sensor that is outputting a duty cycle signal that is too high. The diagnostic monitors the humidity sensor duty cycle output and fails the diagnostic when the humidity duty cycle is too high.</p> <p>The humidity sensor converts the capacitance across the sensor to a relative humidity. The relative humidity value is converted by the sensor to a duty cycle value in %. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the duty cycle of the square wave signal and converts that duty cycle to a relative humidity value in % through a transfer function.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	Humidity Duty Cycle	>= 95.0 %	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>40 failures out of 50 samples</p> <p>1 sample every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Humidity Sensor Circuit Intermittent	P00F6	<p>Detects a noisy or erratic signal in the humidity circuit by monitoring the humidity sensor and failing the diagnostic when the humidity signal has a noisier output than is expected.</p> <p>When the value of relative humidity in % is determined, a delta is calculated between the current reading and the previous reading. The absolute value of these deltas is summed over a number of humidity readings. The result of this summation is called a "string length".</p> <p>Since the humidity signal is anticipated to be relatively smooth, a string length of a particular magnitude indicates a noisy or erratic humidity signal. The diagnostic will fail if the string length is too high.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	<p>String Length</p> <p>Where: "String Length" = sum of "Diff" calculated over</p> <p>And where: "Diff" = ABS(current Humidity reading - Humidity reading from 100 milliseconds previous)</p>	<p>> 80 %</p> <p>10 consecutive Humidity readings</p>	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>4 failures out of 5 samples</p> <p>Each sample takes 1.0 seconds</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Mass Air Flow System Performance (naturally aspirated)	P0101	<p>Detects a performance failure in the Mass Air Flow (MAF) sensor, such as when a MAF value is stuck in range.</p> <p>This diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from other sensors. The other sensors are the Manifold Pressure (MAP) sensor and Throttle Position sensor (TPS).</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the MAF sensor. In this case, the MAF Performance diagnostic will fail.</p>	<p>Filtered Throttle Model Error AND ABS(Measured Flow – Modeled Air Flow) Filtered AND ABS(Measured MAP – MAP Model 2) Filtered</p>	<p>$\leq 125 \text{ kPa}^*(\text{g/s})$</p> <p>$> 15.0 \text{ grams/sec}$</p> <p>$> 22.0 \text{ kPa}$</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>(Coolant Temp OR OBD Max Coolant Achieved</p> <p>Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p>	<p>$\geq 0 \text{ RPM}$ $\leq 5,400 \text{ RPM}$</p> <p>$\geq -9 \text{ Deg C}$</p> <p>= TRUE)</p> <p>$\leq 125 \text{ Deg C}$</p> <p>= FALSE)</p> <p>$\geq -20 \text{ Deg C}$ $\leq 125 \text{ Deg C}$</p> <p>≥ 0.50</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>Modeled Air Flow Error multiplied by P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM and P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>MAP Model 2 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA</p> <p>EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Mass Air Flow Sensor Circuit Low Frequency	P0102	<p>Detects a continuous short to ground in the MAF sensor circuit or a MAF sensor that is outputting a frequency that is too low. The diagnostic monitors the MAF sensor frequency output and fails the diagnostic when the MAF frequency is too low.</p> <p>The MAF sensor monitors the temperature of a circuit in the air flow of the engine. The temperature of this circuit is related to the air velocity across the sensor. The MAF sensor converts this air velocity to a mass air flow value. The mass air flow value is converted by the sensor to a frequency value in Hertz. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the frequency of the square wave signal and converts that frequency to a mass air flow value in grams/second through a transfer function.</p>	MAF Output	<= 840 Hertz (~ 0.28 gm/sec)	Engine Run Time Engine Speed Ignition Voltage Above criteria present for a period of time	> 1.0 seconds >= 300 RPM >= 10.0 Volts >= 1.0 seconds	200 failures out of 250 samples 1 sample every cylinder firing event	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Mass Air Flow Sensor Circuit High Frequency	P0103	<p>Detects a MAF sensor that is outputting a frequency signal that is too high. The diagnostic monitors the MAF sensor frequency output and fails the diagnostic when the MAF frequency is too high.</p> <p>The MAF sensor monitors the temperature of a circuit in the air flow of the engine. The temperature of this circuit is related to the air velocity across the sensor. The MAF sensor converts this air velocity to a mass air flow value. The mass air flow value is converted by the sensor to a frequency value in Hertz. A digital square wave signal is transmitted by the sensor to the ECM. The ECM calculates the frequency of the square wave signal and converts that frequency to a mass air flow value in grams/second through a transfer function.</p>	MAF Output	>= 14,500 Hertz (~ 357.9 gm/sec)	Engine Run Time Engine Speed Ignition Voltage Above criteria present for a period of time	> 1.0 seconds >= 300 RPM >= 10.0 Volts >= 1.0 seconds	200 failures out of 250 samples 1 sample every cylinder firing event	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Manifold Absolute Pressure Sensor Performance (naturally aspirated)	P0106	<p>Detects a performance failure in the Manifold Pressure (MAP) sensor, such as when a MAP value is stuck in range.</p> <p>If the engine has been off for a sufficient amount of time, the pressure values in the induction system will have equalized. The MAP sensor value is checked to see if it is within the normal expected atmospheric pressure range. If it is not, then the MAP performance diagnostic will fail.</p> <p>The engine running portion of this diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from other sensors. The other sensors are the Mass Air Flow (MAF) sensor and Throttle Position sensor (TPS).</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model</p>	<p>Engine Running:</p> <p>Filtered Throttle Model Error AND ABS(Measured MAP – MAP Model 1) Filtered AND ABS(Measured MAP – MAP Model 2) Filtered</p>	<p>$\leq 125 \text{ kPa}^*(\text{g/s})$</p> <p>$> 22.0 \text{ kPa}$</p> <p>$> 22.0 \text{ kPa}$</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>(Coolant Temp OR OBD Max Coolant Achieved</p> <p>Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p> <p>No Active DTCs:</p>	<p>$\geq 0 \text{ RPM}$ $\leq 5,400 \text{ RPM}$</p> <p>$\geq -9 \text{ Deg C}$</p> <p>= TRUE)</p> <p>$\leq 125 \text{ Deg C}$</p> <p>= FALSE)</p> <p>$\geq -20 \text{ Deg C}$ $\leq 125 \text{ Deg C}$</p> <p>≥ 0.50</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>MAP Model 1 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA</p>	<p>Continuous</p> <p>Calculations are performed every 12.5 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the MAP sensor. In this case, the MAP Performance diagnostic will fail.				EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA No Pending DTCs: EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP		
			<u>Engine Not Rotating:</u> Manifold Pressure OR Manifold Pressure	< 50.0 kPa > 115.0 kPa	Time between current ignition cycle and the last time the engine was running Engine is not rotating No Active DTCs: No Pending DTCs:	> 10.0 seconds EngineModeNotRunTimer Error MAP_SensorCircuitFA AAP_SnsrCktFA MAP_SensorCircuitFP AAP_SnsrCktFP	4 failures out of 5 samples 1 sample every 12.5 msec	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Manifold Absolute Pressure Sensor Circuit Low (Gen III)	P0107	Detects a continuous short to ground in the Manifold Absolute Pressure (MAP) signal circuit by monitoring the MAP sensor output voltage and failing the diagnostic when the MAP voltage is too low. The MAP sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	MAP Voltage	< 3.0 % of 5 Volt Range (This is equal to 6.1 kPa)	Continuous		320 failures out of 400 samples 1 sample every 12.5 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Manifold Absolute Pressure Sensor Circuit High (Gen III)	P0108	Detects a continuous short to power or open circuit in the Manifold Absolute Pressure (MAP) signal circuit by monitoring the MAP sensor output voltage and failing the diagnostic when the MAP voltage is too high. The MAP sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	MAP Voltage	> 90.0 % of 5 Volt Range (This is equal to 115.0 kPa)	Continuous		320 failures out of 400 samples 1 sample every 12.5 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit Performance (applications with humidity sensor and manifold temperature sensor)	P0111	<p>Detects an Intake Air Temperature (IAT) sensor value that is stuck in range by comparing the IAT sensor value against the IAT2 and IAT3 sensor values and failing the diagnostic if the IAT value is more different than the IAT2 and IAT3 values than is expected. If the engine has been off for a long enough period of time, the air temperature values in the engine compartment of the vehicle are considered to have equalized, and the diagnostic can be enabled.</p> <p>The diagnostic will fail if the IAT2 and IAT3 values are similar, and the IAT value is not similar to the IAT2 and IAT3 values. The diagnostic will also fail if none of the three sensor values are similar to each other, and the IAT value is furthest from the sensor value that is in the middle of the three sensor values.</p> <p>This diagnostic is executed once per</p>	<u>Good Correlation Between IAT2 and IAT3</u> ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT3)	> 25 deg C > 25 deg C <= 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	Type B, 2 Trips
			<u>Not Good Correlation. IAT2 in Middle:</u> Power Up IAT2 is between Power Up IAT and Power Up IAT3 AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT) > ABS(Power Up IAT2 - Power Up IAT3)	> 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	
			<u>Not Good Correlation. IAT3 in Middle:</u> Power Up IAT3 is between Power Up IAT and Power Up IAT2		Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds	Executes once at the beginning of each ignition cycle if enable conditions are met	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ignition cycle if the enable conditions are met.	AND ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT3 - Power Up IAT) > ABS(Power Up IAT3 - Power Up IAT2)	> 25 deg C	No Active DTCs:	PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit Low	P0112	Detects a continuous short to ground in the Intake Air Temperature (IAT) signal circuit by monitoring the IAT sensor output resistance and failing the diagnostic when the IAT resistance is too low. The IAT sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. A lower resistance is equivalent to a higher temperature.	Raw IAT Input	< 58.00 Ohms (~150 deg C)	Engine Run Time	> 0.00 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit High	P0113	Detects a continuous open circuit in the Intake Air Temperature (IAT) signal circuit by monitoring the IAT sensor output resistance and failing the diagnostic when the IAT resistance is too high. The IAT sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. A higher resistance is equivalent to a lower temperature.	Raw IAT Input	> 142,438 Ohms (~-60 deg C)	Engine Run Time	> 0.00 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Intermittent In-Range	P0114	<p>Detects a noisy or erratic signal in the Intake Air Temperature (IAT) circuit by monitoring the IAT sensor and failing the diagnostic when the IAT signal has a noisier output than is expected.</p> <p>When the value of the IAT signal in °C is determined, a delta is calculated between the current reading and the previous reading. The absolute value of these deltas is summed over a number of IAT readings. The result of this summation is called a "string length".</p> <p>Since the IAT signal is anticipated to be relatively smooth, a string length of a particular magnitude indicates a noisy or erratic IAT signal. The diagnostic will fail if the string length is too high.</p>	<p>String Length</p> <p>Where: "String Length" = sum of "Diff" calculated over</p> <p>And where: "Diff" = ABS(current IAT reading - IAT reading from 100 milliseconds previous)</p>	<p>> 80.00 deg C</p> <p>10 consecutive IAT readings</p>	Continuous		<p>4 failures out of 5 samples</p> <p>Each sample takes 1.0 seconds</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Temp Sensor Circuit Low	P0117	Circuit Continuity This DTC detects a short to ground in the ECT (Engine Coolant temperature) signal circuit or the ECT sensor. This is accomplished by monitoring the resistance of the circuit. If the resistance goes out of the expected range the DTC is set.	ECT Resistance (@ 150°C)	< 55 Ohms			5 failures out of 6 samples 1 sec/ sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Temp Sensor Circuit High	P0118	Circuit Continuity This DTC detects a short to high or open in the ECT (Engine Coolant temperature) signal circuit or the ECT sensor. This is accomplished by monitoring the resistance of the circuit. If the resistance goes out of the expected range the DTC is set.	ECT Resistance (@ -60°C)	> 134,000 Ohms	Engine run time OR IAT min	> 10.0 seconds ≥ -9.0 °C	5 failures out of 6 samples 1 sec/ sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Temperature (ECT) Sensor Circuit Intermittent	P0119	Circuit Erratic This DTC detects large step changes in the ECT (Engine Coolant temperature) signal circuit or the ECT sensor. Allowable high and low limits are calculated for the next sample based on the previous sample and sensor time constant. If the sensor responds faster than should be possible the DTC is set.	ECT temperature step change: 1) positive step change is greater than calculated high limit OR 2) negative step change is lower than calculated low limit. The calculated high and low limits for the next reading use the following calibrations: 1) Sensor time constant 2) Sensor low limit 3) Sensor high limit *****Generic Example***** If the last ECT reading was 90 Deg C, the Time constant was calibrated at 10 seconds, the low limit was calibrated to -80 Deg C and the high limit was calibrated to 200 Deg C the calculated limits are 101 Deg C and 73 Deg C. The next reading (after the 90 Deg C reading) must be between 73 Deg C and 101 Deg C to be valid. *****	13.0 seconds -60.0 Deg C 150.0 Deg C	No Active DTC's	ECT_Sensor_Ckt_FP	3 failures out of 4 samples 1 sec/ sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Throttle Position Sensor Performance (naturally aspirated)	P0121	<p>Detects a performance failure in the Throttle Position sensor (TPS) sensor, such as when a TPS value is stuck in range.</p> <p>This diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from other sensors. The other sensors are the Manifold Pressure (MAP) sensor and Mass Air Flow (MAF) sensor.</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the TPS sensor. In this case, the TPS Performance diagnostic will fail.</p>	<p>Filtered Throttle Model Error AND ABS(Measured MAP – MAP Model 2) Filtered</p>	<p>> 125 kPa*(g/s)</p> <p><= 22.0 kPa</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>(Coolant Temp OR OBD Max Coolant Achieved</p> <p>Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p> <p>No Active DTCs:</p>	<p>>= 0 RPM <= 5,400 RPM</p> <p>>= -9 Deg C</p> <p>= TRUE)</p> <p><= 125 Deg C</p> <p>= FALSE)</p> <p>>= -20 Deg C <= 125 Deg C</p> <p>>= 0.50</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No Pending DTCs:	EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS1 Circuit Low	P0122	Detects a continuous or intermittent short low or open in TPS1 circuit by monitoring the TPS 1 sensor percent Vref and failing the diagnostic when the TPS percent Vref is too low. This diagnostic only runs when battery voltage is high enough.	TPS1 % Vref <	0.3250 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS1 Circuit High	P0123	Detects a continuous or intermittent short high in TPS1 circuit by monitoring the TPS 1 sensor percent Vref and failing the diagnostic when the TPS percent Vref is too high. This diagnostic only runs when battery voltage is high enough.	TPS1 % Vref >	4.750 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Temperature Below Stat Regulating Temperature	P0128	This DTC detects if the ECT (EngineCoolant temperature) does not achieve the required target temperature after an allowed energy accumulation by the engine. This can be caused by an ECT sensor biased low or a cooling system that is not warming up correctly because of a stuck open thermostat or other fault.	<p>Energy is accumulated after the first combustion event using Range #1 or #2 below:</p> <p>Thermostat type is divided into normal (non-heated) and electrically heated.</p> <p>For this application the "type" cal (KeTHMG_b_TMS_ElecThstEquipped) = 1 If the type cal is equal to one, the application has an electrically heated t-stat, if equal to zero the the application has a non heated t-stat. See appropriate section below.</p> <p>*****</p> <p>Type cal above = 1 (Electrically heated t-stat) == == == ==</p> <p>Range #1 (Primary) ECT reaches Commanded temperature minus 11 °C when Ambient min is ≤ 52 °C and > 10 °C. Note: Warm up target for range #1 will be at least 74 °C == == == ==</p> <p>Range #2 (Alternate) ECT reaches Commanded temperature minus 37 °C when Ambient min is ≤ 10 °C and > -9 °C. Note: Warm up target for range #2 will be at least</p>	<p>See the two tables named: P0128_Maximum Accumulated Energy for Start-up ECT conditions - Primary and P0128_Maximum Accumulated Energy for Start-up ECT conditions - Alternate in the Supporting tables section.</p> <p>This diagnostic models the net energy into and out of the cooling</p>	<p>No Active DTC's</p> <p>Engine not run time (soaking time before current trip)</p> <p>Engine run time</p> <p>Fuel Condition</p> <p>Distance traveled</p> <p>*****</p> <p>If Engine RPM is continuously greater than for this time period</p> <p>The diagnostic test for this key cycle will abort</p> <p>*****</p> <p>*****</p> <p>If T-Stat Heater commanded duty cycle for this time period</p>	<p>ECT_Sensor_Ckt_FA ECT_Sensor_Perf_FA VehicleSpeedSensor_FA OAT_PtEstFiltFA IAT_SensorCircuitFA MAF_SensorFA THMR_AWP_AuxPumpFA THMR_AHV_FA THMR_SWP_Control_FA THMR_SWP_NoFlow_FA THMR_SWP_FlowStuckOn_FA EngineTorqueEstInaccuracy</p> <p>≥ 1,800 seconds</p> <p>30 ≤ Eng Run Tme ≤ 1,400 seconds</p> <p>Ethanol ≤ 87 %</p> <p>≥ 0.93 miles</p> <p>*****</p> <p>9,999 rpm 5.0 seconds</p> <p>*****</p> <p>*****</p> <p>> 50.0 % duty cycle > 5.0 seconds</p>	<p>1 failure to set DTC</p> <p>1 sec/ sample</p> <p>Once per ignition key cycle</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			55 °C ***** Type cal above = 0 (non - heated t-stat) == == == == Range #1 (Primary) ECT reaches 81 °C when Ambient min is ≤ 52 °C and > 10 °C. == == == == Range #2 (Alternate) ECT reaches 55 °C when Ambient min is ≤ 10 °C and > -9 °C. *****	system during the warm-up process. The five energy terms are: heat from combustion (with AFM correction), heat from after-run, heat loss to enviroment, heat loss to cabin and heat loss to DFCO.	The diagnostic test for this key cycle will abort ***** ECT at start run	***** -60 ≤ ECT ≤ 69 °C		

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					All Fuel Injectors for active Cylinders Fuel Condition Ethanol Estimation in Progress Fuel State All of the above met for	Enabled (On) Ethanol \leq 87 % = Not Active (Please see " Ethanol Estimation in Progress " in Supporting Tables). DFCO not active > 5.0 seconds		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit High Voltage Bank 1 Sensor 1	P0132	<p>This DTC determines if the O2 sensor signal circuit is shorted high or open. When enabled, the diagnostic monitors the O2S signal and compares it to the threshold.</p> <p>The diagnostic failure counter is incremented if the O2S signal is above the threshold value. This DTC is set based on the fail and sample counters.</p>	Oxygen Sensor Signal	> 1,050 mvolts	<p>No Active DTC's</p> <p>System Voltage AFM Status Heater Warm-up delay Engine Run Time Engine Run Accum</p> <p>Low Fuel Condition Diag Only when FuelLevelDataFault</p> <p>*****</p> <p>Secondary delay after above conditions are complete (cold start condition)</p> <p>Secondary delay after above conditions are complete (not cold start condition)</p> <p>Commanded Equivalence Ratio</p> <p>*****</p> <p>All of the above met for</p>	<p>TPS_ThrottleAuthorityDefaulted MAF_SensorFA MAP_SensorFA EvapExcessPurgePsbl_FA FuelInjectorCircuit_FA Ethanol Composition Sensor FA AIR System FA</p> <p>10.0 < Volts = All Cylinders active = Complete > 5.0 seconds > 30.0 seconds</p> <p>= False</p> <p>= False</p> <p>*****</p> <p>> 150.0 seconds when engine soak time > 28,800 seconds</p> <p>> 150.0 seconds when engine soak time ≤ 28,800 seconds</p> <p>≤ 1.014 EQR</p> <p>*****</p> <p>> 3.0 seconds</p>	<p>40 failures out of 50 samples</p> <p>Frequency: Continuous in 100 milli - second loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Slow Response Bank 1 Sensor 1) (For use with ESPD and w/o WRAF	P0133	<p>This DTC determines if the Bank 1 primary O2 sensor has a slow response (in the Rich to Lean (R2L) or Lean to Rich (L2R) direction) and thereby can no longer be used for closed loop fuel control based on emission correlation testing. This diagnostic runs passively (see enable conditions) and monitors the time the O2 sensor signal is between an upper and lower voltage thresholds over the sample period. The diagnostic also monitors the O2 sensor signal for the number of Slope Time (ST) switches in each direction between the same upper and lower voltage thresholds over the sample period. When the required data is collected, an average R2L and L2R response time and individual R2L and L2R Slope Time (ST) switch count is calculated.</p> <p>This fault is set when the L2R and R2L response test results are compared to the</p>	<p>Fault condition present when the average response time is calculated over the test time, and compared to the threshold.</p> <p>OR</p> <p>Slope Time L/R Switches</p> <p>OR</p> <p>Slope Time R/L Switches</p>	<p>Refer to P0133_O2S Slow Response Bank 1 Sensor 1 Pass/Fail Threshold table in the Supporting Tables tab</p> <p>< 5</p> <p>< 5</p> <p>The test averages the signal response time over 60.0 seconds when the signal is transitioning between 400 mvolts and 600 mvolts. An average rich to lean time and lean to rich time are each calculated separately.</p> <p>Note: the table listed above uses the following calibratable X axis: P0133_KnEOSD_t_ST_LRC_LimRS1 and calibratable Y axis: P0133_KnEOSD_t_ST_RLC_LimRS1</p>	<p>No Active DTC's</p> <p>Bank 1 Sensor 1 DTC's not active</p> <p>System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsrCkt_FA FuelInjectorCircuit_FA AIR System FA Ethanol Composition Sensor FA EngineMisfireDetected_FA</p> <p>P0131, P0132, P0134</p> <p>> 10.0 Volts = Not active = Not active = Not active = Not active</p> <p>= False = False</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than</p>	<p>Sample time is 60 seconds</p> <p>Frequency: Once per trip</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		"P0133_O2S Slow Response Bank 1 Sensor 1 "Pass/Fail Threshold Table" and the outcome determines a response faulted condition. Additionally, this fault is set when the L2R or R2L slope time switch count test results are less than the ST individual thresholds.			<p>O2 Heater on for Learned Htr resistance</p> <p>Engine Coolant (Or OBD Coolant Enable Criteria</p> <p>IAT Engine run Accum</p> <p>Time since any AFM status change Time since Purge On to Off change Time since Purge Off to On change</p> <p>Engine airflow Engine speed Fuel Condition Baro Air Per Cylinder</p> <p>Fuel Control State Closed Loop Active</p>	<p>Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S1, B2S1 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 18.0 grams/sec.</p> <p>≥ 30 seconds = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>> 60 °C = TRUE)</p> <p>> -40 °C > 30 seconds</p> <p>> 1.5 seconds > 0.0 seconds > 1.5 seconds</p> <p>12 ≤ grams/sec ≤ 60 1,000 ≤ RPM ≤ 3,500 < 87 % Ethanol > 70 kpa ≥ 100 mGrams</p> <p>= Closed Loop = TRUE (Please see "Closed Loop Enable")</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>LTM (Block Learn) fuel cell</p> <p>Transient Fuel Mass Baro Fuel Control State Fuel State Commanded Proportional Gain</p> <p>=====</p> <p>All of the above met for</p>	<p>Clarification in Supporting Tables). = Enabled, refer to Multiple DTC Use - Response Cell Enable Table for additional info.</p> <p>≤ 100.0 mgrams = Not Defaulted not = Power Enrichment DFCO not active</p> <p>≥ 0.0 %</p> <p>=====</p> <p>> 4.0 seconds</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Performance Bank 1 Sensor 1	P0135	<p>This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit. This test compares the measured heater current (monitored thru the low side driver) and compares it to the expected values (over the voltage range provided) for the released sensor.</p> <p>The diagnostic failure counter is incremented if the heater current is outside the expected range. This DTC is set based on the fail and sample counters.</p>	Heater Current outside of the expected range of	$0.3 < \text{Amps} < 2.5$	<p>No Active DTC's</p> <p>System Voltage Heater Warm-up delay O2S Heater device control</p> <p>B1S1 O2S Heater Duty Cycle</p> <p>All of the above met for</p>	<p>ECT_Sensor_FA</p> <p>> 10.0 Volts = Complete</p> <p>= Not active</p> <p>> zero</p> <p>> 120 seconds</p>	<p>8 failures out of 10 samples</p> <p>Frequency: 2 tests per trip 10 seconds delay between tests and 1 second execution rate</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					All Fuel Injectors for active Cylinders Fuel Condition Ethanol Estimation in Progress Fuel State All of the above met for	Enabled (On) Ethanol \leq 87 % = Not Active (Please see " Ethanol Estimation in Progress " in Supporting Tables). DFCO not active > 5.0 seconds		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit High Voltage Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0138	<p>This DTC determines if the O2 sensor signal circuit is shorted high or open. When enabled, the diagnostic monitors the O2S signal and compares it to the threshold.</p> <p>The diagnostic failure counter is incremented if the O2S signal is above the threshold value. This DTC is set based on the fail and sample counters.</p>	Oxygen Sensor Signal	> 1,050 mvolts	<p>No Active DTC's</p> <p>System Voltage AFM Status Heater Warm-up delay Engine Run Time Engine Run Accum</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>*****</p> <p>Secondary delay after above conditions are complete (cold start condition)</p> <p>Secondary delay after above conditions are complete (not cold start condition)</p> <p>Commanded Equivalence Ratio</p> <p>*****</p> <p>All of the above met for</p>	<p>TPS_ThrottleAuthorityDefaulted MAF_SensorFA MAP_SensorFA EvapExcessPurgePsbl_FA FuelInjectorCircuit_FA Ethanol Composition Sensor FA AIR System FA</p> <p>10.0 < Volts = All Cylinders active = Complete > 5.0 seconds > 30.0seconds</p> <p>= False</p> <p>= False</p> <p>*****</p> <p>> 175.0 seconds when engine soak time > 28,800 seconds</p> <p>> 175.0 seconds when engine soak time ≤ 28,800 seconds</p> <p>≤ 1.014 EQR</p> <p>*****</p> <p>> 3.0 seconds</p>	<p>40 failures out of 50 samples</p> <p>Frequency: Continuous in 100 milli - second loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Slow Response Rich to Lean Bank 1 Sensor 2	P013A	<p>The P013A diagnostic is the third in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor has an slow response to an A/F change from Rich to Lean and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic commands fuel cut off while monitoring the sensor signal and the accumulated mass air flow.</p> <p>Note: The Primary method is used when the secondary O2 sensor signal transitions from above the upper threshold to below the lower threshold, otherwise the Secondary method is used.</p> <p><u>Primary method:</u> The P013A diagnostic measures the secondary O2 sensor voltage response rate</p>	<p>Primary Method: The EWMA of the Post O2 sensor normalized integral value. The EWMA repass limit is The EWMA calculation uses a 0.28 coefficient.</p> <p>OR</p> <p>Secondary Method: The Accumulated mass air flow monitored during the Slow Response Test (between the upper and lower voltage thresholds)</p>	<p>> 8.0 units ≤ 7.5 units</p> <p>> 60.0 grams (upper voltage threshold is 450 mvolts and lower voltage threshold is 150 mvolts)</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not Active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013B, P013E, P013F, P2270 or P2271</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's") = Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 18.0 grams/sec.</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed.</p>	<p>Type A, 1 Trips EWMA</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>between an upper and lower voltage threshold. The response rate is then normalized to mass air flow rate and scaled resulting in a normalized integral value. The normalized integral is fed into a 1st order lag filter to update the final EWMA result. DTC P013A is set when the EWMA value exceeds the EWMA threshold. Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p>Secondary method:</p>			<p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Post fuel cell</p> <p>Crankshaft Torque</p> <p>DTC's Passed</p> <p>=====</p> <p>After above conditions are met: DFCO mode is continued (wo driver initiated pedal input).</p>	<p>= False</p> <p>= False</p> <p>= Enabled, refer to Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests for additional info. < 125.0 Nm</p> <p>P2270 (and P2272 if applicable) P013E (and P014A if applicable)</p> <p>=====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		This fault is set if the secondary O2 sensor does not achieve the required lower voltage threshold before the accumulated mass air flow threshold is reached.						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Slow Response Lean to Rich Bank 1 Sensor 2	P013B	<p>The P013B diagnostic is the sixth in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor has an slow response to an A/F change from Lean to Rich and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic increases the delivered fuel while monitoring the sensor signal and the accumulated mass air flow.</p> <p>Note: The Primary method is used when the secondary O2 sensor signal transitions from below the lower threshold to above the upper threshold, otherwise the Secondary method is used.</p> <p><u>Primary method:</u> The P013B diagnostic measures the secondary O2 sensor voltage response rate</p>	<p>Primary Method: The EWMA of the Post O2 sensor normalized integral value. The EWMA repass limit is The EWMA calculation uses a 0.28 coefficient.</p> <p>OR</p> <p>Secondary Method: The Accumulated mass air flow monitored during the Slow Response Test (between the upper and lower voltage thresholds)</p>	<p>> 8.0 units ≤ 7.5 units</p> <p>> 805 grams (lower voltage threshold is 350 mvolts and upper voltage threshold is 650 mvolts)</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not Active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013A, P013E, P013F, P2270 or P2271</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed.</p>	<p>Type A, 1 Trips EWMA</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>between an lower and upper voltage threshold. The response rate is then normalized to mass air flow rate and scaled resulting in a normalized integral value. The normalized integral is fed into a 1st order lag filter to update the final EWMA result. DTC P013B is set when the EWMA value exceeds the EWMA threshold. Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p>Secondary method:</p>			<p>Green Cat System Condition</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Post fuel cell</p> <p>DTC's Passed</p> <p>=====</p> <p>After above conditions are met: Fuel Enrich mode continued.</p> <p>=====</p>	<p>is above 18.0 grams/sec.</p> <p>= Not Valid, Green Cat System condition is considered valid until accumulated airflow is greater than 360,000 grams. Airflow accumulation is only enabled when estimated Cat temperature is above 600 Deg C and airflow is greater than 18.0 grams/sec.</p> <p>(Note: This feature is only enabled when the vehicle is new and cannot be enabled in service).</p> <p>= False</p> <p>= False</p> <p>= Enabled, refer to Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests for additional info.</p> <p>P2270 P013E P013A P2271 P013F</p> <p>=====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		This fault is set if the secondary O2 sensor does not achieve the required upper voltage threshold before the accumulated mass air flow threshold is reached.			During this test the following must stay TRUE or the test will abort: 0.960 ≤ Base Commanded EQR ≤ 1.080			

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Rich to Lean Bank 1 Sensor 2	P013E	<p>The P013E diagnostic is the second in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor has an initial delayed response to an A/F change from Rich to Lean and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic commands fuel cut off while monitoring the sensor signal and the accumulated mass air flow.</p> <p>This fault is set if the secondary O2 sensor does not achieve the required voltage before the accumulated mass air flow threshold is reached.</p>	<p>Post O2 sensor voltage</p> <p>AND</p> <p>The Accumulated mass air flow monitored during the Delayed Response Test under DFCO</p> <p>DFCO begins after: 1) Catalyst has been rich for a minimum of AND 2) Catalyst Rich Accumulation Air Flow is</p>	<p>> 450 mvolts</p> <p>> 45 grams</p> <p>> 1 secs</p> <p>≥ 3.0 grams</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not Active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR_System_FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013A, P013B, P013F, P2270 or P2271</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Post fuel cell</p> <p>Crankshaft Torque</p> <p>DTC's Passed</p> <p>Number of fueled cylinders =====</p> <p>After above conditions are met: DFCO mode entered (wo driver initiated pedal input).</p>	<p>is above 18.0 grams/sec.</p> <p>= False</p> <p>= False</p> <p>= Enabled, refer to Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests for additional info. < 125.0 Nm</p> <p>P2270</p> <p>≤ 3 cylinders =====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Lean to Rich Bank 1 Sensor 2	P013F	<p>The P013F diagnostic is the fifth in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor has an initial delayed response to an A/F change from Lean to Rich and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic increases the delivered fuel while monitoring the sensor signal and the accumulated mass air flow.</p> <p>This fault is set if the secondary O2 sensor does not achieve the required voltage before the accumulated mass air flow threshold is reached.</p>	<p>Post O2 sensor voltage</p> <p>AND</p> <p>The Accumulated mass air flow monitored during the Delayed Response Test</p>	<p>< 350 mvolts</p> <p>> 65 grams</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not Active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR_System_FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013A, P013B, P013E, P2270 or P2271</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Green Cat System Condition</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Post fuel cell</p> <p>DTC's Passed</p> <p>Number of fueled cylinders =====</p> <p>After above conditions are met: Fuel Enrich mode entered. =====</p> <p>During this test the</p>	<p>is above 18.0 grams/sec.</p> <p>= Not Valid, Green Cat System condition is considered valid until accumulated airflow is greater than 360,000 grams. Airflow accumulation is only enabled when estimated Cat temperature is above 600 Deg C and airflow is greater than 18.0 grams/sec. (Note: This feature is only enabled when the vehicle is new and cannot be enabled in service).</p> <p>= False</p> <p>= False</p> <p>= Enabled, refer to Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests for additional info.</p> <p>P2270 P013E P013A P2271</p> <p>≥ 1 cylinders =====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					following must stay TRUE or the test will abort: 0.960 ≤ Base Commanded EQR ≤ 1.080			

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Performance Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0141	<p>This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit. This test compares the measured heater current (monitored thru the low side driver) and compares it to the expected values (over the voltage range provided) for the released sensor.</p> <p>The diagnostic failure counter is incremented if the heater current is outside the expected range. This DTC is set based on the fail and sample counters.</p>	Heater Current outside of the expected range of	0.3 > amps > 2.5	<p>No Active DTC's System Voltage Heater Warm-up delay O2S Heater device control B1S1 O2S Heater Duty Cycle</p> <p>All of the above met for</p>	<p>ECT_Sensor_FA > 10.0 Volts = Complete</p> <p>= Not active</p> <p>> zero</p> <p>> 120 seconds</p>	<p>8 failures out of 10 samples</p> <p>Frequency: 2 tests per trip 10 seconds delay between tests and 1 second execution rate.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Rich to Lean Bank 1 Sensor 1) (For use w/o WRAF	P015A	<p>DTC P015A detects that the primary oxygen sensor for Bank 1 has delayed response when the air fuel ratio transitions from rich to lean condition. This diagnostic runs simultaneously with the intrusive secondary O2 monitor rich to lean tests (P013E / P013A / P2271), which commands fuel cut off.</p> <p>Note: The Primary method is used when the primary O2 sensor signal transitions from above to below the O2 voltage threshold, otherwise the Secondary method is used.</p> <p>Primary method: The P015A diagnostic measures the primary O2 sensor response time between a rich condition above a starting voltage threshold and a lower voltage threshold. The response time is then scaled and normalized to mass air flow rate, engine speed, Baro, and intake air temperature resulting in a normalized delay</p>	<p>Primary Method: The EWMA of the Pre O2 sensor normalized R2L time delay value. The EWMA repass limit is The EWMA calculation uses a 0.25 coefficient. This method calculates the result when the Pre O2 sensor voltage is</p> <p>OR</p> <p>Secondary Method: The Accumulated time monitored during the R2L Delayed Response Test.</p> <p>AND</p> <p>Pre O2 sensor voltage is</p>	<p>> 0.70 EWMA (sec) ≤ 0.60 EWMA (sec)</p> <p>< 550 mvolts</p> <p>≥ 2.5 Seconds</p> <p>> 100.0 mvolts</p>	<p>No Active DTC's</p> <p>System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsrCkt_FA FuelInjectorCircuit_FA AIR System FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EthanolCompositionSensor_FA EngineMisfireDetected_FA P0131, P0132, P013A, P013B, P013E, P013F, P2270, P2271</p> <p>> 10.0 Volts = Not active = Not active = Not active = Not active</p> <p>= False</p> <p>= False</p> <p>= Not Valid, Green O2S condition is</p>	<p>Frequency: Once per trip Note: if NaESPD_b_Fast InitResplsActive = TRUE for the given Fuel Bank OR NaESPD_b_RapidResponsesActive = TRUE, multiple tests per trip are allowed</p>	Type A, 1 Trips EWMA

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>value. The normalized delay is fed into a 1st order lag filter to update the final EWMA result. DTC P015A is set when the EWMA value exceeds the EWMA threshold. Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p>Secondary method: This fault is set if the primary O2 sensor does not achieve the required lower voltage threshold before a delay time threshold is reached.</p>			<p>O2 Heater (pre sensor) on for Learned Htr resistance</p> <p>Engine Coolant (Or OBD Coolant Enable Criteria</p> <p>IAT Engine run Accum</p> <p>Engine Speed to initially enable test Engine Speed range to keep test enabled (after initially enabled)</p> <p>Engine Airflow Vehicle Speed to initially enable test Vehicle Speed range to keep test enabled (after initially enabled)</p> <p>Closed loop integral</p>	<p>considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S1, B2S1 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 18.0 grams/sec.</p> <p>≥ 30 seconds = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>> 60 °C = TRUE)</p> <p>> -40 °C > 30 seconds</p> <p>1,050 ≤ RPM ≤ 3,500</p> <p>1,000 ≤ RPM ≤ 3,650</p> <p>2.0 ≤ gps ≤ 20.0</p> <p>40.4 ≤ MPH ≤ 77.7</p> <p>36.0 ≤ MPH ≤ 80.8</p> <p>0.92 ≤ C/L Int ≤ 1.08</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Closed Loop Active</p> <p>Evap</p> <p>Ethanol Estimation in Progress</p> <p>Baro Post fuel cell</p> <p>EGR Intrusive diagnostic All post sensor heater delays O2S Heater (post sensor) on Time Predicted Catalyst temp Fuel State</p> <p>=====</p> <p>All of the above met for at least 2.0 seconds, and then the Force Cat Rich intrusive stage is requested.</p> <p>=====</p> <p>Pre O2S voltage B1S1 at end of Cat Rich stage Fuel State Number of fueled cylinders</p> <p>=====</p> <p>After above conditions are met: DFCO Mode is entered (wo driver</p>	<p>= TRUE (Please see “Closed Loop Enable Clarification” in Supporting Tables).</p> <p>not in control of purge</p> <p>= Not Active (Please see “Ethanol Estimation in Progress” in Supporting Tables).</p> <p>> 70 kpa = enabled</p> <p>= not active</p> <p>= not active</p> <p>≥ 30.0 sec 550 ≤ °C ≤ 910 = DFCO possible</p> <p>=====</p> <p>=====</p> <p>≥ 680 mvolts = DFCO active</p> <p>≤ 3 cylinders</p> <p>=====</p> <p>=====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					initiated pedal input).			

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Lean to Rich Bank 1 Sensor 1) (For use w/o WRAF	P015B	<p>DTC P015B detects that the primary oxygen sensor for Bank 1 has delayed response when the air fuel ratio transitions from lean to rich condition. This diagnostic runs simultaneously with the intrusive secondary O2 monitor lean to rich tests (P013F / P013B), which commands fuel enrichment.</p> <p>Note: The Primary method is used when the primary O2 sensor signal transitions from lean condition to above the O2 voltage threshold, otherwise the Secondary method is used.</p> <p><u>Primary method:</u> The P015B diagnostic measures the primary O2 sensor response time between a lean condition and a higher voltage threshold. The response time is then scaled and normalized to mass air flow rate, engine speed, Baro, and intake air temperature resulting in a normalized delay value. The normalized delay is fed into a 1st</p>	<p>Primary method: The EWMA of the Pre O2 sensor normalized L2R time delay value. The EWMA repass limit is The EWMA calculation uses a 0.25 coefficient.</p> <p>OR</p> <p>Secondary method: The Accumulated time monitored during the L2R Delayed Response Test.</p> <p>AND</p> <p>Pre O2 sensor voltage is</p> <p>OR</p> <p>At end of Cat Rich stage the Pre O2 sensor output is</p>	<p>> 0.65 EWMA (sec) ≤ 0.60 EWMA (sec)</p> <p>≥ 2.0 Seconds</p> <p>< 300 mvolts</p> <p>< 680 mvolts</p>	<p>No Active DTC's</p> <p>P015A test is complete and</p> <p>System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p>	<p>TPS_ThrottleAuthorityDefaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsrCkt_FA FuelInjectorCircuit_FA AIR System FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EthanolCompositionSensor_FA EngineMisfireDetected_FA P0131, P0132, P013A, P013B, P013E, P013F, P015A, P2270, P2271</p> <p>= Passed</p> <p>> 10.0 Volts = Not active = Not active = Not active = Not active</p> <p>= False = False</p>	<p>Frequency: Once per trip Note: if NaESPD_b_Fast InitResplsActive = TRUE for the given Fuel Bank OR NaESPD_b_RapidResponsesActive = TRUE, multiple tests per trip are allowed</p>	Type A, 1 Trips EWMA

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>order lag filter to update the final EWMA result. DTC P015B is set when the EWMA value exceeds the EWMA threshold. Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p><u>Secondary method:</u> This fault is set if the primary O2 sensor does not achieve the required higher voltage threshold before a delay time threshold is reached.</p>			<p>Green O2S Condition</p> <p>O2 Heater (pre sensor) on for Learned Htr resistance</p> <p>Engine Coolant (Or OBD Coolant Enable Criteria</p> <p>IAT Engine run Accum</p> <p>Engine Speed to initially enable test Engine Speed range to keep test enabled (after initially enabled)</p> <p>Engine Airflow Vehicle Speed to initially enable test Vehicle Speed range to keep test enabled (after</p>	<p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use Green Sensor Delay Criteria - Limit for the following locations: B1S1, B2S1 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 18.0 grams/sec.</p> <p>≥ 30 seconds = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>> 60 °C = TRUE)</p> <p>> -40 °C > 30 seconds</p> <p>1,050 ≤ RPM ≤ 3,500</p> <p>1,000 ≤ RPM ≤ 3,650</p> <p>2.0 ≤ gps ≤ 20.0</p> <p>40.4 ≤ MPH ≤ 77.7</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					initially enabled)	36.0 ≤ MPH ≤ 80.8		
					Closed loop integral Closed Loop Active	0.92 ≤ C/L Int ≤ 1.08 = TRUE (Please see “ Closed Loop Enable Clarification ” in Supporting Tables).		
					Evap	not in control of purge		
					Ethanol Estimation in Progress	= Not Active (Please see “ Ethanol Estimation in Progress ” in Supporting Tables).		
					Baro	> 70 kpa		
					Post fuel cell	= enabled		
					EGR Intrusive diagnostic	= not active		
					All post sensor heater delays	= not active		
					O2S Heater (post sensor) on Time	≥ 30.0 sec		
					Predicted Catalyst temp	550 ≤ °C ≤ 910		
					Fuel State	= DFCE inhibit		
					Number of fueled cylinders	≥ 1 cylinders		
					=====	=====		
					When above conditions are met: Fuel Enrich mode is entered.			
					=====	=====		
					During this test: Engine Airflow must stay between: and the delta Engine Airflow over 12.5msec	0 ≤ gps ≤ 20		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					must be :	≤ 20.0 gps		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel System Too Lean Bank 1	P0171	<p>Determines if the primary fuel control system for Bank 1 is in a lean condition, based on the filtered long-term and short-term fuel trim. A normally operating system operates centered around long-term fuel trim metric of 1.0. For lean conditions extra fuel trim is required therefor values > 1.0 indicate a Lean condition.</p> <p>A fault is determined, when the long term fuel metric exceeds the threshold value. In addition to the long-term fuel trim limit, the short-term fuel trim metric can be monitored and the fault sets once both threshold values are exceeded. The short-term fuel trim metric is only monitored on programs that have acceptable emissions when the long-term fuel metric reaches its full authority.</p>	<p>The filtered long-term fuel trim metric</p> <p>AND</p> <p>The filtered short-term fuel trim metric (Note: any value below 0.95 effectively nullifies the short-term fuel trim criteria)</p>	<p>≥ 1.360</p> <p>≥ 0.102</p> <p>If a fault has been detected the long-term fuel trim metric must be < 2.000 and the short-term fuel trim metric must be < 2.000 to repass the diagnostic.</p>	<p>Engine speed BARO Coolant Temp</p> <p>Coolant Temp MAP Inlet Air Temp MAF Fuel Level</p> <p>Long Term Fuel Trim data accumulation:</p> <p>Sometimes, certain Long-Term Fuel Trim Cells are not utilized for control and/or diagnosis</p> <p>Closed Loop Long Term FT</p>	<p>400 <rpm< 6,100 > 70 kPa > -20 °C (or OBD Coolant Enable Criteria = TRUE) < 150 °C 5 <kPa< 255 -20 <°C< 150 1 <g/s< 510 > 10% or if fuel sender is faulty the diagnostic will bypass the fuel level criteria.</p> <p>> 47.0 seconds of data must accumulate on each trip, with at least 35.0 seconds of data in the current fuel trim cell before a pass or fail decision can be made.</p> <p>(Please see P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage in Supporting Tables for a list of cells utilized for diagnosis)</p> <p>Enabled Enabled (Please see "Closed Loop Enable Clarification" and "Long Term FT Enable Criteria" in Supporting Tables.)</p>	Frequency: 100 ms Continuous Loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					EGR Diag. Catalyst Diag. Post O2 Diag. Device Control EVAP Diag. No active DTC:	Intrusive Test Not Active Intrusive Test Not Active Intrusive Test Not Active Not Active Large Leak Diagnostic (P0455) Not Active IAC_SystemRPM_FA MAP_SensorFA MAF_SensorFA MAF_SensorTFTKO AIR System FA EvapExcessPurgePsbl_F A Ethanol Composition Sensor FA FuelInjectorCircuit_FA EngineMisfireDetected_F A EGRValvePerformance_F A EGRValveCircuit_FA MAP_EngineVacuumStat us AmbPresDfltStatus TC_BoostPresSnsrFA O2S_Bank_1_Sensor_1_ FA		

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>term fuel trim metric is only monitored on programs that have acceptable emissions when the long-term fuel metric reaches its full authority.</p> <p>Once purge is enabled if the filtered Purge Long Term Fuel Trim metric > 0.705, the test passes without intrusively checking the filtered Non-Purge Long Term Fuel Trim metric. However if the filtered Purge Long Term Fuel Trim metric is <= 0.705, the Intrusive test is invoked. The purge is ramped off to determine if excess purge vapor is the cause of the rich condition. If during 3 out of 5 intrusive segments, the filtered Purge Long Term Fuel Trim metric <= 0.700 the fault will set.</p> <p>Performing intrusive tests too frequently may also affect EVAP and EPAIII emissions, and the execution frequency of other diagnostics. This is why the intrusive test is operated over several</p>		<p>term fuel trim metric must be > 0.000 to repass the diagnostic. The intrusive test will be enabled at long-term fuel metric values < 0.70 until the diagnostic repasses after a failure.</p>		<p>If the accumulated purge volume is > 0.0 grams, the intrusive test will not be inhibited even if Purge Vapor Fuel is > 100.0%.</p>	<p>time to purge excess vapors from the canister. During this period, fuel trim will pass if the filtered Purge Long Term Fuel Trim metric > 0.705 for at least 200.0 seconds, indicating that the canister has been purged.</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		segments allowing Purge to renable between segments. Likewise, for these reasons, if after the 5 intrusive segments the diagnostic continues to pass, there is a delay period of 300 seconds to allow sufficient time to purge excess vapors from the canister, before re-evaluating a Rich condition if it still exists.						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 1 Circuit Low Fault	P0182	<p>This DTC diagnose SENT fuel rail temperature sensor 1 that is too low out of range.</p> <p>If the sensor digital value (representing the reference voltage) is below the lower digital threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the low sample counter reaches its threshold.</p>	Fuel Temperature Sensor 1 SENT digital read value	< 145	<p>Fuel Temperature Out of Range Diagnostic Enabled</p> <p>No Fault Active on</p> <p>No Fault Pending on</p>	<p>True</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>SENT Internal Error Fault Active (P126E)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128C)</p> <p>SENT Internal Error Fault Pending (P126E)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128C)</p>	50.00 failures out of 62.00 samples 100 ms per Sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 1 Circuit High Fault	P0183	<p>This DTC diagnose SENT fuel rail temperature sensor 1 that is too high out of range.</p> <p>If the sensor digital value (representing the reference voltage) is above the upper digital threshold, the high fail counter then increments. If the high fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the high sample counter reaches its threshold.</p>	Fuel Temperature Sensor 1 SENT digital read value	> 1,865	<p>Fuel Temperature Out of Range Diagnostic Enabled</p> <p>No Fault Active on</p> <p>No Fault Pending</p>	<p>True</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>SENT Internal Error Fault Active (P126E)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128C)</p> <p>SENT Internal Error Fault Pending (P126E)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128C)</p>	50.00 failures out of 62.00 samples 100 ms per Sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 2 Circuit Low Fault	P0187	<p>This DTC diagnose SENT fuel rail temperature sensor 2 that is too low out of range.</p> <p>If the sensor digital value (representing the reference voltage) is below the lower digital read threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the low sample counter reaches its threshold.</p>	Fuel Temperature Sensor 1 SENT digital read value	< 145.00	<p>Fuel Temperature Out of Range Diagnostic Enabled</p> <p>No Fault Active on</p> <p>No Fault Pending</p>	<p>True</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>SENT Internal Error Fault Active (P126F)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128D)</p> <p>SENT Internal Error Fault Pending (P126F)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128D)</p>	50.00 failures out of 62.00 samples 100 ms per Sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 2 Circuit High Fault	P0188	<p>This DTC diagnose SENT fuel rail temperature sensor 2 that is too high out of range.</p> <p>If the sensor digital value (representing the reference voltage) is above the upper digital read threshold, the high fail counter then increments. If the high fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the high sample counter reaches its threshold.</p>	Fuel Temperature Sensor 1 SENT digital read value	> 1,865.00	<p>Fuel Temperature Out of Range Diagnostic Enabled</p> <p>No Fault Active on</p> <p>No Fault Pending</p>	<p>True</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5) SENT Internal Error Fault Active (P126F)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128D)</p> <p>SENT Internal Error Fault Pending (P126F)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128D)</p>	50.00 failures out of 62.00 samples 100 ms per Sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pressure Sensor "B" Circuit Range/ Performance	P018B	<p>This DTC detects a fuel pressure sensor response stuck within the normal operating range using an intrusive test (as follows)</p> <p>a] Intrusive Test Trigger: 1] Fuel Pump Duty Cycle Clamped Time (min or max duty cycle) >= 5 sec</p> <p>Or 2] Fuel Pres Err Variance <= calibration value KeFRPD_cmp_FPSS_MinPres Variance (typically 0.3 to 0.6);</p> <p>Otherwise, Report status as Pass</p> <p>b] Intrusive test freq limit: 60 sec between intrusive tests that pass,</p> <p>c] Intrusive test Fuel Flow limit: Fuel Flow Actual < Max allowed Fuel Flow rate</p>	Absolute value of fuel pressure change (as sensed during intrusive test)	<= 30 kPa	<p>a] Diagnostic Enabled</p> <p>b] Engine Run Time</p> <p>c] Engine Fuel Flow</p> <p>d] Fuel Pump Control Enabled</p> <p>e] Fuel Pump Control State</p> <p>f] Emissions Fuel Level Low</p> <p>g] Validity status VeFRPD_b_FPSS_DataIntegrityOK</p> <p>IF [1] FRP Circuit Low Fault Active (DTC P018C) [2] FRP Circuit High Fault Active (DTC P018D) [3] Fuel Pump Circuit Low Fault Active (DTC P0231) [4] Fuel Pump Circuit High Fault Active (DTC P0232) [5] Fuel Pump Circuit Open Fault Active (DTC P023F) [6] Reference Voltage Fault Status (DTC P0641) [7] Fuel Pump Control Module Driver Over-temperature Fault Active (DTC P1255) [8] Fuel Pump Driver Mod</p>	<p>a] == TRUE</p> <p>b] >= 5.00 sec</p> <p>c] > 0.05 g / sec</p> <p>d] == TRUE</p> <p>e] Normal OR Fuel Pres Sensor Stuck Ctrl (rationality)</p> <p>f] <> True</p> <p>g] == TRUE</p> <p>IF [1] <> True [2] <> True [3] <> True [4] <> True [5] <> True [6] <> Active This Key [7] <> True [8] <> True</p>	<p>1 sample / 12.5 millise</p> <p>Intrusive Test Duration: Fuel Flow - related (5 to 12 sec)</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Ign Sw RunStart Pstn Ckt Low Fault Active (DTC P129D) [9] Fuel Pump Driver Control Mod Enable Ckt Perf Fault Active(DTC P12A6)	[9] <> True		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pressure Sensor "B" Circuit Low	P018C	This DTC detects if the fuel pressure sensor circuit is shorted low	Fuel Pressure Sensor Voltage Percent, 5.0V Nominal ((Abs(5.0V - SensorV_actual) /5.0V) *100)	< 4.00 % or [0 kPa ga]	Ignition circuit input state	High (Run or Crank)	64 failures / 80 samples 1 sample/12.5 ms	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pressure Sensor "B" Circuit High	P018D	This DTC detects if the fuel pressure sensor circuit is shorted high	Fuel Pressure Sensor Voltage Percent, 5.0V Nominal ((Abs(5.0V - SensorV_actual) /5.0V) *100)	> 96.00 % or [743 kPa ga]	Ignition circuit input state	High (Run or Crank)	64 failures / 80 samples 1 sample/12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT SIDI High Pressure Sensor Performance	P0191	The DTC determines if there is a skewed control fuel rail sensor (Sensor1) via a comparison to diagnostic sensor (sensor2) continuously when the engine is running and the commanded pressure is steady.	<p>Primary sensor (P1) vs. Secondary sensor (P2) performance rationality</p> <p>((Low Limit fail Filtered Fuel Control Error)</p> <p>OR</p> <p>(High Limit Fail: Filtered Fuel Control Error))</p> <p>AND</p> <p>(Filtered Absolute delta between sensor1 and sensor2</p>	<p><=</p> <p>P0191 - Low fail limit of fuel control due to pressure sensor skewed low</p> <p>(See supporting table)</p> <p>>=</p> <p>P0191 - High fail limit of fuel control due to high pressure sensor skewed High</p> <p>(see Supporting table)</p> <p>>= 1.00 mpa</p> <p>Note: fuel control error is calculated based on the squareroot of sensor1 divided by sensor2, this value is filter to ensure proper failure detection.</p> <p>Absolute delta between sensor1 and sensor2 value is filter to ensure proper failure detection.</p>	<p>Commanded Pressure rate of change (increasing or dercreasing)</p> <p>for a period of time</p>	<p>< 0.70 mpa</p> <p>>= 1.25 seconds</p> <p>Enabled when a code clear is not active or not exiting device control</p>	<p>Filter Fuel Control Error term and Absolute delta between sensor1 and sensor2 exceed Low or High Fail limit for a duration >= 1.50 seconds</p> <p>This is diagnostic runs Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure Sensor 1 Out of Range	P0192	<p>This DTC diagnose SENT high pressure sensor 1 that is too low out of range.</p> <p>If the sensor digital value (representing the reference voltage) is below the lower digital threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the low sample counter reaches its threshold.</p>	High Pressure Rail Sensor 1 SENT digital read value	=< 94			<p>Time Based: 400 Failuer out of 500 Samples 6.25 ms per Sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 Open Circuit - (SIDI)	P0201	<p>Controller specific output driver circuit diagnoses Injector 1 low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>Or</p> <p>Controller specific output driver circuit diagnoses Injector 1 high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p> <p>Or</p> <p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	<p>≥ 200 KOhms impedance between signal and controller ground</p> <p>≥ 200 KOhms impedance between signal and controller ground</p>	Battery Voltage Engine Running	<p>≥ 11 Volts ≥ 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 Open Circuit - (SIDI)	P0202	<p>Controller specific output driver circuit diagnoses Injector 2 low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>Or</p> <p>Controller specific output driver circuit diagnoses Injector 2 high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p> <p>Or</p> <p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	<p>≥ 200 KOhms impedance between signal and controller ground</p> <p>≥ 200 KOhms impedance between signal and controller ground</p>	Battery Voltage Engine Run Time	<p>≥ 11 Volts ≥ 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 Open Circuit - (SIDI)	P0203	<p>Controller specific output driver circuit diagnoses Injector 3 low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>Or</p> <p>Controller specific output driver circuit diagnoses Injector 3 high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p> <p>Or</p> <p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	<p>≥ 200 KOhms impedance between signal and controller ground</p> <p>≥ 200 KOhms impedance between signal and controller ground</p>	Battery Voltage Engine Running	<p>≥ 11 Volts ≥ 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 Open Circuit - (SIDI)	P0204	<p>Controller specific output driver circuit diagnoses Injector 4 low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>Or</p> <p>Controller specific output driver circuit diagnoses Injector 4 high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p> <p>Or</p> <p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	<p>≥ 200 KOhms impedance between signal and controller ground</p> <p>≥ 200 KOhms impedance between signal and controller ground</p>	Battery Voltage Engine Run Time	<p>≥ 11 Volts ≥ 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS2 Circuit Low	P0222	Detects a continuous or intermittent short low or open in TPS2 circuit by monitoring the TPS 2 sensor percent Vref and failing the diagnostic when the TPS percent Vref is too low. This diagnostic only runs when battery voltage is high enough.	TPS2 % Vref <	0.250 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS2 Circuit High	P0223	Detects a continuous or intermittent short high in TPS2 circuit by monitoring the TPS 2 sensor percent Vref and failing the diagnostic when the TPS percent Vref is too high. This diagnostic only runs when battery voltage is high enough.	TPS2 % Vref >	4.590 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Secondary Circuit Low [FPPM applications only]	P0231	This DTC detects if the fuel pump control circuit is shorted to low. Per "smart device" design guidelines, Fuel Pump Power Driver device reports a Faulted state enumeration if current $\geq 18A$ [25A for high performance variants. FPDCM reports Not Faulted enumeration if current $< 18A$ FPDCM reports Indeterminate state enumeration if the circuit is not being evaluated during current decision loop due to other conditions.	Power driver output current (Fuel Pump Power Module Driver Circuit Ground Short enumeration)	Current $\geq 18.0 A$	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) Fuel Pump Control Enable command d) Fuel Pump Control Enable time [FAFR FPPM GshtDlyThr] e) System Voltage f] FPDCM Driver Status Alive Rolling Count Sample Faulted g] Diagnostic feedback received	a) == FCBR Gas ECM FPPM Sys b) == TRUE c) == TRUE d) ≥ 40.00 seconds e) > 7.00 Volts f] \neq TRUE g] == TRUE	64.00 failures / 80.00 samples 1 sample/12.5 millisec	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Secondary Circuit High [FPPM applications only]	P0232	This DTC detects if the fuel pump control circuit is shorted to high voltage by measuring voltage offset relative to low state level of duty cycle pulse. Per "smart device" design guidelines, Fuel Pump Power device reports a Faulted state enumeration if circuit voltage $\geq 4V$. FPPM reports Not Faulted enumeration if circuit voltage $< 4V$. FPPM reports Indeterminate state enumeration if the circuit is not being evaluated during current decision loop due to other conditions.	Voltage offset relative to low state level of duty cycle pulse measured at fuel pump circuit	$> 4.0 V$	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) Diagnostic System Disabled d) Fuel Pump Control Enabled e) Arbitrated Fuel Pump Duty Cycle Rate of Change [FCBR] f) System voltage g) FPPM Driver Status Alive Rolling Count Sample Faulted h) Diagnostic serial data received	a) == FCBR Gas ECM FPPM Sys b) == TRUE c) \neq True d) == TRUE e) $\geq -100.0 \% / \text{sec}$ f) $> 7.0 \text{ volts}$ g) \neq True h) == TRUE	64 failures / 80 samples 1 sample / 12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Secondary Circuit Open [FPPM applications only]	P023F	This DTC detects if the fuel pump control circuit is open Per "smart device" design guidelines, Fuel Pump Power device reports a Faulted state enumeration if current <= 1A . FPPM reports Not Faulted enumeration if current > 1A. FPPM reports Indeterminate state enumeration if the circuit is not being evaluated during current decision loop due to other conditions.	Output driver current (Fuel Pump Power Module Driver Circuit Open enumeration)	Current <= 1.0 A	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) Arbitrated Fuel Pump Duty Cycle (%) d] Fuel Pump Control Enable Faulted e] FPPM Fuel Pmp Driver Over-temperature Faulted f] FPPM Driver Status Alive Rolling Count Sample Faulted g] Diagnostic feedback received h] System Voltage	a) == FCBR Gas ECM FPPM Sys b) == TRUE c) > 49.00 % d] <> TRUE e] <> TRUE f] <> TRUE g] == TRUE h] > 11.00 Volts	40 failures / 80 samples 1 sample/12.5ms	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 Low side circuit shorted to ground (SIDI)	P0261	Controller specific output driver circuit diagnoses Injector 1 low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	<= 1 volt between signal and controller ground	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 Low side circuit shorted to power (SIDI)	P0262	Controller specific output driver circuit diagnoses Injector 1 low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 Low side circuit shorted to ground (SIDI)	P0264	Controller specific output driver circuit diagnoses Injector 2 low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	<= 1 volt between signal and controller ground	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 Low side circuit shorted to power (SIDI)	P0265	Controller specific output driver circuit diagnoses Injector 2 low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	25 amp >= through low side driver	Battery Voltage Engine Run Time	<p>>= 11 Volts >= 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 Low side circuit shorted to ground (SIDI)	P0267	Controller specific output driver circuit diagnoses Injector 3 low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	<= 1 volt between signal and controller ground	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 Low side circuit shorted to power (SIDI)	P0268	Controller specific output driver circuit diagnoses Injector 3 low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 Low side circuit shorted to ground (SIDI)	P0270	Controller specific output driver circuit diagnoses Injector 4 low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	<= 1 volt between signal and controller ground	Battery Voltage Engine Run Time	<p>>= 11 Volts >= 2 Seconds</p> <p>P062B not FA or TFTK</p>	<p>10.00 failures out of 20.00 samples</p> <p>100 ms /sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 Low side circuit shorted to power (SIDI)	P0271	Controller specific output driver circuit diagnoses Injector 4 low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Random Misfire Detected	P0300	These DTC's will determine if a random or a cylinder specific misfire is occurring by monitoring various terms derived from crankshaft velocity. The rate of misfire over an interval is compared to both emissions and catalyst damaging thresholds. The pattern of crankshaft acceleration after the misfire is checked to differentiate between real misfire and other sources of crank shaft noise.	Crankshaft Deceleration Value(s) vs. Engine Speed and Engine load		Engine Run Time	> 2 crankshaft revolution	Emission Exceedence = any (5) failed 200 rev blocks out of (16) 200 rev block tests	Type B, 2 Trips (Mil Flashes with Catalyst damage level of Misfire)
Cylinder 1 Misfire Detected	P0301		The equation used to calculate deceleration value is tailored to specific vehicle operating conditions. The selection of the equation used is based on the 1st single cylinder continuous misfire threshold tables encountered that are not max of range. If all tables are max of range at a given speed/load, that speed load region is an Undetectable region see Algorithm Description Document for additional details.		Engine Coolant Temp	"ECT" If OBD Max Coolant Achieved = FALSE -12 °C < ECT Or if OBD Max Coolant Achieved = TRUE -12 °C < ECT < 127 °C		
Cylinder 2 Misfire Detected	P0302				Or If ECT at startup Then	< -12 °C If OBD Max Coolant Achieved = FALSE 21 °C < ECT If OBD Max Coolant Achieved = TRUE 21 °C < ECT < 127 °C	Failure reported for (1) Exceedence in 1st (16) 200 rev block tests, or (4) Exceedences thereafter.	
Cylinder 3 Misfire Detected	P0303							
Cylinder 4 Misfire Detected	P0304							
				- see details of thresholds on Supporting Tables Tab	System Voltage + Throttle delta - Throttle delta	9.00 < volts < 32.00 < 100.00 % per 25 ms < 100.00 % per 25 ms		
			SINGLE CYLINDER CONTINUOUS MISFIRE((Medres_Decel Medres_Jerk	> IdleSCD_Decel AND > IdleSCD_Jerk)	Early Termination option: (used on plug ins that may not have enough engine run time at end of trip for normal interval to complete.)	Not Enabled	OR when Early Termination Reporting = Enabled and engine rev > 1,000 revs and < 3,200 revs at end of trip	
			OR (Medres_Decel Medres_Jerk	> SCD_Decel AND > SCD_Jerk)				
			OR (Lores_Decel Lores_Jerk	> IdleCyl_Decel AND > IdleCyl_Jerk)				
			OR (Lores_Decel Lores_Jerk	> CylModeDecel AND > CylModeJerk)				
			OR RevBalanceTime	> RevMode_Decel				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>*****</p> <p>**This Feature not used on Gasoline engines**</p> <p>Combustion Modes that force selection of Idle Tables</p> <p>*****</p> <p>Other patterns of misfire use adjustments to the single cylinder continuous misfire threshold tables:</p> <p>RANDOM MISFIRE Use random misfire thresholds If no misfire for</p> <p style="padding-left: 40px;">(Medres_Decel</p> <p style="text-align: center;">AND</p> <p style="padding-left: 40px;">Medres_Jerk)</p> <p style="padding-left: 40px;">OR (Medres_Decel</p> <p style="text-align: center;">AND</p> <p style="padding-left: 40px;">Medres_Jerk)</p> <p style="padding-left: 40px;">OR (Lores_Decel</p> <p style="text-align: center;">AND</p> <p style="padding-left: 40px;">Lores_Jerk)</p>	<p>*****</p> <p>**This Feature not used on Gasoline engines**</p> <p>CombustModelIdleTbl in Supporting Tables</p> <p>*****</p> <p>> 3 Engine Cycles</p> <p>> IdleSCD_Decel * Random_SCD_Decel</p> <p>> IdleSCD_Jerk * Random_SCD_Jerk</p> <p>> SCD_Decel * Random_SCD_Decel</p> <p>> SCD_Jerk * Random_SCD_Jerk</p> <p>> IdleCyl_Decel * RandomCylModDecel</p> <p>> IdleCyl_Jerk * RandomCylModJerk</p>			<p>any Catalyst Exceedence = (1) 200 rev block as data supports for catalyst damage.</p> <p>Catalyst Failure reported with (1 or 3) Exceedences in FTP, or (1) Exceedence outside FTP.</p> <p>Continuous</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			OR (Lores_Decel AND Lores_Jerk) OR RevBalanceTime PAIRED CYLINDER MISFIRE If a cylinder & it's pair are above PAIR thresholds (Medres_Decel AND Medres_Jerk) OR (Medres_Decel AND Medres_Jerk) OR (Lores_Decel AND Lores_Jerk) OR (Lores_Decel AND Lores_Jerk)	> CylModeDecel * RandomCylModDecel > CylModeJerk * RandomCylModJerk > RevMode_Decel * RandomRevModDecl > IdleSCD_Decel * Pair_SCD_Decel > IdleSCD_Jerk * Pair_SCD_Jerk > SCD_Decel * Pair_SCD_Decel > SCD_Jerk * Pair_SCD_Jerk > IdleCyl_Decel * PairCylModeDecel > IdleCyl_Jerk * PairCylModeJerk > CylModeDecel * PairCylModeDecel > CylModeJerk * PairCylModeJerk				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>OR (Revmode Active AND (within one engine cycle: 2nd largest Lores_Decel)</p> <p style="text-align: center;">AND Above TRUE for))</p> <p>BANK MISFIRE Cylinders above Bank Thresholds</p> <p style="text-align: center;">(Medres_Decel</p> <p style="text-align: center;">AND Medres_Jerk)</p> <p>OR (Medres_Decel</p> <p style="text-align: center;">AND Medres_Jerk)</p> <p>OR (Lores_Decel</p> <p style="text-align: center;">AND Lores_Jerk)</p> <p>OR (Lores_Decel</p> <p style="text-align: center;">AND Lores_Jerk)</p>	<p>> CylModeDecel * PairCylModeDecel</p> <p>> 80 engine cycles out of 100 engine cycles</p> <p>>= 3 cylinders</p> <p>> IdleSCD_Decel * Bank_SCD_Decel</p> <p>> IdleSCD_Jerk * Bank_SCD_Jerk</p> <p>> SCD_Decel * Bank_SCD_Decel</p> <p>> SCD_Jerk * Bank_SCD_Jerk</p> <p>> IdleCyl_Decel * BankCylModeDecel</p> <p>> IdleCyl_Jerk * BankCylModeJerk</p> <p>> CylModeDecel * BankCylModeDecel</p> <p>> CylModeJerk * BankCylModeJerk</p>				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>CONSECUTIVE CYLINDER MISFIRE 1st cylinder uses single cyl continuous misfire thresholds; 2nd Cylinder uses: (Medres_Decel</p> <p style="padding-left: 100px;">AND Medres_Jerk)</p> <p>OR (Medres_Decel</p> <p style="padding-left: 100px;">AND Medres_Jerk)</p> <p>OR (Lores_Decel</p> <p style="padding-left: 100px;">AND Lores_Jerk)</p> <p>OR (Lores_Decel</p> <p style="padding-left: 100px;">AND Lores_Jerk)</p> <p>CYLINDER DEACTIVATION MODE (Active Fuel Managment)</p>	<p>> IdleSCD_Decel * ConsecSCD_Decel</p> <p>> IdleSCD_Jerk * ConsecSCD_Jerk</p> <p>> SCD_Decel * ConsecSCD_Decel</p> <p>> SCD_Jerk * ConsecSCD_Jerk</p> <p>> IdleCyl_Decel * ConsecCylModDecel</p> <p>> IdleSCD_Jerk * ConsecCylModeJerk</p> <p>> CylModeDecel * ConsecCylModDecel</p> <p>> CylModeJerk * ConsecCylModeJerk</p>				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			AFM: SINGLE CYLINDER CONTINUOUS MISFIRE (CylAfterDeacCyl_Decel AND CylAfterDeacCyl_Jerk) OR (CylBeforeDeacCylDecel AND CylBeforeDeacCyl_Jerk)	> CylModeDecel * ClyAfterAFM_Decel > CylModeJerk * CylAfterAFM_Jerk > CylModeDecel * CylBeforeAFM_Decel > CylModeJerk * ClyBeforeAFM_Jerk				
			AFM: RANDOM MISFIRE Use random misfire thresholds If no misfire for (CylAfterDeacCyl_Decel AND CylAfterDeacCyl_Jerk) (CylBeforeDeacCylDecel AND CylBeforeDeacCyl_Jerk)	> 3 Engine Cycles > CylModeDecel * ClyAfterAFM_Decel * RandomAFM_Decl > CylModeJerk * CylAfterAFM_Jerk * RandomAFM_Jerk > CylModeDecel * CylBeforeAFM_Decel * RandomAFM_Decl > CylModeJerk * ClyBeforeAFM_Jerk * RandomAFM_Jerk				
				- see details on Supporting Tables Tab				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>Misfire Percent Emission Failure Threshold</p> <p>Misfire Percent Catalyst Damage</p> <p>When engine speed and load are less than the FTP calcs (3) catalyst damage exceedences are allowed.</p>	<p>$\geq 2.75\%$ P0300</p> <p>$>$ Catalyst_Damage_Misfire_Percentage in Supporting Tables whenever secondary conditions are met.</p> <p>$\leq 1,600$ FTP rpm AND ≤ 35 FTP % load</p>	<p>(at low speed/loads, one cylinder may not cause cat damage)</p> <p>Engine Speed Engine Load Misfire counts</p> <p>Engine Speed</p>	<p>$> 1,600$ rpm AND $> 25\%$ load AND < 180 counts on one cylinder</p> <p>$1,050 < \text{rpm} < ((\text{Engine Over Speed Limit}) - 50)$ OR 8,191)</p> <p>Engine speed limit is a function of inputs like Gear and temperature</p>	<p>4 cycle delay</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
						see EngineOverSpeedLimit in supporting tables		
					No active DTCs:	TPS_FA EnginePowerLimited MAF_SensorTFTKO MAP_SensorTFTKO IAT_SensorTFTKO ECT_Sensor_Ckt_TFTKO 5VoltReferenceB_FA CrankSensor_TFTKO CrankSensor_FA CamLctnIntFA CamLctnExhFA CamSensorAnyLctnTFTKO AnyCamPhaser_FA AnyCamPhaser_TFTKO AmbPresDfItDStatus	4 cycle delay	
					P0315 & engine speed	> 1,000 rpm	4 cycle delay	
					Fuel Level Low	LowFuelConditionDiagnostic	500 cycle delay	
					Cam and Crank Sensors	in sync with each other	4 cycle delay	
					Misfire requests TCC unlock	Not honored because Transmission in hot mode or POPD intrusive diagnostic running	4 cycle delay	
					Fuel System Status	≠ Fuel Cut	4 cycle delay	
					Active FuelManagement	Transition in progress	0 cycle delay	
					Undetectable engine	Undetectable region	4 cycle delay	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					speed and engine load region	from Malfunction Criteria		
					Abusive Engine Over Speed	> 8,192 rpm	0 cycle delay	
					Below zero torque (except CARB approved 3000 rpm to redline triangle.)	< ZeroTorqueEngLoad or < ZeroTorqueAFM if AFM is active in Supporting Tables	4 cycle delay	
					Below zero torque: TPS Vehicle Speed	≤ 2.0 % (≤ 2.0 % in AFM) > 318 mph (> 19 mph AFM)	4 cycle delay	
					NEGATIVE TORQ AFM If deactivated cylinders appear to make power, torque is negative: DeactivatedCyl_Decel AND DeactivatedCyl_Jerk AND # of Deact Cyls Inverted	< DeacCylInversionDecel < DeacCylInversionJerk > 4 cylinders	0 cycle delay	
					EGR Intrusive test	if Active	12 cycle delay	
					Manual Trans		0 cycle delay	
					Accel Pedal Position AND Automatic transmission shift	Clutch shift > 100.00 %	0 cycle delay	
					After Fuel resumes on Automatic shift containing Fuel Cut		2 Cylinder delay	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Delay if PTO engaged</p> <p>*****</p> <p>**This Feature not used on Gasoline engines**</p> <p>Combustion Mode</p> <p>Driver cranks before Wait to Start lamp extinguishes</p> <p>Brake Torque *****</p> <p>DRIVELINE RING FILTER After a low level misfire, another misfire may not be detectable until driveline ringing ceases. If no ringing seen, stop filter early. Filter Driveline ring:</p> <p>Stop filter early:</p> <p>ABNORMAL ENGINE SPEED OSCILLATION: (checks each "misfire" candidate in 100 engine</p>	<p>Enabled</p> <p>*****</p> <p>= InfrequentRegen value in Supporting Tables</p> <p>IF TRUE</p> <p>> 199.99 % Max Torque *****</p> <p>> "Ring Filter" # of engine cycles after misfire in Supporting Tables</p> <p>> "Number of Normals" # of engine cycles after misfire in Supporting Tables tab</p>	<p>4 cycle delay</p> <p>*****</p> <p>0 cycle delay</p> <p>WaitToStart cycle delay</p> <p>0 cycle delay *****</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Cycle test to see if it looks like some disturbance like rough road (abnormal).)</p> <p>Used Off Idle, and while not shifting,</p> <p style="text-align: right;">TPS</p> <p style="text-align: right;">Engine Speed</p> <p style="text-align: right;">Veh Speed</p> <p style="text-align: right;">Auto Transmission</p> <p>individual candidate deemed abnormal if number of consecutive decelerating cylinders after "misfire": (Number of decels can vary with misfire detection equation)</p> <p style="text-align: right;">Consecutive decels while in SCD Mode</p> <p style="text-align: right;">Cyl Mode</p> <p style="text-align: right;">Rev Mode</p> <p>At the end of 100 engine cycle test, the ratio of abnormal/candidate is checked to confirm if real misfire is present within the 100 engine cycles.</p> <p>abnormal candidates/ total candidates</p> <p>MISFIRE CRANKSHAFT</p>	<p>> 1 %</p> <p>> 1,000 rpm</p> <p>> 0 mph</p> <p>not shifting</p> <p>> Abnormal SCD Mode</p> <p>> Abnormal Cyl Mode</p> <p>> Abnormal Rev Mode</p> <p>in Supporting Tables</p> <p>> 0.50 ratio</p>	<p>discard 100 engine cycle test</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>PATTERN RECOGNITION checks each "misfire" candidate in 100 engine Cycle test to see if overall crankshaft pattern looks like real misfire (recognized), or some disturbance like rough road (unrecognized). At the end of 100 engine cycle test, the ratio of unrecog/recognized is checked to confirm if real misfire is present within the 100 engine cycles. Typically used for checking a single misfire per engine cycle but can support some other patterns on some packages</p> <p>Pattern Recog Enabled:</p> <p>Pattern Recog Enabled during Cylinder Deac</p> <p>Pattern Recog Enabled consecutive cyl patrn</p> <p>Engine Speed Veh Speed</p> <p>The 1st check for "recognized" is the 1st fired cylinder after the misfire candidate should both accelerate and jerk an amount based acceleration and jerk of Single Cylinder Misfire</p>	<p>Disabled</p> <p>Not Enabled</p> <p>Disabled</p> <p>700 < rpm < 3,000 > 0.6 mph</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>thresholds in effect at that speed and load. (CylAfter_Accel AND CylAfter_Jerk)</p> <p>Additionally, the crankshaft is checked again a small calibratable number of cylinders later to see if the disturbance is still large like rough road, or has calmed down like real misfire. The size of disturbance is compared to a multiplier times the ddt_jerk value used to detect misfire at that speed and load. If there is repetitive misfire on consecutive engine cycles, the expected snap is adjusted due to the higher expected disturbance.</p> <p>Num of Cylinders after misfire to start check of crankshaft snap</p> <p>"misfire" recognized if: Crankshaft snap after: isolated "misfire"</p>	<p>> Misfire_decel * 1st_FireAftrMisfr_Acel</p> <p>> Misfire_Jerk * 1st_FireAftrMisfr_Jerk</p> <p>Or if AFM mode is active: > Misfire_decel * 1stFireAftrMisAcelAFM > Misfire_Jerk * 1stFireAfterMisJerkAFM</p> <p>2 Cylinders</p> <p>< Misfire_Jerk * SnapDecayAfterMisfire</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>repetative "misfire"</p> <p>At the end of 100 engine cycle test, the ratio of unrecog/recognized is checked to confirm if real misfire is present.</p> <p>Ratio of Unrecog/Recog</p> <p>:</p> <p>NON-CRANKSHAFT BASED ROUGH ROAD:</p> <p>Rough Road Source</p> <p>IF Rough Road Source = WheelSpeedInECM ABS/TCS Wheel speed noise VSES</p> <p>IF Rough Road Source = "FromABS" ABS/TCS RoughRoad VSES</p> <p>IF Rough Road Source = "TOSS" TOSS dispersion</p> <p>AND No Active DTCs</p>	<p>< Misfire_Jerk * SnapDecayAfterMisfire * RepetSnapDecayAdjst in Supporting Tables</p> <p>> 1.00</p> <p>Enabled</p> <p>Wheel Speed in ECM</p> <p>active > WSSRoughRoadThres active</p> <p>active detected active</p> <p>>TOSSRoughRoadThres in supporting tables</p>	<p>discard 100 engine cycle test</p> <p>discard 100 engine cycle test</p> <p>discard 100 engine cycle test</p> <p>discard 100 engine cycle test</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
						Transmission Output Shaft Angular Velocity Validity TransmissionEngagedStat e_FA (Auto Trans only) ClutchPstnSnsr FA (Manual Trans only)	4 cycle delay	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position System Variation Not Learned	P0315	This DTC determines if the crankshaft sensor learn values that are stored in memory are valid. The angle between each tooth of the reluctor wheel is learned, and the sum of all angles together should sum to 360° (one revolution of the reluctor wheel). Default values, or corrupted values will not sum to 360°.	<p>The Crankshaft target wheel should be 360 degrees around in circumference. Loss or controller non-volatile memory or an error in memory will cause the values of individual teeth learn to be defaulted or incorrect.</p> <p>Set the DTC if the Difference between the sum of the reluctor wheel's teeth and 360 degrees is greater than:</p>	> 0.001 degrees	OBD Manufacturer Enable Counter	MEC = 0	0.50 seconds Frequency Continuous100 msec	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Performance Per Cylinder	P0324	This diagnostic checks for knock sensor performance out of the normal expected range on a per cylinder basis due to Excessive Knock (either real or false knock). In the knock detection algorithm, the term "Knock Intensity" (KI) is used to define the relative size of a knock event, and is calculated as (KI = current knock event - knock threshold). This results in a KI amplitude that is proportional to the size of the knock event (as seen by the knock sensor). In addition, Knock Intensity cannot be less than zero as it is forced/limited to be = 0 with no knock detected (i.e. whenever the current knock event < knock threshold, KI = 0). This diagnostic calculates a first-order lag filter version of the Knock Intensity and sets a fault when: (Filtered KI) > (Excessive Knock Diagnostic Threshold)	Filtered Knock Intensity (where 'Knock Intensity' = 0 with no knock; and > 0 & proportional to knock magnitude with knock)	> P0324_PerCyl_ExcessiveKnock_Threshold (no units)	Diagnostic Enabled? Engine Run Time Engine Speed Engine Air Flow Engine Coolant Temperature or OBD Coolant Enable Criteria Inlet Air Temperature Cumulative Number of Engine Revs Above Min Eng Speed (per key cycle)	Yes ≥ 2.0 seconds ≥ 700 RPM AND ≤ 8,500 RPM ≥ 50 mg/cylinder AND ≤ 2,000 mg/cylinder ≥ -40 deg's C = TRUE ≥ -40 deg's C ≥ 170 revs	First Order Lag Filters with Weight Coefficient = 0.0201 Updated each engine event	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit Bank 1	P0325	<p>This diagnostic checks for an open in the knock sensor circuit Sensor 1/Bank 1. There are two possible methods used:</p> <p>1. 20 kHz Method: This method injects a 20 kHz signal (internal to the ECU) onto one of the Knock Sensor inputs. For a normal/good circuit the 20 kHz signal will propagate through the Knock sensor and back to the ECU through the sensor return circuit. The 20 kHz signal is processed through the Fast Fourier Transform (FFT) and then filtered with a first-order lag filter. Since the Knock Detection algorithm uses a Differential Op-Amp to compare the input from the two knock sensor wires, the FFT 20 kHz diagnostic signal will have either: A. Low output with a good circuit (because the 20 kHz injected signal is detected on both of the sensor inputs) or B. High output for an Open Circuit (because</p>	<p>Open Circuit Method chosen (2 possible methods: 20 kHz or Normal Noise):</p> <p>Filtered FFT Output</p> <p>Filtered FFT Output</p>	<p>= P0325_P0330_OpenMethod_2</p> <p><u>Case 1 (20 kHz Method):</u></p> <p>> P0325_P0330_OpenCktThrshMin (20 kHz) AND < P0325_P0330_OpenCktThrshMax (20 kHz)</p> <p><u>Case 2 (Normal Noise Method):</u></p> <p>> P0325_P0330_OpenCktThrshMin (Normal Noise) AND < P0325_P0330_OpenCktThrshMax (Normal Noise)</p>	<p>Diagnostic Enabled?</p> <p>Engine Run Time</p> <p>Engine Speed</p> <p>Cumulative Number of Engine Revs (per key cycle) within min/max Engine Speed enable (above)</p> <p>Engine Air Flow</p> <p>Engine Coolant Temperature</p> <p>or</p> <p>OBD Coolant Enable Criteria</p> <p>Inlet Air Temperature</p>	<p>Yes</p> <p>≥ 2.0 seconds</p> <p>≥ 1,000 RPM and ≤ 4,650 RPM</p> <p>≥ 100 revs</p> <p>≥ 40 mg/cylinder and ≤ 2,000 mg/cylinder</p> <p>≥ -40 deg's C</p> <p>= TRUE</p> <p>≥ -40 deg's C</p>	<p>First Order Lag Filter with Weight Coefficient</p> <p>Weight Coefficient = 0.0100</p> <p>Updated each engine event</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>the 20 kHz injected signal is detected only on one of the sensor inputs).</p> <p>The 20 kHz method is typically used for the entire operating region of the engine. However, some engines may not have adequate separation between good and bad circuits at high engine speed. In these cases the 20 kHz method is used at low and medium engine speeds, and the "Normal Noise" method is used at high engine speed only.</p> <p>2. Normal Noise: The Normal Noise method monitors the background engine noise level for a selected frequency range output of the knock detection FFT. The background noise (i.e. Normal Noise) is filtered with a first-order lag filter. A good circuit is determined when the filtered Normal Noise signal is greater than the threshold.</p> <p>See Supporting Tables for method definition: P0325 P0330 OpenM</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ethod defines which of the two diagnostic methods is used as a function of engine speed (RPM). Typical implementations: A. Use 20 kHz method at all engine RPM (used when acceptable separation achieved at all RPM) or B. Use 20 kHz method at low/medium RPM and Normal Noise at high RPM						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Performance Bank 1	P0326	This diagnostic checks for knock sensor performance out of the normal expected range, on a per sensor basis. This diagnostic is specifically designed to identify the fault condition where the knock sensor is properly attached electrically, but produces an abnormally low output due to being unattached (or loosely attached) with the mounting bolt (and thus unable to properly transfer the engine vibration energy from the engine block to the knock sensor). The term "Abnormal (engine) Noise" is used to define this diagnostic method. A fault condition is identified when a first-order lag filtered version of the Abnormal Noise signal falls below the diagnostic threshold.	<p>Filtered FFT Intensity</p> <p>(where 'FFT Intensity' = Non-knocking, background engine noise for a selected frequency)</p> <p>Filtered FFT Intensity</p>	<p><u>Case 1: Engine <u>not</u> in AFM mode</u></p> <p>< P0326_P0331_AbnormalNoise_Threshold (Supporting Table)</p> <p>OR</p> <p><u>Case 2: Engine <u>is</u> in AFM mode</u></p> <p>< P0326_P0331_AbnormalNoise_Thresh_AF M (Supporting Table; Engine <u>is</u> in AFM mode)</p>	<p>Diagnostic Enabled?</p> <p>Engine Run Time</p> <p>Engine Speed</p> <p>Engine Air Flow</p> <p>Engine Coolant Temperature</p> <p>or</p> <p>OBD Coolant Enable Criteria</p> <p>Inlet Air Temperature</p> <p>Individual Cylinders enabled for Abnormal Noise</p> <p>Cumulative Number of Engine Revs Above Min Eng Speed (per key cycle)</p>	<p>Yes</p> <p>≥ 2.0 seconds</p> <p>≥ 2,000 RPM (not in AFM mode) OR ≥ 8,500 (in AFM mode)</p> <p>AND ≤ 8,500 RPM</p> <p>≥ 50 mg/cylinder AND ≤ 2,000 mg/cylinder</p> <p>≥ -40 deg's C</p> <p>= TRUE</p> <p>≥ -40 deg's C</p> <p>P0326_P0331_Abnormal Noise_CylsEnabled (Supporting Table)</p> <p>≥ 333 Revs</p>	<p>First Order Lag Filters with Weight Coefficient = 0.0021</p> <p>Updated each engine event</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit Low Bank 1	P0327	This diagnostic checks for an out of range low knock sensor signal. A 3-resistor bias network at each sensor input to the ECM provides a DC diagnostic voltage that will remain within a normal range when the external knock sensor circuit is free of short circuit faults. The diagnostic output is reported as a percentage (0 to 100%) when compared to the 5.0 volt reference voltage.	Sensor Input or Return Signal Line	< 8.0 Percent (of 5.0 Volt reference)	Diagnostic Enabled? Engine Speed	Yes > 0 RPM and < 8,500 RPM	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit High Bank 1	P0328	This diagnostic checks for an out of range high knock sensor signal. A 3-resistor bias network at each sensor input to the ECM provides a DC diagnostic voltage that will remain within a normal range when the external knock sensor circuit is free of short circuit faults. The diagnostic output is reported as a percentage (0 to 100%) when compared to the 5.0 volt reference voltage.	Sensor Input or Return Signal Line	> 39.0 Percent (of 5 Volt Reference)	Diagnostic Enabled? Engine Speed	Yes > 0 RPM and < 8,500 RPM	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP) Sensor A Circuit	P0335	Diagnostic will fail if a crank sensor pulse was not received during a period of time; if crank sensor pulses are received the diagnostic will pass.	Time since last crankshaft position sensor pulse received	>= 4.0 seconds	Starter engaged AND (cam pulses being received OR (MAF_SensorFA AND Engine Air Flow	= FALSE > 2.0 grams/second))	Continuous every 100 msec	Type B, 2 Trips
			No crankshaft pulses received	>= 0.3 seconds	Engine is Running Starter is not engaged		Continuous every 12.5 msec	
			No crankshaft pulses received		Engine is Running OR Starter is engaged No DTC Active:	P0365 P0366	2 failures out of 10 samples One sample per engine revolution	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP) Sensor A Performance	P0336	1. Fail counts will occur if the engine goes out of synchronization repeatedly over a period of time and will pass if the engine stays in synchronization. 2. Diagnostic will fail if synchronization gap is not found in a specified period of time and will pass if the synchronization gap is found. 3. Diagnostic will fail if the incorrect number of crank sensor teeth are detected in-between detecting the synchronization gap and will pass if the correct number of teeth are seen.	Time in which 10 or more crank re-synchronizations occur	< 10.0 seconds	Engine Air Flow Cam-based engine speed No DTC Active:	>= 2.0 grams/second > 450 RPM P0335	Continuous every 250 msec	Type B, 2 Trips
			No crankshaft synchronization gap found	>= 0.4 seconds	Engine is Running Starter is not engaged		Continuous every 12.5 msec	
			Time since starter engaged without detecting crankshaft synchronization gap	>= 1.5 seconds	Starter engaged AND (cam pulses being received OR (MAF_SensorFA AND Engine Air Flow	= FALSE > 2.0 grams/second))	Continuous every 100 msec	
			Crank pulses received in one engine revolution OR Crank pulses received in one engine revolution	< 51 > 65	Engine is Running OR Starter is engaged No DTC Active:	 P0365 P0366	8 failures out of 10 samples One sample per engine revolution	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor A	P0340	Diagnostic will fail if a cam sensor pulse was not received during a period of time; if cam sensor pulses are received the diagnostic will pass.	Time since last camshaft position sensor pulse received	>= 5.5 seconds	Starter engaged AND (crank pulses being received OR (MAF_SensorFA AND Engine Air Flow	= FALSE > 2.0 grams/second))	Continuous every 100 msec	Type B, 2 Trips
			OR Time that starter has been engaged without a camshaft sensor pulse					
			Fewer than 4 camshaft pulses received in a time	> 3.0 seconds	Engine is running Starter is not engaged		Continuous every 100 msec	
			No camshaft pulses received during first 12 MEDRES events (There are 12 MEDRES events per engine cycle		Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged No DTC Active:	CrankSensor_FA	Continuous every MEDRES event	
			The number of camshaft pulses received during 100 engine cycles	= 0	Crankshaft is synchronized No DTC Active:	CrankSensor_FA	8 failures out of 10 samples Continuous every engine cycle	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor A	P0341	Diagnostic will fail if an incorrect number of cam sensor pulses are detected over a number of engine cycles and will pass if the number of cam pulses is correct.	The number of camshaft pulses received during first 12 MEDRES events is OR (There are 12 MEDRES events per engine cycle)	< 4 > 6	Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged No DTC Active:	CrankSensor_FA	Continuous every MEDRES event	Type B, 2 Trips
			The number of camshaft pulses received during 100 engine cycles OR	< 398 > 402	Crankshaft is synchronized No DTC Active:	CrankSensor_FA	8 failures out of 10 samples Continuous every engine cycle	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #1 CIRCUIT	P0351	Diagnoses Cylinder #1 Ignition Control (EST) output driver circuit for an Open Circuit fault. Controller specific output driver circuit diagnoses the low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 30 \text{ k}\Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #2 CIRCUIT	P0352	Diagnoses Cylinder #2 Ignition Control (EST) output driver circuit for an Open Circuit fault. Controller specific output driver circuit diagnoses the low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 30 \text{ k}\Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #3 CIRCUIT	P0353	Diagnoses Cylinder #3 Ignition Control (EST) output driver circuit for an Open Circuit fault. Controller specific output driver circuit diagnoses the low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 30 \text{ k}\Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #4 CIRCUIT	P0354	Diagnoses Cylinder #4 Ignition Control (EST) output driver circuit for an Open Circuit fault. Controller specific output driver circuit diagnoses the low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 30 \text{ k}\Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position (CMP) Sensor Circuit Bank 1 Sensor B	P0365	Diagnostic will fail if a cam sensor pulse was not received during a period of time; if cam sensor pulses are received the diagnostic will pass.	Time since last camshaft position sensor pulse received	>= 5.5 seconds	Starter engaged AND (crank pulses being received OR (MAF_SensorFA AND Engine Air Flow	= FALSE > 2.0 grams/second))	Continuous every 100 msec	Type B, 2 Trips
			OR Time that starter has been engaged without a camshaft sensor pulse					
			Fewer than 4 camshaft pulses received in a time	> 3.0 seconds	Engine is running Starter is not engaged		Continuous every 100 msec	
			No camshaft pulses received during first 12 MEDRES events (There are 12 MEDRES events per engine cycle		Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged No DTC Active:	CrankSensor_FA	Continuous every MEDRES event	
			The number of camshaft pulses received during 100 engine cycles	= 0	Crankshaft is synchronized No DTC Active:	CrankSensor_FA	8 failures out of 10 samples Continuous every engine cycle	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position (CMP) Sensor Performance Bank 1 Sensor B	P0366	Diagnostic will fail if an incorrect number of cam sensor pulses are detected over a number of engine cycles and will pass if the number of cam pulses is correct.	The number of camshaft pulses received during first 12 MEDRES events is OR (There are 12 MEDRES events per engine cycle)	< 4 > 6	Crankshaft is synchronized Starter must be engaged to enable the diagnostic, but the diagnostic will not disable when the starter is disengaged No DTC Active:	CrankSensor_FA	Continuous every MEDRES event	Type B, 2 Trips
			The number of camshaft pulses received during 100 engine cycles OR	< 398 > 402	Crankshaft is synchronized No DTC Active:	CrankSensor_FA	8 failures out of 10 samples Continuous every engine cycle	

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Trans gear stable timer Decel fuel cut off state is unchanged for time Vehicle Speed Arbitrated Torque EGR Position Engine Speed MAP change Altitude-compensated MAP [STEP CHANGE DETECTION] IF {{ the difference between the current EWMA and the current map diff > AND Current map diff } Run multiple tests until number of tests have been completed. [Intrusive Mode	> 2.00 sec > 0.25 sec 0.00 ~ 166.00 mph < 50.0 < 4.80 1,100.00 ~ 1,300.00 rpm < 1.00 Kpa 20.00 ~ 50.00 kPa > P0401_StepDelta kPa > P0401_StepMAP_DIFF kPa P0401_StepSamplesPer Trip P0401_SamplesAfterSte p		

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Solenoid Circuit Open	P0403	Controller specific output driver circuit diagnoses the EGR Solenoid high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	$\geq 4\text{ K } \Omega$ impedance between signal and controller ground.	<p>System supply voltage</p> <p>Output driver is commanded on</p> <p>Ignition switch is in crank or run position</p>	> 11.00 Volts	<p>100.00 failures out of 120.00 samples</p> <p>250 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Valve - Open Position Performance	P0404	Diagnostic enables while EGR valve is commanded open and opening position remains stable within time limit. This diagnostic detects if the error between actual and desired is too large.	When EGR is commanded to open, check difference between actual and commanded position of the valve. If this error is more than error threshold than open position performance failure is set.	> 4.90 %	The following DTC's NOT active: Engine is running Off-board device PTO P0401 Intrusive Ignition voltage EGR control Desired EGR position variation Enable conditions met Desired EGR position	P0405 P0406 Active Not Active Not Active Not Active >= 11.00 Volt Enabled < 4.00 for 2.00 sec. 3.00 sec > 0%	80.00 failures out of 100.00 samples 100ms loop Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Valve - Position Sensor - Circuit Low	P0405	This diagnostic detects if the valve position feedback circuit is open or shorted to ground by comparing the sensor feedback to normal operating ranges	Raw EGR feedback sensor signal is less than the expected low limit If below allowed operating range, test fails.	Raw EGR feedback sensor signal < 8.00 %	The following DTC's NOT active: Engine Run State Off-board device PTO EGR Flow Insufficient (P0401) Ignition voltage EGR diagnostic Enable conditions met for	Active Not active Not active Not intrusive >= 11.00 Enabled 3.00 sec.	53.00 failures out of 60.00 samples 100 ms Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Valve - Position Sensor - Circuit High	P0406	This diagnostic detects if the valve position feedback circuit is shorted to high voltage or the 5V return is open.	Raw EGR feedback sensor signal is greater than the expected high limit. By comparing the feedback value to the max allowed operating range.	Raw EGR feedback sensor signal > 89.00 %	The following DTC's NOT active: Engine Run State Off-board device PTO EGR Flow Insufficient (P0401) Ignition voltage EGR diagnostic Enable conditions met for	Active Not active Not active Not intrusive >= 11.00 Enabled 3.00 sec.	53.00 failures out of 60.00 samples 100 ms Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor2 Ckt Range/ Performance	P040B	Determines the EGR temperature Sensor 2 has not moved enough since start after an allowed amount of EGR flow consumed by engine following a long enough soak.	After an allowed amount of EGR flow consumed by engine following a long enough soak, the Down Stream Temperature sensor has not change enough.	Absolute error between current temperature and Initial temperature <= Down Stream Stk Temp Vrtn	System supply voltage Engine soak (not run) time No Active DTCs Engine is running	> 11.00 Volts >= 28,800.00 Sec P262B Active	Cumulative EGR Flow > 4,000.00 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor2 Ckt Low	P040C	Diagnose the EGR Down Stream Temperature sensor circuit low if the feedback of the Down Stream temp sensor is below allowed operating range the sensor is faulted.	The ECM detects that the measured resistance of the temperature sensor is out of range low.	Measured Resistance of the Temperature sensor < 100.00 Ω impedance	System supply voltage Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	50 failures out of 63 samples 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor2 Ckt High	P040D	Diagnose the EGR Down Stream Temperature sensor circuit high if the feedback of the Down Stream temp sensor is above allowed operating range the sensor is faulted	The ECM detects that the measured resistance of the temperature sensor is out of range high.	Measured Resistance of the Temperature sensor > 1,400.00 Ω impedance	System supply voltage Output driver Ignition switch	> 11.00 Volts On Crank or Run	50 failures out of 63 samples 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor2 Ckt Intermittent/ Erratic	P040E	<p>Detects a temperature sensor that is showing erratic or intermittent temperature readings.</p> <p>The temperature feedback is monitored in a 100 ms time loop. If the temperature is changing more than an allowed amount per loop the sensor is determined to be erratic.</p>	The absolute value of the loop to loop (100 ms / sample) resistance change of the temperature sensor is greater than the allowed rate of change.	Delta change > 10.00 Ω impedance	<p>System supply voltage</p> <p>Output driver</p> <p>Ignition switch</p>	<p>> 11.00 Volts</p> <p>On</p> <p>Crank or Run</p>	<p>15 failures out of 30 samples</p> <p>100 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor1 Ckt Range/ Performance	P041B	Determines the EGR temperature Sensor 1 has not moved enough since start after an allowed amount of EGR flow consumed by engine following a long enough soak.	After an allowed amount of EGR flow consumed by engine following a long enough soak, the Up Stream Temperature sensor has not change enough.	Absolute error between current temperature and Initial temperature <= UP Stream Stk Temp Vrtn	System supply voltage Engine soak (not run) time No Active DTCs Engine is running	> 11.00 Volts >= 28,800.00 Sec P262B Active	cumulative EGR Flow > 4,000.00 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor1 Ckt Low	P041C	Diagnose the EGR Up Stream Temperature sensor circuit low by measuring the resistance of the sensor circuit. If the measured resistance of the circuit is below the allowed operating range, the sensor is out of range low.	The ECM detects that the measured resistance of the temperature sensor is out of range low.	Measured Resistance of the Temperature sensor < 100.00 Ω impedance	System supply voltage Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	53 failures out of 60 samples 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor1 Ckt High	P041D	Diagnose the EGR Up Stream Temperature sensor circuit high by measuring the resistance of the sensor circuit. If the measured resistance of the circuit is above the allowed operating range, the sensor is out of range high.	The ECM detects that the measured resistance of the temperature sensor is out of range high.	Measured Resistance of the Temperature sensor > 1,400.00 Ω impedance	System supply voltage Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	50 failures out of 63 samples 100 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor1 Ckt Intermittent/ Erratic	P041E	<p>Detects a temperature sensor that is showing erratic or intermittent temperature readings.</p> <p>The temperature feedback is monitored in a 100 ms time loop. If the temperature is changing more than an allowed amount per loop the sensor is determined to be erratic.</p>	The absolute value of the loop to loop (100 ms / sample) resistance change of the temperature sensor is greater than the allowed rate of change.	Delta chage > 10.00 Ω impedance	<p>System supply voltage</p> <p>Output driver</p> <p>Ignition switch</p>	<p>> 11.00 Volts</p> <p>On</p> <p>Crank or Run</p>	<p>15 failures out of 30 samples</p> <p>100 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Catalyst System Low Efficiency Bank 1	P0420	<p>NOTE: The information below applies to applications that use the Decel Catalyst Monitor Algorithm</p> <p>Oxygen Storage. The catalyst washcoat contains Cerium Oxide. Cerium Oxide reacts with NO and O2 during lean A/F excursions to store the excess oxygen (I.e. Cerium Oxidation). During rich A/F excursions, Cerium Oxide reacts with CO and H2 to release this stored oxygen (I.e. Cerium Reduction). This is referred to as the Oxygen Storage Capacity, or OSC. CatMon's strategy is to "measure" the OSC of the catalyst through forced Rich (intrusive rich) and Lean (decel fuel cutoff) A/F excursions</p> <p>Normalized Ratio OSC Value Calculation Information and Definitions =</p> <ol style="list-style-type: none"> 1. Raw OSC Calculation = (post cat O2 Resp time - pre cat O2 Resp time) 2. BestFailing OSC value from a calibration 	Normalized Ratio OSC Value (EWMA filtered)	< 0.35	<p>All enable criteria associated with P0420 can be found under P2270 - (O2 Sensor Signal Stuck Lean Bank 1 Sensor 2)</p> <p>Rapid Step Response (RSR) feature will initiate multiple tests:</p> <p>If the difference between current EWMA value and the current OSC Normalized Ratio value is</p> <p>and the current OSC Normalized Ratio value is</p> <p>Maximum number of RSR tests to detect failure when RSR is enabled.</p> <p>MAF</p> <p>Predicted catalyst temperature</p> <p>Front O2 Sensor or Front WRAF</p> <p>Rear O2 Sensor</p> <p>General Enable Criteria</p> <p>In addition to the p-codes listed under P2270, the following DTC's shall also</p>	<p>> 0.66</p> <p>< 0.10</p> <p>8</p> <p>> 2.00 g/s < 30.00 g/s</p> <p>< 910 ° C</p> <p>> 680.00 mV or > 1.25 EQR</p> <p>> 700.00 mV</p>	<p>1 test attempted per valid decel period</p> <p>Minimum of 1 test per trip</p> <p>Maximum of 3 tests per trip</p> <p>Frequency: Fueling Related : 12.5 ms</p> <p>OSC Measurements: 100 ms</p> <p>Temp Prediction: 12.5ms</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>table (based on temp and exhaust gas flow)</p> <p>3. WorstPassing OSC value (based on temp and exhaust gas flow)</p> <p>Normalized Ratio Calculation = (1-2) / (3-2)</p> <p>A Normalized Ratio of 1 essentially represents a good part and a ratio of 0 essentially represents a very bad part.</p> <p>Refer to the P0420_WorstPassingOSCTableB1 and P0420_BestFailingOSCTableB1 in Supporting Tables tab for details</p> <p>The Catalyst Monitoring Test is completed during a decel fuel cutoff event. This fuel cutoff event occurs following a rich intrusive fueling event initiated by the O2 Sensor Signal Stuck Lean Bank 1 Sensor 2 test (P2270). Several conditions must be met in order to execute this test.</p> <p>Additional conditions and their related values</p>			<p>not be set:</p> <p>For switching O2 sensors:</p> <p>For WRAF O2 sensors:</p>	<p>O2S_Bank_1_Sensor_1_FA</p> <p>O2S_Bank_1_Sensor_2_FA</p> <p>O2S_Bank_2_Sensor_1_FA</p> <p>O2S_Bank_2_Sensor_2_FA</p> <p>WRAF_Bank_1_FA</p> <p>WRAF_Bank_2_FA</p> <p>P0420_WorstPassingOSCTableB1</p> <p>P0420_BestFailingOSCTableB1</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		are listed in the "Secondary Parameters" and "Enable Conditions" section of this document for P2270 (O2 Sensor Signal Stuck Lean Bank 1 Sensor 2)						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Reference Orifice Low Flow (ELCP Sealed Fuel System)	P043E	<p>A plugged ELCP reference orifice is detected.</p> <p>When the ELCP vacuum pump is on, the ELCP pressure sensor (gauge) measures the vacuum across the reference orifice. The reference vacuum is established when the test time expires. If the reference vacuum is above a maximum reference vacuum threshold then this would indicate a plugged reference orifice.</p> <p>1st Reference Vacuum Measurement</p> <p>If the 1st reference vacuum measurement is above a maximum threshold then a failure is reported for P043E. This condition could indicate a plugged reference orifice or high flow ELCP vacuum pump.</p> <p>If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. In a passing condition,</p>	<p>If 1st 0.020" reference orifice vacuum averaged measurement is</p> <p>after then a plugged ELCP reference orifice is detected and the DTC fails.</p> <p>Or</p> <p>If 2nd 0.020" reference orifice vacuum averaged measurement is</p> <p>after then a plugged ELCP reference orifice is detected and the DTC fails.</p>	<p>3 second ≥ refer to P043E First Reference Orifice Measurement in Supporting Tables 360 seconds</p> <p>3 second ≥ refer to P043E Second Reference Orifice Measurement in Supporting Tables 30 seconds</p>	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p> <p>Refueling request button</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours ≥ 0 hours *****</p> <p>≥ 10 volts *****</p> <p>≤ 3 MPH 0 ≥ 0 seconds ≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Up to twice per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>the P043E will not report a pass at this time since this diagnostic is run again during the 2nd reference orifice check section.</p> <p>2nd Reference Vacuum Measurement</p> <p>If the 2nd reference vacuum measurement is above a maximum threshold then a failure is reported for P043E. This condition could indicate a plugged reference orifice or high flow ELCP vacuum pump. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. In a passing condition, the P043E will report a pass at this time.</p>			<p>pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043F P0451 P145C P145D P145E P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Reference Orifice High Flow (ELCP Sealed Fuel System)	P043F	<p>A missing ELCP reference orifice is detected.</p> <p>When the ELCP vacuum pump is on, the ELCP pressure sensor (gauge) measures the vacuum across the reference orifice. The reference vacuum is established when the test time expires. If the reference vacuum is below a minimum reference vacuum threshold then this would indicate a missing reference orifice.</p> <p>1st Reference Vacuum Measurement</p> <p>If the 1st reference vacuum measurement is below a minimum threshold then a failure is reported for P043F. This condition could indicate a missing reference orifice or low flow ELCP vacuum pump. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. In a passing condition, P043F will not report a pass at this</p>	<p>If 1st 0.020" reference orifice vacuum averaged measurement is</p> <p>after then a missing ELCP reference orifice is detected and the DTC fails.</p> <p>Or</p> <p>If 2nd 0.020" reference orifice vacuum averaged measurement is</p> <p>after then a missing ELCP reference orifice is detected and the DTC fails.</p>	<p>3 second ≤ refer to P043F First Reference Orifice Measurements in Supporting Tables 360 seconds</p> <p>3 second ≤ refer to P043F Second Reference Orifice Measurements in Supporting Tables 30 seconds</p>	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p> <p>Refueling request button</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Up to twice per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>time since this diagnostic is run again during the 2nd reference orifice check section.</p> <p>2nd Reference Vacuum Measurement</p> <p>If the 2nd reference vacuum measurement is below a minimum threshold then a failure is reported for P043F. This condition could indicate a missing reference orifice or low flow ELCP vacuum pump. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. In a passing condition, P043F will report a pass at this time.</p>			<p>pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P0451 P145C P145D P145E P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EVAP System Small Leak Detected (ELCP Sealed Fuel System)	P0442	<p>A small leak (≥ 0.020"") is detected in the EVAP system between the fuel cap, purge solenoid, and diurnal control valve (DCV). The ELCP vacuum pump creates a vacuum across a 0.020" reference orifice. This reference vacuum is then compared to the vacuum level created in the fuel tank to determine if a leak exists.</p> <p>The diagnostic has fast pass capability. If the Fuel Tank Pressure (FTP) sensor measures a fuel tank system pressure greater than 1,276 Pa or a fuel tank system vacuum greater than -1,278 Pa then both the small leak and large leak diagnostics pass without using the ELCP vacuum pump.</p>	If the ELCP pressure sensor (gauge) vacuum reading is less than the 2nd 0.020" reference orifice vacuum measurement for then the fuel tank system has a small leak and the DTC fails.	400 seconds	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p> <p>Refueling request button</p>	<p>4.3 \leq time \leq 5.8 hours or 6.0 \leq time \leq 8.1 hours or 8.2 \leq time \leq 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours ≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH 0 ≥ 0 seconds ≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Once per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145D P145E P145F P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Purge Control Valve Open Circuit (ELCP Sealed/ Vented Fuel System)	P0443	Controller specific output driver circuit diagnoses the canister purge solenoid low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200\text{ K } \Omega$ impedance between output and controller ground.	Powertrain relay voltage	Voltage ≥ 11.0 volts	20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips Note: In certain controllers P0458 may also set (Canister Purge Solenoid Short to Ground)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission (EVAP) Vent System Performance Diagnostic (ELCP Sealed Fuel System)	P0446	<p>EVAP vent system restriction is detected.</p> <p>The vent restriction diagnostic (P0446) is intrusive and runs as part of the purge valve low flow (P0497) diagnostic. It is a X out of Y diagnostic that runs once per trip. The same hysteresis calibrations that define the operating range for the P0497 diagnostic are also used for the vent restriction diagnostic.</p> <p>When the P0497 diagnostic is running purge priority is requested along with an engine vacuum request. The purge priority and vacuum request are maintained until both the P0497 and P0446 diagnostics are complete, or until a maximum engine vacuum request time is reached. The P0446 diagnostic will not begin until the P0497 diagnostic is in a passing condition. If the P0497 diagnostic detects a failure, then the P0446 diagnostic will not execute.</p>	After an initial time delay of if the Fuel Tank Pressure (FTP) sensor indicates a vacuum level is then the fail counter is incremented.	<p>10 seconds,</p> <p>< -3,238 Pa</p>	<p>Min baro Max baro Min OAT Max OAT *****</p> <p>Conditions for corrected / estimated ambient temperature using OAT sensor to be valid = TRUE *****</p> <p>Engine RPM to enable Engine RPM to re-enable Engine vac to enable Engine vac to re-enable Engine airflow to enable Engine airflow to re-enable Fuel level Purge flow to enable Purge flow to re-enable Purge DC to enable Purge DC to re-enable Requested purge flow to enable Delivered purge flow to re-enable Delivered purge flow to enable Vehicle not in assembly plant (value must = 0) Engine Running Run/Crank Voltage</p> <p>Purge is enabled</p> <p>Abort Conditions: Refueling request button pressed Device control exceeds</p>	<p>≥ 70 Pa ≤ 110 kPa ≥ 4 °C ≤ 35 °C *****</p> <p>*****</p> <p>1,400 ≤ RPM ≤ 3,400 1,500 ≤ RPM ≤ 3,300 15 kPa ≤ vac ≤ 56 kPa 16 kPa ≤ vac ≤ 54 kPa 5 gps ≤ airflow ≤ 29 gps</p> <p>6 gps ≤ airflow ≤ 27 gps ≤ 90 % ≥ 0.17 gps ≥ 0.18 gps ≥ 14.5 % ≥ 15.5 % ≥ 2.94 % ≥ 2.89 % ≥ 2.06 % 0 ≥ 11.0 volts</p> <p>0.5 seconds</p>	<p>50 failures out of 63 samples</p> <p>Once per trip when Propulsion System Active and Engine On</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>If a passing condition is reached for the P0497 diagnostic there is then a short time delay before starting the P0446 diagnostic. This allows the ELCP switching valve to transition back to the vent position and the vacuum in the fuel tank to return to normal operating levels.</p> <p>After this time delay the FTP sensor is monitored and compared to an upper vacuum threshold and the sample counter begins to increment. If the vacuum in the fuel tank exceeds the threshold then the fail counter increments. If the fail counter reaches its threshold then a fail is reported for P0446. A pass is reported for P0446 if the sample counter reaches its threshold. The diagnostic concludes when either the fail or sample counters reach their threshold calibrations.</p>			<p>Passing DTC's</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>P0497</p> <p>MAP_SensorFA EnginePowerLimited AmbientAirDefault OAT_EstAmbTemp_FA FuelLevelDataFault</p> <p>P0442 P0443 P0449 P0451 P0452 P0453 P0455 P0458 P0459 P0497 P0498 P0499 P145D P145E P2400 P2401 P2402 P2418 P2419 P2420 P2422 P2450 P24B9 P24BA P24BB</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Vent Solenoid Control Open Circuit (ELCP Sealed Fuel System)	P0449	Controller specific output driver circuit diagnoses the vent solenoid low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200\text{ K } \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips Note: In certain controllers P0498 may also set (Vent Solenoid Short to Ground)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Tank Pressure (FTP) Sensor Circuit Performance Diagnostic (ELCP Sealed Fuel System)	P0451	<p>Fuel Tank Pressure (FTP) sensor correlation diagnostic.</p> <p>Propulsion System Off</p> <p>The FTP sensor correlation follows the ELCP pressure sensor correlation diagnostic. For the FTP sensor to ELCP pressure sensor correlation, the ELCP vacuum pump is off, the ELCP switching valve is in the pump position, and the DCV is open.</p> <p>The ELCP switching valve transitions to the pump position with a short delay time before opening the DCV to prevent excessive venting of the fuel tank. There is another short delay time to allow the ELCP pressure sensor to stabilize with the pressure or vacuum in the fuel tank before the FTP sensor correlation is started.</p> <p>In the case where the pressure or vacuum in the fuel tank is beyond the FTP sensor range the correlation check is based on the ELCP</p>	<p>Purge off time</p> <p>After a delay time of and a stabilization time of</p> <p>This section of the diagnostic can both pass and fail</p> <p>IF 1) the FTP sensor reading is and the FTP sensor is in a readable range. OR 2) the ELCP pressure sensor (gauge) reading is and the ELCP pressure sensor indicates that the FTP sensor is in a readable range. THEN If the average difference between the FTP sensor reading and ELCP pressure sensor (gauge) reading is after then a FTP sensor correlation failure has been detected and the DTC fails.</p> <p>This section of the diagnostic can only pass</p> <p>IF 1) the FTP sensor reading</p>	<p>> 5 seconds</p> <p>2 seconds 3 seconds</p> <p>> -4,010 Pa < 3,587 Pa,</p> <p>> -3,736 Pa < 3,313 Pa,</p> <p>> 1,021 Pa 5 seconds</p>	<p>Propulsion System Not Active</p> <p>Propulsion system not active time</p> <p>Distance since assembly plant Drive distance Min baro Max baro Min fuel level Max fuel level ECT Min IAT Max IAT Time since last test when passing P0442/P0455 Time since last test when failing P0442/P0455 *****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery Voltage *****</p> <p>Vehicle speed Vehicle not in assembly plant (value must = 0) Propulsion system not active time Previous propulsion system active time</p> <p>Abort Conditions: Min fuel level slosh</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours ≥ 0 hours *****</p> <p>≥ 10 volts</p> <p>≤ 3 MPH 0 ≥ 0 seconds ≥ 0 seconds</p> <p>≥ 190 %</p>	<p>Once per trip with Propulsion System Not Active, for each required wake-up event</p> <p>Once per trip with Propulsion System Active and Engine On</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>pressure sensor also indicating high pressure or high vacuum in the fuel tank. If both sensors are above their thresholds for a period of time, then a pass is reported for P0451. In this condition, a failure cannot be detected, only a passing decision can be made.</p> <p>In the case where the FTP sensor is in a readable range the correlation check uses an average difference comparison between the FTP sensor and ELCP pressure sensor readings. This logic is also used when the FTP sensor is beyond its range but the ELCP pressure sensor indicates it should be in a readable range. The difference between the two sensor readings is averaged over a time period and then compared to a fail threshold. If the average difference is above the threshold, a fail is reported for P0451. The ELCP EVAP diagnostic test sequence is complete if a failure is detected.</p>	<p>is and the FTP sensor is outside its readable range. AND 2) the ELCP pressure sensor (gauge) reading is and the ELCP pressure sensor indicates that the FTP sensor is outside its readable range. THEN after the correlation is confirmed and the DTC passes.</p>	<p>< -4,010 Pa > 3,587 Pa,</p> <p>< -3,736 Pa > 3,313 Pa,</p> <p>5 seconds</p>	<p>Max fuel level slosh Key up during test Refueling request button pressed Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p> <p>Propulsion System Active and Engine On</p> <p>Min baro Max baro Min OAT Max OAT</p>	<p>≤ 200 %</p> <p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P145D P24B9</p> <p>≥ 70 kPa ≤ 110 kPa ≥ 4 °C ≤ 35 °C</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>Propulsion System On</p> <p>This section describes the correlation diagnostic between the FTP and ELCP pressure sensors when the propulsion system is on. This diagnostic executes once per trip when the engine is running and purge is not enabled. If the engine does not come on during a trip then the FTP sensor correlation diagnostic does not run.</p> <p>This diagnostic follows the similar steps and shares the same calibration values that are used in the FTP sensor correlation diagnostic with propulsion system off.</p> <p>After the enable conditions are met, there is a short delay period before beginning the correlation check. This allows the two pressure sensors to stabilize in the case where purge was active prior. It also allows the DCV and ELCP switch valve to be in there proper states before</p>			<p>*****</p> <p>Conditions for corrected / estimated ambient temperature using OAT sensor to be valid = TRUE</p> <p>*****</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Engine Running Run/Crank Voltage</p> <p>Purge is not enabled</p> <p>*****</p> <p>When FTP sensor is located in the fuel tank then additional conditions</p> <p>Fuel Level</p> <p>No Active DTC's</p> <p>*****</p> <p>Abort Conditions: Refueling request button pressed</p> <p>Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>*****</p> <p>0</p> <p>≥ 11.0 volts</p> <p>*****</p> <p>Section does not apply</p> <p>≤ 90.0 %</p> <p>FuelLevelDataFault</p> <p>*****</p> <p>0.5 seconds</p> <p>MAP_SensorFA EnginePowerLimited AmbientAirDefault OAT_EstAmbTemp_FA</p> <p>P0442 P0443 P0449 P0452 P0453 P0455</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>beginning.</p> <p>Following this delay period, the ELCP switching valve is moved to the pump position. There is a short delay time before opening the DCV to prevent excessive venting of the fuel tank. There is another short delay time to allow the ELCP pressure sensor to stabilize with the fuel tank before the correlation diagnostic is started.</p> <p>In the case where the pressure or vacuum in the fuel tank is beyond the FTP sensor range, the correlation diagnostic is based on the ELCP pressure sensor also indicating high pressure or vacuum in the fuel tank. If both sensors are above their corresponding thresholds for a period of time then a pass is reported for P0451. In this condition a failure cannot be detected, only a passing decision can be made.</p> <p>In the case where the FTP sensor is in a</p>				P0458 P0459 P0498 P0499 P145D P145E P2400 P2401 P2402 P2418 P2419 P2420 P2422 P2450 P24B9 P24BA P24BB		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		readable range, the correlation diagnostic uses an average difference comparison between the reading of the FTP and ELCP pressure sensors. This logic is also used when the FTP sensor is beyond its range but the ELCP pressure sensor indicates that it should be in a readable range. The difference between the two sensor readings is averaged over a time period and then compared to a fail threshold. If the average difference is above the fail threshold then a failure is reported for P0451.						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Tank Pressure (FTP) Sensor Circuit Low Voltage (ELCP Sealed/Vented Fuel System)	P0452	<p>This DTC will detect a Fuel Tank Pressure (FTP) sensor signal that is too low out of range.</p> <p>The FTP sensor circuit out of range diagnostic compares the raw sensor voltage to a lower voltage threshold. It is an X out of Y diagnostic that runs continuously anytime the controller is awake.</p> <p>If the sensor voltage is below the lower voltage threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported for P0452 DTC. A pass is reported for P0452 DTC if the low sample counter reaches its threshold.</p>	<p>FTP sensor signal</p> <p>The normal operating range of the FTP sensor is 0.5 volts (~ -3757 Pa) to 4.5 volts (~ 3329 Pa).</p>	< 0.15 volts (3.0 % of Vref or ~ -4,111 Pa)			<p>640 failures out of 800 samples</p> <p>12.5 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Tank Pressure (FTP) Sensor Circuit High Voltage (ELCP Sealed/Vented Fuel System)	P0453	<p>This DTC will detect a Fuel Tank Pressure (FTP) sensor signal that is too high out of range.</p> <p>The FTP sensor circuit out of range diagnostic compares the raw sensor voltage to an upper voltage threshold. It is an X out of Y diagnostic that runs continuously anytime the controller is awake.</p> <p>If the sensor voltage is above the upper voltage threshold, the high fail counter then increments. If the high fail counter reaches its threshold then a fail is reported for P0453 DTC. A pass is reported for P0453 DTC if the high sample counter reaches its threshold.</p>	<p>FTP sensor signal</p> <p>The normal operating range of the FTP sensor is 0.5 volts (~ -3757 Pa) to 4.5 volts (~ 3329 Pa).</p>	> 4.85 volts (97.0 % of Vref or ~ 3,684 Pa)			<p>640 failures out of 800 samples</p> <p>12.5 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EVAP System Large Leak Detected (ELCP Sealed Fuel System)	P0455	A large leak (> 0.020 ") is detected in the EVAP system between the fuel cap, purge solenoid, and diurnal control valve (DCV) after a refueling event has been detected. The ELCP vacuum pump creates a vacuum across a 0.020" reference orifice. This reference vacuum is then compared to the vacuum level created in the fuel tank to determine if a leak exists. The diagnostic has fast pass capability. If the Fuel Tank Pressure (FTP) sensor measures a fuel tank system pressure greater than 1,276 Pa or a fuel tank system vacuum greater than -1,278 Pa then both the small leak and large leak diagnostics pass without using the ELCP vacuum pump. The Fast Pass Full Test Sequence is conducted on the 0th consecutive fast pass. All other times, the Fast Pass Reduced Test Sequence is conducted to conserve battery state of charge. The Fast Pass Reduced	After a refueling event has been detected and the small/large leak diagnostics have not passed. A refueling event is detected when there is a fuel level increase $\geq 10\%$ for ≥ 5 seconds. If the ELCP pressure sensor (gauge) vacuum reading is less than the 2nd 0.020" reference orifice vacuum measurement times a for then the fuel tank system has a large leak and the DTC fails.	0.20 multiplier 400 seconds	Propulsion system not active time Distance since assembly plant Drive distance Min baro Max baro Min fuel level Max fuel level ECT Min IAT Max IAT Time since last test when passing P0442/P0455 Time since last test when failing P0442/P0455 ***** ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery Voltage ***** Vehicle speed Vehicle not in assembly plant (value must = 0) Propulsion system not active time Previous propulsion system active time Refueling request active true Abort Conditions: Min fuel level slosh	4.3 \leq time \leq 5.8 hours or 6.0 \leq time \leq 8.1 hours or 8.2 \leq time \leq 11.0 hours ≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa $\geq 10\%$ $\leq 90\%$ ≤ 40 °C ≥ 4 °C ≤ 45 °C ≥ 0 hours ≥ 0 hours ***** ≥ 10 volts ***** ≤ 3 MPH 0 ≥ 0 seconds ≥ 0 seconds $\geq 190\%$	Once per trip after a refueling event has been detected, for each required wake-up event 100 msec loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>Test Sequence includes the following diagnostics: ELCP Pump Stuck On (P145D), ELCP Sensor Performance (P1458), FTP Sensor Performance (P0451), DCV Stuck Closed (P2422), DCV Stuck Open (P2421), Small Leak (P0442) and Large Leak (P0455) diagnostics.</p> <p>Additional Information</p> <p>The large leak diagnostic (P0455) can only be used on fuel systems with fuel caps. The large leak diagnostic (P0455) occurs at the same time the small leak diagnostic evaluation is being done and uses the same EVAP leak check vacuum result. If the small leak diagnostic result is in a passing condition then the large leak diagnostic is also considered passing. The large leak diagnostic can only fail if a prior refueling event was detected.</p> <p>If a prior refueling event was detected and the</p>			<p>Max fuel level slosh Key up during test Refueling request button pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>≤ 200 %</p> <p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145D P145E P145F P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>EVAP leak check vacuum result did not reach the 2nd reference vacuum measurement then the large leak diagnostic failure condition is evaluated. The large leak diagnostic pass/fail decision is then based on comparing the EVAP leak check vacuum result to the large leak threshold.</p> <p>The large leak threshold is calculated by applying a factor to the 2nd reference vacuum measurement. If the EVAP leak check vacuum result is less than the large leak threshold then P0455 is considered failing. The large leak diagnostic will be considered passing if the EVAP leak check vacuum result is greater than or equal to the large leak threshold.</p> <p>As with the small leak diagnostic, the DTC reporting for the large leak diagnostic does not occur until the rest of the sections (2nd reference orifice check and final check sections) successfully</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>complete. Until this occurs, results are temporary stored in VeELCR_e_LargeLeak Fault.</p> <p>With the ELCP leak check hardware it is difficult to distinguish between leak sizes greater than 0.040". A 0.040" leak will generate a vacuum result around 7-12% of the 1st reference vacuum measurement. A 0.090" leak will generate a vacuum result around 0-4% of the 1st reference vacuum measurement.</p> <p>Based on an agreement with CARB, the large leak diagnostic will only be used when a prior refueling event has occurred. The most likely time the fuel cap will be loose or left off is after a refueling event. The large leak diagnostic also has the CARB approved capability of extinguishing the MIL after 1 pass since the "tighten fuel cap" message is supported.</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Purge Control Valve Circuit Low (ELCP Sealed/ Vented Fuel System)	P0458	Controller specific output driver circuit diagnoses the canister purge solenoid low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 0.5 \Omega$ impedance between output and controller ground	Powertrain relay voltage	Voltage \geq 11.0 volts	20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips Note: In certain controllers P0443 may also set (Canister Purge Solenoid Open Circuit)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Purge Control Valve Circuit High (ELCP Sealed/ Vented Fuel System)	P0459	Controller specific output driver circuit diagnoses the canister purge solenoid low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	$\leq 0.5 \Omega$ impedance between output and controller power	Powertrain relay voltage	Voltage ≥ 11.0 volts	20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 1 Performance (For use on vehicles with a single fuel tank)	P0461	This DTC will detect a primary fuel tank level sensor stuck in-range.	a) Sensed fuel volume change is b) while engine fuel consumption is	a) <3 liters b) >= 15.70 liters	1. Diagnostic Enabled 2. Engine Operational State	1. == True 2. == Running	250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 1 Circuit Low Voltage	P0462	This DTC will detect a primary fuel tank sensor stuck out-of-range low.	Fuel level Sender % of 5V range	< 10 % or 33.11 liters	a) Diagnostic enabled status b) Fuel Level Sensor Initialized status c) Fuel Level Sensor Data Available Status d) Communication faults status	a) == True b) == True c) == True d) <> True	100 failures out of 125 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 1 Circuit High Voltage	P0463	This DTC will detect a primary fuel tank level sensor stuck out-of-range high.	Fuel level Sender % of 5V range	> 60 % or 1.88 liters	a) Diagnostic enabled status b) Fuel Level Sensor Initialized status c) Fuel Level Sensor Data Available Status d) Communication faults status	a) == True b) == True c) == True d) <> True	100 failures out of 125 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Solenoid Circuit Low	P0489	This DTC checks the EGR circuit for electrical shorts to ground.	<p>The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match by monitoring the PWM voltage sent to the EGR Valve.</p> <p>If the PWM voltage is pulled down below an allowed operating threshold the circuit is determined to be shorted to ground : LSO</p>	< 0.15 volts (3.0 % of Vref (5V)	<p>System supply voltage</p> <p>Output driver is commanded on</p> <p>Ignition switch is in crank or run position</p>	> 11.00 Volts	100.00 failures out of 120.00 samples 250 ms / sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Solenoid Circuit High	P0490	This DTC checks the EGR circuit for electrical shorts to high voltage.	<p>The ECM detects that the commanded state of the driver and the actual state of the control circuit do not match by monitoring the PWM voltage sent to the EGR Valve.</p> <p>If the PWM voltage is pulled up above an allowed operating threshold the circuit is determined to be shorted to power : LSO</p>	> 4.85 volts (97.0% of Vref (5 V)	<p>System supply voltage</p> <p>Output driver is commanded on</p> <p>Ignition switch is in crank or run position</p>	> 11.00 Volts	<p>100.00 failures out of 120.00 samples</p> <p>250 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Low Purge Flow Diagnostic (ELCP Sealed Fuel System)	P0497	<p>Low purge flow is detected.</p> <p>This diagnostic is executed once per trip when the engine is running and purge enabled. Various parameters are monitored and compared to hysteresis thresholds so that the diagnostic can be run in a reliable purge flow region.</p> <p>In certain conditions, the purge low flow diagnostic has the ability to extinguish the MIL after only 1 pass. This is allowed under the following conditions, the first failure occurs after a refueling event and the MIL was not already on for P0497. This is the likely scenario where the customer left the fuel cap off after the refuel event, failed the purge low flow diagnostic, and later put the fuel cap back on.</p> <p>Note: The MIL not on condition is based on agreements with CARB. If the MIL was</p>	<p>After an initial time delay of</p> <p>when the Fuel Tank Pressure (FTP) sensor reading is</p> <p>or after an initial time delay of</p> <p>when the FTP sensor reading is</p> <p>plus an ELCP switching valve delay time of</p> <p>if the ELCP pressure sensor (gauge) indicates a vacuum change for</p> <p>then a low purge flow failure has been detected and the DTC fails.</p>	<p>3 seconds</p> <p>≥ 299 Pa</p> <p>3 seconds</p> <p>< 299 Pa</p> <p>0.2 seconds,</p> <p>< 2,000 Pa</p> <p>20 seconds</p>	<p>Min baro</p> <p>Max baro</p> <p>Min OAT</p> <p>Max OAT</p> <p>*****</p> <p>Conditions for corrected / estimated ambient temperature using OAT sensor to be valid = TRUE</p> <p>*****</p> <p>Engine RPM to enable</p> <p>Engine RPM to re-enable</p> <p>Engine vac to enable</p> <p>Engine vac to re-enable</p> <p>Engine airflow to enable</p> <p>Engine airflow to re-enable</p> <p>Fuel level</p> <p>Purge flow to enable</p> <p>Purge flow to re-enable</p> <p>Purge DC to enable</p> <p>Purge DC to re-enable</p> <p>Requested purge flow to enable</p> <p>Delivered purge flow to re-enable</p> <p>Delivered purge flow to enable</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Engine Running</p> <p>Run/Crank Voltage</p> <p>Purge is enabled</p> <p>Abort Conditions: Refueling request button pressed</p>	<p>≥ 70 kPa</p> <p>≤ 110 kPa</p> <p>≥ 4 °C</p> <p>≤ 35 °C</p> <p>*****</p> <p>1,400 ≤ RPM ≤ 3,400</p> <p>1,500 ≤ RPM ≤ 3,300</p> <p>15 kPa ≤ vac ≤ 56 kPa</p> <p>16 kPa ≤ vac ≤ 54 kPa</p> <p>5 gps ≤ airflow ≤ 29 gps</p> <p>6 gps ≤ airflow ≤ 27 gps</p> <p>≤ 90 %</p> <p>≥ 0.17 gps</p> <p>≥ 0.18 gps</p> <p>≥ 14.5 %</p> <p>≥ 15.5 %</p> <p>≥ 2.94 %</p> <p>≥ 2.89 %</p> <p>≥ 2.06 %</p> <p>0</p> <p>≥ 11.0 volts</p>	<p>Once per trip with Propulsion System Active and Engine On</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>turned on not due to a refueling event, then the 3 pass MIL off rule needs to be maintained until the MIL is extinguished.</p> <p>If the first failure did not occur after a refueling event or the MIL was already on for P0497, then 3 passes are needed to extinguish the MIL. Using the 1 or 3 pass MIL off is a calibration option. On capless fuel systems, 3 passes are always needed to extinguish the MIL</p> <p>The diagnostic is enabled when the thresholds for requested purge flow, engine RPM, engine airflow, and engine vacuum are met. When these conditions are satisfied then purge priority along with a maximum purge duty cycle value is requested. Once purge priority is granted, an engine vacuum request is made. The ECM communicates with the hybrid controller which allows the engine to operate in a condition that produces the</p>			<p>Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>MAP_SensorFA EnginePowerLimited AmbientAirDefault OAT_EstAmbTemp_FA FuelLevelDataFault</p> <p>P0442 P0443 P0449 P0451 P0452 P0453 P0455 P0458 P0459 P0498 P0499 P145D P145E P2400 P2401 P2402 P2418 P2419 P2420 P2422 P2450 P24B9 P24BA P24BB</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>minimum desired vacuum level.</p> <p>Once the vacuum request is made, various parameters (which include delivered purge flow, engine RPM, engine airflow, engine vacuum, unfiltered purge flow, and purge duty cycle) are monitored for proper purge flow and operating conditions.</p> <p>If those conditions are lost for a period of time greater than a threshold then purge priority is released. Purge priority will not be requested again until a period of time greater than threshold has elapsed. This allows other diagnostics the opportunity to run. The engine vacuum request is also limited to a maximum time per trip. It is a cumulative timer and once the threshold is reached the request will be cancelled and not requested again for the remainder of the trip.</p> <p>If the operating conditions are met</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>there is then a period of time to allow pressure or vacuum in the fuel tank to reach normal operating levels with purge enabled. This time period is based on whether there is pressure or vacuum in the fuel tank initially as indicated by the FTP sensor.</p> <p>If there is vacuum in the fuel tank then the DCV will already be open and this stabilization period will allow for high levels of vacuum to bleed down before starting the purge flow check. If there is pressure in the fuel tank then the DCV will be closed and this stabilization period will allow time to purge the fuel tank of pressure before opening the DCV. After the pressure stabilization period ends, the DCV will be commanded open to run the purge flow check even if there is still pressure in the fuel tank.</p> <p>There is a calibratable option that prevents autostop and DFCO from occurring above a</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>vehicle speed once the stabilization period is complete. If the vehicle speed drops below this calibration then autostop and DFCO are allowed. Using this option may provide more opportunity to complete the diagnostic quicker.</p> <p>When the stabilization period is complete, the ELCP switching valve is moved to the pump position allowing the ELCP pressure sensor to have communication with the fuel tank. A short time later a reading from the ELCP pressure sensor is taken which represents the initial pressure value.</p> <p>The ELCP pressure sensor is then continuously monitored and compared to the initial pressure value. If the difference is greater than a threshold calibration then purge flow is considered to be present and the ELCP switching valve is moved to the vent position.</p> <p>A pass for P0497 is not</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>reported at this time; the engine vacuum request remains active and the operating conditions are monitored until the test timer reaches the fail time threshold calibration.</p> <p>Once the fail time threshold is reached a pass is reported for P0497 and the purge priority and engine vacuum request are released. If the vacuum difference was not achieved within the fail time then a fail is reported for P0497 indicating no purge flow present.</p> <p>The purge priority and engine vacuum request are released once the purge low flow diagnostic and vent restriction diagnostic are complete.</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Vent Solenoid Control Circuit Low (ELCP Sealed Fuel System)	P0498	Controller specific output driver circuit diagnoses the vent solenoid low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 0.5 \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips Note: In certain controllers P0449 may also set (Vent Solenoid Open Circuit)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Vent Solenoid Control Circuit High (ELCP Sealed Fuel System)	P0499	<p>Controller specific output driver circuit diagnoses the vent solenoid low sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>If the P0499 is active, an intrusive test is performed with the vent solenoid commanded closed for 15 seconds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between output and controller power			<p>20 failures out of 25 samples</p> <p>250 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cold Start Rough Idle	P050D	Monitors the combustion performance when the cold start emission reduction strategy is active by accumulating and determining the percentage of engine cycles that have less than complete combustion relative to the total number of engine cycles in which Dual Pulse is active.	<p>Deceleration index vs. Engine Speed Vs Engine load</p> <p>Deceleration index calculation is tailored to specific vehicle. Tables used are 1st tables encountered that are not max of range. Undetectable region at a given speed/load point is where all tables are max of range point.</p> <p>Incomplete combustion identified by P0300 threshold tables:</p>	<p>(>Idle SCD AND >Idle SCD ddt Tables) OR (>Idle Cyl Mode AND > Idle Cyl Mode ddt Tables)</p>	<p>Misfire Algorithm Enabled (Refer to P0300 for Enablement Requirements)</p> <p>OBD Manufacturer Enable Counter</p> <p>To enable the diagnostic, the Cold Start Emission Reduction Strategy Must Be Active per the following:</p> <p>Catalyst Temperature AND Engine Coolant AND Engine Coolant AND Barometric Pressure</p> <p>In addition, Dual Pulse Strategy Is Enabled and Active Per the following:</p> <p>Engine Speed</p> <p>Accel Position</p> <p>Engine Run Time</p> <p>For the engine speeds and loads in which Dual Pulse is active:</p>	<p>= 0</p> <p>< 350.00 degC > -12.00 degC <= 66.00 degC >= 76.00 KPa</p> <p>>= 450.00 RPM <= 2,200.00 RPM</p> <p><= 110.00 Pct</p> <p>< 30 seconds</p>	<p>Runs once per trip when the cold start emission reduction strategy is active and Dual Pulse is enabled and active.</p> <p>Frequency: 100ms</p> <p>Test completes after Dual Pulse is no longer active OR The first 500 engine cycles have been reached</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Dual Pulse Error induced misfires percentage</p> <p>Dual Pulse Error induced misfires percentage</p> <p>Engine Cycles</p> <p>The Cold Start Emission Reduction strategy must not be exiting. The strategy will exit per the following:</p> <p>Catalyst Temperature AND Engine Run Time</p> <p>OR</p> <p>Engine Run Time</p> <p>OR</p> <p>Barometric Pressure</p>	<p>>= catalyst damaging misfire</p> <p>< 90% of the maximum achievable catalyst damaging misfire.</p> <p>>= 50 < 501</p> <p>>= 900.00 degC >= 30.00 seconds</p> <p>></p> <p>P050D_P1400_CatalystLightOffExtendedEngineRunTimeExit</p> <p>This Extended Engine run time exit table is a function of percent ethanol and Catmons NormRatioEWMA. Refer to "Supporting Tables" for details.</p> <p>< 76.00 KPa</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Dual Pulse Strategy will exit per the following:</p> <p>Engine Speed OR Accel Position Engine Run Time</p> <p>Dual Pulse Strategy will also exit if the any of the "Additional Dual Pulse Enabling Criteria" is not satisfied:</p> <p>"Additional Dual Pulse Enabling Criteria":</p> <p>Green Engine Enrichment</p> <p>Misfire Converter Protection strategy</p> <p>Engine Metal Overtemp strategy</p> <p>Fuel control state</p> <p>Output State Control</p> <p>DOD Or DFCO</p> <p>Power Enrichment</p> <p>Dynamic Power Enrichment</p> <p>Piston Protection</p> <p>Hot Coolant Enrichment</p>	<p>> 2,400.00 RPM</p> <p>> 110.00 Pct</p> <p>>= 30 seconds</p> <p>Not Enabled</p> <p>Not being requested</p> <p>Not being requested</p> <p>Open Loop</p> <p>Not being requested for fuel</p> <p>Not Active</p> <p>Not Active</p> <p>Not Active</p> <p>Not Active</p> <p>Not Active</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Injector Flow Test General Enable DTC's Not Set:	Not Active AcceleratorPedalFailure ECT_Sensor_FA IAT_SensorCircuitFA MnfdTempSensorCktFA CrankSensor_FA FuelInjectorCircuit_FA MAF_SensorFA MAP_SensorFA AnyCamPhaser_TFTKO ClutchPstnSnsr FA IAC_SystemRPM_FA IgnitionOutputDriver_FA TPS_FA VehicleSpeedSensor_FA FuelInjectorCircuit_TFTKO FHPR_b_FRP_SnsrCkt_FA FHPR_b_FRP_SnsrCkt_TFTKO FHPR_b_PumpCkt_FA FHPR_b_PumpCkt_TFTKO TransmissionEngagedState_FA EngineTorqueEstInaccuracy FuelPumpRlyCktFA		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Oil Pressure (EOP) Sensor Performance - Two Stage Oil Pump	P0521	<p>Determines if the Engine Oil Pressure (EOP) Sensor is stuck or biased in range. The engine oil pressure is compared against thresholds when engine is running and when engine is off. The engine oil pressure rationality diagnostic has two parts: engine running test and engine off test.</p> <p>The engine running test compares the measured oil pressure to threshold. If the measured oil pressure is out of the thresholds, then the error counter increments. The engine off test compares the measured oil pressure against thresholds after the engine has stopped rotating. If the measured oil pressure is out of the thresholds, then the error counter increments.</p>	<p>Two Stage Oil Pump EOP Sensor Test with Engine Running</p> <p>If enabled:</p> <p><u>To Fail when previously passing with the engine running:</u></p> <p>Filtered Engine Oil Pressure below expected threshold</p> <p>OR</p> <p>Filtered Engine Oil Pressure above expected threshold</p> <p><u>To pass when previously failing:</u></p> <p>Filtered Engine Oil Pressure above low threshold plus an offset</p> <p>OR</p>	<p>Filtered Oil Pressure < P0521_LowMinOilPressureFail - Two Stage Oil Pump</p> <p>OR</p> <p>Filtered Oil Pressure > (P0521_P06DD_P06DE_OP_HiStatePressure * 1.25 + 75.0 kPa)</p> <p>Filtered Oil Pressure > (10.0 kPa+ P0521_LowMinOilPressureFail - Two Stage Oil Pump)</p> <p>OR</p>	<p>Two Stage Oil Pump is Present = TRUE</p> <p>Engine Running Diagnostic Status</p> <p>Engine Off Rationality Test Diagnostic Reporting Status</p> <p>Oil Pressure Sensor In Use</p> <p>Engine Running</p> <p>Ambient Air Pressure</p> <p>Oil Aeration (= TRUE if engine speed > 10,000 RPM for longer than 30.0 seconds)</p> <p>Filtered Engine Speed within range</p> <p>Modelled Oil Temperature within range</p> <p>No active DTC's</p>	<p>TRUE</p> <p>Enabled</p> <p>Test not report a fail state</p> <p>Yes</p> <p>≥ 10.0 seconds</p> <p>≥ 70.0 kPa</p> <p>FALSE</p> <p>1,000 RPM ≤ Filtered Engine Speed ≤ 4,500 RPM</p> <p>40.0 deg C ≤ Oil Temp ≤ 120.0 deg C</p> <p>Fault bundles: MAF_SensorFA ECT_Sensor_FA IAT_SensorFA EngOilPressureSensorCkt FA AmbientAirDefault EngOilTempFA CrankSensor_FA</p>	<p>≥ 40 errors out of 50 samples.</p> <p>Performed every 100 msec</p> <p>≥ 10 passes out of 50 samples.</p> <p>Performed every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Filtered Engine Oil Pressure below high threshold minus an offset	Filtered Oil Pressure < (P0521_P06DD_P06DE_OP_HiStatePressure * 1.25 + 75.0 kPa) - 10.0 kPa (Details on Supporting Tables Tab: P0521_LowMinOilPressureFail - Two Stage Oil Pump P0521_P06DD_P06DE_OP_HiStatePressure)				
			Two Stage Oil Pump EOP Sensor Test with Engine Off If enabled: <u>To Fail when previously passing with the engine off:</u> Filtered Engine Oil Pressure greater than threshold	Filtered Oil Pressure ≥ 40.0 kPa	Two Stage Oil Pump is Present = TRUE Engine Off Rationality Test Diagnostic Status Engine Running Rationality Test Diagnostic Status Modelled Oil Temperature No Engine Movement No active DTC's	TRUE Enabled Test not report a fail state ≥ 70.0 deg C > 10.0 seconds EngineModeNotRunTimer_FA EngOilTempFA EngOilPressureSensorCktFA CrankSensor_FA	≥ 20 errors out of 40 samples. Run once per trip	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Oil Pressure (EOP) Sensor Circuit Low Voltage	P0522	Determines if the Engine Oil Pressure (EOP) Sensor circuit voltage is too low. This diagnostic compares the EOP circuit voltage to the reference voltage.	(Engine Oil Pressure Sensor Circuit Voltage) ÷ 5 Volts) *100	<p>< 5.00 percent</p> <p>Deadband: < 5 percent or > 95 percent</p>	<p>Engine Speed Enable Engine Speed Disable</p> <p>Oil Pressure Sensor In Use</p> <p>Diagnostic Status</p>	<p>> 400 rpm < 350 rpm</p> <p>Yes</p> <p>Enabled</p>	<p>800 failures out of 1,000 samples</p> <p>Performed every 6.25 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Oil Pressure (EOP) Sensor Circuit High Voltage	P0523	Determines if the Engine Oil Pressure (EOP) Sensor circuit voltage is too high. This diagnostic compares the EOP circuit voltage to the reference voltage.	(Engine Oil Pressure Sensor Circuit Voltage) ÷ 5 Volts) *100	> 95.00 percent Deadband: < 5 percent or > 95 percent	Oil Pressure Sensor In Use Diagnostic Status	Yes Enabled	800 failures out of 1,000 samples Performed every 6.25 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Air Conditioning High Side Pressure Sensor (HSPS) Circuit Low Voltage	P0532	Determines if the Air Conditioning High Side Pressure Sensor circuit voltage is too low	(AC High Side Pressure Sensor Circuit Voltage) ÷ 5 Volts) *100	< 3 percent	AC HSP Sensor Present Diagnostic Status	Yes Enabled	80 failures out of 100 samples Performed every 25 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Air Conditioning High Side Pressure Sensor (HSPS) Circuit High Voltage	P0533	Determines if the Air Conditioning High Side Pressure Sensor circuit voltage is too high	(AC High Side Pressure Sensor Circuit Voltage) ÷ 5 Volts) *100	> 94 percent	AC HSP Sensor Present Diagnostic Status	Yes Enabled	80 failures out of 100 samples Performed every 25 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Mutil- Functon Switch Circuit	P0564	Detect when cruise control multi-function switch circuit (analog) voltage is in an invalid range	Cruise Control analog circuit voltage must be "between ranges" for greater than a calibratable period of time.	The cruise control analog voltage A/D count ratio is considered to be "between ranges" when the ratio is measured in the following ranges: 0.28 -0.31, 0.415-0.445, 0.585 - 0.615 0.78 - 0.81, 1.005 - 1.035	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 0.500 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control On Switch Circuit	P0565	Detects a failure of the cruise on/off switch in a continuously applied state	Cruise Control On switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 20.00 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 20.00 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Resume Circuit	P0567	Detects a failure of the cruise resume switch in a continuously applied state	Cruise Control Resume switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 89.000 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 89.000 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Set Circuit	P0568	Detects a failure of the cruise set switch in a continuously applied state	Cruise Control Set switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 89.000 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 89.000 seconds	Type C, No SVS, Emissions Neutral Diagnostics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Cancel Switch Circuit	P056C	Detects a failure of the cruise cancel switch in a continuously applied state	Cruise Control Cancel switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 20.00 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 20.00 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Input Circuit	P0575	Determines if cruise switch state received from the BCM is valid.	If x of y rolling count / protection value faults occur, disable cruise for duration of fault	Message <> 2's complement of message Message rolldng count<>previous message rolling count value plus one	Cruise Control Switch Serial Data Error Diagnostic Enable Serial communication to BCM Power Mode Engine Running	1.00 No loss of communication = RUN = TRUE	9 failures out of /17 samples Performed on every received message 9 rolling count failures out of /17 samples Performed on every received messagw	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake Pedal Position Sensor Circuit Range/ Performance	P057B	This diagnostic monitors the Brake Pedal Position Sensor for a stuck in range failure	.Brake pedal position sensor movement diagnostic cal is enabled 1.00	True	Brake Pedal Position Sensor Circuit Range / Performance Diagnostic Enable	1.00 ignition voltage > 10.00		MIL: Type A, 1 Trips
			Calculated EWMA value must be greater than calibratable threshold after calibratable number of tests have completed to report a "test passed" for P057B	EWMA value looked up in supporting table P057B KtBRKI_K_FastTestPointWeight P057B as a function of calculated brake pedal position delta EWMA value is > 0.80	calculated brake pedal position delta sample counter > 50.00 for fast test OR calculated brake pedal position delta sample counter > 1,000.00 for slow test	calculated brake pedal position delta > 5.00 OR (for slow test) shift lever has been in park once this key cycle vehicle speed >= 5.00 accelerator pedal position < 5.00	total number of EWMA tests > 20.00	
			Calculated EWMA Value must be less than calibratable threshold after calibratable number of tests have completed to report a "test failed" for P057B. This test runs once per key cycle	EWMA value looked up in supporting table P057B KtBRKI_K_CmpltTestPointWeight P057B as a function of calculated brake pedal position delta EWMA value is less than 0.40	no DTC's active (P057C, P057D)	shift lever has been in park once this key cycle vehicle speed >= 5.00 accelerator pedal position < 5.00	total number of EWMA tests > 2.00	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake Pedal Position Sensor Circuit Low	P057C	detects short to ground for brake pedal position sensor	If x of y samples are observed below failure threshold, default brake pedal position to zero percent.	5.00	Brake Pedal Position Sensore Low Voltage Diagnostic Enable	1.00	20 / 32.00 counts	MIL: Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake Pedal Position Sensor Circuit High	P057D	detects open circuit for brake pedal position sensor	If x of y samples are observed above failure threshold, default brake pedal position to zero percent and set DTC	95.00	Brake Pedal Position Sensore High Voltage Diagnostic Enable	1.00	20.00 / 32.00 counts	MIL: Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake Pedal Position Sensor Circuit Intermittent/ Erratic	P057E	detects noisy / erratic output for brake pedal position sensor	If x of y samples are observed above failure threshold, default brake pedal position to zero percent and set DTC	20.00	Brake Pedal Position Sensor Circuit Intermittent / Erratic Diagnostic Enable	1.00	5.00 / 20.00 counts	MIL: Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Multi- function Circuit Low Voltage	P0580	detects short to ground failure for cruise multi- function switch circuit	Cruise Control analog circuit voltage must be in an "Open Short To Ground" range for greater than a calibratable period of time.	The cruise control analog voltage A/D count ratio is considered to be "open short to ground when the ratio is measured in the following ranges: 0 - 0.185	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 2.00 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Multi- function Circuit High Voltage	P0581	detects short to power failure for cruise multi- function switch circuit	Cruise Control analog circuit voltage must be in "Short To Power" range for greater than a calibratable period of time.	The cruise control analog voltage A/D count ratio is considered to be "short to power" when the ratio is measured in the following range: 1.005 - 1.035	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 2.00 seconds	Type C, No SVS ,Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Thermostat Heater Control Open Circuit	P0597	Controller specific output driver circuit diagnoses the Thermostat Heater Control sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground.	<p>Run Crank Ignition in Range</p> <p>Engine not cranking Run Crank active</p> <p>== Above is true and ==</p> <p>Last Open Circuit Test</p>	<p>= True</p> <p>= True = True</p> <p>=====</p> <p>= not Indeterminate</p>	<p>5 failures out of 6 samples</p> <p>1 sec/ sample</p> <p>Continuous</p>	Type B, 2 Trips Note: In certian controllers P0598 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Thermostat Heater Control Circuit Low	P0598	Controller specific output driver circuit diagnoses the Thermostat Heater low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	$\leq 0.5 \Omega$ impedance between signal and controller ground	<p>Run Crank Ignition in Range</p> <p>Engine not cranking Run Crank active</p> <p>== Above is true and ==</p> <p>Last Ground Short Circuit Test</p>	<p>= True</p> <p>= True</p> <p>= True</p> <p>=====</p> <p>= not Indeterminate</p>	<p>5 failures out of 6 samples</p> <p>1 sec/ sample</p> <p>Continuous</p>	Type B, 2 Trips Note: In certian controllers P0597 may also set

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Thermostat Heater Control Circuit High	P0599	Controller specific output driver circuit diagnoses the Thermostat Heater low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between signal and controller power.	<p>Run Crank Ignition in Range</p> <p>Engine not cranking Run Crank active</p> <p>== Above is true and ==</p> <p>Last Power Short Circuit Test</p>	<p>= True</p> <p>= True = True</p> <p>=====</p> <p>= not Indeterminate</p>	<p>5 failures out of 6 samples</p> <p>1 sec/ sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Active Grill Air Shutter A Performance /Stuck OFF	P059F	A 2-part diagnostic. Part 1 continuously monitors for failure to achieve a commanded shutter actuator position [Suspect Stuck Condition] when X failures occur in Y samples after an electronic command latency delay. Part 1 failure enables Part 2 which makes a fixed number of repeat attempts to reach the commanded position [Retry to clear obstruction]. The DTC is set when the calibrated fault threshold count of repeat attempts is reached without achieving the original commanded shutter position.	Smart Shutter Actuator 1 Position Response	<> Smart Shutter Actuator 1 Commanded Position percent	a. Ignition Run_Crank Active, b. Ignition Run_Crank AND Ignition Accessory AND ECU Awake, c. Command Shutter1 Enable	a. = TRUE, b. = FALSE AND = FALSE AND = TRUE, c. = 1.00	1.00 failures out of 1.00 samples 1 sample / 100 milliseconds	Type B, 2 Trips
			AND Shutter 1 Diagnostic Delay Threshold count	AND Counter > 99.00 counts				
			Shutter 1 Performance Test count	= 5.00 counts	a. Ignition Run_Crank Active, b. Ignition Run_Crank AND Ignition Accessory AND ECU Awake, c. Command Shutter1 Enable	a. = TRUE, b. = FALSE AND = FALSE AND = TRUE, c. = 1.00	1-5 actuator cycles [1 cycle typically requires 10-25 seconds]	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Read Only Memory (ROM)	P0601	This DTC will be stored if the calibration check sum is incorrect or the flash memory detects an uncorrectable error via the Error Correcting Code.	The Primary Processor's calculated checksum does not match the stored checksum value. Covers all software and calibrations.	1 failure if the fault is detected during the first pass. 5.00 failures if the fault occurs after the first pass is complete.			Diagnostic runs continuously in the background.	Type A, 1 Trips
			The Primary Processor's Error Correcting Code hardware in the flash memory detects an error. Covers all software and calibrations.	254 failures detected via Error Correcting Code			Diagnostic runs continuously via the flash hardware.	
			The Primary Processor's calculated checksum does not match the stored checksum value for a selected subset of the calibrations.	2 consecutive failures detected or 5 total failures detected.			Diagnostic runs continuously. Will report a detected fault within 200 ms.	
			The Secondary Processor's calculated checksum does not match the stored checksum value. Covers all software and calibrations.	1 failure if the fault is detected during the first pass. 5 failures if the fault occurs after the first pass is complete.			Diagnostic runs continuously in the background.	
				In all cases, the failure count is cleared when controller shuts down				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Not Programmed	P0602	This DTC will be stored if the ECU is a service part that has not been programmed.	Service (reflash) controller calibration present	= 1		none	Diagnostic runs at powerup and once per second continuously after that	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
ECM Long Term Memory Reset	P0603	This DTC detects an invalid NVM which includes a Static NVM, Perserved NVM, ECC ROM in NVM Flash Region, and Perserved NVM during shut down.	Static NVM region error detected during initialization				Diagnostic runs at controller power up.	Type A, 1 Trips
			Perserved NVM region error detected during initialization				Diagnostic runs at controller power up.	
			ECC ROM fault detected in NVM Flash region				Diagnostic runs at controller power up.	
			ECC ROM Error Count >	3				
			Perserved NVM region error detected during shut down.				Diagnostic runs at controller power down.	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
ECM RAM Failure	P0604	Indicates that the ECM has detected a RAM fault. This includes Primary Processor System RAM Fault, Primary Processor Cache RAM Fault, Primary Processor TPU RAM Fault, Primary Processor Update Dual Store RAM Fault, Primary Processor Write Protected RAM Fault, and Secondary Processor RAM Fault. This diagnostic runs continuously.	Indicates that the primary processor is unable to correctly read data from or write data to system RAM. Detects data read does not match data written >=	254 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	Type A, 1 Trips
			Indicates that the primary processor is unable to correctly read data from or write data to cached RAM. Detects data read does not match data written >=	254 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	
			Indicates that the primary processor is unable to correctly read data from or write data to TPU RAM. Detects data read does not match data written >=	5 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	
			Indicates that the primary processor detects a mismatch between the data and dual data is found during RAM updates. Detects a mismatch in data and dual data updates >	0.47856 s			When dual store updates occur.	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Indicates that the primary processor detects an illegal write attempt to protected RAM. Number of illegal writes are >	65,534 counts			Diagnostic runs continuously (background loop)	
			Indicates that the secondary processor is unable to correctly read data from or write data to system RAM. Detects data read does not match data written >=	5 counts			Will finish first memory scan within 30 seconds at all engine conditions - diagnostic runs continuously (background loop)	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal ECM Processor Integrity Fault	P0606	Indicates that the ECM has detected an internal processor integrity fault. These include diagnostics done on the SPI Communication as well as a host of diagnostics for both the primary and secondary processors.	Loss or invalid message of SPI communication from the Secondary Processor at initialization detected by the Primary Processor or loss or invalid message of SPI communication from the Secondary Processor after a valid message was received by the Primary Processor	Loss or invalid message at initialization detected or loss or invalid message after a valid message was received	Run/Crank voltage Run/Crank voltage	>= 6.41 Volts or >= 11.00 Volts, else the failure will be reported for all conditions	In the primary processor, 159 / 399 counts intermittent or 39 counts continuous; 39 counts continuous @ initialization. 12.5 ms /count in the ECM main processor	Type A, 1 Trips
			Loss or invalid message of SPI communication from the Primary Processor at initialization detected by the Secondary Processor or loss or invalid message of SPI communication from the Primary Processor after a valid message was received by the Secondary Processor	Loss or invalid message at initialization detected or loss or invalid message after a valid message was received			In the secondary processor, 20 / 200 counts intermittent or 0.1875 s continuous; 0.4750 s continuous @ initialization. 12.5 ms /count in the ECM secondary processor	
			Checks for stack over or underflow in secondary processor by looking for corruption of known pattern at stack boundaries. Checks number of stack over/under flow since last powerup reset >=	5		KeMEMD_b_StackLimitTestEnbl == 1 Value of KeMEMD_b_StackLimitTestEnbl is: 1. (If 0, this test is disabled)	variable, depends on length of time to corrupt stack	
			MAIN processor is verified by responding to a seed sent from the secondary with a key response to secondary. Checks number of incorrect keys	2 incorrect seeds within 8 messages, 0.2000 seconds		ignition in Run or Crank	150 ms for one seed continually failing	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			received > or Secondary processor has not received a new within time limit					
			Time new seed not received exceeded			always running	0.450 seconds	
			MAIN processor receives seed in wrong order			always running	3 / 17 counts intermittent. 50 ms/count in the ECM main processor	
			2 fails in a row in the Secondary processor's ALU check			KePISD_b_ALU_TestEnbl d == 1 Value of KePISD_b_ALU_TestEnbl d is: 1. (If 0, this test is disabled)	25 ms	
			2 fails in a row in the Secondary processor's configuration register masks versus known good data			KePISD_b_ConfigRegTestEnbl == 1 Value of KePISD_b_ConfigRegTestEnbl is: 1. (If 0, this test is disabled)	12.5 to 25 ms	
			Secondary processor detects an error in the toggling of a hardware discrete line controlled by the MAIN processor: number of discrete changes > = or < = over time window(50ms)	7 17		KePISD_b_MainCPU_SOH_FltEnbl == 1 Value of KePISD_b_MainCPU_SOH_FltEnbl is: 0 (If 0, this test is disabled) time from initialization >= 0.4875 seconds	50 ms	
			Software background task first pass time to complete exceeds			Run/Crank voltage > 6.41	360.000 seconds	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			2 fails in a row in the MAIN processor's ALU check			KePISD_b_ALU_TestEnbl d == 1 Value of KePISD_b_ALU_TestEnbl d is: 1 . (If 0, this test is disabled)	25 ms	
			2 fails in a row in the MAIN processor's configuration register masks versus known good data			KePISD_b_ConfigRegTes tEnbl == 1 Value of KePISD_b_ConfigRegTes tEnbl is: 1 . (If 0, this test is disabled)	12.5 to 25 ms	
			Checks number of stack over/under flow since last powerup reset >=	3		KeMEMD_b_StackLimitTe stEnbl == 1 Value of KeMEMD_b_StackLimitTe stEnbl is: 1 . (If 0, this test is disabled)	variable, depends on length of time to corrupt stack	
			Voltage deviation >	0.4950		KePISD_b_A2D_CnvrtrTe stEnbl == 1 Value of KePISD_b_A2D_CnvrtrTe stEnbl is: 1 . (If 0, this test is disabled)	5 / 10 counts or 0.150 seconds continuous; 50 ms/count in the ECM main processor	
			Checks for ECC (error correcting code) circuit test errors reported by the hardware for flash memory. Increments counter during controller initialization if ECC error occurred since last controller initialization. Counter >=	3 (results in MIL), 5 (results in MIL and remedial action)		KeMEMD_b_FlashECC_ CktTestEnbl == 1 Value of KeMEMD_b_FlashECC_ CktTestEnbl is: 1 . (If 0, this test is disabled)	variable, depends on length of time to access flash with corrupted memory	
			Checks for ECC (error	3 (results in MIL),		KeMEMD_b_RAM_ECC_	variable,	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			correcting code) circuit test errors reported by the hardware for RAM memory circuit. Increments counter during controller initialization if ECC error occurred since last controller initialization. Counter >=	5 (results in MIL and remedial action)		CktTestEnbl == 1 Value of KeMEMD_b_RAM_ECC_CktTestEnbl is: 1. (If 0, this test is disabled)	depends on length of time to write flash to RAM variable, depends on length of time to write flash to RAM	
			MAIN processor DMA transfer from Flash to RAM has 1 failure			KePISD_b_DMA_XferTestEnbld == 1 Value of KePISD_b_DMA_XferTestEnbld is: 0. (If 0, this test is disabled)	variable, depends on length of time to write flash to RAM	
			Safety critical software is not executed in proper order.	>= 1 incorrect sequence.		Table, f(Core, Loop Time). See supporting tables: P0606_Program Sequence Watch Enable f(Core, Loop Time) (If 0, this Loop Time test is disabled)	Fail Table, f(Loop Time). See supporting tables: P0606_PSW Sequence Fail f(Loop Time) / Sample Table, f(Loop Time) See supporting tables: P0606_PSW Sequence Sample f(Loop Time) counts 50 ms/count in the ECM main processor	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			MAIN processor determines a seed has not changed within a specified time period within the 50ms task.	Previous seed value equals current seed value.		KePISD_b_SeedUpdKey StorFltEnbl == 1 Value of KePISD_b_SeedUpdKey StorFltEnbl is: 1 . (If 0, this test is disabled)	Table, f(Loop Time). See supporting tables: P0606_Last Seed Timeout f (Loop Time)	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Relay Control Circuit Open	P0627	Controller specific output driver circuit diagnoses the Feed Fuel Pump Relay high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	≥ 200 KOhms impedance between signal and controller ground.	Run/Crank Voltage Engine Speed	Voltage 11.00 volts 0 RPM	8 failures out of 10 samples 250 ms / sample	Type A, 1 Trips Note: In certain controllers P0629 may also set (Fuel Pump Relay Control Short to Power)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Relay Control Circuit Low Voltage	P0628	Controller specific output driver circuit diagnoses the Feed Fuel Pump Relay high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	<p><= 0.5 Ohms impedance between signal and controller ground</p>	<p>Run/Crank Voltage</p> <p>Engine Speed</p>	<p>Voltage 11.00 volts</p> <p>0 RPM</p>	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Relay Control Circuit High Voltage	P0629	Controller specific output driver circuit diagnoses the Feed Fuel Pump Relay high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	<= 0.5 Ohms impedance between signal and controller power	<p>Run/Crank Voltage</p> <p>Engine Speed</p>	<p>Voltage 11.00 volts</p> <p>0 RPM</p>	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p>	<p>Type A, 1 Trips</p> <p>Note: In certain controllers P0627 may also set (Fuel Pump Relay Control Open Circuit)</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.	
Internal Control Module Fuel Injector Control Performance	P062B	This DTC determines the internal fuel injector control module circuit is faulted. The faulted status is set on any failure that could potentially damage the drivers or injectors, or could result in uncontrolled fueling. The following general classes of failures shall be covered: Communication error with control circuit Internal corruption of control circuit values, Invalid interface values (from control circuit)	Internal ECU Boost Voltage	>= 90 Volts	Battery Voltage	>= 8 or >= 11 Enabled when a code clear is not active or not exiting device control Engine is not cranking Powertrain Relay Voltage within range	High Voltage - 160 failures out of 200 samples	Type A, 1 Trips	
			OR						Low Voltage - 160 failures out of 200 samples
			Internal ECU Boost Voltage	<= 40 Volts					Driver Status Not Ready- 160 failures out of 200 samples
			OR						
			Driver Status	= Not Ready					Driver Status Uninitialized - Uninitialized state for >= 100 counts
			OR						
			Driver Status	= Uninitialized			All at 12.5ms per sample		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Powertrain Internal Control Module EEPROM Error	P062F	This DTC detects a NVM long term performance. There are two types of diagnostics that run during controller power up. One for HWIO reports that writing to NVM (at shutdown) will not succeed, and the other HWIO reports the assembly calibration integrity check has failed.	HWIO reports that writing to NVM (at shutdown) will not succeed				Diagnostic runs at controller power up.	Type B, 2 Trips
			HWIO reports the assembly calibration integrity check has failed				Diagnostic runs at controller power up.	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
VIN Not Programmed or Mismatched - Engine Control Module (ECM)	P0630	This DTC checks that the VIN is correctly written	At least one of the programmed VIN digits	= 00 or FF	OBD Manufacturer Enable Counter	= 0	250 ms / test Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
5 Volt Reference #1 Circuit	P0641	Detects a continuous or intermittent short on the 5 volt reference circuit #1 by monitoring the reference percent Vref1 and failing the diagnostic when the percent Vref1 is too low or too high or if the delta between the filtered percent Vref1 and non-filtered percent Vref1 is too large. This diagnostic only runs when battery voltage is high enough.	ECM percent Vref1 < or ECM percent Vref1 > or the difference between ECM filtered percent Vref1 and percent Vref1 >	4.875 % Vref1 5.125 % Vref1 0.0495 % Vref1	Diagnostic enabled AND [(Run/Crank voltage for Time period AND Starter engaged) OR (Run/Crank voltage AND Starter engaged)]	= 1 > 6.41 Volts = 0.02 Seconds = FALSE > 8.41 Volts = TRUE	19 / 39 counts; or 0.1875 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Malfunction Indicator Lamp (MIL) Control Circuit (ODM) Open	P0650	Detects an inoperative malfunction indicator lamp control low side driver circuit. This diagnostic reports the DTC when an open circuit is detected.	Voltage low during driver off state (indicates open circuit)	Open circuit: ≥ 200 K Ω impedance between signal and controller ground	Run/Crank Voltage Remote Vehicle Start is not active	Voltage ≥ 11.00 volts	1 failures out of 1 samples 50 ms / sample	Type B, No MIL NO MIL Note: In certain controllers P263A may also set (MIL Control Short to Ground)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
5 Volt Reference #2 Circuit	P0651	Detects a continuous or intermittent short on the 5 volt reference circuit #2 by monitoring the reference percent Vref2 and failing the diagnostic when the percent Vref2 is too low or too high or if the delta between the filtered percent Vref2 and non-filtered percent Vref2 is too large. This diagnostic only runs when battery voltage is high enough.	ECM percent Vref2 < or ECM percent Vref2 > or the difference between ECM filtered percent Vref2 and percent Vref2 >	4.875 % Vref2 5.125 % Vref2 0.0495 % Vref2	Diagnostic enabled AND [(Run/Crank voltage for Time period AND Starter engaged) OR (Run/Crank voltage AND Starter engaged)]	= 1 > 6.41 Volts = 0.02 Seconds = FALSE > 8.41 Volts = TRUE	19 / 39 counts; or 0.1875 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Powertrain Relay Control (ODM) Open	P0685	Detects an open circuit in the Powertrain Relay driver. This diagnostic reports the DTC when an open circuit failure is present. Monitoring occurs when the output is powered off. A decision is made by comparing a voltage measurement to a controller specific voltage threshold.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	Open Circuit: ≥ 200 K Ω ohms impedance between output and controller ground	Run/Crank Voltage	Voltage ≥ 11.00 volts	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p>	<p>Type B, 2 Trips</p> <p>Note: In certain controlle rs P0686 may also set (Powertr ain Relay Control Short to Ground).</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Powertrain Relay Control (ODM) Low	P0686	Detects a short to ground in the Powertrain Relay low side driver. This diagnostic reports the DTC when a short to ground failure is present. Monitoring occurs when the output is powered off. A decision is made by comparing a voltage measurement to a controller specific voltage threshold.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	Short to ground: ≤ 0.5 Ω impedance between output and controller ground	Run/Crank Voltage	Voltage ≥ 11.00 volts	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p>	<p>Type B, 2 Trips</p> <p>Note: In certain controlle rs P0685 may also set (Powertr ain Relay Control Open Circuit).</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Powertrain Relay Control (ODM) High	P0687	Detects a short to power in the Powertrain Relay low side driver. This diagnostic reports the DTC when a short to power failure is present. Monitoring occurs when the output is powered off. A decision is made by comparing a voltage measurement to a controller specific voltage threshold.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	Short to power: $\leq 0.5 \Omega$ impedance between output and controller power	Run/Crank Voltage	Voltage ≥ 11.00 volts	8 failures out of 10 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Power Relay Feedback Circuit Low Voltage	P0689	Detects low voltage in the control module relay feedback circuit. This diagnostic reports the DTC when low voltage is present. Monitoring occurs when run crank voltage is above a calibrated value.	Control module relay feedback circuit low voltage	Powertrain relay voltage ≤ 5.00	Powertrain relay short low diagnostic enable Run Crank voltage Powertrain relay state	= 1.00 > 9.00 = ON	5 failures out of 6 samples 1000 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Powertrain Relay Feedback Circuit High	P0690	Detects higher than expected voltage in the powertrain relay feedback circuit. This diagnostic reports the DTC when higher than expected voltage is present. For example, the powertrain relay could be stuck on. Monitoring occurs when the relay is commanded "off" for a calibrated duration.	Powertrain Relay Voltage	>= 4.00 volts will increment the fail counter	Powertrain relay commanded "OFF" No active DTCs:	>= 2.00 seconds PowertrainRelayStateOn_ FA	50 failures out of 63 samples 100ms / Sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
5 Volt Reference #3 Circuit	P0697	Detects a continuous or intermittent short on the 5 volt reference circuit #3 by monitoring the reference percent Vref3 and failing the diagnostic when the percent Vref3 is too low or too high or if the delta between the filtered percent Vref3 and non-filtered percent Vref3 is too large. This diagnostic only runs when battery voltage is high enough.	ECM percent Vref3 < or ECM percent Vref3 > or the difference between ECM filtered percent Vref3 and percent Vref3 >	4.875 % Vref3 5.125 % Vref3 0.0495 % Vref3	Diagnostic enabled AND [(Run/Crank voltage for Time period AND Starter engaged) OR (Run/Crank voltage AND Starter engaged)]	= 1 > 6.41 Volts = 0.02 Seconds = FALSE > 8.41 Volts = TRUE	19 / 39 counts; or 0.1875 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
5 Volt Reference #4 Circuit	P06A3	Detects a continuous or intermittent short on the 5 volt reference circuit #4 by monitoring the reference percent Vref4 and failing the diagnostic when the percent Vref4 is too low or too high or if the delta between the filtered percent Vref4 and non-filtered percent Vref4 is too large. This diagnostic only runs when battery voltage is high enough.	ECM percent Vref4 < or ECM percent Vref4 > or the difference between ECM filtered percent Vref4 and percent Vref4 >	4.875 % Vref4 5.125 % Vref4 0.0495 % Vref4	Diagnostic enabled AND [(Run/Crank voltage for Time period AND Starter engaged) OR (Run/Crank voltage AND Starter engaged)]	= 1 > 6.41 Volts = 0.02 Seconds = FALSE > 8.41 Volts = TRUE	19 / 39 counts; or 0.1875 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module Knock Sensor Processor 1 Performance	P06B6	This diagnostic checks for a fault with the internal test circuit (sensor #1) used only for the '20 kHz' method of the Open Circuit Diagnostic. A fault is present when the signal level from the 20 kHz range of the FFT output falls between the Open Test Circuit thresholds.	FFT Diagnostic Output	> P06B6_P06B7_OpenT estCktThrshMin AND < P06B6_P06B7_OpenT estCktThrshMax See Supporting Tables	Diagnostic Enabled? Engine Run Time Engine Speed Cumulative Number of Engine Revs (per key cycle) within min/max Engine Speed enable (above) Engine Air Flow	Yes ≥ 2.0 seconds > 1,000 RPM and < 4,650 RPM ≥ 200 Revs ≥ 40 mg/cylinder and ≤ 2,000 mg/cylinder	First Order Lag Filter with Weight Coefficient Weight Coefficient = 0.0100 Updated each engine event	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
5 Volt Reference #5 Circuit	P06D2	Detects a continuous or intermittent short on the 5 volt reference circuit #5 by monitoring the reference percent Vref5 and failing the diagnostic when the percent Vref5 is too low or too high or if the delta between the filtered percent Vref5 and non-filtered percent Vref5 is too large. This diagnostic only runs when battery voltage is high enough.	ECM percent Vref5 < or ECM percent Vref5 > or the difference between ECM filtered percent Vref5 and percent Vref5 >	4.875 % Vref5 5.125 % Vref5 0.0495 % Vref5	Diagnostic enabled AND [(Run/Crank voltage for Time period AND Starter engaged) OR (Run/Crank voltage AND Starter engaged)]	= 1 > 6.41 Volts = 0.02 Seconds = FALSE > 8.41 Volts = TRUE	19 / 39 counts; or 0.1875 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Two Stage Oil Pump Control Circuit Open	P06DA	Controller specific output driver circuit diagnoses the two stage oil pump low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	Open Circuit ≥ 200 k Ω impedance between output and controller ground	<p>Diagnostic Status</p> <p>Powertrain Relay Voltage</p> <p>Run/Crank Active</p> <p>Cranking State</p>	<p>Enabled</p> <p>≥ 11.00</p> <p>= True</p> <p>= False</p>	<p>≥ 40 errors out of 50 samples.</p> <p>Performed every 100 msec</p>	<p>Type B, 2 Trips</p> <p>Note: In certain controllers P06DB may also set (Two Stage Oil Pump Control Circuit Short To Ground)</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Two Stage Oil Pump Control Circuit Short To Ground	P06DB	Controller specific output driver circuit diagnoses the two stage oil pump low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	Short to Ground Circuit $\leq 0.5 \Omega$ impedance between output and controller ground	<p>Diagnostic Status</p> <p>Powertrain Relay Voltage</p> <p>Run/Crank Active</p> <p>Cranking State</p>	<p>Enabled</p> <p>≥ 11.00</p> <p>= True</p> <p>= False</p>	<p>≥ 40 errors out of 50 samples.</p> <p>Performed every 100 msec</p>	<p>Type A, 1 Trips</p> <p>Note: In certain controllers P06DA may also set (Two Stage Oil Pump Control Circuit Open)</p>

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Two Stage Oil Pump Control Circuit Short To Power	P06DC	Controller specific output driver circuit diagnoses the two stage oil pump low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	Short to Power ≤ 0.5 Ω impedance between output and controller power	<p>Diagnostic Status</p> <p>Powertrain Relay Voltage</p> <p>Run/Crank Active</p> <p>Cranking State</p>	<p>Enabled</p> <p>≥ 11.00</p> <p>= True</p> <p>= False</p>	<p>≥ 40 errors out of 50 samples.</p> <p>Performed every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Two Stage Oil Pump Control Circuit Performance - Two Sided	P06DD	Diagnoses the two stage oil pump is stuck in the high pressure state. This diagnostic includes an intrusive test and a passive test. Intrusive test: The oil pump control is cycled off (high pressure) and on (low pressure) Y = 15 times at calibratable intervals. If a change in oil pressure above a calibration is not detected then the oil pressure is checked to determine if it is stuck. It takes X-out-of-Y failures to fail and set the appropriate code. Passive test: After the intrusive test passes, then a passive test will begin to run. The passive test will monitor the oil pressure changes associated with oil pump control state changes. If the passive test determines that the oil pressure change was less then desired then the intrusive test is retriggered.	<u>Fail from passing state:</u> Oil Pressure delta is less than a minimum delta pressure on a state change and the measured filtered oil pressure is above a threshold	Oil Pressure delta = ABS [Filtered Oil Pressure at beginning of state change - filtered oil pressure after 1.0 seconds] Oil Pressure delta < P06DD_P06DE_OP_StateChangeMin AND Filtered Oil Pressure ≥ (P0521_P06DD_P06DE_OP_HiStatePressure + P06DD_P06DE_OP_LoStatePressure) ÷ 2 (see P06DD details on Supporting Tables Tab P06DD_P06DE_OP_StateChangeMin P0521_P06DD_P06DE_OP_HiStatePressure P06DD_P06DE_OP_LoStatePressure)	<u>Common Criteria:</u> Two Stage Oil Pump is Present Engine Running Ambient Air Pressure Oil Aeration (= TRUE if engine speed > 10,000 RPM for longer than 30.0 seconds) No active DTC's for diagnsotic enable: Check oil pump TFTKO as a diagnostic enable when Enabled. No active DTC's for control enable: <u>Active Criteria:</u> One Sided Performance Test = Disabled	TRUE ≥ 10.0 seconds ≥ 70.0 kPa FALSE Fault bundles: MAF_SensorFA ECT_Sensor_FA IAT_SensorFA CrankSensor_FA EngOilPressureSensorCktFA AmbientAirDefault EngOilTempFA OilPmpTFTKO Enabled : OilPmpTFTKO Enabled Fault bundles for control disable : OilPmpTFTKO EngineTorqueEstlnaccurate EngOilPressureSensorFA PowertrainRelayFault CrankSensor_FA EngOilTempFA Disabled	≥ 12 errors out of 15 samples. Run once per trip or activated by the Passive Test	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Oil Pump in Low State</p> <p>Modelled Oil Temperature within range</p> <p>Filtered Engine Speed within range</p> <p>Delta Filtered Engine Speed within a range</p> <p>Engine Torque within range</p> <p>Filtered Oil Pressure within range</p>	<p>> 1.0 seconds</p> <p>50.0 deg C ≤ Oil Temp ≤ 110.0 deg C</p> <p>1,150 RPM ≤ Filtered Engine Speed ≤ 3,500 RPM</p> <p>ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.0 seconds] ≤ 50 RPM</p> <p>P06DD_P06DE_MinEnableTorque_OP ≤ Indicated Requested Engine Torque ≤ P06DD_P06DE_MaxEnableTorque_OP</p> <p>(see P06DD details on Supporting Tables Tab P06DD_P06DE_MinEnableTorque_OP P06DD_P06DE_MaxEnableTorque_OP)</p> <p>Filtered Engine Oil Pressure > P06DD_P06DE_MinOilPressureThresh</p> <p>(see P06DD details on Supporting Tables Tab P06DD_P06DE_MinOilPressureThresh)</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Expected Oil Pressure Delta within range</p> <p><u>Passive Criteria:</u></p> <p>Active Test Passed</p> <p>Filtered Engine Speed within range</p> <p>Modelled Oil Temperature within range</p> <p>Delta Filtered Engine Speed within a range</p> <p>Oil Pressure Delta within a range</p>	<p>125.0 kPa < ABS [P0521_P06DD_P06DE_OP_HiStatePressure - P06DD_P06DE_OP_LoSatePressure] < 325.0 kPa</p> <p>TRUE</p> <p>1,000 RPM ≤ Filtered Engine Speed ≤ 4,500 RPM</p> <p>40.0 deg C ≤ Oil Temp ≤ 120.0 deg C</p> <p>ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.00 seconds] ≤ 1,000 RPM</p> <p>Oil Pressure Delta < P06DD_P06DE_OP_StateChangeMin (see P06DD details on Supporting Tables Tab P06DD_P06DE_OP_StateChangeMin)</p>		
			<p><u>Fast Pass Condition</u></p> <p>Oil Pressure delta is less than a minimum delta pressure on a state change and the measured filtered oil pressure is</p>	<p>Oil Pressure delta =</p> <p>ABS [Filtered Oil Pressure at beginning of state change -</p>	<p><u>Common Criteria:</u></p> <p>Two Stage Oil Pump is Present</p> <p>Engine Running</p>	<p>TRUE</p> <p>≥ 10.0 seconds</p>	<p>0 errors out of 5 samples.</p> <p>Run once per trip or activated by the Passive Test</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			above a threshold	<p>filtered oil pressure after 1.0 seconds]</p> <p>Oil Pressure delta < P06DD_P06DE_OP_StateChangeMin</p> <p>AND</p> <p>Filtered Oil Pressure ≥ (P0521_P06DD_P06DE_OP_HiStatePressure - P06DD_P06DE_OP_LoStatePressure) ÷ 2</p> <p>(see P06DD details on Supporting Tables Tab P06DD_P06DE_OP_StateChangeMin P0521_P06DD_P06DE_OP_HiStatePressure P06DD_P06DE_OP_LoStatePressure)</p>	<p>Ambient Air Pressure</p> <p>Oil Aeration (= TRUE if engine speed > 10,000 RPM for longer than 30.0 seconds)</p> <p>No active DTC's for diagnostic enable:</p> <p>Check oil pump TFTKO as a diagnostic enable when Enabled.</p> <p>No active DTC's for control enable:</p> <p><u>Active Criteria:</u> One Sided Performance Test = Disabled</p> <p>Oil Pump in Low State</p> <p>Modelled Oil Temperature within range</p> <p>Filtered Engine Speed within range</p>	<p>≥ 70.0 kPa</p> <p>FALSE</p> <p>Fault bundles: MAF_SensorFA ECT_Sensor_FA IAT_SensorFA EngOilPressureSensorCktFA AmbientAirDefault EngOilTempFA OilPmpTFTKO CrankSensor_FA</p> <p>Enabled : OilPmpTFTKO</p> <p>Enabled Fault bundles for control disable : OilPmpTFTKO EngineTorqueEstInaccuracy EngOilPressureSensorFA PowertrainRelayFault CrankSensor_FA EngOilTempFA</p> <p>Disabled</p> <p>> 1.0 seconds</p> <p>50.0 deg C ≤ Oil Temp ≤ 110.0 deg C</p> <p>1,150 RPM ≤ Filtered Engine Speed ≤ 3,500</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Engine Torque within range</p> <p>Delta Filtered Engine Speed within a range</p> <p>Filtered Oil Pressure within range</p> <p>Expected Oil Pressure Delta within range</p>	<p>RPM</p> <p>P06DD_P06DE_MinEnableTorque_OP \leq Indicated Requested Engine Torque \leq P06DD_P06DE_MaxEnableTorque_OP (see P06DD details on Supporting Tables Tab P06DD_P06DE_MinEnableTorque_OP P06DD_P06DE_MaxEnableTorque_OP)</p> <p>ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.0 seconds] \leq 50 RPM</p> <p>Filtered Engine Oil Pressure > P06DD_P06DE_MinOilPressureThresh (see P06DD details on Supporting Tables Tab P06DD_P06DE_MinOilPressureThresh)</p> <p>125.0 kPa < ABS [P0521_P06DD_P06DE_OP_HiStatePressure - P06DD_P06DE_OP_LoSStatePressure] < 325.0 kPa</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Two Stage Oil Pump Control Circuit StuckOn - Two Sided	P06DE	<p>Diagnoses the two stage oil pump is stuck in the low pressure state. This diagnostic includes an intrusive test and a passive test.</p> <p>Intrusive test: The oil pump control is cycled off (high pressure) and on (low pressure) Y times at calibratable intervals. If a change in oil pressure above a calibration is not detected then the oil pressure is checked to determine if it is stuck. It takes X-out-of-Y failures to fail and set the appropriate code.</p> <p>Passive test: After the intrusive test passes, then a passive test will begin to run. The passive test will monitor the oil pressure changes associated with oil pump control state changes. If the passive test determines that the oil pressure change was less than desired then the intrusive test is retriggered.</p>	<p><u>Fail from a passing state:</u></p> <p>Oil Pressure delta is less than a minimum delta pressure on a state change and the measured filtered oil pressure is below a threshold</p>	<p>Oil Pressure delta = ABS [Filtered Oil Pressure at beginning of state change - filtered oil pressure after 1.0 seconds]</p> <p>Oil Pressure delta < P06DD_P06DE_OP_StateChangeMin (see P06DE details on Supporting Tables Tab)</p> <p>Filtered Oil Pressure ≤ P0521_P06DD_P06DE_OP_HiStatePressure (see P06DE details on Supporting Tables Tab)</p>	<p><u>Common Criteria:</u></p> <p>Two Stage Oil Pump is Present</p> <p>Engine Running</p> <p>Ambient Air Pressure</p> <p>Oil Aeration (= TRUE if engine speed > 10,000 RPM for longer than 30.0 seconds)</p> <p>No active DTC's for diagnosis enable:</p> <p>Check oil pump TFTKO as a diagnostic enable when Enabled.</p> <p>No active DTC's for control enable:</p> <p><u>Active Criteria:</u> One Sided Performance</p>	<p>TRUE</p> <p>≥ 10.0 seconds</p> <p>≥ 70.0 kPa</p> <p>FALSE</p> <p>Fault bundles: MAF_SensorFA ECT_Sensor_FA IAT_SensorFA CrankSensor_FA EngOilPressureSensorCktFA AmbientAirDefault EngOilTempFA</p> <p>Enabled : OilPmpTFTKO</p> <p>Enabled Fault bundles for control disable : OilPmpTFTKO EngineTorqueEstInaccurate EngOilPressureSensorFA PowertrainRelayFault CrankSensor_FA EngOilTempFA</p> <p>Disabled</p>	<p>≥ 12 errors out of 15 samples.</p> <p>Run once per trip or activated by the Passive Test</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Test = Disabled Oil Pump in Low State Modelled Oil Temperature within range Filtered Engine Speed within range Engine Torque within range Delta Filtered Engine Speed within a range Filtered Oil Pressure within range Expected Oil Pressure Delta within range	> 1.0 seconds 50.0 deg C ≤ Oil Temp ≤ 110.0 deg C 1,150 RPM ≤ Filtered Engine Speed ≤ 3,500 RPM P06DD_P06DE_MinEnableTorque_OP ≤ Indicated Requested Engine Torque ≤ P06DD_P06DE_MaxEnableTorque_OP (see P06DE details on Supporting Tables Tab) ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.0 seconds] ≤ 50 RPM Filtered Engine Oil Pressure > P06DD_P06DE_MinOilPressureThresh (see P06DD details on Supporting Tables Tab) 125.0 kPa < ABS [P0521_P06DD_P06DE_OP_HiStatePressure - P06DD_P06DE_OP_LoSatePressure] < 325.0 kPa		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<u>Passive Criteria:</u> Active Test Passed Filtered Engine Speed within range Modelled Oil Temperature within range Delta Filtered Engine Speed within a range Oil Pressure Delta < P06DD_P06DE_OP_StateChangeMin (see P06DE details on Supporting Tables Tab)	TRUE 1,000 RPM ≤ Filtered Engine Speed ≤ 4,500 RPM 40.0 deg C ≤ Oil Temp ≤ 120.0 deg C ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.00 seconds] ≤ 1,000 RPM TRUE		
			<u>Fast Pass Condition</u> Oil Pressure delta is less than a minimum delta pressure on a state change and the measured filtered oil pressure is below a threshold	Oil Pressure delta = ABS [Filtered Oil Pressure at beginning of state change - filtered oil pressure after 1.0 seconds] Oil Pressure delta <	<u>Common Criteria:</u> Two Stage Oil Pump is Present Engine Running Ambient Air Pressure Oil Aeration (= TRUE if engine speed	TRUE ≥ 10.0 seconds ≥ 70.0 kPa FALSE		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
				<p>P06DD_P06DE_OP_StateChangeMin (P06DD Performance Test Details on Supporting Tables Tab)</p> <p>Filtered Oil Pressure ≤</p> <p>P0521_P06DD_P06DE_OP_HiStatePressure (re -</p> <p>P06DD_P06DE_OP_LoStatePressure) / 2 (P06DD Performance Test Details on Supporting Tables Tab)</p>	<p>> 10,000 RPM for longer than 30.0 seconds)</p> <p>No active DTC's for diagnosis enable:</p> <p>Check oil pump TFTKO as a diagnostic enable when Enabled.</p> <p>No active DTC's for control :</p> <p><u>Active Criteria:</u> One Sided Performance Test = Disabled</p> <p>Oil Pump in Low State</p> <p>Modelled Oil Temperature within range</p> <p>Filtered Engine Speed within range</p> <p>Engine Torque within range</p>	<p>Fault bundles: MAF_SensorFA ECT_Sensor_FA IAT_SensorFA CrankSensor_FA EngOilPressureSensorCktFA AmbientAirDefault EngOilTempFA</p> <p>Enabled : OilPmpTFTKO</p> <p>Enabled Fault bundles for control disable : OilPmpTFTKO EngineTorqueEstInaccurate EngOilPressureSensorFA PowertrainRelayFault CrankSensor_FA EngOilTempFA</p> <p>Disabled</p> <p>> 1.0 seconds</p> <p>50.0 deg C ≤ Oil Temp ≤ 110.0 deg C</p> <p>1,150 RPM ≤ Filtered Engine Speed ≤ 3,500 RPM</p> <p>P06DD_P06DE_MinEnableTorque_OP ≤</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Delta Filtered Engine Speed within a range</p> <p>Filtered Oil Pressure within range</p> <p>Expected Oil Pressure Delta within range</p>	<p>Indicated Requested Engine Torque \leq P06DD_P06DE_MaxEnableTorque_OP (P06DD Performance Test Details on Supporting Tables Tab)</p> <p>ABS [Filtered RPM at beginning of State change - Filtered RPM after 1.0 seconds] \leq 50 RPM</p> <p>Filtered Engine Oil Pressure $>$ P06DD_P06DE_MinOilPressureThresh (see P06DD details on Supporting Tables Tab)</p> <p>125.0 kPa $<$ ABS [P0521_P06DD_P06DE_OP_HiStatePressure - P06DD_P06DE_OP_LoSatePressure] $<$ 325.0 kPa</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Wake-up Circuit Performance Diagnostic (ELCP Sealed/ Vented Fuel System)	P06E4	<p>VICM Wake-up events were not received</p> <p>The ELCP EVAP diagnostics with propulsion system off will run many hours after the vehicle has been shut off when the EVAP system is in a stable condition. Since the ECM does not have the capability to wake itself up, a Vehicle Interface Control Module (VICM) is used to wake up the ECM at predetermined intervals to run the EVAP diagnostics.</p> <p>When the propulsion system transitions to off an alarm request is sent to the VICM. After that period of time has elapsed the VICM alarm clock wakes up the ECM. The ECM then requests another wake up and checks the diagnostic enable conditions. If the enable conditions are met and the EVAP diagnostics are able to complete then the future wake up request will be canceled at the next opportunity when there is communication</p>	<p>Whenever the propulsion system goes active, the diagnostic reads its internal timer and evaluates the results from the wake-up events that could have occurred. For each wake-up event the status can be: Pass – the wake-up event occurred within a window Indeterminate – the ECM was already awake at the time the wake-up event could have occurred Fail – the wake-up event occurred outside a window or did not occur at all</p> <p>If the 5.0 hour wake-up event did not occur from to then a failure has occurred.</p> <p>If the 7.0 hour wake-up event did not occur from to then a failure has occurred.</p> <p>If the 9.5 hour wake-up event did not occur from to then a failure has occurred.</p> <p>At Propulsion System Active, if any of the wake-up events indicate a</p>	<p>4.3 hours 5.8 hours</p> <p>6.0 hours 8.1 hours</p> <p>8.2 hours 11.0 hours</p>	<p>Distance since assembly plant Drive distance Time since last test when passing P0442/P0455 Time since last test when failing P0442/P0455</p> <p>No Active DTC's</p>	<p>≥ 9.9 miles ≥ 0.1 miles</p> <p>≥ 0 hours ≥ 0 hours</p> <p>VehicleSpeedSensor_FA ModuleOffTime_FA LostCommBusB_VICM_FA A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA</p>	<p>Once per each wake-up event when Propulsion System is not active</p> <p>Final decision is made when Propulsion System is Active</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>between the VICM and ECM. If the enable conditions are not met then the ECM will go back to sleep and wait for the next wake up to try and run the EVAP diagnostics. There are a total of three wake ups that the ECM can request until there is another transition from propulsion system on to off.</p> <p>This diagnostic indicates if the wake up (s) occurred at the proper requested time (s). A pass will be reported if a wake up occurred at the proper time. A failure will be reported if no wake up occurred, or if a wake up occurred at the incorrect time. The DTC will be indeterminate if the ECM was already awake in a valid window for some reason other than a VICM wake up.</p>	failure then the DTC fails.					

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Traction Control Torque Request Circuit	P0856	Determines if torque request from the EBTCTM is valid	<p>Serial Communication 2's complement message - (\$1C7/\$1C9 for engine torque, \$1CA/\$1C6 for axle torque)</p> <p>OR</p> <p>Serial Communication message (\$1C7/\$1C9 for engine torque, \$1CA/\$1C6 for axle torque) rolling count index value</p> <p>OR</p> <p>Too many minimum limit torque request transitions occur from TRUE to FALSE to TRUE within a time period</p> <p>Torque request greater than torque request diagnostic maximum threshold</p>	<p>Message <> 2's complement of message</p> <p>Message rolling count value <> previous message rolling count value plus one</p> <p>Requested torque intervention type toggles from not increasing request to increasing request</p> <p>> 175 Nm for engine torque based traction torque system, OR > 1,020 Nm for axle torque based traction torque system</p>	<p>Serial communication to EBTCTM (U0108)</p> <p>Power Mode Engine Running</p> <p>Status of traction in GMLAN message (\$4E9)</p>	<p>No loss of communication</p> <p>= Run = True</p> <p>= Traction Present</p>	<p>>= 6 failures out of 10</p> <p>Performed on every received message</p> <p>6 rolling count failures out of 10 samples</p> <p>Performed on every received message</p> <p>>= 3 multi-transitions out of 5 samples.</p> <p>Performed every 200 ms</p> <p>>= 4 out of 10 samples</p> <p>Performed on every received message</p>	Type C, No SVS Safety Special Type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Powertrain Control Module (HPC) Requested MIL Illumination	P0AC4	Monitors the HPC MIL request message to determine when the HPC has detected a MIL illuminating fault.	HPC Module Emissions-Related DTC set and module is requesting MIL	HPC Module Emissions-Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Heater Supply Voltage Sense Circuit Range/ Performance	P103B	<p>The P103B diagnostic determines if the heater supply circuit is rational by comparing the heater supply voltage to the run crank voltage and calculating the difference.</p> <p>The heater supply voltage input is connected to the O2 heater supply circuit inside the vehicle relay center. It is representative of the voltage supplied to the O2 heaters. The O2 heater voltage is used by the HWIO to calculate the O2 heater resistance on switching type O2 sensors (non-WRAF). With a fault set, the resistance calculation is performed with run crank voltage.</p> <p>The diagnostic failure counter is incremented if the voltage difference is greater than the threshold. This DTC is set based on the fail and sample counters.</p>	The absolute value of Heater Supply Voltage delta from Run Crank voltage	> 2.00 volts	<p>Powertrain relay in range (Relay in range is defined as relay voltage</p> <p>Run Crank signal active</p>	<p>= True > 11.00 volts)</p> <p>= True (Please see "Run/Crank Active conditions" in Supporting Tables)</p>	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Heater Supply Voltage Sense Circuit Low	P103C	<p>The P103C diagnostic determines if the heater supply circuit is low by comparing the heater supply voltage to the threshold.</p> <p>The heater supply voltage input is connected to the O2 heater supply circuit inside the vehicle relay center. It is representative of the voltage supplied to the O2 heaters. The O2 heater voltage is used by the HWIO to calculate the O2 heater resistance on switching type O2 sensors (non-WRAF). With a fault set, the resistance calculation is performed with run crank voltage.</p> <p>The diagnostic failure counter is incremented if the heater supply voltage is less than the threshold. This DTC is set based on the fail and sample counters.</p>	Heater Supply Voltage	< 2.00 volts	<p>Powertrain relay in range (Relay in range is defined as relay voltage</p> <p>Run Crank signal active</p>	<p>= True > 11.00 volts)</p> <p>= True (Please see “Run/Crank Active conditions” in Supporting Tables)</p>	<p>8 failures out of 10 samples</p> <p>250 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Inlet Airflow System Performance (naturally aspirated)	P1101	<p>Detects a performance failure in the Manifold Pressure (MAP) sensor, Throttle Position sensor (TPS) or Mass Air Flow (MAF) sensor that cannot be uniquely identified as a failure in one individual sensor. This diagnostic can set when more than one of these sensors has a performance concern.</p> <p>This diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from these three sensors.</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the system, but no</p>	<p>Filtered Throttle Model Error</p> <p>AND</p> <p>ABS(Measured Flow – Modeled Air Flow) Filtered</p> <p>OR</p> <p>ABS(Measured MAP – MAP Model 1) Filtered</p> <p>AND</p> <p>ABS(Measured MAP – MAP Model 2) Filtered</p>	<p>> 125 kPa*(g/s)</p> <p>> 15.0 grams/sec</p> <p>> 22.0 kPa)</p> <p>> 22.0 kPa</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>(Coolant Temp OR OBD Max Coolant Achieved</p> <p>Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p>	<p>>= 0 RPM <= 5,400 RPM</p> <p>>= -9 Deg C</p> <p>= TRUE)</p> <p><= 125 Deg C</p> <p>= FALSE)</p> <p>>= -20 Deg C <= 125 Deg C</p> <p>>= 0.50</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>Modeled Air Flow Error multiplied by P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM and P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		single failed sensor can uniquely be identified. In this case, the Inlet Airflow System Performance diagnostic will fail.				<p>MAP Model 1 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>No Active DTCs: MAP_SensorCircuitFA EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA</p> <p>No Pending DTCs: EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP</p>		

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Sensor3 by 15.0 °C and the time spent cranking the engine without starting is ≥ 14.0 seconds with the LowFuelConditionDiag	= False	<p>Block Heater is detected and diagnostic is aborted when 1) or 2) occurs.</p> <p>1a) IAT monitoring is enabled after the following Vehicle drive constraints</p> <p>1b) Drive time</p> <p>1c) Vehicle speed</p> <p>1d) Additional Vehicle drive time is provided to 1b when Vehicle speed is below 1c as follows:</p> <p>1e) IAT drops from power up IAT</p> <p>2a) ECT monitoring is enabled after engine start in the following engine run time window</p> <p>2b) Sensor1 temp derivative during the test is:</p> <p>2c) Consecutive samples of 2b) being true are:</p> <p>=====</p> <p>Diagnostic is aborted when 3) or 4) occurs:</p> <p>3) Engine run time with vehicle speed below 1b</p> <p>4) Engine off time (i.e. auto stop) during Block heater detection</p>	<p>> 400 Seconds with</p> <p>> 12.4 MPH and</p> <p>0.00 times the seconds with vehicle speed below 1b</p> <p>≥ 8.0 °C</p> <p>10.0 <= seconds <= 15.0</p> <p>< -0.50 °C/sec</p> <p>≥ 10 samples</p> <p>=====</p> <p>$\geq 1,370$ Seconds</p> <p>≥ 300.0 Seconds</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT SIDI High Pressure Rail Temperature Sensor Performance	P111F	This DTC Diagnoses Fuel Temperature sensors rationality by comparing Primary sensor (T1) vs. Secondary sensor (T2)	Fuel Temperature Error (Absolute delta between sensor1 and sensor2)	> 20.00 degC	<p>Fuel Temperature Rationality Diagnostic Enabled</p> <p>No Fault Active on</p> <p>No Fault Pending on</p>	<p>True</p> <p>Enabled when a code clear is not active or not exiting device control</p> <p>Temperature sensors 1 out of range Low or High Fault Active (P0182, P0182)</p> <p>Temperature sensors 2 out of range Low or High (P0187, P0188)</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>SENT Intenal Error Fault Active (P126E, P126F)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128C, P128D)</p> <p>SENT Communication Fault Pending (P16E4, P16E5)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128C, P128D)</p>	<p>100.00 failures out of 125.00 samples</p> <p>100 ms per Sample Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

[illegible]

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 low side circuit shorted to high side circuit	P1248	Controller specific output driver circuit diagnoses injector 1 high sided driver for a short to low sided driver failure when the output is powered on by comparing a voltage measurement to controller specific voltage threshold	Voltage measurement outside of controller specific acceptable range during driver on state indicates high sided driver for a short to low sided driver failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for high sided driver for a short to low sided driver failure.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 low side circuit shorted to high side circuit	P1249	Controller specific output driver circuit diagnoses injector 2 high sided driver for a short to low sided driver failure when the output is powered on by comparing a voltage measurement to controller specific voltage threshold	Voltage measurement outside of controller specific acceptable range during driver on state indicates high sided driver for a short to low sided driver failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for high sided driver for a short to low sided driver failure.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 low side circuit shorted to high side circuit	P124A	Controller specific output driver circuit diagnoses injector 3 high sided driver for a short to low sided driver failure when the output is powered on by comparing a voltage measurement to controller specific voltage threshold	Voltage measurement outside of controller specific acceptable range during driver on state indicates high sided driver for a short to low sided driver failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for high sided driver for a short to low sided driver failure.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 low side circuit shorted to high side circuit	P124B	Controller specific output driver circuit diagnoses injector 4 high sided driver for a short to low sided driver failure when the output is powered on by comparing a voltage measurement to controller specific voltage threshold	Voltage measurement outside of controller specific acceptable range during driver on state indicates high sided driver for a short to low sided driver failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for high sided driver for a short to low sided driver failure.	25 amp >= through low side driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Driver Over Temperature	P1255	To detect if an internal fuel pump driver over- temperature condition exists under normal operating conditions	Fuel Pump Driver Circuit Board temperature (Fuel Pump Driver Overtemperature enumeration)	T>= 160 degC (Fuel Pump Power Module smart device reports Faulted, Not Faulted or Indeterminate)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c] FPPM Driver Status Alive Rolling Count Sample Faulted d] Diagnostic feedback received e] Run_Crank Ignition Switch Position Circuit VoltageSystem Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c] <> True d] == TRUE e] > 7.00 volts	3 failures / 15 samples 1 sample / 12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 1 Internal Fault - Error Code	P126E	This DTC Diagnoses the SENT Fuel Temperature Sensor 1 internal failure	Fuel Temperature Sensor 1 SENT digital read value	>= 4,089.00	<p>No Fault Active on</p> <p>No Fault Pending on</p>	<p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Active (P128C)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128C)</p>	<p>50.00 failures out of 62.00 samples</p> <p>100 ms per Sample Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Temperature Sensor 2 Internal Fault - Error Code	P126F	This DTC Diagnoses the SENT Fuel Temperature Sensor 2 internal failure	Fuel Temperature Sensor 2 SENT digital read value	$\geq 4,089.00$	<p>No Fault Active on</p> <p>No Fault Pending on</p>	<p>Enabled when a code clear is not active or not exiting device control</p> <p>SENT Communication Fault Active (P16E4, P16E5)</p> <p>Fuel Temperature Sensor SENT Message Error (P128D)</p> <p>Fuel Temperature Sensor SENT Message Error Fault Pending (P128D)</p>	50.00 failures out of 62.00 samples 100 ms per Sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail High Pressure Sensor 2 Out of Range	P127C	<p>This DTC diagnose SENT high pressure sensor 2 that is too low out of range.</p> <p>If the sensor digital value (representing the reference voltage) is below the lower digital threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported. A pass is reported for this DTC if the low sample counter reaches its threshold.</p>	High Pressure Rail Sensor 2 SENT digital read value	=< 94			Time Based: 400 Failuer out of 500 Samples 6.25 ms per Sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure Sensor 1 Internal Performance	P128A	This DTC determines if there is internal error within the SENT pressure sensor 1 (i.e. Broken wire bond internal to the SENT Sensor). Once the internal error is detected a fixed faulted digital values is communicated to the ECU.	Digital pressure sensor 1 value	$\geq 4,089$	<p>SENT Fuel Rail Pressure Sensor Internal Performance Enable</p> <p>Not Fault Pending</p>	<p>Enabled when a code clear is not active or not exiting device control</p> <p>True</p> <p>P16E4 P16E5 P128F</p>	<p>400 failures out of 500 samples</p> <p>6.25 ms per Sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure Sensor 2 Internal Performance	P128B	This DTC determines if there is internal error within the SENT pressure sensor 2 (i.e. Broken wire bond internal to the SENT Sensor). Once the internal error is detected a fixed faulted digital values is communicated to the ECU.	Digital pressure sensor 2 value	$\geq 4,089$	<p>SENT Fuel Rail Pressure Sensor Internal Performance Enable</p> <p>Not Fault Pending</p>	<p>Enabled when a code clear is not active or not exiting device control</p> <p>True</p> <p>P16E4 P16E5 P128F</p>	<p>400 failures out of 500 samples</p> <p>6.25 ms per Sample Continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure & Temperat ure Sensor Temperature 1 Message Incorrect	P128C	This DTC diagnoses the the communication errors on the temperature 1 serial data channel	Serial Message 1 Age	>= 0.03 ms	SENT signal Serial waveform diagnostics enable SENT power up delay No Fault Active	True >= 0.00 seconds P16E4 P16E5	134 failures out of 167 samples 6.25 ms per sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure & Temperature Sensor Temperature 2 Message Incorrect	P128D	This DTC diagnoses the the communication errors on the temperature 2 serial data channel	Serial Message 2 Age	>= 0.03 ms	SENT signal Serial waveform diagnostics enable SENT power up delay No Fault Active	True >= 0.00 seconds P16E4 P16E5	134 failures out of 167 samples 6.25 ms per sample Continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure & Temperature Sensor Pressure Message Incorrect	P128F	This DTC determines if there is any SENT signal waveform for discrepancies (i.e. too many pulse, too few pulse, clock shift). The SENT HWIO Determines message waveform fault (i.e.too many pulse, too few pulse, clock shift) and if the message age is too long.	SENT HWIO Determines message fault (i.e.too many pulse, too few pulse, clock shift) Message Age	= true <div>> 1.69 ms</div>	SENT signal Serial waveform diagnostics enable SENT power up delay No Fault Active on	True <div>>= 0.00 seconds</div> Enabled when a code clear is not active or not exiting device control P16E4 P16E5	400 failures out of 500 samples 6.25 ms per sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Driver Module- Ignition Switch Run/ Start Position Circuit Low [FPPM applications only]	P129D	To detect if the Run/ Start position circuit voltage is short to low / open	FPPM Run_Crank Active status	<> ECM Run_Crank Active status	a) FPPM configuration KeFRPR_e_ChassisFuel PresSysType b) Diagnostic KeFRPR_b_FPPM_RunC rnkRatlEnbld c) FPPM Control Status Alive Rolling Count result d) Diagnostic feedback received e) System Voltage	a) == CeFRPR_e_ECM_FPPM _Sys b) == TRUE c) == Valid d) == TRUE e) >= 0.0 v	64 failures / 80 samples 1 sample / 12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Driver Control Module Signal Message Counter Incorrect [FPPM applications only]	P129E	To detect if the command message received as serial data from the engine control module is valid. The "rolling count check" value is created by adding an appended hexadecimal calculation to the pump duty cycle command value. In order to achieve a desired fuel pressure, a hexadecimal equivalent value representing the necessary fuel pump current pulse "On" time (duty cycle as a percent value) is transmitted to the FPPM. The corresponding "check" value is transmitted as well. At the FPPM, the received duty cycle command value is used to create an expected "rolling count" value using the same calculation method as the ECM. The expected "rolling count" value calculated at the receiving power module (smart device) is compared to the transmitted "rolling count" value. If these do not match, a fault condition is reported	FPPM Received Duty Cycle Rolling Count	<> Transmitted Duty Cycle Rolling Count (ECM) (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Control Rolling Count Faulted d) FPPM Diagnostic data received [\$0CE] e) FPPM Diagnostic Data Validity Enabled f) Diagnostic System Disabled g) Communication Faulted h) Run_Crank Ignition Switch Position Circuit Voltage j) Run_Crank Ignition Status k) Sensor Bus Relay On	a) == FCBR ECM FPPM Sys b) == TRUE c) <> True d) == TRUE e) == TRUE f) <> True g) <> True h) > 7.00 Volts j) == TRUE k) == TRUE	64 failures / 80 samples 1 sample / 12.5 millisec	Type B, 2 Trips
			FPPM Received Duty Cycle Protection Value	<> Transmitted Duty Cycle Protection Value (ECM) (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Control Rolling Count Faulted d) FPPM Diagnostic data received [\$0CE] e) FPPM Diagnostic Data Validity Enabled f) Diagnostic System Disabled g) Communication Faulted h) Run_Crank Ignition Switch Position Circuit	a) == FCBR ECM FPPM Sys b) == TRUE c) <> True d) == TRUE e) == TRUE f) <> True g) <> True h) > 7.00 Volts	64 failures / 80 samples 1 sample / 12.5 millisec	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		forward to the ECM where X/Y diagnostic counting is performed.			Voltage j) Run_Crank Ignition Status k) Sensor Bus Relay On	j) == TRUE k) == TRUE		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Driver Control Module Enable Circuit Performance	P12A6	The purpose of the Fuel Pump Driver Control Module Enable Circuit Performance Diagnostic is to detect if the state of the fuel control enable circuit is valid. This is accomplished by comparing the Fuel Control Enable circuit voltage state [high or low] measured by the Fuel Pump Driver Control Module to the state of Fuel Control Enable signal in the ECM. When the measured state does not match the expected state, the fail counter increments.	FPPM Fuel Control Enable Circuit Voltage State	<> Fuel Control Enable State (ECM)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) Diagnostic System Disabled d) Run_Crank Ignition Sw Position Status Active Timer [expired] e) FPPM Control Data Rolling Count Faulted f) Diagnostic serial data received g) Run_Crank Ignition Switch Position Circuit Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c) <> True d) >= 0.50 seconds e) <> True f) == TRUE g) > 7.00 volts	40 failures / 80 samples 1 sample / 12.5 millisec	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Control Status Signal Message Counter Incorrect [FPPM applications only]	P12A8	To detect if the control status message transmitted as serial data from the driver control module is valid. The "rolling count check" value is created by adding an appended hexadecimal calculation to each control command value. The corresponding "check" value is transmitted to the FPPM as well as the actual command. At the FPPM, the received command value is used to create an expected "rolling count" value using the same calculation method as the ECM. The expected "rolling count" value calculated at the receiving power module (smart device) is compared to the transmitted "rolling count" value. If these do not match, a fault condition is reported forward to the ECM where X/Y diagnostic counting is performed.	FPPM Control Status Alive Rolling Count	<> ECM Control Status Alive Rolling Count (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Diagnostic serial data received d) Run_Crank Ignition Switch Position Circuit Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c) == TRUE d) > 0.00 Volts	64 failures / 80 samples 1 sample / 12.5 millisec	Type B, 2 Trips
			FPPM Power Consumption Alive Rolling Count	<> ECM Power Consumption Alive Rolling Count (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Diagnostic serial data received d) Run_Crank Ignition Switch Position Circuit Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c) == TRUE d) > 0.00 Volts	64 failures / 80 samples 1 sample / 12.5 millisec	
			FPPM Driver Status Alive Rolling Count	<> ECM Driver Status Alive Rolling Count (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Diagnostic serial data received d) Run_Crank Ignition Switch Position Circuit Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c) == TRUE d) > 0.00 Volts	64 failures / 80 samples 1 sample / 12.5 millisec	
			FPPM Hardware Status Alive Rolling Count	<> ECM Hardware Status Alive Rolling Count (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate test state)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) FPPM Diagnostic serial data received d) Run_Crank Ignition Switch Position Circuit Voltage	a) == FCBR ECM FPPM Sys b) == TRUE c) == TRUE d) > 0.00 Volts	64 failures / 80 samples 1 sample / 12.5 millisec	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Coil Positive Voltage Circuit Group 1 * * SIDI ONLY * *	P135A	This diagnostic checks for minimum voltage at the fuse which supplies power to the Ignition Coils (applicable only for SIDI applications). A diagnostic failure indicates a blown fuse.	Ignition Module Supply Voltage.	< 2.5 Volts	Diagnostic Enabled? Three possible Ignition Coil Power Sources (only 1 used): Ignition Coil Power Source = <u>Case 1: Battery</u> Delay starting at Key-On <u>Case 2: Ignition Run/Crank</u> Ignition Run/Crank Voltage <u>Case 3: PT Relay</u> PT Relay Voltage	Yes PT Relay (Case 3) 5 Engine Revs > 5.0 volts > 11.0 volts	24 Failures out of 30 Samples 6.25 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cold Start Emissions Reduction System Fault	P1400	Model based test computes power from exhaust flow and thermal energy resulting from elevated idle speed and retarded spark advance. Detects if the cold start emission reduction system has failed resulting in the delivered power being out of range.	<p>Average desired accumulated exhaust power - Average actual accumulated exhaust power (too much energy delivered to catalyst)</p> <p>Average desired accumulated exhaust power - Average actual accumulated exhaust power (too little energy delivered to catalyst)</p> <p>(EWMA filtered)</p> <p>Average Power = output of P1400_EngineSpeedResidual_Table * output of P1400_SparkResidual_Table NOTE: Desired accumulated power would use the desired catalyst light off spark and desired engine speed and the actual accumulated power would use the final commanded spark and actual engine speed. Refer to the Supporting Tables for details</p>	<p>< -3.85 KJ/s (high RPM failure mode)</p> <p>> 5.30 KJ/s (low RPM failure mode)</p>	<p>To enable the diagnostic, the Cold Start Emission Reduction Strategy must be Active per the following:</p> <p>Catalyst Temperature AND Engine Coolant AND Engine Coolant AND Barometric Pressure</p> <p>The Cold Start Emission Reduction strategy must not be exiting. The strategy will exit per the following:</p> <p>Catalyst Temperature AND Engine Run Time</p> <p>OR</p> <p>Engine Run Time</p> <p>OR</p> <p>Barometric Pressure</p>	<p>< 350.00 degC AND > -12.00 degC AND <= 66.00 degC AND >= 76.00 KPa</p> <p>>= 900.00 degC AND >= 30.00 seconds</p> <p>> P050D_P1400_CatalystLightOffExtendedEngineRunTimeExit</p> <p>This Extended Engine run time exit is a function of percent ethanol and Catmons NormRatioEWMA. Refer to "Supporting Tables" for details.</p>	<p>Runs once per trip when the cold start emission reduction strategy is active</p> <p>Frequency: 100ms Loop</p> <p>Test completes after 15 seconds of accumulated qualified data.</p>	EWMA Based - Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Other Enable Criteria:</p> <p>OBD Manufacturer Enable Counter</p> <p>Vehicle Speed</p> <p>Allow diagnostic to calculate residual in an off-idle state. If the value of the OffIdleEnable is equal to 1 then the "DriverOffAccelPedal" will not be checked. However, if the value of OffIdleEnable is 0 then driver must be off the accel pedal</p> <p>A change in throttle position (tip-in/tip-out) will initiate a delay in the calculation of the average qualified residual value. Therefore when the:</p> <p>Pedal Close Delay Timer</p> <p>the diagnostic will continue the calculation.</p> <p>A change in gear will initiate a delay in the calculation of the average qualified residual value to</p>	<p>0</p> <p>< 81.40 MPH</p> <p>1</p> <p>(A value of 1 allows diagnostic to run and calculate the residual while off idle. A value of 0 requires calculation of the residual at idle)</p> <p>> 2.00 seconds</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>allow time for the actual engine speed and actual final commanded spark to achieve their desired values. Therefore, when the:</p> <p>Gear Shift Delay Timer</p> <p>the diagnostic will continue the calculation</p> <p>For Manual Transmission vehicles:</p> <p>Clutch Pedal Position</p> <p>Clutch Pedal Position</p> <p>The diagnostic will delay calculation of the residual value and potentially weight the residual calculation differently based on engine run time. This is to ensure the diagnostic is operating in idle speed control as well as during the peak catalyst light off period.</p> <p>The time weighting factor must be :</p>	<p>> 2.00 seconds</p> <p>> 12.00 %</p> <p>< 75.00 %</p> <p>> 0 These are scalar values that are a function of engine run time. Refer to</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>General Enable:</p> <p>DTC's Not Set:</p>	<p>P1400_ColdStartDiagnosticDelayBasedOnEngineRunTime and the cal axis, P1400_ColdStartDiagnosticDelayBasedOnEngineRunTimeCalAxis in the "Supporting Tables" for details.</p> <p>AcceleratorPedalFailure ECT_Sensor_FA IAT_SensorCircuitFA MnfdTempSensorCktFP CrankSensor_FA FuelInjectorCircuit_FA MAF_SensorFA MAP_SensorFA EngineMisfireDetected_FA ClutchPstnSnsr FA IAC_SystemRPM_FA IgnitionOutputDriver_FA TPS_FA VehicleSpeedSensor_FA 5VoltReferenceMAP_OOR_Flt TransmissionEngagedState_FA EngineTorqueEstInaccurate</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Gas Recirculation (EGR) Internal Error	P1426	This diagnostic monitors the encoded PWM signal from the Smart EGR Valve. The ECM monitors to determine if the Smart EGR Valve start transmitting the specific PWM Duty Cycle (10%) that indicates it has detected an internal error. The ECM then determines when this conditions has existed long enough to determine the part is faulted.	The smart EGR valve has determined that an internal error exists (internal to the EGR valve). The EGR valve has broadcast the specific duty cycle to indicate internal error conditions exist.	12.00 % > Duty Cycle received from EGR Valve > 8.00 %	Engine RPM Engine RPM Output driver Ignition switch	>= 700 RPM <= 5,900 RPM On Crank or Run	> 20 failures 12.50 ms / sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor1 vs IAT Not Plausible	P1427	<p>The power up temperature varies too much from reference sensor after long soak.</p> <p>At start up, after a long enough soak time to stabilize temperatures, the EGR 1 temp sensor is compared to the IAT temp sensor. If the temperature delta is above an allowed operating threshold the sensor is determined to be faulted.</p>	If the power up, initial value of the temp sensor varies more than allowed from the reference temp sensor.	Temperature Delta from IAT. at power up > 25 degC	<p>Engine soak (not run) time</p> <p>No P codes</p> <p>Ignition switch</p>	<p>>= 28,800.00 Sec</p> <p>P262B P0111 P0114 P010B P00E9 P117D P017C P017D P017B P117B P117F P117E P117C P0116 P0117 P0118 P111E P0128 P0119</p> <p>Crank or Run</p>	NA	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor2 vs IAT Not Plausible	P1429	<p>The power up temperature varies too much from reference sensor after long soak.</p> <p>At start up, after a long enough soak time to stabilize temperatures, the EGR 2 temp sensor is compared to the IAT temp sensor. If the temperature delta is above an allowed operating threshold the sensor is determined to be faulted.</p>	If the power up initial value of the temp sensor varies more than allowed from the reference temp sensor.	Temperature Delta from IAT at power up > 25.00 C	<p>Engine soak (not run) time</p> <p>No P codes</p> <p>Ignition switch</p>	<p>>= 28,800.00 Sec</p> <p>P262B P0111 P0114 P010B P00E9 P117D P017C P017D P017B P117B P117F P117E P117C P0116 P0117 P0118 P111E P0128 P0119</p> <p>Crank or Run</p>	NA	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Temperature Sensor "B" Not Plausible	P1437	<p>The Smart EGR valve is requesting a thermal shutdown when conditions do not exist.</p> <p>DETAILED DESCRIPTION: The EGR Valve on this application is a "Smart EGR Valve". Desired Position, Position Feedback as well as other state communication between the ECM and the Valve are done using an Encoded PWM message.</p> <p>The EGR valve has internal temperature determination that can determine the valve is operating at a temperature that is beyond its range and damage to the valve could occur.</p> <p>GM's standard is that Smart Components cannot make this determination on their own and the request to shut down decision must be made and rationalized by the ECM.</p> <p>When the EGR believes it is in an</p>	<p>The smart EGR valve has determined that a thermal condition exists where the valve should be shut down for protection but ECM has determined that condition is not plausible.</p> <p>ECM Received duty Cycle of 14% (request from valve to be shutdown due to thermal conditions) but none of the other engine "hot conditions" exist.</p>	<p>16.00 % > Duty Cycle Received from EGR Valve > 12.00 %</p> <p>and NONE of the following conditions exist:</p> <p>Engine Metal Overtemp:</p> <p>Engine Metal Temperature > 131 C</p> <p>for > 2 Sec.</p> <p>Ambient Temperature >= 140 C</p> <p>Catalyst temperature > 950</p> <p>Piston Protection:</p> <p>RPM > 8,192 RPM and Airflow > Piston Protection Airflow and engine coolant > 63 C for >= 7 Sec</p> <p>Hot Coolant Enrichment:</p> <p>Engine coolant >= 120.00 C and</p> <p>Percent throttle area</p> <p>>= 5.00 % and</p>	<p>Engine RPM</p> <p>Engine RPM</p> <p>Output driver</p> <p>Ignition switch</p>	<p>>= 700 RPM</p> <p><= 5,900 RPM</p> <p>On</p> <p>Crank or Run</p>	<p>>= 800 samples</p> <p>12.50 ms / sample, continuous</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>elevated temperature conditions where it desires to shut down for protection, it must request it from ECM.</p> <p>This is done by sending a 14% DC message as the Feedback position. The range 12% □ 16% of Feedback Position is held for the Valve request for shutdown.</p> <p>The ECM rationalizes this request with several available known temperatures (calibratable). The request can be rationalized versus: Engine Metal Over temp active flag, Ambient Temperature, Catalyst Temperature, Piston Protection Active, High coolant with elevated RPM and Airflow, Hot coolant enrichment active, Turbo Charger Temperature, Engine Metal temperature, Coolant Temperature, Oil temperature. (Calibratable conditions).</p> <p>If the Valve is requesting temperature shutdown and the ECM determines conditions</p>		<p>Intake Manifold Pressure >= 50.00 kPa and</p> <p>vehicle speed >= 15.00 KPH</p> <p>for >= 2.00 sec</p> <p>Turbo Charger Temperature > 930.00 -</p> <p>GearDownShftOffset</p> <p>Engine Metal Temperature > 131.00 for > 2.00 Sec.</p> <p>Engine Coolant Temperature >= 124.00</p> <p>Engine Oil Temperature >= 1,000.00</p>				

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>are such that the valve can be hot and should be requesting temperature protection the request is honored and the ECM sends the message to the Valve via the encoded PWM desired position message that Valve shutdown is commanded.</p> <p>If the Valve is requesting temperature shutdown and the ECM determines conditions are NOT such that the valve can be hot and that is should NOT be requesting temperature protection the request is Not honored. The ECM continues to send the desired position command to the Valve via the encoded PWM desired position message. Debouncing of the P1437 EGR Temperature Sensor "B" Not Plausible fault starts. If the request message continues while not rationalized for long enough, the P1437 code is set.</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Performance /Stuck Off (ELCP Sealed Fuel System)	P145C	<p>This DTC will detect an ELCP vacuum pump that is stuck off.</p> <p>The 1st reference vacuum measurement is compared to a minimum expected vacuum change for the ELCP vacuum pump stuck off diagnostic. If the minimum vacuum change is not met then a failure is reported for P145C. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. In a passing condition, P145C will not report a pass at this time since this diagnostic is run again during the 2nd reference orifice check section.</p> <p>The 2nd reference vacuum measurement is compared to a minimum expected vacuum change for the ELCP vacuum pump stuck off diagnostic. If the minimum vacuum change is not met then a failure is reported for P145C. If a failure is detected then the ELCP EVAP diagnostic test sequence is</p>	<p>When the ELCP vacuum pump is commanded on during the 1st 0.020" reference orifice vacuum measurement, if the stabilized ELCP pressure sensor (gauge) vacuum reading is after then the ELCP vacuum pump is stuck off and the DTC fails.</p> <p>When the ELCP vacuum pump is commanded on during the 2nd 0.020" reference orifice vacuum measurement, if the stabilized ELCP pressure sensor (gauge) vacuum reading is after then the ELCP vacuum pump is stuck off and the DTC fails.</p>	<p>< 100 Pa 360 seconds</p> <p>< 100 Pa 30 seconds</p>	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles</p> <p>≥ 0.1 miles</p> <p>≥ 70 kPa</p> <p>≤ 110 kPa</p> <p>≥ 10 %</p> <p>≤ 90 %</p> <p>≤ 40 °C</p> <p>≥ 4 °C</p> <p>≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 %</p> <p>≤ 200 %</p>	<p>Up to twice per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		complete. In a passing condition, P145C will report a pass at this time.			Refueling request button pressed Service bay test active Device control exceeds No Active DTC's	0.5 seconds FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA		
					No Active DTC's TFTKO	P043E P043F P0451 P145D P145E P1462 P2421 P2422 P2450 P24B9		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Stuck On (ELCP Sealed Fuel System)	P145D	<p>This DTC detects an ELCP vacuum pump that is stuck on.</p> <p>Ambient check section</p> <p>For the ELCP vacuum pump stuck on test, the ELCP vacuum pump is off, the DCV is closed, and the ELCP switching valve is moved from the vent to pump position half way through the test. Utilizing the switching valve allows for proper fault detection whether the ELCP vacuum pump is stuck on before or after the ECM is awake.</p> <p>The ELCP vacuum pump stuck on test is performed by comparing an initial ELCP pressure sensor reading to a second reading after the ELCP switching valve is moved from the vent to pump position. The ELCP switching valve is moved back to the vent position after the second pressure sensor reading is taken. A large difference between the two pressure sensor</p>	<p>The 1st time in the test sequence when the ELCP vacuum pump is commanded off, after the ELCP switching valve transitions from vent to pump position, if the difference between an initial ELCP pressure sensor (absolute) reading and a second ELCP pressure sensor (absolute) reading is after then the ELCP vacuum pump is stuck on and the DTC fails.</p> <p>The 2nd time in the test sequence when the ELCP vacuum pump is commanded off, if the ELCP pressure sensor (gauge) vacuum reading is after then the ELCP vacuum pump is stuck on and the DTC fails.</p>	<p>> 1,000 Pa 8 seconds</p> <p>> 1,180 Pa 14 seconds</p>	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Once or twice per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>readings indicates the ELCP vacuum pump is stuck on and a failure is reported for P145D. The ELCP EVAP diagnostic test sequence is complete if a failure is detected. In a passing condition, P145D will not report a pass at this time since this diagnostic is run again during the final check section.</p> <p>Final check section</p> <p>The ELCP vacuum pump stuck on test in the final check section is not the same as in the ambient check section. Activating the ELCP switching valve in the final check section is not necessary since it was determined in the ambient check section that the pump was not stuck on when the ELCP EVAP diagnostic test sequence started.</p> <p>In the final check section, the ELCP vacuum pump stuck on test is performed by comparing the initial ELCP pressure sensor reading to the final reading when the test</p>			<p>Refueling request button pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTK</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145E P145F P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		time is reached. A large difference between the two pressure measurements indicates the ELCP vacuum pump is stuck on and a failure is reported for P145D. The ELCP EVAP diagnostic test sequence is complete if a failure is detected. A pass is reported for P145D if the difference is below the threshold calibration.						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EVAP System Leak Between Vent Control Valve and Leak Detection Pump (ELCP Sealed Fuel System)	P145E	<p>A small leak (≥ 0.020") is detected in the EVAP system between the Diurnal Control Valve (DCV) and the ELCP vacuum pump. This includes a leak through the DCV.</p> <p>In the leak between check section the following diagnostics occur: ELCP switching valve performance - P2450, leak to atmosphere between the ELCP vacuum pump and DCV - P145E, and DCV stuck open. The DCV stuck open diagnostic is calibrated to set the same DTC (P145E) as the leak between diagnostic.</p> <p>The ELCP vacuum pump creates a vacuum across a 0.020" reference orifice. This reference vacuum is then compared to the vacuum level created between the closed Diurnal Control Valve (DCV) and the ELCP leak detection pump to determine if a leak exists. If the measured vacuum is below the</p>	If the ELCP pressure sensor (gauge) vacuum reading is less than the 1st 0.020" reference orifice vacuum measurement times a plus a offset for then a small leak is detected between the DCV and ELCP vacuum pump and the DTC fails.	1.00 multiplier 200 Pa 15 seconds	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p>	<p>4.3 \leq time \leq 5.8 hours or 6.0 \leq time \leq 8.1 hours or 8.2 \leq time \leq 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Up to once per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		reference vacuum then a leak has been detected and a failure is reported for P145E.			Refueling request button pressed Service bay test active Device control exceeds No Active DTC's	0.5 seconds FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCP_Circuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA		
					No Active DTC's TFTKO	P043E P043F P0451 P145C P145D P1462 P2450 P24B9		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Reference Orifice Performance (ELCP Sealed Fuel System)	P145F	<p>1st and 2nd 0.020" reference orifice vacuum measurements do not correlate.</p> <p>The reference vacuum is re-checked after the leak detection test sequence is complete.</p> <p>If the absolute difference between the 1st and 2nd reference vacuum measurements is above a threshold then a failure is reported for P145F. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete. If the absolute pressure difference is less than the threshold then a pass is reported.</p> <p>Additional Information</p> <p>The 2nd reference vacuum measurement is similar to the 1st reference vacuum measurement but has a few differences. The 2nd reference vacuum measurement does not need a warm up period like the 1st reference vacuum measurement since the ELCP vacuum pump is</p>	<p>If the difference between the 1st 0.020" reference orifice vacuum measurement and the 2nd 0.020" reference orifice vacuum measurement is after then the 1st and 2nd reference orifice vacuum measurements do not correlate and the DTC fails.</p>	> 550 Pa 30 seconds	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles</p> <p>≥ 0.1 miles</p> <p>≥ 70 kPa</p> <p>≤ 110 kPa</p> <p>≥ 10 %</p> <p>≤ 90 %</p> <p>≤ 40 °C</p> <p>≥ 4 °C</p> <p>≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 %</p> <p>≤ 200 %</p>	<p>Up to once per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>already warmed up since it has been on for the prior test sequences. There are wider calibration limits for the 2nd reference vacuum measurement to account for vacuum increases that can occur the longer the pump runs during the EVAP leak check section.</p> <p>During this portion of the test the ELCP vacuum pump is on, the ELCP switching valve is in the vent position, and the DCV is closed. Just like in the 1st reference orifice check section, the results are based on average vacuum measurements calculated over a period of time. The measurements and calculations described in the 1st reference orifice check section of the guide also apply to the 2nd reference orifice check section.</p> <p>The 2nd reference orifice check section also includes a comparison between the 1st and 2nd reference vacuum</p>			<p>Refueling request button pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145D P145E P1462 P2421 P2422 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		measurements. Large differences between these measurements will fail the reference orifice performance diagnostic (P145F).						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative System Leak Detection Reference Orifice Flow Erratic (ELCP Sealed Fuel System)	P1462	0.020" reference orifice vacuum measurement is erratic. When the ELCP vacuum pump is on and the ELCP switching valve is in the vent position, the ELCP pressure sensor measures the absolute pressure between the ELCP vacuum pump and the reference orifice. A short period of time before the tests ends an averaged ELCP pressure sensor (absolute) measurement is captured and compared to a final averaged ELCP pressure sensor (absolute) measurement. Large differences between the two values indicates that a stabilized vacuum measurement did not occur and a failure is detected. The vacuum measurements are considered erratic.	While performing 1st 0.020" reference orifice vacuum measurement for or 2nd 0.020" reference orifice vacuum measurement for If the absolute value of the difference between the averaged ELCP pressure sensor (absolute) reading starting before the end of the reference measurement and the final averaged ELCP pressure sensor (absolute) reading is then a stabilized 0.020" reference orifice vacuum measurement could not be obtained and the DTC fails.	360 seconds 30 seconds 3 second 10 seconds 3 second > 220 Pa	Propulsion system not active time Distance since assembly plant Drive distance Min baro Max baro Min fuel level Max fuel level ECT Min IAT Max IAT Time since last test when passing P0442/P0455 Time since last test when failing P0442/P0455 ***** ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery Voltage ***** Vehicle speed Vehicle not in assembly plant (value must = 0) Propulsion system not active time Previous propulsion system active time Abort Conditions: Min fuel level slosh Max fuel level slosh Key up during test	4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours ≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C ≥ 0 hours ≥ 0 hours ***** ≥ 10 volts ***** ≤ 3 MPH 0 ≥ 0 seconds ≥ 0 seconds ≥ 190 % ≤ 200 %	Up to twice per trip, for each required wake-up event 100 msec loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Refueling request button pressed Service bay test active Device control exceeds No Active DTC's	0.5 seconds IAT_SensorFA FuelLevelDataFault ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCP_Circuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA		
					No Active DTC's TFTKO	P043E P043F P0451 P145C P145D P145E P2421 P2422 P2450 P24B9		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan 1 Output Circuit (Output Driver Monitor) (EREV/ PHEV only) Open	P1485	Diagnoses the cooling fan 1 output low side driver circuit for circuit faults	Voltage low during driver off state (indicates open circuit)	Open circuit: ≥ 200 K Ω impedance between signal and controller ground	Battery voltage to enable Battery voltage to remain enabled Accessory line is high for No Active DTC's	≥ 11.00 volts ≥ 10.00 volts 5.00 >seconds P2537	50.00 failures out of 63.00 samples 100 ms / sample	Type B, 2 Trips Note: In certain controlle rs P1486 may also set (Cooling Fan 1 Output Circuit Short to Ground).

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan 1 Output Circuit Low Voltage (ODM) (EREV/ PHEV only)	P1486	Diagnoses the cooling fan 1 output low side driver circuit for circuit faults	Voltage low during driver off state (indicates short-to-ground)	Short to ground: ≤ 0.5 Ω impedance between signal and controller ground	Battery voltage to enable Battery voltage to remain enabled Accessory line is high for No Active DTC's	≥ 11.00 volts ≥ 10.00 volts 5.00 >seconds P2537	50.00 failures out of 63.00 samples 100 ms / sample	Type B, 2 Trips Note: In certain controllers P1485 may also set (Cooling Fan 1 Output Circuit Open Circuit).

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan 1 Output Circuit High Voltage (ODM) (EREV/ PHEV only)	P1487	Diagnoses the cooling fan 1 output low side driver circuit for circuit faults	Voltage high during driver on state (indicates short to power).	Short to power: $\leq 0.5 \Omega$ impedance between signal and controller power	Battery voltage to enable Battery voltage to remain enabled Accessory line is high for No Active DTC's	≥ 11.00 volts ≥ 10.00 volts 5.00 >seconds P2537	50.00 failures out of 63.00 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Throttle Position Steady State Actuation Fault	P1516	Detect an inability to maintain a steady state throttle position.	The absolute difference between desired and indicated throttle position is >	2.00 percent	Run/Crank voltage TPS minimum learn is not active AND Throttle is being Controlled Throttle is considered in a steady state condition when the desired throttle position over a 12.5 ms period is For a settling time period Ignition voltage failure is false	> 6.41 Volts < 0.25 percent > 4.00 seconds P1682	0.49 ms	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Communicati on Error with Active Grill Air Shutter Module "A"	P151E	This DTC monitors for an internal error or error in communication with the Active Grill Air Shutter Module A	Communication of the Alive Rolling Count from the Shutter Module over LIN bus is incorrect or the Shutter Module signals it has an internal error for out of total samples	 ≥ 10.00 counts ≥ 10.00 counts	All the following conditions are met for Power Mode Powertrain Relay Voltage Run/Crank Ignition Voltage	≥ 3000 milliseconds = Run ≥ 11.00 Volts ≥ 11.00 Volts	LIN bus communication executes in 500ms loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Adaptive Cruise Control Signal Circuit	P1553	Detects rolling count or protection value errors in Adaptive Cruise Control Axle Torque Command serial data signal	If x of y rolling count / protection value faults occur, disable adaptive cruise control for duration of fault		Adaptive Cruise Control Command Serial Data Error Diagnostic Enable	1.00	9 / 17 counts	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Switch State Undertermin ed	P155A	Detects when cruise switch state cannot be determined, such as low voltage conditions	cruise switch state is received as "undetermined" for greater than a calibratable time	fail continuously for greater than 0.5 seconds			fail continuously for greater than 0.5 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Air Conditioning (A/C) Refrigerant Pressure Too High When A/C Off	P156A	Determines if the Air Conditioning High Side Pressure Sensor circuit voltage is stuck or biased in range	Off Test: The pressure sensor has to be greater than a threshold value when AC is off (a function of ambient temp)	Off Test Pressure > P156A_Off_Test_Thre shold (function of ambient temperature) (P156A Off Test Details on Supporting Tables:)	Diagnostic Status Off Test Status AC Off Time No active DTC's	Enabled Enabled Delay Time > P156A_Off_Test_Delay Sec. Fault bundles: ACHighSidePressSnsrCkt FA ACFailedOnSD ACThrmlRefrigSpdVld ACCMLostComm	80 failures out of 100 samples Performed every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Air Conditioning (A/C) Refrigerant Pressure Too Low When A/C On	P156B	Determines if the Air Conditioning High Side Pressure Sensor circuit voltage is stuck or biased in range	On Test: The pressure sensor has to be less than a threshold value when engaged (a function of ambient temp)	On Test Pressure < P156B_On_Test_Thre shold (function of ambient temperature) (P156B On Test Details on Supporting Tables:)	Diagnostic Status On Test Status AC On Time No active DTC's	Enabled Enabled Delay Time > 10 Sec. Fault bundles: ACHighSidePressSnsrCkt FA ACFailedOnSD ACThrmlRefrigSpdVld ACCMLostComm	80 failures out of 100 samples Performed every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Calibration Incorrect	P158A	Type of cruise in Body Control Module does not match that in the Engine Control Module for 2.5 seconds	Type of cruise system in GMLAN \$4E9 does not match with that in the Engine Control Module for a fix time.	2.5 seconds	DID \$40 from BCM says cruise system is present (ECM recieves programmble information from Body Control Module) OR ECM will not receive Programmable information for Cruise from Body Control Module	True	fail continuously for greater than 2.5 seconds.	Type C, No SVS Emissio ns Neutral Diagnost ics – Special Type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Torque Command Circuit	P15F2	This DTC monitors for an error in communication with the Hybrid Commanded Engine Torque Signal	Communication of the Alive Rolling Count or Protection Value for the the Hybrid Commanded Engine Torque Signal over CAN bus is incorrect for out of total samples	>= 10.00 counts <div>>= 10.00 counts</div>	All the following conditions are met for Power Mode Powertrain Relay Voltage Run/Crank Ignition Voltage	>= 3000 milliseconds = Run >= 11.00 Volts >= 11.00 Volts	Executes in 10ms loop.	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Front Object Detection Control Module Torque Request Signal Message Counter Incorrect	P15F6	Detects rolling count or protection value errors in Collision Preparation System Axle Torque Command serial data signal	If x of y rolling count / protection value faults occur, disable collision preparation system for duration of fault		Front Object Detection Module Torque Request Serial Data Error Diagnostic Enable	1.00	4 / 10 counts	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Automatic Braking Engine Torque Request Signal Message Incorrect	P15F8	Detects rolling count or protection value errors Rear Virtual Bumper Axle Torque Command serial data signal	If x of y rolling count / protection value faults occur, disable rear virtual bumper or collision preparation system for duration of fault		Automatic Braking Engine Torque Request Serial Data Error Diagnostic Enable	1.00	4 / 10 counts	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Control Speed Request Circuit Signal Message Counter Incorrect	P15F9	This DTC monitors for an error in communication with the Torque Request signal in \$281	Communication of the Alive Rolling Count or Protection Value in the Torque Request signal over CAN bus is incorrect for out of total samples	>= 10 counts >= 10 counts	All the following conditions are met for Power Mode Powertrain Relay Voltage Run/Crank Ignition Voltage	>= 3000 milliseconds = Run >= 11.00 Volts >= 11.00 Volts	Executes in 25ms loop.	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EVAP System Alarm Clock Signal Not Received (ELCP Sealed/ Vented Fuel System)	P162D	<p>ECM did not receive VICM alarm clock feedback signal</p> <p>The ELCP EVAP diagnostics with propulsion system off will run many hours after the vehicle has been shut off when the EVAP system is in a stable condition. Since the ECM does not have the capability to wake itself up, a Vehicle Interface Control Module (VICM) is used to wake up the ECM at predetermined intervals to run the EVAP diagnostics.</p> <p>When the propulsion system transitions to off an alarm request is sent to the VICM. After that period of time has elapsed the VICM alarm clock wakes up the ECM. The ECM then requests another wake up and checks the diagnostic enable conditions. If the enable conditions are met and the EVAP diagnostics are able to complete then the future wake up request will be canceled at the next opportunity when</p>	<p>Whenever the propulsion system goes active, the diagnostic reads its internal timer and evaluates the results from the wake-up events that could have occurred.</p> <p>If the ECM did not receive feedback from the VICM that the alarm clock was set, the 5.0 hour wake-up event did not occur, and the ECM did not wake up for any reason from to then a failure has occurred.</p> <p>If the ECM did not receive feedback from the VICM that the alarm clock was set, the 7.0 hour wake-up event did not occur, and the ECM did not wake up for any reason from to then a failure has occurred.</p> <p>If the ECM did not receive feedback from the VICM that the alarm clock was set, the 9.5 hour wake-up event did not occur, and the ECM did not wake up for any reason from to then a failure has occurred.</p>	<p>4.3 hours 5.8 hours</p> <p>6.0 hours 8.1 hours</p> <p>8.2 hours 11.0 hours</p>	<p>Distance since assembly plant Drive distance Time since last test when passing P0442/P0455 Time since last test when failing P0442/P0455</p> <p>No Active DTC's</p> <p>Abort Conditions: Service bay test active</p>	<p>≥ 9.9 miles ≥ 0.1 miles</p> <p>≥ 0 hours ≥ 0 hours</p> <p>VehicleSpeedSensor_FA ModuleOffTime_FA LostCommBCM_FA LostCommBusB_VICM_FA CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA</p>	<p>Once per each wake-up event when Propulsion System is not active</p> <p>Final decision is made when Propulsion System is Active</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>there is communication between the VICM and ECM. If the enable conditions are not met then the ECM will go back to sleep and wait for the next wake up to try and run the EVAP diagnostics. There are a total of three wake ups that the ECM can request until there is another transition from propulsion system on to off.</p> <p>This diagnostic indicates if the ECM received feedback from the VICM after a wake up request was made. A pass will be reported if feedback was received. A failure will be reported if no wake up occurred and no feedback was received. The DTC will be indeterminate if feedback was not received, but a VICM wake up occurred or the ECM was already awake in a valid window for some reason other than a VICM wake up.</p>	At Propulsion System Active, if any of the wake-up events indicate a failure then the DTC fails.					

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module SIDI High Pressure Pump current monitor	P163A	This DTC Diagnoses the current from the control area and compares it with calibrated thresholds to set current high and low flags	SIDI fuel pump High Current Test		Battery Voltage	>= 11 Volts	Current High/ Low	Type B, 2 Trips
			Current	>= 11.00 Amps	Low Side Fuel Pressure	> 0.300 MPa		
			SIDI fuel pump Low Current Test					
			Current	<= 0.10 Amps	Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control commanded pressure is false and Device control pump ckt enabled on is false andEngine movement detected is true and Manufacturers enable	Enabled when a code clear is not active or not exiting device control Engine is not cranking	10 seconds failures out of 12.50 seconds sample	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active and Barometric Pressure Inlet Air Temp Fuel Temp	>= 70.0 KPA >= -10.0 degC -10 <= Temp degC <= 132		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Voltage Correlation	P1682	Detect a continuous or intermittent out of correlation between the Run/Crank Ignition Voltage and the Powertrain Relay Ignition Voltage. The diagnostic monitors the difference in voltage between Run/Crank Voltage and the Powertrain Relay Ignition Voltage and fails the diagnostic when the voltage difference is too high. This diagnostic only runs when the powertrain is commanded on and the Run/Crank Voltage is greater than a threshold based on IAT or the powertrain ignition voltage is high enough the Run/Crank voltage is high enough.	Run/Crank – PT Relay Ignition >	3.00 Volts		Powertrain commanded on AND (Run/Crank voltage > Table, f(IAT). See supporting tables: P1682_PT Relay Pull-in Run/Crank Voltage f(IAT) OR PT Relay Ignition voltage > 5.50 Volts) AND Run/Crank voltage > 5.50 Volts	240 / 480 counts; or 0.175 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS SENT Comm Circuit Low (Gasoline applications ONLY)	P16A0	Detects a continuous or intermittent short low or open fault in the TPS SENT Communication Circuit by monitoring the voltage and failing the diagnostic when the voltage for the wave pulse is below state threshold as defined by SAE J2716 SENT Protocol. This diagnostic only runs when battery voltage is high enough.	Voltage for wave pulse is below state threshold as defined by SAE J2716 SENT Protocol	0.5 V	Run/Crank voltage	> 6.41 Volts	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS SENT Comm Circuit High (Gasoline applications ONLY)	P16A1	Detects a continuous or intermittent short high fault in the TPS SENT Communication Circuit by monitoring the voltage and failing the diagnostic when the voltage for the wave pulse is above state threshold as defined by SAE J2716 SENT Protocol. This diagnostic only runs when battery voltage is high enough. Detects a High Circuit Fault in the TPS SENT Communication Circuit	Voltage for wave pulse is above state threshold as defined by SAE J2716 SENT Protocol	4.1 V	Run/Crank voltage	> 6.41 Volts	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
TPS SENT Comm Circuit Performance (Gasoline applications ONLY)	P16A2	Detects a message fault in the TPS SENT Communication Circuit by monitoring the message pulse time and failing the diagnostic when the time for the pulse is above a low time threshold or above a high time threshold or if the message age limit is greater than a time threshold. This diagnostic only runs when battery voltage is high enough. Detects a Message Fault in the TPS SENT Communication Circuit	Message Pulse < Message Pulse > or Message Age Limit >= or Signal CRC fails	0.125977 ms 0.209991 ms 3.125 ms	Run/Crank voltage	> 6.41 Volts	79 / 159 counts; 57 counts continuous; 3.125 ms /count in the ECM main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Voltage Correlation #2	P16A7	Detect a continuous or intermittent out of correlation between the Run/Crank Ignition Voltage and the Powertrain Relay Ignition Voltage #2. The diagnostic monitors the difference in voltage between Run/Crank Voltage and the Powertrain Relay Ignition Voltage and fails the diagnostic when the voltage difference is too high. This diagnostic only runs when the powertrain is commanded on and the Run/Crank Voltage is greater than a threshold based on IAT or the powertrain ignition voltage is high enough the Run/Crank voltage is high enough. Detect a continuous or intermittent out of correlation between the Run/Crank Ignition Voltage & the Powertrain Relay Ignition Voltage #2.	Run/Crank – PT Relay Ignition >	3.00 Volts		Powertrain commanded on AND (Run/Crank voltage > Table, f(IAT). See supporting tables: P1682_PT Relay Pull-in Run/Crank Voltage f(IAT) OR PT Relay Ignition voltage > 5.50 Volts) AND Run/Crank voltage > 5.50 Volts	240 / 480 counts; or 0.175 sec continuous; 12.5 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Controls Ignition Relay Feedback Circuit 2 High Voltage - (GEN III Controllers ONLY)	P16B3	Detects high voltage in the engine controls ignition relay feedback circuit 2. This diagnostic reports the DTC when high voltage is present. Monitoring occurs when the relay state is inactive.	Engine controls ignition relay feedback circuit 2 high voltage	Relay voltage ≥ 4.00	Powertrain relay high diag enable Powertrain relay state	= 1.00 = INACTIVE	50 failures out of 63 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure & Temperature Sensor Communicati on Circuit 3 Low Voltage	P16E4	This DTC determines if the SENT signal shorted low, this is determined by monitoring the number pulses on the SENT signal line received at the ECU and the SENT Signal Line State always indicating low.	The number pulses on the SENT signal line SENT Signal Line State	<= 40 = Low	SENT Sensor Communication Circuit Diagnostic Enabled SENT power up delay	True >= 0.00 seconds Enabled when a code clear is not active or not exiting device control	400 failures out of 500 samples 6.25 ms per sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SENT Fuel Rail Pressure & Temperature Sensor Communicati on Circuit 3 High Voltage	P16E5	This DTC determines if the SENT signal shorted low, this is determined by monitoring the number pulses on the SENT signal line received at the ECU and the SENT Signal Line State always indicating high.	The number pulses on the SENT signal line SENT Signal Line State	<= 40 = High	SENT Sensor Communication Circuit Diagnostic Enabled SENT power up delay	True >= 0.00 seconds Enabled when a code clear is not active or not exiting device control	400 failures out of 500 samples 6.25 ms per sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 1	P16F0	This DTC detects intermittent and continuous invalid SPI messages. This is based on the detection of missing or invalid receive message within the main processor before receiving a valid message.	This function detects a serial communications fault based upon the detection of missing or invalid (receive) message within the main processor before receiving a valid message.		Run/Crank voltage	> 6.41 Volts	39 / 399 counts continuous; 12.5 ms /count in the ECM main processor	Type A, 1 Trips
			This function detects a serial communications fault based upon the detection of missing or invalid (receive) message within the main processor after receiving a valid message.		Run/Crank voltage	> 6.41 Volts	159 / 399 counts continuous; 12.5 ms /count in the ECM main processor	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module Redundant Memory Performance (Gasoline applications ONLY)	P16F3	<p>Detect Processor Calculation faults due to RAM corruptions, ALU failures and ROM failures</p> <p>For all of the following cases: If the individual diagnostic threshold is equal to 2048 ms, this individual case is not applicable. If any of the following cases are X out of Y diagnostics and the fail (x) is greater than the sample (Y), this individual case is also not applicable.</p>	Equivance Ratio torque compensation exceeds threshold	-132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	Type A, 1 Trips
			Absolute difference between Equivance Ratio torque compensation and its dual store out of bounds given by threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of Accessory torque and its redundant calculation is out of bounds given by threshold range	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Absolute difference of Filtered Air-per-cylinder and its redundant calculation is out of bounds given by threshold range	140.87 mg	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference between the previous Final Advance and the current Final Advance not Adjusted for Equivalence Ratio is out of bounds given by threshold range	34.58 degrees		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Torque Learn offset is out of bounds given by threshold range	High Threshold 0.00 Nm Low Threshold 0.00	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
				Nm				
			One step ahead calculation of air-per-cylinder and two step ahead is greater than threshold	80.00 mg		Engine speed > 1,400 rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference between Unmanaged Spark and PACS Spark is greater than threshold	34.58 degrees	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Commanded Predicted Engine Torque and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Zero pedal axle torque is out of bounds given by threshold range	High Threshold 998.00 Nm Low Threshold -1,497.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Creep Coast Axle Torque is out of bounds given by threshold range	High Threshold 998.00 Nm Low Threshold -1,497.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Absolute difference of Friction torque and its redundant calculation is out of bounds given by threshold range	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Arbitrated Air-Per-Cylinder filter coefficient is out of bounds given by threshold range	High Threshold 1.000 Low Threshold 0.074	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Launch spark is active but the launch spark redundant path indicates it should not be active	N/A		Engine speed < 7,800.00 or 7,900.00 rpm (hysteresis pair)	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Rate limited vehicle speed and its dual store do not equal	N/A		Time since first CAN message with vehicle speed >= 0.500 sec	10 / 20 counts; 25.0msec/count	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Commanded engine torque due to fast actuators and its dual store do not equal	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Commanded engine torque due to slow actuators and its dual store do not equal	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			TOS to wheel speed conversion factor is out of bounds given by threshold range	High Threshold: 1.10 T/C Range Hi 0.10 T/C Range Lo Low Threshold: 1.10 T/C Range Hi 0.10 T/C Range Lo	Ignition State	Accessory, run or crank	255 / 6 counts; 25.0msec/count	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Cylinders active greater than commanded	5 cylinders		Engine run flag = TRUE > 2.00 s Number of cylinder events since engine run > 24 No fuel injector faults active	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Transfer case neutral request from four wheel drive logic does not match with operating conditions	N/A	Ignition State	Accessory, run or crank Transfer case range valid and not over-ridden FWD Apps only	7.00/ 10.00 counts; 25.0msec/count	
			Driver progression mode and its dual store do not equal	N/A	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
							multiplier	
			Predicted torque for uncorrected zero pedal determination is greater than calculated limit.	Table, f(Engine, Oil Temp). P16F3_Speed Control External Load f(Oil Temp, RPM) + 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine Predicted Request Without Motor is greater than its redundant calculation plus threshold	131.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine Immediate Request Without Motor is greater than its redundant calculation plus threshold	131.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
							down time multiplier	
			Positive Torque Offset is greater than its redundant calculation plus threshold OR Positive Torque Offset is less than its redundant calculation minus threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Commanded Predicted Engine Request is greater than its redundant calculation plus threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, down time	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
							multiplier 0.5	
			Commanded Hybrid Predicted Crankshaft Request is greater than its redundant calculation plus threshold	131.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Commanded Hybrid Immediate Crankshaft Request is less than its redundant calculation minus threshold	131.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Regeneration Brake Assist is not within a specified range	Brake Regen Assist < 0 Nm or Brake Regen Assist > 0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Cylinder Spark Delta Correction exceeds the absolute difference as compared to Unadjusted Cylinder Spark Delta	34.58 degrees	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			1. Cylinder Torque Offset exceeds step size threshold OR	1. 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			2. Sum of Cylinder Torque Offset exceeds sum threshold	2. 132.90 Nm				
			Engine Capacity Minimum Immediate Without Motor is greater than its dual store plus threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine Capacity Minimum Engine Off is greater than threshold	0 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Engine Capacity Minimum Engine Immediate Without Motor is greater than threshold	0 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Commanded Immediate Engine Request is greater than its redundant calculation plus threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine Speed Lores Intake Firing (event based) calculation does not equal its redundant calculation	N/A		Engine speed greater than 0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Engine Speed Lores Intake Firing timing (event based) calculation does not equal its redundant calculation	N/A		Engine speed greater than 0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Idle speed control calculated predicted minimum torque request exceeds calculated torque limit	Table, f(Oil Temp, RPM). See supporting tables: P16F3_Speed Control External Load f(Oil Temp, RPM) + 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Idle speed control calculated predicted minimum torque without reserves exceeds calculated torque limit	Table, f(Oil Temp, RPM). See supporting tables: P16F3_Speed Control External Load f(Oil Temp, RPM) +	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
				132.90 Nm				
			Difference between Driver Requested Immediate Torque primary path and its secondary exceeds threshold	998.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Driver Immediate Request is less than its redundant calculation minus threshold	998.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded Immediate Request is greater than its redundant calculation plus threshold	998.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			OR Commanded Immediate Request is less than its redundant calculation minus threshold				multiplier	
			Commanded Immediate Response Type is set to Inactive	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference between Cruise Axle Torque Arbitrated Request and Cruise Axle Torque Request exceeds threshold	37.42 Nm		Cruise has been engaged for more than 4.00 seconds	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Desired engine torque request greater than redundant calculation plus threshold	131.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine min capacity above threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			No fast unmanaged retarded spark above the applied spark plus the threshold	15.00 Degree		Engine speed greater than 0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of adjustment factor based on temperature and its dual store above threshold	2.76 m/s	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			1. Absolute difference of redundant calculated engine speed above threshold	1,808 RPM		Engine speed greater than 0 RPM	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			After throttle blade pressure and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Speed Control's Predicted Torque Request and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Engine oil temperature and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Desired throttle position greater than redundant calculation plus threshold	10.00 percent	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of the rate limited pre-throttle pressure and its redundant calculation greater than threshold	0.06 kpa	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Throttle desired torque above desired torque plus threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Desired filtered throttle torque exceeds the threshold plus the higher of desired throttle torque or modeled throttle torque	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Torque feedback proportional term is out of allowable range or its dual store copy does not match	High Threshold 66.45 Nm Low Threshold -66.45 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Torque feedback integral term magnitude or rate of change is out of allowable range or its dual store	High Threshold 124.59 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			copy do not match	Low Threshold -132.90 Nm Rate of change threshold 8.31 Nm/loop			down time multiplier	
			Difference of Final Torque feedback proportional plus integral term and its redundant calculation is out of bounds given by threshold range	High Threshold 132.90 Nm Low Threshold - 132.90 Nm			Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference of torque desired throttle area and	High Threshold	Ignition State	Accessory, run or crank	Up/down timer 2,048	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			its redundant calculation is out of bounds given by threshold range	2.50 % Low Threshold - 2.50 %			ms continuous, 0.5 down time multiplier	
			Difference of torque model coefficients and its redundant calculation is out of bounds given by threshold range	High Threshold 0.0006730 Low Threshold - 0.0006730	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference of base friction torque and its redundant calculation is out of bounds given by threshold range	High Threshold 132.90 Nm Low Threshold - 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Accessory drive friction torque is out of bounds given by threshold range	High Threshold 132.90 Nm Low Threshold 0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			AC friction torque is greater than commanded by AC control software or less than threshold limit	High Threshold 0.00 Nm Low Threshold 0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Difference of Oil temperature delta friction torque and its redundant calculation is out of bounds given by threshold range	High Threshold 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
				Low Threshold - 132.90 Nm				
			Generator friction torque is out of bounds given by threshold range	High Threshold 132.90 Nm Low Threshold 0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Absolute difference between the Supercharger friction torque and its redundant calculation greater than threshold	132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Filtered Torque error magnitude or its increase rate of change is out of	High Threshold 132.90		Engine speed >0rpm MAF, MAP and Baro DTCs are false	Up/down timer 2,048 ms continuous.	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			allowable range or its dual store copy do not match	Nm Low Threshold -132.90 Nm Rate of change threshold 8.31 Nm/loop			0.5 down time multiplier	
			Torque error compensation is out of bounds given by threshold range	High Threshold 132.90 Nm Low Threshold 0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Delta Torque Baro compensation is out of bounds given by threshold	High Threshold 1.32	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous,	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			range	Nm Low Threshold -1.27 Nm			0.5 down time multiplier	
			1. Difference of reserve torque value and its redundant calculation exceed threshold OR 2. Reserve request does not agree with operating conditions or Difference of final predicted torque and its redundant calculation exceed threshold OR 3. Rate of change of reserve torque exceeds threshold, increasing direction only OR 4. Reserve engine torque above allowable capacity threshold	1. 131.90 Nm 2. N/A 3. 131.90 Nm 4. 131.90 Nm	3. & 4.: Ignition State	1. & 2.: Torque reserve (condition when spark control greater than optimum to allow fast transitions for torque disturbances) > 132.90 Nm 3. & 4.: Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Engine Vacuum and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of the calculated Intake Manifold Pressure during engine event versus during time event is greater than threshold	Table, f(Desired Engine Torque). See supporting tables: P16F3_Delta MAP Threshold f(Desired Engine Torque)		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Min. Axle Torque Capacity is greater than threshold	-3,250.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 175 ms continuous, 0.5 down time multiplier	
			Driver Predicted Request is greater than its redundant calculation plus threshold OR	998.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Driver Predicted Request is less than its redundant calculation minus threshold					
			Cold Delta Friction Torque and its dual store do not match	N/A	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Predicted torque for zero pedal determination is greater than calculated limit.	Table, f(Oil Temp, RPM). See supporting tables: Speed Control External Load f(Oil Temp, RPM) + 132.90 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Commanded Predicted	1 Nm	Ignition State	Accessory, run or crank	Up/down timer	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Axle Torque and its dual store do not match				475 ms continuous, 0.5 down time multiplier	
			Steady State Estimated Engine Torque and its dual store are not equal	N/A		AFM not changing from Active to Inactive and preload torque not changing and one loop after React command Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference of Weighting factor for number of cylinders fueled and its redundant calculation is above threshold	0.26		Engine run flag = TRUE > 0.20 s	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Difference of minimum spark advance limit and its redundant calculation is out of bounds given by threshold range	34.58 degrees	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Difference of commanded spark advance and adjusted delivered is out of bounds given by threshold range	34.58 degrees		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference between Estimated Engine Torque and its dual store are above a threshold	132.90 Nm		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference between Estimated Engine Torque without reductions due to torque control and its dual store are above a threshold	132.90 Nm		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Difference of desired spark advance for managed torque and its redundant calculation is out of bounds given by threshold range	34.58 degrees		Torque reserve (condition when spark control greater than optimum to allow fast transitions for torque disturbances) > 132.90 Nm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of Engine Capacity Minimum Running Immediate Brake Torque Excluding Cylinder Sensitivity and its redundant calculation is out of bounds given by threshold range	133 Nm		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			One step ahead calculation of air-per-cylinder greater than two step ahead calculation by threshold for time	Threshold: Dynamically calculated based on current engine conditions Fault Pending Threshold: 100		Engine speed > 1,400 rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
				ms				
			Rate limited cruise axle torque request and its dual store do not match within a threshold	37.42 Nm	Ignition State	Accessory, run or crank	Up/down timer 163 ms continuous, 0.5 down time multiplier	
			1. Absolute difference of Calculated accelerator pedal position compensated for carpet learn and error conditions and its redundant calculation is out of bounds given by threshold range OR 2. Absolute difference of Calculated accelerator pedal position compensated for carpet learn and error conditions and its dual store do not equal OR	1. 5.00 % 2. N/A 3. N/A	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			3. Absolute difference of Calculated accelerator pedal position and its dual store do not equal					
			Commanded axle torque is greater than its redundant calculation by threshold	998.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Commanded axle torque is less than its redundant calculation by threshold	1,497.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Preload timer and its redundant calculation do not equal	N/A	Ignition State	Accessory, run or crank AFM apps only	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			AC friction torque is greater than commanded by AC control software	0.00 Nm	Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Engine Speed Lores Intake Firing (time based) calculation does not equal its redundant calculation	N/A		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of the calculated spark offset for equivalence ratio and its redundant calculation is greater than a threshold	34.58 degrees		Engine speed >0rpm	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Transmission Torque Request calculations do not equal their dual stores	N/A		Run or Crank = TRUE > 0.50 s	16 / 32 counts; 25.0msec/count	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Absolute difference of the predicted motor torque ACS and its redundant calculation is greater than a threshold	0.01 Nm			Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of maximum throttle area and its redundant calculation is greater than a threshold	15 mm ²			Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Absolute difference of Desired TIAP and its redundant calculation is greater than a threshold	5.00 kPa			Up/down timer 2,048 ms continuous, 0.5 down time multiplier	
			Pedal learns and their redundant calculation do not equal		Ignition State	Accessory, run or crank	Up/down timer 475 ms continuous, 0.5 down time multiplier	
			Throttle learns and their redundant calculation do not equal		Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Desired Throttle Position and its redundant calculation do not equal		Ignition State	Accessory, run or crank	Up/down timer 2,048 ms continuous, 0.5 down time multiplier	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Driver Intended Brake Torque Fault	P1B12	Detect a rolling count or protection value error in Driver Intended Brake Torque serial data. This is a plausibility test that will fail if there are enough X out of Y errors.	X of Y failure, or continuous criteria have been met for rolling count or protection errors for Driver Intended Brake Torque.			<p>Propulsion System is active</p> <p>KeBRKI_b_TrqSerialData FailEnbl == 1 Value of KeBRKI_b_TrqSerialData FailEnbl is: 1 . (If 0, this test is disabled)</p> <p>Manufacturer Enable Counter is 0</p>	9 / 17 counts or 0.488 seconds continuous; 25 ms/count in main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Powertrain Control Module (HPC) 2 Requested MIL Illumination	P1E00	Monitors the HPC 2 MIL request message to determine when the HPC has detected a MIL illuminating fault.	HPC 2 Module Emissions-Related DTC set and module is requesting MIL	HPC 2 Module Emissions-Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Camshaft Actuator Solenoid Circuit Low– Bank 1	P2088	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 0.5 \Omega$ impedance between signal and controller ground	System supply voltage Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	20 failures out of 25 samples 250 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Camshaft Actuator Solenoid Circuit High – Bank 1	P2089	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	$\leq 0.5 \Omega$ impedance between signal and controller power	System supply Output driver is commanded on Ignition switch is in crank or run position	> 11.00 Volts	20 failures out of 25 samples 250 ms /sample, continuous	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Camshaft Actuator Solenoid Circuit Low – Bank 1	P2090	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p>	$\leq 0.5 \Omega$ impedance between signal and controller ground	<p>System supply voltage</p> <p>Output driver is commanded on</p> <p>Ignition switch is in crank or run position</p>	> 11.00 Volts	<p>20 failures out of 25 samples</p> <p>250 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Camshaft Actuator Solenoid Circuit High – Bank 1	P2091	Controller specific output driver circuit diagnoses the CAM phaser oil control valve solenoid high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between signal and controller power	<p>System supply voltage</p> <p>Output driver</p> <p>Ignition switch</p>	<p>> 11.00 Volts</p> <p>On</p> <p>Crank or Run</p>	<p>20 failures out of 25 samples</p> <p>250 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Post Catalyst Fuel Trim System Low Limit Bank 1 (Too Rich)	P2096	<p>Determines if the post catalyst O2 sensor based fuel control system is indicating a rich exhaust gas condition. If the rich condition is such that the control system utilizes all or most of its available low limit authority (low limit = -100% authority), then P2096 will set.</p> <p>The monitor can be calibrated to fail based on the Average Integral Offset % Authority, the Average Total Offset % Authority or both combined. The Average Total Offset metric consists of the average of the Integral Offset+ Proportional Offset.</p> <p>Note: When the post catalyst O2 voltage is too rich, the post catalyst O2 integral and proportional offset control is decreased (negative % authority). This applies a lean bias to fuel control in an attempt to counteract the rich condition. A perfectly balanced control system (no rich or lean bias required) is represented by integral</p>	<p>The Average Integral Offset % Authority</p> <p>AND</p> <p>The Average Total Offset % Authority</p> <p>(Note: any value greater than or equal to +100% effectively nullifies the Average Total Offset % Authority criteria)</p> <p>High Vapor Feature: The diagnostic is at risk of reporting a false fail when excessively High Vapor (HV) conditions are present. This HV condition is indicated when the purge valve is open AND percent vapor is $\geq 18\%$ for ≥ 5.0 seconds AND the % Authority metric is approaching the failure threshold.</p> <p>Diagnosis resumes if the purge valve is closed OR the percent vapor is $\leq 14\%$ for ≥ 5.0 seconds. This was done to minimize disabling the diagnostic for longer than necessary.</p>	<p>$\leq -99.0\%$</p> <p>$\leq -50.0\%$</p> <p>If the P2096 is actively failing then the Average Integral Offset must be $> -99.0\%$ and the Average Total Offset must be $> -50.0\%$ for the diagnostic to report a pass.</p>	<p>The diagnostic is enabled during: Deceleration Idle Cruise Light Acceleration Heavy Acceleration</p> <p>Ambient Air Pressure Engine AirFlow Intake Manifold Pressure Induction Air Temperature Start-up Coolant Temp.</p> <p>PTO Intrusive diag. fuel control Ethanol Estimation in Progress</p> <p>O2 Heater Learned Resistance</p> <p>Long Term Secondary Fuel Trim Enabled for (see "Long Term Secondary Fuel Trim Enable Criteria" in Supporting Tables)</p> <p>High Vapor Conditions</p> <p>Green Cat System Condition</p>	<p>No No Yes Yes Yes</p> <p>≥ 70 kPa ≥ 0.0 g/s $\leq 10,000.0$ ≥ 10 kPa ≤ 255 ≥ -20 deg. C ≤ 150 ≥ -20 deg. C (or OBD Coolant Enable Criteria = TRUE)</p> <p>Not Active Not Active Not Active</p> <p>= Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>≥ 0.1 seconds</p> <p>Not Present</p> <p>= Not Valid, Green Cat System condition is considered valid until the</p>	<p>Frequency: Continuous Monitoring in 100ms loop.</p> <p>The Integral and Total Offset % Authority metrics are sampled every 100ms and an average is calculated every 100.0 seconds (1,000 samples) before comparing to their respective failure thresholds.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		and proportional offset values of "0" (i.e. 0% authority) and a post catalyst O2 sensor that is within its optimal operating range (neither rich nor lean).			No Fault Active for:	accumulated air flow is greater than 360,000 grams. Airflow accumulation is only enabled when estimated Cat temperature is above 600 Deg C and airflow is above 18 grams/sec. AmbientAirDefault AIR_System_FA Ethanol Composition Sensor_FA ECT_Sensor_FA EGRValveCircuit_FA EGRValvePerformance_FA IAT_SensorFA CamSensorAnyLocationFA EvapEmissionSystem_FA EvapFlowDuringNonPurge_FA FuelTankPressureSnsrCkt_FA EvapPurgeSolenoidCircuit_FA EvapSmallLeak_FA EvapVentSolenoidCircuit_FA FuelInjectorCircuit_FA MAF_SensorFA MAF_SensorTFTKO MAP_SensorFA MAP_EngineVacuumStatus EngineMisfireDetected_FA A/F Imbalance Bank1 O2S_Bank_1_Sensor_1_FA		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>For the cells identified as enabled (i.e. those containing a "Yes" at the beginning of the Enable Conditions column), the minimum accumulated samples required before the fuel control metric is considered usable for that cell (1 sample = 100ms):</p> <p>Deceleration Idle Cruise Light Acceleration Heavy Acceleration</p> <p>(Note: A value in any of the above operating "cells" that is an order of magnitude (or more) higher than other cells is an indication that the diagnostic is not capable of diagnosing in that cell).</p>	<p>O2S_Bank_1_Sensor_2_FA</p> <p>300 300 300 300 300</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Post Catalyst Fuel Trim System High Limit Bank 1 (Too Lean)	P2097	<p>Determines if the post catalyst O2 sensor based fuel control system is indicating a lean exhaust gas condition. If the lean condition is such that the control system utilizes all or most of its available high limit authority (high limit = 100% authority), then P2097 will set.</p> <p>The monitor can be calibrated to fail based on the Average Integral Offset % Authority, the Average Total Offset % Authority or both combined. The Average Total Offset metric consists of the average of the Integral Offset+ Proportional Offset.</p> <p>Note: When the post catalyst O2 voltage is too lean, the post catalyst O2 integral and proportional offset control is increased (positive % authority). This applies a rich bias to fuel control in an attempt to counteract the lean condition. A perfectly balanced control system (no rich or lean bias required) is represented by integral</p>	<p>The Average Integral Offset % Authority</p> <p>AND</p> <p>The Average Total Offset % Authority</p> <p>(Note: any value less than or equal to -100% effectively nullifies the Average Total Offset % Authority criteria)</p> <p>High Vapor Feature: The diagnostic is at risk of reporting a false fail when excessively High Vapor (HV) conditions are present. This HV condition is indicated when the purge valve is open AND percent vapor is >= 18 % for >= 5.0 seconds.</p> <p>Diagnosis resumes if the purge valve is closed OR the percent vapor is <= 14 % for >= 5.0 seconds. This was done to minimize disabling the diagnostic for longer than necessary.</p>	<p>>= 99.0 %</p> <p>>= 50.0 %</p> <p>If the P2097 is actively failing then the Average Integral Offset must be < 99.0 % and the Average Total Offset must be < 50.0 % for the diagnostic to report a pass.</p>	Same as P2096	Same as P2096	<p>Frequency: Continuous Monitoring in 100ms loop.</p> <p>The Integral and Total Offset % Authority metrics are sampled every 100ms and an average is calculated every 100.0 seconds (1,000 samples) before comparing to their respective failure thresholds.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		and proportional offset values of "0" (i.e. 0% authority) and a post catalyst O2 sensor that is within its optimal operating range (neither rich nor lean).						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Throttle Actuator Position Performance	P2101	1) Detect a throttle positioning error. This is determined if the difference between measured throttle position and modeled throttle position is greater than a threshold or less than a threshold. This diagnostic only runs when the engine is running and the ignition voltage is high enough and there is not an ignition voltage failure and the throttle position minimum learn is not active and the throttle is being controlled 2) Throttle control is driving the throttle in the incorrect direction. This is determined if the throttle position is greater than a threshold percent and the powertrain relay voltage is high enough and the throttle position minimum learn is active 3) Throttle control exceeds the reduced power limit. This is determined if the throttle position is greater and a threshold and the powertrain relay voltage is high enough and reduced power is active.	Difference between measured throttle position and modeled throttle position > OR Difference between modeled throttle position and measured throttle position >	10.00 percent 10.00 percent	Run/Crank voltage TPS minimum learn is not active and Throttle is being Controlled AND (Engine Running or Ignition Voltage) OR Ignition Voltage Ignition voltage failure is false (P1682)	> 6.41 Volts > 5.50 Volts > 8.41 Volts	15 counts; 12.5 ms/count in the primary processor	Type A, 1 Trips
			Throttle Position >	36.00 percent	Powertrain Relay voltage TPS minimum learn active	> 6.41 Volts = TRUE	11 counts; 12.5 ms/count in the primary processor	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Accelerator Pedal Position (APP) Sensor 1 Lo	P2122	Detects a continuous or intermittent short low or open in the APP sensor #1 by monitoring the APP1 sensor percent Vref and failing the diagnostic when the APP1 percent Vref is too low. This diagnostic only runs when battery voltage is high enough. Detects a continuous or intermittent short low or open in the APP sensor #1 on the Main processor.	APP1 percent Vref	< 0.4625 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	19 / 39 counts; or 14 counts continuous; 12.5 ms/count in the main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Accelerator Pedal Position (APP) Sensor 1 Hi	P2123	Detects a continuous or intermittent short high in the APP sensor #1 by monitoring the APP1 sensor percent Vref and failing the diagnostic when the APP1 percent Vref is too high. This diagnostic only runs when battery voltage is high enough. Detect a continuous or intermittent short high in the APP sensor #1 on the Main processor.	APP1 percent Vref >	4.7500 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P06A3	19 / 39 counts; or 14 counts continuous; 12.5 ms/count in the main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Accelerator Pedal Position (APP) Sensor 2 Lo	P2127	Detects a continuous or intermittent short low or open in the APP sensor #2 by monitoring the APP2 sensor percent Vref and failing the diagnostic when the APP2 percent Vref is too low. This diagnostic only runs when battery voltage is high enough. Detects a continuous or intermittent short low or open in the APP sensor #2 on the Main processor.	APP2 percent Vref <	0.3250 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P0697	19 / 39 counts; or 14 counts continuous; 12.5 ms/count in the main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Accelerator Pedal Position (APP) Sensor 2 Hi	P2128	Detects a continuous or intermittent short high in the APP sensor #2 by monitoring the APP2 sensor percent Vref and failing the diagnostic when the APP2 percent Vref is too high. This diagnostic only runs when battery voltage is high enough. Detect a continuous or intermittent short high in the APP sensor #2 on the Main processor.	APP2 percent Vref >	2.6000 % Vref	Run/Crank voltage No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts P0697	19 / 39 counts; or 14 counts continuous; 12.5 ms/count in the main processor	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Throttle Position (TP) Sensor 1-2 Correlation	P2135	Detect a continuous or intermittent correlation fault between TPS sensors #1 and #2 on Main processor. 1.) The diagnostic monitors the difference in position between TPS1 and the TPS2 and fails the diagnostic when the difference is too high. This diagnostic only runs when the battery voltage is high enough. 2.) The diagnostic monitors the difference in reference voltage between normalized min TPS1 and the normalized min TPS2 and fails the diagnostic when the difference is too high. This diagnostic only runs when the battery voltage is high enough. Detects a continuous or intermittent correlation fault between TPS sensors #1 and #2 on Main processor	Difference between TPS1 displaced and TPS2 displaced >	6.797 % offset at min. throttle position with a linear threshold to 9.720 % at max. throttle position	Run/Crank voltage No TPS sensor faults No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts (P0122, P0123, P0222, P0223) P06A3	79 / 159 counts; or 58 counts continuous; 3.125 ms/count in the main processor	Type A, 1 Trips
			Difference between (normalized min TPS1) and (normalized min TPS2) >	5.000 % Vref	Run/Crank voltage No TPS sensor faults No 5V reference error or fault for # 4 5V reference circuit	> 6.41 Volts (P0122, P0123, P0222, P0223) P06A3	79 / 159 counts; or 58 counts continuous; 3.125 ms/count in the main processor	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Accelerator Pedal Position (APP) Sensor 1-2 Correlation	P2138	Detect a continuous or intermittent correlation fault between APP sensors #1 and #2 on Main processor. 1.) The diagnostic monitors the difference in position between APP1 and the APP2 and fails the diagnostic when the difference is too high. This diagnostic only runs when the battery voltage is high enough. 2.) The diagnostic also monitors the difference in reference voltage between normalized min APP1 and the normalized min APP2 and fails the diagnostic when the difference is too high. This diagnostic only runs when the battery voltage is high enough. Detects a continuous or intermittent correlation fault between APP sensors #1 and #2 on Main processor	Difference between APP1 displaced and APP2 displaced >	5.000 % offset at min. pedal position with a linear threshold to 10.001 % at max. pedal position	Run/Crank voltage No APP sensor faults No 5V reference errors or faultst for # 3 & # 4 5V reference circuits	> 6.41 Volts (P2122, P2123,P2127, P2128) (P06A3, P0697)	19 / 39 counts intermittent; or 15 counts continuous, 12.5 ms/count in the main processor	Type A, 1 Trips
			Difference between (normalized min APP1) and (normalized min APP2) >	5.000 % Vref	Run/Crank voltage No APP sensor faults No 5V reference errors or faultst for # 3 & # 4 5V reference circuits	> 6.41 Volts (P2122, P2123,P2127, P2128) (P06A3, P0697)	19 / 39 counts intermittent; or 15 counts continuous, 12.5 ms/count in the main processor	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 high side circuit shorted to ground	P2147	Controller specific output driver circuit diagnoses Injector 1 high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	25 amp >= through High Side Driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 1 high side circuit shorted to power	P2148	Controller specific output driver circuit diagnoses Injector 1 high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	 ≤ 1 volt between signal and controller power	Battery Voltage Engine Run Time	≥ 11 Volts ≥ 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 high side circuit shorted to ground	P2150	Controller specific output driver circuit diagnoses Injector 2 high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	25 amp >= through High Side Driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 2 high side circuit shorted to power	P2151	Controller specific output driver circuit diagnoses Injector 2 high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	<= 1 volt between signal and controller power	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 high side circuit shorted to ground	P2153	Controller specific output driver circuit diagnoses Injector 3 high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	25 amp >= through High Side Driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 3 high side circuit shorted to power	P2154	Controller specific output driver circuit diagnoses Injector 3 high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	<= 1 volt between signal and controller power	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 high side circuit shorted to ground	P2156	Controller specific output driver circuit diagnoses Injector 4 high sided driver for a short to ground failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	25 amp >= through High Side Driver	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Injector 4 high side circuit shorted to power	P2157	Controller specific output driver circuit diagnoses Injector 4 high sided driver for a short to power failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	<= 1 volt between signal and controller power	Battery Voltage Engine Run Time	>= 11 Volts >= 2 Seconds P062B not FA or TFTK	10.00 failures out of 20.00 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Vehicle Speed – Output Shaft Speed Correlation	P215B	Detect invalid vehicle speed source. This failure is set by two different conditions. Either the absolute difference between wheel speed vehicle speed and TOS vehicle speed is too high, or secure vehicle speed is not available.	The absolute difference between wheel speed vehicle speed and TOS vehicle speed greater than > OR Secure vehicle speed source is unavailable	6.21 mph		Time since first CAN activity > 0.5000 s Secure vehicle speed source is TOS vehicle speed or wheel speed vehicle speed Trans engaged state is equal to engaged.	400 / 800 counts for wheel speed correlation or 400 / 800 counts for TOS correlation; 25ms/count	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Minimum Throttle Position Not Learned	P2176	Detect when the throttle position minimum learn on the main processor is not learned. This diagnostic detects this by monitoring if the throttle position is greater than a threshold and the number of learn attempts is greater than a threshold. This diagnostic only runs when the battery voltage is high enough and the throttle position minimum learn is active. Throttle position sensors were not in the minmum learn window after multiple attempts to learn the minimum.	During TPS min learn on the Main processor, TPS percent Vref > AND Number of learn attempts >	0.5740 % Vref 10 counts	Run/Crank voltage TPS minimum learn is active No previous TPS min learn values stored in long term memory	> 6.41 Volts = TRUE	2.0 secs	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 1 / 2 Correlation	P2199	<p>Detects when the Intake Air Temperature (IAT) sensor and IAT2 sensor values do not correlate with each other. These two temperature sensors are both in the induction system, although they do have different sensor time constants and different positional relationships with components that produce heat. If these two temperature values differ by a large enough amount, the Intake Air Temperature 1 / 2 Correlation Diagnostic will fail.</p> <p>This diagnostic is enabled if the Powertrain Relay voltage is high enough.</p>	ABS (IAT - IAT2)	> 55.0 deg C	<p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>>= 11.0 Volts >= 0.9 seconds</p> <p>PowertrainRelayFault</p>	<p>40 failures out of 50 samples</p> <p>1 sample every 100 msec</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.	
Bank 1 Air- Fuel Ratio Imbalance	P219A	<p>This monitor determines if there is an Air Fuel Imbalance in the fueling system for a cylinder on a Bank 1. Detection is based on a the pre catalyst oxygen sensor voltage. The pre catalyst O2 voltage is used to generate a variance metric that represents the statistical variation of the O2 sensor voltage over a given engine cycle. This metric is proportional to the air-fuel ratio imbalance (variance is higher with an imbalance than without).</p> <p>The observed Variance is dependent on engine speed and load and is normalized by comparing it to a known "good system" result for that speed and load, and generating a Ratio metric.</p> <p>The Ratio metric is calculated by selecting the appropriate threshold calibration from a 17x17 table (see Supporting Table</p>	<p>Filtered Ratio ></p> <p>The Ratio metric is calculated by selecting the appropriate threshold calibration from a 17x17 table (see Supporting Table</p> <p>P219A Variance Threshold Bank1 Table) and subtracting it from the measured Variance. The result is then divided by a normalizer calibration from another 17 x 17 table (see Supporting Table</p> <p>P219A Normalizer Bank1 Table). This quotient is then multiplied by a quality factor calibration from a 17 x 17 table (see Supporting Table</p> <p>P219A Quality Factor Bank1 Table). This result is referred to as the Ratio. Note that the quality factor ranges between 0 and 1 and represents robustness to false diagnosis in the current operating region. Regions with low quality factors are not used.</p>	0.60	<p>If the diagnostic has reported a failure on the prior trip, the Filtered Ratio must fall below 0.51 in order to report a pass. This feature prevents the diagnostic from toggling between failing and passing when the Filtered Ratio remains near the initial failure threshold of 0.60 .</p>	<p>System Voltage</p> <p>Fuel Level</p> <p>Engine Coolant Temperature</p> <p>Cumulative engine run time</p> <p>Diagnostic enabled at Idle (regardless of other operating conditions)</p> <p>Engine speed range</p> <p>Engine speed delta during a short term sample period</p> <p>Mass Airflow (MAF) range</p> <p>Cumulative delta MAF during a short term sample period</p> <p>Filtered MAF delta between samples Note: first order lag filter coefficient applied to MAF = 0.050</p> <p>Air Per Cylinder (APC)</p> <p>APC delta during short term sample period</p>	<p>no lower than 10.0 Volts for more than 0.2 seconds</p> <p>> 10.0 percent AND no fuel level sensor fault</p> <p>> -20 deg. C (or OBD Coolant Enable Criteria = TRUE)</p> <p>> 0.0 seconds</p> <p>No</p> <p>800 to 10,000 RPM</p> <p>< 1,000 RPM</p> <p>0 to 1,000 g/s</p> <p>< 1,000 g/s</p> <p>< 1,000.00 g/s</p> <p>100 to 1,200 mg/cylinder</p> <p>< 1,000 mg/cylinder</p>	<p>Minimum of 1 test per trip, up to 8 tests per trip during RSR or FIR.</p> <p>The front O2 sensor voltage is sampled once per cylinder event. Therefore, the time required to complete a single test (when all enable conditions are met) decreases as engine speed increases. For example, 41.40 seconds of data is required at 1000 rpm while double this time is required at 500 rpm and half this time is required at 2000 rpm. This data is collected only when enable conditions are met, and as such significantly more operating time is required than is indicated above. Generally, a report will be</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>P219A Variance Threshold Bank1 Table) and subtracting it from the measured Variance. The result is then divided by a normalizer calibration from another 17 x 17 table (see Supporting Table P219A Normalizer Bank1 Table). This quotient is then multiplied by a quality factor calibration from a 17 x 17 table (see Supporting Table P219A Quality Factor Bank1 Table). This result is referred to as the Ratio. Note that the quality factor ranges between 0 and 1 and represents robustness to false diagnosis in the current operating region. Regions with low quality factors are not used.</p> <p>Finally, a EWMA filter is applied to the Ratio metric to generate the Filtered Ratio malfunction criteria metric. Generally, a normal system will result in a negative Filtered Ratio while a failing system will result in a positive Filtered</p>			<p>Filtered APC delta between samples Note: first order lag filter coefficient applied to APC = 1.000</p> <p>Spark Advance</p> <p>Throttle Area (percent of max)</p> <p>Intake Cam Phaser Angle</p> <p>Exhaust Cam Phaser Angle</p> <p>Quality Factor (QF) QF calibrations are located in a 17x17 lookup table versus engine speed and load (see Supporting Table P219A Quality Factor Bank1 Table). QF values less than "1" indicate that we don't have 4sigma/2sigma robustness in that region. The quality of the data is determined via statistical analysis of Variance data.</p> <p>Fuel Control Status Closed Loop and Long Term FT Enabled for:</p>	<p>< 100.00 percent</p> <p>0 to 100 degrees</p> <p>0 to 200 percent</p> <p>0 to 100 degrees</p> <p>0 to 100 degrees</p> <p>>= 0.89</p> <p>>= 1.2 seconds (Please see "Closed Loop Enable Clarification" and "Long Term FT Enable Criteria" in Supporting Tables)</p>	<p>made within 5 minutes of operation.</p> <p>For RSR or FIR, 16 tests must complete before the diagnostic can report.</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>Ratio.</p> <p>The range of the Filtered Ratio metric is application specific since both the emissions sensitivity and relationship between imbalance and the Variance metric are application specific.</p> <p>Some applications may need to command a unique cam phaser value before performing the above calculations since cam phasing has been shown to have an impact on overall signal quality. This application Does Not Use this feature.</p>			<p>Device Control</p> <p>AIR pump</p> <p>CASE learn</p> <p>EGR</p> <p>EVAP</p> <p>Engine Over Speed Protection</p> <p>Idle speed control</p> <p>PTO</p> <p>Injector base pulse width</p> <p>O2 learned htr resistance</p> <p>Rapid Step Response (RSR):</p> <p>RSR will trigger if the Ratio result from the last test is</p> <p>AND it exceeds the last Filtered ratio by</p> <p>Once triggered, the filtered ratio is reset to:</p> <p>Fast Initial Response (FIR):</p> <p>FIR will trigger when an NVM reset or code clear occurs.</p> <p>Once triggered, the filtered ratio is reset to:</p> <p>No Fault Active for:</p>	<p>Not active</p> <p>Not on</p> <p>Not active</p> <p>Not intrusive</p> <p>Not intrusive</p> <p>Not Active</p> <p>Normal</p> <p>Not Active</p> <p>Above min pulse limit</p> <p>= Valid (the O2 heater resistance has learned since NVM reset)</p> <p>>= 0.60</p> <p>>= 0.30</p> <p>0.00</p> <p>0.00</p> <p>EngineMisfireDetected_F A MAP_SensorFA MAF_SensorFA ECT_Sensor_FA</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
						TPS_ThrottleAuthorityDef aulted FuelInjectorCircuit_FA AIR System FA EvapExcessPurgePsbl_F A CamSensorAnyLocationF A FuelTrimSystemB1_FA O2S_Bank_1_Sensor_1_ FA O2S_Bank_1_Sensor_2_ FA WRAF_Bank_1_FA		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Performance (naturally aspirated)	P2227	<p>Detects a performance failure in the Barometric Pressure (BARO) sensor, such as when a BARO value is stuck in range.</p> <p>If the engine has been off for a sufficient amount of time, the pressure values in the induction system will have equalized. The BARO sensor value is checked to see if it is within the normal expected atmospheric pressure range. If it is not, then the BARO performance diagnostic will fail.</p> <p>When the engine is running, there is an estimate of barometric pressure that is determined with the Manifold Pressure (MAP) sensor, throttle position, engine air flow and engine speed. If the BARO value from the sensor is not similar to this barometric pressure estimate, then the BARO performance diagnostic will fail.</p>	<p><u>Engine Running:</u></p> <p>Difference between Baro Pressure reading and Estimated Baro when distance since last Estimated Baro update</p> <p>OR</p> <p>Difference between Baro Pressure reading and Estimated Baro when distance since last Estimated Baro update</p>	<p>> 15.0 kPa</p> <p><= 1.06 miles</p> <p>> 20.0 kPa</p> <p>> 1.06 miles</p>	No Active DTCs:	<p>AmbPresSnsrCktFA</p> <p>IAT_SensorFA</p> <p>MAF_SensorFA</p> <p>AfterThrottlePressureFA</p> <p>TPS_FA</p> <p>TPS_Performance_FA</p> <p>VehicleSpeedSensor_FA</p>	<p>320 failures out of 400 samples</p> <p>1 sample every 12.5 msec</p>	Type B, 2 Trips
			<p><u>Engine Not Rotating:</u></p> <p>Barometric Pressure</p> <p>OR</p> <p>Barometric Pressure</p>	<p>< 50.0 kPa</p> <p>> 115.0 kPa</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Engine is not rotating</p> <p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>> 10.0 seconds</p> <p>EngineModeNotRunTimer Error</p> <p>MAP_SensorCircuitFA</p> <p>AAP_SnsrCktFA</p> <p>MAP_SensorCircuitFP</p> <p>AAP_SnsrCktFP</p>	<p>4 failures out of 5 samples</p> <p>1 sample every 12.5 msec</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Circuit Low (non-boosted applications, Gen III)	P2228	Detects a continuous short to ground in the Barometric Pressure (BARO) signal circuit by monitoring the BARO sensor output voltage and failing the diagnostic when the BARO voltage is too low. The BARO sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	BARO Voltage	< 39.3 % of 5 Volt Range (This is equal to 50.0 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Circuit High (non-boosted applications, Gen III)	P2229	Detects a continuous short to power or open circuit in the Barometric Pressure (BARO) signal circuit by monitoring the BARO sensor output voltage and failing the diagnostic when the BARO voltage is too high. The BARO sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	BARO Voltage	> 90.0 % of 5 Volt Range (This is equal to 115.0 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Circuit Intermittent	P2230	<p>Detects a noisy or erratic signal in the barometric pressure (BARO) circuit by monitoring the BARO sensor and failing the diagnostic when the BARO signal has a noisier output than is expected.</p> <p>When the value of BARO in kilopascals (kPa) is determined, a delta is calculated between the current reading and the previous reading. The absolute value of these deltas is summed over a number of BARO readings. The result of this summation is called a "string length".</p> <p>Since the BARO signal is anticipated to be relatively smooth, a string length of a particular magnitude indicates a noisy or erratic BARO signal. The diagnostic will fail if the string length is too high.</p>	<p>String Length</p> <p>Where: "String Length" = sum of "Diff" calculated over</p> <p>And where: "Diff" = ABS(current BARO reading - BARO reading from 12.5 milliseconds previous)</p>	<p>> 100 kPa</p> <p>80 consecutive BARO readings</p>			<p>4 failures out of 5 samples</p> <p>Each sample takes 1.0 seconds</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Signal Stuck Lean Bank 1 Sensor 2	P2270	<p>The P2270 diagnostic is the first in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor is stuck in a normal lean voltage range and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic increases the delivered fuel while monitoring the sensor signal and the accumulated mass air flow.</p> <p>This fault is set if the secondary O2 sensor does not achieve the required rich voltage before the accumulated mass air flow threshold is reached.</p>	<p>Post O2 sensor signal</p> <p>AND</p> <p>The Accumulated mass air flow monitored during the Stuck Lean Voltage Test</p>	<p>< 760 mvolts</p> <p>> 60 grams</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013A, P013B, P013E, P013F, P2270 or P2271</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Pedal position</p> <p>Engine Airflow</p> <p>Closed loop integral Closed Loop Active</p> <p>Evap</p> <p>Ethanol Estimation in Progress</p> <p>Post fuel cell</p> <p>Crankshaft Torque</p> <p>EGR Intrusive diagnostic All post sensor heater delays O2S Heater (post sensor) on Time</p> <p>Predicted Catalyst temp Fuel State</p> <p>=====</p>	<p>is above 18.0 grams/sec.</p> <p>= False</p> <p>= False</p> <p>≤ 10.0 %</p> <p>2.0 ≤ gps ≤ 20.0</p> <p>0.92 ≤ C/L Int ≤ 1.08 = TRUE (Please see “Closed Loop Enable Clarification” in Supporting Tables).</p> <p>not in control of purge</p> <p>= Not Active (Please see “Ethanol Estimation in Progress” in Supporting Tables).</p> <p>= Enabled, refer to Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests for additional info. < 125.0 Nm</p> <p>= not active</p> <p>= not active</p> <p>≥ 30.0 sec</p> <p>550 ≤ °C ≤ 910 = DFCO possible</p> <p>=====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>All of the above met for at least 0.0 seconds, and then check the following</p> <p>Engine Speed to initially enable test Engine Speed range to keep test enabled (after initially enabled)</p> <p>Vehicle Speed to initially enable test Vehicle Speed range to keep test enabled (after initially enabled)</p> <p>=====</p> <p>All of the above met for at least 2.0 seconds, and then the Force Cat Rich intrusive stage is requested.</p> <p>=====</p> <p>During Stuck Lean test the following must stay TRUE or the test will abort: Commanded Fuel Crankshaft Torque</p>	<p>1,050 ≤ RPM ≤ 3,500</p> <p>1,000 ≤ RPM ≤ 3,650</p> <p>40.4 ≤ MPH ≤ 77.7</p> <p>36.0 ≤ MPH ≤ 80.8</p> <p>0.96 ≤ EQR ≤ 1.08 < 110.0 Nm</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Signal Stuck Rich Bank 1 Sensor 2	P2271	<p>The P2271 diagnostic is the fourth in a sequence of six intrusive secondary O2 monitors which include DTCs P2270, P013E, P013A, P2271, P013F, & P013B. This DTC determines if the secondary O2 sensor is stuck in a normal rich voltage range and thereby can no longer be used for secondary O2 sensor fuel control or for catalyst monitoring. This diagnostic commands fuel cut off while monitoring the sensor signal and the accumulated mass air flow.</p> <p>This fault is set if the secondary O2 sensor does not achieve the required lean voltage before the accumulated mass air flow threshold is reached.</p>	<p>Post O2 sensor signal</p> <p>AND</p> <p>The Accumulated mass air flow monitored during the Stuck Rich Voltage Test</p>	<p>> 100 mvolts</p> <p>> 6.0 grams</p>	<p>No Active DTC's</p> <p>B1S2 DTC's Not Active this key cycle</p> <p>System Voltage Learned heater resistance</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted ECT_Sensor_FA IAT_SensorFA MAF_SensorFA MAP_SensorFA AIR System FA FuelInjectorCircuit_FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EngineMisfireDetected_FA Ethanol Composition Sensor FA O2S_Bank_1_TFTKO O2S_Bank_2_TFTKO</p> <p>P013A, P013B, P013E, P013F or P2270</p> <p>> 10.0 Volts = Valid (the heater resistance has learned since NVM reset, see enable conditions for "HO2S Heater Resistance DTC's")</p> <p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S2, B2S2 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow</p>	<p>Frequency: Once per trip Note: if NaPOPD_b_Res etFastRespFunc = FALSE for the given Fuel Bank OR NaPOPD_b_Rap idResponseActiv e = TRUE, multiple tests per trip are allowed.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Fuel State</p> <p>DTC's Passed</p> <p>=====</p> <p>After above conditions are met: DFCO mode is continued (w/o driver initiated pedal input).</p>	<p>is above 18.0 grams/sec.</p> <p>= False</p> <p>= False</p> <p>= DFCO possible</p> <p>= P2270</p> <p>= P013E</p> <p>= P013A</p> <p>=====</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SIDI High Pressure Pump Performance	P228C	This DTC determines if the high pressure pump is not able to maintain target pressure. The fault is set if the measured fuel rail pressure is lower than desired fuel pressure by a value that can impact emission and drivability for a number of pump events.	Fuel Pressure Error (Desired Pressure - Measure Pressure)	>= P228C P2C1F - High Pressure Pump Control (HPC) fail threshold of pressure too low Mpa (see supporting tables)	High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control commanded pressure is false and Device control pump ckt enabled on is false and	True >= 11 Volts > 0.300 MPa Enabled when a code clear is not active or not exiting device control Engine is not cranking	Positive Pressure Error - 10.00 second failures out of 12.50 second samples	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Engine movement detected is true and Manufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active Barometric Pressure Inlet Air Temp Fuel Temp	>= 70.0 KPA >= -10.0 degC -10 <=Temp degC <= 132		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SIDI High Pressure Pump Performance	P228D	This DTC determines if the high pressure pump is delivering high pressure that desired pressure. The fault is set if the measured fuel rail pressure is higher than desired fuel pressure by a value that can impact emission and drivability for a number of pump events.	Fuel Pressure Error (Desired Pressure - Measure Pressure)	<= P228D P2C20 - High Pressure Pump Control (HPC) fail threshold for pressure too high Mpa (see supporting tables)	High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control commanded pressure is false and Device control pump ckt	True ≥ 11 Volts > 0.300 MPa Enabled when a code clear is not active or not exiting device control Engine is not cranking	Negative Pressure Error - 10.00 second failures out of 12.50 second samples	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					enabled on is false and Engine movement detected is true andManufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active Barometric Pressure Inlet Air Temp Fuel Temp	>= 70.0 KPA >= -10.0 DegC -10 <= Temp degC <= 132		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #1 CIRCUIT LOW	P2300	Diagnoses Cylinder #1 Ignition Control (EST) output driver circuit for a Short to Ground fault. Controller specific output driver circuit diagnoses the low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 100 \Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #1 CIRCUIT High	P2301	Diagnoses Cylinder #1 Ignition Control (EST) output driver circuit for a Short to Power fault. Controller specific output driver circuit diagnoses the low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	$\leq 100 \Omega$ impedance between signal and controller power	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #2 CIRCUIT Low	P2303	Diagnoses Cylinder #2 Ignition Control (EST) output driver circuit for a Short to Ground fault. Controller specific output driver circuit diagnoses the low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 100 \Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #2 CIRCUIT High	P2304	Diagnoses Cylinder #2 Ignition Control (EST) output driver circuit for a Short to Power fault	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 100 \Omega$ impedance between signal and controller power	<p>Engine running</p> <p>Ignition Voltage</p>	> 11.0 Volts	<p>50 Failures out of 63 Samples</p> <p>100 msec rate</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #3 CIRCUIT Low	P2306	Diagnoses Cylinder #3 Ignition Control (EST) output driver circuit for a Short to Ground fault. Controller specific output driver circuit diagnoses the low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 100 \Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #3 CIRCUIT High	P2307	Diagnoses Cylinder #3 Ignition Control (EST) output driver circuit for a Short to Power fault	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 100 \Omega$ impedance between signal and controller power	<p>Engine running</p> <p>Ignition Voltage</p>	> 11.0 Volts	<p>50 Failures out of 63 Samples</p> <p>100 msec rate</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #4 CIRCUIT Low	P2309	Diagnoses Cylinder #4 Ignition Control (EST) output driver circuit for a Short to Ground fault. Controller specific output driver circuit diagnoses the low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 100 \Omega$ impedance between signal and controller ground	Engine running Ignition Voltage	> 11.0 Volts	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
IGNITION CONTROL #4 CIRCUIT High	P2310	Diagnoses Cylinder #4 Ignition Control (EST) output driver circuit for a Short to Power fault	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 100 \Omega$ impedance between signal and controller power	<p>Engine running</p> <p>Ignition Voltage</p>	> 11.0 Volts	<p>50 Failures out of 63 Samples</p> <p>100 msec rate</p>	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Control Open Circuit (ELCP Sealed Fuel System)	P2400	Controller specific output driver circuit diagnoses the leak detection pump low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200\text{ K } \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Control Circuit Low (ELCP Sealed Fuel System)	P2401	Controller specific output driver circuit diagnoses the leak detection pump low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.	$\leq 0.5 \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Control Circuit High (ELCP Sealed Fuel System)	P2402	<p>Controller specific output driver circuit diagnoses the leak detection pump low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>If the P2402 is active, an intrusive test is performed with the pump commanded on for 15 seconds.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p>	$\leq 0.5 \Omega$ impedance between output and controller power			<p>20 failures out of 25 samples</p> <p>250 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Switching Valve Control Open Circuit (ELCP Sealed Fuel System)	P2418	Controller specific output driver circuit diagnoses the switching valve low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\geq 200\text{ K } \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Switching Valve Control Circuit Low (ELCP Sealed Fuel System)	P2419	Controller specific output driver circuit diagnoses the switching valve low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	$\leq 0.5 \Omega$ impedance between output and controller ground			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Switching Valve Control Circuit High (ELCP Sealed Fuel System)	P2420	Controller specific output driver circuit diagnoses the switching valve low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds. If the P2420 is active, an intrusive test is performed with the switching valve commanded on for 15 seconds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.	$\leq 0.5 \Omega$ impedance between output and controller power			20 failures out of 25 samples 250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EVAP System Vent Valve Stuck Closed (ELCP Sealed Fuel System)	P2422	<p>This DTC detects a Diurnal Control Valve (DCV) that is stuck closed. There are two ways to run this diagnostic depending on the amount of pressure or vacuum in the fuel tank system.</p> <p>Fuel Tank Venting Section</p> <p>The DCV stuck closed diagnostic is performed in either the fuel tank venting or EVAP leak check sections. If there is a sufficient amount of pressure or vacuum in the fuel tank then the DCV stuck closed diagnostic will be performed in the fuel tank venting section by monitoring the change in the FTP sensor when the DCV is commanded open.</p> <p>In the fuel tank venting section, the ELCP vacuum pump is off, ELCP switching valve is in the vent position, and the DCV is open. After the DCV is commanded open, the FTP sensor is monitored for a change in pressure or vacuum</p>	<p>When sufficient pressure or vacuum exists in the fuel tank system</p> <p>When the Fuel Tank Pressure (FTP) sensor indicates a pressure or a vacuum</p> <p>With the DCV commanded opened, if the change in the FTP sensor reading is after then the DCV is stuck closed and the DTC fails.</p> <p>When no pressure or vacuum exists in the fuel tank system</p> <p>When the FTP sensor indicates a pressure or a vacuum</p> <p>With the DCV commanded opened, the ELCP switching valve in the pump position and the ELCP vacuum pump commanded on, if the leak between result minus the ELCP pressure sensor (gauge) vacuum reading is after then the DCV is stuck</p>	<p>> 697 Pa < -697 Pa.</p> <p>< 249 Pa 10 seconds</p> <p>< 697 Pa > -697 Pa.</p> <p>< 300 Pa 5 seconds</p>	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p> <p>Min fuel level slosh</p> <p>Max fuel level slosh</p> <p>Key up during test</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p> <p>≥ 190 % ≤ 200 %</p>	<p>Up to once per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>and compared to a threshold. Changes larger than the threshold indicate the DCV opened and a pass is reported for P2422.</p> <p>The DCV is closed and the pressure or vacuum in the fuel tank is allowed to stabilize for a period of time. A new fuel tank pressure or vacuum starting level is established before transitioning to the next test section.</p> <p>If no change in fuel tank pressure or vacuum is detected within a period of time after the DCV is commanded open, then a fail is reported for P2422. The DCV is commanded closed and the ELCP EVAP diagnostic test sequence is complete.</p> <p>If the DCV stuck closed diagnostic passes in the fuel tank venting section then the diagnostic is skipped in the EVAP leak check section.</p> <p>The DCV stuck closed diagnostic is performed</p>	closed and the DTC fails.		<p>Refueling request button pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>0.5 seconds</p> <p>FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145D P1462 P2421 P2450 P24B9</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>during the EVAP leak check section when there is not sufficient pressure or vacuum in the fuel tank. A short period of time after the start of the EVAP leak check section, the ELCP pressure sensor gauge calculation is compared to the leak between the ELCP vacuum pump and DCV result. With a properly functioning DCV, the ELCP pressure sensor gauge calculation vacuum level should drop when the DCV opens and not be close to the previous results a short time later.</p> <p>EVAP Leak Check Section</p> <p>The DCV stuck closed diagnostic is performed during the EVAP leak check section when there is not sufficient pressure or vacuum in the fuel tank. A short period of time after the EVAP leak check section starts, the ELCP pressure sensor gauge calculation is compared to the leak between result. If the DCV is stuck closed</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>then the vacuum will be greater than or close to the leak between result and a fail is reported for P2422.</p> <p>A pass is reported for P2422 if the vacuum level is sufficiently below the leak between result. The ELCP EVAP diagnostic test sequence will be complete if a failure is detected.</p>						

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
ELCP Switching Valve Control Performance (ELCP Sealed Fuel System)	P2450	<p>This DTC detects a ELCP switching valve that is stuck.</p> <p>After the 1st reference vacuum measurement is complete, the ELCP switching valve transitions to the pump position. With a sealed system and a correctly functioning ELCP switching valve there will be an initial vacuum drop followed by a vacuum increase.</p> <p>The ELCP switching valve performance diagnostic compares the change (either a decrease or increase) from the 1st reference vacuum measurement to a threshold. If the change is less than the threshold then a fail is reported for P2450. If a failure is detected then the ELCP EVAP diagnostic test sequence is complete.</p>	When the ELCP vacuum pump is commanded on and the ELCP switching valve transitions from vent to pump position, if the difference between the 1st 0.020" orifice reference vacuum measurement and the ELCP pressure sensor (gauge) vacuum reading is after then the ELCP switching value is stuck and the DTC fails.	< 400 Pa 5 seconds	<p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p>	<p>Up to once per trip, for each required wake-up event</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Min fuel level slosh Max fuel level slosh Key up during test Refueling request button pressed Service bay test active Device control exceeds No Active DTC's	$\geq 190\%$ $\leq 200\%$ 0.5 seconds FuelLevelDataFault IAT_SensorFA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCP_Circuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA		
					No Active DTC's TFTKO	P043E P043F P0451 P145C P145D P1462 P2422 P24B9		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
EGR Cooler Efficiency (Performance)	P2457	<p>Diagnose EGR Cooler Heat Transfer Efficiency.</p> <p>The efficiency of the EGR cooler is determined by deciding the temperature drop of the EGR gasses before to after the EGR cooler relative to the coolant's ability to absorb the heat. If the cooler is not removing an acceptable amount of heat relative to what it should be able to remove the difference between the EGR gas temperature before the cooler relative to the Coolant temperature, the cooler is determined to be faulted.</p> <p>Diagnose EGR Cooler Heat Transfer Efficiency.</p>	The ECM monitors the heat transfer efficiency from the exhaust gas to the coolant. if the efficiency drops below a calibrated level, the fault is set.	<p>Calculated instantaneous efficiency:</p> <p>[((Up Stream temp - Down Stream temp) / (Up Stream temp - Coolant temp)) % + EGR Efficiency Flow Offset]</p> <p>SUM over 700 samples:</p> <p>Determine Average efficiency:</p> <p>Summation efficiency / 700 samples</p> <p>Fail Threshold:</p> <p>< 80.00 % efficient</p>	<p>Ignition switch</p> <p>System supply voltage</p> <p>Up stream exhaust gas temperature</p> <p>RPM</p> <p>BARO</p> <p>Ambient Temperature</p> <p>Coolant Temperature</p> <p>No Active DTCs</p>	<p>Crank or Run</p> <p>> 11.00 Volts</p> <p>> 200 C < 370 C</p> <p>> 1,100 RPM < 4,000 RPM</p> <p>> 70 kPa</p> <p>> -12 C</p> <p>> 60.00 C AND < 125.00 C</p> <p>P041E, P041C, P041D, P041B, P040E, P040C, P040D, P040B, P0070, P0071, P0072, P0073, P2229, P2228, P222C, P222D, P0116, P0117, P0118, P0119, P111E, P0128, P0101, P0102, P0103, P010B, P010C, P010D, P0403, P0489, P0490, P0404, P0405, P0406, P042E, P1426, P1437, P0107, P0108, P00C7, P0106, P2228, P2229, P0237, P0238, P0016, P0017, P0018, P0019, P0335, P0336, P0261, P0262, P0264, P0265, P0266, P0267, P0270, P0271, P0273, P0274, P0276, P0277, P0279, P0280, P0282, P0283, P0201, P0202,</p>	<p>700 samples</p> <p>100 ms /sample, continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
						P0203, P0204, P0205, P0206, P0207, P0208, P2147, P2148, P2150, P2151, P2153, P2154, P2156, P2157, P216B, P216C, P216E, P216F, P217B, P217C, P217E, P217F, P012B, P012C, P012D, P0300, P0351, P0352, P0353, P0354, P0355, P0356, P0357, P0358, P2300, P2301, P2303, P2304, P2306, P2307, P2309, P2310, P2312, P2313, P2315, P2316, P2318, P2319, P2321, P2322		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Pressure Sensor Circuit Performance Diagnostic (ELCP Sealed Fuel System)	P24B9	<p>ELCP Pressure Sensor Correlation Diagnostic</p> <p>The ambient check section</p> <p>The correlation of the ELCP pressure sensor to barometric pressure follows the ELCP vacuum pump stuck on diagnostic. For this diagnostic the ELCP vacuum pump is off, the DCV is closed, and the ELCP switching valve is in the vent position. The ELCP pressure sensor correlation is a X out of Y diagnostic that runs for a period of time.</p> <p>During this time, the ELCP pressure sensor reading is compared to the barometric pressure value which is based on the MAP sensor. Large deviations will increment the fail counter and a failure is reported for P24B9 when the fail count threshold is exceeded. The ELCP EVAP diagnostic test sequence is complete if a failure is detected. In a passing condition,</p>	<p>Propulsion System Not Active</p> <p>If the difference between the ELCP pressure sensor (absolute) reading and the barometric pressure value from the MAP sensor is then increment the fail counter. This diagnostic runs for</p>	<p>> 3,000 Pa</p> <p>14 seconds.</p>	<p>Propulsion System Not Active</p> <p>Propulsion system not active time</p> <p>Distance since assembly plant</p> <p>Drive distance</p> <p>Min baro</p> <p>Max baro</p> <p>Min fuel level</p> <p>Max fuel level</p> <p>ECT</p> <p>Min IAT</p> <p>Max IAT</p> <p>Time since last test when passing P0442/P0455</p> <p>Time since last test when failing P0442/P0455</p> <p>*****</p> <p>ELCP hardware can be powered by battery or powertrain relay. For this application the ELCP hardware is powered by battery</p> <p>Voltage</p> <p>*****</p> <p>Vehicle speed</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Propulsion system not active time</p> <p>Previous propulsion system active time</p> <p>Abort Conditions:</p>	<p>4.3 ≤ time ≤ 5.8 hours or 6.0 ≤ time ≤ 8.1 hours or 8.2 ≤ time ≤ 11.0 hours</p> <p>≥ 9.9 miles ≥ 0.1 miles ≥ 70 kPa ≤ 110 kPa ≥ 10 % ≤ 90 % ≤ 40 °C ≥ 4 °C ≤ 45 °C</p> <p>≥ 0 hours</p> <p>≥ 0 hours</p> <p>*****</p> <p>≥ 10 volts</p> <p>*****</p> <p>≤ 3 MPH</p> <p>0</p> <p>≥ 0 seconds</p> <p>≥ 0 seconds</p>	<p>Once or twice per trip with Propulsion System Not Active, for each required wake-up event</p> <p>First time diagnostic runs,</p> <p>50 failures out of 63 samples</p> <p>Second time diagnostic runs,</p> <p>50 failures out of 63 samples</p> <p>100 msec loop</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>P24B9 will not report a pass at this time since this diagnostic is run again during the final check section.</p> <p>The final check section</p> <p>The correlation of the ELCP pressure sensor to barometric pressure is the same as in the ambient check section. For this diagnostic the ELCP vacuum pump is off, the DCV is closed, and the ELCP switching valve is in the vent position. The ELCP pressure sensor correlation is a X out of Y diagnostic that runs for a period of time.</p> <p>During this time, the ELCP pressure sensor reading is compared to the barometric pressure value which is based on the MAP sensor. Large deviations will increment the fail counter and a failure is reported for P24B9 when the fail count threshold is exceeded. The ELCP EVAP diagnostic test sequence is complete if a failure is detected. When the sample</p>	<p>Propulsion System Active</p> <p>After a stabilization time</p>		<p>Min fuel level slosh Max fuel level slosh Key up during test Refueling request button pressed</p> <p>Service bay test active Device control exceeds</p> <p>No Active DTC's</p> <p>No Active DTC's TFTKO</p>	<p>≥ 190 % ≤ 200 %</p> <p>0.5 seconds</p> <p>FuelLevelDataFault IAT_Sensor_FA ECT_Sensor_FA VehicleSpeedSensor_FA AmbientAirDefault VentCircuit_FA ELCPCircuit_FA FTP_SensorCircuit_FA ELCP_PumpCircuit_FA ELCP_SwitchCircuit_FA VICM_WakeupDiag_FA VICM_WakeupDiag_TFT KO LostCommBCM_FA LostCommBusB_VICM_F A CommBusAOff_VICM_FA CommBusBOff_VICM_FA AccCktLo_FA ModuleOffTime_FA</p> <p>P043E P043F P0451 P145C P145D P145E P145F P1462 P2421 P2422 P2450</p>		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		counter exceeds the sample count threshold then a pass is reported for P24B9.	<p>of</p> <p>When a recent barometric pressure update has occurred within the last if the difference between the ELCP pressure sensor (absolute) reading and the barometric pressure value from the MAP sensor is then increment the fail counter.</p> <p>When a recent barometric pressure update has not occurred within the last if the difference between the ELCP pressure sensor (absolute) reading and the barometric pressure value from the MAP sensor is then increment the fail counter.</p>	<p>10 seconds.</p> <p>0.1 miles,</p> <p>> 15,000 Pa</p> <p>0.1 miles,</p> <p>> 20,000 Pa</p>	<p>Propulsion System Active</p> <p>Min baro Max baro Min OAT *****</p> <p>Conditions for corrected / estimated ambient temperature using OAT sensor to be valid = TRUE *****</p> <p>Vehicle not in assembly plant (value must = 0)</p> <p>Run/Crank Voltage Purge is not enabled</p> <p>Abort Conditions: Refueling request button pressed</p> <p>Device control exceeds</p> <p>FTP correlation diagnostic (P0451) is running</p> <p>Purge Low Flow diagnostic (P0497) is running</p> <p>Vent Restriction diagnostic (P0446) is running</p> <p>No Active DTC's</p>	<p>≥ 70 kPa ≤ 110 kPa ≥ 4 °C *****</p> <p>*****</p> <p>0</p> <p>≥ 11.0 volts</p> <p>0.5 seconds</p> <p>MAP_SensorFA EnginePowerLimited</p>	<p>When Propulsion System Active</p> <p>50 failures out of 63 samples</p> <p>100 msec loop</p>	

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No Active DTC's TFTKO	AmbientAirDefault OAT_EstAmbTemp_FA P0443 P0458 P0459 P145D P2400 P2401 P2402 P2418 P2419 P2420 P2450 P24BA P24BB		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Pressure Sensor Circuit Low Voltage (ELCP Sealed/ Vented Fuel System)	P24BA	<p>This DTC will detect an ELCP pressure sensor signal that is too low out of range.</p> <p>The ELCP pressure sensor circuit out of range diagnostic compares the raw sensor voltage to a lower voltage threshold. It is an X out of Y diagnostic that runs continuously anytime the controller is awake.</p> <p>If the sensor voltage is below the lower voltage threshold, the low fail counter then increments. If the low fail counter reaches its threshold then a fail is reported for P24BA DTC. A pass is reported for P24BA DTC if the low sample counter reaches its threshold.</p>	ELCP pressure sensor signal	< 0.70 volts (14.0 % of Vref or ~ 47 kPa)			<p>640 failures out of 800 samples</p> <p>12.5 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission System Leak Detection Pump Pressure Sensor Circuit High Voltage (ELCP Sealed/ Vented Fuel System)	P24BB	<p>This DTC will detect an ELCP pressure sensor signal that is too high out of range.</p> <p>The ELCP pressure sensor circuit out of range diagnostic compares the raw sensor voltage to an upper voltage threshold. It is an X out of Y diagnostic that runs continuously anytime the controller is awake.</p> <p>If the sensor voltage is above the upper voltage threshold, the high fail counter then increments. If the high fail counter reaches its threshold then a fail is reported for P24BB DTC. A pass is reported for P24BB DTC if the high sample counter reaches its threshold.</p>	ELCP pressure sensor signal	> 4.85 volts (97.0 % of Vref or ~ 120 kPa)			<p>640 failures out of 800 samples</p> <p>12.5 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Accessory Position Circuit Low (EREV/ PHEV only)	P2537	Detects a low ignition switch accessory position circuit. This diagnostic reports the DTC when this circuit is low. Monitoring occurs when the propulsion system has been active for a calibrated duration.	<p>The ECM detects that the state of the accessory line is low when it should be high.</p> <p>The diagnostic is evaluated when Propulsion System Active time is > 5.0 seconds.</p> <p>Diagnostic fails when pass counts are</p>	< 8 counts.			<p>12.5 ms / sample</p> <p>Once per trip</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake System Control Module Requested MIL Illumination	P25A2	Monitors the Brake System Control Module MIL request message to determine when the Brake System Control Module has detected a MIL illuminating fault.	Brake System Control Module Emissions-Related DTC set and module is requesting MIL	Brake System Control Module Emissions-Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake System Control Module B Requested MIL Illumination	P25C9	Monitors the Brake System Control Module B MIL request message to determine when the Brake System Control Module B has detected a MIL illuminating fault.	Brake System Control Module B Emissions-Related DTC set and module is requesting MIL	Brake System Control Module B Emissions-Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position Signal Output Circuit Low	P2618	Controller specific output driver circuit diagnoses the crankshaft position output low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.	Short to ground: ≤ 0.5 Ohms impedance between signal and controller ground Open Circuit: ≥ 200 K Ohms impedance between signal and controller ground	Powertrain Relay Voltage Engine is not cranking Crankshaft Position Output is commanded high	≥ 11.0 Volts	40 failures out of 50 samples 1 sample every 100 msec	Type B, 2 Trips Note: In certain controllers P2617 may also set (Crankshaft Position Signal Output Circuit / Open)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Power Off Timer Performance	P262B	<p>This DTC determines if the hardware timer does not initialize or count properly. There are two tests to ensure proper functioning of the timer: Count Up Test (CUT) and Range Test (RaTe).</p> <p>Count Up Test (CUT): Verifies that the HWIO timer is counting up with the proper increment.</p> <p>Range Test (RaTe): When the run/crank is not active both the hardware and mirror timers are started. The timers are compared when module shutdown is initiated or run/crank becomes active.</p>	<p>Count Up Test:</p> <p>Time difference between the current read and the previous read of the timer</p> <p>Range Test:</p> <p>The variation of the HWIO timer and mirror timer is</p>	<p>> 1.50 seconds</p> <p>> 0.25 %.</p>			<p>Count Up Test: 4 failures out of 20 samples</p> <p>1 sec / sample</p> <p>Continuous while run/crank is not active and until controller shutdown is initiated.</p> <p>Range Test: Once per trip when controller shutdown is initiated or run/crank becomes active.</p>	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump "A" Low Flow / Performance	P2635	This DTC detects degradation in the performance of the electronically regulated fuel system	Filtered fuel rail pressure error	<= Low Threshold [Supporting Table] P2635 Threshold Low OR >= High Threshold [Supporting Table] P2635 Threshold High	a) Fuel Pres Sensor Circuit Low Fault Active (DTC P018C) b) Fuel Pres Sensor Circuit High Fault Active (DTC P018D) c) Fuel Pres Sensor Perf Fault Active (DTC P018B) d) Fuel Pump Circuit Low Fault Active (DTC P0231) e) Fuel Pump Circuit High Fault Active (DTC P0232) f) Fuel Pump Circuit Open Fault Active (DTC P023F) g) Reference Voltage Fault Status (DTC P0641) h) Fuel Pump Driver Control Module Overtemperature Fault Active (DTC P1255) j) Barometric Pressure Signal Valid (PPEI \$4C1) k) Engine run time l) Emissions Fuel Level Low (PPEI \$3FB) m) Fuel Pump Control Enabled	a) <> TRUE b) <> TRUE c) <> TRUE d) <> TRUE e) <> TRUE f) <> TRUE g) <> Active This Key h) <> TRUE j) == TRUE (for absolute fuel pressure sensor) k) >= 30 sec l) <> TRUE m) == TRUE	1 sample / 12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					n] Fuel Pump Control state p] System Voltage q] Fuel flow rate r] Fuel Pressure Control System	n] == Normal p] 11V< System V <32V q1] > 0.047 gram/sec AND q2] <= Max allowed fuel flow rate [Supporting Table] P2635 Max Fuel Flow r1] Not responding to overperformance due to pressure buildup during Deceleration Fuel Cut Off OR r2] Not responding to a decreasing desired fuel pres commnad		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Malfunction Indicator Lamp (MIL) Control Circuit (ODM) Low	P263A	Detects an inoperative malfunction indicator lamp control circuit. This diagnostic reports the DTC when a short to ground is detected.	Voltage low during driver off state (indicates short-to-ground)	Short to ground: $\leq 0.5 \Omega$ impedance between output and controller ground	Run/Crank Voltage Remote Vehicle Start is not active	Voltage ≥ 11.00 volts	1 failures out of 1 samples 50 ms / sample	Type B, No MIL NO MIL Note: In certain controllers P0650 may also set (MIL Control Open Circuit)

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Malfunction Indicator Lamp (MIL) Control Circuit (ODM) High	P263B	Detects an inoperative malfunction indicator lamp control circuit. This diagnostic reports the DTC when a short to power is detected.	Voltage high during driver on state (indicates short to power)	Short to power: $\leq 0.5 \Omega$ impedance between output and controller power	Run/Crank Voltage Remote Vehicle Start is not active	Voltage ≥ 11.00 volts	4 failures out of 5 samples 50 ms / sample	Type B, No MIL NO MIL

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module SIDI High Pressure Pump min/ max authority During Catalyst Warm Up	P2C1E	This DTC determines when the high pressure pump control has reached to its max or min authority during Catalyst Warm up	High Pressure Fuel Pump Delivery Angle OR High Pressure Fuel Pump Delivery Angle	$\geq 92^\circ$ $\leq 0^\circ$	Catalyst Warm Up High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Barometric Pressure Inlet Air Temp Fuel Temp Catalyst Warm up enabled (See Definition in Supporting Material below) Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or	True ≥ 11 Volts > 0.300 MPa Enabled when a code clear is not active or not exiting device control Engine is not cranking ≥ 70.0 KPA ≥ -10.0 degC $-10 \leq \text{Temp degC} \leq 132$ = True	Windup High/ Low 10.00 seconds failures out of 12.50 Seconds samples	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and Device control commanded pressure is false and Device control pump ckt enabled on is false and Engine movement detected is true andManufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active			

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SIDI High Pressure Pump Performance During Catalyst Warm Up	P2C1F	This DTC determines if the high pressure pump is not able to maintain target pressure Catalyst Warm Up. The fault is set if the measured fuel rail pressure is lower than desired fuel pressure by a value that can impact emission and drivability for a number of pump events.	Fuel Pressure Error (Desired Pressure - Measure Pressure)	>= P228C P2C1F - High Pressure Pump Control (HPC) fail threshold of pressure too low Mpa (see supporting tables)	Catalyst Warm Up High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Catalyst Warm up enabled (See Definition in Supporting Material below) Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not active and	True ≥ 11 Volts > 0.300 MPa = True Enabled when a code clear is not active or not exiting device control Engine is not cranking	Positive Pressure Error - 10.00 second failures out of 12.50 second samples	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Device control commanded pressure is false and Device control pump ckt enabled on is false and Engine movement detected is true and Manufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active Barometric Pressure Inlet Air Temp Fuel Temp	>= 70.0 KPA >= -10.0 degC -10 <=Temp degC <= 132		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
SIDI High Pressure Pump Performance During Catalyst Warm Up	P2C20	This DTC determines if the high pressure pump is delivering high pressure that desired pressure Catalyst Warm Up. The fault is set if the measured fuel rail pressure is higher than desired fuel pressure by a value that can impact emission and drivability for a number of pump events.	Fuel Pressure Error (Desired Pressure - Measure Pressure)	<= P228D P2C20 - High Pressure Pump Control (HPC) fail threshold for pressure too high Mpa (see supporting tables)	Catalyst Warm Up High Pressure Pump Performance Diagnostic Enable Battery Voltage Low Side Fuel Pressure Catalyst Warm up enabled (See Definition in Supporting Material below) Additional Enable Conditions: All must be true (High Pressure Pump is enabled and High Fuel pressure sensor ckt is Not (FA,FP or TFTKO) and High Pressure fuel pump ckt is Not (FA,FP or TFTKO) and Cam or Crank Sensor Not FA and IAT,IAT2,ECT Not FA and Low side Fuel Pump Relay ckt Not FA and Estimate fuel rail pressure is valid and Green Engine (In assembly plant) is not enabled and Not if low fuel condition and Low side Fuel Pump is on and Injector Flow Test is not	True ≥ 11 Volts > 0.300 MPa = True Enabled when a code clear is not active or not exiting device control Engine is not cranking	Negative Pressure Error - 10.00 second failures out of 12.50 second samples	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					active and Device control commanded pressure is false and Device control pump ckt enabled on is false and Engine movement detected is true andManufacturers enable counter is 0) Flex Fuel Sensor Not FA Ignition voltage out of correlation error(P1682) not active Barometric Pressure Inlet Air Temp Fuel Temp	>= 70.0 KPA >= -10.0 DegC -10 <= Temp degC <= 132		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus A Off	U0073	This DTC monitors for a BUS A off condition	Bus off failures exceeds before the sample time of is reached	5 counts (equivalent to 0.06 seconds) 0.56 seconds	General Enable Criteria: U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Run/Crank Ignition voltage Power Mode Off Cycle Enable Criteria: KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active > 6.41 Volts = run = 0 (1 indicates enabled) = Active > 11.00 Volts > 0.1125 seconds	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus B Off	U0074	This DTC monitors for a BUS B off condition	Bus off failures exceeds before the sample time of is reached	5 counts (equivalent to 0.06 seconds) 0.56 seconds	General Enable Criteria: U0074 Normal CAN transmission on Bus B Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Run/Crank Ignition voltage Power Mode Off Cycle Enable Criteria: KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active > 6.41 Volts = run = 0 (1 indicates enabled) = Active > 11.00 Volts > 0.1125 seconds	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Cruise Control Module	U0104	This DTC monitors for a loss of communication with the Cruise Control Module.	<p>Message is not received from controller for</p> <p>Message \$2CB</p> <p>Message \$2CD</p>	<p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type C, No SVS "Special Type C"

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Network Management is not active for U0104 Cruise Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Brake System Control Module	U0129	This DTC monitors for a loss of communication with the Brake System Control Module (OBD Module ID 7E5).	<p>Message is not received from controller for</p> <p>Message \$0C1</p> <p>Message \$0C5</p> <p>Message \$0D1</p> <p>Message \$1C6</p> <p>Message \$1C7</p> <p>Message \$1E9</p> <p>Message \$2F1</p> <p>Message \$2F9</p>	<p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U0129 Brake System Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Body Control Module	U0140	This DTC monitors for a loss of communication with the Body Control Module.	<p>Message is not received from controller for</p> <p>Message \$0F1</p> <p>Message \$12A</p> <p>Message \$1E1</p> <p>Message \$1F1</p> <p>Message \$1F3</p> <p>Message \$3C9</p> <p>Message \$3CB</p> <p>Message \$3F1</p> <p>Message \$451</p> <p>Message \$4D7</p> <p>Message \$4E1</p> <p>Message \$4E9</p>	<p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p> <p>> 0.4000 seconds</p>	Diagnostic runs in 12.5 ms loop	Type C, No SVS "Special Type C"

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U0140 Body Control Module	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Active Grill Air Shutter Module A	U0284	This DTC monitors for a loss of communication on the LIN bus with Shutter Module A	ECM has lost communication over the LIN bus with Device 0 / Shutter 1 for	 >= 3.00 counts	The following criteria have been enabled for Power Mode Run/Crank Voltage	 >= 0.38 milliseconds =Run >= 11.00 Volts	LIN bus communication executes in 500ms loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module	U0293	This DTC monitors for a loss of communication with the Hybrid Powertrain Control Module.	<p>Message is not received from controller for</p> <p>Message \$0B4</p> <p>Message \$0D3</p> <p>Message \$186</p> <p>Message \$1DF</p> <p>Message \$3C1</p>	<p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U0293 Hybrid Powertrain Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Control Module LIN Bus 1	U1345	This DTC monitors for a LIN bus off condition	LIN bus off failures	>= 3.00 counts	The following criteria have been enabled for Power Mode Run/Crank Voltage	>= 0.38 milliseconds =Run >= 11.00 Volts	Dependent on bus loading.	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module on Bus B	U1817	This DTC monitors for a loss of communication with the Hybrid Powertrain Control Module on Bus B	<p>Message is not received from controller for</p> <p>Message \$0A7</p> <p>Message \$1E3</p> <p>Message \$281</p>	<p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for U1817 Hybrid Powertrain Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module B on Bus B	U182D	This DTC monitors for a loss of communication with the Hybrid Powertrain Control Module B on Bus B	<p>Message is not received from controller for</p> <p>Message \$1D8</p> <p>Message \$3C5</p> <p>Message \$3DA</p> <p>Message \$3FF</p> <p>Message \$4C2</p>	<p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U182D Hybrid Powertrain Control Module B (VICM)	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Fuel Pump Driver Control Module on Bus S	U18A2	This DTC monitors for a loss of communication with the Fuel Pump Driver Control Module on Bus S	<p>Message is not received from controller for</p> <p>Message \$0D5</p> <p>Message \$0D7</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>=Active</p> <p>> 11.00 Volts</p> <p>> 0.4000 seconds</p>	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U18A2 Fuel Pump Driver Control Module	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (Common) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Pump Driver Control Module Lost Communicati on with ECM [FPPM applications only]	U2616	To detect lost serial data communication from the power driver controller to the ECM	Timer - Fuel System Control message not received (FPPM Received Data Communication Status)	t > 10 s (Fu Pmp Pwr Mod smart device reports Faulted, Not Faulted or Indeterminate)	a) Chassis Fuel Pres Sys Type configuration selection b) Diagnostic Enabled c) Diagnostic System Disabled condition d) FPPM Control Alive Rolling Count Faulted e) FPPM serial data received [\$0CE] f) Run_Crank Input Circuit Voltage g) Run_Crank Ignition Switch Position status h) Sensor Bus Relay On	a) == FCBR ECM FPPM Sys b) == TRUE c) <> True d) <> True e) == TRUE f) > 7.00 volts g) == TRUE h) == TRUE	64.00 failures / 80.00 samples 1 sample / 12.5 millisec	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Bypass Valve A Control Circuit	P0033	<p>Controller specific output driver circuit diagnostic, diagnosing the 'compressor recirculation valve 'A' actuator' low sided driver for an open circuit failure, when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series applications, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In parallel applications, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	≥ 200 K Ω impedance between output and controller ground	<p>Diagnostic enabled *****</p> <p>Powertrain relay voltage *****</p> <p>Engine does not crank</p> <p>Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts *****</p>	<p>20 failures out of 100 samples</p> <p>PWM CRV: 100ms / sample eCRV: 12.5ms / sample</p>	<p>Type A, 1 Trips</p> <p>Note: In certain controllers P0034 may also set turbo/super charger bypass valve control circuit low</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Bypass Valve A Control Circuit Low	P0034	<p>Controller specific output driver circuit diagnostic, diagnosing the 'compressor recirculation valve 'A' actuator' low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series application, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In parallel applications, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p> <p>In certain controllers this diagnosis runs only when the HWIO-output is driven by the application S/W.</p>	$\leq 0.5 \Omega$ impedance between output and controller ground	<p>Diagnostic Enabled *****</p> <p>Powertrain relay voltage *****</p> <p>Engine does not crank</p> <p>Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts *****</p>	<p>20 failures out of 100 samples</p> <p>PWM CRV: 100ms / sample eCRV: 12.5ms / sample</p>	<p>Type A, 1 Trips Note: In certain controllers P0033 may also set turbo/super charger bypass valve control circuit</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Bypass Valve A Control Circuit High	P0035	<p>Controller specific output driver circuit diagnostic, diagnosing the 'compressor recirculation valve 'A' actuator' low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series application, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In parallel applications, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p> <p>In certain controllers this diagnosis runs only when the HWIO-output is driven by the application S/W.</p>	<p>$\leq 0.5 \Omega$ impedance between output and controller power.</p>	<p>Diagnostic enabled *****</p> <p>Powertrain relay voltage *****</p> <p>Engine does not crank Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts *****</p>	<p>20 failures out of 100 samples</p> <p>PWM CRV: 100ms / sample eCRV: 12.5ms / sample</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
MAP / MAF / Throttle Position Correlation	P0068	Detect when MAP and MAF do not match estimated engine airflow as established by the TPS	<p>Difference between MAP and estimated MAP exceeds threshold (kPa), or P0651 (5 Volt Ref), or P0107 (MAP circuit low), or P0108 (MAP circuit high) have failed this key cycle, then MAP portion of diagnostic fails</p> <p>Absolute difference between MAF and estimated MAF exceed threshold (grams/sec), or P0102 (MAF circuit low), or P0103 (MAF circuit hi) have failed this key cycle, or maximum MAF versus RPM (Table) is greater than or equal to maximum MAF versus battery voltage, then MAF portion of diagnostic fails</p>	<p>Table, f(TPS). See supporting tables: P0068_Delta MAP Threshold f(TPS)</p> <p>Table, f(TPS). See supporting tables: P0068_Delta MAF Threshold f(TPS)</p> <p>Table, f(RPM). See supporting tables: P0068_Maximum MAF f(RPM)</p> <p>Table, f(Volts). See supporting tables: P0068_Maximum MAF f(Volts)</p>	<p>Engine Speed</p> <p>Run/Crank voltage</p>	<p>> 800 RPM</p> <p>> 6.41 Volts</p>	<p>Continuously fail MAP and MAF portions of diagnostic for 0.1875 s</p> <p>Continuous in MAIN processor</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 2 Circuit Performance (applications with humidity sensor and manifold temperature sensor)	P0096	<p>Detects an Intake Air Temperature 2 (IAT2) sensor value that is stuck in range by comparing the IAT2 sensor value against the IAT and IAT3 sensor values and failing the diagnostic if the IAT2 value is more different than the IAT and IAT3 values than is expected. If the engine has been off for a long enough period of time, the air temperature values in the engine compartment of the vehicle are considered to have equalized, and the diagnostic can be enabled.</p> <p>The diagnostic will fail if the IAT and IAT3 values are similar, and the IAT2 value is not similar to the IAT and IAT3 values. The diagnostic will also fail if none of the three sensor values are similar to each other, and the IAT2 value is furthest from the sensor value that is in the middle of the three sensor values.</p> <p>This diagnostic is executed once per</p>	<u>Good Correlation Between IAT and IAT3:</u> ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT3)	> 30 deg C <= 25 deg C > 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	Type B, 2 Trips
			<u>Not Good Correlation. IAT in middle:</u> Power Up IAT is between Power Up IAT2 and Power Up IAT3 AND ABS(Power Up IAT2 - Power Up IAT3) AND ABS(Power Up IAT - Power Up IAT2) > ABS(Power Up IAT - Power Up IAT3)	> 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	
			<u>Not Good Correlation. IAT3 in middle:</u> Power Up IAT3 is between Power Up IAT and Power Up IAT2		Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds	Executes once at the beginning of each ignition cycle if enable conditions are met	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ignition cycle if the enable conditions are met.	AND ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT3 - Power Up IAT2) > ABS(Power Up IAT3 - Power Up IAT)	> 30 deg C	No Active DTCs:	PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Press Regulator Solenoid Supply Voltage Control High Side Circuit Open	P00C8	Controller specific output driver circuit diagnoses High Pressure pump Control Solenoid high sided driver for an open circuit failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates open circuit failure. Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.	 ≥ 200 KOhms impedance between signal and controller ground	Engine Speed Battery Voltage	≥ 50 RPM ≥ 11 Volts Not in pump device control Enabled when a code clear is not active or not exiting device control	20 failures out of 40 samples 100 ms /sample Continuous	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 3 Circuit Performance (applications with humidity sensor and manifold temperature sensor)	P00E9	<p>Detects an Intake Air Temperature 3 (IAT3) sensor value that is stuck in range by comparing the IAT3 sensor value against the IAT and IAT2 sensor values and failing the diagnostic if the IAT3 value is more different than the IAT and IAT2 values than is expected. If the engine has been off for a long enough period of time, the air temperature values in the engine compartment of the vehicle are considered to have equalized, and the diagnostic can be enabled.</p> <p>The diagnostic will fail if the IAT and IAT2 values are similar, and the IAT3 value is not similar to the IAT and IAT2 values. The diagnostic will also fail if none of the three sensor values are similar to each other, and the IAT3 value is furthest from the sensor value that is in the middle of the three sensor values.</p> <p>This diagnostic is executed once per</p>	<p><u>Good Correlation Between IAT and IAT2:</u></p> <p>ABS(Power Up IAT - Power Up IAT2)</p> <p>AND</p> <p>ABS(Power Up IAT - Power Up IAT3)</p> <p>AND</p> <p>ABS(Power Up IAT2 - Power Up IAT3)</p>	<p><= 30 deg C</p> <p>> 25 deg C</p> <p>> 25 deg C</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts</p> <p>>= 0.9 seconds</p> <p>PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	Type B, 2 Trips
			<p><u>Not Good Correlation, IAT in Middle:</u></p> <p>Power Up IAT is between Power Up IAT2 and Power Up IAT3</p> <p>AND</p> <p>ABS(Power Up IAT2 - Power Up IAT3)</p> <p>AND</p> <p>ABS(Power Up IAT - Power Up IAT3) > ABS(Power Up IAT - Power Up IAT2)</p>	<p>> 25 deg C</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p> <p>No Active DTCs:</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts</p> <p>>= 0.9 seconds</p> <p>PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	
			<p><u>Not Good Correlation, IAT2 in Middle:</u></p> <p>Power Up IAT2 is between Power Up IAT and Power Up IAT3</p>		<p>Time between current ignition cycle and the last time the engine was running</p> <p>Powertrain Relay Voltage for a time</p>	<p>> 28,800 seconds</p> <p>>= 11.0 Volts</p> <p>>= 0.9 seconds</p>	<p>Executes once at the beginning of each ignition cycle if enable conditions are met</p>	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ignition cycle if the enable conditions are met.	AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT3) > ABS(Power Up IAT2 - Power Up IAT)	> 25 deg C	No Active DTCs:	PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit 3 Low (applications with manifold temperature and humidity)	P00EA	Detects a continuous short to ground in the Intake Air Temperature 3 (IAT3) signal circuit by monitoring the IAT3 sensor output resistance and failing the diagnostic when the IAT3 resistance is too low. The IAT3 sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. A lower resistance is equivalent to a higher temperature.	Raw IAT 3 Input	< 56.50 Ohms (~150 deg C)	Engine Run Time	> 0.00 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit 3 High (applications with manifold temperature and humidity)	P00EB	Detects a continuous open circuit in the Intake Air Temperature 3 (IAT3) signal circuit by monitoring the IAT3 sensor output resistance and failing the diagnostic when the IAT3 resistance is too high. The IAT3 sensor is a thermistor in which the resistance across the sensor can be equated to a temperature. A higher resistance is equivalent to a lower temperature.	Raw IAT 3 Input	> 162,529 Ohms (~-60 deg C)	Engine Run Time	> 0.00 seconds	40 failures out of 50 samples 1 sample every 100 msec	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor 3 Intermittent In-Range	P00EC	<p>Detects a noisy or erratic signal in the Intake Air Temperature 3 (IAT3) circuit by monitoring the IAT3 sensor and failing the diagnostic when the IAT3 signal has a noisier output than is expected.</p> <p>When the value of the IAT3 signal in °C is determined, a delta is calculated between the current reading and the previous reading. The absolute value of these deltas is summed over a number of IAT3 readings. The result of this summation is called a "string length".</p> <p>Since the IAT3 signal is anticipated to be relatively smooth, a string length of a particular magnitude indicates a noisy or erratic IAT3 signal. The diagnostic will fail if the string length is too high.</p>	<p>String Length</p> <p>Where: "String Length" = sum of "Diff" calculated over</p> <p>And where: "Diff" = ABS(current IAT 3 reading - IAT 3 reading from 100 milliseconds previous)</p>	<p>> 80.00 deg C</p> <p>10 consecutive IAT 3 readings</p>	Continuous		<p>4 failures out of 5 samples</p> <p>Each sample takes 1.0 seconds</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Air Temperature Sensor Circuit Performance (applications with humidity sensor and manifold temperature sensor)	P0111	<p>Detects an Intake Air Temperature (IAT) sensor value that is stuck in range by comparing the IAT sensor value against the IAT2 and IAT3 sensor values and failing the diagnostic if the IAT value is more different than the IAT2 and IAT3 values than is expected. If the engine has been off for a long enough period of time, the air temperature values in the engine compartment of the vehicle are considered to have equalized, and the diagnostic can be enabled.</p> <p>The diagnostic will fail if the IAT2 and IAT3 values are similar, and the IAT value is not similar to the IAT2 and IAT3 values. The diagnostic will also fail if none of the three sensor values are similar to each other, and the IAT value is furthest from the sensor value that is in the middle of the three sensor values.</p> <p>This diagnostic is executed once per</p>	<u>Good Correlation Between IAT2 and IAT3</u> ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT3)	> 30 deg C > 25 deg C <= 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	Type B, 2 Trips
			<u>Not Good Correlation. IAT2 in Middle:</u> Power Up IAT2 is between Power Up IAT and Power Up IAT3 AND ABS(Power Up IAT - Power Up IAT3) AND ABS(Power Up IAT2 - Power Up IAT) > ABS(Power Up IAT2 - Power Up IAT3)	> 25 deg C	Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time No Active DTCs:	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error	Executes once at the beginning of each ignition cycle if enable conditions are met	
			<u>Not Good Correlation. IAT3 in Middle:</u> Power Up IAT3 is between Power Up IAT and Power Up IAT2		Time between current ignition cycle and the last time the engine was running Powertrain Relay Voltage for a time	> 28,800 seconds >= 11.0 Volts >= 0.9 seconds	Executes once at the beginning of each ignition cycle if enable conditions are met	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		ignition cycle if the enable conditions are met.	AND ABS(Power Up IAT - Power Up IAT2) AND ABS(Power Up IAT3 - Power Up IAT) > ABS(Power Up IAT3 - Power Up IAT2)	> 30 deg C	No Active DTCs:	PowertrainRelayFault ECT_Sensor_Ckt_FA IAT_SensorCircuitFA MnfdTempSensorCktFA HumTempSnsrCktFA EngineModeNotRunTimer Error		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Throttle Position Sensor Performance (single turbo)	P0121	<p>Detects a performance failure in the Throttle Position sensor (TPS) sensor, such as when a TPS value is stuck in range.</p> <p>This diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from other sensors. The other sensors are the Manifold Pressure (MAP) sensor, Turbocharger Boost Pressure sensor and Mass Air Flow (MAF) sensor.</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the TPS sensor. In this case, the TPS</p>	<p>See table P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix for combinations of model failures that can set this DTC.</p> <p>MAF model fails when ABS(Measured Flow – Modeled Air Flow) Filtered</p> <p>MAP1 model fails when ABS(Measured MAP – MAP Model 1) Filtered</p> <p>MAP2 model fails when ABS(Measured MAP – MAP Model 2) Filtered</p> <p>MAP3 model fails when ABS(Measured MAP – MAP Model 3) Filtered</p> <p>TIAP1 model fails when ABS(Measured TIAP – TIAP Model 1) Filtered</p> <p>TPS model fails when Filtered Throttle Model Error</p> <p>TIAP Correlation model fails when</p> <p>High Engine Air Flow is TRUE AND Measured TIAP -</p>	<p>> 20.0 grams/sec</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 300 kPa*(g/s)</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>Coolant Temp Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p> <p>-</p>	<p>>= 400 RPM <= 6,000 RPM</p> <p>>= -9 Deg C</p> <p>= TRUE)</p> <p><= 130 Deg C >= -20 Deg C <= 125 Deg C</p> <p>>= 0.50</p> <p>Modeled Air Flow Error multiplied by P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM and P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est</p> <p>MAP Model 1 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	<p>Type B, 2 Trips</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		Performance diagnostic will fail.	<p>measured MAP - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Offset</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND Measured TIAP - measured Baro - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Offset</p> <p>TIAP Correlation is valid when High Engine Air Flow has been TRUE for a period of time OR Low Engine Air Flow has been TRUE for a period of time</p> <p>High Engine Air Flow is TRUE when Mass Air Flow</p> <p>AND</p>	<p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 1.0 seconds</p> <p>> 1.0 seconds</p> <p>> a threshold in gm sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min Air Flow</p>	<p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP Model 3 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP3 Residual Weight Factor based on RPM</p> <p>TIAP Model 1 Error multiplied by P0101, P0106, P0121, P0236, P1101: TIAP Residual Weight Factor based on RPM</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA EGRValvePerformance_FA A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA MnfdTempSensorFA TC_BoostPresSnsrCktFA AmbientAirDefault</p> <p>EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP MnfdTempSensorCktFP</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>Manifold Pressure</p> <p>> a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min MAP</p> <p>AND Filtered Mass Air Flow - Mass Air Flow</p> <p>< 3.0 gm/sec</p> <p>Low Engine Air Flow is TRUE when Mass Air Flow</p> <p>< a threshold in gm sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max Air Flow</p> <p>AND Manifold Pressure</p> <p>< a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max MAP</p> <p>AND Mass Air Flow - Filtered Mass Air Flow</p> <p>< 2.0 gm/sec</p>					

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit Low Voltage Bank 1 Sensor 1 (For use with WRAF - E80	P0131	<p>This DTC determines if the WRAF O2 sensor signal circuit is shorted low. This DTC will detect a short to ground fault to the Pump Current, Reference Cell Voltage and Reference Ground circuits. When enabled, the diagnostic monitors the three different failure counters it receives from the WRAF Application-Specific Integrated Circuit (ASIC).</p> <p>The individual diagnostic failure counters are incremented based on the message received from the ASIC. The DTC is set based on any of the three individual fail and sample counters.</p>	<p>B1S1 WRAF ASIC indicates a ground short to any of the following WRAF signals:</p> <p>A) Pump Current - short to ground fail counts are accumulated to determine fault status.</p> <p>B) Reference Cell Voltage - short to ground fail counts are accumulated to determine fault status.</p> <p>C) Reference Ground - short to ground fail counts are accumulated to determine fault status.</p> <p><u>Note:</u> This ASIC is referred to as C2WRAF (Delphi).</p> <p><u>Note:</u> A ground short on the Pump Current or Reference Voltage signal may also set a P223C DTC.</p>	<p>The ASIC provides a fault indication when the pump current pin is between -150 mV and +175 mV.</p> <p>The ASIC provides a fault indication when the Reference Cell Voltage pin < 225 mV.</p> <p>The ASIC provides a fault indication when during the intrusive test the Reference Cell impedance change is ≤ 90 ohms.</p> <p><u>Note:</u> Signal A & B faults must exist for 24 ASIC clock cycles to qualify for a fail flag.</p> <p>The three fault signals have individual X out of Y calibrations. When the X out of Y is reached in any region this DTC is set.</p>	<p>B1S1 DTC's Not active this key cycle</p> <p>Measure Valid status (ASIC)</p> <p>Controller status (ASIC)</p> <p>Engine Run or Auto stop</p> <p>WRAF Ref cell temperature</p> <p>*****</p> <p>Heater Warm-up delay Then WRAF circuit diagnostic delay (since heater Warm-up delay is complete)</p> <p>*****</p>	<p>P0135, P0030, P0031 or P0032</p> <p>= Valid</p> <p>= Ready</p> <p>= True</p> <p>≥ 628 Deg C</p> <p>= Complete</p> <p>≥ 20.0 seconds</p>	<p>Signal A: 128 failures out of 160 samples</p> <p>OR</p> <p>Signal B: 128 failures out of 160 samples</p> <p>OR</p> <p>Signal C: 3 failures out of 1 samples</p> <p>Frequency for Signal A & B: Continuous in 25 milli - second loop</p> <p>Frequency for Signal C: Tested during an intrusive event performed every 60 seconds. During each event the impedance is measured 3 times once every 12.5 msec.</p> <p><u>Note:</u> If the fail count value is greater than the sample count value that individual</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
							monitor is disabled.	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit High Voltage Bank 1 Sensor 1 (For use with WRAF - E80	P0132	<p>This DTC determines if the WRAF O2 sensor signal circuit is shorted high. This DTC will detect a short to power fault to the Pump Current (and Trim circuit), Reference Cell Voltage and Reference Ground circuit. When enabled, the diagnostic monitors the three different failure counters it receives from the WRAF Application-Specific Integrated Circuit (ASIC).</p> <p>The individual diagnostic failure counters are incremented based on the message received from the ASIC. The DTC is set based on any of the three individual fail and sample counters.</p>	<p>B1S1 WRAF ASIC indicates a short to power on any of the following WRAF signals:</p> <p>A) Pump Current - short to power fail counts are accumulated to determine fault status.</p> <p>B) Reference Cell Voltage - short to power fail counts are accumulated to determine fault status.</p> <p>C) Reference Ground - short to power fail counts are accumulated to determine fault status.</p> <p><u>Note:</u> This ASIC is referred to as C2WRAF (Delphi).</p>	<p>The ASIC provides a fault indication when the pump current pin > 2.8 V.</p> <p>The ASIC provides a fault indication when the Reference Cell Voltage pin > 3.3 V.</p> <p>The ASIC provides a fault indication when the Reference Ground pin > 225 mV.</p> <p><u>Note:</u> The above faults must exist for 21 ASIC clock cycles to qualify for a fail flag.</p> <p>The three fault signals have individual X out of Y calibrations. When the X out of Y is reached in any region this DTC is set.</p>	<p>B1S1 DTC's Not active this key cycle</p> <p>Measure Valid Status (ASIC)</p> <p>Controller status (ASIC)</p> <p>Engine Run or Auto stop</p> <p>WRAF Ref cell temperature</p> <p>*****</p> <p>Heater Warm-up delay Then WRAF circuit diagnostic delay (since heater Warm-up delay is complete)</p> <p>*****</p>	<p>P0135, P0030, P0031 or P0032</p> <p>= Valid</p> <p>= Ready</p> <p>= True</p> <p>≥ 628 Deg C</p> <p>= Complete</p> <p>≥ 20.0 seconds</p>	<p>Signal A: 128 failures out of 160 samples</p> <p>OR</p> <p>Signal B: 128 failures out of 160 samples</p> <p>OR</p> <p>Signal C: 128 failures out of 160 samples</p> <p>Frequency: Continuous in 25 milli - second loop</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit Low Voltage Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0137	<p>This DTC determines if the O2 sensor signal circuit is shorted low. When enabled, the diagnostic monitors the O2S signal and compares it to the threshold.</p> <p>The diagnostic failure counter is incremented if the O2S signal is below the threshold value. This DTC is set based on the fail and sample counters.</p>	Oxygen Sensor Signal	< 50 mvolts	<p>No Active DTC's</p> <p>AIR intrusive test Fuel intrusive test Idle intrusive test EGR intrusive test System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Commanded Equivalence Ratio Air Per Cylinder Fuel Control State Closed Loop Active</p>	<p>TPS_ThrottleAuthorityDef aulted MAP_SensorFA AIR System FA Ethanol Composition Sensor FA EvapPurgeSolenoidCircuit _FA EvapFlowDuringNonPurg e_FA EvapVentSolenoidCircuit_ FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnsrCkt _FA FuelInjectorCircuit_FA</p> <p>= Not active = Not active = Not active = Not active 10.0 < Volts = Not active = Not active = Not active = Not active</p> <p>= False = False</p> <p>0.991 ≤ ratio ≤ 1.040 140 ≤ mgrams ≤ 1,000 = Closed Loop = TRUE (Please see “Closed Loop Enable Clarification” in Supporting Tables).</p>	<p>320 failures out of 400 samples</p> <p>Frequency: Continuous in 100 milli - second loop</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					All Fuel Injectors for active Cylinders Fuel Condition Ethanol Estimation in Progress Fuel State All of the above met for	Enabled (On) Ethanol \leq 87 % = Not Active (Please see " Ethanol Estimation in Progress " in Supporting Tables). DFCO not active > 5.0 seconds		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Circuit High Voltage Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0138	<p>This DTC determines if the O2 sensor signal circuit is shorted high or open. When enabled, the diagnostic monitors the O2S signal and compares it to the threshold.</p> <p>The diagnostic failure counter is incremented if the O2S signal is above the threshold value. This DTC is set based on the fail and sample counters.</p>	Oxygen Sensor Signal	> 1,050 mvolts	<p>No Active DTC's</p> <p>System Voltage AFM Status Heater Warm-up delay Engine Run Time Engine Run Accum</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>*****</p> <p>Secondary delay after above conditions are complete (cold start condition)</p> <p>Secondary delay after above conditions are complete (not cold start condition)</p> <p>Commanded Equivalence Ratio</p> <p>*****</p> <p>All of the above met for</p>	<p>TPS_ThrottleAuthorityDefaulted MAF_SensorFA MAP_SensorFA EvapExcessPurgePsbl_FA FuelInjectorCircuit_FA Ethanol Composition Sensor FA AIR System FA</p> <p>10.0 < Volts = All Cylinders active = Complete > 5.0 seconds > 30.0 seconds</p> <p>= False = False</p> <p>*****</p> <p>> 175.0 seconds when engine soak time > 28,800 seconds</p> <p>> 175.0 seconds when engine soak time ≤ 28,800 seconds</p> <p>≤ 1.040 EQR</p> <p>*****</p> <p>> 5.0 seconds</p>	<p>100 failures out of 125 samples</p> <p>Frequency: Continuous in 100 milli - second loop</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2S Heater Performance Bank 1 Sensor 2) (For Single Bank Exhaust Only	P0141	<p>This DTC determines if the O2 sensor heater is functioning properly by monitoring the current through the heater circuit. This test compares the measured heater current (monitored thru the low side driver) and compares it to the expected values (over the voltage range provided) for the released sensor.</p> <p>The diagnostic failure counter is incremented if the heater current is outside the expected range. This DTC is set based on the fail and sample counters.</p>	Heater Current outside of the expected range of	0.3 > amps > 2.5	<p>No Active DTC's System Voltage Heater Warm-up delay O2S Heater device control B1S1 O2S Heater Duty Cycle</p> <p>All of the above met for</p>	<p>ECT_Sensor_FA > 10.0 Volts = Complete</p> <p>= Not active</p> <p>> zero</p> <p>> 120 seconds</p>	<p>8 failures out of 10 samples</p> <p>Frequency: 2 tests per trip 30 seconds delay between tests and 1 second execution rate.</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Rich to Lean Bank 1 Sensor 1) (For use with WRAF	P015A	<p>DTC P015A detects that the primary WRAF oxygen sensor for Bank 1 has delayed response when the air fuel ratio transitions from rich to lean condition. This diagnostic runs simultaneously with the intrusive secondary O2 monitor rich to lean tests (P013E / P013A / P2271), which commands fuel cut off.</p> <p>Note: The Primary method is used when the primary WRAF O2 sensor signal transitions from above to below the O2 measured EQR threshold, otherwise the Secondary method is used.</p> <p><u>Primary method:</u> The P015A diagnostic measures the primary WRAF O2 sensor response time between a rich condition above a starting measured EQR threshold and a lower measured EQR threshold. The response time is then scaled and normalized to mass air flow rate, engine speed, Baro,</p>	<p>Primary method: The EWMA of the Pre O2 sensor normalized R2L time delay value. The EWMA repass limit is The EWMA calculation uses a 0.20 coefficient.</p> <p>OR</p> <p>Secondary Method: The Accumulated time monitored during the R2L Delayed Response Test.</p> <p>AND</p> <p>Pre WRAF O2 sensor measured EQR is</p>	<p>> 0.52 EWMA (sec) ≤ 0.47 EWMA (sec)</p> <p>≥ 4.0 Seconds</p> <p>> 0.800 EQR</p>	<p>No Active DTC's</p> <p>System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p> <p>Green O2S Condition</p>	<p>TPS_ThrottleAuthorityDefaulted MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR System FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EthanolCompositionSensor_FA EngineMisfireDetected_FA WRAF_Bank_1_FA P0131, P0132, P013A, P013B, P013E, P013F, P2270, P2271</p> <p>> 10.0 Volts = Not active = Not active = Not active = Not active</p> <p>= False = False</p> <p>= Not Valid,</p>	<p>Frequency: Once per trip Note: if NaESPD_b_Fast InitResplsActive = TRUE for the given Fuel Bank OR NaESPD_b_RapidResponsesActive = TRUE, multiple tests per trip are allowed</p>	<p>Type A, 1 Trips EWMA</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>and intake air temperature resulting in a normalized delay value. The normalized delay is fed into a 1st order lag filter to update the final EWMA result. DTC P015A is set when the EWMA value exceeds the EWMA threshold.</p> <p>Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p><u>Secondary method:</u> This fault is set if the primary WRAF O2 sensor does not achieve the required lower measured EQR</p>			<p>O2 Heater (pre sensor) on for</p> <p>Engine Coolant (Or OBD Coolant Enable Criteria</p> <p>IAT</p> <p>Engine run Accum</p> <p>Engine Speed to initially enable test</p> <p>Engine Speed range to keep test enabled (after initially enabled)</p> <p>Engine Airflow</p> <p>Vehicle Speed to initially enable test</p> <p>Vehicle Speed range to keep test enabled (after initially enabled)</p> <p>Closed loop integral</p> <p>Closed Loop Active</p>	<p>Green O2S condition is considered valid until the accumulated air flow is greater than</p> <p>Multiple DTC Use_Green Sensor Delay Criteria - Limit</p> <p>for the following locations: B1S1, B2S1 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 22.0 grams/sec.</p> <p>≥ 20 seconds</p> <p>> 62 °C</p> <p>= TRUE)</p> <p>> -40 °C</p> <p>> 30 seconds</p> <p>950 ≤ RPM ≤ 2,950</p> <p>900 ≤ RPM ≤ 3,050</p> <p>1.0 ≤ gps ≤ 20.0</p> <p>40.4 ≤ MPH ≤ 77.7</p> <p>35.4 ≤ MPH ≤ 82.0</p> <p>0.85 ≤ C/L Int ≤ 1.07</p> <p>= TRUE</p> <p>(Please see "Closed Loop Enable Clarification" in Supporting Tables).</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		threshold before a delay time threshold is reached.			<p>Evap</p> <p>Ethanol Estimation in Progress</p> <p>Baro Post fuel cell</p> <p>EGR Intrusive diagnostic All post sensor heater delays O2S Heater (post sensor) on Time Predicted Catalyst temp Fuel State</p> <p>=====</p> <p>All of the above met for at least 1.5 seconds, and then the Force Cat Rich intrusive stage is requested.</p> <p>=====</p> <p>Pre O2S EQR B1S1 at end of Cat Rich stage Fuel State Number of fueled cylinders</p> <p>=====</p> <p>After above conditions are met: DFCO Mode is entered (wo driver initiated pedal input).</p>	<p>not in control of purge</p> <p>= Not Active (Please see "Ethanol Estimation in Progress" in Supporting Tables).</p> <p>> 70 kpa = enabled</p> <p>= not active</p> <p>= not active</p> <p>≥ 80.0 sec 550 ≤ °C ≤ 850 = DFCO possible</p> <p>=====</p> <p>=====</p> <p>≥ 1.080 EQR = DFCO active</p> <p>≤ 3 cylinders</p> <p>=====</p> <p>=====</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Delayed Response Lean to Rich Bank 1 Sensor 1) (For use with WRAF	P015B	<p>DTC P015B detects that the primary WRAF oxygen sensor for Bank 1 has delayed response when the air fuel ratio transitions from lean to rich condition. This diagnostic runs simultaneously with the intrusive secondary O2 monitor lean to rich tests (P013F / P013B), which commands fuel enrichment.</p> <p>Note: The Primary method is used when the primary WRAF O2 sensor signal transitions from lean condition to above the O2 measured EQR threshold, otherwise the Secondary method is used.</p> <p><u>Primary method:</u> The P015B diagnostic measures the primary WRAF O2 sensor response time between a lean condition and a higher measured EQR threshold. The response time is then scaled and normalized to mass air flow rate, engine speed, Baro, and intake air temperature resulting in</p>	<p>Primary method: The EWMA of the Pre O2 sensor normalized L2R time delay value. The EWMA repass limit is The EWMA calculation uses a 0.20 coefficient.</p> <p>OR</p> <p>Secondary method: The Accumulated time monitored during the L2R Delayed Response Test.</p> <p>AND</p> <p>Pre WRAF O2 sensor measured EQR is</p> <p>OR</p> <p>At end of Cat Rich stage the Pre WRAF O2 sensor measured EQR is</p>	<p>> 0.53 EWMA (sec) ≤ 0.49 EWMA (sec)</p> <p>≥ 4.4 Seconds</p> <p>< 1.000 EQR</p> <p>< 1.080 EQR</p>	<p>No Active DTC's</p> <p>P015A test is complete and</p> <p>System Voltage EGR Device Control Idle Device Control Fuel Device Control AIR Device Control</p> <p>Low Fuel Condition Only when FuelLevelDataFault</p>	<p>TPS_ThrottleAuthorityDefault MAP_SensorFA IAT_SensorFA ECT_Sensor_FA AmbientAirDefault MAF_SensorFA EvapPurgeSolenoidCircuit_FA EvapFlowDuringNonPurge_FA EvapVentSolenoidCircuit_FA EvapSmallLeak_FA EvapEmissionSystem_FA FuelTankPressureSnrCkt_FA FuelInjectorCircuit_FA AIR System FA FuelTrimSystemB1_FA FuelTrimSystemB2_FA EthanolCompositionSensor_FA EngineMisfireDetected_FA WRAF_Bank_1_FA P0131, P0132, P013A, P013B, P013E, P013F, P015A, P2270, P2271</p> <p>= Passed</p> <p>> 10.0 Volts = Not active = Not active = Not active = Not active</p> <p>= False</p> <p>= False</p>	<p>Frequency: Once per trip Note: if NaESPD_b_Fast InitResplsActive = TRUE for the given Fuel Bank OR NaESPD_b_RapidResponsesActive = TRUE, multiple tests per trip are allowed</p>	<p>Type A, 1 Trips EWMA</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>a normalized delay value. The normalized delay is fed into a 1st order lag filter to update the final EWMA result. DTC P015B is set when the EWMA value exceeds the EWMA threshold.</p> <p>Note: This EWMA diagnostic employs two features, Fast Initial Response (FIR) and Rapid Step Response (RSR). The FIR feature is used following a code clear event or any event that results in erasure of the engine controller's non-volatile memory. The RSR feature is used when a step change in the test result is identified. Both these temporary features improve the EWMA result following a non-typical event by allowing multiple intrusive tests on a given trip until the total number of tests reach a calibration value.</p> <p><u>Secondary method:</u> This fault is set if the primary WRAF O2 sensor does not achieve the required higher measured EQR threshold before a delay time threshold is</p>			<p>Green O2S Condition</p> <p>O2 Heater (pre sensor) on for</p> <p>Engine Coolant (Or OBD Coolant Enable Criteria</p> <p>IAT Engine run Accum</p> <p>Engine Speed to initially enable test Engine Speed range to keep test enabled (after initially enabled)</p> <p>Engine Airflow Vehicle Speed to initially enable test Vehicle Speed range to keep test enabled (after initially enabled)</p> <p>Closed loop integral Closed Loop Active</p>	<p>= Not Valid, Green O2S condition is considered valid until the accumulated air flow is greater than Multiple DTC Use_Green Sensor Delay Criteria - Limit for the following locations: B1S1, B2S1 (if applicable) in Supporting Tables tab. Airflow accumulation is only enabled when airflow is above 22.0 grams/sec.</p> <p>≥ 20 seconds</p> <p>> 62 °C = TRUE)</p> <p>> -40 °C > 30 seconds</p> <p>950 ≤ RPM ≤ 2,950</p> <p>900 ≤ RPM ≤ 3,050</p> <p>1.0 ≤ gps ≤ 20.0</p> <p>40.4 ≤ MPH ≤ 77.7</p> <p>35.4 ≤ MPH ≤ 82.0</p> <p>0.85 ≤ C/L Int ≤ 1.07 = TRUE</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		reached.			<p>Evap</p> <p>Ethanol Estimation in Progress</p> <p>Baro Post fuel cell EGR Intrusive diagnostic All post sensor heater delays O2S Heater (post sensor) on time</p> <p>Predicted Catalyst temp Fuel State Number of fueled cylinders</p> <p>=====</p> <p>When above conditions are met: Fuel Enrich mode is entered.</p> <p>=====</p> <p>During this test: Engine Airflow must stay between: and the delta Engine Airflow over 12.5msec must be :</p>	<p>(Please see “Closed Loop Enable Clarification” in Supporting Tables).</p> <p>not in control of purge</p> <p>= Not Active (Please see “Ethanol Estimation in Progress” in Supporting Tables).</p> <p>> 70 kpa = enabled = not active</p> <p>= not active</p> <p>≥ 80.0 sec</p> <p>550 ≤ °C ≤ 850 = DFCO inhibit</p> <p>≥ 1 cylinders</p> <p>=====</p> <p>=====</p> <p>4 ≤ gps ≤ 27</p> <p>≤ 16.0 gps</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Engine Overboost Turbocharge r with wastegate. Not supercharge r with mechanical compressor	P0234	This DTC indicates an over boost failure. Two failure paths are considered. When pressure control closed loop control being active, a negative boost pressure deviation indicates overboost conditions at constant driving conditions. In case boost pressure close loop control not being active and with desired boost pressure below basic boost pressure, overboost conditions can be detected when actual boost pressure is higher than basic boost pressure plus a diagnostic offset.	Desired boost pressure - Actual boost pressure	< refer to P0234: Overboost pressure deviation limit as a function of engine speed and desired boost pressure - P0234 P0299: Ambient pressure correction as a function of engine speed and ambient pressure in Supporting tables.	Dev. diagnostic enable ***** Coolant temperature or OBD Coolant enable criteria and Coolant temperature Intake air temperature is in range Ambient air pressure is in range Engine speed in range Desired boost pressure in range Desired boost pressure derivative in range ***** All conditions have to be fulfilled for: ***** No active DTCs: ***** Pressure control has to be in closed loop.	True ***** > -40.0 °C = TRUE < 130.0 °C > -40.0 °C < 80.0 °C > 60.0 kPa < 120.0 kPa > 1,600 rpm < 6,000 rpm > 140.0 kPa < 300.0 kPa > -75.0 kPa/s < 75.0 kPa/s ***** > refer to P0234 P0299: Boost deviation diagnostic enable delay as a function of engine speed in Supporting tables. ***** BSTR_b_PCA_CktFA BSTR_b_TurboBypassCkt FA ECT_Sensor_FA IAT_SensorFA BSTR_b_BoostSnrFA AmbientAirDefault *****	15 failures out of 15 samples 100ms / sample	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No device control active for WG and compressor recirculation valve.			
			Actual boost pressure	> refer to P0234: Overboost pressure limit below basic pressure as a function of engine speed and ambient pressure in Supporting tables. +Basic Pressure	Basic pressure diag enable and Dev. diagnostic enable ***** Coolant temperature or OBD Coolant enable criteria and Coolant temperature Intake air temperature is in range Ambient air pressure is in range Engine speed in range All conditions have to be fulfilled for: ***** No active DTCs: ***** Pressure control has to be in open loop.	False True ***** > -40.0 °C = TRUE < 130.0 °C > -40.0 °C < 80.0 °C > 60.0 kPa < 120.0 kPa > 2,000 rpm < 3,500 rpm > 2.00 Seconds ***** BSTR_b_PCA_CktFA BSTR_b_TurboBypassCktFA ECT_Sensor_FA IAT_SensorFA BSTR_b_BoostSnrFA AmbientAirDefault BSTR_b_PCA_TFTKO *****	100 failures out of 150 samples 100ms / sample	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No device control active for WG and compressor recirculation valve.			

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Boost Pressure (TIAP) Sensor Performance (single turbo)	P0236	<p>Detects a performance failure in the Turbocharger Boost Pressure sensor, such as when a Turbocharger Boost Pressure value is stuck in range.</p> <p>If the engine has been off for a sufficient amount of time, the pressure values in the induction system will have equalized. The Turbocharger Boost Pressure sensor value is checked to see if it is within the normal expected atmospheric pressure range. If it is not, then the Turbocharger Boost Pressure performance diagnostic will fail.</p> <p>If the Turbocharger Boost Pressure sensor value is within the normal expected atmospheric range, then Manifold Pressure (MAP), Turbocharger Boost Pressure and Barometric Pressure (BARO) are compared to see if their values are similar. If the MAP and BARO sensor values are similar, but the Turbocharger Boost Pressure value is not</p>	<p><u>Engine Running:</u></p> <p>See table P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix</p> <p>for combinations of model failures that can set this DTC.</p> <p>MAF model fails when ABS(Measured Flow – Modeled Air Flow) Filtered</p> <p>MAP1 model fails when ABS(Measured MAP – MAP Model 1) Filtered</p> <p>MAP2 model fails when ABS(Measured MAP – MAP Model 2) Filtered</p> <p>MAP3 model fails when ABS(Measured MAP – MAP Model 3) Filtered</p> <p>TIAP1 model fails when ABS(Measured TIAP - TIAP Model 1) Filtered</p> <p>TPS model fails when Filtered Throttle Model Error</p> <p>TIAP Correlation model fails when High Engine Air Flow is TRUE AND Measured TIAP -</p>	<p>> 20.0 grams/sec</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 300 kPa*(g/s)</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>Coolant Temp Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p> <p>-</p>	<p>>= 400 RPM <= 6,000 RPM</p> <p>>= -9 Deg C</p> <p>= TRUE)</p> <p><= 130 Deg C >= -20 Deg C <= 125 Deg C</p> <p>>= 0.50</p> <p>Modeled Air Flow Error multiplied by P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM and P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est</p> <p>MAP Model 1 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>similar, then a Turbocharger Boost Pressure performance diagnostic will fail.</p> <p>The engine running portion of this diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from other sensors. The other sensors are the Mass Air Flow (MAF) sensor, Manifold Pressure (MAP) sensor and Throttle Position sensor (TPS).</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with the Turbocharger Boost Pressure sensor. In this case, the Turbocharger Boost Pressure Performance</p>	<p>measured MAP - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Offset</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND Measured TIAP - measured Baro - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Offset</p> <p>TIAP Correlation is valid when High Engine Air Flow has been TRUE for a period of time OR Low Engine Air Flow has been TRUE for a period of time</p> <p>High Engine Air Flow is TRUE when Mass Air Flow</p>	<p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 1.0 seconds</p> <p>> 1.0 seconds</p> <p>> a threshold in gm/sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min Air Flow</p>	<p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP Model 3 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP3 Residual Weight Factor based on RPM</p> <p>TIAP Model 1 Error multiplied by P0101, P0106, P0121, P0236, P1101: TIAP Residual Weight Factor based on RPM</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA MnfdTempSensorFA TC_BoostPresSnsrCktFA AmbientAirDefault</p> <p>EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP MnfdTempSensorCktFP</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		diagnostic will fail.	<p>AND Manifold Pressure</p> <p>> a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- MAP Correlation Min MAP</p> <p>AND Filtered Mass Air Flow - Mass Air Flow</p> <p>< 3.0 gm/sec</p> <p>Low Engine Air Flow is TRUE when Mass Air Flow</p> <p>< a threshold in gm/ sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- Baro Correlation Max Air Flow</p> <p>AND Manifold Pressure</p> <p>< a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- Baro Correlation Max MAP</p> <p>AND Mass Air Flow - Filtered Mass Air Flow</p> <p>< 2.0 gm/sec</p>					
			<p><u>Engine Not Rotating:</u></p> <p>Turbocharger Boost Pressure OR Turbocharger Boost</p>	<p>< 50.0 kPa</p>	<p>Time between current ignition cycle and the last time the engine was running</p> <p>Engine is not rotating</p>	<p>> 10.0 seconds</p>	<p>4 failures out of 5 samples</p> <p>1 sample every 12.5 msec</p>	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Pressure OR ABS(Manifold Pressure - Baro Pressure) AND ABS(Turbocharger Boost Pressure - Manifold Pressure) AND ABS(Turbocharger Boost Pressure - Baro Pressure)	> 115.0 kPa ≤ 10.0 kPa > 10.0 kPa > 10.0 kPa	- No Active DTCs: No Pending DTCs:	EngineModeNotRunTimer Error MAP_SensorCircuitFA AAP_SnsrCktFA AAP2_SnsrCktFA MAP_SensorCircuitFP AAP_SnsrCktFP AAP2_SnsrCktFP		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Boost Pressure Sensor Circuit Low (Gen III)	P0237	Detects a continuous short to ground in the Turbocharger Boost Pressure signal circuit by monitoring the Turbocharger Boost Pressure sensor output voltage and failing the diagnostic when the Turbocharger Boost Pressure voltage is too low. The Turbocharger Boost Pressure sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	Turbocharger Boost Pressure Voltage	< 19.4 % of 5 Volt Range (This is equal to 49.9 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Boost Pressure Sensor Circuit High (Gen III)	P0238	Detects a continuous short to power or open circuit in the Turbocharger Boost Pressure signal circuit by monitoring the Turbocharger Boost Pressure sensor output voltage and failing the diagnostic when the Turbocharger Boost Pressure voltage is too high. The Turbocharger Boost Pressure sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	Turbocharger Boost Pressure Voltage	> 78.0 % of 5 Volt Range (This is equal to 299.0 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit	P0243	<p>Controller specific output driver circuit diagnostic, diagnosing the 'turbocharger boost solenoid'A' actuator' low sided driver for an open circuit failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series applications, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In a parallel application, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates open circuit failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for an open circuit.</p>	<p>≥ 200 K Ω impedance between output and controller ground</p>	<p>Diagnostic enabled *****</p> <p>Powertrain relay voltage</p> <p>Ignition run crank voltage *****</p> <p>Engine does not crank</p> <p>Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts</p> <p>> 5.00 Volts *****</p>	<p>10 failures out of 20 samples</p> <p>100ms / sample</p>	<p>Type A, 1 Trips</p> <p>Note: In certain controllers P0245 may also set turbocharger wastegate / supercharger boost solenoid A control circuit low</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit Low	P0245	<p>Controller specific output driver circuit diagnostic, diagnosing the 'turbocharger boost solenoid 'A' actuator' low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series applications, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In a parallel application, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to ground.</p> <p>In certain controllers this diagnosis runs only when the HWIO-output is driven by the application S/W.</p>	<p>$\leq 0.5 \Omega$ impedance between output and controller ground</p>	<p>Diagnostic enabled *****</p> <p>Powertrain relay voltage</p> <p>Ignition run crank voltage *****</p> <p>Engine does not crank</p> <p>Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts</p> <p>> 5.00 Volts *****</p>	<p>10 failures out of 20 samples</p> <p>100ms / sample</p>	<p>Type A, 1 Trips</p> <p>Note: In certain controllers P0243 may also set turbocharger wastegate / supercharger boost solenoid A control circuit</p>

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbocharger Wastegate / Supercharger Boost Solenoid A Control Circuit High	P0246	<p>Controller specific output driver circuit diagnostic, diagnosing the 'turbocharger boost solenoid 'A' actuator' low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.</p> <p>In series applications, turbocharger 'A' is the first turbocharger in the direction of exhaust flow. In a parallel application, turbocharger 'A' is associated with engine bank 1.</p>	<p>Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.</p> <p>Controller specific output driver circuit voltage thresholds are set to meet the following controller specification for a short to power.</p> <p>In certain controllers this diagnosis runs only when the HWIO-output is driven by the application S/W.</p>	<p>$\leq 0.5 \Omega$ impedance between output and controller power</p>	<p>Diagnostic enabled *****</p> <p>Powertrain relay voltage</p> <p>Ignition run crank voltage *****</p> <p>Engine does not crank</p> <p>Diagnostic system not disabled</p>	<p>True *****</p> <p>≥ 11.0 Volts</p> <p>> 5.00 Volts *****</p>	<p>10 failures out of 20 samples</p> <p>100ms / sample</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Engine Underboost Turbocharge r with wastegate. Not supercharge r with mechanical compressor	P0299	This DTC indicates an under boost failure. Two failure paths are considered. At steady state engine operating conditions with boost pressure closed loop control being active, a positive boost pressure deviation indicates underboost conditions. During transient conditions, in case the boost pressure increase gradient is below a diagnostic threshold, underboost conditions will be detected.	Desired boost pressure - Actual boost pressure	<refr to P0299: Underboost pressure deviation limit as a function of engine speed and desired boost pressure + P0234 P0299: Ambient pressure correction as a function of engine speed and ambient pressure in Supporting tables.	Dev. Diagnostic enable ***** Coolant temperature or OBD Coolant Enable Criteria and Coolant temperature Intake air temperature is in range Ambient air pressure is in range Engine speed in range Desired boost pressure in range Desired boost pressure derivative in range ***** All conditions haveto be fullfilled for: ***** No active DTCs: ***** Pressure control has to be in closed loop.	True ***** > -40.0 °C = TRUE) < 130.0 °C > -40.0 °C < 80.0 °C > 60.0 kPa < 120.0 kPa > 1,600 rpm < 6,000 rpm > 140.0 kPa < 300.0 kPa > -75.0 kPa/s < 75.0 kPa/s ***** >refer to P0234 P0299: Boost deviation diagnostic enable delay as a function of engine speed in Supporting tables. ***** BSTR_b_PCA_CktFA BSTR_b_TurboBypassCkt FA ECT_Sensor_FA IAT_SensorFA BSTR_b_BoostSnsrFA AmbientAirDefault *****	15 failures out of 15 samples 100ms / sample	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No device control active for WG and compressor recirculation valve.			
			Actual boost pressure delta the delta is limited by these tables: refer to Max: P0299: Underboost high rate limit as a function of engine speed Min: P0299: Underboost low rate limit as a function of engine speed in supporting tables.	< 10.00	Rate base diagnostic enable and Dev. Diagnostic enable ***** Coolant temperature or OBD Coolant enable criteria and Coolant temperature Intake air temperature is in range Ambient air pressure is in range Desired boost pressure in range Desired boost pressure derivative in hysteresis range Engine speed is in range ***** All conditions have to be fulfilled for: ***** No active DTCs:	False True ***** > -40.0 °C = TRUE) < 130.0 °C > -40.0 °C < 80.0 °C > 60.0 kPa < 120.0 kPa > 140.0 kPa < 300.0 kPa Enable Limit: 20.0 Disable Limit: -20.0 > 2,000 rpm < 3,500 rpm ***** > 0.20 Seconds ***** BSTR_b_PCA_CktFA BSTR_b_TurboBypassCktFA ECT_Sensor_FA IAT_SensorFA BSTR_b_BoostSnsrFA	10 failures out of 20 samples 100ms / sample	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>*****</p> <p>Pressure control has to be in closed loop.</p> <p>No device control active for WG and compressor recirculation valve.</p>	<p>AmbientAirDefault *****</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit Bank 2	P0330	<p>This diagnostic checks for an open in the knock sensor circuit Sensor 2/Bank 2. There are two possible methods used:</p> <p>1. 20 kHz Method: This method injects a 20 kHz signal (internal to the ECU) onto one of the Knock Sensor inputs. For a normal/good circuit the 20 kHz signal will propagate through the Knock sensor and back to the ECU through the sensor return circuit. The 20 kHz signal is processed through the Fast Fourier Transform (FFT) and then filtered with a first-order lag filter. Since the Knock Detection algorithm uses a Differential Op-Amp to compare the input from the two knock sensor wires, the FFT 20 kHz diagnostic signal will have either:</p> <p>A. Low output with a good circuit (because the 20 kHz injected signal is detected on both of the sensor inputs) or B. High output for an</p>	<p>Open Circuit Method chosen (2 possible methods: 20 kHz or Normal Noise):</p> <p>Filtered FFT Output</p> <p>Filtered FFT Output</p>	<p>= P0325_P0330_OpenMethod_2 (supporting table)</p> <p>Case 1 (20 kHz Method): > P0325_P0330_OpenCktThrshMin (20 kHz) AND < P0325_P0330_OpenCktThrshMax (20 kHz)</p> <p>Case 2 (Normal Noise Method): > P0325_P0330_OpenCktThrshMin (Normal Noise) AND < P0325_P0330_OpenCktThrshMax (Normal Noise)</p>	<p>Diagnostic Enabled?</p> <p>Engine Run Time</p> <p>Engine Speed</p> <p>Cumulative Number of Engine Revs (per key cycle) within min/max Engine Speed enable (above)</p> <p>Engine Air Flow</p> <p>Engine Coolant Temperature</p> <p>or</p> <p>OBD Coolant Enable Criteria</p> <p>Inlet Air Temperature</p>	<p>Yes</p> <p>≥ 2.0 seconds</p> <p>≥ 650 RPM and ≤ 8,500 RPM</p> <p>≥ 100 revs</p> <p>≥ 40 mg/cylinder and ≤ 2,000 mg/cylinder</p> <p>≥ -40 deg's C</p> <p>= TRUE</p> <p>≥ -40 deg's C</p>	<p>First Order Lag Filter with Weight Coefficient</p> <p>Weight Coefficient = 0.0100</p> <p>Updated each engine event</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>Open Circuit (because the 20 kHz injected signal is detected only on one of the sensor inputs).</p> <p>The 20 kHz method is typically used for the entire operating region of the engine. However, some engines may not have adequate separation between good and bad circuits at high engine speed. In these cases the 20 kHz method is used at low and medium engine speeds, and the "Normal Noise" method is used at high engine speed only.</p> <p>2. Normal Noise: The Normal Noise method monitors the background engine noise level for a selected frequency range output of the knock detection FFT. The background noise (i.e. Normal Noise) is filtered with a first-order lag filter. A good circuit is determined when the filtered Normal Noise signal is greater than the threshold.</p> <p>See Supporting Tables</p>						

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>for method definition: P0325_P0330_OpenMeth defines which of the two diagnostic methods is used as a function of engine speed (RPM). Typical implementations: A. Use 20 kHz method at all engine RPM (used when acceptable separation achieved at all RPM) or B. Use 20 kHz method at low/medium RPM and Normal Noise at high RPM</p>						

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Performance Bank 2	P0331	This diagnostic checks for knock sensor performance out of the normal expected range, on a per sensor basis. This diagnostic is specifically designed to identify the fault condition where the knock sensor is properly attached electrically, but produces an Abnormally low output due to being unattached (or loosely attached) with the the mounting bolt (and thus unable to properly transfer the engine vibration energy from the engine block to the knock sensor). The term "Abnormal (engine) Noise" is used to define this diagnostic method. A fault condition is identified when a first-order lag filtered version of the Abnormal Noise signal falls below the diagnostic threshold.	<p>Filtered FFT Intensity (where 'FFT Intensity' = Non-knocking, background engine noise)</p> <p>Filtered FFT Intensity</p>	<p>Case 1: Engine <u>not</u> in AFM mode < P0326_P0331_AbnormalNoise_Threshold (Supporting Table)</p> <p>OR</p> <p>Case 2: Engine <u>is</u> in AFM mode < P0326_P0331_AbnormalNoise_Thresh_AFM (Supporting Table)</p>	<p>Diagnostic Enabled?</p> <p>Engine Run Time</p> <p>Engine Speed</p> <p>Engine Air Flow</p> <p>Engine Coolant Temperature</p> <p>or</p> <p>OBD Coolant Enable Criteria</p> <p>Inlet Air Temperature</p> <p>Individual Cylinders enabled for Abnormal Noise</p> <p>Cumulative Number of Engine Revs Above Min Eng Speed (per key cycle)</p>	<p>Yes ≥ 2.0 seconds</p> <p>≥ 2,000 RPM (not in AFM mode) OR > 2,000 (in AFM mode)</p> <p>AND ≤ 8,500 RPM</p> <p>≥ 0 mg/cylinder AND ≤ 2,000 mg/cylinder</p> <p>≥ -40 deg's C</p> <p>= TRUE</p> <p>≥ -40 deg's C</p> <p>P0326_P0331_Abnormal Noise_CylsEnabled (Supporting Table)</p> <p>≥ 200 Revs</p>	<p>First Order Lag Filters with Weight Coefficient = 0.0100</p> <p>Updated each engine event</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit Low Bank 2	P0332	This diagnostic checks for an out of range low knock sensor signal. A 3-resistor bias network at each sensor input to the ECM provides a DC diagnostic voltage that will remain within a normal range when the external knock sensor circuit is free of short circuit faults. The diagnostic output is reported as a percentage (0 to 100%) when compared to the 5.0 volt reference voltage.	Sensor Input or Return Signal Line	< 8.0 Percent (of 5 Volt Reference)	Diagnostic Enabled? Engine Speed	Yes > 0 RPM and < 8,500 RPM	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Knock Sensor (KS) Circuit High Bank 2	P0333	This diagnostic checks for an out of range high knock sensor signal. A 3-resistor bias network at each sensor input to the ECM provides a DC diagnostic voltage that will remain within a normal range when the external knock sensor circuit is free of short circuit faults. The diagnostic output is reported as a percentage (0 to 100%) when compared to the 5.0 volt reference voltage.	Sensor Input or Return Signal Line	> 39.00 Percent (of 5 Volt Reference)	Diagnostic Enabled? Engine Speed	Yes > 0 RPM and < 8,500 RPM	50 Failures out of 63 Samples 100 msec rate	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position Sensor - Crankshaft Start Position Incorrect	P034A	Monitors the position of the crankshaft during auto-start's to verify that the crankshaft is in the expected position-diagnostic will fail if the crankshaft is not in the expected range otherwise the diagnostic will pass	Crankshaft position is in error by a number of crankshaft wheel teeth	> 2 crankshaft teeth	Engine has started rotating during a hybrid auto-start Crankshaft position is being verified No Active DTCs:	CrankSensor_FA	2 failures out of 3 samples a sample occurs each time the engine is started	Type B, 2 Trips
			Crankshaft position is in error by at least one crankshaft wheel tooth		Engine has started rotating during a hybrid auto-start Crankshaft position is being verified No Active DTCs:	CrankSensor_FA	4 failures out of 5 samples a sample occurs each time the engine is started	

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position Sensor - Crankshaft Direction Incorrect	P034B	Detects if the crankshaft is not rotating in the correct direction- will fail if the engine is reported to be spinning backwards while the engine is running otherwise the diagnostic will pass.	Number of crankshaft sensor reversals within a period of time	>= 3 <= 10.0 seconds	Engine Speed Engine Speed Engine Air Flow Engine Movement Detected No Active DTCs:	> 400 RPM < 2,000 RPM >= 3.0 grams/second CrankSensor_FA	Continuous Every 250 msec	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

[illegible]

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Multi- Function Input B Circuit	P0589	Detect when cruise control multi-function switch circuit B (analog) voltage is in an illegal range	Cruise Control analog circuit B voltage must be "between ranges" for greater than a calibratable period of time.	The cruise control analog voltage A/D count ratio is considered to be "between ranges" when the ratio is measured in the following ranges: 0.28 -0.31, 0.415-0.445, 0.585 - 0.615, 0.78 - 0.81, 1.005 - 1.035	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 0.500 seconds	Type C, No SVS ,Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Multi- Function Input B Circuit Low	P0592	detects short to ground failure for cruise multi- function switch circuit B	Cruise Control analog circuit B voltage must be in an "Open Short To Ground" range for greater than a calibratable period of time.	The cruise control Circuit B analog voltage A/D count ratio is considered to be "open short to groun"d when the ratio is measured in the following ranges: 0 - 0.185	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 2.00 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Multi- Function Input B Circuit High	P0593	detects short to power failure for cruise multi- function switch circuit B	Cruise Control analog circuit B voltage must be in a "Short To Power" range for greater than a calibratable period of time.	The cruise control Circuit B analog voltage A/D count ratio is considered to be "short to power" when the ratio is measured in the following range: 1.005 - 1.035	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 2.00 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Intake Camshaft System Cold Start Performance – Bank 1	P05CC	<p>Detects a VVT system error during Cold Starts by comparing the desired and actual cam positions when VVT is activated.</p> <p>This is the same type diagnostic as P0011 except this detects excessive deviations of position while the cold start phaser positions are being commanded.</p>	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive	Cam Position Error > 6.00 deg.	<p>Intake Cam Phsr Enable</p> <p>System Voltage</p> <p>Engine Running</p> <p>Power Take Off (PTO) active</p> <p>Catalyst Warmup Enabled</p> <p>Desired cam position</p> <p>Desired AND Measured cam position</p> <p>Desired cam position variation</p> <p>No Active DTCs</p>	<p>= TRUE</p> <p>> 11.00 Volts</p> <p>= TRUE</p> <p>= FALSE</p> <p>= TRUE</p> <p>> 0 deg</p> <p>> 6.00 deg AND < 26.00 deg</p> <p>< 3.00 deg for (P0011_P05CC_StablePo sitionTimeIc1) seconds</p> <p>P0010 P2088 P2089</p>	<p>65 failures out of 75 samples</p> <p>100 ms /sample</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Exhaust Camshaft System Cold Start Performance – Bank 1	P05CE	<p>Detects a VVT system error during Cold Starts by comparing the desired and actual cam positions when VVT is activated.</p> <p>This is the same type diagnostic as P0014 except this detects excessive deviations of position while the cold start phaser positions are being commanded.</p>	Camshaft position error [absolute value of (desired position - actual position)] is compared to thresholds to determine if excessive	Cam Position Error > 6.00 deg.	<p>Exhaust Cam Phsr Enable</p> <p>System Voltage</p> <p>Engine Running</p> <p>Power Take Off (PTO) active</p> <p>Catalyst Warmup Enabled</p> <p>Desired cam position</p> <p>Desired AND Measured cam position</p> <p>Desired cam position variation</p> <p>No Active DTCs</p>	<p>= TRUE</p> <p>> 11.00 volts</p> <p>= TRUE</p> <p>= FALSE</p> <p>= TRUE</p> <p>> 0 deg</p> <p>> 6.00 deg AND < 32.00 deg</p> <p>< 3.00 deg for (P0014_P05CE_StablePo sitionTimeEc1) sec</p> <p>P0013 P2090 P2091</p>	<p>65 failures out of 75 samples</p> <p>100 ms /sample</p>	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module O2 Sensor Processor Performance Bank 1) (For use with WRAF	P064D	<p>Diagnoses the WRAF Application-Specific Integrated Circuit (ASIC) for Controller Status and Measure Valid faults. These faults can impact closed loop fuel control. This DTC when enabled, monitors the two different failure counters it receives from the WRAF ASIC.</p> <p>The individual diagnostic failure counters are incremented based on the message received from the ASIC. The DTC is set based on any of the two individual fail and sample counters.</p>	B1S1 WRAF ASIC indicates control module faults	Controller Status fail counts and Measure Valid fail counts are accumulated to determine fault status	<p>Engine Run or Auto stop</p> <p>Heater Warm-up delay</p> <p>WRAF circuit diagnostic delay since power up</p>	<p>= True</p> <p>= Complete</p> <p>≥ 20.0 sec</p>	<p>128 controller status fail counts out of 160 samples</p> <p>OR</p> <p>128 measure valid fail counts out of 160 samples</p> <p>25 ms / sample</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module Knock Sensor Processor 2 Performance	P06B7	This diagnostic checks for a fault with the internal test circuit (sensor #2) used only for the '20 kHz' method of the Open Circuit Diagnostic. A fault is present when the signal level from the 20 kHz range of the FFT output falls between the Open Test Circuit thresholds.	FFT Diagnostic Output	> P06B6_P06B7_OpenT estCktThrshMin AND < P06B6_P06B7_OpenT estCktThrshMax See Supporting Tables	Diagnostic Enabled? Engine Run Time Engine Speed Cumulative Number of Engine Revs (per key cycle) within min/max Engine Speed enable (above) Engine Air Flow	Yes ≥ 2.0 seconds > 650 RPM and < 8,500 RPM ≥ 200 Revs ≥ 10 mg/cylinder and ≤ 2,000 mg/cylinder	First Order Lag Filter with Weight Coefficient Weight Coefficient = 0.0100 Updated each engine event	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Control Module (TCM) Requested MIL Illumination	P0700	Monitors the TCM MIL request message to determine when the TCM has detected a MIL illuminating fault.	Transmission Control Module Emissions-Related DTC set and module is requesting MIL	Transmission Control Module Emissions-Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Inlet Airflow System Performance (single turbo)	P1101	<p>Detects a performance failure in the Manifold Pressure (MAP) sensor, Turbocharger Boost Pressure sensor, Throttle Position sensor (TPS) or Mass Air Flow (MAF) sensor that cannot be uniquely identified as a failure in one individual sensor. This diagnostic can set when more than one of these sensors has a performance concern.</p> <p>This diagnostic is performed using the Intake Flow Rationality Diagnostic (IFRD). IFRD calculates modeled values of sensors from these four sensors.</p> <p>These modeled values are compared against the actual sensor values to see if they are similar. If they are similar, then the model passes. If they are not similar, then that model is considered to be failed. Certain combinations of model passes and model failures can be interpreted to be caused by a performance issue with</p>	<p>See table P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix for combinations of model failures that can set this DTC.</p> <p>MAF model fails when ABS(Measured Flow – Modeled Air Flow) Filtered</p> <p>MAP1 model fails when ABS(Measured MAP – MAP Model 1) Filtered</p> <p>MAP2 model fails when ABS(Measured MAP – MAP Model 2) Filtered</p> <p>MAP3 model fails when ABS(Measured MAP – MAP Model 3) Filtered</p> <p>TIAP1 model fails when ABS(Measured TIAP – TIAP Model 1) Filtered</p> <p>TPS model fails when Filtered Throttle Model Error</p> <p>TIAP Correlation model fails when High Engine Air Flow is TRUE AND Measured TIAP -</p>	<p>> 20.0 grams/sec</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 300 kPa*(g/s)</p>	<p>Engine Speed Engine Speed</p> <p>(Coolant Temp OR OBD Coolant Enable Criteria</p> <p>Coolant Temp Intake Air Temp Intake Air Temp</p> <p>Minimum total weight factor (all factors multiplied together)</p> <p>See Residual Weight Factor tables.</p> <p>-</p>	<p>>= 400 RPM <= 6,000 RPM</p> <p>>= -9 Deg C</p> <p>= TRUE)</p> <p><= 130 Deg C >= -20 Deg C <= 125 Deg C</p> <p>>= 0.50</p> <p>Modeled Air Flow Error multiplied by P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM and P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est</p> <p>MAP Model 1 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM</p> <p>MAP Model 2 Error multiplied by</p>	<p>Continuous</p> <p>Calculation are performed every 12.5 msec</p>	<p>Type B, 2 Trips</p>

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		the system, but no single failed sensor can uniquely be identified. In this case, the Inlet Airflow System Performance diagnostic will fail.	<p>measured MAP - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Offset</p> <p>OR</p> <p>Low Engine Air Flow is TRUE AND Measured TIAP - measured Baro - offset as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Offset</p> <p>TIAP Correlation is valid when High Engine Air Flow has been TRUE for a period of time OR Low Engine Air Flow has been TRUE for a period of time</p> <p>High Engine Air Flow is TRUE when Mass Air Flow</p>	<p>> 30.0 kPa</p> <p>> 30.0 kPa</p> <p>> 1.0 seconds</p> <p>> 1.0 seconds</p> <p>> a threshold in gm sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min Air Flow</p>	<p>No Active DTCs:</p> <p>No Pending DTCs:</p>	<p>P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM</p> <p>MAP Model 3 Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: MAP3 Residual Weight Factor based on RPM</p> <p>TIAP Model 1 Error multiplied by P0101, P0106, P0121, P0236, P1101: TIAP Residual Weight Factor based on RPM</p> <p>Filtered Throttle Model Error multiplied by P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM</p> <p>MAP_SensorCircuitFA EGRValvePerformance_F A MAF_SensorCircuitFA CrankSensor_FA ECT_Sensor_FA IAT_SensorFA MnfdTempSensorFA TC_BoostPresSnsrCktFA AmbientAirDefault</p> <p>EGRValve_FP ECT_Sensor_Ckt_FP IAT_SensorCircuitFP MnfdTempSensorCktFP</p>		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>AND Manifold Pressure</p> <p>AND Filtered Mass Air Flow - Mass Air Flow</p> <p>Low Engine Air Flow is TRUE when Mass Air Flow</p> <p>AND Manifold Pressure</p> <p>AND Mass Air Flow - Filtered Mass Air Flow</p>	<p>> a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- MAP Correlation Min MAP</p> <p>< 3.0 gm/sec</p> <p>< a threshold in gm sec as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- Baro Correlation Max Air Flow</p> <p>< a threshold in kPa as a function of engine speed See table P0101, P0106, P0121, P0236, P1101: TIAP- Baro Correlation Max MAP</p> <p>< 2.0 gm/sec</p>				

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Set/ Coast Signal 2 Circuit	P155B	Detects a failure of the cruise set 2 switch in a continuously applied state	Cruise Control Set 2 switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 89.000 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 89.000 seconds	Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cruise Control Resume/ Acceleration Signal 2 Circuit	P155C	Detects a failure of the cruise resume 2 switch in a continuously applied state	Cruise Control Resume 2 switch remains applied for greater than a calibratable period of time.	fail continuously in the applied state for greater than 89.000 seconds	CAN cruise switch diagnostic enable in ECM	1.00	fail continuously for greater than 89.000 seconds	MIL: Type C, No SVS , Emissio ns Neutral Diagnost ics – special type C

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Analog Mode Switch Circuit Low	P159F	This DTC will detect an analog driver mode switch input that is too low out of range.	<p>For button type Normal_Button</p> <p>Analog Mode Switch low voltage threshold % of 5V range</p> <p>For button type Enhanced_Button</p> <p>Analog Mode Switch low voltage threshold % of 5V range</p> <p>For button type Multiple_Button</p> <p>Analog Mode Switch low voltage threshold % of 5V range</p>	<p>< 29.00 %</p> <p>< 24.30 %</p> <p>< 21.20 %</p>	Vehicle mode analog switch button type	= CeDMDG_e_Normal_Button	<p>200 failures out of 250 samples</p> <p>25 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Analog Mode Switch Circuit High	P15A0	This DTC will detect an analog driver mode switch input that is too high out of range.	<p>For button type Normal_Button</p> <p>Analog Mode Switch high voltage threshold % of 5V range</p> <p>For button type Enhanced_Button</p> <p>Analog Mode Switch high voltage threshold % of 5V range</p> <p>For button type Multiple_Button</p> <p>Analog Mode Switch high voltage threshold % of 5V range</p>	<p>>= 88.80 %</p> <p>>= 94.10 %</p> <p>>= 95.30 %</p>	Vehicle mode analog switch button type	= CeDMDG_e_Normal_Button	<p>200 failures out of 250 samples</p> <p>25 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Analog Mode Switch Performance	P15A1	This DTC will detect an analog driver mode switch input that is in an indeterminate range.	<p>For button type Normal_Button</p> <p>Analog Mode Switch indeterminate region % of 5V range</p> <p>For button type Enhanced_Button</p> <p>Analog Mode Switch indeterminate regions % of 5V range</p> <p>For button type Multiple_Button</p> <p>Analog Mode Switch indeterminate regions % of 5V range</p>	<p>66.80 % \leq % of 5 volts < 72.80 %</p> <p>63.50 % \leq % of 5 volts < 65.50 %</p> <p>83.50 % \leq % of 5 volts < 85.50 %</p> <p>52.90 % \leq % of 5 volts < 54.10 %</p> <p>74.10 % \leq % of 5 volts < 75.30 %</p> <p>87.50 % \leq % of 5 volts < 88.60 %</p>	Vehicle mode analog switch button type	= CeDMDG_e_Normal_Button	<p>200 failures out of 250 samples</p> <p>25 ms / sample</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Brake Pedal Position Sensor Signal Message Counter Incorrect	P15FB	Detects rolling count or protection value errors in Chassis Brake Pedal Position Emissions Related serial data signal	If x of y rolling count / protection value faults occur, default brake pedal position to zero for duration of fault		Chassis Brake Pedal Position Emissions Related Serial Data Error Diagnostic Enable	1.00	9.00 / 17.00 counts	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 2 Performance (For use on vehicles with mechanical transfer pump dual fuel tanks)	P2066	This DTC will detect a fuel sender stuck in range in the secondary fuel tank.	<p>*****</p> <p>Fuel Level in Primary and Secondary Tanks Remain in an Unreadable Range too Long</p> <p>*****</p> <p>This subtest is used</p> <p>If fuel volume in primary tank is</p> <p>and fuel volume in secondary tank is</p> <p>and remains in this condition for</p> <p>of fuel consumed by the engine.</p> <p>OR</p> <p>*****</p> <p>Fuel Level is in a Readable Range for both Primary and Secondary Tanks too Long</p> <p>*****</p> <p>This subtest is not used</p> <p>Volume in primary tank is</p> <p>and volume in secondary tank is</p> <p>and remains in this condition for</p> <p>OR</p> <p>*****</p> <p>Fuel consumed without a Secondary Fuel Level Change</p>	<p>≥ 28.3 liters</p> <p>< 5.0 liters</p> <p>18.1 liters</p> <p>< 28 liters</p> <p>> 5 liters</p> <p>1,800 seconds</p>	<p>Engine Running</p> <p>No active DTCs:</p>	<p>VehicleSpeedSensor_FA</p>	250 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>*****</p> <p>If the vehicle is driven with the fuel consumed by the engine of without the secondary fuel level changing by 3 liters, then the sender must be stuck.</p>	20 liters				

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 2 Circuit Low Voltage (For use on vehicles with dual fuel tanks)	P2067	This DTC will detect a fuel sender stuck out of range low in the secondary fuel tank.	Fuel level Sender % of 5V range	< 10 %			100 failures out of 125 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Level Sensor 2 Circuit High Voltage (For use on vehicles with dual fuel tanks)	P2068	This DTC will detect a fuel sender stuck out of range low in the secondary fuel tank.	Fuel level Sender % of 5V range	> 60 %			100 failures out of 125 samples 100 ms / sample	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Performance (single turbo)	P2227	Detects a performance failure in the Barometric Pressure (BARO) sensor, such as when a BARO value is stuck in range.	<u>Engine Running:</u>		No Active DTCs:	AmbPresSnsrCktFA IAT_SensorFA MAF_SensorFA AfterThrottlePressureFA TPS_FA TPS_Performance_FA VehicleSpeedSensor_FA TC_BoostPresSnsrFA	320 failures out of 400 samples	Type A, 1 Trips
		If the engine has been off for a sufficient amount of time, the pressure values in the induction system will have equalized. The BARO sensor value is checked to see if it is within the normal expected atmospheric pressure range. If it is not, then the BARO performance diagnostic will fail.	Difference between Baro Pressure reading and Estimated Baro when distance since last Estimated Baro update	> 15.0 kPa <= 0.06 miles			1 sample every 12.5 msec	
		If the BARO sensor value is within the normal expected atmospheric range, then Manifold Pressure (MAP), Turbocharger Boost Pressure and BARO are compared to see if their values are similar. If the MAP and Turbocharger Boost Pressure sensor values are similar, but the BARO value is not similar, then a BARO performance diagnostic will fail.	<u>Engine Not Rotating:</u>		Time between current ignition cycle and the last time the engine was running		4 failures out of 5 samples	
			Barometric Pressure OR Barometric Pressure	< 50.0 kPa > 115.0 kPa	Engine is not rotating	> 10.0 seconds	1 sample every 12.5 msec	
			OR		No Active DTCs:	EngineModeNotRunTimer Error MAP_SensorCircuitFA AAP_SnsrCktFA AAP2_SnsrCktFA		
			ABS(Manifold Pressure - Baro Pressure) AND ABS(Turbocharger Boost Pressure - Manifold Pressure) AND ABS(Turbocharger Boost Pressure - Baro Pressure)	> 10.0 kPa <= 10.0 kPa > 10.0 kPa	No Pending DTCs:	MAP_SensorCircuitFP AAP_SnsrCktFP AAP2_SnsrCktFP		
		When the engine is						

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		running, there is an estimate of barometric pressure that is determined with the Turbocharger Boost Pressure sensor, engine air flow and engine speed. If the BARO value from the sensor is not similar to this barometric pressure estimate, then the BARO performance diagnostic will fail.						

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Circuit Low (boosted applications, Gen III)	P2228	Detects a continuous short to ground in the Barometric Pressure (BARO) signal circuit by monitoring the BARO sensor output voltage and failing the diagnostic when the BARO voltage is too low. The BARO sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	BARO Voltage	< 39.3 % of 5 Volt Range (This is equal to 50.0 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Barometric Pressure (BARO) Sensor Circuit High (boosted applications, Gen III)	P2229	Detects a continuous short to power or open circuit in the Barometric Pressure (BARO) signal circuit by monitoring the BARO sensor output voltage and failing the diagnostic when the BARO voltage is too high. The BARO sensor is a pressure transducer which outputs a voltage proportional to the absolute pressure.	BARO Voltage	> 90.0 % of 5 Volt Range (This is equal to 115.0 kPa)			320 failures out of 400 samples 1 sample every 12.5 msec	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Pumping Current Performance Bank 1 (For use with WRAF - E80	P223C	<p>This DTC determines if the WRAF O2 sensor pumping current has an incorrect or out of range value. This DTC will detect open circuit faults to the Pump current, Ref Cell voltage, Ref Ground and Trim circuits. When enabled, the diagnostic monitors the pumping current in three different fault regions during DFCO.</p> <p>The individual diagnostic failure counters are incremented based on the diagnostic results in each region. The DTC is set based on any of the three individual fail and sample counters.</p>	<p>Fault condition present when the pump current is in any of the fault regions when this test is enabled during DFCO.</p> <p>Note: This ASIC is referred to as C2WRAF (Delphi).</p>	<p>The three pump current fault regions are:</p> <p>A) Pump current > 4.18 ma</p> <p>B) Pump current ≤ 0.10 ma and ≥ -0.10 ma</p> <p>C) Pump current < -0.10 ma</p> <p>The three fault regions have individual X out of Y calibrations. When the X out of Y is reached in any region this DTC is set.</p> <p>Note: A open circuit on the Pump current signal may also set a P0131 DTC.</p> <p>Note: A short to ground on the trim circuit can set P223C.</p>	<p>B1S1 DTC's Not active this key cycle</p> <p>Measure Valid status (ASIC)</p> <p>Controller status (ASIC)</p> <p>Engine Run or Auto stop</p> <p>*****</p> <p>Heater Warm-up delay Then WRAF circuit diagnostic delay (since heater Warm-up delay is complete) *****</p> <p>WRAF Ref cell temperature</p> <p>Test starts when time in DFCO</p> <p>Test stops when time in DFCO</p>	<p>P0135, P0030, P0031 or P0032</p> <p>= Valid</p> <p>= Ready</p> <p>= True</p> <p>= Complete</p> <p>≥ 20.0 seconds</p> <p>≥ 628 Deg C</p> <p>≥ 5.0 seconds</p> <p>> 12.0 seconds</p>	<p>Region A: 224 failures out of 280 samples</p> <p>OR</p> <p>Region B: 224 failures out of 280 samples</p> <p>OR</p> <p>Region C: 224 failures out of 280 samples</p> <p>Sample rate is 25 msec.</p> <p>Test enabled during DFCO.</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
O2 Sensor Reference Resistance Out Of Range Bank 1	P223E	<p>This DTC determines if the WRAF O2 sensor reference cell has an incorrect or out of range resistance value. This test compares the element's resistance (from the WRAF sensor Application-Specific Integrated Circuit (ASIC)) to the expected values for the enabled condition. The element temperature is directly related to the element resistance based on the released sensor element specifications.</p> <p>The diagnostic failure counter is incremented if the element temperature is outside the expected range. This DTC is set based on the fail and sample counters.</p>	Measured Reference cell temperature	< 700 Deg C OR > 1,000.0 Deg C	<p>B1S1 DTC's Not active this key cycle</p> <p>Measure Valid status (ASIC)</p> <p>Controller status (ASIC)</p> <p>Engine Run or Auto stop</p> <p>*****</p> <p>Heater Warm-up delay Then WRAF circuit diagnostic delay (since heater Warm-up delay is complete) Then Delay after WRAF circuit diagnostic delay *****</p>	<p>P0135, P0030, P0031 or P0032</p> <p>= Valid</p> <p>= Ready</p> <p>= True</p> <p>= Complete</p> <p>≥ 20.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>128 failures out of 160 samples</p> <p>Sample rate is 25 msec</p> <p>Continuous</p>	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Turbo/Super Charger Bypass Valve - Mechanical Turbocharge r with wastegate. Not supercharge r with mechanical compressor	P2261	This DTC indicates the compressor recirculation valve being stuck closed. This diagnostic is active at coast down let off conditions, where an airflow pulsation criteria is used as basis of this diagnostic.	When measuring time accumulated air mass flow derivate boost pressure is high pass filtered with filter frequency ***** A failure is detected when Acc. Filtered Air Mass Flow or Acc.Der.Filtered boost pressure	< 0.50 Second, = 10.00 Hz ***** > 65.00 g/s > 1,000.00 kPa/s	Diagnostic enabled ***** Engine speed ***** Bypass valve commanded open duty cycle For at least ***** Pressure ratio over the compressor relative limit Condition keep true for x seconds extra ***** Negative transient -> TRUE Relative boost and Pressure derivate Hysteresis negative transient -> FALSE Relative boost or Pressure derivate ***** No Active DTCs:	True ***** >= 1,500 rpm ***** > 6.00 % >= 0.25 s ***** > refer to P00C4 P2261: Compressor Surge Line in Supporting Tables 0.80 s ***** TRUE >= 35.00 kPa <= -150.00 kPa/s < 0.00 kPa > 55.00 kPa/s ***** BSTR_b_TurboBypassCkt FA BSTR_b_BoostSnrFA MAF_SensorFA	5 Failed tests out of 6 tests 25ms/ sample	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position Signal Output Circuit Low	P2615	Controller specific output driver circuit diagnoses the camshaft output low sided driver for a short to ground failure when the output is powered off by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver off state indicates short to ground failure.	Short to ground: ≤ 0.5 Ohms impedance between signal and controller ground Open Circuit: ≥ 200 K Ohms impedance between signal and controller ground	Powertrain Relay Voltage Engine is not cranking Camshaft Position Output is commanded high	≥ 11.0 Volts	40 failures out of 50 samples 1 sample every 100 msec	Type C, No SVS Note: In certain controllers P2614 may also set (Camshaft Position Signal Output Circuit / Open)

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Camshaft Position Signal Output Circuit High	P2616	Controller specific output driver circuit diagnoses the camshaft position output low sided driver for a short to power failure when the output is powered on by comparing a voltage measurement to controller specific voltage thresholds.	Voltage measurement outside of controller specific acceptable range during driver on state indicates short to power failure.	Short to power: ≤ 0.5 Ohms impedance between signal and controller power	Powertrain Relay Voltage Engine is not cranking Camshaft Position Output is commanded low	≥ 11.0 Volts	40 failures out of 50 samples 1 sample every 100 msec	Type C, No SVS

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Chassis Control Module 1 Requested MIL Illumination	P26C8	Monitors the Chassis Control Module 1 MIL request message to determine when the Chassis Control Module 1 has detected a MIL illuminating fault.	Chassis Control Module 1 Emissions-Related DTC set and module is requesting MIL	Chassis Control Module 1 Emissions- Related DTC set and module is requesting MIL		Time since power-up \geq 3 seconds	Continuous	Type A, No MIL

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With TCM	U0101	This DTC monitors for a loss of communication with the transmission control module	<p>Message is not received from controller for</p> <p>Message \$0BD</p> <p>Message \$0C7</p> <p>Message \$0F9</p> <p>Message \$189</p> <p>Message \$199</p> <p>Message \$19D</p> <p>Message \$1AF</p> <p>Message \$1F5</p> <p>Message \$4C9</p>	<p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 5.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U0101 TCM	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Brake System Control Module B (BSC2)	U01B4	This DTC monitors for a loss of communication with the Brake System Control Module B (BSC2) on the main high speed bus.	Message is not received from controller for Message \$4FB	 ≥ 10.0 seconds	General Enable Criteria: U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Run/Crank Ignition voltage Power Mode Off Cycle Enable Criteria: KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 5.0000 seconds Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for	Not Active on Current Key Cycle Enabled Not Active Not Active > 6.41 Volts = run = 1 (1 indicates enabled) = Active > 11.00 Volts > 0.4000 seconds	Diagnostic runs in 12.5 ms loop.	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U01B4 BSCM B or BSC2	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on LIN Bus 1 Off	U1501	This DTC monitors for a LIN bus off condition	LIN bus off failures	>= 3.00 counts	The following criteria have been enabled for Power Mode Run/Crank Voltage	>= 400.00 milliseconds =Run >= 11.00 Volts	Dependent on bus loading.	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
LIN Bus 1 Lost Communicati on with Device 0 (Shutter 1)	U1510	This DTC monitors for a loss of communication on the LIN bus with Shutter 1	ECM has lost communication over the LIN bus with Device 0 / Shutter 1 for	>= 3.00 counts	The following criteria have been enabled for Power Mode Run/Crank Voltage	>= 400.00 milliseconds =Run >= 11.00 Volts	LIN bus communication executes in 500ms loop	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module B	U179A	This DTC monitors for a loss of communication with the Hybrid Powertrain Control Module B	Message is not received from controller for	≥ 10.0 seconds	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Run/Crank Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 5.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>> 6.41 Volts</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00 Volts</p>	Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 ECM (CT6 Unique) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U179A Hybrid Powertrain Control Module B	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Multiple DTC Use_Green Sensor Delay Criteria - Limit

Description: This Calibration is the accumulated airflow limit above which the Green condition is expired

Used for: P0133, P013A, P013B, P013C, P013D, P013E, P013F, P014A, P014B, P0153, P015A, P015B, P015C, P015D, P1133, P1153, P2270, P2271, P2272 and P2273.

Note: This feature is only enabled when the vehicle is new and cannot be enabled in service.

Value Units: Grams

X Unit: Accumulated Engine Airflow

y/x	CiOXYR_O2_Bank1_Sensor1	CiOXYR_O2_Bank1_Sensor2	CiOXYR_O2_Bank2_Sensor1	CiOXYR_O2_Bank2_Sensor2
1	120,000	120,000	120,000	120,000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P05CC_StablePositionTimeIc1

Description: Minimum time for Intake Cam 1 phase position to be stable to enable performance diagnostic.

Value Units: Minimum time (sec)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P05CE_StablePositionTimeEc1

Description: Minimum time for Exhaust Cam 1 phase position to be stable to enable performance diagnostic.

Value Units: Minimum time (sec)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,200	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,600	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,000	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,400	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,800	100.0	80.0	6.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P00C4 P2261: Compressor Surge Line

Description: Turbo compressor recirculation valve diagnosis surge area limit.**Value Units:** [ratio] CRV diagnosis surge area limit.**X Unit:** [g/sec[] KnBSTD_dm_AirFlowBP - Air FLow

y/x	0.00	38.09	76.63	100.00	143.52	189.11
1	1.000	1.500	2.444	2.700	3.100	3.412

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

Description: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix - This table describes combinations of individual model failures that will set P0101, P0106, P010B, P0121, P0236 and P1101 on turbocharged applications.

Value Units: Boolean

X Unit: Unitless (See top line for heading information)

Y Units: Unitless

y/x	1	2	3	4	5	6	7	8	9
1	MAF Model	MAP1 Model	MAP2 Model	MAP3 Model	TIAP1 Model	TPS Model	TIAP Correlation	TIAP Correlation	DTC Set
2	Failed	Failed	Failed	Failed	Failed	Failed	Failed	Valid	
3	F	F	F	F	F	F	F	F	No DTC
4	F	F	F	F	F	F	F	T	No DTC
5	F	F	F	F	F	F	T	F	No DTC
6	F	F	F	F	F	F	T	T	No DTC
7	F	F	F	F	F	T	F	F	No DTC
8	F	F	F	F	F	T	F	T	No DTC
9	F	F	F	F	F	T	T	F	No DTC
10	F	F	F	F	F	T	T	T	No DTC
11	F	F	F	F	T	F	F	F	No DTC
12	F	F	F	F	T	F	F	T	No DTC
13	F	F	F	F	T	F	T	F	No DTC
14	F	F	F	F	T	F	T	T	No DTC
15	F	F	F	F	T	T	F	F	P1101
16	F	F	F	F	T	T	F	T	P0121
17	F	F	F	F	T	T	T	F	P1101
18	F	F	F	F	T	T	T	T	P0236
19	F	F	F	T	F	F	F	F	No DTC
20	F	F	F	T	F	F	F	T	P1101
21	F	F	F	T	F	F	T	F	P1101
22	F	F	F	T	F	F	T	T	P1101
23	F	F	F	T	F	T	F	F	P1101
24	F	F	F	T	F	T	F	T	P1101
25	F	F	F	T	F	T	T	F	P1101
26	F	F	F	T	F	T	T	T	P1101
27	F	F	F	T	T	F	F	F	P1101
28	F	F	F	T	T	F	F	T	P1101
29	F	F	F	T	T	F	T	F	P1101
30	F	F	F	T	T	F	T	T	P1101
31	F	F	F	T	T	T	F	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

32	F	F	F	T	T	T	F	T	P1101
33	F	F	F	T	T	T	T	F	P1101
34	F	F	F	T	T	T	T	T	P1101
35	F	F	T	F	F	F	F	F	No DTC
36	F	F	T	F	F	F	F	T	P1101
37	F	F	T	F	F	F	T	F	P1101
38	F	F	T	F	F	F	T	T	P1101
39	F	F	T	F	F	T	F	F	P1101
40	F	F	T	F	F	T	F	T	P1101
41	F	F	T	F	F	T	T	F	P1101
42	F	F	T	F	F	T	T	T	P1101
43	F	F	T	F	T	F	F	F	P1101
44	F	F	T	F	T	F	F	T	P1101
45	F	F	T	F	T	F	T	F	P1101
46	F	F	T	F	T	F	T	T	P1101
47	F	F	T	F	T	T	F	F	P1101
48	F	F	T	F	T	T	F	T	P1101
49	F	F	T	F	T	T	T	F	P1101
50	F	F	T	F	T	T	T	T	P1101
51	F	F	T	T	F	F	F	F	P1101
52	F	F	T	T	F	F	F	T	P1101
53	F	F	T	T	F	F	T	F	P1101
54	F	F	T	T	F	F	T	T	P1101
55	F	F	T	T	F	T	F	F	P1101
56	F	F	T	T	F	T	F	T	P1101
57	F	F	T	T	F	T	T	F	P1101
58	F	F	T	T	F	T	T	T	P1101
59	F	F	T	T	T	F	F	F	No DTC
60	F	F	T	T	T	F	F	T	No DTC
61	F	F	T	T	T	F	T	F	No DTC
62	F	F	T	T	T	F	T	T	No DTC
63	F	F	T	T	T	T	F	F	P1101
64	F	F	T	T	T	T	F	T	P1101
65	F	F	T	T	T	T	T	F	P1101
66	F	F	T	T	T	T	T	T	P1101
67	F	T	F	F	F	F	F	F	No DTC
68	F	T	F	F	F	F	F	T	P1101
69	F	T	F	F	F	F	T	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

70	F	T	F	F	F	F	T	T	P0236
71	F	T	F	F	F	T	F	F	P1101
72	F	T	F	F	F	T	F	T	P0121
73	F	T	F	F	F	T	T	F	P1101
74	F	T	F	F	F	T	T	T	P0236
75	F	T	F	F	T	F	F	F	P1101
76	F	T	F	F	T	F	F	T	P1101
77	F	T	F	F	T	F	T	F	P1101
78	F	T	F	F	T	F	T	T	P0236
79	F	T	F	F	T	T	F	F	P1101
80	F	T	F	F	T	T	F	T	P0121
81	F	T	F	F	T	T	T	F	P1101
82	F	T	F	F	T	T	T	T	P0236
83	F	T	F	T	F	F	F	F	P1101
84	F	T	F	T	F	F	F	T	P1101
85	F	T	F	T	F	F	T	F	P1101
86	F	T	F	T	F	F	T	T	P1101
87	F	T	F	T	F	T	F	F	P1101
88	F	T	F	T	F	T	F	T	P1101
89	F	T	F	T	F	T	T	F	P1101
90	F	T	F	T	F	T	T	T	P1101
91	F	T	F	T	T	F	F	F	P1101
92	F	T	F	T	T	F	F	T	P1101
93	F	T	F	T	T	F	T	F	P1101
94	F	T	F	T	T	F	T	T	P1101
95	F	T	F	T	T	T	F	F	P1101
96	F	T	F	T	T	T	F	T	P1101
97	F	T	F	T	T	T	T	F	P1101
98	F	T	F	T	T	T	T	T	P1101
99	F	T	T	F	F	F	F	F	P1101
100	F	T	T	F	F	F	F	T	P1101
101	F	T	T	F	F	F	T	F	P1101
102	F	T	T	F	F	F	T	T	P1101
103	F	T	T	F	F	T	F	F	P1101
104	F	T	T	F	F	T	F	T	P1101
105	F	T	T	F	F	T	T	F	P1101
106	F	T	T	F	F	T	T	T	P1101
107	F	T	T	F	T	F	F	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

108	F	T	T	F	T	F	F	T	P1101
109	F	T	T	F	T	F	T	F	P1101
110	F	T	T	F	T	F	T	T	P1101
111	F	T	T	F	T	T	F	F	P1101
112	F	T	T	F	T	T	F	T	P1101
113	F	T	T	F	T	T	T	F	P1101
114	F	T	T	F	T	T	T	T	P1101
115	F	T	T	T	F	F	F	F	P0106
116	F	T	T	T	F	F	F	T	P0106
117	F	T	T	T	F	F	T	F	P0106
118	F	T	T	T	F	F	T	T	P0106
119	F	T	T	T	F	T	F	F	P1101
120	F	T	T	T	F	T	F	T	P1101
121	F	T	T	T	F	T	T	F	P1101
122	F	T	T	T	F	T	T	T	P1101
123	F	T	T	T	T	F	F	F	P1101
124	F	T	T	T	T	F	F	T	P1101
125	F	T	T	T	T	F	T	F	P1101
126	F	T	T	T	T	F	T	T	P1101
127	F	T	T	T	T	T	F	F	P1101
128	F	T	T	T	T	T	F	T	P1101
129	F	T	T	T	T	T	T	F	P1101
130	F	T	T	T	T	T	T	T	P1101
131	T	F	F	F	F	F	F	F	No DTC
132	T	F	F	F	F	F	F	T	P1101
133	T	F	F	F	F	F	T	F	P1101
134	T	F	F	F	F	F	T	T	P0236
135	T	F	F	F	F	T	F	F	P1101
136	T	F	F	F	F	T	F	T	P0121
137	T	F	F	F	F	T	T	F	P1101
138	T	F	F	F	F	T	T	T	P0236
139	T	F	F	F	T	F	F	F	P1101
140	T	F	F	F	T	F	F	T	P1101
141	T	F	F	F	T	F	T	F	P1101
142	T	F	F	F	T	F	T	T	P0236
143	T	F	F	F	T	T	F	F	P1101
144	T	F	F	F	T	T	F	T	P0121
145	T	F	F	F	T	T	T	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

146	T	F	F	F	T	T	T	T	P0236
147	T	F	F	T	F	F	F	F	P1101
148	T	F	F	T	F	F	F	T	P1101
149	T	F	F	T	F	F	T	F	P1101
150	T	F	F	T	F	F	T	T	P1101
151	T	F	F	T	F	T	F	F	P1101
152	T	F	F	T	F	T	F	T	P1101
153	T	F	F	T	F	T	T	F	P1101
154	T	F	F	T	F	T	T	T	P1101
155	T	F	F	T	T	F	F	F	P1101
156	T	F	F	T	T	F	F	T	P1101
157	T	F	F	T	T	F	T	F	P1101
158	T	F	F	T	T	F	T	T	P1101
159	T	F	F	T	T	T	F	F	P1101
160	T	F	F	T	T	T	F	T	P1101
161	T	F	F	T	T	T	T	F	P1101
162	T	F	F	T	T	T	T	T	P1101
163	T	F	T	F	F	F	F	F	P1101
164	T	F	T	F	F	F	F	T	P1101
165	T	F	T	F	F	F	T	F	P1101
166	T	F	T	F	F	F	T	T	P1101
167	T	F	T	F	F	T	F	F	P1101
168	T	F	T	F	F	T	F	T	P1101
169	T	F	T	F	F	T	T	F	P1101
170	T	F	T	F	F	T	T	T	P1101
171	T	F	T	F	T	F	F	F	P1101
172	T	F	T	F	T	F	F	T	P1101
173	T	F	T	F	T	F	T	F	P1101
174	T	F	T	F	T	F	T	T	P1101
175	T	F	T	F	T	T	F	F	P1101
176	T	F	T	F	T	T	F	T	P1101
177	T	F	T	F	T	T	T	F	P1101
178	T	F	T	F	T	T	T	T	P1101
179	T	F	T	T	F	F	F	F	P1101
180	T	F	T	T	F	F	F	T	P1101
181	T	F	T	T	F	F	T	F	P1101
182	T	F	T	T	F	F	T	T	P1101
183	T	F	T	T	F	T	F	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

184	T	F	T	T	F	T	F	T	P1101
185	T	F	T	T	F	T	T	F	P1101
186	T	F	T	T	F	T	T	T	P1101
187	T	F	T	T	T	F	F	F	P0101 or P010B
188	T	F	T	T	T	F	F	T	P0101 or P010B
189	T	F	T	T	T	F	T	F	P0101 or P010B
190	T	F	T	T	T	F	T	T	P0101 or P010B
191	T	F	T	T	T	T	F	F	P1101
192	T	F	T	T	T	T	F	T	P1101
193	T	F	T	T	T	T	T	F	P1101
194	T	F	T	T	T	T	T	T	P1101
195	T	T	F	F	F	F	F	F	P1101
196	T	T	F	F	F	F	F	T	P1101
197	T	T	F	F	F	F	T	F	P1101
198	T	T	F	F	F	F	T	T	P0236
199	T	T	F	F	F	T	F	F	P1101
200	T	T	F	F	F	T	F	T	P0121
201	T	T	F	F	F	T	T	F	P1101
202	T	T	F	F	F	T	T	T	P0236
203	T	T	F	F	T	F	F	F	P1101
204	T	T	F	F	T	F	F	T	P1101
205	T	T	F	F	T	F	T	F	P1101
206	T	T	F	F	T	F	T	T	P0236
207	T	T	F	F	T	T	F	F	P1101
208	T	T	F	F	T	T	F	T	P0121
209	T	T	F	F	T	T	T	F	P1101
210	T	T	F	F	T	T	T	T	P0236
211	T	T	F	T	F	F	F	F	P1101
212	T	T	F	T	F	F	F	T	P1101
213	T	T	F	T	F	F	T	F	P1101
214	T	T	F	T	F	F	T	T	P1101
215	T	T	F	T	F	T	F	F	P1101
216	T	T	F	T	F	T	F	T	P1101
217	T	T	F	T	F	T	T	F	P1101
218	T	T	F	T	F	T	T	T	P1101
219	T	T	F	T	T	F	F	F	P1101
220	T	T	F	T	T	F	F	T	P1101
221	T	T	F	T	T	F	T	F	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P0236, P1101: Turbocharger Intake Flow Rationality Diagnostic Failure Matrix

222	T	T	F	T	T	F	T	T	P1101
223	T	T	F	T	T	T	F	F	P1101
224	T	T	F	T	T	T	F	T	P1101
225	T	T	F	T	T	T	T	F	P1101
226	T	T	F	T	T	T	T	T	P1101
227	T	T	T	F	F	F	F	F	P1101
228	T	T	T	F	F	F	F	T	P1101
229	T	T	T	F	F	F	T	F	P1101
230	T	T	T	F	F	F	T	T	P1101
231	T	T	T	F	F	T	F	F	P1101
232	T	T	T	F	F	T	F	T	P1101
233	T	T	T	F	F	T	T	F	P1101
234	T	T	T	F	F	T	T	T	P1101
235	T	T	T	F	T	F	F	F	P1101
236	T	T	T	F	T	F	F	T	P1101
237	T	T	T	F	T	F	T	F	P1101
238	T	T	T	F	T	F	T	T	P1101
239	T	T	T	F	T	T	F	F	P1101
240	T	T	T	F	T	T	F	T	P1101
241	T	T	T	F	T	T	T	F	P1101
242	T	T	T	F	T	T	T	T	P1101
243	T	T	T	T	F	F	F	F	P1101
244	T	T	T	T	F	F	F	T	P1101
245	T	T	T	T	F	F	T	F	P1101
246	T	T	T	T	F	F	T	T	P1101
247	T	T	T	T	F	T	F	F	P1101
248	T	T	T	T	F	T	F	T	P1101
249	T	T	T	T	F	T	T	F	P1101
250	T	T	T	T	F	T	T	T	P1101
251	T	T	T	T	T	F	F	F	P1101
252	T	T	T	T	T	F	F	T	P1101
253	T	T	T	T	T	F	T	F	P1101
254	T	T	T	T	T	F	T	T	P1101
255	T	T	T	T	T	T	F	F	P1101
256	T	T	T	T	T	T	F	T	P1101
257	T	T	T	T	T	T	T	F	P1101
258	T	T	T	T	T	T	T	T	P1101

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 MAP1 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1.000	1.000	1.000	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 MAP2 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1.000	1.000	1.000	1.000	0.857	0.896	0.850	0.999	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: MAP3 Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 MAP3 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1.000	1.000	1.000	1.000	0.864	0.889	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900	0.900

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 TPS Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P0236_P1101 TIAP Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1.000	0.700	0.600	1.000	1.000	0.990	0.990	0.947	0.928	1.000	0.800	0.800	0.800	0.800	0.800	0.800	0.800

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max Air Flow

Description: P0101_P0106_P0121_P0236_P1101 TIAP-Baro Correlation Max Air Flow

Value Units: Engine Air Flow (Grams/Second)

X Unit: Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	13.0	13.0	13.0	16.0	20.0	24.0	28.0	31.0	32.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Max MAP

Description: P0101_P0106_P0121_P0236_P1101 TIAP-Baro Correlation Max MAP

Value Units: Manifold Pressure (kPa)

X Unit: Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0	70.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-Baro Correlation Offset

Description: P0101_P0106_P0121_P0236_P1101 TIAP-Baro Correlation Offset

Value Units: Pressure Difference (kPa)

X Unit: Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	0.0	1.5	3.5	6.0	9.0	12.0	16.0	20.0	25.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min Air Flow

Description: P0101_P0106_P0121_P0236_P1101 TIAP-MAP Correlation Min Air Flow

Value Units: Engine Air Flow (Grams/Second)

X Unit: Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	17.0	47.0	85.0	124.0	162.0	184.0	206.0	206.0	206.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Min MAP

Description: P0101_P0106_P0121_P0236_P1101 TIAP-MAP Correlation Min MAP

Value Units: Manifold Pressure (kPa)

X Unit: Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	110.0	158.0	192.0	203.0	214.0	207.0	200.0	182.0	182.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P0236, P1101: TIAP-MAP Correlation Offset

Description: P0101_P0106_P0121_P0236_P1101 TIAP-MAP Correlation Offset**Value Units:** Pressure Difference (kPa)**X Unit:** Engine Speed (RPM)

y/x	1,000	1,750	2,500	3,250	4,000	4,750	5,500	6,250	7,000
1	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0234 P0299: Ambient pressure correction as a function of engine speed and ambient pressure

Description: Additive offset on boost pressure control deviation fail limit.

Value Units: [kPa] Control Deviation - Ambient correction.

X Unit: [kPa] KnBSTD_p_CntrlDevDiagAmbCorrBP - Ambient Air Pressure

Y Units: [rpm] KnBSTD_n_CntrlDevDiagAmbCorrBP - Engine Speed

y/x	60.00	70.00	80.00	90.00	100.00	110.00
1,500	130.00	130.00	130.00	130.00	130.00	130.00
2,500	125.00	120.00	90.00	55.00	0.00	0.00
3,000	115.00	105.00	75.00	35.00	0.00	0.00
4,000	65.00	60.00	50.00	25.00	0.00	0.00
5,000	30.00	25.00	20.00	10.00	0.00	0.00
6,000	0.00	0.00	0.00	0.00	0.00	0.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0234 P0299: Boost deviation diagnostic enable delay as a function of engine speed

Description: Timer to stabilize enable conditions for over and underboost diagnosis.

Value Units: [sec] Pressure control deviation diagnosis enable delay.

X Unit: [rpm] KnBSTD_n_CntrlDevDiagEngSpdBP - Engine Speed

y/x	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	6,000
1	1.7500	1.5000	1.3750	1.1250	1.0000	0.8750	0.7500	0.6250	0.5000	0.5000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0234: Overboost pressure deviation limit as a function of engine speed and desired boost pressure

Description: Negative boost pressure control deviation fail limit.

Value Units: [kPa] Negative boost pressure deviation limit.

X Unit: [kPa] KnBSTD_p_CntrlDevDiagDsrBP - Boost pressure

Y Units: [rpm] KnBSTD_n_CntrlDevDiagEngSpdBP - Engine speed

y/x	5.00	50.00	100.00	120.00	140.00	160.00	180.00	200.00	250.00	300.00
1,000	-100.00	-100.00	-100.00	-100.00	-100.00	-100.00	-100.00	-100.00	-100.00	-100.00
1,500	-100.00	-80.00	-80.00	-80.00	-80.00	-80.00	-80.00	-80.00	-80.00	-80.00
2,000	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
2,500	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
3,000	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
3,500	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
4,000	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
4,500	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
5,000	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00
6,000	-100.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00	-30.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0299: Underboost pressure deviation limit as a function of engine speed and desired boost pressure

Description: Positive boost pressure control deviation fail limit.

Value Units: [kPa] Positive boost pressure deviation limit.

X Unit: [kPa] KnBSTD_p_CntrlDevDiagDsrdBP - Boost pressure

Y Units: [rpm] KnBSTD_n_CntrlDevDiagEngSpdBP - Engine speed

y/x	5.00	50.00	100.00	120.00	140.00	160.00	180.00	200.00	250.00	300.00
1,000	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00	100.00
1,500	100.00	80.00	80.00	80.00	80.00	80.00	80.00	80.00	80.00	130.00
2,000	100.00	80.00	80.00	75.00	40.00	40.00	40.00	50.00	80.00	120.00
2,500	100.00	80.00	80.00	75.00	40.00	40.00	40.00	40.00	60.00	90.00
3,000	100.00	80.00	80.00	75.00	40.00	40.00	40.00	40.00	40.00	80.00
3,500	100.00	50.00	50.00	50.00	40.00	40.00	40.00	40.00	40.00	80.00
4,000	100.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	40.00	80.00
4,500	100.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	40.00	80.00
5,000	100.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	40.00	80.00
6,000	100.00	30.00	30.00	30.00	30.00	30.00	30.00	30.00	40.00	80.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Delta MAF Threshold f(TPS)

Description: Table of delta MAF values as a function of desired throttle position. The output of this table provides a delta MAF that if the measured minus the estimated MAF exceeds, is considered a fail.

y/x	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
1.00	9.38	12.13	16.89	19.20	29.84	49.55	255.00	255.00	255.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Delta MAP Threshold f(TPS)

Description: Table of delta MAP values as a function of desired throttle position. The output of this table provides a delta MAP that if the measured minus the estimated MAP exceeds, is considered a fail.

y/x	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
1.00	37.45	44.08	46.55	45.54	46.96	41.86	255.00	255.00	255.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Maximum MAF f(RPM)

Description: Table of maximum MAF values vs. engine speed. This is the maximum MAF the engine can see under all ambient conditions.

y/x	600.00	1,400.00	2,200.00	3,000.00	3,800.00	4,600.00	5,400.00	6,200.00	7,000.00
1.00	17.90	39.19	63.43	80.91	112.92	138.31	168.70	174.20	176.70

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Maximum MAF f(Volts)

Description: Table of maximum MAF values vs. system voltage. The output of the air meter is clamped to lower values as system voltage drops off.

y/x	6.00	7.00	8.00	9.00	10.00	11.00	12.00	13.00	14.00
1.00	6.50	25.00	65.00	140.00	260.00	300.00	300.70	300.70	300.70

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est

Description: P0101_P0106_P010B_P0121_P012B_P0236_P1101 MAF1 Residual Weight Factor based on MAF Est

Value Units: Weight Factor (Unitless)

X Unit: Estimated Engine Air Flow (Grams/Second)

y/x	0	15	30	45	60	75	90	105	120	135	150	165	180	195	210	230	250
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM

Description: P0101_P0106_P010B_P0121_P012B_P0236_P1101 MAF1 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	6,200
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0234: Overboost pressure limit below basic pressure as a function of engine speed and ambient pressure

Description: Overboost under basic pressure (open loop pressure control) diagnose failure limit.

Value Units: [kPa] Overboost under basic pressure fail limit.

X Unit: [kPa] KnBSTD_p_CntrlDevDiagAmbCorrBP - Ambient Air Pressure

Y Units: [rpm] KnBSTD_n_CntrlDevDiagAmbCorrBP - Engine Speed

y/x	60.00	70.00	80.00	90.00	100.00	110.00
1,500.00	90.000	90.000	80.000	70.000	60.000	60.000
2,500.00	62.000	52.000	32.000	30.000	30.000	30.000
3,000.00	42.000	25.000	10.000	10.000	10.000	10.000
4,000.00	30.000	10.000	10.000	10.000	10.000	10.000
5,000.00	30.000	10.000	10.000	10.000	10.000	10.000
6,000.00	30.000	10.000	10.000	10.000	10.000	10.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0299: Underboost high rate limit as a function of engine speed

Description: Allowed positive rate limit on desired boost pressure. In allowed kPa per 100 ms.

Value Units: [kPa] Allowed positive rate limit

X Unit: [rpm] KnBSTD_n_CntrlDevDiagEngSpdBP - Engine Speed

y/x	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	6,000
1	2.000	2.500	2.700	2.900	3.000	3.000	3.100	3.200	3.500	4.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0299: Underboost low rate limit as a function of engine speed

Description: Allowed negative rate limit on desired boost pressure. In allowed kPa per 100 ms.

Value Units: [kPa] Allowed negative rate limit.

X Unit: [rpm] KnBSTD_n_CntrlDevDiagEngSpdBP - Engine Speed

y/x	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	6,000
1	-200.00	-200.00	-200.00	-200.00	-200.00	-200.00	-200.00	-200.00	-200.00	-200.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Delta MAF Threshold f(TPS)

Description: Table of delta MAF values as a function of desired throttle position. The output of this table provides a delta MAF that if the measured minus the estimated MAF exceeds, is considered a fail.

Value Units: Delta MAF Values (dm)

X Unit: Desired Throttle Position (Pct)

y/x	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
1.00	9.38	12.13	16.89	19.20	29.84	49.55	255.00	255.00	255.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Delta MAP Threshold f(TPS)

Description: Table of delta MAP values as a function of desired throttle position. The output of this table provides a delta MAP that if the measured minus the estimated MAP exceeds, is considered a fail.

Value Units: Delta MAP Values (kPa)

X Unit: Desired Throttle Position (Pct)

y/x	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	100.00
1.00	37.45	44.08	46.55	45.54	46.96	41.86	255.00	255.00	255.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Maximum MAF f(RPM)

Description: Table of maximum MAF values vs. engine speed. This is the maximum MAF the engine can see under all ambient conditions.

Value Units: Delta MAF Values (dm)

X Unit: Engine Speed (RPM)

y/x	600.00	1,400.00	2,200.00	3,000.00	3,800.00	4,600.00	5,400.00	6,200.00	7,000.00
1.00	17.90	39.19	63.43	80.91	112.92	138.31	168.70	174.20	176.70

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0068_Maximum MAF f(Volts)

Description: Table of maximum MAF values vs. system voltage. The output of the air meter is clamped to lower values as system voltage drops off.

Value Units: Delta MAF Values (dm)

X Unit: System Voltage (V)

y/x	6.00	7.00	8.00	9.00	10.00	11.00	12.00	13.00	14.00
1.00	6.50	25.00	65.00	140.00	260.00	300.00	300.70	300.70	300.70

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_Thresh_AFM

Description: Fail threshold for the Knock Performance Abnormal Noise Diagnostic when engine IS in AFM mode

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.881	0.721	0.590	0.483	0.396	0.324	0.266	0.217	0.178	0.146	0.119	0.098	0.080	0.065	0.054	0.044	0.036

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMax (20 kHz)

Description: Knock Open Circuit Diagnostic Maximum Threshold when using the 20 kHz method (see "OpenMethod" description)

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM).

Y Units: N/A

y/x	750	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	8.0703	8.5195	8.5078	8.4121	8.4160	8.3320	8.4141	8.4141	8.7715	8.2207	8.0234	7.6289	7.2500	7.2500	7.2500	7.2500	7.2500

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMax (Normal Noise)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the Normal Noise method (see "OpenMethod" description): When using the Normal Noise method (see "OpenMethod" description).

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	2,700	2,900	3,000	3,250	3,500	3,750	4,000	4,250	4,500	4,750	5,000	5,500	6,000	6,500	7,000	7,500	8,500
1	0.4980	0.4980	0.4980	0.4980	0.4980	0.4570	0.4160	0.4082	0.4004	0.3477	0.2949	0.2441	0.2520	0.2109	0.2109	0.2109	0.2109

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMin (20 kHz)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the 20 kHz method (see "OpenMethod" description)

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine (RPM)

Y Units: N/A

y/x	750	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	2.8887	3.0430	3.0410	2.9941	2.9902	2.9648	2.9961	2.9980	3.1523	2.9336	2.8887	2.7480	2.6309	2.6309	2.6309	2.6309	2.6309

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMin (Normal Noise)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the Normal Noise method (see "OpenMethod" description): When using the Normal Noise method (see "OpenMethod" description).

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	2,700	2,900	3,000	3,250	3,500	3,750	4,000	4,250	4,500	4,750	5,000	5,500	6,000	6,500	7,000	7,500	8,500
1	0.1621	0.1621	0.1621	0.1621	0.1621	0.1543	0.1465	0.1406	0.1328	0.1172	0.0996	0.0840	0.0879	0.0781	0.0781	0.0781	0.0781

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenMethod_2

Description: Defines which Knock Open Circuit Diagnostic method to use.

Value Units: Identifies one of two diagnostic methods (either 20 kHz or Normal Noise) used (as a function of engine speed) for Open Circuit detection

X Unit: Engine Speed Index, 500 to 8500 (RPM) by 500 rpm increments (Index 0, 1, 2.... 16 = 500, 1000, 1500.... 8500 RPM)

Y Units: N/A

P0325_P0330_OpenMethod_2 - Part 1

y/x	0	1	2	3	4
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz

P0325_P0330_OpenMethod_2 - Part 2

y/x	5	6	7	8	9
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_None	CeKNKD_e_Open_None

P0325_P0330_OpenMethod_2 - Part 3

y/x	10	11	12	13	14
1	CeKNKD_e_Open_NormalNoise	CeKNKD_e_Open_NormalNoise	CeKNKD_e_Open_NormalNoise	CeKNKD_e_Open_NormalNoise	CeKNKD_e_Open_NormalNoise

P0325_P0330_OpenMethod_2 - Part 4

y/x	15	16			
1	CeKNKD_e_Open_NormalNoise	CeKNKD_e_Open_NormalNoise			

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_CylsEnabled

Description: Specifies which cylinders will be used for the Abnormal Noise portion of the performance diagnostics (1 = cylinder used, 0 = cylinder not used)

Value Units: Boolean that indicates which engine cylinders are being used for the per-sensor Knock Performance diagnostic (0 = not used, 1 = used)

X Unit: Cylinder number in firing order (i.e. Cyl 0 = first cylinder in firing order, Cyl 1 = second cylinder in firing order....)

Y Units: N/A

y/x	0	1	2	3	4	5	6	7
1	1	1	1	1	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_Threshold

Description: Fail threshold for the Knock Performance Abnormal Noise Diagnostic when engine is NOT in AFM mode

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.881	0.721	0.590	0.483	0.396	0.324	0.266	0.217	0.178	0.146	0.119	0.098	0.080	0.065	0.054	0.044	0.036

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06B6_P06B7_OpenTestCktThrshMax

Description: Knock Open Circuit Minimum Threshold for Internal Circuit Diagnostic. Used only when the 20 kHz method is being used (see "OpenMethod" description). The Open Test Circuit ensures that the internal circuit used to generate the 20 kHz signal for the Open Circuit diags (P0325, P0330) is within range.

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	750	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.209	0.209	0.215	0.215	0.232	0.232	0.232	0.271	0.305	0.367	0.588	0.576	0.592	0.592	0.592	0.592	0.592

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06B6_P06B7_OpenTestCktThrshMin

Description: Knock Open Circuit Minimum Threshold for Internal Circuit Diagnostic. Used only when the 20 kHz method is being used (see "OpenMethod" description). The Open Test Circuit ensures that the internal circuit used to generate the 20 kHz signal for the Open Circuit diags (P0325, P0330) is within range.

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM).

Y Units: N/A

y/x	750	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.102	0.102	0.104	0.104	0.115	0.115	0.115	0.139	0.154	0.191	0.320	0.311	0.322	0.322	0.322	0.322	0.322

Estimated OAT Accurate (Estimated OAT Accurate)
--

Conditions for Estimated Ambient Temperature Using OAT Sensor to be Valid

1. Startup OAT is less than previous trip EAT

OR

2. Startup ECT - previous trip EAT $\leq 0^{\circ}\text{C}$

OR

3. Engine off time $\geq 7,200$ seconds

OR

4. At startup, time since previous EAT valid and able to learn $\leq 3,600$ seconds

OR

5. EAT - current OAT $0^{\circ}\text{C} \leq \text{difference} \leq 2^{\circ}\text{C}$

OR

6. EAT < current OAT

and speed timer ≥ 240 seconds

and current OAT - EAT $\leq 2^{\circ}\text{C}$

Speed timer increments at 100 msec rate and increments vary based on vehicle speed as follows:

vehicle speed < 10 mph - 2.0 seconds

10 mph < speed < 35 mph 1.00 seconds

35 mph < speed < 124 2.00 seconds

124 mph < speed < 124 2.00 seconds

Speed timer can never be less than 0 seconds

Closed Loop Enable Clarification: Calibration values are in the Supporting Tables
--

**** Closed Loop Fuel Control Enable Criteria ****

Engine run time greater than

Closed Loop Enable Clarification - KtFSTA_t_ClosedLoopAutostart

(HYBRID ONLY)

X axis: AutoStart Coolant

Y axis: Close Loop Enable Time

and

Closed Loop Enable Clarification - KtFSTA_t_ClosedLoopTime

X axis: Start-Up Coolant

Y axis: Close Loop Enable Time

and

[

Pre converter O2 sensor voltage less than

(

Closed Loop Enable Clarification - KfFULC_U_O2_SensorReadyThrshLo

(Switching Sensor)

Voltage < XXXX millivolts

or

Closed Loop Enable Clarification - KeEOSD_U_RichThrsh

(Switching Sensor)

Voltage < XXXX millivolts

)

for

Closed Loop Enable Clarification - KcFULC_O2_SensorReadyEvents

(Switching Sensor)

Time (events * 12.5 milliseconds) > XXXX events

or

WRAF pumping cell temperature greater than

[

Closed Loop Enable Clarification - KeWRSC_T_HtrCntrlCL

Closed Loop Enable Clarification: Calibration values are in the Supporting Tables

(WRAF Sensor)
and
Closed Loop Enable Clarification - KeWRSI_T_PumpCurrentEnable
(WRAF Sensor)
and
Closed Loop Enable Clarification - KeFULC_T_WRAF_SensorReadyThrsh
(WRAF Sensor)
]

and

COSC (Converter Oxygen Storage Control) not enabled

and

Consumed AirFuel Ratio is stoichiometry i.e. not in component protection

and

POPD or Catalyst Diagnostic not intrusive

and

Turbo Scavenging Mode not enabled

and

All cylinders whose valves are active also have their injectors enabled

and
(
O2S_Bank_1_TFTKO and
O2S_Bank_2_TFTKO and
FuelInjectorCircuit_FA and
FuelInjectorCircuit_TFTKO = False
)

Closed Loop Enable Clarification: Calibration values are in the Supporting Tables

**** Primary Long Term Fuel Trim Enable Criteria ****

Closed Loop Enable and

Coolant greater than

Closed Loop Enable Clarification - KfFCLL_T_AdaptiveLoCoolant

Coolant > XXXX Celcius

and

MAP greater than

Closed Loop Enable Clarification - KtFCLL_p_AdaptiveLowMAP_Limit

Manifold Pressure > XXXX KPa

X axis: Barometric Pressure

Y axis: Manifold Air Pressure

and

TPS_ThrottleAuthorityDefaulted = False

and

Ethanol Estimation in Progress is not True

and

Excessive fuel vapors boiling off from the engine oil algorithm (BOFR) is not enabled

and

Catalyst or EVAP large leak test not intrusive

Closed Loop Enable Clarification: Calibration values are in the Supporting Tables
--

**** Secondary Fuel Trim Enable Criteria ****

Closed Loop Enable and Post converter O2 voltage less than
Closed Loop Enable Clarification - KfFCLP_U_O2ReadyThrshLo

Voltage < XXXX millivolts

for
Closed Loop Enable Clarification - KcFCLP_Cnt_O2RdyCyclesThrsh

Time (events * 12.5 milliseconds) > XXXX events

**** Long Term Secondary Fuel Trim Enable Criteria ****

Closed Loop Enable Clarification - KtFCLP_t_PostIntglDisableTime

X axis: Start-Up Coolant
 Y axis: Post Integral Enable Time
 Plus

Closed Loop Enable Clarification - KtFCLP_t_PostIntglRampInTime

X axis: Start-Up Coolant
 Y axis: Post Integral Ramp In Time
 and

Modeled Catalyst Temperature < XXXX Celcius
Closed Loop Enable Clarification - KeFCLP_T_IntegrationCatalystMax

and
 Modeled Catalyst Temperature > XXXX Celcius

Closed Loop Enable Clarification - KeFCLP_T_IntegrationCatalystMin

Closed Loop Enable Clarification: Calibration values are in the Supporting Tables

and
(PO2S_Bank_1_Snsr_2_FA and
PO2S_Bank_2_Snsr_2_FA = False)

and
Modeled catalytic converter sulfur percent < XXXX Percent
Closed Loop Enable Clarification - KeFCLP_Pct_CatAccuSlphrPostDsbl

and
Post Integral Learn < **Closed Loop Enable Clarification - KaFCLP_U_SlphrIntglOfst_Thrsh**
X axis: Post O2 Sensor Bank
Y axis: Post O2 Mode Cell
Z: Post Integral threshold

and
Airflow < **Closed Loop Enable Clarification - KeFCLP_dm_IntegrationAirflowMax**

OBD Coolant Enable Criteria (OBD Coolant Enable Criteria)

OBD Coolant enable

Starting in 11.15A software GM has created a coordinated signal within the ECM that serves as a master enable for diagnostics/controls that use coolant as an enable condition. Controls and diagnostics may choose to enable prior to this calculated signal, but calibrating beyond the OBD limit will not function because of this signal. This enable condition is also put on the CAN bus for other modules to consume as well.

KeTHMG_b_elecstatequipd = 1 for this application

For mechanical thermostat applications (KeTHMG_b_elecstatequipd = 0)

OBD Coolant Enable Temp = P0128 Primary target temp – Calibratable offset (0-32) – 1

OBD Coolant Enable Temp = 81 - 0.0 – 1

OBD Coolant Enable Temp = 80.0

For E-stat applications (KeTHMG_b_elecstatequipd = 1)

OBD Coolant Enable Temp = Max(Min(ECT Control Temp) – Primary Warm up delta, Min primary P0128 target) – Calibratable offset (0-32) – 1

OBD Coolant Enable Temp = Max(Min(KaTHMC_T_TMS_EngCoolReq) - KaECTR_T_CTR_WrmUpDeltaTemp[0],

KaECTR_T_CTR_WrmUpTargetMin[0]) - KeECTR_T_CTR_GlbMinOffst – 1

OBD Coolant Enable Temp = Max(85.0 - 11 , 81) - 0.0 – 1

OBD Coolant Enable Temp = 73.0

OBD Max Coolant Achieved (OBD Max Coolant Achieved)**OBD Max Coolant Achieved**

Starting in 18.18 software GM has created a coordinated signal within the ECM that serves as a master indication that the overtemperature "hot" light is active. This coordination forces controls and diagnostics to be active up until this signal is true. Controls and diagnostics may choose to disable at a higher temperature than this signal, but calibrating to a lower temperature will not work because of this signal.

This signal is also broadcast on the CAN buss for other modules to consume as well.

An indication of "True" means that the overtemperature "hot" light is active

IF

Engine Coolant Temperature > 125.0 °C OR Engine Metal Temperature (if equipped) > 135.0 °C

AND

Engine runtime ≥ 0.0 seconds

Set OBD Max Coolant Achieved = TRUE

MEM FNA Matched Flag (MEM FNA Matched Flag)**MEMR FNA Matched Flag**

GM software maintains a flag that indicates when an ECU has been programmed. When the controller is powered on, the logic compares the application software and calibration data file part numbers and design level suffixes (DLS) that are programmed into ECU flash memory to the part number and DLS data stored in ECU non-volatile memory. If any difference in the part number or DLS values are found, the MEMR_FNA_Matched flag is set to FALSE, otherwise the flag is set to TRUE.

Run/Crank Active (Run/Crank Active)**Run/Crank Active conditions**

Run/Crank Active is governed by a hysteresis pair of voltages.

Run/Crank Active = True when the run/crank ignition voltage > 5.0 volts.

Run/Crank Active = False when the run/crank ignition voltage drops < 2.0 volts.

Battery Voltage In Range (Battery Voltage In Range)**Battery Voltage In Range conditions**

Depending on available inputs, the best battery voltage analog input is chosen via calibration.

Supported options include:

- Standard Battery Voltage
- Ignition Run/Crank
- Battery Input 1
- Battery Input 2
- Higher of Battery Input 1 and Battery Input 2
- Serial data

If BatteryPresent = `True` then Battery voltage = standard battery voltage

Else if Run/Crank Active = `TRUE` then Battery voltage = run/crank ignition voltage

Else Battery voltage = Serial data battery voltage

Battery Voltage In Range = `True` when Battery Voltage > 11.0volts

DFCO Conditions (DFCO Conditions)

DFCO Enable Conditions

COOLANT ENABLE CRITERIA

Coolant temperature < **DFCO_CoolEnbHi_Temp** °C See Supporting Table

RUN TIME ENEBALE CRIETRIA

Engine run time > **DFCO_DelayAfterStart_Time** seconds See Supporting Table

ENGINE SPEED ENABLE CRITERIA

TORQUE CONVERETR CLUTCH UNLOCK

POPD OFF:

- i) enabled when engine speed > (1,400.0 + supporting table value **DFCO_EngSpdEnbIOfst**)
- ii) once enabled continue to be enabled until engine speed < (1,400.0 + supporting table value **DFCO_EngSpdEnbIOfst**)

POPD ON:

- i) enabled when engine speed > (1,400.0 + supporting table value **DFCO_EngSpdEnbIOfst**)
- ii) once enabled continue to be enabled until engine speed < (1,400.0 + supporting table value **DFCO_EngSpdEnbIOfst**)

TORQUE CONVERETR CLUTCH LOCK

POPD OFF:

- i) enabled when engine speed > (1,000.0 + supporting table value **DFCO_EngSpdEnbIOfst**)
- ii) once enabled continue to be enabled until engine speed < (900.00 + supporting table value **DFCO_EngSpdEnbIOfst**)

POPD ON:

- i) enabled when engine speed > (1,200.0 + supporting table value **DFCO_EngSpdEnbIOfst**)
- ii) once enabled continue to be enabled until engine speed < (1,100.0 + supporting table value **DFCO_EngSpdEnbIOfst**)

VEHICLE SPEED CRITERIA:

- i) enabled when vehicle speed >= (**DFCO_EnbHi_Vehicle_Speed**)
- ii) once enabled continue to be enabled until vehicle speed < **DFCO_DsblLo_Vehicle_Speed**

TORQUE CRITERIA :

- i) enabled when following condition is satisfied
 - a) driver shaped trq delta1 = shaped immediate torque - zero pedal torque <= 1.00
- ii) once enabled, disabled when following OR conditions are satisfied
 - a) driver raw trq delta1 = raw torque - zero pedal torque > 5.0
 - b) driver shaped trq delta2 = zero pedal torque - minimum combustion managed torque > 65,535.0

CATALYST TEMPERATURE

- i) enabled based on following AND criteria
 - a) (CatTemp < 900.0 °C and vehicle speed < 50.0 kph)
 - b) CatTemp < 1,000.0 °C
 - c) CatalystWarmupEnabled = FALSE
- ii) once enabled, disabled when following OR conditions are met

OTHER CONDITIONS:

- a) Transmission is not about to unlock

DFCO Conditions (DFCO Conditions)

- b) Engine not about to stall
- c) Transmission is not shifting if already not in DFCO
- d) POPD or EOSD
 - 1) POPD requesting DFCO or neither requesting DFCO OFF nor inhibit DFCO
 - 2) EOSD not active
- e) EVAP does not inhibit DFCO
- f) O2 response test is not inhibiting DFCO event
- g) Throttle is not in default mode

Dilution Definitions (Dilution Flags Report)

Exhaust Cam Phsr Enable

Exhaust Cam Phsr Enable = TRUE if:

DTCs not set:

CrankSensor_TFTKO

CamSnsrExhTFTKO

CamLctnExhFA

AND

CamSensorAnyLocationFAdiagnostic has executed and passed

AND

Cam edge locations have been learned

AND

[**Intake Cam Phsr Enable** = TRUE

OR

Intake Park Position is Retarded (TRUE)]

AND

[Catalyst Warmup Enabled = TRUE

AND

Engine RPM > 900.00

AND

Engine Run Time > P0011_P0021_P05CC_P05CD_P0014_P0024_P05CE_P05CF_ColdStartEngRunning sec]

OR

[Engine is running and engine power is requested

Dilution Definitions (Dilution Flags Report)

AND

ExhEngineSpeed is Enabled (see below)

AND

ExhOilPressure is Enabled (see below)

AND

ExhEngineOilTemp is Enabled (see below)]

ExhEngineSpeed is Enabled when**P0014_P0024_P05CE_P05CF_LoRpmHiEnbIEc** < Engine RPM < **P0014_P0024_P05CE_P05CF_HiEngSpdLoEnbIEc**ExhEngineSpeed is Disabled whenEngine RPM < **P0014_P0024_P05CE_P05CF_LoRpmLoDsblEc**

OR

Engine RPM > **P0014_P0024_P05CE_P05CF_HiEngSpdHiDsblEc**

If an oil pressure sensor is present (TRUE) and is being used (FALSE) then

ExhOilPressureEnable is Enabled whenOil Pressure > **P0014_P0024_P05CE_P05CF_LoPresHiEnbIEc** kPafor **P0014_P0024_P05CE_P05CF_EngOilPressEnbIEc** secondsExhOilPressureEnable is Disabled whenOil pressure < **P0014_P0024_P05CE_P05CF_LoPresLoDsblEc** kPa

If an oil pressure sensor is not present (FALSE) OR is not being used (TRUE) then

ExhOilPressureEnable is Enabled whenEngine RPM > **P0014_P0024_P05CE_P05CF_LoRpmHiEnbIEc**for **P0014_P0024_P05CE_P05CF_EngOilPressEnbIEc** seconds

ExhEngineOilTemp is Enabled when

Dilution Definitions (Dilution Flags Report)

-40.00 < Engine Oil Temp < 155.00 deg C

ExhEngineOilTemp is Disabled when

Engine Oil Temp < -42.00 deg C

OR

Engine Oil Temp > 165.00 deg C

Intake Cam Phsr Enable

Intake Cam Phsr Enable = TRUE if:

DTCs not set:

CrankSensor_TFTKO

CamSnsrIntTFTKO

CamLctnIntFA

AND

CamSensorAnyLocationFA has executed and passed

AND

Cam edge locations have been learned

AND

[Catalyst Warmup Enabled = TRUE

AND

Engine RPM > 900.00

AND

Engine Run Time > P0011_P0021_P05CC_P05CD_P0014_P0024_P05CE_P05CF_ColdStartEngRunning sec]

OR

Dilution Definitions (Dilution Flags Report)

[Engine is running and engine power is requested

AND

IntEngineSpeed is Enabled

AND

IntOilPressure is Enabled

AND

IntEngineOilTemp is Enabled]

IntEngineSpeed is Enabled when

P0011_P0021_P05CC_P05CD_LoRpmHiEnblc < Engine RPM < **P0011_P0021_P05CC_P05CD_HiEngSpdLoEnblc**

IntEngineSpeed is Disabled when

Engine RPM < **P0011_P0021_P05CC_P05CD_LoRpmLoDsblc**

OR

Engine RPM > **P0011_P0021_P05CC_P05CD_HiEngSpdHiDsblc**

If an oil pressure sensor is present (TRUE) and is being used (FALSE) then

IntOilPressureEnable is Enabled when

Oil Pressure > **P0011_P0021_P05CC_P05CD_LoPresHiEnblc** kPa

for **P0011_P0021_P05CC_P05CD_EngOilPressEnblc** seconds

IntOilPressureEnable is Disabled when

Oil pressure < **P0011_P0021_P05CC_P05CD_LoPresLoDsblc**

If an oil pressure sensor is not present (FALSE) or is not being used (TRUE) then

IntOilPressureEnable is Enabled when

Engine RPM > **P0011_P0021_P05CC_P05CD_LoRpmHiEnblc**

for **P0011_P0021_P05CC_P05CD_EngOilPressEnblc** seconds

IntEngineOilTemp is Enabled when

Dilution Definitions (Dilution Flags Report)

-40.00 < Engine Oil Temp < 155.00 deg C

IntEngineOilTemp is Disabled when

Engine Oil Temp < -42.00 deg C

OR

Engine Oil Temp > 165.00 deg C

EGR Control Enabled:

EGR is enabled when the following are true:

Cold start: coolant temperature > 35.00 C OR warm start: coolant temperature > 32.00 C

Coolant temperature < 130.00 C

Intake ambient temperature > -23.00 C when airflow > 6.00 g/s, AND IAT does not drop below -25.00 C after enabling

Engine run time (function of powerup coolant temp) > 4.00 s

Ignition voltage > 11.00 V

Vehicle speed < 5.00 m/s AND does not exceed 9.00 m/s after enabling, AND raw requested pedal torque is zero

IF 1.00 = 1.00, all equipped cam phasers must be enabled

IF closed loop fuel control is enabled (1.00), fuel control state must be in closed loop status

IF power enrichment fuel control is enabled (1.00), power enrichment must not be active

Engine is not in reduced power state (REP light not illuminated)

POPD/Catalyst monitoring diagnostics are not active

Engine speed is between 650.00 and 6,000.00 RPM (if limits exceeded, engine speed must return to between 700.00 and 5,900.00 RPM)

IF EGR gas temperature limits are set, EGR gas temp must not exceed 145.00 C (if limit exceeded, gas must drop below 140.00 C)

No diagnostic errors exist that prevent EGR from operating

Fuel Level Flag (Fuel Level Flag)**Low Fuel Condition Diagnostic flag** Flag

set to TRUE if the fuel level < 10.0 % AND

No Active DTCs: FuelLevelDataFault, P0462, P0463 for at least 30.0 seconds

Transfer Pump is Commanded On Flag

Fuel Volume in Primary Fuel Tank < 0.0 liters AND

Fuel Volume in Secondary Fuel Tank \geq 0.0 liters AND

Transfer Pump on Time < P0461, P2066, P2636: Transfer Pump Enable (see supporting table for numeric value) AND

Transfer Pump had been Off for at least 0.0 seconds AND

Evap Diagnostic (Purge Valve Leak Test, Large Leak Test, and Waiting for Purge) is not running AND

Engine Running

Open Loop Diagnostics Enable Flags (Open Loop Diagnostics Enable Flags)

```
*****
*****
*****
*****
```

Small Pulse General Diagnostic Enable

Small Pulse General Diagnostic Enable = True IF:

Ignition State in Run or Crank

AND

Fuel Level >= 10.00 % Volume

AND

FuelInjectorCircuit_FA

AND

FuelInjectorCircuit_TFTKO

AND

FULR_b_FuelInjCkt_FP

AND

Engine Run Time >= 5.00 Seconds

AND

Measured Fuel Rail Pressure >= 5.00 MPa

AND

[System Voltage >= 8.00 Volts

OR

System Voltage >= 11.00 Volts]

```
*****
*****
```

Fuel Pulse Voltage Feedback Data Ready

Fuel Pulse Voltage Feedback Data Ready = True If;

Fuel pulse was commanded

AND

FPV data collection was commanded

AND

[(Dual or Triple Injection Pulse Mode

AND

Engine Speed <P2B00 P2B01 P2B02 P2B03 P2B04 P2B05 P2B06 P2B07 P2B96 P2B08 P2B09 P2B0A P2B0B P2B0C P2B0D P2B0E P2B0F - kaFULO_n_RPM_MultiPuls[x][y])

Open Loop Diagnostics Enable Flags (Open Loop Diagnostics Enable Flags)

OR
(Single Injection Pulse Mode
AND
Engine Speed < 5,000.00)]

**

Fuel Pulse Voltage Feedback Data Valid

Fuel Pulse Voltage Feedback Data Valid = True IF:

Fuel pulse was commanded

AND

FPV data collection was commanded

AND

[(Dual or Triple Injection Pulse Mode

AND

Engine Speed <P2B00 P2B01 P2B02 P2B03 P2B04 P2B05 P2B06 P2B07 P2B96 P2B08 P2B09 P2B0A P2B0B P2B0C P2B0D P2B0E P2B0F - kaFULO_n_RPM_MultiPuls[x][y])

OR

(Single Injection Pulse Mode

AND

Engine Speed < 5,000.00)]

AND

Fuel pulse voltage feedback data sample is capature from the HWIO and reported complete

Run/Start Input Supply Source Relay Control Range/Performance Enable

Open Loop Diagnostics Enable Flags (Open Loop Diagnostics Enable Flags)

Run/Start Input Supply Source Relay Control Range/Performance Enable = True IF:

(Vehicle Power mode = Accessory

OR

Vehicle Power mode = OFF)

AND

Remote Vehicle start request = False

AND

Power Take Off request = False

AND

Engine Mode = Off

AND

Diagnostic Delay timer \geq 50 ms

Initial Supporting table - Multiple DTC Use - Block learn cells to enable Post oxygen sensor tests

Description: This table describes the adaptive (Block Learn) cells in which to enable the Post (Secondary) Oxygen sensor response tests.

Note: When the table column heading matches the calibration value below it, that individual cell is enabled.

The cell numbers in the table are defined as:

CeFADR_e_Cell00_PurgOnAirMode5 = 0,
 CeFADR_e_Cell01_PurgOnAirMode4 = 1,
 CeFADR_e_Cell02_PurgOnAirMode3 = 2,
 CeFADR_e_Cell03_PurgOnAirMode2 = 3,
 CeFADR_e_Cell04_PurgOnAirMode1 = 4,
 CeFADR_e_Cell05_PurgOnAirMode0 = 5,
 CeFADR_e_Cell06_PurgOnIdle = 6,
 CeFADR_e_Cell07_PurgOnDecel = 7,
 CeFADR_e_Cell08_PurgOffAirMode5 = 8,
 CeFADR_e_Cell09_PurgOffAirMode4 = 9,
 CeFADR_e_Cell10_PurgOffAirMode3 = 10,
 CeFADR_e_Cell11_PurgOffAirMode2 = 11,
 CeFADR_e_Cell12_PurgOffAirMode1 = 12,
 CeFADR_e_Cell13_PurgOffAirMode0 = 13,
 CeFADR_e_Cell14_PurgOffIdle = 14,
 CeFADR_e_Cell15_PurgOffDecel = 15

Value Units: Block Learn cell number

X Unit: Block Learn cell number

y/x	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Multiple DTC Use -Response Cell Enable Table

Description: This table describes the Block learn cells which enable the Pre (Primary) Oxygen sensor response tests.
Note: When the table column heading matches the calibration value below it, that individual cell is enabled.

Value Units: Block Learn cell name and number

X Unit: Block Learn cell name and number

Multiple DTC Use - Response Cell Enable Table - Part 1

y/x	CeFADR_e_Cell00_PurgOnAirMode	CeFADR_e_Cell01_PurgOnAirMode	CeFADR_e_Cell02_PurgOnAirMode	CeFADR_e_Cell03_PurgOnAirMode
1	5	4	3	2

Multiple DTC Use - Response Cell Enable Table - Part 2

y/x	CeFADR_e_Cell04_PurgOnAirMode	CeFADR_e_Cell05_PurgOnAirMode	CeFADR_e_Cell06_PurgOnIdle	CeFADR_e_Cell07_PurgOnDecel
1	1	0		

Multiple DTC Use - Response Cell Enable Table - Part 3

y/x	CeFADR_e_Cell08_PurgOffAirMode	CeFADR_e_Cell09_PurgOffAirMode	CeFADR_e_Cell10_PurgOffAirMode	CeFADR_e_Cell11_PurgOffAirMode
1	5	4	3	2

Multiple DTC Use - Response Cell Enable Table - Part 4

y/x	CeFADR_e_Cell12_PurgOffAirMode	CeFADR_e_Cell13_PurgOffAirMode	CeFADR_e_Cell14_PurgOffIdle	CeFADR_e_Cell15_PurgOffDecel
1	1	0		

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Multiple DTC Use_Green Sensor Delay Criteria - Limit

Description: This Calibration is the accumulated airflow limit above which the Green condition is expired

Used for: P0133, P013A, P013B, P013C, P013D, P013E, P013F, P014A, P014B, P0153, P015A, P015B, P015C, P015D, P1133, P1153, P2270, P2271, P2272 and P2273.

Note: This feature is only enabled when the vehicle is new and cannot be enabled in service.

Value Units: Grams

X Unit: Accumulated Engine Airflow

y/x	CiOXYR_O2_Bank1_Sensor1	CiOXYR_O2_Bank1_Sensor2	CiOXYR_O2_Bank2_Sensor1	CiOXYR_O2_Bank2_Sensor2
1	120,000	120,000	120,000	120,000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_CamPosErrorLimlc1

Description: Maximum Intake Cam 1 phase error as a function of engine speed and engine oil temperature.

Value Units: Maximum Intake Cam 1 phase error (degCAM)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
1,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
1,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
3,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
3,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
5,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
5,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_EngOilPressEnblIc

Description: Delay time before the oil pressure enable flag is set assuming all the oil pressure enable criteria are met

Value Units: Time (sec)

X Unit: Engine Coolant Temperature (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	3	3	3	2	2	1	1	1	1	1	1	1	1	1	1	1	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_HiEngSpdHiDsbllc

Description: Minimum engine speed to disable Intake cam**Value Units:** Engine Speed (rpm)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_HiEngSpdLoEnbllc

Description: Maximum engine speed to enable Intake cam - works as hysteresis.

Value Units: Engine Speed (rpm)

X Unit: Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_LoPresHiEnblIc

Description: Intake cam is enabled when oil pressure exceeds this value**Value Units:** Engine Speed (rpm)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_LoPresLoDsbllc

Description: Intake cam is disabled when oil pressure falls below this value**Value Units:** Engine Oil Pressure (kPa)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_LoRpmHiEnbllc

Description: Intake cam is enabled when engine speed exceeds this value.

Value Units: Engine Speed (rpm)

X Unit: Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130

18 OBDG01 ECM Supporting Tables

Initial Supporting table- P0011_P0021_P05CC_P05CD_LoRpmLoDsbllc

Description: Intake cam is disabled when engine speed is below this value.

Value Units: Engine Speed (rpm)

X Unit: Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P0021_P05CC_P05CD_P0014_P0024_P05CE_P05CF_ColdStartEngRunning

Description: Engine running time must be greater than this threshold during a cold start to enable cam phasing

Value Units: Time (sec)

X Unit: Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0011_P05CC_StablePositionTimeIc1

Description: Minimum time for Intake Cam 1 phase position to be stable to enable performance diagnostic.

Value Units: Minimum time (sec)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
800	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,200	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,600	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,000	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,400	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,800	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,200	100.0	80.0	11.5	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,600	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,000	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,400	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,800	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,200	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,600	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,000	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,400	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,800	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_CamPosErrorLimEc1

Description: Maximum Exhaust Cam 1 phase error as a function of engine speed and engine oil temperature.

Value Units: Maximum Exhaust Cam 1 phase error (degCAM)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
1,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
1,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
2,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
3,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
3,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
4,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
5,200	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
5,600	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,000	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,400	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
6,800	6.0	6.0	4.0	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_EngOilPressEnblEc

Description: Delay time before the oil pressure enable flag is set assuming all the oil pressure enable criteria are met

Value Units: Time (sec)

X Unit: Engine Coolant Temperature (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	3	3	3	2	2	1	1	1	1	1	1	1	1	1	1	1	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_HiEngSpdHiDsblEc

Description: Exhaust cam is disabled when engine speed exceeds this value**Value Units:** Engine Speed (rpm)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000	8,000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_HiEngSpdLoEnbIEc

Description: Exhaust cam is enabled when engine speed remains below this value**Value Units:** Engine Speed (rpm)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800	7,800

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_LoPresHiEnbIEc

Description: Exhaust cam is enabled when oil pressure exceeds this value**Value Units:** Engine Oil Pressure (kPa)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160	160

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_LoPresLoDsblEc

Description: Exhaust cam is disabled when oil pressure falls below this value**Value Units:** Engine Oil Pressure (kPa)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150	150

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_LoRpmHiEnbIEc

Description: Exhaust cam is enabled when engine speed exceeds this value.

Value Units: Engine Speed (rpm)

X Unit: Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130	130

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P0024_P05CE_P05CF_LoRpmLoDsblEc

Description: Exhaust cam is disabled when engine speed is below this value.**Value Units:** Engine Speed (rpm)**X Unit:** Engine Oil Temp (degC)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0014_P05CE_StablePositionTimeEc1

Description: Minimum time for Exhaust Cam 1 phase position to be stable to enable performance diagnostic.

Value Units: Minimum time (sec)

X Unit: Engine Oil Temperature (degC)

Y Units: Engine Speed (rpm)

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
400	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
800	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,200	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
1,600	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,000	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,400	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
2,800	100.0	80.0	20.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,200	100.0	80.0	11.5	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
3,600	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,000	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,400	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
4,800	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,200	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
5,600	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,000	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,400	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
6,800	100.0	80.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0016, P0017, P0018, P0019: Cam Correlation Oil Temperature Threshold

Description: P0016, P0017, P0018, P0019: Cam Correlation Oil Temperature Threshold

Value Units: Engine Run Time- Seconds

X Unit: Oil Temperature- C

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	300	300	160	18	18	18	18	10	3	3	3	3	3	3	3	3	3

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: MAP1 Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 MAP1 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	8,000
1	0.750	1.000	1.000	0.961	0.949	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: MAP2 Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 MAP2 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	8,000
1	0.750	1.000	1.000	0.906	1.000	0.760	0.802	0.890	0.661	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P0121, P012B, P0236, P1101: TPS Residual Weight Factor based on RPM

Description: P0101_P0106_P0121_P012B_P0236_P1101 TPS Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	8,000
1	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000	1.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0133_KnEOSD_t_ST_LRC_LimRS1

Description: X Table Axis for P0133**Value Units:** Seconds**X Unit:** X Table Axis for P0133, L2R Response time breakpoints for table

y/x	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
1	0.000	0.010	0.020	0.030	0.040	0.050	0.060	0.070	0.080	0.090	0.100	0.110	0.120	0.130	0.140	0.150	0.160

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0133_KnEOSD_t_ST_RLC_LimRS1

Description: Y Table Axis for P0133**Value Units:** Seconds**Y Units:** Y Table Axis for P0133, R2L Response time breakpoints for table

y/x	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
1	0.000	0.010	0.020	0.030	0.040	0.050	0.060	0.070	0.080	0.090	0.100	0.110	0.120	0.130	0.140	0.150	0.160

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0133_O2S Slow Response Bank 1 Sensor 1 Pass/Fail Threshold table

Description: This table describes the Pass and Fail regions based on the diagnostic test result

Value Units: If the cell contains a "0" then the fault is indicated, if it contains a "1" a fault is not indicated.

X Unit: X axis is Lean to Rich response time (in sec), Please see the table below named "KnEOSD_t_ST_LRC_LimRS1" for the 17 X axis table breakpoints.

Y Units: Y axis is Rich to Lean response time (in sec), Please see the table below named "KnEOSD_t_ST_RLC_LimRS1" for the 17 Y axis table breakpoints.

y/x	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
2	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
3	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
5	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
6	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
7	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
8	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
9	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
10	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
11	0	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
12	0	1	1	1	1	1	1	1	1	1	1	1	1	1	0	0	0
13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
14	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0401_SamplesAfterReset

Description: Total number of samples allowed after a reset. A greater number of samples allows the EWMA logic to make a decision sooner after a reset. Also used as the threshold of total sample counts above which a test can be considered complete for a particular trip. This is a function of barometric pressure to allow compliant response at different altitudes.

Value Units: Total number of samples allowed after a reset (samples)

X Unit: Barometric pressure (kPa)

y/x	65	70	75	80	85	90	95	100	105
1	20	20	20	15	10	10	10	10	10

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0401_SamplesAfterStep

Description: Total number of samples needed after a step change. A greater number of samples allows the EWMA logic to make a decision sooner after a step change. Also used as the threshold of total step counts above which a test can be considered complete for a particular trip. This is a function of barometric pressure to allow compliant response at different altitudes.

Value Units: Total number of samples needed after a step change(samples)

X Unit: Barometric pressure (kPa)

y/x	65	70	75	80	85	90	95	100	105
1	15	15	15	15	15	15	15	15	15

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0401_StepDelta

Description: Minimum difference between MAP difference and EWMA to trigger multiple tests for step change. This is a function of barometric pressure to allow compliant response at different altitudes.

Value Units: Minimum difference between MAP difference and EWMA (kPa)

X Unit: Barometric pressure (kPa)

y/x	65	70	75	80	85	90	95	100	105
1	15	15	15	15	15	15	15	15	15

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0401_StepMAP_DIFF

Description: Minimum value of MAP difference to trigger multiple tests for step change. This is a function of barometric pressure to allow compliant response at different altitudes.

Value Units: Minimum value of MAP difference (kPa)

X Unit: Barometric pressure (kPa)

y/x	65	70	75	80	85	90	95	100	105
1	2	2	2	2	2	2	2	2	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0401_StepSamplesPerTrip

Description: Maximum number of samples per trip after a step change. Also used as the threshold of trip step counts above which a test can be considered complete for a particular trip. This is a function of barometric pressure to allow compliant response at different altitudes.

Value Units: Maximum number of samples per trip after a step change (samples)

X Unit: Barometric pressure (kPa)

y/x	65	70	75	80	85	90	95	100	105
1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P050D_P1400_CatalystLightOffExtendedEngineRunTimeExit

Description: Exit Catalyst Warm-up mode if Engine Run Time is greater than this value. This table is based on percent ethanol (x-axis) and catmon's NormRatio_EWMA value (y-axis). The NormRatio_EWMA value determines the state of the catalyst. Typically, NormRatio_EWMA values below 0.35 (0 is bad and 1 is good) represent catalysts that have degraded. The emission performance of these degraded catalysts can be improved by extending catalyst light off of GetE85R_Pct_FFS_CompAtEngFloat.

y/x	0	25	50	75	100
0.000	30	30	30	30	30
0.125	30	30	30	30	30
0.250	30	30	30	30	30
0.375	30	30	30	30	30
0.500	30	30	30	30	30
0.625	30	30	30	30	30
0.750	30	30	30	30	30
0.875	30	30	30	30	30
1.000	30	30	30	30	30

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1400_ColdStartDiagnosticDelayBasedOnEngineRunTime

Description: Quality weight-based on engine run time. This allows adjustment of the weighting factors at various engine run times in order to prevent the updating of the cumulative quality timer or to change the value of the average qualified residual energy calculation to prevent false Fails of the diagnostic under circumstances inappropriate to update the calculation of the average qualified residual value.

y/x	0	4	8	10	12	16	20	24	30
1	0	0	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1400_ColdStartDiagnosticDelayBasedOnEngineRunTimeCalAxis

Description: This is the x-axis for the KtCSED_K_TimeWght calibration table. Refer to the description for KtCSED_K_TimeWght for details.

y/x	1	2	3	4	5	6	7	8	9
1	0	4	8	10	12	16	20	24	30

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1400_EngineSpeedResidual_Table

Description: This 1x17 table of engine exhaust flow values is used to calculate both the desired and the actual engine exhaust flow based on desired and actual engine speed. The desired engine exhaust flow is gathered from the desired engine speed (VeSPDR_n_EngDsrd). The value used for the actual engine exhaust flow is based on the actual engine RPM value.

y/x	100	300	500	700	800	850	880	925	980	1,025	1,050	1,100	1,300	1,500	1,800	2,000	2,200
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1400_SparkResidual_Table

Description: Predicted engine-out energy potential based on either the desired cold start spark advance value or the actual spark advance value. ExhEngyPerUnitMass calibration is used to calculate both desired exhaust energy and actual energy. The desired and actual exhaust energy per unit mass values are used in part to calculate the desired exhaust energy per unit time and actual exhaust energy per unit time. Both desired and actual go into the residual exhaust energy per unit time calculation.

y/x	-20	-17	-15	0	1	2	3	5	10
1	20.00	10.50	9.00	8.81	7.81	6.19	2.50	1.44	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on MAF Est

Description: P0101_P0106_P010B_P0121_P012B_P0236_P1101 MAF1 Residual Weight Factor based on MAF Est

Value Units: Weight Factor (Unitless)

X Unit: Estimated Engine Air Flow (Grams/Second)

y/x	0	50	70	73	76	79	82	85	89	95	100	110	150	170	200	230	250
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0101, P0106, P010B, P0121, P012B, P0236, P1101: MAF1 Residual Weight Factor based on RPM

Description: P0101_P0106_P010B_P0121_P012B_P0236_P1101 MAF1 Residual Weight Factor based on RPM

Value Units: Weight Factor (Unitless)

X Unit: Engine Speed (RPM)

y/x	0	400	800	1,200	1,600	2,000	2,400	2,800	3,200	3,600	4,000	4,400	4,800	5,200	5,600	6,000	8,000
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0128_Maximum Accumulated Energy for Start-up ECT conditions - Alternate

Description: KtECTR_E_CTR_WrmUpEnrgyLimTest1**Value Units:** Cooling system energy failure threshold (kJ)**X Unit:** Minimum ECT for the key cycle (°C)

y/x	-10	0	10	30	51	69	76
1	3,537	2,998	2,459	1,382	250	250	250

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0128_Maximum Accumulated Energy for Start-up ECT conditions - Primary

Description: KtECTR_E_CTR_WrmUpEnrgyLimTest0

Value Units: Cooling system energy failure threshold (kJ)

X Unit: Minimum ECT for the key cycle (°C)

y/x	-10	0	10	30	51	69	76
1	3,724	3,724	3,346	2,590	1,796	1,116	852

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0606_Last Seed Timeout f(Loop Time)

Description: The max time for the Last Seed Timeout as a function of operating loop time sequence.

P0606_Last Seed Timeout f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	200.000	200.000	200.000	200.000	200.000	200.000	200.000

P0606_Last Seed Timeout f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	200.000	200.000	500.000	8,191.875	8,191.875	8,191.875	

Initial Supporting table - P0606_PSW Sequence Fail f(Loop Time)

Description: Fail threshold for PSW per operating loop.

P0606_PSW Sequence Fail f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	5	3	5	3	5	3	5

P0606_PSW Sequence Fail f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	5	5	5	3	5	5	

Initial Supporting table - P0606_PSW Sequence Sample f(Loop Time)

Description: Sample threshold for PSW per operating loop.

P0606_PSW Sequence Sample f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	4	4	4	4	4	4	4

P0606_PSW Sequence Sample f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	4	4	4	4	4	4	

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1682_PT Relay Pull-in Run/Crank Voltage f(IAT)

Description: The Run/Crank voltages required to pull in the PT relay as a function of induction air temperature.

Value Units: Run/Crank Voltages required to pull in PT Relay (V)

X Unit: Induction Air Temperature (deg C)

y/x	23.000	85.000	95.000	105.000	125.000
1.000	7.000	8.699	9.000	9.199	10.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P16F3_Delta MAP Threshold f(Desired Engine Torque)

Description: Engine Sync based and Time based delta pressure threshold above which Torque Security error is reported.

y/x	0.00	50.00	100.00	150.00	200.00	300.00
1.00	34.92	34.92	34.92	34.92	34.92	34.92

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P16F3_Speed Control External Load f(Oil Temp, RPM)

Description: Specifies the external load table for SPDR torque security as a function of engine oil temperature and engine RPM.

y/x	-40.00	-20.00	-10.00	0.00	50.00	90.00
700.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00
900.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00
1,100.00	70.00	70.00	70.00	70.00	60.00	50.00
1,400.00	45.00	42.00	38.00	35.00	35.00	35.00
1,600.00	32.89	29.44	27.18	25.55	18.09	15.26
1,800.00	34.82	31.10	28.67	26.92	19.35	16.51
2,000.00	37.64	32.56	30.68	29.85	21.71	18.36
2,200.00	40.80	35.20	33.13	32.22	23.24	19.84
2,500.00	43.58	39.76	37.58	36.01	26.21	23.06
2,700.00	42.72	38.90	36.72	35.15	25.34	22.19
3,000.00	40.65	36.83	34.65	33.08	23.27	20.13
3,300.00	36.87	33.05	30.87	29.30	19.49	16.35
3,500.00	13.41	9.58	7.41	5.84	-3.97	-7.12
3,700.00	7.50	3.67	1.50	-0.08	-9.88	-13.03
4,000.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28
4,500.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28
5,000.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KaFCLP_U_SlphrIntglOfst_Thrsh

Description: Integral Offset voltage thresholds (bank and cell specific calcs) used with KeFCLP_Pct_CatAccuSlphrPostDsbl to check for sulphur poisoning.

Value Units: millivolts

X Unit: Post Catalyst Number

y/x	CiOXYR_O2_PostCat1	CiOXYR_O2_PostCat2
CiFCLP_Decel	2,048	2,048
CiFCLP_Idle	2,048	2,048
CiFCLP_Cruise	2,048	2,048
CiFCLP_LightAccel	2,048	2,048
CiFCLP_HeavyAccel	2,048	2,048

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KcFCLP_Cnt_O₂Rd₂C₂clesThrsh**Description:** Number of times a post oxygen sensor value must be in range before declaring it ready**Value Units:** Time (events * 12.5 milliseconds)

y/x	1
1	80

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KcFULC_O2_SensorReadyEvents

Description: Number of times a pre oxygen sensor value must be in range before declaring it ready**Value Units:** Time (events * 12.5 milliseconds)

y/x	1
1	20

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeEOSD_U_RichThrsh

Description: The oxygen sensor voltage above which a sensor will be considered failing during a Rich Test.

Value Units: Volts

y/x	1
1	1,050

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeFCLP_dm_IntegrationAirflowMax

Description: Maximum allowed estimated airflow for post O2 integral terms to be updated.**Value Units:** Grams per Second

y/x	1
1	512

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeFCLP_Pct_CatAccuSlphrPostDsbl

Description: Sulphur percent threshold above which post integral learning is disabled if the threshold criteria KaFCLP_U_SlphrIntglOfst_Thrsh is also met.

Value Units: Percent

y/x	1
1	255

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeFCLP_T_IntegrationCatalystMax

Description: Maximum allowed estimated catalytic converter temperature for post O2 integral terms to be updated.**Value Units:** Celcius

y/x	1
1	950

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeFCLP_T_IntegrationCatalystMin

Description: Minimum allowed estimated catalytic converter temperature to begin using post O2 integration correction terms. Converter temperature must remain above this threshold to ramp-in the post O2 integration adjustments. Once the ramp-in has started, a converter temperature below this threshold will freeze the ramp-in multiplier. Post O2 integration will not be allowed below this converter temperature

Value Units: Celcius

y/x	1
1	350

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeFULC_T_WRAF_SensorReadyThrsh

Description: Pumping cell temperature threshold above which the wideband oxygen sensor will be considered ready for use**Value Units:** Degrees Celcius

y/x	1
1	700

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KeWRSC_T_HtrCntrlCL

Description: WRAF heater temperature enabling threshold for transition from Open Loop to Closed Loop

Value Units: Degrees Celcius

y/x	1
1	628

Initial Supporting table - Closed Loop Enable Clarification - KeWRSI_T_PumpCurrentEnable

Description: WRAF heater temperature threshold for enabling the sensor pump current

Value Units: Degrees Celcius

y/x	1
1	628

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KfFCLL_T_AdaptiveLoCoolant

Description: LTM learning is inhibited if the engine coolant temperature is below this calibration.

Value Units: Degrees Celcius

y/x	1
1	35

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KfFCLP_U_O2ReadyThrshLo

Description: Voltage limit checked against when determining if a post converter oxygen sensor is in range**Value Units:** millivolts

y/x	1
1	1,100

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KfFULC_U_O2_SensorReadyThrshLo

Description: Voltage limit checked against when determining if a pre converter oxygen sensor is in range

Value Units: millivolts

y/x	1
1	1,100

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KtFCLL_p_AdaptiveLowMAP_Limit

Description: Long term fuel learning is disabled below this MAP limit as a function of barometric pressure.

Value Units: KPa

X Unit: KPa

y/x	65	70	75	80	85	90	95	100	105
1	17.0	17.0	17.0	17.0	17.5	18.0	18.5	19.0	19.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KtFCLP_t_PostIntglDisableTime

Description: Disable integral offset after engine start for this amount of time as a function of start up coolant temperature.

Value Units: Time in seconds

X Unit: Degrees Celcius

y/x	-40	-29	-18	-6	5	16	28	39	50	61	73	84	95	106	118	129	140
1	60.0	60.0	60.0	60.0	47.0	33.0	20.0	20.0	20.0	20.0	20.0	15.0	15.0	15.0	12.0	12.0	12.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KtFCLP_t_PostIntglRampInTime

Description: Time required to ramp integral offset to desired value as a function of start up coolant temperature.

Value Units: Time in seconds

X Unit: Degrees Celcius

y/x	-40	-29	-18	-6	5	16	28	39	50	61	73	84	95	106	118	129	140
1	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KtFSTA_t_ClosedLoopAutostart

Description: Engine run time following an autostart, as a function of begin run coolant, which must be exceeded to enable CLOSED LOOP.

Value Units: Time in seconds

X Unit: Degrees Celcius

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1.5	1.0	1.0	1.0	1.0	1.0	1.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Closed Loop Enable Clarification - KtFSTA_t_ClosedLoopTime

Description: Engine run time, as a function of startup coolant temperature, which must be exceeded to enable CLOSED LOOP.

Value Units: Time in seconds

X Unit: Degrees Celcius

y/x	-40	-28	-16	-4	8	20	32	44	56	68	80	92	104	116	128	140	152
1	250.0	250.0	200.0	100.0	30.0	20.0	20.0	20.0	20.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P043E First Reference Orifice Measurement

Description: First reference orifice measurement maximum value as a function of barometric pressure

Value Units: First reference orifice measurement maximum (kPa)

X Unit: Barometric pressure (kPa)

y/x	70	80	90	100	110
1	3.7	3.8	3.9	4.0	4.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P043E Second Reference Orifice Measurement

Description: Second reference orifice measurement maximum value as a function of barometric pressure**Value Units:** Second reference orifice measurement maximum value (kPa)**X Unit:** Barometric pressure (kPa)

y/x	70	80	90	100	110
1	4.2	4.3	4.4	4.6	4.6

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P043F First Reference Orifice Measurements

Description: First reference orifice measurement minimum value as a function of barometric pressure

Value Units: First reference orifice measurement minimum value (kPa)

X Unit: Barometric pressure (kPa)

y/x	70	80	90	100	110
1	1.2	1.3	1.4	1.5	1.5

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P043F Second Reference Orifice Measurements

Description: Second reference orifice measurement minimum value as a function of barometric pressure**Value Units:** Second reference orifice measurement minimum value (kPa)**X Unit:** Barometric pressure (kPa)

y/x	70	80	90	100	110
1	1.2	1.3	1.4	1.5	1.5

18 OBDG01 ECM Supporting Tables

Initial Supporting table - 1st_FireAftrMisfr_Acel

Description: Used for P0300 - P0308, Multiplier for establishing the expected acceleration of the cylinder after the misfire

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	500	600	700	800	900	1,000	1,100	1,200	1,400	1,800	2,200	2,600	3,000	4,000	5,000	6,000	7,000
8	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
12	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
16	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
24	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
30	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
40	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - 1st_FireAftrMisfr_Jerk

Description: Used for P0300 - P0308, Multiplier for establishing the expected Jerk of the cylinder after the misfire

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	500	600	700	800	900	1,000	1,100	1,200	1,400	1,800	2,200	2,600	3,000	4,000	5,000	6,000	7,000
8	-0.71	-0.71	-0.71	-0.71	-0.71	-0.67	-0.64	-0.60	-0.67	-0.64	-0.53	-0.48	-0.43	-0.43	-0.43	-0.43	-0.43
12	-0.66	-0.66	-0.66	-0.66	-0.66	-0.66	-0.66	-0.66	-0.71	-0.69	-0.60	-0.57	-0.53	-0.53	-0.53	-0.53	-0.53
16	-0.59	-0.59	-0.59	-0.59	-0.59	-0.64	-0.68	-0.73	-0.78	-0.76	-0.68	-0.65	-0.62	-0.62	-0.62	-0.62	-0.62
20	-0.58	-0.58	-0.58	-0.58	-0.58	-0.64	-0.69	-0.75	-0.83	-0.81	-0.70	-0.65	-0.61	-0.61	-0.61	-0.61	-0.61
24	-0.48	-0.48	-0.48	-0.48	-0.48	-0.60	-0.71	-0.83	-0.88	-0.83	-0.74	-0.73	-0.72	-0.72	-0.72	-0.72	-0.72
30	-0.38	-0.38	-0.38	-0.38	-0.38	-0.53	-0.68	-0.84	-0.88	-0.87	-0.81	-0.80	-0.79	-0.79	-0.79	-0.79	-0.79
40	-0.26	-0.26	-0.26	-0.26	-0.26	-0.42	-0.59	-0.75	-0.83	-0.94	-0.93	-0.88	-0.83	-0.83	-0.83	-0.83	-0.83
60	-0.26	-0.26	-0.26	-0.26	-0.26	-0.42	-0.59	-0.75	-0.83	-0.94	-0.93	-0.88	-0.83	-0.83	-0.83	-0.83	-0.83
100	-0.26	-0.26	-0.26	-0.26	-0.26	-0.42	-0.59	-0.75	-0.83	-0.94	-0.93	-0.88	-0.83	-0.83	-0.83	-0.83	-0.83

18 OBDG01 ECM Supporting Tables

Initial Supporting table - 1stFireAfterMisJerkAFM

Description: Used for P0300 - P0308, Multiplier for establishing the expected jerk of the cylinder after the misfire if Active Fuel Management cylinder deact mode is active

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
8	1	1	1	1	1	1	1	1	1
12	1	1	1	1	1	1	1	1	1
16	1	1	1	1	1	1	1	1	1
20	1	1	1	1	1	1	1	1	1
24	1	1	1	1	1	1	1	1	1
30	1	1	1	1	1	1	1	1	1
40	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1
100	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - 1stFireAfrMisAcelAFM

Description: Used for P0300 - P0308, Multiplier for establishing the expected acceleration of the cylinder after the misfire if Active Fuel Management cylinder deact mode is active

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
8	1	1	1	1	1	1	1	1	1
12	1	1	1	1	1	1	1	1	1
16	1	1	1	1	1	1	1	1	1
20	1	1	1	1	1	1	1	1	1
24	1	1	1	1	1	1	1	1	1
30	1	1	1	1	1	1	1	1	1
40	1	1	1	1	1	1	1	1	1
60	1	1	1	1	1	1	1	1	1
100	1	1	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Abnormal Cyl Mode

Description: Used for P0300-P0308. Number of consecutive number of decelerating cylinders after the misfire that would be considered abnormal. (Cylinder Mode Equation)

Value Units: Number of consecutive number of decelerating cylinders (integer)

X Unit: thousands of RPM (rpm/1000)

y/x	0	1	2	3	4	5	6	7	8
1	2	2	2	2	2	2	2	2	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Abnormal Rev Mode

Description: Used for P0300-P0308. Abnormal Rev Mode Number of consecutive number of decelerating cylinders after the misfire that would be considered abnormal. (Rev Mode Equation)

Value Units: Number of consecutive number of decelerating cylinders (integer)

X Unit: thousands of RPM (rpm/1000)

y/x	0	1	2	3	4	5	6	7	8
1	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Abnormal SCD Mode

Description: Used for P0300-P0308. Number of consecutive number of decelerating cylinders after the misfire that would be considered abnormal. (SCD Mode Equation)

Value Units: Number of consecutive number of decelerating cylinders (integer)

X Unit: thousands of RPM (rpm/1000)

y/x	0	1	2	3	4	5	6	7	8
1	2	2	2	2	2	2	2	2	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Bank_SCD_Decel

Description: Used for P0300 - P0308, Multplier to SCD decel to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
5	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
10	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
20	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
30	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
40	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
50	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
60	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
80	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
100	12.03	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Bank_SCD_Jerk

Description: Used for P0300 - P0308, Multplier to Medres SCD jerk to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: mulitplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
5	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
10	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
20	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
30	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
40	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
50	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
60	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
80	13.14	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
100	5.66	8.21	11.37	15.00	15.00	15.00	15.00	15.00	15.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - BankCylModeDecel

Description: Used for P0300 - P0308, Multplier to Lores Decel to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
5	10.71	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
10	10.71	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
20	9.38	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
30	4.92	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
40	3.19	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
50	2.63	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
60	2.63	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
80	6.25	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
100	3.95	15.00	15.00	15.00	8.35	10.33	11.94	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - BankCylModeJerk

Description: Used for P0300 - P0308, Multplier to Lores Jerk to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
5	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
10	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
20	6.50	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
30	4.45	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
40	3.75	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
50	3.12	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
60	3.12	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
80	6.22	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00
100	3.25	8.54	11.81	11.81	11.81	11.81	11.81	13.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00	15.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Catalyst_Damage_Misfire_Percentage

Description: Catalyst Damaging Misfire Percentage" Table whenever secondary conditions are met.

Value Units: percent misfire over 200 revolutions (%)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	0	1,000	2,000	3,000	4,000	5,000	6,000	7,000
0	22.5	22.5	22.5	20.0	16.6	12.5	4.6	4.6
10	22.5	22.5	22.5	20.0	16.6	12.5	4.6	4.6
20	22.5	22.5	22.5	20.0	16.6	10.0	4.6	4.6
30	20.0	20.0	20.0	20.0	14.4	8.3	4.6	4.6
40	16.7	16.7	16.7	16.7	12.5	5.0	4.6	4.6
50	10.0	10.0	10.0	10.0	10.0	4.6	4.6	4.6
60	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
70	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
80	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
90	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
100	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ClyAfterAFM_Decel

Description: Used for P0300 - P0308, Multiplier to Lores decel to account for different pattern of misfire after a deactivated cylinder. Similar to the second cylinder of consecutive cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
10	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
40	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
60	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
80	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
100	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ClyBeforeAFM_Jerk

Description: Used for P0300 - P0308, Multiplier to Lores decel to account for different pattern of misfire before a deactivated cylinder, but after an active cylinder that follows an deactive cylinder on engine that supports cylinder deactivation in non even fire patterns.. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
10	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
20	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
30	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
40	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
50	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
80	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60
100	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60	0.60

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CombustModelIdleTbl

Description: Used for P0300 - P0308, Only used on Diesel engines. Combustion modes that will force use of Idle table. A value of CeCMBR_i_CombModesMax means not selected.

Value Units: Enumerated value of different combustion modes (enumeration)

X Unit: Current Combustion Mode (enumeration)

CombustModelIdleTbl - Part 1

y/x	0	1	2	3	4	5
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max

CombustModelIdleTbl - Part 2

y/x	6	7	8	9	10	11
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max

CombustModelIdleTbl - Part 3

y/x	12	13	14	15	16	
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ConsecCylModDecel

Description: Used for P0300 - P0308, Multiplier to Lores decel to account for different pattern of the second cylinder of consecutive misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	0.82	0.82	0.82	0.82	0.82	1.01	0.66	1.02	0.64	0.64	1.02	1.73	1.65	1.60	1.33	1.30	1.30
8	0.82	0.82	0.82	0.82	0.82	1.01	0.66	1.02	0.64	0.64	1.02	1.73	1.65	1.60	1.33	1.30	1.30
12	0.82	0.82	0.82	0.82	0.82	1.01	0.66	1.02	0.64	0.64	1.02	1.73	1.65	1.60	1.33	1.30	1.30
16	1.22	1.22	1.22	1.22	1.22	1.23	1.47	1.17	1.07	1.07	1.40	1.73	1.65	1.60	1.33	1.30	1.30
20	1.32	1.32	1.32	1.32	1.32	1.58	1.53	1.53	1.48	1.29	1.28	1.27	1.50	1.78	1.77	1.70	1.70
24	1.32	1.32	1.32	1.32	1.32	1.58	1.55	1.56	1.46	1.50	1.28	1.27	1.34	1.33	2.00	2.17	2.17
26	1.23	1.23	1.23	1.23	1.23	1.76	1.46	1.44	1.42	1.42	1.38	1.68	1.49	1.19	1.33	2.33	2.33
30	0.83	0.83	0.83	0.83	0.83	0.90	1.22	1.54	1.49	1.44	1.33	1.26	1.31	1.38	1.27	1.29	1.29
50	0.83	0.83	0.83	0.83	0.83	0.90	1.08	1.26	1.98	1.78	1.73	1.64	1.64	1.62	1.57	1.45	1.45

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ConsecCylModeJerk

Description: Used for P0300 - P0308, Multplier to Lores Jerk to account for different pattern of the second cylinder of consecutive misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	0	0	0	0	0	0	-1	-1	-1	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	-1	-1	-1	0	0	0	0	0	0	0	0
12	0	0	0	0	0	0	-1	-1	-1	0	0	0	0	0	0	0	0
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
24	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
26	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
30	-1	-1	-1	-1	-1	-1	-5	0	0	0	0	0	0	0	0	0	0
50	-1	-1	-1	-1	-1	-1	-3	0	0	0	0	0	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ConsecSCD_Decel

Description: Used for P0300 - P0308, Multitplier to medres decel to account for different pattern of the second cylinder of consecutive misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	-0.23	-0.23	-0.23	-0.23	-0.23	-0.23	0.35	0.00	0.00
8	-0.23	-0.23	-0.23	-0.23	-0.23	-0.23	0.35	-0.35	0.00
12	0.01	0.01	0.01	0.01	0.01	0.01	0.35	-0.35	0.25
16	0.01	0.01	0.01	0.01	0.01	0.01	0.55	0.36	0.53
20	0.14	0.14	0.14	0.14	0.14	0.14	0.10	0.24	0.15
24	0.13	0.13	0.13	0.13	0.13	0.13	-0.47	0.01	0.15
26	0.11	0.11	0.11	0.11	0.11	0.11	-1.05	-0.35	0.48
30	0.11	0.11	0.11	0.11	0.11	0.11	-1.82	-1.14	-1.19
50	0.11	0.11	0.11	0.11	0.11	0.11	-1.82	-0.89	-1.19

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ConsecSCD_Jerk

Description: Used for P0300 - P0308, Multiplier to medres Jerk to account for different pattern of the second cylinder of consecutive misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	-1.73	-1.73	-1.73	-1.73	-1.73	-1.73	-1.02	-2.10	-0.91
8	-2.00	-2.00	-2.00	-2.00	-2.00	-2.00	-1.09	-2.04	-1.02
12	-2.00	-2.00	-2.00	-2.00	-2.00	-2.00	-1.09	-2.04	-1.02
16	-1.86	-1.86	-1.86	-1.86	-1.86	-1.86	-1.00	-0.97	-0.78
20	-1.70	-1.70	-1.70	-1.70	-1.70	-1.70	-1.70	-2.25	-1.48
24	-1.76	-1.76	-1.76	-1.76	-1.76	-1.76	-1.76	-2.25	-1.48
26	-1.73	-1.73	-1.73	-1.73	-1.73	-1.73	-1.73	-2.46	-1.33
30	-3.65	-3.65	-3.65	-3.65	-3.65	-3.65	-3.65	-2.97	-3.12
50	-2.01	-2.01	-2.01	-2.01	-2.01	-2.01	-2.01	-2.10	-3.12

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylAfterAFM_Jerk

Description: Used for P0300 - P0308, Multiplier to Lores Jerk to account for different pattern of misfire after a deactivated cylinder. Similar to the second cylinder of consecutive cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	0	0	0	0	0	0	0	0	0
10	0	0	0	0	0	0	0	0	0
20	0	0	0	0	0	0	0	0	0
30	0	0	0	0	0	0	0	0	0
40	0	0	0	0	0	0	0	0	0
50	0	0	0	0	0	0	0	0	0
60	0	0	0	0	0	0	0	0	0
80	0	0	0	0	0	0	0	0	0
100	0	0	0	0	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylBeforeAFM_Decel

Description: Used for P0300 - P0308, Multiplier to Lores decel to account for different pattern of misfire before a deactivated cylinder, but after an active cylinder that follows an deactive cylinder on engine that supports cylinder deactivation in non even fire patterns.. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
10	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
40	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
60	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
80	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
100	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylModeDecel

Description: Used for P0300-P0308. Crankshaft decel threshold. Thresholds are a function of rpm and % engine Load.

Value Units: Delta time per cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

CylModeDecel - Part 1

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,000
3	2,800	1,800	1,250	825	621	420	389	289	249	180	158	110	76
6	2,800	1,800	1,250	825	621	420	389	289	249	180	158	110	76
8	2,800	1,800	1,250	825	621	420	389	289	249	180	158	110	76
10	2,800	1,800	1,250	825	621	420	389	289	249	180	158	110	76
12	2,950	1,875	1,310	900	644	498	415	333	255	188	159	116	78
14	3,199	2,090	1,403	1,004	732	570	560	400	344	209	160	126	80
16	4,743	2,920	1,958	1,466	1,041	884	676	476	415	265	191	174	97
18	6,103	3,809	2,568	1,775	1,212	1,016	830	618	450	306	253	205	132
20	7,610	4,743	3,084	2,110	1,497	1,241	1,186	658	506	318	266	239	149
22	9,410	5,726	3,795	2,597	1,798	1,589	1,315	953	571	340	327	245	153
24	9,585	5,996	3,930	2,726	1,976	1,743	1,405	1,055	631	369	350	271	166
26	11,428	7,062	4,663	3,261	2,264	1,859	1,539	1,080	900	491	428	317	196
30	3,200	2,200	1,600	1,200	900	700	350	1,130	956	868	606	447	274
40	4,338	3,099	2,066	1,505	1,122	783	388	365	1,387	1,115	1,011	644	422
50	4,800	3,250	2,150	1,600	1,250	908	521	450	1,731	1,362	1,165	660	438
60	6,100	3,800	2,550	1,800	1,350	1,033	900	783	2,142	1,688	1,455	880	571
97	7,600	4,750	3,100	2,100	1,500	1,583	1,350	1,122	3,593	2,905	2,513	1,469	961

CylModeDecel - Part 2

y/x	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000
3	59	42	32	26	25	14	10	7	5	5	5	5	5
6	59	42	32	26	25	14	10	7	5	5	5	5	5
8	59	42	32	26	25	14	10	7	5	5	5	5	5
10	59	42	32	26	25	14	10	7	5	5	5	5	5
12	63	44	36	30	26	14	10	7	5	5	5	5	5
14	65	46	37	31	26	16	11	8	6	5	5	5	5
16	70	51	42	32	27	17	12	8	6	5	5	5	5
18	85	61	45	33	28	17	12	9	7	5	5	5	5
20	108	82	68	59	46	19	13	10	7	6	6	6	6
22	127	91	70	60	48	31	18	10	8	6	6	6	6
24	146	107	85	69	52	32	22	15	8	6	6	6	6

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylModeDecel

26	158	118	90	73	55	34	24	18	12	6	6	6	6
30	201	134	99	79	62	43	29	20	15	10	10	10	10
40	311	210	147	120	100	56	36	26	20	16	16	16	16
50	318	261	178	142	116	70	46	31	26	19	19	19	19
60	420	316	220	176	142	73	48	36	28	20	20	20	20
97	704	535	364	292	235	132	85	62	50	36	36	36	36

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylModeJerk

Description: Crankshaft jerk threshold. Thresholds are a function of rpm and % engine Load.

Value Units: Change in Delta time per cylinder from last cylinder (usec)

Y Units: percent load of max indicated torque (%)

CylModeJerk - Part 1

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,000
3	1,991	1,393	1,012	772	579	419	374	316	259	238	189	155	109
6	1,991	1,393	1,012	772	579	419	374	316	259	238	189	155	109
8	1,991	1,393	1,012	772	579	419	374	316	259	238	189	155	109
10	1,991	1,393	1,012	772	579	419	374	316	259	238	189	155	109
12	2,570	1,754	1,264	956	726	500	481	382	318	269	250	186	145
14	4,615	3,135	2,199	1,633	1,197	902	722	542	460	379	316	253	214
16	6,422	4,271	2,954	2,166	1,606	1,115	932	749	633	516	440	363	250
18	6,738	4,535	3,146	2,331	1,709	1,268	1,043	818	687	557	464	371	286
20	7,041	4,750	3,328	2,442	1,823	1,398	1,114	830	732	634	538	443	303
22	8,004	5,387	3,756	2,788	2,049	1,477	1,241	1,004	840	676	583	489	328
24	8,674	5,824	4,060	3,035	2,215	1,610	1,337	1,065	892	719	620	521	373
26	9,603	6,485	4,506	3,322	2,458	1,790	1,494	1,199	977	756	676	595	420
30	2,871	2,163	1,639	1,272	970	700	700	1,000	1,000	841	728	615	495
40	3,307	2,608	2,096	1,584	1,180	800	800	1,200	1,200	966	879	792	652
50	4,826	3,604	2,803	2,234	1,749	1,327	1,327	1,327	1,327	1,327	1,190	1,050	812
60	5,770	4,243	3,467	2,743	2,148	1,583	1,583	1,583	1,583	1,583	1,429	1,264	994
97	9,219	6,944	5,547	4,430	3,512	2,541	2,541	2,541	2,541	2,541	2,309	2,071	1,630

CylModeJerk - Part 2

y/x	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000
3	81	62	54	43	35	25	20	13	9	7	7	7	7
6	81	62	54	43	35	25	20	13	9	7	7	7	7
8	81	62	54	43	35	25	20	13	9	7	7	7	7
10	81	62	54	43	35	25	20	13	9	7	7	7	7
12	108	84	63	56	44	31	24	15	10	9	9	9	9
14	172	129	100	71	62	37	24	19	12	9	9	9	9
16	200	134	119	99	68	49	26	22	15	11	11	11	11
18	207	173	132	109	85	50	38	26	15	13	13	13	13
20	230	184	140	114	95	57	40	29	20	15	15	15	15
22	256	202	149	121	104	58	42	32	23	15	15	15	15
24	266	219	167	136	109	64	45	32	24	17	17	17	17

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CylModeJerk

26	318	242	193	147	112	72	50	34	28	19	19	19	19
30	371	261	208	162	148	91	60	45	33	22	22	22	22
40	507	380	270	243	200	110	70	57	42	28	28	28	28
50	586	428	334	298	239	135	91	64	56	41	41	41	41
60	732	545	404	362	291	157	104	74	64	50	50	50	50
97	1,205	888	656	597	478	292	181	128	110	83	83	83	83

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DeacCylInversionDecel

Description: Used for P0300 - P0308, Negative Torque can cause crank readings to invert (active cylinders appear weak & deactivated cylinders appear "strong" If deactivated cylinders don't decelerate at least this amount then the crank signal is inverting. Function of speed and load.

Value Units: Delta time per cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	30	10	5	0	0	0	0	0	0
10	30	15	5	0	0	0	0	0	0
20	30	15	8	0	0	0	0	0	0
30	125	55	25	0	0	0	0	0	0
40	175	100	50	0	0	0	0	0	0
50	275	150	75	14	0	0	0	0	0
60	325	175	100	25	15	7	5	2	2
80	375	200	120	40	30	12	10	7	7
100	475	250	160	60	50	25	20	17	17

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DeacCylInversionJerk

Description: Used for P0300 - P0308, Negative Torque can cause crank readings to invert (active cylinders appear weak & deactivated cylinders appear "strong" If deactivated cylinders don't jerk at least this amount then the crank signal is inverting. Function of speed and load.

Value Units: Change in Delta time per cylinder from last cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	100	25	10	5	5	2	0	0	0
10	250	80	30	18	10	2	0	0	0
20	350	150	100	35	16	5	2	0	0
30	600	300	185	75	20	15	5	4	4
40	800	450	230	100	30	19	14	5	5
50	950	600	350	115	45	25	18	12	12
60	1,025	650	450	200	90	40	30	20	20
80	1,100	700	475	225	100	50	35	25	25
100	1,250	800	535	275	120	70	45	40	40

18 OBDG01 ECM Supporting Tables

Initial Supporting table - EngineOverSpeedLimit

Description: Engine OverSpeed Limit versus gear**Value Units:** RPM**X Unit:** Enumeration of transmission gear state (enumeration)**EngineOverSpeedLimit - Part 1**

y/x	CeTGRR_e_TransGr1	CeTGRR_e_TransGr2	CeTGRR_e_TransGr3	CeTGRR_e_TransGr4	CeTGRR_e_TransGr5	CeTGRR_e_TransGr6	CeTGRR_e_TransGr9
1	5,800	5,800	5,800	5,800	5,800	5,800	5,800

EngineOverSpeedLimit - Part 2

y/x	CeTGRR_e_TransGr10	CeTGRR_e_TransGrNaut	CeTGRR_e_TransGrRvrs	CeTGRR_e_TransGrPark	CeTGRR_e_TransGr7	CeTGRR_e_TransGr8	
1	5,800	5,800	5,800	5,800	5,800	5,800	

18 OBDG01 ECM Supporting Tables

Initial Supporting table - IdleCyl_Decel

Description: Used for P0300-P0308. Crankshaft decel threshold. Thresholds are a function of rpm and % engine Load.

Value Units: Delta time per cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,250	1,300	1,350	1,375	1,400	1,425	1,450	1,500	1,600	1,700	1,800	1,900	2,000
3	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
6	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
8	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
10	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
12	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
14	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
16	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
18	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
20	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
22	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
24	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
26	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
30	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
40	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
50	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
60	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
97	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767

18 OBDG01 ECM Supporting Tables

Initial Supporting table - IdleCyl_Jerk

Description: Crankshaft jerk threshold. Thresholds are a function of rpm and % engine Load.

Value Units: Change in Delta time per cylinder from last cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,250	1,300	1,350	1,375	1,400	1,425	1,450	1,500	1,600	1,700	1,800	1,900	2,000
3	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
6	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
8	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
10	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
12	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
14	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
16	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
18	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
20	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
22	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
24	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
26	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
30	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
40	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
50	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
60	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
97	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767

18 OBDG01 ECM Supporting Tables

Initial Supporting table - IdleSCD_Decel

Description: Used for P0300-P0308. Crankshaft decel threshold while in SCD mode. SCD mode uses smaller windows near TDC. Thresholds are a function of rpm and % engine Load. Note: Misfire's Load term is %, but not PID\$04. PID \$04 is not robust to temperature and altitude shifts. (especially decel and jerk thresholds since they track actual air trapped in cylinder)

Value Units: Delta time per cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,150	1,200	1,250	1,300	1,350	1,400	1,450	1,500
3	353	249	179	128	84	77	69	62	55	46	38	37	36
6	353	249	179	128	84	77	69	62	55	46	38	37	36
8	353	249	179	128	84	77	69	62	55	46	38	37	36
10	418	287	206	153	117	100	84	76	68	59	51	50	50
12	592	374	267	194	140	115	90	92	94	79	65	64	62
14	678	467	315	227	170	154	138	136	134	112	90	83	76
16	808	543	379	270	197	157	116	137	157	133	108	99	89
18	980	678	443	318	231	185	138	126	113	121	129	120	111
20	1,007	702	462	345	250	207	164	143	122	132	142	133	125
22	1,212	824	567	404	295	248	201	189	177	166	156	145	133
24	1,209	815	562	411	308	266	224	216	208	186	164	135	106
26	1,302	887	639	458	347	301	255	239	222	200	178	168	158
30	1,448	971	680	491	367	333	299	232	165	152	138	163	188
40	800	594	459	374	292	266	240	184	128	232	335	247	160
50	1,054	782	609	485	380	347	313	240	167	286	405	305	205
60	1,307	970	747	602	466	425	384	291	197	335	472	361	250
97	2,245	1,654	1,272	1,022	799	733	667	502	336	546	756	589	423

18 OBDG01 ECM Supporting Tables

Initial Supporting table - IdleSCD_Jerk

Description: Used for P0300-P0308. Crankshaft jerk threshold while in SCD mode. SCD mode uses smaller windows near TDC. Thresholds are a function of rpm and % engine Load.

Value Units: Change in Delta time per cylinder from last cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,150	1,200	1,250	1,300	1,350	1,400	1,450	1,500
3	256	185	131	94	69	64	59	55	52	44	36	35	34
6	256	185	131	94	69	64	59	55	52	44	36	35	34
8	256	185	131	94	69	64	59	55	52	44	36	35	34
10	341	241	173	129	97	85	72	68	63	58	52	48	44
12	432	300	219	164	127	108	90	86	81	77	72	68	63
14	633	429	309	233	176	158	139	126	113	100	88	83	78
16	793	536	381	287	216	190	165	144	123	107	90	85	80
18	889	607	429	340	258	214	169	164	160	138	115	108	101
20	966	672	477	354	264	235	207	186	165	144	124	116	109
22	1,065	727	529	381	286	250	214	200	186	157	128	125	122
24	1,180	804	558	421	304	264	224	210	195	177	158	142	126
26	1,297	870	611	459	346	291	237	222	206	189	171	158	146
30	1,327	921	666	499	385	338	292	207	121	149	176	180	183
40	2,055	1,411	1,014	754	577	491	406	381	356	340	324	260	196
50	2,468	1,710	1,221	911	696	594	492	441	390	381	373	319	264
60	2,961	2,036	1,467	1,094	839	713	587	527	467	461	456	385	313
97	4,767	3,289	2,375	1,768	1,356	1,159	961	830	699	732	765	631	498

18 OBDG01 ECM Supporting Tables

Initial Supporting table - InfrequentRegen

Description: Used for P0300-P0308. Only used on Diesel engines. Initiates a misfire delay when the current combustion mode matches a selection in the table. A value of CeCMBR_i_CombModesMax means not selected.

Value Units: Enumerated value of different combustion modes (enumeration)

X Unit: Current Combustion Mode (enumeration)

InfrequentRegen - Part 1

y/x	0	1	2	3	4	5
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max

InfrequentRegen - Part 2

y/x	6	7	8	9	10	11
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max

InfrequentRegen - Part 3

y/x	12	13	14	15	16	
1	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	CeCMBR_i_CombModes Max	

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Number of Normals

Description: Used for P0300-P0308. Number of Normals for the Driveline Ring Filter

After a low level misfire, another misfire may not be detectable until driveline ringing ceases. If no ringing seen, stop filter early.

Value Units: Number of Engine cycles after isolated misfire (Engine cycles)

X Unit: thousands of RPM (rpm/1000)

y/x	0	1	2	3	4	5	6	7	8
1	2	2	2	2	2	2	2	2	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P00C6 - High Pressure Pump Control Mode timeout

Description: High Pressure Pump Control Mode timeout**Value Units:** Time (Seconds)**X Unit:** Coolant Temperature (Deg C)

y/x	-40	-32	-25	-25	-16	-8	0	8	16	20	24	32	40	48	64	80	96
1	12.0	12.0	11.5	11.5	9.0	7.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P00C6 - maximum acceptable counts of fuel rail pressure below KtFHPD_p_HPS_PressFallLoThrsh after High Pressure State

Description: The maximum acceptable counts of fuel rail pressure below KtFHPD_p_HPS_PressFallLoThrsh after High Pressure Start (HPS) is executed but before engine is in run mode.

Value Units: maximum acceptable counts of fuel rail pressure below KtFHPD_p_HPS_PressFallLoThrsh after High Pressure Start (Count)

X Unit: Ethanol Precent (%)

Y Units: Coolant Temperature (Deg C)

y/x	-40	-32	-25	-25	-16	-8	0	8	16	20	24	32	40	48	64	80	96
0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
13	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
25	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
38	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
50	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
63	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
75	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
88	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
100	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P00C6 - Minimum acceptable value of fuel rail pressure after High Pressure Start

Description: The minimum acceptable value of fuel rail pressure after High Pressure Start (HPS) is executed. This ensures the pressure does not fall off drastically after High Pressure Start (HPS) is executed, but before engine is in run mode.

Value Units: Minimum acceptable value of fuel rail pressure after High Pressure Start (Mpa)

X Unit: Ethanol Precent (%)

Y Units: Coolant Temperature (Deg C)

y/x	-40	-32	-25	-25	-16	-8	0	8	16	20	24	32	40	48	64	80	96
0	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
13	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
25	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
38	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
50	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
63	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
75	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
88	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
100	2.0	2.0	2.0	2.0	2.0	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P00C6 - Minimum pressure in MPa that will exit High Pressure Start mode and allow fuel delivery

Description: This calibration is the minimum pressure in MPa that will exit High Pressure Start mode and allow fuel delivery

Value Units: Minimum pressure in MPa that will exit High Pressure Start mode and allow fuel delivery

X Unit: Ethanol Precent (%)

Y Units: Coolant Temperature (Deg C)

y/x	-40	-32	-25	-25	-16	-8	0	8	16	20	24	32	40	48	64	80	96
0	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
13	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
25	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
38	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
50	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
63	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
75	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
88	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
100	18.0	18.0	17.0	17.0	15.0	10.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0191 - High fail limit of fuel control due to high pressure sensor skewed High

Description: High fail limit of fuel control due to high pressure sensor skewed High error as Function of desired pressure

Value Units: Ratio

X Unit: Desired Pressure (Mpa)

y/x	1.50	3.00	4.00	10.00	15.00	20.00	25.00	30.00	35.00
1.00	1.20	1.20	1.20	1.20	1.20	1.20	1.20	1.09	1.05

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0191 - Low fail limit of fuel control due to pressure sensor skewed low

Description: Low fail limit of fuel control due to pressure sensor skewed low error as Function of desired pressure

Value Units: Ratio

X Unit: Desired Pressure (Mpa)

y/x	1.50	3.00	4.00	10.00	15.00	20.00	25.00	30.00	35.00
1.00	0.75	0.75	0.75	0.75	0.79	0.82	0.86	0.92	0.95

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0201BestFailingOSCTableB1

Description: This table is a 9x17 table of baseline Best Failing (e.g. threshold converter) OSC times for catalyst Bank 1. The axis' for this table include the average airflow and the catalyst temperature. After OSC is measured for a specific temp and airflow,the BestFailing OSC value is found within this table for the measured temp and airflow and is used along with the OSC_TimeRaw (and the WorstPassing value) to calculate the Normalized Ratio for that specific test. The values in this table are based on the measured OSC for the identified BPU converter that is used for MIL illumination across the specific temp and airflow range for a given program.

y/x	1.63	1.86	2.10	2.33	2.57	2.80	3.04	3.28	3.51	3.75	3.98	4.22	4.46	4.69	4.93	5.16	5.40
576.00	2.02	1.54	1.06	0.99	0.89	0.81	0.80	0.78	0.64	0.63	0.61	0.60	0.59	0.58	0.54	0.48	0.45
610.00	2.03	1.55	1.09	1.03	0.90	0.84	0.83	0.81	0.66	0.65	0.64	0.63	0.61	0.60	0.55	0.50	0.47
644.00	2.09	1.61	1.12	1.08	0.92	0.86	0.85	0.83	0.66	0.66	0.64	0.63	0.61	0.59	0.57	0.52	0.49
678.00	2.18	1.69	1.19	1.17	0.93	0.88	0.86	0.84	0.67	0.66	0.65	0.64	0.61	0.59	0.57	0.54	0.50
712.00	2.22	1.72	1.23	1.21	0.93	0.90	0.89	0.87	0.69	0.68	0.67	0.66	0.64	0.61	0.58	0.54	0.51
746.00	2.23	1.73	1.24	1.22	0.96	0.93	0.91	0.88	0.72	0.71	0.70	0.69	0.67	0.64	0.60	0.57	0.53
780.00	2.50	1.91	1.33	1.23	1.01	0.95	0.92	0.89	0.74	0.72	0.72	0.71	0.68	0.65	0.62	0.59	0.55
814.00	2.51	1.92	1.36	1.24	1.08	0.97	0.92	0.90	0.76	0.74	0.72	0.71	0.70	0.66	0.64	0.61	0.58
848.00	2.66	2.02	1.39	1.24	1.09	0.98	0.93	0.91	0.79	0.79	0.76	0.75	0.73	0.72	0.67	0.64	0.60

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0420_WorstPassingOSCTableB1

Description: This table is a 9x17 table of WorstPassing (e.g. 120k) OSC times for catalyst Bank 1. The axis' for this table include the average airflow and the catalyst temperature. After OSC is measured for a specific temp and airflow, the WorstPassing OSC value is found within this table for the measured temp and airflow and is used along with the OSC_TimeRaw (and the BestFailing OSC value) to calculate the Normalized Ratio for that specific test. The values in this table are based on the measured OSC for the WPA part across the temp and airflow range.

y/x	1.63	1.86	2.10	2.33	2.57	2.80	3.04	3.28	3.51	3.75	3.98	4.22	4.46	4.69	4.93	5.16	5.40
576.00	2.89	2.35	1.81	1.70	1.47	1.19	1.18	1.13	1.09	0.97	0.88	0.87	0.85	0.83	0.81	0.77	0.75
610.00	2.90	2.36	1.83	1.72	1.51	1.21	1.20	1.17	1.12	1.01	0.90	0.88	0.87	0.85	0.83	0.78	0.76
644.00	2.94	2.39	1.84	1.75	1.53	1.23	1.23	1.18	1.15	1.04	0.93	0.92	0.90	0.88	0.86	0.80	0.76
678.00	2.98	2.43	1.88	1.82	1.54	1.28	1.27	1.23	1.17	1.06	0.95	0.94	0.92	0.90	0.88	0.82	0.77
712.00	3.01	2.45	1.90	1.86	1.54	1.33	1.33	1.26	1.19	1.08	0.97	0.95	0.94	0.92	0.89	0.83	0.79
746.00	3.02	2.46	1.92	1.87	1.54	1.34	1.33	1.27	1.19	1.11	0.99	0.97	0.95	0.93	0.92	0.87	0.80
780.00	3.15	2.55	1.96	1.88	1.55	1.35	1.34	1.27	1.21	1.11	1.01	0.99	0.97	0.96	0.92	0.89	0.82
814.00	3.16	2.56	1.98	1.89	1.69	1.51	1.47	1.31	1.23	1.13	1.03	1.01	0.99	0.96	0.94	0.89	0.85
848.00	3.24	2.62	2.00	1.89	1.70	1.53	1.50	1.38	1.27	1.17	1.06	1.04	1.02	1.00	0.95	0.93	0.87

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P228C P2C1F - High Pressure Pump Control (HPC) fail threshold of pressure too low

Description: The High Pressure Pump Control (HPC) fail threshold of pressure too low test as a function of desired fuel pressure.

Value Units: Pressure Error - Desired pressure - Actual Pressure (Mpa)

X Unit: Desired Pressure (Mpa)

y/x	2	3	4	10	15	20	25	30	35
1	0	2	3	3	4	5	5	5	5

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P228D P2C20 - High Pressure Pump Control (HPC) fail threshold for pressure too high

Description: The High Pressure Pump Control (HPC) fail threshold for pressure too high test as a function of desired fuel pressure.

Value Units: Pressure Error - Desired pressure - Actual Pressure (Mpa)

X Unit: Desired Pressure (Mpa)

y/x	1.50	3.00	4.00	10.00	15.00	20.00	25.00	30.00	35.00
1	-3.00	-3.00	-3.00	-3.00	-4.00	-4.00	-4.00	-4.00	-4.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P2635 Max Fuel Flow

Description: P2635 Maximum Fuel Flow Disable Criteria

Maximum allowed fuel flow values above which the diagnostic is disabled

Value Units: grams / sec

X Unit: kPa [desired fuel pressure]

Y Units: Volts [device supply]

y/x	200.0	250.0	300.0	350.0	400.0	450.0	500.0	550.0	600.0
4.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
6.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
7.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
9.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
10.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
12.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
13.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
15.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
16.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
18.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
19.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
21.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
22.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
24.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
25.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
27.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0
28.5	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0	512.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P2635 Threshold High

Description: P2635 Filtered Fuel Pressure Error High Threshold [under-performing pump]
Instantaneously calculated filtered fuel pressure error

Value Units: kPa

X Unit: kPa [desired fuel pressure]

Y Units: grams / sec [fuel flow]

y/x	200.0	250.0	300.0	350.0	400.0	450.0	500.0	550.0	600.0
0.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
1.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
3.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
4.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
6.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
7.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
9.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
10.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
12.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
13.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
15.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
16.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
18.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
19.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
21.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
22.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
24.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
25.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
27.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
28.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
30.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
31.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
33.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
34.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
36.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
37.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
39.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
40.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
42.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
43.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
45.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P2635 Threshold High

46.5	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0
48.0	30.0	37.5	45.0	52.5	60.0	67.5	75.0	82.5	90.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P2635 Threshold Low

Description: P2635 Filtered Pressure Error Low Threshold [over-performing pump]
Instantaneously calculated filtered fuel pressure error

Value Units: kPa

X Unit: kPa [desired fuel pressure]

Y Units: grams / sec [fuel flow]

y/x	200.0	250.0	300.0	350.0	400.0	450.0	500.0	550.0	600.0
0.0	-260.0	-210.0	-160.0	-110.0	-60.0	-67.5	-75.0	-82.5	-90.0
1.5	-145.0	-125.0	-102.5	-81.3	-60.0	-67.5	-75.0	-82.5	-90.0
3.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
4.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
6.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
7.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
9.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
10.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
12.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
13.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
15.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
16.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
18.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
19.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
21.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
22.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
24.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
25.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
27.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
28.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
30.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
31.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
33.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
34.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
36.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
37.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
39.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
40.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
42.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
43.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
45.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P2635 Threshold Low

46.5	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0
48.0	-30.0	-37.5	-45.0	-52.5	-60.0	-67.5	-75.0	-82.5	-90.0

P2B00 P2B01 P2B02 P2B03 P2B04 P2B05 P2B06 P2B07 P2B96 P2B08 P2B09 P2B0A P2B0B P2B0C P2B0D P2B0E P2B0F - kaFULO_n R

Description: Max Engine Speed to allow Multipulse function of injector energy profile				
Value Units: Max Engine Speed to allow Multipulse				
X Unit: Injector Energy Profile				
Y Units: Multipulse Mode (0 = Double Pulse, 1 = Triple Pulse)				
y/x	0	1	2	3
0	3,600	3,600	3,600	3,600
1	3,000	3,000	3,000	3,000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Pair_SCD_Decel

Description: Used for P0300 - P0308, Multplier to SCD_Decel to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	0.61	0.61	0.61	0.61	0.61	0.61	0.67	0.72	0.72
8	0.61	0.61	0.61	0.61	0.61	0.61	0.67	0.72	0.72
12	0.61	0.61	0.61	0.61	0.61	0.61	0.67	0.72	0.72
16	0.61	0.61	0.61	0.61	0.61	0.61	0.65	0.69	0.69
20	0.91	0.91	0.91	0.91	0.91	0.91	0.80	0.69	0.69
24	0.91	0.91	0.91	0.91	0.91	0.91	0.82	0.73	0.73
26	0.84	0.84	0.84	0.84	0.84	0.84	0.81	0.77	0.77
30	0.84	0.84	0.84	0.84	0.84	0.84	0.61	0.39	0.39
50	0.84	0.84	0.84	0.84	0.84	0.84	0.62	0.39	0.39

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Pair_SCD_Jerk

Description: Used for P0300 - P0308, Multplier to P0300_SCD_Jerk to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	1.31	1.31	1.31	1.31	1.31	1.31	1.42	1.52	1.52
8	1.31	1.31	1.31	1.31	1.31	1.31	1.42	1.52	1.52
12	1.31	1.31	1.31	1.31	1.31	1.31	1.41	1.52	1.52
16	1.31	1.31	1.31	1.31	1.31	1.31	1.41	1.52	1.52
20	1.56	1.56	1.56	1.56	1.56	1.56	1.58	1.59	1.59
24	1.76	1.76	1.76	1.76	1.76	1.76	1.70	1.65	1.65
26	1.84	1.84	1.84	1.84	1.84	1.84	1.75	1.65	1.65
30	1.84	1.84	1.84	1.84	1.84	1.84	1.60	1.36	1.36
50	1.84	1.84	1.84	1.84	1.84	1.84	1.60	1.36	1.36

18 OBDG01 ECM Supporting Tables

Initial Supporting table - PairCylModeDecel

Description: Used for P0300 - P0308, Multitplier to Cyl Mode Deceleration to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	0.42	0.42	0.48	0.54	0.50	0.46	0.49	0.53	0.55	0.42	0.62	0.74	0.86	0.80	0.80	0.65	0.65
8	0.42	0.42	0.48	0.54	0.50	0.46	0.49	0.53	0.55	0.42	0.62	0.74	0.86	0.80	0.80	0.65	0.65
12	0.42	0.42	0.48	0.54	0.50	0.46	0.49	0.53	0.55	0.42	0.62	0.74	0.86	0.80	0.80	0.65	0.65
16	0.50	0.50	0.51	0.52	0.53	0.53	0.53	0.53	0.55	0.69	0.62	0.74	0.86	0.80	0.80	0.65	0.65
20	0.41	0.41	0.41	0.42	0.61	0.80	0.75	0.70	0.67	0.71	0.71	0.87	0.81	0.80	0.80	0.65	0.65
24	0.41	0.41	0.41	0.42	0.61	0.81	0.81	0.81	0.67	0.74	0.81	0.87	0.81	0.97	0.80	0.65	0.65
26	0.41	0.41	0.44	0.47	0.59	0.71	0.73	0.76	0.75	0.79	0.85	0.90	0.96	0.94	0.80	0.65	0.65
30	0.65	0.65	0.50	0.35	0.34	0.33	0.42	0.51	0.61	0.61	0.79	0.88	0.86	0.86	0.79	0.65	0.65
50	0.65	0.65	0.50	0.35	0.34	0.33	0.42	0.51	0.61	0.61	0.79	0.88	0.86	0.86	0.79	0.65	0.65

18 OBDG01 ECM Supporting Tables

Initial Supporting table - PairCylModeJerk

Description: Used for P0300 - P0308, Multplier to P0300_CylModeJerk to account for different pattern of Paired cylinder misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	0.62	0.62	0.72	0.82	0.68	0.55	0.42	0.30	0.30	0.37	0.48	0.58	0.72	0.82	0.80	0.65	0.65
8	0.62	0.62	0.72	0.82	0.68	0.55	0.42	0.30	0.30	0.37	0.48	0.58	0.72	0.82	0.75	0.65	0.65
12	0.62	0.62	0.72	0.82	0.68	0.55	0.42	0.30	0.30	0.37	0.48	0.58	0.72	0.82	0.75	0.65	0.65
16	0.62	0.62	0.71	0.79	0.68	0.57	0.43	0.30	0.30	0.45	0.48	0.58	0.72	0.82	0.75	0.65	0.65
20	0.77	0.77	0.78	0.79	0.81	0.83	0.77	0.71	0.64	0.64	0.69	0.76	0.72	0.79	0.75	0.65	0.65
24	0.88	0.88	0.85	0.81	0.82	0.83	0.81	0.79	0.67	0.69	0.85	0.94	0.88	0.83	0.75	0.65	0.65
26	0.89	0.89	0.88	0.88	0.91	0.95	0.88	0.81	0.75	0.78	0.85	0.87	0.92	0.80	0.75	0.65	0.65
30	1.22	1.22	1.02	0.82	0.73	0.65	0.73	0.81	0.67	0.67	0.80	0.85	0.89	0.80	0.78	0.65	0.65
50	1.22	1.22	1.02	0.82	0.73	0.65	0.73	0.81	0.67	0.67	0.80	0.85	0.89	0.80	0.78	0.65	0.65

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Random_SCD_Decel

Description: Used for P0300 - P0308, Multplier to SCD_Decel to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.19	1.20
8	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.12	1.08
12	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.12	1.08
16	1.12	1.08	1.17	1.18	1.23	1.10	1.00	1.00	1.05
20	1.00	1.00	1.03	1.07	1.11	1.13	1.13	1.00	1.00
24	1.00	1.00	1.03	1.07	1.11	1.10	1.00	1.00	1.00
26	1.00	1.01	1.01	1.04	1.05	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.19	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Random_SCD_Jerk

Description: Used for P0300 - P0308, Multplier to Random_SCD_Jerk to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,500
2	1.10	1.00	1.07	1.15	1.20	1.12	1.15	1.15	1.05
8	1.00	1.00	1.03	1.05	1.09	1.11	1.14	1.07	1.00
12	1.00	1.00	1.03	1.05	1.09	1.11	1.14	1.07	1.00
16	1.20	1.18	1.18	1.08	1.08	1.07	1.00	1.10	1.12
20	1.06	1.06	1.04	1.07	1.08	1.00	1.00	1.09	1.10
24	1.02	1.02	1.04	1.03	1.09	1.00	1.00	1.00	1.10
26	1.00	1.02	1.04	1.03	1.04	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RandomAFM_Decl

Description: Used for P0300 - P0308, Multplier to Cylinder_Decel while in Cylnder Deactivation mode to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
10	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
40	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
60	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
80	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
100	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RandomAFM_Jerk

Description: Used for P0300 - P0308, Multplier to Cylinder_Jerk while in Cylnnder Deactivation mode to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	800	1,000	1,200	1,600	2,000	2,400	2,600	3,000	3,500
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
10	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
40	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
60	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
80	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
100	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RandomCylModDecel

Description: Used for P0300 - P0308. Multiplier to CylMode_Decel. account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: Multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	1.01	1.16	1.09	1.33	1.15	1.40	1.29	1.45	1.45	1.61	1.60	2.14	2.00	2.14	2.00	2.00	2.00
8	1.01	1.16	1.09	1.33	1.15	1.40	1.29	1.45	1.45	1.61	1.60	2.14	2.00	2.14	2.00	2.00	2.00
12	1.01	1.16	1.09	1.33	1.15	1.40	1.29	1.45	1.45	1.61	1.60	2.14	2.00	2.14	2.00	2.00	2.00
16	1.29	1.27	1.28	1.36	1.48	1.80	1.92	1.96	2.20	2.77	2.54	2.74	2.64	2.67	2.55	2.20	2.20
20	1.09	1.00	1.00	1.09	1.52	1.85	1.81	1.89	2.05	2.07	2.07	2.16	2.39	2.89	2.92	3.00	3.00
24	1.08	1.00	1.00	1.01	1.43	1.85	1.81	1.50	1.50	2.04	2.09	2.16	2.14	2.57	3.00	3.00	3.00
26	1.05	1.00	1.00	1.13	1.12	1.64	1.66	1.80	1.70	2.00	2.10	2.20	2.28	2.28	2.46	3.00	3.00
30	3.00	3.00	2.50	1.26	1.00	1.00	1.01	1.45	1.65	1.90	2.05	2.20	2.16	2.12	2.37	2.29	2.29
50	3.00	3.00	3.00	3.00	1.00	1.00	1.01	1.45	1.65	1.70	2.00	2.20	2.16	2.04	2.22	2.29	2.29

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RandomCylModJerk

Description: Used for P0300 - P0308, Multiplier to CylMode_Jerk to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,200	2,600	3,000	3,500	4,000	4,500	5,000	5,500	6,000
2	1.03	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
8	1.03	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
12	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
16	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.08	1.08
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
24	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.07	1.07
26	1.01	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.13	1.00	1.08	1.08
30	2.00	2.00	2.00	1.23	1.02	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.05	1.05	1.05
50	2.00	2.00	1.94	1.23	1.02	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RandomRevModDecI

Description: Used for P0300 - P0308, Multitplier to RevMode_Decel to account for different pattern of light level misfire. Multipliers are a function of engine rpm and % engine Load.

Value Units: multiplier

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	3,000	3,500	4,000	4,500	5,000	5,500	6,000	7,000	8,000
2	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
8	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
12	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
16	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
20	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
24	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
26	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
30	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
50	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RepetSnapDecayAdjst

Description: Used for P0300 - P0308, If misfire is present in consecutive engine cycles, this multiplier is applied to the misfire jerk threshold and compared to a crankshaft snap value after the misfire has taken place.. Table lookup as a function of engine rpm.

Value Units: multiplier

X Unit: RPM

y/x	500	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000
1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - RevMode_Decel

Description: Used for P0300-P0308. Crankshaft decel threshold. Thresholds are a function of rpm and % engine Load.

Value Units: Delta time between revolutions (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	1,100	1,200	1,400	1,600	1,800	2,000	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000
3	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
6	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
8	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
10	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
12	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
14	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
16	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
18	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
20	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
22	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
24	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
26	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
30	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
40	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
50	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
60	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767
97	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767	32,767

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Ring Filter

Description: Used for P0300-P0308. Driveline Ring Filter

After a low level misfire, another misfire may not be detectable until driveline ringing ceases. If no ringing seen, stop filter early.

Value Units: Number of Engine cycles after isolated misfire (Engine cycles)

X Unit: thousands of RPM (rpm/1000)

y/x	0	1	2	3	4	5	6	7	8
1	4	4	4	4	4	4	4	4	4

18 OBDG01 ECM Supporting Tables

Initial Supporting table - SCD_Decel

Description: Used for P0300-P0308 Crankshaft decel threshold. SCD mode uses smaller windows near TDC. Thresholds are a function of rpm and % engine Load.

Value Units: Delta time per cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,150	1,200	1,250	1,300	1,350	1,400	1,450	1,500
3	392	276	199	142	94	85	77	69	61	52	42	41	40
6	392	276	199	142	94	85	77	69	61	52	42	41	40
8	392	276	199	142	94	85	77	69	61	52	42	41	40
10	464	319	229	170	130	111	93	84	75	66	57	56	55
12	657	415	296	216	155	128	100	102	104	88	72	71	69
14	753	519	350	252	189	172	154	151	149	125	100	93	85
16	897	604	421	300	219	174	129	152	174	147	120	110	99
18	1,089	754	492	354	257	205	154	140	125	134	143	134	124
20	1,119	780	513	384	278	230	182	159	135	146	157	148	139
22	1,346	916	630	449	328	276	224	210	196	185	173	161	148
24	1,343	906	624	456	342	296	249	240	231	207	182	150	117
26	1,447	985	710	509	385	334	283	265	247	222	197	186	175
30	1,609	1,079	755	545	408	370	332	258	184	169	153	181	209
40	889	660	510	415	324	295	266	204	142	257	372	275	177
50	1,171	869	677	539	422	385	348	267	185	318	450	339	228
60	1,452	1,077	830	669	518	473	427	323	219	372	524	401	277
97	2,494	1,838	1,413	1,136	888	815	741	557	373	607	840	655	470

18 OBDG01 ECM Supporting Tables

Initial Supporting table - SCD_Jerk

Description: Used for P0300-P0308. Crankshaft jerk threshold. SCD mode uses smaller windows near TDC. Thresholds are a function of rpm and % engine Load.

Value Units: Change in Delta time per cylinder from last cylinder (usec)

X Unit: RPM

Y Units: percent load of max indicated torque (%)

y/x	700	800	900	1,000	1,100	1,150	1,200	1,250	1,300	1,350	1,400	1,450	1,500
3	284	206	146	104	77	71	65	62	58	49	40	39	38
6	284	206	146	104	77	71	65	62	58	49	40	39	38
8	284	206	146	104	77	71	65	62	58	49	40	39	38
10	379	268	192	144	108	94	80	75	70	64	58	54	49
12	480	334	243	182	141	121	100	95	90	85	80	75	70
14	703	476	343	259	196	175	154	140	125	111	97	92	86
16	881	596	423	319	240	212	183	160	137	119	100	95	89
18	987	674	476	378	287	237	188	183	177	153	128	120	112
20	1,073	747	530	393	293	262	230	207	183	160	137	129	121
22	1,184	808	588	423	318	278	237	222	207	175	142	139	135
24	1,311	893	620	468	338	294	249	233	217	196	176	158	140
26	1,441	966	679	510	384	324	263	246	229	210	190	176	162
30	1,475	1,023	740	555	427	376	324	230	135	165	195	200	204
40	2,283	1,568	1,126	838	641	546	451	423	396	378	360	289	218
50	2,742	1,900	1,357	1,012	773	660	547	490	433	424	414	354	294
60	3,290	2,262	1,630	1,216	932	792	652	585	519	513	506	427	348
97	5,297	3,655	2,639	1,965	1,507	1,287	1,068	922	777	813	850	702	553

18 OBDG01 ECM Supporting Tables

Initial Supporting table - SnapDecayAfterMisfire

Description: Used for P0300 - P0308, multiplier times the ddt_jerk value used used to detect misfire at that speed and load to see if size of disturbance has died down as expected of real misfire. Table lookup as a function of engine rpm and trans gear ratio.

Value Units: multiplier

X Unit: RPM

Y Units: gear ratio

y/x	500	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000
1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
2	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
2	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
3	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
5	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - TOSSRoughRoadThres

Description: Used for P0300-P0308. Only used if Rough Road source = TOSS: dispersion value on Transmission Output Speed Sensor above which rough road is indicated present

Value Units: change in rpm per sec (rpm)

X Unit: Engine Speed (RPM)

Y Units: Transmission Speed (RPM)

y/x	600	800	1,000	1,200	1,400	1,600	1,800	2,000	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000
100	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
200	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
300	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
400	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
500	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
600	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
700	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
800	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
900	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1,000	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1,100	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1,200	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1,300	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1,400	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - WaitToStart

Description: Used for P0300-P0308. Number of engine cycles to delay if diesel engine is cranked before wait to start lamp is extinguished. This lookup table determines the delay length by taking into account the coolant temperature.

Value Units: Number of Engine Cycles (integer)

X Unit: Engine Coolant (deg C)

y/x	-20	-10	0	10	20	30	40	50	60
1	0	0	0	0	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - WSSRoughRoadThres

Description: Used for P0300-P0308. Only used if Wheel speed from ABS is used. If difference between wheel speed readings is larger than this limit, rough road is present

Value Units: acceleration

X Unit: Vehicle Speed (KPH)

y/x	0	12	24	36	48	60	72	85	97	109	121	133	145	157	169	181	193
1	0.40002	0.40002	0.40002	0.40002	0.40002	0.40002	0.42505	0.44995	0.47498	0.50000	0.50354	0.50720	0.51074	0.51428	0.51782	0.52148	0.52502

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ZeroTorqueAFM

Description: Used for P0300-P0308. Zero torque engine load while in Active Fuel Management. %of Max Brake Torque along the Neutral rev line, as a function of RPM and Baro

Value Units: Percent of Maximum Brake torque (%)

X Unit: RPM

Y Units: Barometric Pressure (kPa)

ZeroTorqueAFM - Part 1

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,000
65	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
75	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
85	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
95	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
105	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80

ZeroTorqueAFM - Part 2

y/x	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000
65	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
75	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
85	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
95	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
105	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25

18 OBDG01 ECM Supporting Tables

Initial Supporting table - ZeroTorqueEngLoad

Description: Used for P0300-P0308. %of Max Brake Torque that represents Zero Brake torque along the Neutral rev line, as a function of RPM and Baro

Value Units: Percent of Maximum Brake torque (%)

X Unit: RPM

Y Units: Barometric Pressure (kPa)

ZeroTorqueEngLoad - Part 1

y/x	700	800	900	1,000	1,100	1,200	1,300	1,400	1,501	1,600	1,700	1,800	2,000
65	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
75	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
85	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
95	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80
105	4.50	4.30	4.10	3.90	3.70	3.50	4.10	4.70	4.75	4.80	4.80	4.80	4.80

ZeroTorqueEngLoad - Part 2

y/x	2,200	2,400	2,600	2,800	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000
65	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
75	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
85	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
95	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
105	4.70	4.50	4.40	4.25	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P057B KtBRKI_K_CmpltTestPointWeight

Description:

y/x	0.000	0.020	0.040	0.100	0.150	0.250	0.500	0.750	1.000
1	0	0	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P057B KtBRKI_K_FastTestPointWeight

Description:

y/x	0.000	0.020	0.040	0.100	0.150	0.250	0.500	0.750	1.000
1	0	0	1	1	1	1	1	1	1

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DFCO_CoolEnblHi_Temp

Description:			
y/x	-40	0	25
1	45.0	45.0	45.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DFCO_DelayAfterStart_Time

Description:					
y/x	-30	-10	20	60	90
1	20.0	15.0	10.0	8.0	5.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DFCO_DsblLo_Vehicle_Speed

Description:		
y/x	CeTCOR_e_NonEcoMode	CeTCOR_e_EcoMode
CeTGRR_e_TransGr1	0	0
CeTGRR_e_TransGr2	0	0
CeTGRR_e_TransGr3	0	0
CeTGRR_e_TransGr4	0	0
CeTGRR_e_TransGr5	0	0
CeTGRR_e_TransGr6	0	0
CeTGRR_e_TransGr9	0	0
CeTGRR_e_TransGr10	0	0
CeTGRR_e_TransGrNeut	0	0
CeTGRR_e_TransGrRvrs	0	0
CeTGRR_e_TransGrPark	0	0
CeTGRR_e_TransGr7	0	0
CeTGRR_e_TransGr8	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DFCO_EnblHi_Vehicle_Speed

Description:		
y/x	CeTCOR_e_NonEcoMode	CeTCOR_e_EcoMode
CeTGRR_e_TransGr1	0.0	0.0
CeTGRR_e_TransGr2	0.0	0.0
CeTGRR_e_TransGr3	0.0	0.0
CeTGRR_e_TransGr4	0.0	0.0
CeTGRR_e_TransGr5	0.0	0.0
CeTGRR_e_TransGr6	0.0	0.0
CeTGRR_e_TransGr9	0.0	0.0
CeTGRR_e_TransGr10	0.0	0.0
CeTGRR_e_TransGrNeut	0.0	0.0
CeTGRR_e_TransGrRvrs	0.0	0.0
CeTGRR_e_TransGrPark	0.0	0.0
CeTGRR_e_TransGr7	0.0	0.0
CeTGRR_e_TransGr8	0.0	0.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - DFCO_EngSpdEnbLOfst

Description:									
y/x	-1,750	-1,500	-1,250	-1,000	-700	-500	-300	-100	0
1	500	500	500	50	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CalculatedPerfMaxEc1

Description: Maximum desired camshaft position for Exhaust CAM - Bank1

Value Units: Maximum desired camshaft position (degCam)

X Unit: Engine Oil Temperature (degC)

[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17]

[-40 -28 -16 -4 8 20 32 44 56 68 80 92 104 116 128 140 152]

Y Units: Engine Speed (rpm)

[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17]

[400 800 1200 1600 2000 2400 2800 3200 3600 4000 4400 4800 5200 5600 6000 6400 6800]

y/x	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
1	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
2	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
3	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
4	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
5	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
6	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
7	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
8	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
9	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
10	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
11	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
12	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
13	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
14	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
15	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
16	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
17	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - CalculatedPerfMaxlc1

Description: Maximum desired camshaft position for Intake CAM - Bank1

Value Units: Maximum desired camshaft position (degCam)

X Unit: Engine Oil Temperature (degC)

[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17]

[-40 -28 -16 -4 8 20 32 44 56 68 80 92 104 116 128 140 152]

Y Units: Engine Speed (rpm)

[1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17]

[400 800 1200 1600 2000 2400 2800 3200 3600 4000 4400 4800 5200 5600 6000 6400 6800]

y/x	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
1	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
2	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
3	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
4	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
5	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
6	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
7	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
8	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
9	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
10	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
11	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
12	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
13	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
14	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
15	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
16	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0
17	25.5	25.5	27.5	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0521_LowMinOilPresFail - Two Stage Oil Pump

Description: Minimum expected oil pressure readings**Value Units:** Min oil pressure (kPa)**X Unit:** Engine speed (RPM)

y/x	1,000.0	1,500.0	2,000.0	2,500.0	3,000.0	3,500.0	4,000.0	4,500.0	5,000.0
1.0	50.0	64.0	75.0	75.0	75.0	80.0	90.0	104.0	115.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0521_P06DD_P06DE_OP_HiStatePressure

Description: Two Stage Oil Pump Oil Pressure in High State**Value Units:** Nominal high state oil pressure (kPa)**X Unit:** Engine oil temperature (deg C)

y/x	0.0	20.0	40.0	60.0	80.0	90.0	100.0	110.0	120.0
1,000.0	482.3	472.8	452.4	421.9	378.7	359.6	313.6	274.1	234.6
1,500.0	495.6	485.9	465.4	436.7	392.9	378.4	360.3	310.0	259.7
2,000.0	512.3	502.3	488.3	476.6	457.5	444.5	432.1	398.3	364.4
2,500.0	523.2	512.9	499.3	488.1	472.6	464.3	452.8	417.8	382.8
3,000.0	527.7	517.3	515.0	504.4	488.5	481.3	472.4	455.3	438.1
3,500.0	545.4	534.6	536.1	522.2	506.6	499.4	490.0	484.9	479.8
4,000.0	559.3	548.3	546.5	536.9	521.3	515.4	500.7	491.9	483.0
4,500.0	573.1	561.9	556.9	551.6	535.9	531.4	511.4	498.8	486.3
5,000.0	587.1	575.6	567.4	566.4	550.6	547.4	522.1	505.8	489.4

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06DD_P06DE_MaxEnableTorque_OP

Description: Two Stage Oil Pump Rationality Test Torque Max Enable Threshold

Value Units: Maximum engine torque (Nm)

X Unit: Engine speed (RPM)

y/x	0.0	750.0	1,500.0	2,250.0	3,000.0	3,750.0	4,500.0	5,250.0	6,000.0
1.0	0.0	0.0	115.0	131.0	139.0	148.0	150.0	0.0	0.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06DD_P06DE_MinEnableTorque_OP

Description: Two Stage Oil Pump Rationality Test Torque Min Enable Threshold**Value Units:** Min engine torque (Nm)**X Unit:** Engine speed (RPM)

y/x	0.0	750.0	1,500.0	2,250.0	3,000.0	3,750.0	4,500.0	5,250.0	6,000.0
1.0	0.0	0.0	13.0	13.0	13.0	13.0	13.0	0.0	0.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06DD_P06DE_MinOilPressThresh

Description: Intrusive diagnostic minimum pressure limit that is a function of Engine Speed and Oil Temperature

Value Units: Minimum engine oil pressure threshold (kPa)

X Unit: Engine oil temperature (deg C)

y/x	0	20	40	60	80	90	100	110	120
1,000	25	32	38	45	52	59	65	68	71
1,500	25	32	38	45	52	59	65	68	71
2,000	25	32	38	45	52	59	65	68	71
2,500	25	32	38	45	52	59	65	68	71
3,000	25	32	38	45	52	59	65	68	71
3,500	25	32	38	45	52	59	65	68	71
4,000	25	32	38	45	52	59	65	68	71
4,500	25	32	38	45	52	59	65	68	71
5,000	25	32	38	45	52	59	65	68	71

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06DD_P06DE_OP_LoStatePressure

Description: Two Stage Oil Pump Oil Pressure in Low State**Value Units:** Nominal low state oil pressure (kPa)**X Unit:** Engine oil temperature (deg C)

y/x	0	20	40	60	80	90	100	110	120
1,000	265	260	242	236	225	218	210	205	199
1,500	268	262	245	239	230	225	217	212	207
2,000	274	269	251	250	244	240	235	229	222
2,500	283	277	256	254	249	246	241	237	233
3,000	287	281	266	260	255	252	247	244	240
3,500	295	289	277	266	260	256	251	249	246
4,000	304	298	289	269	263	259	255	253	251
4,500	312	306	295	271	266	262	258	257	256
5,000	320	314	303	274	269	264	262	262	262

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06DD_P06DE_OP_StateChangeMin

Description: Minimum allowed pressure change on a Two Stage Oil Pump state change

Value Units: Min pressure change (kPa)

X Unit: Engine oil temperature (deg C)

y/x	0.0	20.0	40.0	60.0	80.0	90.0	100.0	110.0	120.0
1,000.0	108.3	101.3	94.3	87.9	65.0	40.6	28.8	16.2	4.1
1,500.0	112.0	104.5	96.9	91.7	74.1	47.4	41.2	23.1	5.6
2,000.0	115.3	110.1	104.9	101.5	88.3	62.3	60.7	40.6	23.7
2,500.0	127.9	117.8	107.7	104.1	91.8	65.1	64.1	47.6	35.8
3,000.0	123.6	118.1	112.5	110.1	96.1	68.9	67.9	54.8	47.9
3,500.0	125.4	122.6	119.8	116.3	100.6	72.8	71.5	63.4	63.7
4,000.0	151.1	140.3	129.4	118.6	104.1	75.6	74.1	65.0	64.2
4,500.0	176.7	157.8	139.0	120.8	107.7	78.4	76.6	66.5	64.8
5,000.0	183.0	165.0	146.0	123.1	109.0	81.3	79.3	68.0	65.3

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P156A_Off_Test_Delay

Description: Delay time for AC High Side Pressure Rationality

Value Units: Delay time before running off test (seconds)

X Unit: Ambient Temperature (Deg C) KnACCD_T_HSP_RatOffTestPresMax

y/x	-10.0	20.0	50.0	80.0	110.0
1.0	20.0	20.0	20.0	20.0	20.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P156A_Off_Test_Threshold

Description: AC High Side Pressure Sensor Rationality Off Test Threshold

Value Units: A/C high side pressure (kPa)

X Unit: Ambient Temperature (Deg C) KnACCD_T_HSP_RatOffTestPresMax

y/x	-10	20	50	80	110
1	1,000	2,000	2,700	3,300	3,800

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P156B_On_Test_Threshold

Description: AC High Side Pressure Sensor Rationality On Test Threshold**Value Units:** A/C high side pressure (kPa)**X Unit:** Ambient Temperature (Deg C) KnACCD_T_HSPRat_OnTestPresMin

y/x	-10	20	50	80	110
1	65.0	320.0	500.0	650.0	800.0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Down Stream Stk Temp Vrtn

Description: Minimum temperature movement required to pass the stuck diagnostic.

Value Units: Minimum temperature movement (degC)

X Unit: Downstream Temp sensor temp (degC)

y/x	-40	0	20	40	60	80	100	120
1	3	4	5	5	5	4	3	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - EGR Efficiency Flow Offset

Description: Efficiency offset correction map to be applied to the HPE cooler efficiency calculation.

Value Units: Cooler Efficiency offset (%)

X Unit: Valve Total Flow (g/s)

y/x	1	5	10	20	30
1	0	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - GearDownShftOffset

Description: Offset for Turbine Blade Protection - correction to turbo temperature for recent downshifts that can elevate temp for short period of time

Value Units: Offset for Turbine Blade Protection (degC)

X Unit: Turbo temp (degC)

Y Units: Engine Speed (rpm)

y/x	700	800	850	900	1,000
2,250	50	50	50	50	50
2,750	50	50	50	50	50
3,250	50	50	50	50	50
4,250	50	50	50	50	50
5,250	50	50	50	50	50

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Minimum Non-Purge Samples for Purge Vapor Fuel

Description: Number of Fuel Trim Monitor sample counts required to allow the Purge Vapor Fuel value to inhibit the Intrusive Rich test

Value Units: Sample Counts per loop rate of 100ms (divide by 10 to get seconds)

X Unit: Long Term Fuel Trim Cell I.D. (no units) (Only PurgeOff cells are used)

Minimum Non-Purge Samples for Purge Vapor Fuel - Part 1

y/x	CeFADR_e_Cell00_PurgOnAirMode 5	CeFADR_e_Cell01_PurgOnAirMode 4	CeFADR_e_Cell02_PurgOnAirMode 3	CeFADR_e_Cell03_PurgOnAirMode 2
1	65,535	65,535	65,535	65,535

Minimum Non-Purge Samples for Purge Vapor Fuel - Part 2

y/x	CeFADR_e_Cell04_PurgOnAirMode 1	CeFADR_e_Cell05_PurgOnAirMode 0	CeFADR_e_Cell06_PurgOnIdle	CeFADR_e_Cell07_PurgOnDecel
1	65,535	65,535	65,535	65,535

Minimum Non-Purge Samples for Purge Vapor Fuel - Part 3

y/x	CeFADR_e_Cell08_PurgOffAirMode 5	CeFADR_e_Cell09_PurgOffAirMode 4	CeFADR_e_Cell10_PurgOffAirMode 3	CeFADR_e_Cell11_PurgOffAirMode 2
1	65,535	65,535	65,535	65,535

Minimum Non-Purge Samples for Purge Vapor Fuel - Part 4

y/x	CeFADR_e_Cell12_PurgOffAirMode 1	CeFADR_e_Cell13_PurgOffAirMode 0	CeFADR_e_Cell14_PurgOffIdle	CeFADR_e_Cell15_PurgOffDecel
1	65,535	65,535	65,535	65,535

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage

Description: Identifies which Long Term Fuel Trim Cell I.D.s are used for diagnosis. Only cells identified as "CeFADD_e_NonSelectedCell" are not used for diagnosis.

P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage - Part 1

y/x	CeFADR_e_Cell00_PurgOnAirMode 5	CeFADR_e_Cell01_PurgOnAirMode 4	CeFADR_e_Cell02_PurgOnAirMode 3	CeFADR_e_Cell03_PurgOnAirMode 2
1	CeFADD_e_SelectedPurgeCell	CeFADD_e_SelectedPurgeCell	CeFADD_e_SelectedPurgeCell	CeFADD_e_SelectedPurgeCell

P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage - Part 2

y/x	CeFADR_e_Cell04_PurgOnAirMode 1	CeFADR_e_Cell05_PurgOnAirMode 0	CeFADR_e_Cell06_PurgOnIdle	CeFADR_e_Cell07_PurgOnDecel
1	CeFADD_e_SelectedPurgeCell	CeFADD_e_SelectedPurgeCell	CeFADD_e_SelectedPurgeCell	CeFADD_e_NonSelectedCell

P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage - Part 3

y/x	CeFADR_e_Cell08_PurgOffAirMode 5	CeFADR_e_Cell09_PurgOffAirMode 4	CeFADR_e_Cell10_PurgOffAirMode 3	CeFADR_e_Cell11_PurgOffAirMode 2
1	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_SelectedNonPurgeCell

P0171_P0172_P0174_P0175 Long-Term Fuel Trim Cell Usage - Part 4

y/x	CeFADR_e_Cell12_PurgOffAirMode 1	CeFADR_e_Cell13_PurgOffAirMode 0	CeFADR_e_Cell14_PurgOffIdle	CeFADR_e_Cell15_PurgOffDecel
1	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_SelectedNonPurgeCell	CeFADD_e_NonSelectedCell

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P219A Normalizer Bank1 Table

Description: Bank 1 Normalizer table used in the calculation of the Ratio for the current sample period.

Value Units: Unitless Scalar

X Unit: Engine Speed (RPM)

Y Units: Air Per Cylinder (APC) (mg/cylinder)

y/x	235	471	706	941	1,176	1,412	1,647	1,882	2,118	2,353	2,588	2,823	3,059	3,294	3,529	3,765	4,000
21	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
45	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
69	9,999.00	9,999.00	9,999.00	9,999.00	50.00	50.00	50.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
103	9,999.00	9,999.00	9,999.00	52.50	51.25	50.00	43.50	37.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
137	9,999.00	9,999.00	9,999.00	52.50	52.50	47.75	37.00	37.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
161	9,999.00	9,999.00	9,999.00	62.00	62.00	74.00	48.25	41.75	47.50	41.50	47.00	43.00	30.50	25.50	25.50	9,999.00	9,999.00
185	9,999.00	9,999.00	9,999.00	98.50	98.50	53.50	74.25	35.25	47.50	41.50	47.00	43.00	30.50	25.50	25.50	9,999.00	9,999.00
209	9,999.00	9,999.00	9,999.00	95.00	95.00	109.50	99.50	86.00	77.00	67.25	75.75	55.00	52.00	26.00	26.00	9,999.00	9,999.00
233	9,999.00	9,999.00	9,999.00	90.50	90.50	99.00	113.00	121.50	117.25	103.50	101.50	77.00	85.50	50.75	50.75	9,999.00	9,999.00
257	9,999.00	9,999.00	9,999.00	76.75	76.75	90.25	131.75	129.50	131.00	117.00	118.00	118.50	100.50	100.25	100.25	9,999.00	9,999.00
281	9,999.00	9,999.00	9,999.00	88.50	88.50	91.25	128.00	121.00	103.50	108.75	79.00	115.25	122.25	91.50	91.50	9,999.00	9,999.00
305	9,999.00	9,999.00	9,999.00	58.25	58.25	96.25	124.00	102.50	100.25	88.75	60.50	78.75	118.50	93.50	93.50	9,999.00	9,999.00
329	9,999.00	9,999.00	9,999.00	126.00	126.00	111.00	69.75	108.00	106.25	93.50	105.00	102.25	112.00	101.25	101.25	9,999.00	9,999.00
353	9,999.00	9,999.00	9,999.00	126.00	126.00	111.00	92.50	115.25	83.50	73.25	92.75	115.75	85.50	87.25	87.25	9,999.00	9,999.00
377	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	115.25	115.25	83.50	73.25	92.75	109.50	103.00	84.25	84.25	9,999.00	9,999.00
396	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	103.00	103.00	84.25	84.25	9,999.00	9,999.00
415	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P219A Quality Factor Bank1 Table

Description: Bank 1 lookup table of Quality Factors used in the calculation of the Ratio for the current sample period

Value Units: Unitless Scalar

X Unit: Engine Speed (RPM)

Y Units: Air Per Cylinder (APC) (mg/cylinder)

y/x	235	471	706	941	1,176	1,412	1,647	1,882	2,118	2,353	2,588	2,823	3,059	3,294	3,529	3,765	4,000
21	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
45	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
69	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
103	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
137	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
161	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
185	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
209	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
233	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
257	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
281	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
305	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00	0.95	1.00	1.00	1.00	0.00	0.00	0.00
329	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
353	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00
377	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	0.00	0.00	0.00
396	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
415	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P219A Variance Threshold Bank1 Table

Description: Bank 1 lookup table of Variance metric used to calculate the Ratio for the current sample period

Value Units: Unitless ratio

X Unit: Engine Speed (RPM)

Y Units: Air Per Cylinder (APC) (mg/cylinder)

y/x	235	471	706	941	1,176	1,412	1,647	1,882	2,118	2,353	2,588	2,823	3,059	3,294	3,529	3,765	4,000
21	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
45	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
69	9,999.00	9,999.00	9,999.00	9,999.00	34.00	34.00	34.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
103	9,999.00	9,999.00	9,999.00	52.75	43.25	34.00	43.00	52.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
137	9,999.00	9,999.00	9,999.00	52.75	52.75	58.50	52.00	52.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00
161	9,999.00	9,999.00	9,999.00	108.00	108.00	66.75	43.50	45.50	42.50	31.25	38.50	24.50	31.75	32.50	32.50	9,999.00	9,999.00
185	9,999.00	9,999.00	9,999.00	80.75	80.75	79.25	46.00	47.75	42.50	31.25	38.50	24.50	31.75	32.50	32.50	9,999.00	9,999.00
209	9,999.00	9,999.00	9,999.00	91.00	91.00	72.25	50.00	41.50	41.25	26.75	33.75	26.50	25.25	44.25	44.25	9,999.00	9,999.00
233	9,999.00	9,999.00	9,999.00	102.00	102.00	73.75	59.75	48.00	47.00	30.75	43.00	38.00	34.00	55.50	55.50	9,999.00	9,999.00
257	9,999.00	9,999.00	9,999.00	123.00	123.00	82.75	67.50	55.50	57.00	50.75	47.25	46.75	38.50	54.25	54.25	9,999.00	9,999.00
281	9,999.00	9,999.00	9,999.00	117.75	117.75	78.50	75.50	50.50	58.50	53.75	84.75	46.25	37.50	58.50	58.50	9,999.00	9,999.00
305	9,999.00	9,999.00	9,999.00	181.00	181.00	118.75	90.50	75.25	67.25	62.25	119.00	80.00	43.50	57.75	57.75	9,999.00	9,999.00
329	9,999.00	9,999.00	9,999.00	108.50	108.50	125.00	146.00	87.75	72.75	72.75	70.50	58.00	58.00	61.75	61.75	9,999.00	9,999.00
353	9,999.00	9,999.00	9,999.00	108.50	108.50	125.00	118.50	91.00	95.50	90.00	69.00	52.00	67.00	66.00	66.00	9,999.00	9,999.00
377	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	91.00	91.00	95.50	90.00	69.00	54.50	57.00	54.00	54.00	9,999.00	9,999.00
396	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	57.00	57.00	54.00	54.00	9,999.00	9,999.00
415	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00	9,999.00

18 OBDG01 ECM Supporting Tables

Initial Supporting table - Piston Protection Airflow

Description: Mass of air per cylinder threshold above which piston protection will be enabled if it is currently disabled

Value Units: Air Per Cylinder (mg/cylinder)

X Unit: Engine Speed (rpm)

y/x	1,600	2,400	3,200	4,000	4,800	5,600	6,400	7,200	8,000
1	560	560	560	400	400	400	400	400	400

18 OBDG01 ECM Supporting Tables

Initial Supporting table - UP Stream Stk Temp Vrtn

Description: Minimum temperature movement to pass the stuck diagnostic.

Value Units: Minimum temperature movement (degC)

X Unit: Upstream Temp sensor temp (degC)

y/x	-40	0	20	40	60	80	100	120
1	3	4	5	5	5	4	3	2

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_Thresh_AFM

Description: Fail threshold for the Knock Performance Abnormal Noise Diagnostic when engine IS in AFM mode

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0606_Last Seed Timeout f(Loop Time)

Description: The max time for the Last Seed Timeout as a function of operating loop time sequence.

Value Units: Max Time for Last Seed Timeout (ms)

X Unit: Operating Loop Sequence (enum)

P0606_Last Seed Timeout f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	200.000	200.000	200.000	200.000	200.000	200.000	200.000

P0606_Last Seed Timeout f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	200.000	200.000	500.000	8,191.875	8,191.875	8,191.875	

Initial Supporting table - P0606_Program Sequence Watch Enable f(Core, Loop Time)

Description: The enabling flags for the program sequence watch as a function of processor core and operating loop time sequence.

Value Units: PSW enable flag (boolean)

X Unit: Processor Core (enum)

Y Units: Operating Loop Time Sequence (enum)

y/x	CeTSKR_e_CPU	CeTSKR_e_CPU2	CeTSKR_e_CPU3	CeTSKR_e_CPU4
CePISR_e_5msSeq	0	0	0	0
CePISR_e_6p25msSeq	1	1	0	0
CePISR_e_10msSeq	0	0	0	0
CePISR_e_12p5msSeq	1	1	0	0
CePISR_e_20msSeq	0	0	0	0
CePISR_e_25msSeq	1	1	0	0
CePISR_e_40msSeq	0	0	0	0
CePISR_e_50msSeq	0	0	0	0
CePISR_e_80msSeq	0	0	0	0
CePISR_e_100msSeq	0	0	0	0
CePISR_e_EventA_Seq	1	0	0	0
CePISR_e_EventB_Seq	0	0	0	0
CePISR_e_EventC_Seq	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0606_PSW Sequence Fail f(Loop Time)

Description: Fail threshold for PSW per operating loop.

Value Units: Fail threshold for PSW (count)

X Unit: Operating Loop (enum)

P0606_PSW Sequence Fail f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	5	3	5	3	5	3	5

P0606_PSW Sequence Fail f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	5	5	5	3	5	5	

Initial Supporting table - P0606_PSW Sequence Sample f(Loop Time)

Description: Sample threshold for PSW per operating loop.**Value Units:** Sample threshold for PSW (count)**X Unit:** Operating Loop (enum)

P0606_PSW Sequence Sample f(Loop Time) - Part 1

y/x	CePISR_e_5msSeq	CePISR_e_6p25msSeq	CePISR_e_10msSeq	CePISR_e_12p5msSeq	CePISR_e_20msSeq	CePISR_e_25msSeq	CePISR_e_40msSeq
1	4	4	4	4	4	4	4

P0606_PSW Sequence Sample f(Loop Time) - Part 2

y/x	CePISR_e_50msSeq	CePISR_e_80msSeq	CePISR_e_100msSeq	CePISR_e_EventA_Seq	CePISR_e_EventB_Seq	CePISR_e_EventC_Seq	
1	4	4	4	4	4	4	

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P1682_PT Relay Pull-in Run/Crank Voltage f(IAT)

Description: The Run/Crank voltages required to pull in the PT relay as a function of induction air temperature.

Value Units: Run/Crank Voltages required to pull in PT Relay (V)

X Unit: Induction Air Temperature (deg C)

y/x	23.0	85.0	95.0	105.0	125.0
1	7.000	8.699	9.000	9.199	10.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P16F3_Delta MAP Threshold f(Desired Engine Torque)

Description: Engine Sync based and Time based delta pressure threshold above which Torque Security error is reported.

Value Units: Torque Security Threshold for Engine Sync and Time Based Delta Pressure (kPa)

X Unit: Desired Engine Torque (Nm)

y/x	0.00	50.00	100.00	150.00	200.00	300.00
1.00	34.92	34.92	34.92	34.92	34.92	34.92

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P16F3_Speed Control External Load f(Oil Temp, RPM)

Description: Specifies the external load table for SPDR torque security as a function of engine oil temperature and engine RPM.

Value Units: External Load Table for SPDR (Nm)

X Unit: Engine Oil Temperature (deg C)

Y Units: Engine Speed (RPM)

y/x	-40.00	-20.00	-10.00	0.00	50.00	90.00
700.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00
900.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00	4,096.00
1,100.00	70.00	70.00	70.00	70.00	60.00	50.00
1,400.00	45.00	42.00	38.00	35.00	35.00	35.00
1,600.00	32.89	29.44	27.18	25.55	18.09	15.26
1,800.00	34.82	31.10	28.67	26.92	19.35	16.51
2,000.00	37.64	32.56	30.68	29.85	21.71	18.36
2,200.00	40.80	35.20	33.13	32.22	23.24	19.84
2,500.00	43.58	39.76	37.58	36.01	26.21	23.06
2,700.00	42.72	38.90	36.72	35.15	25.34	22.19
3,000.00	40.65	36.83	34.65	33.08	23.27	20.13
3,300.00	36.87	33.05	30.87	29.30	19.49	16.35
3,500.00	13.41	9.58	7.41	5.84	-3.97	-7.12
3,700.00	7.50	3.67	1.50	-0.08	-9.88	-13.03
4,000.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28
4,500.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28
5,000.00	4.25	0.43	-1.75	-3.32	-13.13	-16.28

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0324_PerCyl_ExcessiveKnock_Threshold

Description: Fail threshold for the Knock Performance per-cylinder Excessive Knock Diagnostic

Value Units: Filtered Knock Intensity. Unit-less term scaled from 0.0 (no knock) to 5.0 (maximum/large knock)

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	2.25	2.25	2.00	1.63	1.63	1.63	1.63	1.63	1.63	1.56	1.63	1.63	1.63	1.63	1.63	1.63	1.63

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMax (20 kHz)

Description: Knock Open Circuit Diagnostic Maximum Threshold when using the 20 kHz method (see "OpenMethod" description)

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM).

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	4,650	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.0000	2.0156	2.0000	2.0020	1.9648	1.9609	1.9648	1.9648	1.9629	1.9063	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMax (Normal Noise)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the Normal Noise method (see "OpenMethod" description): When using the Normal Noise method (see "OpenMethod" description).

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.4668	0.4102	0.3672	0.3359	0.3145	0.2988	0.2930	0.2891	0.2891	0.2910	0.2930	0.2910	0.2891	0.2793	0.2656	0.2402	0.2070

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMin (20 kHz)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the 20 kHz method (see "OpenMethod" description)

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	4,650	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.0000	0.6133	0.6152	0.6074	0.5898	0.5879	0.5898	0.5918	0.5938	0.5781	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenCktThrshMin (Normal Noise)

Description: Knock Open Circuit Diagnostic Minimum Threshold when using the Normal Noise method (see "OpenMethod" description): When using the Normal Noise method (see "OpenMethod" description).

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.2422	0.1895	0.1523	0.1289	0.1191	0.1211	0.1387	0.1680	0.2090	0.2617	0.3281	0.4043	0.4941	0.5918	0.7012	0.8223	0.9531

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0325_P0330_OpenMethod_2

Description: Defines which Knock Open Circuit Diagnostic method to use.

Value Units: Identifies one of two diagnostic methods (either 20 kHz or Normal Noise) used (as a function of engine speed) for Open Circuit detection

X Unit: Engine Speed Index, 500 to 8500 (RPM) by 500 rpm increments (Index 0, 1, 2.... 16 = 500, 1000, 1500.... 8500 RPM)

Y Units: N/A

P0325_P0330_OpenMethod_2 - Part 1

y/x	0	1	2	3	4
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz

P0325_P0330_OpenMethod_2 - Part 2

y/x	5	6	7	8	9
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz

P0325_P0330_OpenMethod_2 - Part 3

y/x	10	11	12	13	14
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz

P0325_P0330_OpenMethod_2 - Part 4

y/x	15	16			
1	CeKNKD_e_Open_20KHz	CeKNKD_e_Open_20KHz			

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_CylsEnabled

Description: Specifies which cylinders will be used for the Abnormal Noise portion of the performance diagnostics (1 = cylinder used, 0 = cylinder not used)

Value Units: Boolean that indicates which engine cylinders are being used for the per-sensor Knock Performance diagnostic (0 = not used, 1 = used)

X Unit: Cylinder number in firing order (i.e. Cyl 0 = first cylinder in firing order, Cyl 1 = second cylinder in firing order....)

Y Units: N/A

y/x	0	1	2	3	4	5	6	7
1	1	1	1	1	0	0	0	0

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P0326_P0331_AbnormalNoise_Threshold

Description: Fail threshold for the Knock Performance Abnormal Noise Diagnostic when engine is NOT in AFM mode

Value Units: Filtered background engine noise. Unit-less term from the Knock Detection Fast Fourier Transform (FFT) for a selected frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	5,000	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.302	0.302	0.302	0.302	0.077	0.083	0.067	0.058	0.063	0.063	0.063	0.063	0.063	0.063	0.063	0.063	0.063

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06B6_P06B7_OpenTestCktThrshMax

Description: Knock Open Circuit Minimum Threshold for Internal Circuit Diagnostic. Used only when the 20 kHz method is being used (see "OpenMethod" description). The Open Test Circuit ensures that the internal circuit used to generate the 20 kHz signal for the Open Circuit diags (P0325, P0330) is within range.

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM)

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	4,650	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.000	0.043	0.043	0.047	0.047	0.049	0.051	0.053	0.059	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

18 OBDG01 ECM Supporting Tables

Initial Supporting table - P06B6_P06B7_OpenTestCktThrshMin

Description: Knock Open Circuit Minimum Threshold for Internal Circuit Diagnostic. Used only when the 20 kHz method is being used (see "OpenMethod" description). The Open Test Circuit ensures that the internal circuit used to generate the 20 kHz signal for the Open Circuit diags (P0325, P0330) is within range.

Value Units: Unit-less, filtered term from the Knock Detection Fast Fourier Transform (FFT) for the 20 kHz frequency range.

X Unit: Engine Speed (RPM).

Y Units: N/A

y/x	500	1,000	1,500	2,000	2,500	3,000	3,500	4,000	4,500	4,650	5,500	6,000	6,500	7,000	7,500	8,000	8,500
1	0.000	0.020	0.020	0.021	0.021	0.023	0.023	0.025	0.029	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

18 OBDG01 Fault Bundle Definitions

Bundle Name: 5VoltReferenceA_FA
P0641
Bundle Name: 5VoltReferenceB_FA
P0651
Bundle Name: 5VoltReferenceMAP_OOR_Flt
P0697
Bundle Name: A/F Imbalance Bank1
P219A
Bundle Name: AAP_SnsrCktFA
Naturally aspirated: P2228, P2229. Turbocharged: P0237, P0238
Bundle Name: AAP_SnsrCktFP
Naturally aspirated: P2228, P2229. Turbocharged: P0237, P0238
Bundle Name: AAP_SnsrFA
Naturally Aspirated: P2227, P2228, P2229, P2230. Turbocharged: P0237, P0238.
Bundle Name: AccCktLo_FA
P2537
Bundle Name: AcceleratorPedalFailure
P2122, P2123, P2127, P2128, P2138, P0697, P06A3
Bundle Name: ACCMLostComm
U016B
Bundle Name: ACFailedOnSD
See ACCM Document
Bundle Name: ACHighSidePressSnsrCktFA
P0532, P0533
Bundle Name: ACThrmIRefrigSpdVld
See ACCM Document
Bundle Name: AfterThrottlePressureFA
Naturally Aspirated or Turbocharged: P0106, P0107, P0108. Supercharged: P012B, P012C, P012D.
Bundle Name: AIR System FA
P0411, P2440, P2444
Bundle Name: AmbientAirDefault
Baro Sensor Present: P2227, P2228, P2229, P2230. No Baro Sensor Present: P0101, P0102, P0103, P0106, P0107, P0108, P0111, P0112, P0113, P0114, P0121, P0122, P0123, P012B, P012C, P012D, P0222, P0223, P1221
Bundle Name: AmbPresDfltStatus
Baro Sensor Present: P2227, P2228, P2229, P2230. No Baro Sensor Present: P0101, P0102, P0103, P0106, P0107, P0108, P0111, P0112, P0113, P0114, P0121, P0122, P0123, P012B, P012C, P012D, P0222, P0223, P1221
Bundle Name: AmbPresSnsrCktFA

18 OBDG01 Fault Bundle Definitions

P2228, P2229
Bundle Name: AnyCamPhaser_FA
P0010, P0011, P0013, P0014, P0020, P0021, P0023, P0024, P2088, P2089, P2090, P2091, P2092, P2093, P2094, P2095, P05CC, P05CD, P05CE, P05CF,
Bundle Name: AnyCamPhaser_TFTKO
P0010, P0011, P0013, P0014, P0020, P0021, P0023, P0024, P2088, P2089, P2090, P2091, P2092, P2093, P2094, P2095, P05CC, P05CD, P05CE, P05CF,
Bundle Name: CamLctnExhFA
P0017, P0019, P0365, P0366, P0390, P0391
Bundle Name: CamLctnIntFA
P0016, P0018, P0340, P0341, P0345, P0346
Bundle Name: CamSensorAnyLctnTFTKO
P0016, P0017, P0018, P0019, P0340, P0341, P0345, P0346, P0365, P0366, P0390, P0391
Bundle Name: CamSensorAnyLocationFA
P0016, P0017, P0018, P0019, P0340, P0341, P0345, P0346, P0365, P0366, P0390, P0391
Bundle Name: CamSnsrExhTFTKO
P0017, P0019, P0365, P0366, P0390, P0391
Bundle Name: CamSnsrIntTFTKO
P0016, P0018, P0340, P0341, P0345, P0346
Bundle Name: Catalyst Warmup Enabled
N/A
<p>Catalyst Warmup Enabled - Other Definitions: To enable the Cold Start Emission Reduction Strategy:</p> <p>Catalyst Temperature < 350.00 degC AND Engine Coolant > -12.00 degC AND Engine Coolant <= 66.00 degC AND Barometric Pressure>= 76.00 KPa AND</p> <p>DTC's Not Set:</p> <p>ECT_Sensor_FA MAP_SensorFA</p> <p>The Cold Start Emission Reduction Strategy will remain active until:</p> <p>Engine Run Time > P050D_P1400_CatalystLightOffExtendedEngineRunTimeExit This Extended Engine run time exit is a function of percent ethanol and Catmons NormRatioEWMA. Refer to "Supporting Tables" for details.</p>

18 OBDG01 Fault Bundle Definitions

OR

Catalyst Temperature >= 900.00 degC

AND

Engine Run Time >= 30.00 seconds

OR

Barometric Pressure < 76.00 KPa

Bundle Name: ClutchPstnSnsr_FA

P08A8, P0806(pre2018), P08A9, P0807(Pre2018), P08AA, P0808(Pre2018)

Bundle Name: CommBusAOff_VICM_FA

U0073

Bundle Name: CommBusBOff_VICM_FA

U0074

Bundle Name: CrankSensor_FA

P0335, P0336

Bundle Name: CrankSensor_TFTKO

P0335, P0336

Bundle Name: ECT_Sensor_Ckt_FA

P0117, P0118

Bundle Name: ECT_Sensor_Ckt_FP

P0117, P0118

Bundle Name: ECT_Sensor_Ckt_TFTKO

P0117, P0118

Bundle Name: ECT_Sensor_FA

P0116, P0117, P0118, P0119, P0128, P111E

Bundle Name: ECT_Sensor_Perf_FA

P0116, P111E

Bundle Name: EGRValve_FP

P0405, P0406, P042E

Bundle Name: EGRValveCircuit_FA

P0403, P0404, P0405, P0406, P0489, P0490, P042E, P1426, P1437

Bundle Name: EGRValvePerformance_FA

P0404, P042E, P0401

Bundle Name: ELCP_PumpCircuit_FA

P2400, P2401, P2402

Bundle Name: ELCP_SwitchCircuit_FA

P2418, P2419, P2420

18 OBDG01 Fault Bundle Definitions

Bundle Name: ELCPCircuit_FA
P24BA, P24BB
Bundle Name: EngineMetalOvertempActive
P1258
Bundle Name: EngineMisfireDetected_FA
P0300, P0301, P0302, P0303, P0304, P0305, P0306, P0307, P0308
Bundle Name: EngineModeNotRunTimer_FA
P2610
Bundle Name: EngineModeNotRunTimerError
P2610
Bundle Name: EnginePowerLimited
P0068, P00C8, P00C9, P00CA, P0090, P0091, P0092, P0122, P0123, P0191, P0192, P0193, P0222, P0223, P0601, P0604, P0606, P0697, P06A3, P06DB, P06D2, P06DE, P0A1D, P1104, P127A, P127C, P127D, P135A, P135B, P15F2, P160D, P160E, P1682, P16A0, P16A1, P16A2, P16A7, P16F3, P2100, P2101, P2102, P2103, P2122, P2123, P2127, P2128, P2135, P2138, P215B, P2176, P228C, P228D, U0073, U0074, U0293, U1817
Bundle Name: EngineTorqueEstInaccurate
EngineMisfireDetected_FA, FuelInjectorCircuit_FA, FuelInjectorCircuit_TFTKO, FuelTrimSystemB1_FA, FuelTrimSystemB2_FA, MAF_SensorTFTKO, MAP_SensorTFTKO, EGRValvePerformance_FA, P16F3
EngineTorqueEstInaccurate - Other Definitions: P16F3 with GetXOYR_b_SecurityFlt (CeXOYR_e_MAPR_AfterThrotPresFlt, CeXOYR_e_MAPR_EngineVacuumFlt, CeXOYR_e_MAPR_IntkMnfdPresFlt, CeXOYR_e_MAFR_Ahead1vs2FinalFlt)
Bundle Name: EngOilPressureSensorCktFA
P0522, P0523
Bundle Name: EngOilPressureSensorFA
P0521, P0522, P0523
Bundle Name: EngOilTempFA
EngOilTempSensorCircuitFA, EngOilModeledTempValid, P16F3
EngOilTempFA - Other Definitions: P16F3 with GetXOYR_b_SecurityFlt(CeXOYR_e_EOTR_SecurityFlt)
Bundle Name: Ethanol Composition Sensor FA
P0178, P0179, P2269
Bundle Name: EvapEmissionSystem_FA
P0455, P0446
Bundle Name: EvapExcessPurgePsbl_FA
ELCP sealed/vented fuel system, P0442, P0455, P0458 OR Conventional fuel system, P0442, P0455, P0458, P0496
Bundle Name: EvapFlowDuringNonPurge_FA
P0496
Bundle Name: EvapPurgeSolenoidCircuit_FA
P0443, P0458, P0459
Bundle Name: EvapSmallLeak_FA

18 OBDG01 Fault Bundle Definitions

P0442
Bundle Name: EvapVentSolenoidCircuit_FA
P0449, P0498, P0499
Bundle Name: FHPR_b_FRP_SnsrCkt_FA
P0192, P0193, P127C, P127D, P16E4, P16E5, P128A, P128B, 128F
Bundle Name: FHPR_b_FRP_SnsrCkt_TFTKO
P0192, P0193, , P127C, P127D, P16E4, P16E5, P128A, P128B, 128F
Bundle Name: FHPR_b_PumpCkt_FA
P0090, P0091, P0092, P00C9, P00CA, P10E8
Bundle Name: FHPR_b_PumpCkt_TFTKO
P0090, P0091, P0092, P00C9, P00CA, P10E8
Bundle Name: FTP_SensorCircuit_FA
P0452, P0453
Bundle Name: FuelInjectorCircuit_FA
PFI: P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0261, P0264, P0267, P0270, P0273, P0276, P0279, P0282, P0262, P0265, P0268, P0271, P0274, P0277, P0280, P0283 SIDI: P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0261, P0264, P0267, P0270, P0273, P0276, P0279, P0282, P0262, P0265, P0268, P0271, P0274, P0277, P0280, P0283, P2147, P2150, P2153, P2156, P216B, P216E, P217B, P217E, P2148, P2151, P2154, P2157, P216C, P216F, P217C, P217F, P1248, P1249, P124A, P124B, P124C, P124D, P124E, P124F
Bundle Name: FuelInjectorCircuit_TFTKO
PFI: P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0261, P0264, P0267, P0270, P0273, P0276, P0279, P0282, P0262, P0265, P0268, P0271, P0274, P0277, P0280, P0283 SIDI: P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0261, P0264, P0267, P0270, P0273, P0276, P0279, P0282, P0262, P0265, P0268, P0271, P0274, P0277, P0280, P0283, P2147, P2150, P2153, P2156, P216B, P216E, P217B, P217E, P2148, P2151, P2154, P2157, P216C, P216F, P217C, P217F, P1248, P1249, P124A, P124B, P124C, P124D, P124E, P124F
Bundle Name: FuelLevelDataFault
P0461, P0462, P0463, P2066, P2067, P2068
FuelLevelDataFault - Other Definitions:
AccCktLo_FA
Bundle Name: FuelPumpRlyCktFA
P0627, P0628, P0629
Bundle Name: FuelTankPressureSnsrCkt_FA
P0452, P0453
Bundle Name: FuelTrimSystemB1_FA
P0171, P0172, P11E9, P11EA, P2178
Bundle Name: FuelTrimSystemB2_FA
P0174, P0175, P11EB, P11EC, P2179
Bundle Name: FULR_b_FuellnjCkt_FP
SIDI: P0201, P0202, P0203, P0204, P0205, P0206, P0207, P0208, P0261, P0264, P0267, P0270, P0273, P0276, P0279, P0282, P0262, P0265, P0268, P0271, P0274, P0277, P0280, P0283, P2147, P2150, P2153, P2156, P216B, P216E, P217B, P217E, P2148, P2151, P2154, P2157, P216C, P216F, P217C, P217F, P1248, P1249, P124A, P124B, P124C, P124D, P124E, P124F
Bundle Name: HumTempSnsrCktFA

18 OBDG01 Fault Bundle Definitions

P0097, P0098
Bundle Name: IAC_SystemRPM_FA
P0506, P0507
Bundle Name: IAT_SensorCircuitFA
P0112, P0113
Bundle Name: IAT_SensorCircuitFP
P0112, P0113
Bundle Name: IAT_SensorFA
P0111, P0112, P0113, P0114
Bundle Name: IAT_SensorTFTKO
P0111, P0112, P0113, P0114
Bundle Name: IgnitionOutputDriver_FA
P0351, P0352, P0353, P0354, P0355, P0356, P0357, P0358, P2300, P2301, P2303, P2304, P2306, P2307, P2309, P2310, P2312, P2313, P2315, P2316, P2318, P2319, P2321, P2322
Bundle Name: LostCommBCM_FA
U0140
Bundle Name: LostCommBusB_VICM_FA
U182D
Bundle Name: MAF_SensorCircuitFA
P0102, P0103, P010C, P010D
Bundle Name: MAF_SensorFA
P0101, P0102, P0103, P010B, P010C, P010D
Bundle Name: MAF_SensorTFTKO
P0101, P0102, P0103, P010B, P010C, P010D
Bundle Name: MAP_EngineVacuumStatus
P0106, P0107, P0108 Fault Active OR P0107, P0108 Fault Pending
Bundle Name: MAP_SensorCircuitFA
P0107, P0108
Bundle Name: MAP_SensorCircuitFP
P0107, P0108
Bundle Name: MAP_SensorFA
P0106, P0107, P0108
Bundle Name: MAP_SensorTFTKO
P0106, P0107, P0108
Bundle Name: MnfdTempSensorCktFA
Turbocharged or Supercharged, with Humidity sensor: P00EA, P00EB. Turbocharged or Supercharged, without Humidity sensor: P0097, P0098. Naturally Aspirated: P0112, P0113.
Bundle Name: MnfdTempSensorCktFP
Turbocharged or Supercharged, with Humidity sensor: P00EA, P00EB. Turbocharged or Supercharged, without Humidity sensor: P0097, P0098. Naturally Aspirated: P0112, P0113.

18 OBDG01 Fault Bundle Definitions

Bundle Name: ModuleOffTime_FA
P262B
Bundle Name: O2S_Bank_1_TFTKO
P0131, P0132, P0134, P2195, P2196, P2A00 (With WRAF sensor add: P0030, P0031, P0032, P064D, P0135, P2237, P223C, P223E, P2243, P2251, P2626)
Bundle Name: O2S_Bank_2_TFTKO
P0151, P0152, P0154, P2197, P2198, P2A03 (With WRAF sensor add: P0050, P0051, P0052, P064E, P0155, P223D, P223F, P2240, P2247, P2254, P2629)
Bundle Name: O2S_Bank_1_Sensor_1_FA
P2A00, P0131, P0132, P0133, P0134, P0135, P0053, P1133, P015A, P015B, P0030
Bundle Name: O2S_Bank_1_Sensor_2_FA
P013A, P013B, P013E, P013F, P2270, P2271, P0137, P0138, P0140, P0141, P0054, P0036
Bundle Name: O2S_Bank_2_Sensor_1_FA
P2A03, P0151, P0152, P0153, P0154, P0155, P0059, P1153, P015C, P015D, P0050
Bundle Name: O2S_Bank_2_Sensor_2_FA
P013C, P013D, P014A, P014B, P2272, P2273, P0157, P0158, P0160, P0161, P0060, P0056
Bundle Name: OAT_EstAmbTemp_FA
ELCP sealed/vented fuel system, P0071, P0072, P0073, P0502, P0503, P0722, P0723 OR Conventional fuel system, P0071, P0072, P0073, P0074, P2610
Bundle Name: OAT_PtEstFiltFA
ECM OAT: P0071, P0072, P0073, P0074, EngModeNotRunTmErr, VehicleSpeedSensor_FA, IAT_SensorFA, ECT_Sensor_DefaultDetected, MAF_SensorFA. VIMC OAT: P0072, P0073, EngModeNotRunTmErr, VehicleSpeedSensor_FA, ECT_Sensor_DefaultDetected. IAT-Based OAT: VehicleSpeedSensor_FA, IAT_SensorFA, MAF_SensorFA. All other cases: EngModeNotRunTmErr, VehicleSpeedSensor_FA, IAT_SensorFA, ECT_Sensor_DefaultDetected.
Bundle Name: OAT_PtEstRawFA
ECM OAT: P0071, P0072, P0073, P0074. VIMC OAT: P0071, P0072, P0073, EngModeNotRunTmErr, VehicleSpeedSensor_FA, ECT_Sensor_DefaultDetected. IAT-Based OAT: IAT_SensorFA. All other cases: IAT_SensorFA, ECT_Sensor_DefaultDetected.
Bundle Name: OilPmpTFTKO
P06DA, P06DB, P06DC, P06DD, P06DE
OilPmpTFTKO - Other Definitions:
TFTKO only for Output Driver and rationality
Bundle Name: PO2S_Bank_1_Snsr_2_FA
P0137, P0138, P0140, P0036, P0054, P0141, P2270, P2271
Bundle Name: PO2S_Bank_2_Snsr_2_FA
P0157, P0158, P0160, P0056, P0060, P0161, P2272, P2273
Bundle Name: PowertrainRelayFault
P1682, P16A7, P16BC
Bundle Name: PowertrainRelayStateOn_FA
P0685, P0686, P0687
Bundle Name: TC_BoostPresSnsrFA
P0236, P0237, P0238
Bundle Name: THMR_AHV_FA
P2681, P26A3, P26A6, P26A7, P26A9

18 OBDG01 Fault Bundle Definitions

THMR_AHV_FA - Other Definitions:
Bundle Name: THMR_AWP_AuxPumpFA
B269A, B269C, B269D
Bundle Name: THMR_ECT_Sensor_Ckt_FA
P0116, P0117, P0118, P0119, P111E
Bundle Name: THMR_RCT_Sensor_Ckt_FA
P00B3, P00B4
Bundle Name: THMR_SWP_Control_FA
P261A, P261D, P261C
Bundle Name: THMR_SWP_FlowStuckOn_FA
P261A, P261D, P261E
Bundle Name: THMR_SWP_NoFlow_FA
P261B, P261C
Bundle Name: TPS_FA
P0122, P0123, P0222, P0223, P16A0, P16A1, P16A2, P2135
Bundle Name: TPS_Performance_FA
P0068, P0121, P1104, P2100, P2101, P2102, P2103
Bundle Name: TPS_ThrottleAuthorityDefaulted
P0068, P0122, P0123, P0222, P0223, P16F3, P16A0, P16A1, P16A2, P1104, P2100, P2101, P2102, P2103, P2135
Bundle Name: Transmission Output Shaft Angular Velocity Validity
P0722, P0723, P077C, P077D
Bundle Name: TransmissionEngagedState_FA
P1824, P182A, P182B, P182C, P182D, P182E, P182F, P1838, P1839, P1840, P1841, P18B5, P18B6, P18B7, P18B8, P18B9, P18BA, P18BB, P18BC, P18BD, P18BE, P18BF, P18C0, P18C1, P18C2, P18C3, P1915
Bundle Name: VehicleSpeedSensor_FA
P0502, P0503, P0722, P0723
Bundle Name: VentCircuit_FA
ELCP sealed/vented fuel system, P0449, P0498, P0499
Bundle Name: VICM_WakeupDiag_FA
P06E4
Bundle Name: VICM_WakeupDiag_TFTKO
P06E4
Bundle Name: WRAF_Bank_1_FA
P0131, P0132, P064D, P223C, P223E, P2626(P2237, P2243, P2251 added in 18.18.123)
Bundle Name: WRAF_Bank_2_FA
P0151, P0152, P064E, P223D, P223F, P2629(P2240, P2247, P2254 added in 18.18.123)

18 OBDG01 Fault Bundle Definitions

Bundle Name: AAP2_SnsrCktFA
P2228, P2229
Bundle Name: BSTR_b_BoostSnsrFA
P0106, P0107, P0108, P2228, P2229, P0236
BSTR_b_BoostSnsrFA - Other Definitions:
Turbo Charger: P2228, P2229, P0236
Super Charger: P0106, P0107, P0108
Bundle Name: BSTR_b_PCA_CktFA
P0033, P0034, P0035, P0045, P0047, P0048, P0243, P0245, P0246, P0247, P0249, P0250
Bundle Name: BSTR_b_PCA_TFTKO
P0234, P0299, P0033, P0034, P0035, P0045, P0047, P0048, P0243, P0245, P0246, P2261, P0247, P0249, P0250
Bundle Name: BSTR_b_TurboBypassCktFA
P0033, P0034, P0035, P00C0, P00C1, P00C2

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ambient Air Temperature Sensor Range/ Performance	P0071	The purpose of the rationality diagnostic is to detect and report a failure of the sensor when rationalized with other sensors in the vehicle. This diagnostic will run after the soak conditions are met. If the enable criteria are met and if the temperature difference of the compared sensors is greater than their calibrated thresholds, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS.	ABS (Outside Air Temperature - Inlet Air Temperature) AND ABS (Outside Air Temperature - Engine Coolant Temperature)	> 28.00 > 28.00	System Voltage Power mode Test complete this trip Compressor running Propulsion Off Timer Power Electronic Pump transition soak time Compressor Off transition soak time Charger Off transition soak time No active power electronic pump DTC: No active outside air temperature DTC: No active run crank DTCs: No active propulsion system off timer DTC: ECT compare No active inlet air temperature DTCs: No active engine coolant temperature DTCs:	> 10.20 V = Run for < 20.00 s = FALSE = FALSE > 21,600.00 s > 3,600.00 s > 3,600.00 s > 3,600.00 P0CE9, P1F44, P1F45 P0072, P0073 P2534, P2535 P0606 = TRUE P0110, P0111, P0112, P0113, P0114 P0115, P0116, P0117, P0118, P0119	32.00 fails / 40.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ambient Air Temperature Sensor Circuit Low Input	P0072	This diagnostic detects if the temperature sensor has an out of range low circuit fault. If the enable criteria are met and the temperature sensor voltage read is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	< 2.00 % (0.10 V) of reference voltage	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ambient Air Temperature Sensor Circuit High Input	P0073	This diagnostic detects if the temperature sensor has an out of range high circuit fault. If the enable criteria are met and the temperature sensor voltage read is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	> 96.00 % (4.80 V) of reference voltage	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ambient Air Temperature Sensor Circuit Intermittent	P0074	This diagnostic detects if the temperature sensor circuit has an intermittent circuit fault. The string length is the addition of absolute difference between consecutive readings for a calibrated number of samples. If the string length is greater than the calibrated fail threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	String Length Where: "String Length" = sum of "Diff" calculated over And where: "Diff" = ABS (current OAT reading - OAT sensor value from 250 milliseconds previous)	> 50.00 % 4 consecutive OAT samples	System Voltage	> 10.20 V	4.00 fails / 5.00 samples at 1 second	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Switch Stuck Closed	P04B6	Fuel Door Position Rationality	Fuel door opened AND refuel request AND refuel detected (10% delta fuel level change)	False True True	Fuel Fill Door Switch Stuck Closed Diagnostic Enable Calibration	= TRUE	50ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Position Sensor/ Switch Circuit	P04B8	Detects if sensor reading is invalid	Fuel Fill Door Position Sensor reading within an invalid range	65.88 %< Reported Position <= 81.56 %	Fuel Fill Door Position Sensor/Switch Circuit Diagnostic calibration	= TRUE	6 out of 8 samples @ 500ms per sample 3 seconds out of a 4 seconds window	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Position Sensor/ Switch Circuit Low	P04B9	Detects if the Circuit is Shorted to Ground	Fuel Fill Door Position Sensor reading below a threshold	Reported Position< 22.40 %	Fuel Fill Door Position Sensor/Switch Circuit Low Diagnostic Calibration	= TRUE	6.00 out of 8.00 samples @ 500ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Position Sensor/ Switch Circuit High	P04BA	Detects if the Circuit is Shorted to Battery	Fuel Fill Door Position Sensor reading above a threshold	Reported Position > 94.50 %	Fuel Fill Door Position Sensor/Switch Circuit High Diagnostic Enable Calibration	= TRUE	6.00 out of 8.00 samples @ 500ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Lock Control Circuit/Open	P04BB	Detects a fault in the Fuel Fill Door Lock/ Unlock Control Circuit	Hardware Reported Test Result for OPEN Circuit	Fault =TRUE	Fuel Fill Door Lock Control Circuit/Open Diagnostic Enable Calibration	= TRUE	80.00 % of total number samples @ 50ms per sample (<5sec)	Type A, 1 Trips
			OR		The Hardware reported test result, for an open circuit or short to power condition	≠ INDETERMINATE		
			Hardware Reported Test Result for SHORT Circuit to Battery		The door lock driver circuit must be active to assert an Unlock OR The door lock driver circuit must be active to assert Lock state	=ASSERT UNLOCK =ASSERT LOCK		
			Hardware Reported Test Result for SHORT Circuit to Ground	Fault =TRUE	Fuel Fill Door Lock Control Circuit/Open Diagnostic Enable Calibration	= TRUE	64.00 out of 80.00 samples @ 50ms per sample	
		The door lock driver circuit is NOT be active	=ASSERT NONE					

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Open Request Sensor/ Switch Circuit	P04C8	Detects if the circuit resistance is incorrect	Switch sensor reading within invalid range	65.88 %< Reported Position <= 81.56 %	Fuel Fill Door Open Request Sensor/Switch Circuit Diagnostic Enable Calibration	= TRUE	6.00 out of 8.00 samples @ 500ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Open Request Sensor/ Switch Circuit Low	P04CA	Detects if the circuit is shorted to ground	Fuel Fill Door Lock Request Switch sensor reading less than threshold	Reported Position< 22.94 %	Fuel Fill Door Open Request Sensor/Switch Circuit Low Diagnostic Enable Calibration	= TRUE	6.00 out of 8.00 samples @ 500ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Open Request Sensor/ Switch Circuit High	P04CB	Detects if the Circuit is shorted to battery or open	Fuel Fill Door Request Switch sensor reading above threshold	Reported Position > 94.50 %	Fuel Fill Door Open Request Sensor/Switch Circuit High Diagnostic Enable Calibration	= TRUE	6.00 out of 8.00 samples @ 500ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Air Conditioner (A/C) Refrigerant Charge Loss	P0534	<p>Refrigerant charge loss is inferred from monitoring the low side refrigerant pressure (LSRP) sensor reading under compressor running and compressor off cases.</p> <p>For the compressor on case, this diagnostic will run after the soak conditions are met. If the enable criteria are met and the LSRP sensor reading drops below a calibration look up table value for longer than a calibrated time then a FAIL is reported. The compressor on look up table is used for pressure calibration threshold values based on ambient temperature. A diagnostic PASS is reported when failure criteria has not been met after a calibrated maximum evaluation time.</p> <p>For the compressor off case, this diagnostic will run after the soak conditions are met. The LSRP sensor reading is compared to a calibration look up</p>	<p>CASE1: determine low refrigerant charge fail - compressor running</p> <p>Low Side Refrigerant Pressure based on Minimum of OAT Raw or OAT Filtered</p> <p>for</p> <p>Low Side Pressure Exceeded Threshold Time</p>	<p>< Case 1 (CompON) See Supporting Tables</p> <p>> 3.00 s</p>	<p>System Voltage</p> <p>No active pressure sensor or temperature sensor or clock DTCs:</p> <p>Diagnostic Complete Flag</p> <p>Compressor Running Flag</p> <p>Compressor Status</p> <p>Continuous Compressor RPM check (Run Mode) OR Continuous Compressor RPM check (Charge Mode)</p> <p>Compressor Off Time</p> <p>(Propulsion System Active AND Run Crank Active) OR Charge Function Available</p>	<p>> 10.20 V</p> <p>P2517, P2518, P2516, P151C, P0606, P0071, P0072, P0073, P0074</p> <p>= False</p> <p>= True</p> <p>= Normal Operation</p> <p>> 500.00 RPM to Enable < 250.00 RPM to Disable (Hysteresis) > 500.00 RPM to Enable < 250.00 RPM to Disable (Hysteresis)</p> <p>> 3,600.00 s</p> <p>= True</p> <p>= True</p> <p>= True</p>	up to 60.00 s	Type B, 2 Trips
			<p>CASE2a: determine low refrigerant charge fail - compressor off/soaked</p> <p>Low Side Refrigerant Pressure based on Minimum of OAT Raw or OAT Filtered</p> <p>for</p> <p>Low Side Pressure Exceeded Threshold Time</p>	<p>Case 2 < (CompOFF_Fail) See Supporting Tables</p> <p>> 30.00 s</p>	<p>System Voltage</p> <p>No active pressure sensor or temperature sensor or clock DTCs:</p> <p>Compressor Off Time</p> <p>Compressor Running Flag</p>	<p>> 10.20 V</p> <p>P2517, P2518, P2516, P151C, P0606, P0071, P0072, P0073, P0074</p> <p>> 3,600.00 s</p> <p>= False</p>	up to 30.00 s	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		table for the threshold pressure value based on ambient temperature. A separate table is used for the compressor off fail and compressor off pass cases. If the enable criteria are met and the LSRP sensor reading exceeds the threshold value from the compressor off fail look up table for longer than a calibrated time then a FAIL is reported. If the enable criteria are met and LSRP sensor reading exceeds the compressor off pass look up table value for longer than a calibrated time then a PASS is reported.	CASE2b: determine low refrigerant charge pass - compressor off/soaked Low Side Refrigerant Pressure based on Minimum of OAT Raw or OAT Filtered for Low Side Pressure did not exceed threshold Time	Case 2 > (CompOFF_Pass) See Supporting Tables > 480.00 s	System Voltage No active pressure sensor or temperature sensor or clock DTCs: Compressor Off Time Compressor Running Flag	> 10.20 V P2517, P2518, P2516, P151C, P0606, P0071, P0072, P0073, P0074 > 3,600.00 s = False	up to 480.00 s	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage Low	P0562	Detects if Battery input voltage is below a threshold	Battery voltage is below a threshold	≤ 10.20 volts		Continuous	1 failed sample for 500ms below Threshold value	Type C, No SVS

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Read Only Memory (Rom)	P0601	See Malfunction criteria for Case Description.	This DTC will be stored if any software or calibration checksum is incorrect - Case 1 - Calculated Checksum does not match stored checksum				Runs once per powerup	Type A, 1 Trips
			Flash ECC Circuit Test - Case 2 - Failed detection of invalid data written to ECC			Continuous	1s loop, 3 failures in powerup cycle	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Not Programmed	P0602	Indicates that the Control Module needs to be programmed	'No Start' Calibration is set to true which is only available on a new un- programmed Module			Continuous	1s loop, 1 failure	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Reset	P0603	Non-volatile memory checksum error	Checksum at power-up does not match checksum at power-down			Runs at battery connect OR after a controller reset OR When Battery Backed RAM failure detected OR next controller init when Failure counter increments to 1 OR Fault is active OR Test not passed since code clear OR Test failed this key on OR MIL Request is ON	2 consecutive failed samples	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Random Access Memory (RAM) Failure	P0604	RAM ECC Circuit Test	Failed validation of test data written to ECC			Continuous	1s loop, 3 failures in powerup cycle	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Internal Performance	P0606	See Malfunction criteria for Case Description.	ALU and Register Test - Case 1 - Control Module fails to execute a diagnostic test algorithm			Continuous	1s loop, 3 failures in powerup cycle	Type A, 1 Trips
			Program Sequence Counter - Case 2 - Incorrect sequence of frame executionProgram Sequence Counter	10 samples in incorrect sequence in consecutive order		Continuous	1s loop, 3 failures in powerup cycle	
			Configuration Registers Test - Case 3 - Comparison of current configuration register settings with predefined values fails			Continuous	1s loop, 3 failures in powerup cycle	
			MMU Test - Case 4 - Test of memory management related instructions fails	Fails MMU instruction		Continuous	1s loop, 3 failures in powerup cycle	
			MMU Configuration Fault - Case 5 - Verifies MMU TLB's are properly configured for the application	TLB set incorrectly		Continuous	1s loop, 3 failures in powerup cycle	
			Stack Limits Test - Case 6 - Verifies stack usage does not exceed maximum stack size	Stack usage exceeds 100%		Continuous	1s loop, 3 failures in powerup cycle	
			Clock Status - Case 7 - Checks for loss of lock/ clock, forces a reset if failed			Continuous	1s loop, 3 failures in powerup cycle	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Auxiliary ALU Test - Case 8 - Auxiliary microprocessor fails to run a defined diagnostic algorithm			Continuous	100ms loop, 3 failures in powerup cycle	
			Auxiliary RAM Test - Case 9 - Auxiliary microprocessor fails a write/read data diagnostic RAM test			Continuous	1s loop, 3 failures in powerup cycle	
			Auxiliary ROM Test - Case 10 - Auxiliary microprocessor ROM checksum error			Continuous	2.5s loop, 3 failures in powerup cycle	
			Auxiliary Register Configuration Test - Case 11 - Configuration register values do not match expected pre-configured values			Continuous	100ms loop, 3 failures in powerup cycle	
			Auxiliary Stack Test - Case 12 - Auxiliary microprocessor stack underflow or overflow			Continuous	100ms loop, 3 failures in powerup cycle	
			Seed and Key Test - Case 13 - Seed and key test failed - invalid order, timeout, incorrect seed, incorrect key			Continuous	100ms loop, 3 failures in powerup cycle	
			Main Detected Seed Incorrect Order - Case 14 - Seed and key test failed - main microprocessor received seed from the auxiliary microprocessor out of order			Continuous	100ms loop, 3 failures in powerup cycle	
			Main Detected Unknown			Continuous	100ms loop, 3	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Seed - Case 15 - Seed and key test failed - main microprocessor received an unknown seed				failures in powerup cycle	
			Internal IO Diagnostic (BVREF) - Case 16 - 5V reference voltages out of range	10.46 % above or below		Continuous	1s loop, 3 failures in powerup cycle	
			Internal IO Diagnostic (Analog 25% reference line) - Case 17 - 25% reference line out of range	Reference less than 22% or greater than 28%		Continuous	1s loop, 3 failures in powerup cycle	
			Internal IO Diagnostic (Analog 75% reference line) - Case 18 - 75% reference line out of range	Reference less than 72% or greater than 78%		Continuous	1s loop, 3 failures in powerup cycle	
			SPI Fault Detection Test - Case 19 - SPI B, C, or D fault detected			Continuous	1s loop, 3 failures in powerup cycle	
			SPI B Fault Detection Test - Case 20 - Fault detected via echo test on SPI bus B			Continuous	1s loop, 3 failures in powerup cycle	
			SPI C Fault Detection Test - Case 21- Fault detected via echo test on SPI bus C			Continuous	1s loop, 3 failures in powerup cycle	
			SPI D Fault Detection Test - Case 22 - Fault detected via echo test on SPI bus D			Continuous	1s loop, 3 failures in powerup cycle	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Performance	P062F	Update BINVDM operation	Battery independent non- volatile status update failed				Runs at controller shutdown and after new data is written to EEPROM (which is checked every 600 seconds) 2 consecutive failed samples	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.	
Control Module Wake-up Circuit Performance	P06E4	Detects a fault in the Control Module Output Wake-Up Circuit	Case 1: Short to Ground		Diagnostic Enabled	=TRUE	480.00 failed samples within 560.00 samples 1 sample every 12.5ms	Type B, 2 Trips	
			Case 2:Short to Battery or Open circuit		Control Module Output Wake-Up Circuit Enabled	=TRUE			
					Diagnostic Enabled	=TRUE			
					Control Module Output Wake-Up Circuit Enabled	=FALSE			

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Control Circuit/Open	P0CE9	This diagnostic detects if the host controller has detected an open, short to ground or short to voltage fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Pump Control Current When Active	< 200 mA and > 3A	System Voltage Coolant Pump Control PWM Range Between Coolant Pump Enable	> 10.20 V 5.00 % < Pulse Width Modulation Duty Cycle < 95.00 % = True	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips
			Coolant Pump Control Current When Inactive	< 120 uA	System Voltage Coolant Pump Control PWM Range Between Coolant Pump Enable	> 10.20 V 5.00 % < Pulse Width Modulation Duty Cycle < 95.00 % = False	16.00 fails / 20.00 samples at 250ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Temperature Sensor Circuit Range/ Performance	P0CEF	The purpose of the rationality diagnostic is to detect and report a failure of the sensor when rationalized with other sensors in the vehicle. This diagnostic will run after the soak conditions are met. If the enable criteria are met and if the temperature difference of the compared sensors is greater than their calibrated thresholds, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS.	ABS (Power Electronic Coolant Temperature - Outside Air Temperature) AND ABS (Power Electronic Coolant Temperature - Transmission Oil Temperature) AND ABS (Power Electronic Coolant Temperature - High Side Refrigerant Pressure converted to Temperature)	> 27.00 °C > 27.00 °C > 28.00 °C	System Voltage No active power electronic coolant temperature DTCs: No active outside air temperature DTC: No active transmission fluid temperature DTC: No active high side refrigerant pressure DTC: No active power electronic pump DTCs: No active propulsion system off timer DTC: Power mode Test complete this trip Compressor running Propulsion Off Timer Power Electronic Pump transition soak time Compressor transition soak time Charger transition soak time	> 10.20 V P0CF0, P0CF1, P0CF2 P0071, P0072, P0073, P0074 P0711, P0712, P0713 P0532, P0533 P1F44, P1F45, P0CE9 P0606 = Run for < 20.00 s = FALSE = FALSE > 3,600.00 s > 3,600.00 s > 3,600.00 s > 3,600.00 s	32.00 fails / 40.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Temperature Sensor Circuit Low	P0CF0	This diagnostic detects if the temperature sensor has a out of range low circuit fault. If the enable criteria are met and the temperature sensor voltage read is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	< 4.00 % (0.20 V) of reference voltage	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Temperature Sensor Circuit High	P0CF1	This diagnostic detects if the temperature sensor has a out of range high circuit fault. If the enable criteria are met and the temperature sensor voltage read is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	> 98.00 % (4.90 V) of reference voltage	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Temperature Sensor Circuit Intermittent/ Erratic	P0CF2	This diagnostic detects if the temperature sensor circuit has an erratic circuit fault. The string length is the addition of absolute difference between consecutive readings for a calibrated number of samples. If the string length is greater than the calibrated fail threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	String Length Where: "String Length" = sum of "Diff" calculated over And where: "Diff" = ABS (current PECL reading - PECL reading from 250 milliseconds previous)	> 90.00 °C 4 consecutive PECL samples	System Voltage	> 10.20 V	4.00 fails / 5.00 samples at 1 second	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Evaporative Emission (EVAP) System Pressure Incorrect During Fuel Fill Door Open Request	P1461	Detects incorrect EVAP System pressure during a Fuel Fill Door Open Request	The Fuel Tank Vapor Pressure does NOT fall within a pressure range	Fuel Tank Vapor Pressure \geq 0.623 Kpa OR Fuel Tank Vapor Pressure < -0.623 Kpa	Evaporative Emission (EVAP) System Pressure Incorrect During Fuel Fill Door Open Request Diagnostic Enable Calibration A request to refuel the vehicle has been detected	= TRUE =TRUE	120.00 sec	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Refrigerant Pressure Sensor B Rationality	P151C	The purpose of the rationality diagnostic is to detect and report a failure of the low side refrigerant pressure (LSRP) sensor when rationalized with other sensors in the vehicle. This diagnostic will run after the soak conditions are met. If the enable criteria are met and if the pressure difference of the compared sensors is greater than their calibrated thresholds, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS.	ABS (Low Side Refrigerant Pressure - High Side Refrigerant Pressure)	> 200.0 kpa	System Voltage No active pressure sensor DTCs: No active temperature sensor DTCs: No active clock DTC: No active engine coolant temperature sensor DTCs: Engine Present Engine Coolant Temperature Signal Status Power mode OAT Emission Status OAT Corrected Status Compressor Running Flag ABS (Engine Coolant Temperature - Outside Ambient Temperature Filtered) Outside Air Temp Raw High Side Refrigerant Pressure HSRP Status	> 10.2 V P2517, P2518, P0533, P0532 P0074, P0073, P0072, P0071 P0606 P0119, P0118, P0117, P0116 = True = Valid ≠ Crank = Valid = Valid = False < 15.0 C 0.0 C < OAT_raw < 25.0 C 0.0 Kpa < HSRP < 675.0 Kpa = Valid	32 fails / 40 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Compressor Off Time	> 3,600 s		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Fuel Fill Door Switch Wake-up Circuit Performance	P169D	Detects a circuit fault in the Fuel Fill Door Switch Wake-Up Circuit	Refuel Request Wake- up circuit state not equal to Refuel request Switch Position State Case 1: Fuel Fill Door Switch Wake-Up Circuit Active Case 2: Fuel Fill Door Switch Wake-Up Circuit Active	 =FALSE =TRUE	Fuel Fill Door Switch Wake-up Circuit Performance Diagnostic Enable Calibration No Active DTCs for the Open Request Sensor/ Switch Circuit Fuel Fill Door Open Switch Request Fuel Fill Door Open Switch Request	= TRUE P04C8, P04CA, P04CB =TRUE =FALSE	 4.00 out of 4.00 samples @ 50ms per sample 64.00 out of 80.00 samples @ 50ms per sample	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Feedback Circuit High Voltage	P19FA	This diagnostic detects if the feedback has an out of range high frequency speed fault. If the enable criteria are met and the feedback speed read is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Pump feedback frequency	≥ 750.00 Hz	System Voltage Coolant Pump Enable Pump control commanded speed Pump ON time	> 10.20 V = True $11.00\% < \text{Pulse Width Modulation Duty Cycle} < 90.00\%$ > 3.00 seconds	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Feedback Circuit Low Voltage	P19FB	This diagnostic detects if the feedback has an out of range low frequency speed fault. If the enable criteria are met and the feedback speed read is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Pump feedback frequency	0.00 Hz >= Pump feedback frequency <= 8.60 Hz	System Voltage Coolant Pump Enable Pump control commanded speed Pump ON time	> 10.20 V = True 11.00 %< Pulse Width Modulation Duty Cycle < 90.00 % > 3.00 seconds	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Feedback Circuit Performance	P19FC	<p>The purpose of the performance diagnostic is to detect and report a failure of the input circuit. If the enable criteria are met, the speed difference between the commanded speed to the pump feedback speed is calculated. For the pump actuated state, the speed difference is filtered and when this filtered difference exceeds the calibrated fault threshold, the diagnostic reports a FAIL. If filtered speed difference does not exceed the calibrated fault threshold, the diagnostic reports a PASS. The diagnostic will continue to report as long as the enablement criteria are met.</p> <p>For the pump non-actuated state, if the feedback speed exceeds the calibrated fault threshold, the diagnostic reports a FAIL. If feedback speed does not exceed the calibrated fault threshold, the diagnostic reports a PASS. The diagnostic</p>	<p>Pump feedback performance fail in actuated state</p> <p>Filtered (command speed - feedback speed)</p> <p>OR</p> <p>Filtered (command speed - feedback speed)</p>	<p>< PCOD Pump Feedback Fault Low Threshold</p> <p>> PCOD Pump Feedback Fault High Threshold</p>	<p>System Voltage</p> <p>Coolant Pump Enable</p> <p>No active power electronic coolant temperature DTCs:</p> <p>No active power electronic pump DTCs:</p> <p>Pump control commanded speed</p> <p>Pump ON time</p> <p>Power electronic temperature</p>	<p>> 10.20 V</p> <p>= True</p> <p>P0CF0, P0CF1, P0CF2 P0CEF,</p> <p>P0CE9, P1F44, P1F45</p> <p>11.00 % < Pulse Width Modulation Duty Cycle < 90.00 %</p> <p>> 5.00 seconds</p> <p>-20.00 < °C < 9,999.00</p>	Up to 257 seconds	Type B, 2 Trips
			<p>Pump feedback performance fail in non-actuated state</p> <p>Pump speed feedback RPM</p>	> 250.00	<p>System Voltage</p> <p>Coolant Pump Enable</p> <p>Pump OFF time</p> <p>Pump feedback performance fail in actuated state</p>	<p>> 10.20 V</p> <p>= False</p> <p>> 10.00 seconds</p> <p>= FALSE</p>	32.00 fails / 40.00 samples at 250ms	
			<p>If the pump feedback diagnostic fails the actuated state</p> <p>Filtered (command speed - feedback speed)</p> <p>AND</p> <p>Filtered (command speed - feedback speed)</p>	<p>> PCOD Pump Feedback Repass Low Threshold</p> <p><</p>	<p>System Voltage</p> <p>Coolant Pump Enable</p> <p>No active power electronic coolant temperature DTCs:</p> <p>No active power electronic pump DTCs:</p>	<p>> 10.20 V</p> <p>= True</p> <p>P0CF0, P0CF1, P0CF2 P0CEF</p> <p>P0CE9, P1F44, P1F45</p>	Up to 311 seconds	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		will continue to report as long as the enablement criteria are met.		PCOD Pump Feedback Repass High Threshold	Pump control commanded speed Pump ON time Power electronic temperature	11.00 %< Pulse Width Modulation Duty Cycle < 90.00 % > 5.00 seconds -20.00 < °C < 9,999.00		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Voltage Energy Management Communicati on Bus Enable Circuit	P1EB9	Detects a fault in the High Voltage Energy Management Communication (HVEM) Bus Enable Circuit	Case 1: Short to Ground		Diagnostic Enabled	= TRUE	480.00 failed samples within 560.00 samples 1 sample every 12.5ms	Type A, 1 Trips
			Case 2: Short to Battery or open circuit		HVEM Bus Enabled	=TRUE		
					Diagnostic Enabled	= TRUE		
					HVEM Bus Enabled	=FALSE		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Enable Circuit Low	P1F44	This diagnostic detects a Short to Ground fault on the output circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Pump Enable Line Current	> 0.6 A	System Voltage Coolant Pump Enable	> 10.20 V = True	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Electronics Coolant Pump Enable Circuit High	P1F45	This diagnostic detects a Short to Voltage fault on the output circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Pump Enable Line Current OR Coolant Pump Enable Line Voltage	> 35 uA < 4.5 V	System Voltage Coolant Pump Enable	> 10.20 V = False	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Level Sensor Circuit	P1FFB	This diagnostic detects if the sensor reading has an in-range but invalid region circuit fault. If the enable criteria are met and the sensor voltage read is within the calibrated region, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Level Sensor Sensed Voltage	$2.85\text{ V} \leq \text{Sensed Voltage} \leq 3.11\text{ V}$	12V Battery Voltage	$> 10.20\text{ V}$	40 out of 50 samples at 100ms	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Level Sensor Circuit Low Voltage	P1FFC	This diagnostic detects if the sensor has a out of range low circuit fault. If the enable criteria are met and the sensor voltage read is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Level Sensor Sensed Voltage	Sensed Voltage ≤ 1.37 V	12V Battery Voltage	> 10.20 V	40 out of 50 samples at 100ms	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Level Sensor Circuit High Voltage	P1FFD	This diagnostic detects if the sensor has a out of range high or open circuit fault. If the enable criteria are met and the sensor voltage read is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Level Sensor Sensed Voltage	Sensed Voltage ≥ 4.00 V	12V Battery Voltage	> 10.20 V	40 out of 50 samples at 100ms	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Level Low	P1FFE	<p>This diagnostic detects if the RESS coolant level is normal or low based on the sensor voltage reading.</p> <p>If the enable criteria are met and the sensor voltage read is within the coolant level low calibrated region then the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, a FAIL THIS KEY (FTK) flag is set and FTK is stored into a memory buffer. A calibrated total number of samples is used to define number of most recent stored values in the buffer to sum the number of FTKs stored. If the total number of FTK incidences exceeds the calibrated threshold value then a FAIL is reported.</p> <p>If the enable criteria are met and the sensor voltage read is within the normal coolant level calibrated region then the fail counter will not increment but the sample counter will increment. When the</p>	Coolant Level Sensor Sensed Voltage	$1.38\text{ V} \leq \text{Sensed Voltage} \leq 2.84\text{ V}$ (Low State)	<p>[(Vehicle Speed in Range for time) OR (Propulsion System Off Time AND Vehicle Speed)]</p> <p>AND</p> <p>HV Battery Temperature in Range for time</p> <p>HV Battery Temperature Signal Status</p> <p>Propulsion System Off Time Signal Status</p> <p>Loss of Communication, Ignition Off Timer, Output Speed Sensor, Battery Voltage Sensor DTC's are not ACTIVE</p>	<p>-1.00 < Vehicle speed < 1.00 KPH > 30.00 s</p> <p>> 30.00 s</p> <p>< 1.00 KPH</p> <p>0.00 °C < HV Battery Temp < 120.00 °C > 30.00 s</p> <p>= Valid</p> <p>= Valid</p> <p>U0100, P2610, P0721, P077B, P215C, U0101, P0ABC, P0ABD, P0ABB, U0111, U185A</p>	<p>16 out of 20 samples at 250ms</p> <p>and failed 2 of 3 key cycles</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		sample count matures per the sample count calibration threshold value then a PASS THIS KEY (PTK) flag is stored to memory. At the end of the current trip, if a FTK has not been stored for the current trip and a PTK has been registered and the total number of FTK incidences does not exceed the calibrated threshold value then a diagnostic PASS will be reported.						

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Refrigerant Pressure Sensor B Stuck Performance	P2516	The purpose of the low side refrigerant pressure (LSRP) sensor stuck diagnostic is to detect and report a failure of the sensor stuck in range. This diagnostic will run after the soak conditions are met. If the enable criteria are met then the sensor reading is expected to vary and update with compressor running. If the LSRP sensor reading does not exceed a calibration threshold after a calibrated time then the diagnostic will report a FAIL, else a PASS will be reported.	IF Low Side Refrigerant Pressure at Start Of Diag - Low Side Refrigerant Pressure at End of Diag	< 4.00 kpa after 180.00 s	System Voltage No active temperature sensor DTCs: No active clock DTC: No active engine coolant temperature sensor DTCs: Engine Present Engine Coolant Temperature Signal Status Power mode Compressor Off Time Compressor Running Flag TRUE for Compressor Running Flag ABS (Engine Coolant Temperature - Outside Ambient Temperature Filtered) Test Passed	> 10.20 V P0074, P0073, P0072, P0071 P0606 P0119, P0118, P0117, P0116 = TRUE = Valid ≠ Crank > 3,600.00 s < 185.00 s = TRUE > 15.00 C Diagnostic has not already reported a Pass this trip	Up to 180.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Refrigerant Pressure Sensor B Circuit Low Input	P2517	This diagnostic detects if the low side refrigerant pressure (LSRP) sensor has an out of range low or open circuit fault. The LSRP sensor voltage read vs the reference voltage ratio is used. If the enable criteria are met and the ratio exceeds a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	< 2.00 % (0.10 V) of reference voltage	System Voltage	> 10.20 V	16 fails / 20 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Refrigerant Pressure Sensor B Circuit High Input	P2518	This diagnostic detects if the low side refrigerant pressure (LSRP) sensor has an out of range high circuit fault. The LSRP sensor voltage read vs the reference voltage ratio is used. If the enable criteria are met and the ratio exceeds a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Sensor voltage	> 98 % (4.9 V) of reference voltage	System Voltage	> 10.2 V	40 fails / 50 samples at 100ms	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit Low	P2534	Detects a run crank relay open circuit	Run Crank Line Voltage	< 2 volts	Diagnostic Enabled CAN Communication ECM Run/Crank Active Data	= TRUE Enabled Available and Active	2.5 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit High	P2535	Detects a run crank relay short to power	Run Crank Line Voltage	> 5 volts	Diagnostic Enabled CAN Communication ECM Run/Crank Active Data	= TRUE Enabled Available and False	2.5 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Accessory Position Circuit Low	P2537	See Malfunction criteria for Case Description	Detects an accessory position circuit open	False	P2537 Propulsion System Propulsion System Active Time	Not Test Failed This Key On and Not Test Passed This Key On Active > 0.5 seconds	0.1 seconds (8 * 0.0125)	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Hood Switch Performance	P257D	Rationality Check for the Vehicle Hood Switch	Hood Switch Position Sensor reading within an invalid range	Within the following ranges: 67.80 % < reading < 71.50 % 43.40 % < reading < 45.70 % 14.60 % < reading < 17.20 %	Diagnostic Enabled Battery System in Range Diagnostic System Disable	= TRUE =TRUE = FALSE	1 seconds out of a 1.25 seconds window	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Hood Switch Circuit Low Voltage	P257E	Detects if the Vehicle Hood Switch is Shorted to Ground	Hood Switch Position Sensor reading below a threshold	<= 14.60 %	Diagnostic Enabled Battery System in Range Diagnostic System Disable	= TRUE =TRUE = FALSE	1 seconds out of a 1.25 seconds window	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Hood Switch Circuit High Voltage	P257F	Detects if the Vehicle Hood Switch is Shorted to Battery	Hood Switch Position Sensor reading above a threshold	>= 71.50 %	Diagnostic Enabled Battery System in Range Diagnostic System Disable	= TRUE =TRUE = FALSE	1 seconds out of a 1.25 seconds window	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Power Off Timer Performance	P262B	Detects a fault in the internal Control Module off-timer	The absolute value of the difference between the Control Module 'Off' Timer and Control Module 'On' Timer (both timers operating during Controller 'On') exceeds a threshold	Difference > 0.056	Diagnostic Enabled Controller 'On' Time RunCrank DTCs Not Active	= TRUE > 60.00 seconds =TRUE P0601, P0602, P0603, P062F, P0604 and P0606	Runs once per drive cycle (when Run/ Crank transitions from TRUE to FALSE).	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus A Off	U0073	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state.	CAN Controller Interface in a Bus Off state	=TRUE	Controller On ECU is sending/ receiving on CAN Battery Voltage	=TRUE =TRUE >= 10.20 V	5 failures out of 5 samples 1 s loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus B Off	U0074	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state.	CAN Controller Interface in a Bus Off state	=TRUE	Controller On ECU is sending/ receiving on CAN Battery Voltage	=TRUE =TRUE >= 10.20 V	5 failures out of 5 samples 1 s loop	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus H Off	U007A	Detects that a CAN serial data bus shorted condition has occurred to force the CAN device driver to enter a bus-off state.	CAN Controller Interface in a Bus Off state	=TRUE	Controller On ECU is sending/ receiving on CAN Battery Voltage	=TRUE =TRUE >= 10.20 V	5 failures out of 5 samples 1 s loop	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With ECM on Bus A	U0100	Detects Lost Communication with ECM	Detects that CAN serial data communication has been lost with the ECM on Bus A - Messages have not been received from the ECM for a specified time	$\geq 500\text{ms}$	Controller On Bus A Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Battery Energy Control Module	U0111	Detects Lost Communication with Battery Energy Control Module	Detects that CAN serial data communication has been lost with the Battery Energy Control Module on Bus A - Messages have not been received from the BECM for a specified time	$\geq 500\text{ms}$	Controller On Bus A Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Brake System Control Module	U0129	Detects Lost Communication with Brake System Control Module	Detects that CAN serial data communication has been lost with the Brake System Control Module on Bus A - Messages have not been received from the EBCM for a specified time	$\geq 500\text{ms}$	Controller On Bus A Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Electric A/C Compressor Control Module	U016B	Detects Lost Communication with Electric A/C Compressor Control Module	Detects that CAN serial data communication has been lost with the Electric A/C Compressor Control Module on Bus A - Messages have not been received from the EACCM for a specified time	$\geq 500\text{ms}$	Controller On Bus A Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module	U0293	Detects Lost Communication with Hybrid Powertrain Control Module	Detects that CAN serial data communication has been lost with the Hybrid Powertrain Control Module on Bus A - Messages have not been received from the HCP for a specified time	$\geq 500\text{ms}$	Controller On Bus A Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Hybrid Powertrain Control Module on Bus B	U1817	Detects Lost Communication with Hybrid Powertrain Control Module on Bus B	Detects that CAN serial data communication has been lost with the Hybrid Powertrain Control Module on Bus B - Messages have not been received from the HCP for a specified time	$\geq 500\text{ms}$	Controller On Bus B Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With ECM on Bus B	U1818	Detects Lost Communication with ECM on Bus B	Detects that CAN serial data communication has been lost with the ECM on Bus B - Messages have not been received from the ECM for a specified time	$\geq 500\text{ms}$	Controller On Bus B Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Battery Energy Control Module on Bus H	U185A	Detects Lost Communication with Battery Energy Control Module on Bus H	Detects that CAN serial data communication has been lost with the Battery Energy Control Module on Bus H - Messages have not been received from the Battery Energy Control Module for a specified time	$\geq 500\text{ms}$	Controller On Bus H Communication Enabled Time Battery Voltage	=TRUE >=5 seconds >= 10.20 V	Runs in 10ms loop	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Improper Wake-up Performance	U3012	Control Module Wake- up Circuit Performance (Self Wakeup Fault)	Control module unable to do a Self Wakeup when there is a request to do so		Diagnostic Enabled	= TRUE	Runs once at powerup if a Self-Wakeup request was active last power down	Type A, 1 Trips
					Self-Wakeup Requested	=TRUE		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan 1 Control Circuit	P0480	This diagnostic detects if the host controller has detected an open, short to ground, and short to voltage fault on the output circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Fan Control Current When Active	< 200 mA and > 3A	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips
			Fan Control Current When Inactive	< 80 uA	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Voltage System Interlock Circuit Low	P0A0C	The diagnostic monitors the sensed interlock voltage for values that are below a threshold when the HVIL circuit is commanded to 5 volts	HVIL Sensed % of 5 volts	< 30 %	HVIL Commanded Status 12V Battery Voltage	5V > 10.2V	2 failures out of 2 samples 12.5 ms /sample 25 ms	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
High Voltage System Interlock Circuit High	P0A0D	The diagnostic monitors the sensed interlock voltage for values that are above a threshold. The threshold is different depending upon when the HVIL circuit is commanded to 5 volts or 0 volts.	HVIL Sensed % of 5 volts	> 24 %	HVIL Commanded Status 12V Battery Voltage	0V > 10.2V	5 failures out of 8 samples 12.5 ms /sample	One Trip, Type A
			OR HVIL Sensed % of 5 volts	> 44 %	HVIL Commanded Status 12V Battery Voltage	5V > 10.2V	4 failures out of 6 samples 12.5 ms /sample 100 ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Over temperature	P0A7E	This diagnostic detects if the max battery temperature is above a threshold. If the enable criteria are met and the temperature is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Battery Max Temperature Above Threshold	> 73.50 °C	System Voltage No Active DTCs (Battery temperature status) Short Low Short High Communication Performance	> 10.20 V P0A9D P0AC7 P0ACC P0AEA P0BC4 P0C35 P0A9E P0ACD P0AC8 P0AEB P0BC5 P0C36 U179C P0A9C P0AC6 P0ACB P0AE9 P0BC3 P0C34	50.00 fails / 60.00 samples at 100ms	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Life (EV Range)	P0A7F	High Pack Power capability	Power limits	< KtBSED_P_BPD_D_E ndOfLifePwrThrsh (kW) - see VICM Supporting Tables	Maximum battery temperature Minimum battery temperature Battery SOC RunCrank System Voltage Battery Voltage Sensor (see Fault Bundle Page) Battery Current Sensor (see Fault Bundle Page) TempRationalityFA (see Fault Bundle Page) Actual battery power exceedance of power limits in terms of % overshoot multiplied by seconds of duration	< 50.00 °C > 20.00 °C > 15.00 % < 100.00 % = TRUE >10.2 V = False = False = False > 80 %-Sec	5 seconds	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor Range/ Performance	P0A9C	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Positive Contactor Circuit Stuck Closed	P0AA1	The propulsion positive contactor is a high voltage relay that is used to connect the positive side of the high voltage battery to the positive side of the propulsion bus. This DTC detects when the propulsion positive contactor is stuck closed by monitoring for excessive voltage on the positive side of the propulsion bus when all contactors are commanded open for greater than a calibratable time. The calibratable time is necessary in order to guarantee that the propulsion bus has been fully discharged in order to prevent false failures.	Propulsion Positive Bus Voltage	> 30 Volts	Propulsion Bus Voltage Sensor Propulsion Positive Bus Voltage High Voltage Battery Voltage Sensor All Contactors OR [All Contactors AND Propulsion Bus Voltage]	Not Failed Not Failed Not Failed Open for > 120 seconds Open < 5 % of High Voltage Battery Voltage	4 failures out of 6 samples 12.5 ms /sample 75 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Negative Contactor Circuit Stuck Closed	P0AA4	The propulsion negative contactor is a high voltage relay that is used to connect the negative side of the high voltage battery to the negative side of the propulsion bus. This DTC detects when the propulsion negative contactor is stuck closed by monitoring for excessive voltage on the negative side of the propulsion bus when all contactors are commanded open for greater than a calibratable time. The calibratable time is necessary in order to guarantee that the propulsion bus has been fully discharged in order to prevent false failures.	Propulsion Negative Bus Voltage	> 30 V	Propulsion Bus Voltage Sensor Propulsion Negative Bus Voltage High Voltage Battery Voltage Sensor All Contactors OR [All Contactors AND Propulsion Bus Voltage]	Not Failed Not Failed Not Failed Open for > 120 seconds Open < 5 % of High Voltage Battery Voltage	4 failures out of 6 samples 12.5 ms /sample 75 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

[illegible]

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
							Pass if any single resistance measurement exceeds resistance threshold	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Voltage Sense Circuit Rationality	P0ABB	Rationality compares pack voltage sensor to average cell voltage * 96	Average cell voltage * 96 - Battery Pack voltage	> 12.00 V	VICMVoltageFA (see Fault Bundle Page) No active DTCs:	= FALSE U0111 U185A	2 seconds out of a 2.5 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 2 Temperature Sensor Performance	P0AC6	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 3 Temperature Sensor Performance	P0ACB	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Positive Contactor Control Circuit	P0AD9	Diagnoses the Propulsion Positive Contactor high side driver circuit for circuit faults	The HPC2 detects that voltage is high during driver OFF state (indicates short to power or open circuit). It also detects that current is low during driver ON state (indicates open circuit).	Short to Power: Detected while OFF and output voltage is greater than the 12V battery voltage - 0.4V. Open Circuit: Detected while OFF and output voltage > 4V. Detected while ON and current sense feedback < 194 mA	12V Battery Voltage High Voltage Battery Current	> 10.2V < 999 amps	40 failures out of 50 samples 12.5 ms /sample 625 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Negative Contactor Control Circuit	P0ADD	Diagnoses the Propulsion Negative Contactor high side driver circuit for circuit faults	The HPC2 detects that voltage is high during driver OFF state (indicates short to power or open circuit). It also detects that current is low during driver ON state (indicates open circuit).	Short to Power: Detected while OFF and output voltage is greater than the 12V battery voltage - 0.4V. Open Circuit: Detected while OFF and output voltage > 4V. Detected while ON and current sense feedback < 194 mA	12V Battery Voltage High Voltage Battery Current	> 10.2V < 999 amps	40 failures out of 50 samples 12.5 ms /sample 625 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Precharge Contactor Circuit Stuck Open	P0AE3	The precharge contactor is used to bring two high voltage circuits to the same voltage so that the contactor is prevented from damage prior to closing of the propulsion contactors. This DTC detects when the precharge contactor is stuck open by monitoring for insufficient bus voltage during precharge.	Propulsion Negative Bus Voltage	< 5 V	Precharge Contactor Propulsion Negative Contactor Propulsion Negative Bus Voltage RESS Heating Mode	Closed For 0.090 Seconds Open Not Failed OFF	8 failures out of 10 samples 12.5 ms/sample Executed once per HPC2 Wake up cycle during the precharge 125 ms	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Precharge Contactor Control Circuit	P0AE4	Diagnoses the Precharge Contactor high side driver circuit for circuit faults.	The HPC2 detects that voltage is high during driver OFF state (indicates short to power). It also detects that current is low during driver ON state (indicates open circuit).	Short to Power: Detected while OFF and output voltage is greater than the 12V battery voltage - 0.4V. Open Circuit: Detected while ON and current sense feedback < 194 mA	12V Battery Voltage High Voltage Battery Current	> 10.2V < 1 amp	40 failures out of 50 samples 12.5 ms /sample Continuous 625 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 4 Temperature Sensor Performance	P0AE9	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Voltage Sense Circuit Correlation	P0AF8	Correlation compares pack voltage sensor to either TPIM Bus Voltage or Charger Bus Voltage	Battery Pack voltage - TPIM Bus Voltage	> 16.00 V	Battery Pack Connected to TPIM No active DTCs:	= TRUE P0ABC P0ABD P1A07 P0ABB P1AEC P1AED P1E28 P1AE9 P1AEB P1AE21 P1AE8 P1AEA P1AE20 U1817	10 seconds out of a 12.5 seconds window	One Trip, Type A
			OR Battery Pack voltage - Charger Bus Voltage	> 16.00 V	Battery Pack Connected to Charger AND Battery Pack Connected to TPIM	= TRUE = FALSE	10 seconds out of a 12.5 seconds window	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					No active DTCs:	P0ABC P0ABD P1A07 P0ABB P0D4E P0D4F P1EEB P1EEC P0D5C P1ECE P16C5 U1838		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery System Voltage Low	P0AFA	Voltage too lowDTC Clear	High Voltage Battery Pack Voltage	< KtBSED_U_BUV_Pack kVoltThresh (V) (see VICM Supporting Tables)	No active DTCs:	P0ABC P0ABD P1A07 P0AF8 P0ABB U0111 U185A	8 seconds out of a 39.875 seconds window	One Trip, Type A
			OR Any Cell Voltage	< KtBSED_U_BUV_Cell VoltThresh (V) (see VICM Supporting Tables)	VICMVoltageFA (see Fault Bundle Page) No active DTCs:	= FALSE U0111 U185A	1 seconds out of a 4.875 seconds window	
					Must Send CPID	0x7E4 07 AE 32 0C 0C 00 00 00		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery System Voltage High	P0AFB	Voltage too highDTC Clear	High Voltage Battery Pack Voltage	> KtBSED_U_BOV_Pack kVoltThresh (V) (see VICM Supporting Tables)	No active DTCs:	P0ABC P0ABD P1A07 P0AF8 P0ABB U0111 U185A	8 seconds out of a 39.875 seconds window	One Trip, Type A
			OR Any Cell Voltage	> KtBSED_U_BOV_Cell VoltThresh (V) (see VICM Supporting Tables)	VICMVoltageFA (see Fault Bundle Page) No active DTCs: Must Send CPID	= FALSE U0111 U185A 0x7E4 07 AE 32 0C 0C 00 00 00	1 seconds out of a 4.875 seconds window	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Current Sensor A/B Correlation	P0B13	Checks for deviation between Fine and Coarse current sensors	Fine Current - Coarse Current	> 10.00 A	Fine Current measured OR Coarse Current measured No active DTCs:	Between -20.00 A and 20.00 A Between -20.00 A and 20.00 A P0AC1 P0AC2 P1EBA P1A07 P0B13 P0B10 P0B11 P1EBB U0111 U185A	10 seconds out of a 12.5 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense A Circuit Range/ Performance	P0B3C	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense B Circuit Range/ Performance	P0B41	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense C Circuit Range/ Performance	P0B46	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense D Circuit Range/ Performance	P0B4B	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense E Circuit Range/ Performance	P0B50	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense F Circuit Range/ Performance	P0B55	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense G Circuit Range/ Performance	P0B5A	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense H Circuit Range/ Performance	P0B5F	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense I Circuit Range/ Performance	P0B64	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense J Circuit Range/ Performance	P0B69	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense K Circuit Range/ Performance	P0B6E	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense L Circuit Range/ Performance	P0B73	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense M Circuit Range/ Performance	P0B78	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense N Circuit Range/ Performance	P0B7D	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense O Circuit Range/ Performance	P0B82	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense P Circuit Range/ Performance	P0B87	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Q Circuit Range/ Performance	P0B8C	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense R Circuit Range/ Performance	P0B91	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense S Circuit Range/ Performance	P0B96	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense T Circuit Range/ Performance	P0B9B	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense U Circuit Range/ Performance	P0BA0	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense V Circuit Range/ Performance	P0BA5	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense W Circuit Range/ Performance	P0BAA	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense X Circuit Range/ Performance	P0BAF	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Y Circuit Range/ Performance	P0BB4	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Z Circuit Range/ Performance	P0BB9	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor E Circuit Range/ Performance	P0BC3	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor F Circuit Range/ Performance	P0C34	Rationality compares temperature with the other sensor values read	Temperature input deviates from the average battery temperature of other Module_Groups	> 20.00 °C	TempRationalityFA (see Fault Bundle Page)	= FALSE	5 seconds out of a 6.7 seconds window	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Temperature Sensor Circuit Range/ Performance	P0C43	This diagnostic detects and reports a failure of the sensor when rationalized with other sensors in the vehicle. This diagnostic will run after the soak conditions are met. If the enable criteria are met and if the temperature difference of the compared sensors is greater than their calibrated thresholds, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS.	<p>Absolute value of the difference of the Inlet Coolant Temperature to Battery Temperature greater than threshold</p> <p>AND</p> <p>Absolute value of the difference of the Inlet Coolant Temperature to Out Side Air Temperature greater than threshold</p>	<p>>= 23.00 °C</p> <p>>= 22.00 °C</p>	<p>System Voltage</p> <p>Power mode (Bus wake up)</p> <p>No Active DTCs (RESS Pump)</p> <p>No Active DTCs (Inlet Temperature)</p> <p>No Active DTCs (HV Battery Temperature)</p> <p>OAT Arbitrated Status</p> <p>No Active DTCs (Communications)</p> <p>Test complete this trip (TFTKO or TPTKO)</p> <p>Heater duty cycle</p> <p>All HV Battery contactors Open</p>	<p>> 10.20 V</p> <p>> 1.00 s AND < 20.00 s</p> <p>P1E8C, P1E8D, P0C47, P19FD, P19FE, P19FF</p> <p>P0C44, P0C45, P0C46</p> <p>P0A9C, P0A9D, P0A9E</p> <p>= VALID</p> <p>U0111</p> <p>= FALSE</p> <p><= 100.00 %</p> <p>>= 14,400.00 seconds</p>	32.00 fails / 40.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Temperature Sensor A Circuit Intermittent/ Erratic	P0C46	This diagnostic detects if the temperature sensor circuit has an erratic circuit fault. The string length is the addition of absolute difference between consecutive readings for a calibrated number of samples. If the string length is greater than the calibrated fail threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	String Length Where: "String Length" = sum of "Diff" calculated over And where: "Diff" = ABS(Current reading - reading from 250ms previous)	> 64.00 °C 10.00 consecutive samples	System Voltage No DTCs (Coolant Inlet Temperature sensor Status) OORL OORH Loss of Comms	> 10.20 V P0C44 P0C45 U185A	4.00 fails / 5.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Pump Control Circuit/Open	P0C47	This diagnostic detects if the host controller has detected an OPEN, STG or STV fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	When Active: Coolant Pump Control line current	<=200mA OR >3A	System Voltage HWIO Pump Control Circuit Status RESS Coolant Pump Enable RESS Pump Commanded PWM	> 10.20 V ≠ Indeterminate = TRUE 5.00 % < command < 95.00 %	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips
			When Inactive: Coolant Pump Control line current	<=120uA	System Voltage HWIO Pump Control Circuit Status RESS Coolant Pump Enable RESS Pump Commanded PWM	> 10.20 V ≠ Indeterminate = TRUE 5.00 % < command < 95.00 %	40.00 fails / 50.00 samples at 100ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery System Precharge Time Too Long	P0C78	The precharge contactor is used to bring two high voltage circuits to the same voltage so that the propulsion contactors are prevented from damage prior to closing of the propulsion contactors. This DTC sets if the Propulsion Bus Voltage does not get within a percentage band of high voltage battery voltage within a calibratable amount of time during the precharge. If the amount of time expires without reaching the required voltage, then the DTC fails.	Propulsion Bus Voltage	Is less than 95 % or more than 105 % of high voltage battery pack voltage at 0.700 seconds from the start of contactor precharge	High Voltage Battery Voltage Sensor Propulsion Bus Voltage Sensor Propulsion Contactor Status RESS Heating Mode	Valid Valid Precharging OFF	Executed Once Per Precharge 0.700 seconds to fail less than 0.700 to pass	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Pilot Circuit Range/ Performance	P0CF4	<p>This diagnostic tests the integrity of the Charge Control Pilot circuit. There are two tests to ensure proper functioning of the pilot.</p> <p>Part A: Sets when control pilot percent voltage is above a threshold OR aux micro logic state is in HIGH state OR main micro logic state is in LOW state</p> <p>Part B: Sets when control pilot percent voltage is above a high threshold OR control pilot percent voltage is below a low threshold OR aux micro logic state is in LOW state OR main micro logic state is in HIGH state.</p> <p>It requires both Part A and Part B to pass in order to pass the diagnostic.</p>	<p><u>Part A:</u></p> <p>Control Pilot Normalized Voltage</p> <p>OR</p> <p>Aux Micro Logic State</p> <p>OR</p> <p>Main Micro Logic State</p> <p><u>Part B:</u></p> <p>Control Pilot Normalized Voltage</p> <p>OR</p> <p>Aux Micro Logic State</p> <p>OR</p> <p>Main Micro Logic State</p> <p>Note: Control Pilot Normalized Voltage=Charging System Control Pilot Voltage / Battery Voltage</p>	<p>> 0.03</p> <p>High</p> <p>Low</p> <p>> 0.55 OR < 0.30</p> <p>Low</p> <p>High</p>	<p>Global Diagnostic System Disable</p> <p>System Voltage</p> <p>Charge Cord State</p> <p><u>Part A:</u></p> <p>Control Pilot Diagnostic Switch State</p> <p>Vehicle Speed</p> <p><u>Part B:</u></p> <p>Control Pilot Diagnostic Switch State</p> <p>Control Pilot Charging Switch State</p> <p>Charging Ventilation Switch State</p>	<p>FALSE</p> <p>>= 10.20 V</p> <p>Not Connected</p> <p>Not Asserted</p> <p>> = 8.00 kph</p> <p>Asserted</p> <p>Open</p> <p>Open</p>	<p>30 failures out of 50 samples</p> <p>100ms per sample</p> <p>5 seconds</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Pilot Circuit Low	P0CF5	Monitors the control pilot signal for an out of range low condition.	Control Pilot Normalized Voltage Note: Control Pilot Normalized Voltage=Charging System Control Pilot Voltage / Battery Voltage	< 0.03	Global Diagnostic System Disable System Voltage Control Pilot Diag Switch Charge Cord State	FALSE >= 10.20 V Asserted Not Connected	30 failures out of 50 samples 100ms per sample 5 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Pilot Circuit High	P0CF6	Monitors the control pilot signal for an out of range high condition.	Control Pilot Normalized Voltage Note: Control Pilot Normalized Voltage=Charging System Control Pilot Voltage / Battery Voltage	> 0.55	Global Diagnostic System Disable System Voltage Charge Cord State Vehicle Speed	FALSE >= 10.20 V Not Connected >= 8.00 kph	30 failures out of 50 samples 100ms per sample 5 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Pilot Charging Switch Range/ Performance	P0CF9	Sets when the control pilot normalized voltage (percentage) is below a threshold or above a threshold	Control Pilot Normalized Voltage Note: Control Pilot Normalized Voltage=Charging System Control Pilot Voltage / Battery Voltage	< 0.14 OR > 0.28	Global Diagnostic System Disable System Voltage Control Pilot Diagnostic Switch Charge Cord State Control Pilot Circuit and Performance Diagnostics Control Pilot Charging Switch Range/ Performance Control Pilot Charging Ventilation Switch Range/ Performance	FALSE >= 10.20 V Closed Not Connected Completed this Key-Cycle Not Completed this Key- Cycle Not Completed this Key- Cycle	30 failures out of 50 samples 100ms per sample 5 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Pilot Charging Ventilation Switch Range/ Performance	P0D01	Sets when Control Pilot voltage is below a threshold or if it is above a threshold	Control Pilot Normalized Voltage Note: Control Pilot Normalized Voltage=Charging System Control Pilot Voltage / Battery Voltage	< 0.04 OR > 0.10	Global Diagnostic System Disable System Voltage Control Pilot Diagnostic Switch Charge Cord State Control Pilot Circuit and Performance Diagnostics Control Pilot Charging Switch Performance Control Pilot Charging Ventilation Switch Range/ Performance	FALSE >= 10.20 V Closed Not Connected Completed this Key-Cycle Completed this Key-Cycle Not Completed this Key- Cycle	30 failures out of 50 samples 100ms per sample 5 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charging System Positive Contactor Stuck Open	P0D09	The charging system positive contactor is used to connect the high voltage battery charger to the high voltage battery. This DTC diagnoses a stuck open positive charging contactor by monitoring for insufficient charger voltage during precharge.	Charger Voltage	< 10 Volts	Charger Contactor Precharge Contactor Propulsion Negative Contactor Charger Voltage Propulsion Negative Bus Voltage Propulsion Negative Bus Voltage	Closed Closed Open Not Faulted Not Faulted > 40 Volts	8 failures out of 9 samples 12.5ms / sample Executed once per charger precharge 112.5 ms	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charging System Positive Contactor Control Circuit	P0D0A	Diagnoses the Charging Contactor high side driver circuit for circuit faults.	The HPC2 detects that voltage is high during driver OFF state (indicates short to power or open circuit). It also detects that current is low during driver ON state (indicates open circuit).	Short to Power: Detected while OFF and output voltage is greater than the 12V battery voltage - 0.4V. Open Circuit: Detected while OFF and output voltage > 4V. Detected while ON and current sense feedback < 194 mA	12V Battery Voltage High Voltage Battery Current	> 10.2V < 999 amps	40 failures out of 50 samples 12.5 ms /sample 625 ms	Two Trips, Type B

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Hybrid/EV System Precharge Time Too Long	P0D26	The precharge contactor is used to bring two high voltage circuits to the same voltage so that the charge contactors are prevented from damage prior to closing of the charge contactors. This DTC sets if the Charge Bus Voltage does not get within a percentage band of high voltage battery voltage within a calibratable amount of time during the precharge. If the amount of time expires without reaching the required voltage, then the DTC fails.	Charger Bus Voltage	Is less than 95 % or more than 105 % of high voltage battery pack voltage at 0.700 seconds from the start of contactor precharge	High Voltage Battery Voltage Sensor Charger Voltage Sensor Charger Contactor Status OR Propulsion Contactor Staus	Valid Valid Precharging Precharging	Executed Once Per Precharge 0.700 seconds to fail less than 0.700 to pass	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Input AC Voltage Sensor Rationality	P0D3E	Sets when the AC charger input voltage sensor signal is outside a duty cycle threshold window when above a vehicle speed threshold.	AC Charger Input Voltage Sensor Duty Cycle	>= 12.00 OR <= 8.00	Global Diagnostic System Disable	FALSE	60 failures out of 80 samples	Type B, 2 Trips
					System Voltage	>= 10.20 V	25ms per sample	
					Charger Enable Mask	TRUE	2 seconds	
					AC Input Voltage Sensor OORH	Not Fault Active		
					AC Input Voltage Sensor OORL	Not Fault Active		
					Vehicle Speed Valid	TRUE		
					Vehicle Speed	>= 6.00 kph		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Input Voltage Sensor Circuit Low	P0D3F	Monitors the AC charger input voltage sensor for an out of range low condition	AC Charger Input Voltage Sensor Duty Cycle	<= 8.00 AND > 0.00	Global Diagnostic System Disable	FALSE	30 failures out of 40 samples	Type B, 2 Trips
			OR		System Voltage	>= 10.20 V	25ms per sample	
			AC Charger Input Voltage Sensor Duty Cycle	= 100.00	Charger Enable Mask	TRUE	1 second	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Input Voltage Sensor Circuit High	P0D40	Monitors the AC charger input voltage sensor signal for an out of range high condition	AC Charger Input Voltage Sensor Duty Cycle	≥ 92.00 AND < 100.00	Global Diagnostic System Disable	FALSE	30 failures out of 40 samples	Type B, 2 Trips
			OR		System Voltage	≥ 10.20 V	25ms per sample	
			AC Charger Input Voltage Sensor Duty Cycle	$= 0.00$	Charger Enable Mask	TRUE	1 second	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger DC Output Voltage Rationality	P0D4D	Sets when the difference between DC charger output voltage signal and battery DC input voltage signal is above a threshold.	abs[Charger DC Output Sensor Voltage - Battery DC Voltage]	> 30.00	Global Diagnostic System Disable	FALSE	60 failures out of 80 samples	Type B, 2 Trips
					System Voltage	>= 10.20 V	25ms per sample	
					Charger Enable Mask	TRUE	2 seconds	
					Charger DC Output Voltage Sensor OORH	Not Fault Active		
					Charger DC Output Voltage Sensor OORL	Not Fault Active		
					Battery Voltage Sensor	Not Fault Active		
					Charging Ready	TRUE		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Hybrid/EV Battery Output Voltage Sensor Circuit Low	P0D4E	Monitors the charger output voltage sensor signal for an out of range low condition	DC Charger Output Voltage Sensor Duty Cycle OR DC Charger Output Voltage Sensor Duty Cycle	<= 8.00 AND > 0.00 = 100.00	Global Diagnostic System Disable System Voltage Charger Enable Mask	FALSE >= 10.20 V TRUE	30 failures out of 40 samples 25ms per sample 1 second	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Hybrid/EV Battery Output Voltage Sensor Circuit High	P0D4F	Monitors the charger output voltage sensor signal for an out of range high condition	DC Charger Output Voltage Sensor Duty Cycle OR DC Charger Output Voltage Sensor Duty Cycle	>= 92.00 AND < 100.00 = 0.00	Global Diagnostic System Disable System Voltage Charger Enable Mask	FALSE >= 10.20 V TRUE	30 failures out of 40 samples 25ms per sample 1 second	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Proximity Detection Circuit Low	P0D58	Sets when Proximity Detection Circuit Voltage is below a threshold	Proximity Detection Circuit Voltage	< 4.20 V	Global Diagnostic System Disable	FALSE	240 failures out of 400 samples	Type A, 1 Trips
					System Voltage	>= 10.20 V	12.5ms per sample	
					Vehicle Speed	> 20.00 kph	5 seconds	
					Shift Lever Position	Not in Park		
					Vehicle Speed Valid	TRUE		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Proximity Detection Circuit High	P0D59	Sets when Proximity Detection Circuit Voltage is above a threshold	Proximity Detection Circuit Voltage	> 4.80 V	Global Diagnostic System Disable System Voltage Vehicle Speed Shift Lever Position Vehicle Speed Valid	FALSE >= 10.20 V > 20.00 kph Not in Park TRUE	240 failures out of 400 samples 12.5ms per sample 5 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Output Power Performance	P0D5C	Sets when the output power of the charger is below an efficiency threshold	AC Charger Efficiency	<p>< Fail threshold (see supporting table) P0D5C Fail Threshold</p> <p>Charger efficiency is less than a threshold value, which is 67% times the nominal charger efficiency as a function of Power Electronics Coolant Loop temperature and AC input power.</p>	<p>Global Diagnostic System Disable</p> <p>System Voltage</p> <p>Charger Enable Mask</p> <p>Propulsion System Active</p> <p>Power Electronics Coolant Loop Temperature</p> <p>Power Electronics Coolant Loop Temperature</p> <p>DC Battery Voltage</p> <p>Processed DC Charger Output Voltage</p> <p>Current Control Ready</p> <p>Maximum Current Control Ready Time</p> <p>Diagnostic Failed Since Reset</p> <p>Diagnostic Passed Since Reset</p> <p>Charge Power Level</p> <p>Battery Current Sensor Status</p> <p>Thermal Mode Status</p>	<p>FALSE</p> <p>>= 10.20 V</p> <p>TRUE</p> <p>FALSE</p> <p>< 65.00 C (re-enables below 60.00 C if this threshold is crossed)</p> <p>> -12.00 C (re-enables above -7.00 C if this threshold is crossed)</p> <p>Not Fault Active</p> <p>Not Fault Active</p> <p>TRUE</p> <p><= 40.00 s</p> <p>FALSE</p> <p>FALSE</p> <p>= AC Level 1 or AC Level 2</p> <p>VALID</p> <p>= Bypass Engage</p>	<p>320 failures out of 400 samples</p> <p>25ms per sample</p> <p>10 seconds</p>	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Commanded Input Power Minimum Current Control Control Delay Time	> 600.00 W > 13.00 s		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Hybrid/EV System Discharge Time Too Long	P0D5E	Discharging of high voltage circuits to voltage levels below 60 volts is necessary for safety purposes. This DTC can set two ways. First, this DTC sets if the Charger Bus Voltage does not fall below a calibratable voltage within a calibratable amount of time during a charger discharge. If the amount of time expires without reaching the required voltage, then the DTC fails. Second, this DTC sets if the charger voltage sensor is faulted and the propulsion negative bus voltage is faulted or the negative propulsion contactor is stuck closed. This second fail criteria is necessary in cases where there has been a loss of safety critical information. This DTC latches for safety reasons and further charging and propulsion are disabled until service is performed.	Charger Voltage	>= 60 V	Negative Contactor	Open	Executed Once	One Trip, Type A
					Charger Contactor	Open	Per any contactor (except precharge contactor) transitioning from closed to open	
					DTC Not Active	P0D5E		
				12V Battery Maintenance Mode	OFF		< 4 seconds to pass	
			Charger Voltage			Not Faulted	4 seconds to fail	
			Charger Voltage	Faulted	Negative Contactor	Open		
			AND		Charger Contactor	Open		
			[Propulsion Negative Bus Voltage	Faulted	DTC Not Active	P0D5E		
			OR		12V Battery Maintenance Mode	OFF		
			Propulsion Negative Contactor]	Faulted (Stuck Closed only)	Charger Voltage	Not Faulted		
							4 seconds to fail	
			DTC Clear	Must Send CPID	0x7E4 07 AE 32 02 02		Cannot Pass Case 2	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Motor Voltage Sensor Performance	P0D69	The purpose of the Compressor Voltage Sensor performance diagnostic is to detect and report a failure of the sensor when rationalized with Vehicle High Voltage Battery Voltage sensor. If the enable criteria are met and the voltage difference of the compared sensors is greater than the calibrated threshold, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL, and if not it will report a PASS.	<p>ABS (High Voltage Battery Cell Voltage - Compressor Sensed Input Voltage*)</p> <p>* Compressor Sensed Input Voltage is transmitted by the compressor over HS GMLAN bus to the Host controller</p>	> 30.00 V	<p>No Active Run/Crank DTCs:</p> <p>No Active Loss of Communication DTCs:</p> <p>System Voltage</p> <p>(Accessory ON Signal OR Run Crank Active Signal) for time</p> <p>No active Compressor Voltage Sensor Circuit DTCs:</p> <p>No active High Voltage Battery DTCs:</p> <p>No Active High Voltage Contactor DTCs:</p> <p>Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value</p> <p>High Voltage Positive, Negative and Charging Contactors for time</p>	<p>P2534, P2535</p> <p>U016B</p> <p>> 10.20 V</p> <p>= True</p> <p>= True</p> <p>> 1.00 s</p> <p>P0D6A, P0D6B</p> <p>P0ABB, P0ABC, P0ABD, (U0111 AND U185A)</p> <p>P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3</p> <p>Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)</p> <p>= Closed</p> <p>≥ 1.00 s</p>	32.00 fail counts out of 40.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Motor Voltage Sensor Circuit High	P0D6A	This diagnostic detects if the Compressor HV Voltage sensor has an out of range high circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range high fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor High Voltage Input Voltage Value	> 527.25 V	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs: No Active Loss of Comm DTCs: (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Motor Voltage Sensor Circuit Low	P0D6B	This diagnostic detects if the Compressor HV Voltage sensor has a out of range low circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range low fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor High Voltage Input Voltage Value	< 27.75 V	<p>Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value</p> <p>High Voltage Positive, Negative and Charging Contactor for time</p> <p>System Voltage</p> <p>No Active Run/Crank DTCs:</p> <p>No Active Loss of Comm DTCs:</p> <p>No Active High Voltage Contactor DTCs:</p> <p>(Accessory On Signal OR Run Crank Active Signal) for time</p>	<p>Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)</p> <p>= Closed</p> <p>> 1.00 sec</p> <p>> 10.20 V</p> <p>P2534, P2535</p> <p>U016B</p> <p>P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3</p> <p>= True</p> <p>= True > 1.00 s</p>	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

[illegible]

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module Internal Temperature Sensor Circuit High	P0D72	This diagnostic detects if the Compressor CPU temperature sensor has an out of range high circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range high fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor CPU Temperature Sensor Value	< -40 degC	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module Internal Temperature Sensor Circuit Low	P0D73	This diagnostic detects if the Compressor CPU Temperature sensor has a out of range low circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range low fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor CPU Temperature Sensor Value	> 150 degC	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

[illegible]

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module Output Driver Temperature Sensor Circuit High	P0D77	This diagnostic detects if the Compressor IGBT temperature sensor has a out of range high circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range high fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor IGBT Temperature Sensor Value	< -40 degC	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module Output Driver Temperature Sensor Circuit Low	P0D78	This diagnostic detects if the Compressor IGBT temperature sensor has a out of range low circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range low fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor IGBT Temperature Sensor Value	> 150 degC	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Enable Circuit	P0E61	Monitors the charger 12V enable circuit for a faulted condition	Enable Line Hardware I/O fault Flag	TRUE	Global Diagnostic System Disable	FALSE	30 failures out of 40 samples	Type B, 2 Trips
					System Voltage	>= 10.20 V	25ms per sample	
					Enable Line Hardware I/O fault Flag	Not Indeterminate	1 second	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Control Circuit	P0E65	Monitors the charger control circuit for a faulted condition	Command Line Hardware I/O fault Flag	TRUE	Global Diagnostic System Disable	FALSE	30 failures out of 40 samples	Type B, 2 Trips
					System Voltage	>= 10.20 V	25ms per sample	
					Charger Enable Mask	TRUE	1 second	
					Command Line Hardware I/O fault Flag	Not Indeterminate		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

[illegible]

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan Signal Circuit Low	P148B	This diagnostic detects if the cooling fan has an out of range low circuit fault. If the enable criteria are met and the pulse width modulation input signal is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	HWIO pulse width modulation duty cycle from ECM	< 3.00 %	System Voltage	> 10.20 V	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Cooling Fan Signal Circuit High	P148C	This diagnostic detects if the cooling fan has an out of range high circuit fault. If the enable criteria are met and the pulse width modulation input signal is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	HWIO pulse width modulation duty cycle from ECM	> 97.00 %	System Voltage Propulsion system active OR (Propulsion system active AND Energy storage system thermal condition request AND Engine Cooling fan operation enable)	> 10.20 V = True for > 43.00 s = False = ActiveCool = True for > 43.00 s	16.00 fails / 20.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Motor Input Current - Positive Contactor State Not Plausible	P154F	The purpose of the rationality diagnostic is to detect and report a failure of the Compressor Current Sensor when the feedback current value transmitted by the compressor is not correct for its operating conditions. If the enable criteria are met and if the current sensor reading is outside the calibrated threshold for the given operating condition, the fail counter will be incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS	Case 1 - HV Battery Contactors Open (Motor Not spinning) Compressor Electrical Current* *Measured and Reported by the compressor over serial GMLAN bus	< -1.00 A OR > 1.00 A	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time No Active Compressor Sensor DTCs: No Active HSRP Sensor DTCs: No active High Voltage Battery DTCs: No Active High Voltage Contactor DTCs: Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value Time elapsed since High Voltage Contactors (Positive, Negative, Charging) Opened or Closed High Voltage Positive, Negative and Charge Contactors	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s P1F0C, P1F0D, P0D69, P0D6A, P0D6B, P15CA, P1F0A P0532, P0533 P0ABB, P0ABC, P0ABD, (U0111 AND U185A) P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3 Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 1.00 s = Open	32.00 fails / 40.00 samples at 250ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			<p>Case 2 - HV Battery Contactors Closed and Compressor Motor Commanded OFF (0 RPM Speed Requested)</p> <p>Compressor Electrical Current*</p> <p>*Measured and Reported by the compressor over serial GMLAN bus</p>	<p>< -1.00 A OR > 1.00 A</p>	<p>No Active Run/Crank DTCs:</p> <p>No Active Loss of Communication DTCs:</p> <p>System Voltage (Accessory On Signal OR Run Crank Active Signal) for time)</p> <p>No Active Compressor Sensor DTCs:</p> <p>No Active HSRP Sensor DTCs:</p> <p>No active High Voltage Battery DTCs:</p> <p>No Active High Voltage Contactor DTCs:</p> <p>Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value</p> <p>Time elapsed since High Voltage Contactors (Positive, Negative, Charging) Opened or Closed</p> <p>{{(Compressor Speed Feedback</p>	<p>P2534, P2535</p> <p>U016B</p> <p>> 10.20 V</p> <p>= True</p> <p>= True > 1.00 s</p> <p>P1F0C, P1F0D, P0D69, P0D6A, P0D6B, P15CA, P1F0A</p> <p>P0532, P0533</p> <p>P0ABB, P0ABC, P0ABD, (U0111 AND U185A)</p> <p>P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3</p> <p>Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)</p> <p>> 1.00 s</p> <p>< 60.00 RPM</p>	<p>32.00 fails / 40.00 samples at 250ms</p>	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					OR Climate Control HV Device Shutdown Command) AND High Voltage Positive, Negative and Charge Contactors}	= True = Closed		
			Case 3 - HV Battery Contactors Closed and Compressor Commanded ON (Motor Spinning) Compressor Electrical Current* *Measured and Reported by the compressor over serial GMLAN bus	< 0.20 A OR > 27.00 A	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time No Active Compressor Sensor DTCs: No Active HSRP Sensor DTCs: No active High Voltage Battery DTCs: No Active High Voltage Contactor DTCs: Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s P1F0C, P1F0D, P0D69, P0D6A, P0D6B, P15CA, P1F0A P0532, P0533 P0ABB, P0ABC, P0ABD, (U0111 AND U185A) P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3 Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	32.00 fails / 40.00 samples at 250ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Time elapsed since High Voltage Contactors (Positive, Negative, Charging) Opened or Closed High Side Refrigerant Pressure in range AND HV Battery Voltage in range AND Compressor Speed Feedback in range AND High Voltage Positive, Negative and Charge Contactors	> 1.00 s 200.00 kPa < HSRP < 2,300.00 kPa 300.00 V < HVBattVolt < 410.00 V 1,000.00 RPM < CompSpeed < 8,600.00 RPM = Closed		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Ignition Switch Run/ Start Position Circuit Low	P15B9	This diagnostic detects if the hardwired Run/Crank wakeup circuit to the Compressor is stuck Low. If the enable criteria are met and the instantaneous Run/Crank hardwire status reported by the compressor does not match the Host Controller's internal status of the Run/Crank terminal, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor Run Crank Hardwire Signal status *Reported by Compressor over HS GMLAN interface	= False	[No Active Run/Crank DTCs AND No Active Loss of Comm DTCs AND System Voltage AND Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value AND Run Crank Active Signal] for time	P2534, P2535 U016B > 10.20 V Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) = True > 2.00 sec	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Ignition Switch Run/ Start Position Circuit High	P15BA	This diagnostic detects if the hard wired Run/Crank wakeup circuit to the Compressor is stuck High. If the enable criteria are met and the Run/Crank hardwire instantaneous status reported by the compressor does not match the Host Controller's internal status of the Run/Crank terminal, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor Run Crank Hardwire Signal status *Reported by Compressor over HS GMLAN interface	= True	[No Active Run/Crank DTCs AND No Active Loss of Comm DTCs AND System Voltage AND Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value AND Run Crank Active Signal AND Accessory On Signal] for time	P2534, P2535 U016B > 10.20 V Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) = False = True > 2.00 sec	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve A Position Sensor Circuit Range/ Performance - Unexpected Position Change Detected	P15C5	This diagnostic detects if the valve position feedback has drifted out of commanded position when the valve should not be moving. If the enable criteria are met and the feedback has drifted from the commanded position greater than a calibrated threshold value then the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve feedback position	> 3.00 % from valve commanded position	Propulsion System Active System Voltage No Active Valve DTCs Valve Control Command	= True > 10.20 V P2682, P2683, P26AD, P26AE, P26A6, P26A7, P26A9, P26A5 = Stop	80 fails / 100 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Signal Message Counter Incorrect	P15C8	This diagnostic detects when the Compressor Data Packet Alive Rolling Count serial data signal received by the host controller from the compressor is not being updated. Each GMLAN message transmitted by the compressor contains an incrementing counter value (0, 1, 2, 3, 0..) known as Alive Rolling Count. Host Controller performs instantaneous evaluation on each received message to check that the rolling counts are incrementing in sequence. If an error is determined, the instantaneous fail counter is incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value	Message Rolling Count value \neq Mod4(Previous Message Rolling Count value +1)	System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	> 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Status Message Counter Incorrect	P15C9	This diagnostic detects when the Compressor Device State Packet Alive Rolling Count serial data signal received by the host controller from the compressor is not being updated. Each GMLAN message transmitted by the compressor contains an incrementing counter value (0, 1, 2, 3, 0..) known as Alive Rolling Count. Host Controller performs instantaneous evaluation on each received message to check that the rolling counts are incrementing in sequence. If an error is determined, the instantaneous fail counter is incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Serial Communication message \$22E: Compressor Device State Packet Alive Rolling Count index value	Message Rolling Count value \neq Mod4(Previous Message Rolling Count value +1)	System Voltage No Active Run/Crank DTCs: No Active Loss of Comm DTCs: (Accessory On Signal OR Run Crank Active Signal) for time	> 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Sensor Signal Message Counter Incorrect	P15CA	This diagnostic detects when the Compressor Sensor Data Packet Alive Rolling Count serial data signal received by the host controller from the compressor is not being updated. Each GMLAN message transmitted by the compressor contains an incrementing counter value (0, 1, 2, 3, 0..) known as Alive Rolling Count. Host Controller performs instantaneous evaluation on each received message to check that the rolling counts are incrementing in sequence. If an error is determined, the instantaneous fail counter is incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Serial Communication message \$222: Compressor Sensor Data Packet Alive Rolling Count index value	Message Rolling Count value \neq Mod4(Previous Message Rolling Count value +1)	System Voltage No Active Run/Crank DTCs: No Active Loss of Comm DTCs: (Accessory On Signal OR Run Crank Active Signal) for time	> 10.20 V P2534, P2535, U016B U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Sensor Status Message Counter Incorrect	P15CB	This diagnostic detects when the Compressor Sensor State Packet Alive Rolling Count serial data signal received by the host controller from the compressor is not being updated. Each GMLAN message transmitted by the compressor contains an incrementing counter value (0, 1, 2, 3, 0..) known as Alive Rolling Count. Host Controller performs instantaneous evaluation on each received message to check that the rolling counts are incrementing in sequence. If an error is determined, the instantaneous fail counter is incremented. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value	Message Rolling Count value \neq Mod4(Previous Message Rolling Count value +1)	System Voltage No Active DTCs: (Accessory On Signal OR Run Crank Active Signal) for time	> 10.20 V P2534, P2535, U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Wake-up Circuit Performance	P16B7	This diagnostic detects if the hardwired Accessory wakeup circuit to the Compressor is stuck Low. If the enable criteria are met and the Accessory hardwire instantaneous status reported by the compressor does not match the Host Controller's internal status of the Accessory terminal, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor Accessory Wakeup Hardwire Signal status *Reported by Compressor over HS GMLAN bus interface	= False	[No Active Loss of Comm DTCs AND Accessory On Signal AND System Voltage AND Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value] for time	U016B = True > 10.20 V Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 2.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Random Access Memory (RAM) Error	P16B8	The purpose of the RAM diagnostic is to detect and report a failure or error on RAM portion of the memory which is embedded inside the compressor's internal microcontroller chip. A Pattern Read/Write error detection routine is performed by the compressor microcontroller at every boot-up. The Host Controller monitors the instantaneous status reported by the compressor. If the enable criteria are met and a RAM fault is detected, the diagnostic will report a FAIL, and if not, it will report a PASS.	RAM Read/Write Error State (This RAM self-check routine is performed by compressor's internal microcontroller as part of the bootup routine. Evaluated error state is transmitted by the compressor over GMLAN bus to the host controller)	= Fault	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$22E: Compressor Device State Packet Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	At Compressor Bootup	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Read Only Memory (ROM) Error	P16B9	The purpose of the ROM diagnostic is to detect and report a failure or error on the Read-Only portion of the memory which is embedded inside the compressor's internal microcontroller chip. A Checksum error detection routine is performed by the compressor microcontroller at every boot-up. The Host Controller monitors the instantaneous status reported by the compressor. If the enable criteria are met and a ROM fault is detected, the diagnostic will report a FAIL, and if not, it will report a PASS.	ROM Checksum Error State (This ROM Checksum routine is executed by compressor's internal microcontroller as part of the bootup routine. Evaluated error state is transmitted by the compressor over GMLAN bus to the host controller)	= Fault	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$22E: Compressor Device State Packet Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True OR = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	At Compressor Bootup	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Control Module Keep Alive Memory (KAM) Error	P16BA	The purpose of the KAM diagnostic is to detect and report a failure or error on the Electrically Erasable Programmable Read-Only Memory (EEPROM) Integrated Circuit component located on the compressor's internal circuit board. A Checksum error detection routine is performed by the compressor microcontroller at every boot-up. The Host Controller monitors the instantaneous status reported by the compressor. If the enable criteria are met and a ROM fault is detected, the diagnostic will report a FAIL, and if not, it will report a PASS.	EEPROM Checksum Error state (This EEPROM Checksum routine is executed by compressor's internal microcontroller as part of the bootup routine. Evaluated error state is transmitted by the compressor over GMLAN bus to the host controller)	= Fault	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$22E: Compressor Device State Packet Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	At Compressor Bootup	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Pump Feedback Circuit High Voltage	P19FD	This diagnostic detects if the feedback speed is out of range high. If the enable criteria are met and the feedback speed read is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Pump Feedback Frequency	≥ 750.00 Hz	System Voltage System Voltage Coolant Pump Enable Pump control commanded speed Diagnostics enable delay time	> 10.20 V = TRUE $11.00\% < \text{PWM} < 90.00\%$ > 3.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Pump Feedback Circuit Low Voltage	P19FE	This diagnostic detects if the feedback speed is out of range low. If the enable criteria are met and the feedback speed read is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Pump Feedback Frequency	0.00 <= Hz <= 8.60	System Voltage System Voltage Coolant Pump Enable Pump control commanded speed Diagnostics enable delay time	> 10.20 V = TRUE 11.00 %< PWM < 90.00 % > 3.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Coolant Pump Feedback Circuit Performance	P19FF	The purpose of the performance diagnostic is to detect and report a failure of the component. If the enable criteria are met, the difference between the commanded speed to the component feedback speed is calculated. The speed difference is filtered and when the difference exceeds the calibrated fault threshold, the diagnostic reports a FAIL. If filtered speed difference does not exceed the calibrated fault threshold, the diagnostic reports a PASS. The diagnostic will continue to report as long as the enablement criteria are met. For the pump non-actuated state, if the feedback speed exceeds the calibrated fault threshold, the diagnostic reports a FAIL. If feedback speed does not exceed the calibrated fault threshold, the diagnostic reports a PASS. The diagnostic will continue to report as long as the	Coolant Pump Feedback performance fail in actuated state: Filtered (command speed - feedback speed) OR Filtered (command speed - feedback speed)	RESS Pump Feedback Fault low <Threshold RESS Pump Feedback Fault high >Threshold	System VoltageSystem Voltage Coolant Pump Enable Pump control commanded speed Diagnostics enable delay time No Active DTCs (RESS Pump) No Active DTCs (Inlet Temperature Sensor) RESS Coolant Inlet temperature	> 10.20 V = TRUE 11.00 % < DC < 90.00 % > 5.00 s P1E8C, P1E8D, P0C47, P19FD, P19FE P0C43, P0C44, P0C45, -20.00 °C < RESS inlet temp < 9,999.00 °C	Up To 257 s	Type B, 2 Trips
			Coolant Pump Feedback performance fail in non-actuated state: Pump feedback RPM	> 250.00	System VoltageSystem Voltage Coolant Pump Enable No Active DTC from atuated state	> 10.20 V = FALSE for 10.00 sec P19FF	80.00 fails / 100.00 samples at 100ms	
			Coolant Pump Feedback performance repass in actuated state: Filtered (command speed - feedback speed) AND Filtered (command speed - feedback speed)Coolant Pump Feedback signal is not functioning as	RESS Pump Feedback Repass <High Threshold RESS Pump Feedback Repass >Low Threshold	System VoltageSystem Voltage Coolant Pump Enable Pump control commanded speed Diagnostics enable delay time No Active DTCs (RESS Pump)	> 10.20 V = TRUE 11.00 % < DC < 90.00 % > 5.00 s P1E8C, P1E8D, P0C47, P19FD, P19FE	Up To 547 s	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		enablement criteria are met.	intended in actuated state:		No Active DTCs (Inlet Temperature Sensor) RESS Coolant Inlet temperature Coolant Pump Enable Diagnostics enable delay time	P0C43, P0C44, P0C45, -20.00 °C < RESS inlet temp < 9,999.00 °C = FALSE > 10.00 s		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AA Circuit Range/ Performance	P1B16	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AB Circuit Range/ Performance	P1B19	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AC Circuit Range/ Performance	P1B1C	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AD Circuit Range/ Performance	P1B1F	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AE Circuit Range/ Performance	P1B22	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AF Circuit Range/ Performance	P1B25	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AG Circuit Range/ Performance	P1B45	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AH Circuit Range/ Performance	P1B48	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AI Circuit Range/ Performance	P1B4B	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AJ Circuit Range/ Performance	P1B4E	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AK Circuit Range/ Performance	P1B51	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AL Circuit Range/ Performance	P1B54	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AM Circuit Range/ Performance	P1B57	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AN Circuit Range/ Performance	P1B5A	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AO Circuit Range/ Performance	P1B5D	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AP Circuit Range/ Performance	P1B60	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AQ Circuit Range/ Performance	P1B63	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AR Circuit Range/ Performance	P1B66	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AS Circuit Range/ Performance	P1B69	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AT Circuit Range/ Performance	P1B6C	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AU Circuit Range/ Performance	P1B6F	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AV Circuit Range/ Performance	P1B72	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AW Circuit Range/ Performance	P1B75	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AX Circuit Range/ Performance	P1B78	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AY Circuit Range/ Performance	P1B7B	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AZ Circuit Range/ Performance	P1B7E	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BA Circuit Range/ Performance	P1B81	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BB Circuit Range/ Performance	P1B84	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BC Circuit Range/ Performance	P1B87	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BD Circuit Range/ Performance	P1B8A	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BE Circuit Range/ Performance	P1B8D	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BF Circuit Range/ Performance	P1B90	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BG Circuit Range/ Performance	P1B93	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BH Circuit Range/ Performance	P1B96	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BI Circuit Range/ Performance	P1B99	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BJ Circuit Range/ Performance	P1B9C	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BK Circuit Range/ Performance	P1B9F	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BL Circuit Range/ Performance	P1BA2	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BM Circuit Range/ Performance	P1BA5	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BN Circuit Range/ Performance	P1BA8	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BO Circuit Range/ Performance	P1BAB	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BP Circuit Range/ Performance	P1BAE	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BQ Circuit Range/ Performance	P1BB1	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BR Circuit Range/ Performance	P1BB4	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BS Circuit Range/ Performance	P1BB7	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BT Circuit Range/ Performance	P1BBA	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BU Circuit Range/ Performance	P1BBD	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BV Circuit Range/ Performance	P1BC0	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BW Circuit Range/ Performance	P1BC3	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BX Circuit Range/ Performance	P1BC6	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BY Circuit Range/ Performance	P1BC9	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BZ Circuit Range/ Performance	P1BCC	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CA Circuit Range/ Performance	P1BCF	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CB Circuit Range/ Performance	P1BD2	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CC Circuit Range/ Performance	P1BD5	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CD Circuit Range/ Performance	P1BD8	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CE Circuit Range/ Performance	P1BDB	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CF Circuit Range/ Performance	P1BDE	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CG Circuit Range/ Performance	P1BE1	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CH Circuit Range/ Performance	P1BE4	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CI Circuit Range/ Performance	P1BE7	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CJ Circuit Range/ Performance	P1BEA	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CK Circuit Range/ Performance	P1BED	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CL Circuit Range/ Performance	P1BF0	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CM Circuit Range/ Performance	P1BF3	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CN Circuit Range/ Performance	P1BF6	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CO Circuit Range/ Performance	P1BF9	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CP Circuit Range/ Performance	P1BFC	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CQ Circuit Range/ Performance	P1E01	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CR Circuit Range/ Performance	P1E04	Rationality compares cell voltage to movement of other cell voltages	Individual Cell voltage movement	Not in same direction as the Average Cell Voltage Movement OR < 0.005 V	CellVoltageRationalityFA (see Fault Bundle Page) Average Cell Voltage Movement No active DTCs:	= FALSE > 0.022 V U185A	7 seconds out of a 8 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Pump Enable Circuit Low	P1E8C	This diagnostic detects if the host controller has detected an STG fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Coolant Pump Enable line Current	>0.6A	System Voltage HWIO Pump Control Circuit Status Coolant Pump Enable	> 10.20 V ≠ Indeterminate = TRUE	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

[illegible]

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Hybrid/EV Battery Cell Overvoltage	P1EAB	Voltage too highDTC Clear	Cell Voltage OR Any BECM response to HPC2 request to NOT test overvoltage signal/circuit (assert line logic-level- high).	> 4.5 V = Overvoltage Signal/ Circuit line logic-level- low	No active DTC's: System Voltage RUN/CRANK Transitions to Charger contactor Status CellVoltageRationalityFA (see Fault Bundle Page) Inverter voltage System Voltage No active DTC's: Must Send CPID	(U185A AND U0111) >10.2V = ON for > 5 s = Open = FALSE > 312.00 V >10.2 V (U185A AND U0111) 0x7E4 07 AE 32 0C 0C 00 00 00	2 seconds out of a 2.5 seconds window 10 seconds out of a 10 seconds window	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.					
Hybrid/EV Battery Cell Overvoltage Signal/ Circuit Performance	P1EAC	Over voltage circuit 2nd protection - Fault Flag Test	Any BECM response to HPC2 request to test overvoltage signal/circuit (assert line logic-level- low).	= Overvoltage Signal/ Circuit line logic-level- high	RUN/CRANK Transitions to	= ON for > 5 s	5 seconds out of a 5 seconds window	One Trip, Type A					
					Charger contactor Status	= Open							
					CellVoltageRationalityFA (see Fault Bundle Page)	= FALSE							
					Inverter voltage	> 312.00 V							
					System Voltage	> 10.2V							
					No active DTC's:	(U185A AND U0111)							
		Test Active Stuck OnTest Active Stuck Off	OR	BECM overvoltage signal/ circuit test response.	= Test Active	HPC2 overvoltage signal/ circuit test request to BECM.	= Cease Test		10 seconds out of a 10 seconds window				
						System Voltage	> 10.2V						
						No active DTC's:	(U185A AND U0111)						
						OR	BECM overvoltage signal/ circuit test response.			= Not Test Active	HPC2 overvoltage signal/ circuit test request to BECM.	= Run Test	10 seconds out of a 10 seconds window
											System Voltage	> 10.2V	
											No active DTC's:	(U185A AND U0111)	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charging System Contactor(s) Stuck Open	P1EBD	This DTC determines if the charger system contactors have opened by comparing charger voltage to high voltage battery voltage during propulsion or charging.	Charger Voltage	< 80 % of High Voltage Battery Voltage	12V Battery Voltage Charger Contactor Negative Contactor Charger Voltage High Voltage Battery Voltage	> 10.2V Closed Closed Not Faulted Not Faulted	40 failures out of 50 samples, 12.5 ms /sample 625 ms	One Trip, Type A
			Charger Voltage	< 80 %of High Voltage Battery Voltage	12V Battery Voltage RESS Heating Mode Charger Contactor Negative Contactor OBCM Processed Charger Voltage High Voltage Battery Voltage	> 10.2V ON Closed Open Not Faulted Not Faulted	40 failures out of 50 samples, 12.5 ms /sample 625 ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery System Contactor(s) Stuck Open	P1EC0	This DTC determines if the propulsion system contactors have opened by comparing propulsion bus voltage to high voltage battery voltage during propulsion.	Propulsion Bus Voltage	< 80 % of High Voltage Battery Voltage	Propulsion Positive Contactor	Closed	6 failures out of 6 samples 12.5 ms /sample Continuous 75 ms	One Trip, Type A
					Negative Contactor	Closed		
					Charger Contactor	Closed		
					Propulsion Bus Voltage	Not Faulted		
					High Voltage Battery Voltage	Not Faulted		
					12V Battery Voltage	> 10.2V		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Heater Transistor Control Circuit/Open	P1EC3	This diagnostic detects if the host controller has detected an OPEN, STG or STV fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	When OFF: Heater Transistor Control Circuit OR Heater Transistor Control Circuit	>V_batt-0.4 V OR >3 V AND <100uA	System Voltage Heater control Commanded PWM	> 10.20 V 0.00 % <command< 100.00 %	20.00 fails / 40.00 samples at 100ms	Type B, 2 Trips
			When ON: Heater Transistor Control Circuit OR Heater Transistor Control Circuit	<160mOhms OR < 600mA	System Voltage Heater control Commanded PWM	> 10.20 V 0.00 % <command< 100.00 %	20.00 fails / 40.00 samples at 100ms	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Heater Performance	P1EC6	The purpose of the performance diagnostic is to detect and report a failure of the component. If the enable criteria are met, the diagnostic will control the pump and heater to calibrated values to induce heat into the system. If the temperature does not exceed the calibrated threshold with-in the calibrated time, the diagnostic reports a FAIL. If the temperature does exceed the calibrated threshold, the diagnostic reports a PASS.	Inlet Temperature sensor rise	Case: AC Compressor ON < 3.00 °C OR Case: AC Compressor OFF < 3.00 °C	PSA Mode Propulsion System Active Charge Mode Plugged in Charge System Voltage RESS Thermal Mode HV SOC No Active DTCs (RESS Coolent Level Sensor) RESS Inlet Temperature No Active DTCs (RESS Inlet Temperature Sensor) No Active DTCs (RESS Coolent Pump) No Active DTCs (RESS Heater Control) OAT Arbitrated Status Battery High/Medium Sevrerity Status High Voltage Battery voltage	Once per Drive cycle If diagnostic did not complete in charge OR Once per Drive Cycle If diagnostic did not complete in PSA AND > 10.20 V Active heat request > 5.00 % P1FFB, P1FFC, P1FFD, P1FFE < 20.00 Deg C P0C44, P0C45, P0C43 P19FE, P19FD, P19FF, P0C47, P1E8C, P1E8D P1EC3 = VALID None > 280.00 V	154.1 seconds to fail.	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					<p>Then overrides as follows:</p> <p>1. Comand pump and heater</p> <p>2. Command pump and heater</p> <p>3. Turn heater off Wait for temperature change</p>	<p>Pump 7.00 % DC and Heater DC 100.00 % for 4.10 s</p> <p>Heater DC based on battery voltage to input 30,600.00 kJ with heater resistance of 70.00 ohms for 90.00 s and and pump DC 7.00 %</p> <p><= 60.00 s with heater DC 0.00 %</p>		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
A/C Compressor Motor Speed Performance	P1F0A	The purpose of the performance diagnostic is to detect and report a failure of the compressor. If the compressor is commanded to run and other enable criteria are met, the difference between the commanded speed to the compressor's feedback speed is calculated. The speed difference is filtered and when the difference exceeds the calibrated fault threshold, the diagnostic reports a FAIL. If filtered speed difference does not exceed the calibrated fault threshold, the diagnostic reports a PASS. Compressor Speed Feedback is also diagnosed when the compressor is not being commanded to run. In this case, if the enable criteria are met, and the compressor feedback speed is greater than a calibrateable small number (0RPM), the diagnostic reports a FAIL. If speed feedback does not exceed the calibrated	<p>Case 1 - Monitor HV Compressor Motor Speed - Compressor Motor Commanded to Run Fail (Compressor commanded to run and not meeting requested speed)</p> <p>Compressor Speed Difference RPM Filtered Error</p> <p>OR</p> <p>Compressor Speed Difference RPM Filtered Error</p> <p>(Compressor Speed Difference RPM Filtered Error = Filtered difference between Commanded Speed and Feedback Speed)</p>	<p>> CompON_FaultHi</p> <p>< CompON_FaultLo</p> <p>(See supporting tables for the above threshold values)</p>	<p>ALL the following conditions are met for time:</p> <p>No Active Run/Crank DTCs:</p> <p>No Active Loss of Communication DTCs:</p> <p>System Voltage</p> <p>(Accessory On Signal OR Run Crank Active Signal) for time</p> <p>Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value</p> <p>Compressor Speed Request</p> <p>No Active HSRP Sensor DTCs:</p> <p>No Active High Voltage Battery DTCs:</p> <p>No Active High Voltage Contactor DTCs:</p> <p>Climate Control HV Device Shutdown</p>	<p>> 6.00 s</p> <p>P2534, P2535</p> <p>U016B</p> <p>> 10.20 V</p> <p>= True</p> <p>= True</p> <p>> 1.00 s</p> <p>Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)</p> <p>960.00 RPM < Speed Request < 8,600.00 RPM</p> <p>P0532, P0533</p> <p>P0ABB, P0ABC, P0ABD, (U0111 AND U185A)</p> <p>P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3</p> <p>= False</p>	<p>Continuous Check every 250ms</p> <p>(Fail time between 28s and 1700s depending on the severity of the problem. Speed error of higher magnitude will cause the diagnostic to fail quicker)</p>	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		fault threshold, the diagnostic reports a PASS.			Command Compressor Commanded to Run High Side Refrigerant Pressure Sensor Data High Voltage Battery Cell Voltage High Voltage Positive, Negative and Charging Contactor for time	= True < 2,800.00 kPa > 270.00 V = Closed > 1.00 s		
			Case 2 - Monitor HV Compressor Motor Speed - Compressor Motor Commanded to Run Repass Compressor Speed Difference RPM Filtered Error OR Compressor Speed Difference RPM Filtered Error (Compressor Speed Difference RPM Filtered Error = Filtered difference between Commanded Speed and Feedback Speed)	< CompON_RepassHi > CompON_RepassLo (See supporting tables for the above threshold values)	All of the following conditions are met for time: No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$222: Compressor Sensor Data Alive Rolling Count index value Compressor Speed	> 6.00 s P2534, P2535 U016B > 10.20 V = True = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) 960.00 RPM < Speed	Continuous Check every 250ms (Repass time between 896s and 2237s depending on the severity of the problem. Speed error of lesser magnitude will cause the diagnostic to Repass quicker)	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Request	Request < 8,600.00 RPM		
					No Active HSRP Sensor DTCs:	P0532, P0533		
					No Active High Voltage Battery DTCs:	P0ABB, P0ABC, P0ABD, (U0111 AND U185A)		
					No Active High Voltage Contactor DTCs:	P3061, P0C78, P0AD9, P0AA4, P0D5E, P1EC3		
					Climate Control HV Device Shutdown Command	= False		
					Compressor Commanded to Run	= True		
					High Side Refrigerant Pressure Sensor Data	< 2,800.00 kPa		
					High Voltage Battery Cell Voltage	> 270.00 V		
					High Voltage Positive, Negative and Charging Contactor for time	= Closed > 1.00 s		
			Case 3 - Monitor HV Compressor Motor Speed - Compressor Motor Commanded to Stop (If compressor has failed in ON state, then it is required to repass the ON case before running OFF monitor)		No Active DTC from Compressor ON Failure (Case 1) AND If any of the following conditions is met for time: Compressor Speed	P1F0A > 10.00 s < 959.00 RPM	32.00 fails / 40.00 samples at 250ms rate	

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Compressor Speed Feedback* *Transmitted by the compressor over High Speed GMLAN bus to the Host Controller	> 960.00 RPM	Request OR Climate Control High Voltage Device Shutdown Commanded	= True		

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module A/C Compressor Motor Current Feedback Circuit Low	P1F0C	This diagnostic detects if the Compressor Current sensor has an out of range Low circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range low fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor DC Link Current Sensor Value	< -3.29 A	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs: AND No Active Loss of Comm DTCs: (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module A/C Compressor Motor Current Feedback Circuit High	P1F0D	This diagnostic detects if the Compressor Current sensor has an out of range High circuit fault. If the enable criteria are met and compressor has detected an instantaneous out of range high fault on the sensor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Compressor DC Link Current Sensor Value	> 32.71 A	Serial Communication message \$22E: Compressor Sensor State Packet Alive Rolling Count index value System Voltage No Active Run/Crank DTCs AND No Active Loss of Comm DTCs Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Isolation / Impact Sensor Fault - Hybrid Battery System Contactors Open	P1F17	When the Air Bag Module detects that a crash has occurred, it requests the HPC2 to latch open all high voltage contactors for safety reasons. When the Air Bag Module is faulty and a high voltage isolation fault is present, for safety reasons it is assumed that a vehicle crash has occurred. This DTC detects when these faults have occurred and contactors are latched open for safety reasons.	Control Module Hybrid Battery Voltage System Isolation Fault (P1AF0,P1AF2, or P1E22)in HPC1	Active	Rollover or Airbag or Inertial Sensors Run/Crank	Not working ON	25 ms Once set, this DTC cannot pass. DTC passes when latch is not set.	One Trip, Type A
			Control Module Hybrid Battery Voltage System Isolation Fault (P1AF0,P1AF2, or P1E22)in HPC1	Active	Lost Communication with Inflatable Restraint Sensing and Diagnostic Module on Bus F (U184E) Run/Crank	Active ON	25 ms Once set, this DTC cannot pass. DTC passes when latch is not set.	
			Lost Comm with HPC1	Active	Lost Communication with Inflatable Restraint Sensing and Diagnostic Module on Bus F (U184E) Run/Crank	Active ON	25 ms Once set, this DTC cannot pass. DTC passes when latch is not set.	
			Lost Comm with HPC1	Active	Rollover or Airbag or Inertial Sensors Run/Crank	Not working ON	25 ms Once set, this DTC cannot pass. DTC passes when latch is not set.	
			DTC Clear	Must Send CPID	0x7E4 07 AE 32 01 01			

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Isolation/ Coolant Level Sensor Fault - Hybrid/EV Battery Charging System	P1FFF	This DTC checks the integrity of the charging system by monitoring if the battery pack is suffering from a low coolant level condition or if the battery pack has an isolation fault.	RESS Coolant Level Sensor Circuit Fault Active RESS Coolant Level Low Battery Isolation Status Active Isolation Circuit Fault Active	TRUE TRUE Isolation Test Failed TRUE			Diagnostic will fail as soon as any of the malfunction criteria transitions to their threshold value	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Control Circuit Low	P2682	This diagnostic detects if the host controller has detected a valve motor drive 1 STG fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve Motor Driver 1 HWIO Sense State	= LOW	System Voltage Valve	> 10.20 V Must be commanded to Low position	4 fails / 5 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Control Circuit High	P2683	This diagnostic detects if the host controller has detected a valve motor drive 1 STV fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve Motor Driver 1 HWIO Sense State	= HIGH	System Voltage Valve	> 10.20 V Must be Stopped or commanded to High position	16 fails / 20 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve A Position Sensor Circuit Range/ Performance	P26A5	This diagnostic detects if the valve position feedback has an in-range but invalid region circuit fault. If the enable criteria are met and the feedback position read is not within the calibrated regions, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve feedback has exceeded valid range - low end OR Valve feedback has exceeded valid range - high end	5.00 % < Feedback < 30.00 % 70.00 % < Feedback < 95.00 %	Propulsion System Active System Voltage No Active Valve DTCs	= True > 10.20 V P2682, P2683, P26AD, P26AE, P26A6, P26A7	80 fails / 100 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Position Sensor Circuit Low	P26A6	This diagnostic detects if the valve position feedback has an out of range low circuit fault. If the enable criteria are met and the feedback position is below a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve feedback voltage	< 5.00 % of reference voltage (0.25 V)	System Voltage	> 10.20 V	40 fails / 50 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Position Sensor Circuit High	P26A7	This diagnostic detects if the valve position feedback has an out of range high or an open circuit fault. If the enable criteria are met and the feedback position is above a calibrated threshold, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve feedback voltage	> 95.00 % of reference voltage (4.75 V)	System Voltage	> 10.20 V	40 fails / 50 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Position Sensor Stop/ Minimum Stop Performance	P26A9	<p>This performance diagnostic detects if the valve is stuck or an end position learn has failed. An open circuit fault on the valve motor circuit 1 or 2 will also cause valve learn fail. If the enable criteria are met then for each valve move command the commanded position is compared to the feedback position after a calibrated time has been exceeded. If the position difference is greater than a calibrated threshold value then a valve stalled flag is set.</p> <p>Upon valve stalled flag setting a second timer is used to allow a calibrated number of retries for the valve to get to commanded position. If the valve still fails to reach commanded position within a calibrated margin after the retry total time allowed calibrated threshold has been exceeded then a FAIL is reported, else a PASS is reported.</p>	<p>IF Valve has not reached its commanded position THEN attempt valve relearn</p> <p>IF Valve still does not reach its commanded position</p>	<p>< 15.00 s</p> <p>up to 3.00 times</p> <p>< 10.00 s</p>	<p>System Voltage</p> <p>No active Valve or ECT Sensor DTCs</p> <p>Propulsion System Active</p> <p>Engine Coolant Temperature OR Legislated Diagnostics Minimum Engine Coolant Temperature Reached Signal</p>	<p>> 10.20 V</p> <p>P2682, P2683, P26AD, P26AE, P26A6, P26A7, P0116, P0117, P0118, P0119</p> <p>Diag has not already run this key cycle</p> <p>= True</p> <p>> 58.00 °C</p> <p>= True</p>	up to 25.00 secs.	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Control Circuit 2 Low Voltage	P26AD	This diagnostic detects if the host controller has detected a valve motor drive 2 STG fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve Motor Driver 2 HWIO Sense State	= LOW	System Voltage Valve	> 10.20 V Must be commanded to High position	4 fails / 5 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Coolant Bypass Valve Control Circuit 2 High Voltage	P26AE	This diagnostic detects if the host controller has detected a valve motor drive 2 STV fault on the circuit. If the enable criteria are met and a fault is detected on the circuit, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Valve Motor Driver 2 HWIO Sense State	= HIGH	System Voltage Valve	> 10.20 V Must be Stopped or commanded to Low position	16 fails / 20 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Precharge Current Too High	P3061	This DTC sets if battery current remains over a threshold during precharge for a calibratable amount of time.	High Voltage Battery Current	> 3.00 Amperes	High Voltage Battery Current High Voltage Battery Voltage Contactor Status OR Charger Contactor Status	Not Faulted Not Faulted Precharging	7 consecutive failed samples 12.5 ms /sample 87.50 ms to Fail Successful Precharge to Pass	One Trip, Type A

18 OBDG01 HPC2 (VICM) - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Control Module Lost Communicati on with Hybrid Powertrain Control Module B	U1860	This diagnostic detects when there is a one-sided loss of communication on the HS GMLAN Bus where the Compressor is able to transmit but not receive serial data from the host controller. This function monitors the instantaneous status reported by the Compressor based on its internal processing of the CAN bus status. If GMLAN message \$236 has not been received by the compressor for more than 250ms, it will transmit a faulted message to the host controller. If the enable criteria are met and faulted message has been received from the compressor, the fail counter will increment. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Case 1 - DTC Fail Compressor Detected Loss of Communication with Host Controller (Fault detected by the compressor CAN Handler - Messages have not been received from the Host Controller for 250ms)	= True	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	40.00 fails / 50.00 samples at 100ms loop rate	Type B, 2 Trips
			Case 2 - DTC Pass Compressor Detected Loss of Communication with Host Controller (Compressor received CAN message from the Host controller-Status reported every 100ms by the compressor)	= False,	No Active Run/Crank DTCs: No Active Loss of Communication DTCs: System Voltage (Accessory On Signal OR Run Crank Active Signal) for time Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value	P2534, P2535 U016B > 10.20 V = True = True > 1.00 s Message Rolling Count value = mod4(Previous Message Rolling Count value + 1)	less than 40.00 fails / 50.00 samples at 100ms loop rate	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Internal Performance	P0A1F	VITM Software Watchdog	If Watchdog resets controller	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	N/A Immediate	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor Circuit Low	P0A9D	Sets when Temperature Sensor 1 falls below a threshold	Temperature Sensor 1	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor Circuit High	P0A9E	Sets when Temperature Sensor 1 falls above a threshold	Temperature Sensor 1	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Voltage Sense Circuit Low	P0ABC	If Pack side Voltage is below Threshold	Pack Voltage	< 24V (ADC Count < 197)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Pack Voltage >= 24V (ADC Count >= 197)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Voltage Sense Circuit High	P0ABD	If Pack side Voltage is above Threshold	Pack Voltage	> 479V (ADC Count > 3925)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Pack Voltage <= 479V (ADC Count <=3925)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Current Sensor Circuit Low	P0AC1	If Coarse Current is below Threshold	Coarse Current	< -555A (ADC Count <163)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Coarse Current >= -555A (ADC Count >= 163)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Current Sensor Circuit High	P0AC2	If Coarse Current is above Threshold	Coarse Current	> 285A (ADC Count > 3934)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Coarse Current <= 285A (ADC Count <= 3934)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 2 Temperature Sensor Circuit Low Voltage	P0AC7	Sets when Temperature Sensor 2 falls below a threshold	Temperature Sensor 2	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 2 Temperature Sensor Circuit High Voltage	P0AC8	Sets when Temperature Sensor 2 falls above a threshold	Temperature Sensor 2	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 3 Temperature Sensor Circuit Low Voltage	P0ACC	Sets when Temperature Sensor 3 falls below a threshold	Temperature Sensor 3	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 3 Temperature Sensor Circuit High Voltage	P0ACD	Sets when Temperature Sensor 3 falls above a threshold	Temperature Sensor 3	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 4 Temperature Sensor Circuit Low Voltage	P0AEA	Sets when Temperature Sensor 4 falls below a threshold	Temperature Sensor 4	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery 4 Temperature Sensor Circuit High Voltage	P0AEB	Sets when Temperature Sensor 4 falls above a threshold	Temperature Sensor 4	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Current Sensor B Circuit Low	P0B10	If Fine Current is below Threshold	Fine Current	< -23A (ADC Count < 163)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Fine Current >= -23A (ADC Count >= 163)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Current Sensor B Circuit High	P0B11	If Fine Current is above Threshold	Fine Current	> 23A (ADC Count > 3934)	Diagnostic Enable	True	175 ms in a 250 ms window	Type A, 1 Trips
			DTC Pass	Fine Current <= 23A (ADC Count <= 3934)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	250 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense A Circuit	P0B3B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense A Circuit Low	P0B3D	Sets when cell voltage is detected below threshold	Cell Voltage A	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense A Circuit High	P0B3E	Sets when cell voltage is detected above threshold	Cell Voltage A	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense B Circuit	P0B40	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense B Circuit Low	P0B42	Sets when cell voltage is detected below threshold	Cell Voltage B	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense B Circuit High	P0B43	Sets when cell voltage is detected above threshold	Cell Voltage B	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense C Circuit	P0B45	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense C Circuit Low	P0B47	Sets when cell voltage is detected below threshold	Cell Voltage C	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense C Circuit High	P0B48	Sets when cell voltage is detected above threshold	Cell Voltage C	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense D Circuit	P0B4A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense D Circuit Low	P0B4C	Sets when cell voltage is detected below threshold	Cell Voltage D	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense D Circuit High	P0B4D	Sets when cell voltage is detected above threshold	Cell Voltage D	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense E Circuit	P0B4F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense E Circuit Low	P0B51	Sets when cell voltage is detected below threshold	Cell Voltage E	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense E Circuit High	P0B52	Sets when cell voltage is detected above threshold	Cell Voltage E	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense F Circuit	P0B54	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense F Circuit Low	P0B56	Sets when cell voltage is detected below threshold	Cell Voltage F	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense F Circuit High	P0B57	Sets when cell voltage is detected above threshold	Cell Voltage F	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense G Circuit	P0B59	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense G Circuit Low	P0B5B	Sets when cell voltage is detected below threshold	Cell Voltage G	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense G Circuit High	P0B5C	Sets when cell voltage is detected above threshold	Cell Voltage G	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense H Circuit	P0B5E	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense H Circuit Low	P0B60	Sets when cell voltage is detected below threshold	Cell Voltage H	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense H Circuit High	P0B61	Sets when cell voltage is detected above threshold	Cell Voltage H	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense I Circuit	P0B63	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense I Circuit Low	P0B65	Sets when cell voltage is detected below threshold	Cell Voltage I	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense I Circuit High	P0B66	Sets when cell voltage is detected above threshold	Cell Voltage I	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense J Circuit	P0B68	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense J Circuit Low	P0B6A	Sets when cell voltage is detected below threshold	Cell Voltage J	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense J Circuit High	P0B6B	Sets when cell voltage is detected above threshold	Cell Voltage J	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense K Circuit	P0B6D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense K Circuit Low	P0B6F	Sets when cell voltage is detected below threshold	Cell Voltage K	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense K Circuit High	P0B70	Sets when cell voltage is detected above threshold	Cell Voltage K	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense L Circuit	P0B72	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense L Circuit Low	P0B74	Sets when cell voltage is detected below threshold	Cell Voltage L	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense L Circuit High	P0B75	Sets when cell voltage is detected above threshold	Cell Voltage L	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense M Circuit	P0B77	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense M Circuit Low	P0B79	Sets when cell voltage is detected below threshold	Cell Voltage M	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense M Circuit High	P0B7A	Sets when cell voltage is detected above threshold	Cell Voltage M	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense N Circuit	P0B7C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense N Circuit Low	P0B7E	Sets when cell voltage is detected below threshold	Cell Voltage N	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense N Circuit High	P0B7F	Sets when cell voltage is detected above threshold	Cell Voltage N	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense O Circuit	P0B81	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense O Circuit Low	P0B83	Sets when cell voltage is detected below threshold	Cell Voltage O	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense O Circuit High	P0B84	Sets when cell voltage is detected above threshold	Cell Voltage O	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense P Circuit	P0B86	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense P Circuit Low	P0B88	Sets when cell voltage is detected below threshold	Cell Voltage P	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense P Circuit High	P0B89	Sets when cell voltage is detected above threshold	Cell Voltage P	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Q Circuit	P0B8B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Q Circuit Low	P0B8D	Sets when cell voltage is detected below threshold	Cell Voltage Q	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Q Circuit High	P0B8E	Sets when cell voltage is detected above threshold	Cell Voltage Q	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense R Circuit	P0B90	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense R Circuit Low	P0B92	Sets when cell voltage is detected below threshold	Cell Voltage R	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense R Circuit High	P0B93	Sets when cell voltage is detected above threshold	Cell Voltage R	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense S Circuit	P0B95	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense S Circuit Low	P0B97	Sets when cell voltage is detected below threshold	Cell Voltage S	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense S Circuit High	P0B98	Sets when cell voltage is detected above threshold	Cell Voltage S	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense T Circuit	P0B9A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense T Circuit Low	P0B9C	Sets when cell voltage is detected below threshold	Cell Voltage T	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense T Circuit High	P0B9D	Sets when cell voltage is detected above threshold	Cell Voltage T	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense U Circuit	P0B9F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense U Circuit Low	P0BA1	Sets when cell voltage is detected below threshold	Cell Voltage U	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense U Circuit High	P0BA2	Sets when cell voltage is detected above threshold	Cell Voltage U	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense V Circuit	P0BA4	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense V Circuit Low	P0BA6	Sets when cell voltage is detected below threshold	Cell Voltage V	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense V Circuit High	P0BA7	Sets when cell voltage is detected above threshold	Cell Voltage V	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense W Circuit	P0BA9	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense W Circuit Low	P0BAB	Sets when cell voltage is detected below threshold	Cell Voltage W	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense W Circuit High	P0BAC	Sets when cell voltage is detected above threshold	Cell Voltage W	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense X Circuit	P0BAE	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense X Circuit Low	P0BB0	Sets when cell voltage is detected below threshold	Cell Voltage X	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense X Circuit High	P0BB1	Sets when cell voltage is detected above threshold	Cell Voltage X	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Y Circuit	P0BB3	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Y Circuit Low	P0BB5	Sets when cell voltage is detected below threshold	Cell Voltage Y	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Y Circuit High	P0BB6	Sets when cell voltage is detected above threshold	Cell Voltage Y	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Z Circuit	P0BB8	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Z Circuit Low	P0BBA	Sets when cell voltage is detected below threshold	Cell Voltage Z	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense Z Circuit High	P0BBB	Sets when cell voltage is detected above threshold	Cell Voltage Z	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor E Circuit Low	P0BC4	Sets when Temperature Sensor 5 falls below a threshold	Temperature Sensor 5	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor E Circuit High	P0BC5	Sets when Temperature Sensor 5 falls above a threshold	Temperature Sensor 5	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor F Circuit Low	P0C35	Sets when Temperature Sensor 6 falls below a threshold	Temperature Sensor 6	> 87.5C (ADC Count < 135)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Temperature Sensor F Circuit High	P0C36	Sets when Temperature Sensor 6 falls above a threshold	Temperature Sensor 6	< -40C (ADC Count > 4008)	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	1.4 seconds in a 2 second window	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Temperature Sensor Circuit Low	P0C44	Sets when Inlet Coolant Temp Sensor falls below a Threshold	Inlet Temp	>= 87.9C (ADC Count <= 133)	Diagnostic Enable	True	1.75 seconds in a 2.5 seconds window	Type B, 2 Trips
			DTC Pass	Inlet Temp < 87.9C (ADC Count > 133)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	2.5 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Pack Coolant Temperature Sensor Circuit High	P0C45	Sets when Inlet Coolant Temp Sensor goes above a Threshold	Inlet Temp	< -40C (ADC Count > 3890)	Diagnostic Enable	True	1.75 seconds in a 2.5 seconds window	Type B, 2 Trips
			DTC Pass	Inlet Temp >= -40C (ADC Count <= 3890)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V	2.5 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Random Accessories Memory (RAM)	P1A05	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM Initialization Status Extended VITM System Voltage	True True Initializing ≥ 9V	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Read Only Memory (ROM)	P1A06	Flash ROM Checksum method	Flash ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable	True	At power up	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM Initalization Status Extended VITM System Voltage	True Initializing >= 9V		

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module 5 Volt Reference Circuit	P1A07	Sets when 5V VITM reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator) DTC Pass	5V Reference Value < 2.8V or 5V Reference Value > 3.2V 2.8V <= 5V Reference Value <= 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	600 ms in a 1 second window 1 Second	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module System Voltage Low	P1A0C	If 12V System Voltage is below Threshold	12V System Voltage	< 9.0V	Diagnostic Enable	True	5 seconds in a 6 seconds window	Type C, No SVS
			DTC Pass	12V System Voltage ≥ 9.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True	6 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module System Voltage High	P1A0D	If 12V System Voltage is above Threshold	12V System Voltage DTC Pass	>18.5V 12V System Voltage ≥ 18.5V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True True	5 seconds in a 6 seconds window 6 Seconds	Type C, No SVS

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Ignition Switch Run/ Start Position Circuit Low	P1A5E	If RunCrank input state is below Threshold and RunCrank Received Serial Data State = Active	RunCrank Hardwire Input and Serial Data signal	RunCrank Input < 5V	Diagnostic Enable	True	5 seconds in a 6 second window	Type A, 1 Trips
			DTC Pass	RunCrank Input >= 5V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus H	True >= 9V U185B	6 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Ignition Switch Run/ Start Position Circuit High	P1A5F	If RunCrank input state is above Threshold and RunCrank Received Serial Data State = Inactive	RunCrank Hardwire Input and Serial Data signal	RunCrank Input >= 5V	Diagnostic Enable	True	5 seconds in a 6 second window	Type A, 1 Trips
			DTC Pass	RunCrank Input < 5V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus H	True >= 9V U185B	6 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Ignition Switch Accessory Position Circuit Low	P1A60	If Accessory input state is below Threshold and received serial data Propulsion System Active state = True and Accessory Diagnostic Delay is Expired	Accessory Hardwire Input	Accessory Input < 5V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTC for Battery Energy Control Module Lost Communication With with HCP (TPIM) on Bus A (HS GMLAN Bus) VITM System Voltage Propulsion System Active	True True U1885 >= 9V True	0.1 seconds (8 * 0.0125)	Type B, 2 Trips
			DTC Pass	Accessory Input >= 5V			0.1 seconds (8 * 0.0125)	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Hybrid Battery Voltage Isolation Sensor Circuit	P1AE6	Sets when Isolation Ckt components detected open/short	Active Isolation Circuit	If $K \leq 0.985$ or $K \geq 1.015$	Diagnostic Enable	True	30s	Type A, 1 Trips
			DTC Pass	$0.985 < K < 1.015$ (diagnose open sw and/or open/short in circuit resistors) Or $\{ \{ \text{abs}(\text{AD1} - \text{AD2}) < 30\text{mV} \} \text{ or } \{ \text{abs}(\text{BD1} - \text{BD2}) < 30\text{mV} \} \}$ (diagnose shorted sw)	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VICM Isolation Start Request VITM System Voltage No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus H	True True > 9V U185B	30s	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AA Circuit Low	P1B17	Sets when cell voltage is detected below threshold	Cell Voltage AA	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 P0B3B, P0B40, P0B45, P0B4A, P0B4F, P0B54, P0B59, P0B5E, P0B63, P0B68, P0B6D, P0B72, P0B77, P0B7C, P0B81, P0B86, P0B8B, P0B90, P0B95, P0B9A, P0B9F, P0BA4, P0BA9, P0BAE, P0BB3, P0BB8, P1B28, P1B29, P1B2A, P1B2B, P1B2C, P1B2D, P1E4C, P1E4D, P1E4E, P1E4F, P1E50, P1E51, P1E52, P1E53, P1E54, P1E55, P1E56, P1E57, P1E58, P1E59, P1E5A, P1E5B, P1E5C, P1E5D, P1E5E, P1E5F, P1E60, P1E61, P1E62, P1E63, P1E64, P1E65, P1E66, P1E67, P1E68, P1E69, P1E6A, P1E6B, P1E6C, P1E6D, P1E6E, P1E6F, P1E70, P1E71, P1E72, P1E73, P1E74, P1E75, P1E76, P1E77, P1E78, P1E79, P1E7A, P1E7B, P1E7C, P1E7D, P1E7E, P1E7F, P1E80, P1E81, P1E82, P1E83, P1E84, P1E86,	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	P1E87, P1E88, P1E89, P1E8A Not Running P1E92, P1E98, P1E9E, P1EA4, P1FC9, P1FCA, P1FCB, P1FCC, P1FCD, P1FCE, P3036, P3041 P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3034, P303F		

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AA Circuit High	P1B18	Sets when cell voltage is detected above threshold	Cell Voltage AA	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AB Circuit Low	P1B1A	Sets when cell voltage is detected below threshold	Cell Voltage AB	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AB Circuit High	P1B1B	Sets when cell voltage is detected above threshold	Cell Voltage AB	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AC Circuit Low	P1B1D	Sets when cell voltage is detected below threshold	Cell Voltage AC	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AC Circuit High	P1B1E	Sets when cell voltage is detected above threshold	Cell Voltage AC	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AD Circuit Low	P1B20	Sets when cell voltage is detected below threshold	Cell Voltage AD	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AD Circuit High	P1B21	Sets when cell voltage is detected above threshold	Cell Voltage AD	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AE Circuit Low	P1B23	Sets when cell voltage is detected below threshold	Cell Voltage AE	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AE Circuit High	P1B24	Sets when cell voltage is detected above threshold	Cell Voltage AE	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AF Circuit Low	P1B26	Sets when cell voltage is detected below threshold	Cell Voltage AF	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AF Circuit High	P1B27	Sets when cell voltage is detected above threshold	Cell Voltage AF	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AA Circuit	P1B28	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AB Circuit	P1B29	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AC Circuit	P1B2A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AD Circuit	P1B2B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AE Circuit	P1B2C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AF Circuit	P1B2D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AG Circuit Low	P1B46	Sets when cell voltage is detected below threshold	Cell Voltage AG	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AG Circuit High	P1B47	Sets when cell voltage is detected above threshold	Cell Voltage AG	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AH Circuit Low	P1B49	Sets when cell voltage is detected below threshold	Cell Voltage AH	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AH Circuit High	P1B4A	Sets when cell voltage is detected above threshold	Cell Voltage AH	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AI Circuit Low	P1B4C	Sets when cell voltage is detected below threshold	Cell Voltage AI	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AI Circuit High	P1B4D	Sets when cell voltage is detected above threshold	Cell Voltage AI	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AJ Circuit Low	P1B4F	Sets when cell voltage is detected below threshold	Cell Voltage AJ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AJ Circuit High	P1B50	Sets when cell voltage is detected above threshold	Cell Voltage AJ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AK Circuit Low	P1B52	Sets when cell voltage is detected below threshold	Cell Voltage AK	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AK Circuit High	P1B53	Sets when cell voltage is detected above threshold	Cell Voltage AK	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AL Circuit Low	P1B55	Sets when cell voltage is detected below threshold	Cell Voltage AL	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AL Circuit High	P1B56	Sets when cell voltage is detected above threshold	Cell Voltage AL	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AM Circuit Low	P1B58	Sets when cell voltage is detected below threshold	Cell Voltage AM	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AM Circuit High	P1B59	Sets when cell voltage is detected above threshold	Cell Voltage AM	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AN Circuit Low	P1B5B	Sets when cell voltage is detected below threshold	Cell Voltage AN	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AN Circuit High	P1B5C	Sets when cell voltage is detected above threshold	Cell Voltage AN	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AO Circuit Low	P1B5E	Sets when cell voltage is detected below threshold	Cell Voltage AO	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AO Circuit High	P1B5F	Sets when cell voltage is detected above threshold	Cell Voltage AO	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AP Circuit Low	P1B61	Sets when cell voltage is detected below threshold	Cell Voltage AP	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AP Circuit High	P1B62	Sets when cell voltage is detected above threshold	Cell Voltage AP	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AQ Circuit Low	P1B64	Sets when cell voltage is detected below threshold	Cell Voltage AQ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AQ Circuit High	P1B65	Sets when cell voltage is detected above threshold	Cell Voltage AQ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AR Circuit Low	P1B67	Sets when cell voltage is detected below threshold	Cell Voltage AR	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AR Circuit High	P1B68	Sets when cell voltage is detected above threshold	Cell Voltage AR	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AS Circuit Low	P1B6A	Sets when cell voltage is detected below threshold	Cell Voltage AS	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AS Circuit High	P1B6B	Sets when cell voltage is detected above threshold	Cell Voltage AS	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AT Circuit Low	P1B6D	Sets when cell voltage is detected below threshold	Cell Voltage AT	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AT Circuit High	P1B6E	Sets when cell voltage is detected above threshold	Cell Voltage AT	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AU Circuit Low	P1B70	Sets when cell voltage is detected below threshold	Cell Voltage AU	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AU Circuit High	P1B71	Sets when cell voltage is detected above threshold	Cell Voltage AU	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AV Circuit Low	P1B73	Sets when cell voltage is detected below threshold	Cell Voltage AV	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AV Circuit High	P1B74	Sets when cell voltage is detected above threshold	Cell Voltage AV	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AW Circuit Low	P1B76	Sets when cell voltage is detected below threshold	Cell Voltage AW	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AW Circuit High	P1B77	Sets when cell voltage is detected above threshold	Cell Voltage AW	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AX Circuit Low	P1B79	Sets when cell voltage is detected below threshold	Cell Voltage AX	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AX Circuit High	P1B7A	Sets when cell voltage is detected above threshold	Cell Voltage AX	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AY Circuit Low	P1B7C	Sets when cell voltage is detected below threshold	Cell Voltage AY	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AY Circuit High	P1B7D	Sets when cell voltage is detected above threshold	Cell Voltage AY	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AZ Circuit Low	P1B7F	Sets when cell voltage is detected below threshold	Cell Voltage AZ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AZ Circuit High	P1B80	Sets when cell voltage is detected above threshold	Cell Voltage AZ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BA Circuit Low	P1B82	Sets when cell voltage is detected below threshold	Cell Voltage BA	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BA Circuit High	P1B83	Sets when cell voltage is detected above threshold	Cell Voltage BA	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BB Circuit Low	P1B85	Sets when cell voltage is detected below threshold	Cell Voltage BB	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BB Circuit High	P1B86	Sets when cell voltage is detected above threshold	Cell Voltage BB	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BC Circuit Low	P1B88	Sets when cell voltage is detected below threshold	Cell Voltage BC	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BC Circuit High	P1B89	Sets when cell voltage is detected above threshold	Cell Voltage BC	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BD Circuit Low	P1B8B	Sets when cell voltage is detected below threshold	Cell Voltage BD	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BD Circuit High	P1B8C	Sets when cell voltage is detected above threshold	Cell Voltage BD	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BE Circuit Low	P1B8E	Sets when cell voltage is detected below threshold	Cell Voltage BE	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BE Circuit High	P1B8F	Sets when cell voltage is detected above threshold	Cell Voltage BE	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BF Circuit Low	P1B91	Sets when cell voltage is detected below threshold	Cell Voltage BF	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BF Circuit High	P1B92	Sets when cell voltage is detected above threshold	Cell Voltage BF	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BG Circuit Low	P1B94	Sets when cell voltage is detected below threshold	Cell Voltage BG	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BG Circuit High	P1B95	Sets when cell voltage is detected above threshold	Cell Voltage BG	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BH Circuit Low	P1B97	Sets when cell voltage is detected below threshold	Cell Voltage BH	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BH Circuit High	P1B98	Sets when cell voltage is detected above threshold	Cell Voltage BH	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BI Circuit Low	P1B9A	Sets when cell voltage is detected below threshold	Cell Voltage BI	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BI Circuit High	P1B9B	Sets when cell voltage is detected above threshold	Cell Voltage BI	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BJ Circuit Low	P1B9D	Sets when cell voltage is detected below threshold	Cell Voltage BJ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BJ Circuit High	P1B9E	Sets when cell voltage is detected above threshold	Cell Voltage BJ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BK Circuit Low	P1BA0	Sets when cell voltage is detected below threshold	Cell Voltage BK	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BK Circuit High	P1BA1	Sets when cell voltage is detected above threshold	Cell Voltage BK	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BL Circuit Low	P1BA3	Sets when cell voltage is detected below threshold	Cell Voltage BL	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BL Circuit High	P1BA4	Sets when cell voltage is detected above threshold	Cell Voltage BL	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BM Circuit Low	P1BA6	Sets when cell voltage is detected below threshold	Cell Voltage BM	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BM Circuit High	P1BA7	Sets when cell voltage is detected above threshold	Cell Voltage BM	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BN Circuit Low	P1BA9	Sets when cell voltage is detected below threshold	Cell Voltage BN	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BN Circuit High	P1BAA	Sets when cell voltage is detected above threshold	Cell Voltage BN	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BO Circuit Low	P1BAC	Sets when cell voltage is detected below threshold	Cell Voltage BO	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BO Circuit High	P1BAD	Sets when cell voltage is detected above threshold	Cell Voltage BO	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BP Circuit Low	P1BAF	Sets when cell voltage is detected below threshold	Cell Voltage BP	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BP Circuit High	P1BB0	Sets when cell voltage is detected above threshold	Cell Voltage BP	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BQ Circuit Low	P1BB2	Sets when cell voltage is detected below threshold	Cell Voltage BQ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BQ Circuit High	P1BB3	Sets when cell voltage is detected above threshold	Cell Voltage BQ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BR Circuit Low	P1BB5	Sets when cell voltage is detected below threshold	Cell Voltage BR	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BR Circuit High	P1BB6	Sets when cell voltage is detected above threshold	Cell Voltage BR	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BS Circuit Low	P1BB8	Sets when cell voltage is detected below threshold	Cell Voltage BS	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BS Circuit High	P1BB9	Sets when cell voltage is detected above threshold	Cell Voltage BS	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BT Circuit Low	P1BBB	Sets when cell voltage is detected below threshold	Cell Voltage BT	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BT Circuit High	P1BBC	Sets when cell voltage is detected above threshold	Cell Voltage BT	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BU Circuit Low	P1BBE	Sets when cell voltage is detected below threshold	Cell Voltage BU	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BU Circuit High	P1BBF	Sets when cell voltage is detected above threshold	Cell Voltage BU	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BV Circuit Low	P1BC1	Sets when cell voltage is detected below threshold	Cell Voltage BV	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BV Circuit High	P1BC2	Sets when cell voltage is detected above threshold	Cell Voltage BV	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BW Circuit Low	P1BC4	Sets when cell voltage is detected below threshold	Cell Voltage BW	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BW Circuit High	P1BC5	Sets when cell voltage is detected above threshold	Cell Voltage BW	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BX Circuit Low	P1BC7	Sets when cell voltage is detected below threshold	Cell Voltage BX	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BX Circuit High	P1BC8	Sets when cell voltage is detected above threshold	Cell Voltage BX	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BY Circuit Low	P1BCA	Sets when cell voltage is detected below threshold	Cell Voltage BY	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BY Circuit High	P1BCB	Sets when cell voltage is detected above threshold	Cell Voltage BY	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BZ Circuit Low	P1BCD	Sets when cell voltage is detected below threshold	Cell Voltage BZ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BZ Circuit High	P1BCE	Sets when cell voltage is detected above threshold	Cell Voltage BZ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CA Circuit Low	P1BD0	Sets when cell voltage is detected below threshold	Cell Voltage CA	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CA Circuit High	P1BD1	Sets when cell voltage is detected above threshold	Cell Voltage CA	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CB Circuit Low	P1BD3	Sets when cell voltage is detected below threshold	Cell Voltage CB	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CB Circuit High	P1BD4	Sets when cell voltage is detected above threshold	Cell Voltage CB	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CC Circuit Low	P1BD6	Sets when cell voltage is detected below threshold	Cell Voltage CC	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CC Circuit High	P1BD7	Sets when cell voltage is detected above threshold	Cell Voltage CC	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CD Circuit Low	P1BD9	Sets when cell voltage is detected below threshold	Cell Voltage CD	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CD Circuit High	P1BDA	Sets when cell voltage is detected above threshold	Cell Voltage CD	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CE Circuit Low	P1BDC	Sets when cell voltage is detected below threshold	Cell Voltage CE	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CE Circuit High	P1BDD	Sets when cell voltage is detected above threshold	Cell Voltage CE	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CF Circuit Low	P1BDF	Sets when cell voltage is detected below threshold	Cell Voltage CF	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CF Circuit High	P1BE0	Sets when cell voltage is detected above threshold	Cell Voltage CF	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CG Circuit Low	P1BE2	Sets when cell voltage is detected below threshold	Cell Voltage CF	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CG Circuit High	P1BE3	Sets when cell voltage is detected above threshold	Cell Voltage CG	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CH Circuit Low	P1BE5	Sets when cell voltage is detected below threshold	Cell Voltage CH	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CH Circuit High	P1BE6	Sets when cell voltage is detected above threshold	Cell Voltage CH	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CI Circuit Low	P1BE8	Sets when cell voltage is detected below threshold	Cell Voltage CI	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CI Circuit High	P1BE9	Sets when cell voltage is detected above threshold	Cell Voltage CI	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CJ Circuit Low	P1BEB	Sets when cell voltage is detected below threshold	Cell Voltage CJ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CJ Circuit High	P1BEC	Sets when cell voltage is detected above threshold	Cell Voltage CJ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CK Circuit Low	P1BEE	Sets when cell voltage is detected below threshold	Cell Voltage CK	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CK Circuit High	P1BEF	Sets when cell voltage is detected above threshold	Cell Voltage CK	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CL Circuit Low	P1BF1	Sets when cell voltage is detected below threshold	Cell Voltage CL	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CL Circuit High	P1BF2	Sets when cell voltage is detected above threshold	Cell Voltage CL	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CM Circuit Low	P1BF4	Sets when cell voltage is detected below threshold	Cell Voltage CM	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CM Circuit High	P1BF5	Sets when cell voltage is detected above threshold	Cell Voltage CM	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CN Circuit Low	P1BF7	Sets when cell voltage is detected below threshold	Cell Voltage CN	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CN Circuit High	P1BF8	Sets when cell voltage is detected above threshold	Cell Voltage CN	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CO Circuit Low	P1BFA	Sets when cell voltage is detected below threshold	Cell Voltage CO	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CO Circuit High	P1BFB	Sets when cell voltage is detected above threshold	Cell Voltage CO	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CP Circuit Low	P1BFD	Sets when cell voltage is detected below threshold	Cell Voltage CP	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CP Circuit High	P1BFE	Sets when cell voltage is detected above threshold	Cell Voltage CP	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CQ Circuit Low	P1E02	Sets when cell voltage is detected below threshold	Cell Voltage CQ	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CQ Circuit High	P1E03	Sets when cell voltage is detected above threshold	Cell Voltage CQ	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CR Circuit Low	P1E05	Sets when cell voltage is detected below threshold	Cell Voltage CR	<= 0.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CR Circuit High	P1E06	Sets when cell voltage is detected above threshold	Cell Voltage CR	>= 4.8V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AG Circuit	P1E4C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AH Circuit	P1E4D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AI Circuit	P1E4E	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AJ Circuit	P1E4F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AK Circuit	P1E50	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AL Circuit	P1E51	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AM Circuit	P1E52	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AN Circuit	P1E53	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AO Circuit	P1E54	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AP Circuit	P1E55	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AQ Circuit	P1E56	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AR Circuit	P1E57	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AS Circuit	P1E58	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AT Circuit	P1E59	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AU Circuit	P1E5A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AV Circuit	P1E5B	Sets when cell voltage is detected open	1st Cell V – 2nd Cell V or Cell V_gate on Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on Case 2: General Sense Line 1st Cell V – 2nd Cell V Case 3: Common Power Line 1st Cell V – 2nd Cell V Case 4: Common Ground Line 1st Cell V – 2nd Cell V Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on Case 6: Splice Line Splice Cap Voltage Case 7: BusBar Splice Splice Cap Voltage	Case 1: Cell V_On Gate < 36mV Case 2: 1st Cell V – 2nd Cell V >= 1.3V Case 3 : 1st Cell V – 2nd Cell V >= 1.3V Case 4 : 1st Cell V – 2nd Cell V >= 1.3V Case 5 : Cell V_On Gate < 36mV Case 6: Splice Cap Voltage > 0.1V Case 7: Splice Cap Voltage > 0.5V	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Cell Balancing Fault No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Open Sense Line Fault Not Running Slave Cell Balancing Fault Slave Internal Performance Fault	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AW Circuit	P1E5C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AX Circuit	P1E5D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AY Circuit	P1E5E	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense AZ Circuit	P1E5F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BA Circuit	P1E60	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BB Circuit	P1E61	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BC Circuit	P1E62	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BD Circuit	P1E63	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BE Circuit	P1E64	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BF Circuit	P1E65	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BG Circuit	P1E66	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BH Circuit	P1E67	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BI Circuit	P1E68	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BJ Circuit	P1E69	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BK Circuit	P1E6A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BL Circuit	P1E6B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BM Circuit	P1E6C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BN Circuit	P1E6D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BO Circuit	P1E6E	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BP Circuit	P1E6F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BQ Circuit	P1E70	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BR Circuit	P1E71	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BS Circuit	P1E72	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BT Circuit	P1E73	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BU Circuit	P1E74	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BV Circuit	P1E75	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BW Circuit	P1E76	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BX Circuit	P1E77	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BY Circuit	P1E78	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense BZ Circuit	P1E79	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CA Circuit	P1E7A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CB Circuit	P1E7B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CC Circuit	P1E7C	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CD Circuit	P1E7D	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CE Circuit	P1E7E	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CF Circuit	P1E7F	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CG Circuit	P1E80	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CH Circuit	P1E81	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CI Circuit	P1E82	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CJ Circuit	P1E83	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CK Circuit	P1E84	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CL Circuit	P1E85	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CM Circuit	P1E86	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CN Circuit	P1E87	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CO Circuit	P1E88	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CP Circuit	P1E89	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CQ Circuit	P1E8A	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Voltage Sense CR Circuit	P1E8B	Sets when cell voltage is detected open	<p> 1st Cell V – 2nd Cell V or Cell V_gate on</p> <p>Case 1: Single Power Line - Positive side Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 2: General Sense Line 1st Cell V – 2nd Cell V </p> <p>Case 3: Common Power Line 1st Cell V – 2nd Cell V </p> <p>Case 4: Common Ground Line 1st Cell V – 2nd Cell V </p> <p>Case 5: Single Ground Line Affected Cell Voltage when Cell Balance Gate is on</p> <p>Case 6: Splice Line Splice Cap Voltage</p> <p>Case 7: BusBar Splice Splice Cap Voltage</p>	<p>Case 1: Cell V_On Gate < 36mV</p> <p>Case 2: 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 3 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 4 : 1st Cell V – 2nd Cell V >= 1.3V</p> <p>Case 5 : Cell V_On Gate < 36mV</p> <p>Case 6: Splice Cap Voltage > 0.1V</p> <p>Case 7: Splice Cap Voltage > 0.5V</p>	<p>Diagnostic Enable</p> <p>Run/Crank, Accessory/ Run or HVEM EB Comm Enable</p> <p>No Active DTCs associated with Slave Loss of Comm</p> <p>No Active DTCs associated with Open Sense Line</p> <p>2nd Protection Self Test Diagnostic</p> <p>No Active DTCs associated with Slave Cell Balancing Fault</p> <p>No Active DTCs associated with Slave Internal Performance</p>	<p>True</p> <p>True</p> <p>Slave Loss of Comm Fault</p> <p>Open Sense Line Fault</p> <p>Not Running</p> <p>Slave Cell Balancing Fault</p> <p>Slave Internal Performance Fault</p>	0.6 seconds out of a 0.6 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A Performance	P1E8E	Slave A fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A RAM	P1E8F	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM A Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A ROM	P1E90	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM A Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A KAM	P1E91	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM A Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A Cell Balancing Circuit	P1E92	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				3.5V < Cell Voltage < 4.0V				
				Threshold = 41mV	2nd Protection Self Test Diagnostic	Not Running		
				3.0V < Cell Voltage < 3.5V				
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module A 5V Ref	P1E93	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B Performance	P1E94	Slave B fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B RAM	P1E95	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM B Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B ROM	P1E96	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True Transitions: TRUE to FALSE (During VTSM B Power down)	At power down	Type A, 1 Trips
			DTC Pass	1	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B KAM	P1E97	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM B Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B Cell Balancing Circuit	P1E98	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM: 4.0V < Cell Voltage < 5.0V Threshold = 66mV 3.5V < Cell Voltage < 4.0V Threshold = 41mV 3.0V < Cell Voltage < 3.5V Threshold = 22mV Slaves in VITM: 3.8V < Cell Voltage < 5.0V Threshold = 44mV 3.0V < Cell Voltage < 3.8V Threshold = 23mV Threshold is above values specified for Cell Voltage specified	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Internal Performance	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042	14 seconds in a 20 seconds window	Type A, 1 Trips
			DTC Pass				20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module B 5V Ref	P1E99	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C Performance	P1E9A	Slave C fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C RAM	P1E9B	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM C Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C ROM	P1E9C	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM C Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C KAM	P1E9D	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM C Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C Cell Balancing Circuit	P1E9E	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module C 5V Ref	P1E9F	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D Performance	P1EA0	Slave D fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D RAM	P1EA1	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM D Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D ROM	P1EA2	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM D Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D KAM	P1EA3	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM D Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D Cell Balancing Circuit	P1EA4	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				3.5V < Cell Voltage < 4.0V				
				Threshold = 41mV	2nd Protection Self Test Diagnostic	Not Running		
				3.0V < Cell Voltage < 3.5V				
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module D 5V Ref	P1EA5	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module Software Incompatible	P1EB1	VITM Software version and Software version of ALL Slave modules are compatible	If any software version incompatibility is detected	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage No Active DTCs associated with Slave Loss of Comm	True True >= 9V Slave Loss of Comm Fault	At power up - 0.200 seconds	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Not Programmed	P1EB2	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Not Programmed	P1EB3	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Not Programmed	P1EB4	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Not Programmed	P1EB5	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Current Sensor A Exceeded Learning Limit	P1EBA	If Pack Current Coarse Offset is out of range	Pack Current Coarse Offset	> 8A	Diagnostic Enable	True	At power up - 185 ms	Type A, 1 Trips
					Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
					High Voltage Contactor Status	Open		
					Charger Contactor Status	Open		
					VITM System Voltage	>= 9V		
					VITM Initialization Status Extended	Initializing		
					No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus H	U185B		
			DTC Pass	Pack Current Coarse Offset <= 8A			At power up - 185 ms	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Pack Current Sensor B Exceeded Learning Limit	P1EBB	If Pack Current Fine Offset is out of range	Pack Current Fine Offset	Pack Current Fine Offset > 2.5A	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable High Voltage Contactor Status Charger Contactor Status VITM System Voltage VITM Initialization Status Extended No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus H	True True Open Open >= 9V Initializing U185B	At power up - 185 ms At power up - 185 ms	Type A, 1 Trips
			DTC Pass	Pack Current Fine Offset <= 2.5A				

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module High Voltage Energy Management Communicati on Bus Enable Circuit Low	P1EC1	If High Voltage Energy Management (HVEM) Wakeup input state is below Threshold and HVEM Received Serial Data State = Active	HVEM Hardwire Input and Serial Data signal	HVEM Input < 5V	Diagnostic Enable	True	7 seconds in a 10 second window	Type A, 1 Trips
					Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
					VITM System Voltage	>= 9V		
					No Active DTC for Battery Energy Control Module System Voltage Low	P1A0C		
					No Active DTC for Battery Energy Control Module Lost Communication with Hybrid Processor Control Module B on Bus A (HS)	U2602		
			DTC Pass	HVEM Input >= 5V			10 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Processor Performance	P1F06	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Processor Performance	P1F07	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Processor Performance	P1F08	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Processor Performance	P1F09	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Not Programmed	P1FA6	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Not Programmed	P1FA7	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Not Programmed	P1FA8	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Not Programmed	P1FA9	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Not Programmed	P1FAA	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Not Programmed	P1FAB	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E ROM	P1FAC	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM E Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G ROM	P1FAD	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM G Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H ROM	P1FAE	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM H Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I ROM	P1FAF	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM I Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module J ROM	P1FB0	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM J Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E RAM	P1FB1	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM E Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F RAM	P1FB2	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM F Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G RAM	P1FB3	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM G Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H RAM	P1FB4	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM H Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I RAM	P1FB5	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM I Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module J RAM	P1FB6	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM J Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E KAM	P1FB7	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM E Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F KAM	P1FB8	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM F Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G KAM	P1FB9	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM G Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H KAM	P1FBA	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM H Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I KAM	P1FBB	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM I Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module J KAM	P1FBC	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM J Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E Performance	P1FBD	Slave E fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F Performance	P1FBE	Slave F fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G Performance	P1FBF	Slave G fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H Performance	P1FC0	Slave H fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I Performance	P1FC1	Slave I fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module J Performance	P1FC2	Slave J fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E 5V Ref	P1FC3	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F 5V Ref	P1FC4	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G 5V Ref	P1FC5	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H 5V Ref	P1FC6	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I 5V Ref	P1FC7	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module J 5V Ref	P1FC8	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module E Cell Balancing Circuit	P1FC9	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				3.5V < Cell Voltage < 4.0V				
				Threshold = 41mV	2nd Protection Self Test Diagnostic	Not Running		
				3.0V < Cell Voltage < 3.5V	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Threshold = 22mV				
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F Cell Balancing Circuit	P1FCA	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module G Cell Balancing Circuit	P1FCB	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module H Cell Balancing Circuit	P1FCC	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM: 4.0V < Cell Voltage < 5.0V Threshold = 66mV 3.5V < Cell Voltage < 4.0V Threshold = 41mV 3.0V < Cell Voltage < 3.5V Threshold = 22mV Slaves in VITM: 3.8V < Cell Voltage < 5.0V Threshold = 44mV 3.0V < Cell Voltage < 3.8V Threshold = 23mV	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Internal Performance	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042	14 seconds in a 20 seconds window	Type A, 1 Trips
			DTC Pass	Threshold is above values specified for Cell Voltage specified	20 seconds			

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module I Cell Balancing Circuit	P1FCD	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V Threshold = 66mV 3.5V < Cell Voltage < 4.0V Threshold = 41mV 3.0V < Cell Voltage < 3.5V Threshold = 22mV Slaves in VITM: 3.8V < Cell Voltage < 5.0V Threshold = 44mV 3.0V < Cell Voltage < 3.8V Threshold = 23mV	Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic No Active DTCs associated with Slave Internal Performance	True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Cell Balancing Circuit	P1FCE	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Processor Performance	P1FCF	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Processor Performance	P1FD0	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Processor Performance	P1FD1	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Processor Performance	P1FD2	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Processor Performance	P1FD3	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Processor Performance	P1FD4	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Voltage Sensor Circuit Low	P1FD5	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Voltage Sensor Circuit Low	P1FD6	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Voltage Sensor Circuit Low	P1FD7	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Voltage Sensor Circuit Low	P1FD8	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Voltage Sensor Circuit Low	P1FD9	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Voltage Sensor Circuit Low	P1FDA	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Voltage Sensor Circuit Low	P1FDB	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Voltage Sensor Circuit Low	P1FDC	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Voltage Sensor Circuit Low	P1FDD	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Voltage Sensor Circuit Low	P1FDE	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Voltage Sensor Circuit High	P1FDF	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Voltage Sensor Circuit High	P1FE0	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Voltage Sensor Circuit High	P1FE1	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Voltage Sensor Circuit High	P1FE2	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Voltage Sensor Circuit High	P1FE3	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Voltage Sensor Circuit High	P1FE4	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Voltage Sensor Circuit High	P1FE5	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Voltage Sensor Circuit High	P1FE6	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Voltage Sensor Circuit High	P1FE7	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Voltage Sensor Circuit High	P1FE8	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Voltage Sensor Circuit Range/ Performance	P1FE9	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Voltage Sensor Circuit Range/ Performance	P1FEA	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Voltage Sensor Circuit Range/ Performance	P1FEB	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Voltage Sensor Circuit Range/ Performance	P1FEC	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Voltage Sensor Circuit Range/ Performance	P1FED	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Voltage Sensor Circuit Range/ Performance	P1FEE	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Voltage Sensor Circuit Range/ Performance	P1FEF	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Voltage Sensor Circuit Range/ Performance	P1FF0	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Voltage Sensor Circuit Range/ Performance	P1FF1	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Voltage Sensor Circuit Range/ Performance	P1FF2	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module F ROM	P1FF3	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM F Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Not Programmed	P3030	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K ROM	P3031	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM K Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K RAM	P3032	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM K Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K KAM	P3033	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM K Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K Performance	P3034	Slave K fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True ≥ 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K 5V Ref	P3035	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module K Cell Balancing Circuit	P3036	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Processor Performance	P3037	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Voltage Sensor Circuit Low	P3038	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Voltage Sensor Circuit High	P3039	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Voltage Sensor Circuit Range/ Performance	P303A	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Not Programmed	P303B	If Slave did not Program correctly	Wrong or No response from Slave indicating error in Programming	1	After Programming session Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	 True True >= 9V	As soon as Programming session ends	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L ROM	P303C	ROM Checksum Method	ROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM L Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L RAM	P303D	RAM Read Write function Failed	RAM Read not Equal to RAM Written	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM L Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power up	Type A, 1 Trips
			DTC Pass	1			At power up	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L KAM	P303E	Using Checksum method	EEPROM Checksum Value Calculated is Different than Stored	1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm	True Transitions: TRUE to FALSE (During VTSM L Power down) U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624	At power down	Type A, 1 Trips
			DTC Pass	1			At power down	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L Performance	P303F	Slave L fails for any of the following reasons: - Illegal Address Detect Reset - Illegal Opcode or Detect Reset - Watchdog Timer Reset - Loss of Clock Reset - Low Voltage Detect Reset - SPI Bus Malfunction (Read Value from Register Not Equal to Written Value)	If Watchdog resets controller OR Wrong value Read DTC Pass	1 All should pass	Diagnostic Enable Run/Crank, Accessory/Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	Instantaneous - all reasons other than SPI bus 500us - SPI Bus 500 us in 200ms window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L 5V Ref	P3040	Sets when 5V Slave reference voltage is out of range	5V Reference Value (Circuit for Reference Diagnostic, Shunt Regulator)	5V Reference Value < 2.8V or 5V Reference Value > 3.2V	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624 Not Running	1.4 seconds in a 2.0 seconds window	Type A, 1 Trips
			DTC Pass	2.8V <= 5V Reference Value <= 3.2V			2.0 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery Interface Control Module L Cell Balancing Circuit	P3041	Cell Balance switch output	Cell Balance switch is below threshold	Slaves in VTSM:	Diagnostic Enable	True	14 seconds in a 20 seconds window	Type A, 1 Trips
				4.0V < Cell Voltage < 5.0V	Run/Crank, Accessory/ Run or HVEM EB Comm Enable	True		
				Threshold = 66mV				
				3.5V < Cell Voltage < 4.0V	No Active DTCs associated with Slave Loss of Comm	U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624		
				Threshold = 41mV				
				3.0V < Cell Voltage < 3.5V	2nd Protection Self Test Diagnostic	Not Running		
				Threshold = 22mV	No Active DTCs associated with Slave Internal Performance	P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3037, P3042		
				Slaves in VITM:				
				3.8V < Cell Voltage < 5.0V				
				Threshold = 44mV				
				3.0V < Cell Voltage < 3.8V				
				Threshold = 23mV				
			DTC Pass	Threshold is above values specified for Cell Voltage specified			20 seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Processor Performance	P3042	Compare Slave Reported Value with Expected Value in VITM	Reported Key Value by Slave is not correct	5	Diagnostic Enable Seed and Key Algorithm Calibration Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm 2nd Protection Self Test Diagnostic	True True True Slave Loss of Comm Fault Not Running	1 second in a 1.4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Voltage Sensor Circuit Low	P3043	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	< 1.5V (ADC Count < 123)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Voltage Sensor Circuit High	P3044	Sets when Module Voltage Sensor falls below a Threshold	Module Voltage	> 48.5V (ADC Count > 3972)	Diagnostic Enable Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Slave Internal Performance	True True Slave Loss of Comm Fault Slave Internal Performance Fault	1.4 second in a 2 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Voltage Sensor Circuit Range/ Performance	P3045	Compares Slave Module Voltage to sum of Cells measured by Slave	abs(Slave Module Voltage - Slave sum of Cell Voltages)	6-cell Slave Module: > 512mV (ADC Count > 422) 7-cell Slave Module: > 557mV (ADC Count > 445) 8-cell Slave Module: > 636mV (ADC Count > 521) 9-cell Slave Module: > 660mV (ADC Count > 540)	Diagnostic Enable No Active DTCs associated with Cell Voltage Ckt Low Run/Crank, Accessory or HVEM EB Comm Enable No Active DTCs associated with Slave Loss of Comm No Active DTCs associated with Open Sense Line No Active DTCs associated with Cell Voltage Ckt High No Active DTCs associated with Slave Internal Performance	True Cell Voltage Ckt Low True Slave Loss of Comm Fault Open Sense Line Fault Cell Voltage Ckt High Slave Internal Performance Fault	3 seconds in a 4 second window	Type A, 1 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Communicati on Bus H Off	U1806	If Bus Off is Detected	Transmit Error Counter (TEC)	TEC > 255	Diagnostic Enable	True	1.4 seconds in a 2 seconds window	Type B, 2 Trips
			DTC Pass	TEC < 255	Run/Crank or Accessory/ Run VITM System Voltage	True >= 9V		
							2 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Communicati on Bus A Off	U180B	If Bus Off is Detected	Transmit Error Counter (TEC)	TEC > 255	Diagnostic Enable	True	1.4 seconds in a 2 seconds window	Type B, 2 Trips
			DTC Pass	TEC < 255	Run/Crank or Accessory/ Run VITM System Voltage	True >= 9V		
							2 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Powertrain Control Module B on Bus H	U185B	If message \$20A OR \$20E OR \$304 are not Received by VITM	Loss of Supervision with VICM module on Charger CAN bus DTC Pass	# of consecutive \$20A message not received > 5 OR # of consecutive \$20E message not received > 4 OR # of consecutive \$304 message not received >4 1	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True True >= 9V	700 ms in a 1 second window 1 Second	Type B, 2 Trips

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communicati on With Hybrid Powertrain Control Module	U1885	If message \$1DF is not Received by VITM	Loss of Supervision with HCP module on HS GMLAN bus	# of consecutive \$1DF message not received > 10	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage Flashing Programming Session (Other Modules or itself) Mode \$28 Executed on HS Bus	True True >= 9V Completed False	1.75 seconds in a 2 second window 2 Seconds	Type B, 2 Trips
			DTC Pass	1				

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Dedicated Bus 1 Off	U2401	If Bus Off is Detected	Transmit Error Counter (TEC)	TEC > 255	Diagnostic Enable	True	1.4 seconds in a 2 second window	Type A, 1 Trips
			DTC Pass	TEC < 255	Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage	True >= 9V		

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communicati on with Hybrid Processor Control Module B on HS	U2602	If message \$236 is not Received by VITM	Loss of Supervision with VICM module on HS GMLAN bus	# of consecutive \$236 message not received > 3	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable VITM System Voltage Flashing Programming Session (Other Modules or itself) Mode \$28 Executed on HS Bus	True True >= 9V Completed False	2.8 seconds in a 4 second window 4 Seconds	Type B, 2 Trips
			DTC Pass	1				

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module A	U2603	If associated message from Slave is not received	Loss of Supervision with Slave A on Private CAN bus	# of consecutive serial data message from Slave A not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module B	U2604	If associated message from Slave is not received	Loss of Supervision with Slave B on Private CAN bus	# of consecutive serial data message from Slave B not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module C	U2605	If associated message from Slave is not received	Loss of Supervision with Slave C on Private CAN bus	# of consecutive serial data message from Slave C not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module D	U2606	If associated message from Slave is not received	Loss of Supervision with Slave D on Private CAN bus	# of consecutive serial data message from Slave D not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module E	U2617	If associated message from Slave is not received	Loss of Supervision with Slave E on Private CAN bus	# of consecutive serial data message from Slave E not received > 7	Diagnostic Enable Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True True Not Running ≥ 9V	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1			4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module F	U2618	If associated message from Slave is not received	Loss of Supervision with Slave F on Private CAN bus	# of consecutive serial data message from Slave F not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module G	U2619	If associated message from Slave is not received	Loss of Supervision with Slave G on Private CAN bus	# of consecutive serial data message from Slave G not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module H	U2620	If associated message from Slave is not received	Loss of Supervision with Slave H on Private CAN bus	# of consecutive serial data message from Slave H not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module I	U2621	If associated message from Slave is not received	Loss of Supervision with Slave I on Private CAN bus	# of consecutive serial data message from Slave I not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module J	U2622	If associated message from Slave is not received	Loss of Supervision with Slave J on Private CAN bus	# of consecutive serial data message from Slave J not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module K	U2623	If associated message from Slave is not received	Loss of Supervision with Slave J on Private CAN bus	# of consecutive serial data message from Slave J not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VITM) - Common Summary Tables

Component/ System	Fault Code	Monitor Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Energy Control Module Lost Communication with Hybrid Battery Interface Control Module L	U2624	If associated message from Slave is not received	Loss of Supervision with Slave J on Private CAN bus	# of consecutive serial data message from Slave J not received > 7	Diagnostic Enable	True	2.8 seconds in a 4 second window	Type A, 1 Trips
			DTC Pass	1	Run/Crank, Accessory/ Run or HVEM EB Comm Enable 2nd Protection Self Test Diagnostic VITM System Voltage	True Not Running >= 9V	4 Seconds	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Electric A/C Compressor Speed Request Message Counter Incorrect	P15C6	This diagnostic detects a fault when the Compressor Speed Request serial data received by the Compressor from the host controller is not being updated. Each transmitted Speed Request message by the host controller has an incrementing counter value associated with it (0, 1, 2, 3, 0...) known as Alive Rolling Count. Compressor performs instantaneous evaluation on each received message to check that the speed request rolling counts are in sequence. If not in sequence, an instantaneous FAIL state is transmitted to the Host Controller and the fail counter is incremented in the host controller. If the calibrated fail count threshold is met before the calibrated sample count, the diagnostic will report a FAIL and if not it will report a PASS. The diagnostic will continue to report as long as the enablement criteria are met.	Serial Communication message \$236: Compressor Speed Request Alive Rolling Count index value * This malfunction criteria is evaluated internal to the compressor and then instantaneous evaluation state is transmitted back to the host controller	MessageRollingCount value \neq Mod4(Previous Compressor Speed RequestAlive Rolling Count+1)	Serial Communication message \$22E: Compressor Data Packet Alive Rolling Count index value Compressor Loss of Communication Occurred Compressor Speed Request Alive Rolling Count State System Voltage No Active Run/Crank DTCs No Active Loss of Comm DTCs (Accessory On Signal OR Run Crank Active Signal) for time	Message Rolling Count value = mod4(Previous Message Rolling Count value + 1) = False \neq Indeterminate > 10.20 V P2534, P2535 U016B = True = True > 1.00 s	40.00 fails / 50.00 samples at 100ms	Type B, 2 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Cell Overvoltage Signal/ Circuit Performance	P1EAD	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Cell Overvoltage Signal/ Circuit Performance	P1EAE	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Cell Overvoltage Signal/ Circuit Performance	P1EAF	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Cell Overvoltage Signal/ Circuit Performance	P1EB0	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Battery Charger Total Output Power Performance	P1ECE	Monitors the charging system efficiency. There are two distinct sections of logic- a passive check logic section and an active or intrusive section of logic. The diagnostic fails on the active or intrusive logic only (requires brief disablement of the charger to measure the power draw on the HV battery, which enables a calculated estimate of charger output) but can pass in either the active or the passive sections.	Output Power Active Calculated Efficiency (AC charger efficiency failure thresholds are tabled and a function of AC Input Power)	>= 167.00 OR <= 62.32 (See supporting table for charger efficiency threshold values)	Global Diagnostic System Disable System Voltage Charger Enable Mask Propulsion System Active HV Battery Current HV Battery Voltage Charge Power Level Battery Current Sensor Status Power Electronics Coolant Loop Temperature Power Electronics Coolant Loop Temperature PASSIVE CHECK ENABLE: Filtered AC Input Power Threshold for a certain amount of delay time Active Output Power Shutdown Request Active Output Power Shutdown Complete	FALSE >= 10.20 V TRUE FALSE Not Fault Active Not Fault Active AC Level 1 or AC Level 2 VAID < 65.00 C (re-enables below 60.00 C if this threshold is crossed) > -12.00 C (re-enables above -7.00 C if this threshold is crossed) >= 600.00 >= 60.00 FALSE FALSE	12.00 failures out of 16.00 samples up to 5.00 min per sample 80.00 min	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					ACTIVE CHECK ENABLE: Filtered AC Input Power Threshold for a certain amount of delay time Active check has not run OR it has been a certain amount of time since the Active Check has run Active Run on Reported Passive Failure Bit Passive Check Indeterminate Bit Passive Check has not Reported a Pass for a certain amount of time	>= 600.00 >= 5.00 >= 900.00 = TRUE TRUE >= 600.00		

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module A Cell Overvoltage	P3240	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module B Cell Overvoltage	P3241	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module C Cell Overvoltage	P3242	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module D Cell Overvoltage	P3243	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Cell Overvoltage	P3244	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module E Cell Overvoltage Signal/ Circuit Performance	P3245	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Cell Overvoltage	P3246	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module F Cell Overvoltage Signal/ Circuit Performance	P3247	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Cell Overvoltage	P3248	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module G Cell Overvoltage Signal/ Circuit Performance	P3249	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Cell Overvoltage	P324A	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module H Cell Overvoltage Signal/ Circuit Performance	P324B	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Cell Overvoltage	P324C	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module I Cell Overvoltage Signal/ Circuit Performance	P324D	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Cell Overvoltage	P324E	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module J Cell Overvoltage Signal/ Circuit Performance	P324F	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	Run Crank Transitions to Inverter voltage System Voltage No active DTC's:	= ON for > 5 seconds > 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page)	Failure after 4 retries without a pass 50.00 s	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Cell Overvoltage	P3250	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module K Cell Overvoltage Signal/ Circuit Performance	P3251	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Cell Overvoltage	P3252	This diagnostic monitors for hybrid/EV battery cell voltage too high. It is a system monitor that checks each cell's voltage in this module by comparing their values collected using a secondary cell voltage sensing system against a calibratable threshold. If the voltage is above the failure threshold for sufficient time, the diagnostic will fail. For safety reasons, failures of this DTC cannot be cleared with a code clear and must be cleared by a service technician using the CPID in secondary parameters. To pass all cell voltages in this module must be below the threshold.	Cell Voltage	> 4.5 V	No active DTC's: System Voltage DTC Clear: Must Send CPID	Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) > 10.20 V 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 100 samples 25 ms /sample 2.50 s	Type A, 1 Trips
			Any response from this battery interface control module to request to NOT test the overvoltage signal	= Overvoltage signal detected	Inverter voltage System Voltage No active DTC's: Run Crank Transitions to DTC Clear: Must Send CPID	> 312 V > 10.20 V Cell Voltage Circuit Open (see Fault Bundle Page) BICM Loss of Comm (see Fault Bundle page) = ON for > 5 seconds 0x7E4 07 AE 32 0C 0C 00 00 00	80 failures out of 80 samples 25 ms /sample	

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV Battery Interface Control Module L Cell Overvoltage Signal/ Circuit Performance	P3253	<p>This diagnostic monitors the battery interface control module's secondary voltage sensing system for its ability to detect a voltage which is too high. Each battery interface control module has the ability to enter an over voltage performance test where it applies a high voltage on its secondary voltage sensing input. These performance tests are not continuous monitors and instead are run once to completion on each run-crank rising edge transition. Upon failure the test is retried a calibrated number of times. If the calibrated number of retries is exceeded, the test will fail.</p> <p>If any of these tests fail for this module, the diagnostic will fail. If all of these tests for this module pass, the diagnostic will pass.</p>	Any response from this battery interface control module to the request to test the overvoltage signal	= Overvoltage signal not detected > 10 seconds	<p>Run Crank Transitions to</p> <p>Inverter voltage</p> <p>System Voltage</p> <p>No active DTC's:</p>	<p>= ON for > 5 seconds</p> <p>> 312 V</p> <p>> 10.20 V</p> <p>Cell Voltage Circuit Open (see Fault Bundle Page</p> <p>BICM Loss of Comm (see Fault Bundle page)</p>	<p>Failure after 4 retries without a pass</p> <p>50.00 s</p>	Type A, 1 Trips

18 OBDG01 HPC2 (VICM) - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Transmissio n Control Module	U0101	Detects that CAN serial data communication has been lost with the TCM on Bus A	Messages have not been received from the TCM for a specified time	$\geq 1500\text{ms}$	Controller On Bus A Communication Enabled Bus A Off Inhibit (Battery Voltage OR Battery Voltage Transition: From To for time required)	=TRUE >= 5 seconds =FALSE > 10.20 V ≤ 10.20 V ≥ 11.00 V ≥ 5,000.00 ms	Runs in 10ms loop	Type A, 1 Trips

OAT Emission Status (OAT Emission Status)

Conditions for Ambient Temperature Emissions Status Using OAT Sensor to be Valid

OAT Validity is VALID where no OAT diagnostic fault active for DTC P0071, P0072, P0073, P0074

If all of the following conditions are TRUE, the Mask = Use Data

1. Startup OAT is less than previous trip EAT

OR

2. Startup ECT - previous trip EAT $\leq 0^{\circ}\text{C}$

OR

3. Engine Off Time $\geq 7,200$ seconds

OR

4. At startup, time since previous EAT valid and able to learn $\geq 3,600$ seconds

OR

5. EAT - current OAT $0^{\circ}\text{C} \leq \text{difference} \leq 2^{\circ}\text{C}$

OR

6. EAT < current OAT and speed timer ≥ 420 seconds
and current OAT - EAT $\leq 2^{\circ}\text{C}$

Speed timer increments at 100msec rate and increments vary based on the vehicle speed as follows:

Vehicle speed < 26 mph for 2 seconds

26 mph < speed < 56 mph for 1 seconds

56 mph < speed < 199 mph for 2 seconds

199 mph < speed < 200 mph for 2 seconds

Speed timer can never be less than 0 seconds

If OAT Validity = VALID and Mask = Use Data, then Status = VALID

OAT Corrected Status (OAT Corrected Status)

Conditions for Corrected / Estimated Ambient Temperature Status Using OAT Sensor to be Valid

OAT Validity is VALID where no OAT diagnostic fault active for DTC P0071, P0072, P0073, P0074

AND

Engine Time Off Validity = VALID

AND

Vehicle Speed Validity = VALID

AND

If all of the following conditions are TRUE, the Mask = Use Data

1. Startup OAT is less than previous trip EAT

OR

2. Startup ECT - previous trip EAT $\leq 0^{\circ}\text{C}$

OR

3. Engine Off Time $\geq 7,200$ seconds

OR

4. At startup, time since previous EAT valid and able to learn $\geq 3,600$ seconds

OR

5. EAT - current OAT $0^{\circ}\text{C} \leq \text{difference} \leq 2^{\circ}\text{C}$

OR

6. EAT < current OAT and speed timer ≥ 420 seconds

and current OAT - EAT $\leq 2^{\circ}\text{C}$

Speed timer increments at 100msec rate and increments vary based on the vehicle speed as follows:

Vehicle speed < 26 mph for 2 seconds

26 mph < speed < 56 mph for 1 seconds

56 mph < speed < 199 mph for 2 seconds

199 mph < speed < 200 mph for 2 seconds

Speed timer can never be less than 0 seconds

If OAT Validity = VALID and Mask = Use Data, then Status = VALID

OAT Arbitrated Status (OAT Arbitrated Status)

Conditions for Arbitrated Ambient Temperature Status Using OAT Sensor to be Valid

Path 1:
Run Crank Active Fault Active Flag is TRUE (DTC P2534 or P2535)
AND
Vehicle Power Mode Status is Valid
AND
Vehicle Power Mode = Run
THEN
Outside Air Temperature Arbitrated Status = Outside Air Temperature Corrected Status (See tab)
ELSE
Outside Air Temperature Arbitrated Status = Outside Air Temperature Emissions Status (See tab)

Path 2:
Run Crank Active Fault Active Flag is TRUE (DTC P2534 or P2535)
AND
Run Crank Active = TRUE
AND
Accessory = TRUE
THEN
Outside Air Temperature Arbitrated Status = Outside Air Temperature Corrected Status (See tab)
ELSE
Outside Air Temperature Arbitrated Status = Outside Air Temperature Emissions Status (See tab)

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - CompON_FaultHi

Description: Compressor Speed Feedback Rationality - Compressor ON - Fail Threshold High										
y/x	0	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000
1	900	900	900	900	900	900	900	900	900	900

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - CompON_FaultLo

Description: Compressor Speed Feedback Rationality - Compressor ON - Fail Threshold Low

y/x	0	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000
1	-900	-900	-900	-900	-900	-900	-900	-900	-900	-900

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - CompON_RepassHi

Description: Compressor Speed Feedback Rationality - Compressor ON - Repass Threshold High										
y/x	0	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000
1	875	875	875	875	875	875	875	875	875	875

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - CompON_RepassLo

Description: Compressor Speed Feedback Rationality - Compressor ON - Repass Threshold Low

y/x	0	1,000	2,000	3,000	4,000	5,000	6,000	7,000	8,000	9,000
1	-875	-875	-875	-875	-875	-875	-875	-875	-875	-875

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - P0D5C Fail Threshold

Description:									
y/x	-40.00	-18.00	-12.00	0.00	68.00	70.00	75.00	87.00	96.00
0.00	11.66	11.66	53.18	53.18	53.18	51.00	48.08	8.74	0.00
440.00	12.43	12.43	56.71	56.71	56.71	54.37	51.27	9.32	0.00
880.00	13.20	13.20	60.23	60.23	60.23	57.75	54.45	9.90	0.00
1,320.00	13.66	13.66	62.32	62.32	62.32	59.76	56.35	10.25	0.00
1,760.00	13.71	13.71	62.54	62.54	62.54	59.97	56.54	10.28	0.00
2,200.00	13.77	13.77	62.81	62.81	62.81	60.23	56.79	10.33	0.00
2,640.00	13.82	13.82	63.05	63.05	63.05	60.46	57.00	10.37	0.00
3,520.00	13.95	13.95	63.65	63.65	63.65	61.03	57.55	10.46	0.00
3,960.00	13.95	13.95	63.65	63.65	63.65	61.03	57.55	10.46	0.00

Initial Supporting table - PCOD Pump Feedback Fault High

Description: Pump Feedback Fault High Threshold										
y/x	10	11	20	30	40	50	60	70	80	90
1	800	800	800	800	800	800	800	800	800	800

Initial Supporting table - PCOD Pump Feedback Fault Low Threshold										
Description: Pump Feedback Fault Low Threshold										
y/x	10	11	20	30	40	50	60	70	80	90
1	-800	-800	-800	-800	-800	-800	-800	-800	-800	-800

Initial Supporting table - PCOD Pump Feedback Repass High Threshold										
Description: Pump Feedback Repass High Threshold										
y/x	10	11	20	30	40	50	60	70	80	90
1	600	600	600	600	600	600	600	600	600	600

Initial Supporting table - PCOD Pump Feedback Repass Low Threshold										
Description: Pump Feedback Repass Low Threshold										
y/x	10	11	20	30	40	50	60	70	80	90
1	-600	-600	-600	-600	-600	-600	-600	-600	-600	-600

Initial Supporting table - RESS Pump Feedback Fault high Threshold										
Description:										
y/x	10	11	20	30	40	50	60	70	80	90
1	450	450	450	450	450	450	450	450	450	450

Initial Supporting table - RESS Pump Feedback Fault low Threshold

Description:										
y/x	10	11	20	30	40	50	60	70	80	90
1	-450	-450	-450	-450	-450	-450	-450	-450	-450	-450

Initial Supporting table - RESS Pump Feedback Repass High Threshold										
Description:										
y/x	10	11	20	30	40	50	60	70	80	90
1	-250	-250	-250	-250	-250	-250	-250	-250	-250	-250

Initial Supporting table - RESS Pump Feedback Repass Low Threshold										
Description:										
y/x	10	11	20	30	40	50	60	70	80	90
1	250	250	250	250	250	250	250	250	250	250

18 OBDG01 HPC2 (VICM) Supporting Tables

Initial Supporting table - KtBSED_P_BPD_D_EndOfLifePwrThrsh

Description:							
y/x	-30	-20	-10	0	20	30	50
10	-3.728	-3.134	-6.983	-11.552	-39.206	-75.000	-75.000
20	-5.119	-9.330	-17.391	-34.447	-75.000	-75.000	-75.000
30	-6.290	-14.000	-24.966	-46.175	-75.000	-75.000	-75.000
50	-7.831	-18.246	-32.027	-57.443	-75.000	-75.000	-75.000
70	-9.007	-21.403	-38.385	-66.691	-75.000	-75.000	-75.000
80	-9.255	-22.078	-39.743	-69.341	-75.000	-75.000	-75.000
90	-9.463	-22.666	-40.876	-71.805	-75.000	-75.000	-75.000

Initial Supporting table - KtBSED_U_BOV_CellVoltThresh

Description:									
y/x	-30	-20	-10	0	10	20	30	40	50
1	4.564	4.564	4.564	4.564	4.564	4.564	4.564	4.564	4.564

Initial Supporting table - KtBSED_U_BOV_PackVoltThresh

Description:									
y/x	-30	-20	-10	0	10	20	30	40	50
1	438.300	438.300	438.300	438.300	438.300	438.300	438.300	438.300	438.300

Initial Supporting table - KtBSED_U_BUV_CellVoltThresh

Description:									
y/x	-30	-20	-10	0	10	20	30	40	50
1	1.550	1.550	1.720	1.720	1.720	1.720	1.720	1.720	1.720

Initial Supporting table - KtBSED_U_BUV_PackVoltThresh

Description:									
y/x	-30	-20	-10	0	10	20	30	40	50
1	148.900	148.900	164.900	164.900	164.900	164.900	164.900	164.900	164.900

18 OBDG01 Fault Bundle Definitions

Bundle Name: Battery Current Sensor
P0AC1, P0AC2, P1EBA, P1A07, P0B13, P0B10, P0B11, P1EBB, (U0111 and U185A)
Bundle Name: Battery Voltage Sensor
P0ABC, P0ABD, P1A07, P0AF8, P0ABB, (U0111 and U185A)
Bundle Name: CellVoltageRationalityFA
P0B3D, P0B42, P0B47, P0B4C, P0B51, P0B56, P0B5B, P0B60, P0B65, P0B6A, P0B6F, P0B74, P0B79, P0B7E, P0B83, P0B88, P0B8D, P0B92, P0B97, P0B9C, P0BA1, P0BA6, P0BAB, P0BB0, P0BB5, P0BBA, P1B17, P1B1A, P1B1D, P1B20, P1B23, P1B26, P1B46, P1B49, P1B4C, P1B4F, P1B52, P1B55, P1B58, P1B5B, P1B5E, P1B61, P1B64, P1B67, P1B6A, P1B6D, P1B70, P1B73, P1B76, P1B79, P1B7C, P1B7F, P1B82, P1B85, P1B88, P1B8B, P1B8E, P1B91, P1B94, P1B97, P1B9A, P1B9D, P1BA0, P1BA3, P1BA6, P1BA9, P1BAC, P1BAF, P1BB2, P1BB5, P1BB8, P1BBB, P1BBE, P1BC1, P1BC4, P1BC7, P1BCA, P1BCD, P1BD0, P1BD3, P1BD6, P1BD9, P1BDC, P1BDF, P1BE2, P1BE5, P1BE8, P1BEB, P1BEE, P1BF1, P1BF4, P1BF7, P1BFA, P1BFD, P1E02, P1E05, P0B3E, P0B43, P0B48, P0B4D, P0B52, P0B57, P0B5C, P0B61, P0B66, P0B6B, P0B70, P0B75, P0B7A, P0B7F, P0B84, P0B89, P0B8E, P0B93, P0B98, P0B9D, P0BA2, P0BA7, P0BAC, P0BB1, P0BB6, P0BBB, P1B18, P1B1B, P1B1E, P1B21, P1B24, P1B27, P1B47, P1B4A, P1B4D, P1B50, P1B53, P1B56, P1B59, P1B5C, P1B5F, P1B62, P1B65, P1B68, P1B6B, P1B6E, P1B71, P1B74, P1B77, P1B7A, P1B7D, P1B80, P1B83, P1B86, P1B89, P1B8C, P1B8F, P1B92, P1B95, P1B98, P1B9B, P1B9E, P1BA1, P1BA4, P1BA7, P1BAA, P1BAD, P1BB0, P1BB3, P1BB6, P1BB9, P1BBC, P1BBF, P1BC2, P1BC5, P1BC8, P1BCB, P1BCE, P1BD1, P1BD4, P1BD7, P1BDA, P1BDD, P1BE0, P1BE3, P1BE6, P1BE9, P1BEC, P1BEF, P1BF2, P1BF5, P1BF8, P1BFB, P1BFE, P1E03, P1E06, P0B3B, P0B40, P0B45, P0B4A, P0B4F, P0B54, P0B59, P0B5E, P0B63, P0B68, P0B6D, P0B77, P0B7C, P0B81, P0B86, P0B8B, P0B95, P0B9A, P0B9F, P0BA4, P0BA9, P0BAE, P0BB3, P0BB8, P1B28, P1B29, P1B2A, P1B2B, P1B2C, P1B2D, P1E4C, P1E4D, P1E4E, P1E4F, P1E50, P1E51, P1E52, P1E53, P1E54, P1E56, P1E57, P1E58, P1E59, P1E5A, P1E5B, P1E5C, P1E5D, P1E5E, P1E5F, P1E60, P1E61, P1E62, P1E63, P1E64, P1E65, P1E66, P1E67, P1E68, P1E69, P1E6A, P1E6B, P1E6C, P1E6E, P1E6F, P1E70, P1E71, P1E72, P1E73, P1E74, P1E75, P1E76, P1E77, P1E78, P1E79, P1E7A, P1E7B, P1E7C, P1E7D, P1E7E, P1E7F, P1E80, P1E81, P1E82, P1E83, P1E84, P1E86, P1E87, P1E88, P1E89, P1E8A, U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624, P1EB1, P1EB2, P1EB3, P1EB4, P1EB5, P1FA6, P1FA7, P1FA8, P1FA9, P1FAA, P1FAB, P3030, P303B
Bundle Name: TempRationalityFA
P0AC6, P0ACB, P0AE9, P0BC3, P0C34, P0A9E, P0AC8, P0ACD, P0AEB, P0BC5, P0C36, P0A9D, P0AC7, P0ACC, P0AEA, P0BC4, P0C35, P1EB1, P1EB2, P1EB3, P1EB4, P1EB5, P1FA6, P1FA7, P1FA8, P1FA9, P1FAA, P1FAB, P3030, P303B, U2401, U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624
Bundle Name: VICMVoltageFA
P0B3D, P0B42, P0B47, P0B4C, P0B51, P0B56, P0B5B, P0B60, P0B65, P0B6A, P0B6F, P0B74, P0B79, P0B7E, P0B83, P0B88, P0B8D, P0B92, P0B97, P0B9C, P0BA1, P0BA6, P0BAB, P0BB0, P0BB5, P0BBA, P1B17, P1B1A, P1B1D, P1B20, P1B23, P1B26, P1B46, P1B49, P1B4C, P1B4F, P1B52, P1B55, P1B58, P1B5B, P1B5E, P1B61, P1B64, P1B67, P1B6A, P1B6D, P1B70, P1B73, P1B76, P1B79, P1B7C, P1B7F, P1B82, P1B85, P1B88, P1B8B, P1B8E, P1B91, P1B94, P1B97, P1B9A, P1B9D, P1BA0, P1BA3, P1BA6, P1BA9, P1BAC, P1BAF, P1BB2, P1BB5, P1BB8, P1BBB, P1BBE, P1BC1, P1BC4, P1BC7, P1BCA, P1BCD, P1BD0, P1BD3, P1BD6, P1BD9, P1BDC, P1BDF, P1BE2, P1BE5, P1BE8, P1BEB, P1BEE, P1BF1, P1BF4, P1BF7, P1BFA, P1BFD, P1E02, P1E05, P0B3E, P0B43, P0B48, P0B4D, P0B52, P0B57, P0B5C, P0B61, P0B66, P0B6B, P0B70, P0B75, P0B7A, P0B7F, P0B84, P0B89, P0B8E, P0B93, P0B98, P0B9D, P0BA2, P0BA7, P0BAC, P0BB1, P0BB6, P0BBB, P1B18, P1B1B, P1B1E, P1B21, P1B24, P1B27, P1B47, P1B4A, P1B4D, P1B50, P1B53, P1B56, P1B59, P1B5C, P1B5F, P1B62, P1B65, P1B68, P1B6B, P1B6E, P1B71, P1B74, P1B77, P1B7A, P1B7D, P1B80, P1B83, P1B86, P1B89, P1B8C, P1B8F, P1B92, P1B95, P1B98, P1B9B, P1B9E, P1BA1, P1BA4, P1BA7, P1BAA, P1BAD, P1BB0, P1BB3, P1BB6, P1BB9, P1BBC, P1BBF, P1BC2, P1BC5, P1BC8, P1BCB, P1BCE, P1BD1, P1BD4, P1BD7, P1BDA, P1BDD, P1BE0, P1BE3, P1BE6, P1BE9, P1BEC, P1BEF, P1BF2, P1BF5, P1BF8, P1BFB, P1BFE, P1E03, P1E06, P0B3B, P0B40, P0B45, P0B4A, P0B4F, P0B54, P0B59, P0B5E, P0B63, P0B68, P0B6D, P0B77, P0B7C, P0B81, P0B86, P0B8B, P0B95, P0B9A, P0B9F, P0BA4, P0BA9, P0BAE, P0BB3, P0BB8, P1B28, P1B29, P1B2A, P1B2B, P1B2C, P1B2D, P1E4C, P1E4D, P1E4E, P1E4F, P1E50, P1E51, P1E52, P1E53, P1E54, P1E56, P1E57, P1E58, P1E59, P1E5A, P1E5B, P1E5C, P1E5D, P1E5E, P1E5F, P1E60, P1E61, P1E62, P1E63, P1E64, P1E65, P1E66, P1E67, P1E68, P1E69, P1E6A, P1E6B, P1E6C, P1E6E, P1E6F, P1E70, P1E71, P1E72, P1E73, P1E74, P1E75, P1E76, P1E77, P1E78, P1E79, P1E7A, P1E7B, P1E7C, P1E7D, P1E7E, P1E7F, P1E80, P1E81, P1E82, P1E83, P1E84, P1E86, P1E87, P1E88, P1E89, P1E8A, P0B3C, P0B41, P0B46, P0B4B, P0B50, P0B55, P0B5A, P0B5F, P0B64, P0B69, P0B6E, P0B73, P0B78, P0B7D, P0B82, P0B87, P0B8C, P0B91, P0B96, P0B9B, P0BA0, P0BA5, P0BAA, P0BAF, P0BB4, P0BB9, P1B16, P1B19, P1B1C, P1B1F, P1B22, P1B25, P1B45, P1B48, P1B4E, P1B51, P1B54, P1B57, P1B5A, P1B5D, P1B60, P1B63, P1B66, P1B69, P1B6C, P1B6F, P1B72, P1B75, P1B78, P1B7B, P1B7E, P1B81, P1B84, P1B87, P1B8A, P1B8D, P1B90, P1B93, P1B96, P1B99, P1B9C, P1B9F, P1BA2, P1BA5, P1BA8, P1BAB, P1BAE, P1BB1, P1BB4, P1BB7, P1BBA, P1BBD, P1BC0, P1BC3, P1BC6, P1BC9, P1BCC, P1BCF, P1BD2, P1BD5, P1BD8, P1BDB, P1BDE, P1BE1, P1BE4, P1BE7, P1BEA, P1BED, P1BF0, P1BF3, P1BF6, P1BF9, P1BFC, P1E01, P1E04, U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624, P1EB1, P1EB2, P1EB3, P1EB4, P1EB5, P1FA6, P1FA7, P1FA8, P1FA9, P1FAA,

18 OBDG01 Fault Bundle Definitions

Bundle Name: Cell Voltage Ckt High
P0B3E, P0B43, P0B48, P0B4D, P0B52, P0B57, P0B5C, P0B61, P0B66, P0B6B, P0B70, P0B75, P0B7A, P0B7F, P0B84, P0B89, P0B8E, P0B93, P0B98, P0B9D, P0BA2, P0BA7, P0BAC, P0BB1, P0BB6, P0BBB, P1B18, P1B1B, P1B1E, P1B21, P1B24, P1B27, P1B47, P1B4A, P1B4D, P1B50, P1B53, P1B56, P1B59, P1B5C, P1B5F, P1B62, P1B65, P1B68, P1B6B, P1B6E, P1B71, P1B74, P1B77, P1B7A, P1B7D, P1B80, P1B83, P1B86, P1B89, P1B8C, P1B8F, P1B92, P1B95, P1B98, P1B9B, P1B9E, P1BA1, P1BA4, P1BA7, P1BAA, P1BAD, P1BB0, P1BB3, P1BB6, P1BB9, P1BBC, P1BBF, P1BC2, P1BC5, P1BC8, P1BCB, P1BCE, P1BD1, P1BD4, P1BD7, P1BDA, P1BDD, P1BE0, P1BE3, P1BE6, P1BE9, P1BEC, P1BEF, P1BF2, P1BF5, P1BF8, P1BFB, P1BFE, P1E03, P1E06
Bundle Name: Cell Voltage Ckt Low
P0B3D, P0B42, P0B47, P0B4C, P0B51, P0B56, P0B5B, P0B60, P0B65, P0B6A, P0B6F, P0B74, P0B79, P0B7E, P0B83, P0B88, P0B8D, P0B92, P0B97, P0B9C, P0BA1, P0BA6, P0BAB, P0BB0, P0BB5, P0BBA, P1B17, P1B1A, P1B1D, P1B20, P1B23, P1B26, P1B46, P1B49, P1B4C, P1B4F, P1B52, P1B55, P1B58, P1B5B, P1B5E, P1B61, P1B64, P1B67, P1B6A, P1B6D, P1B70, P1B73, P1B76, P1B79, P1B7C, P1B7F, P1B82, P1B85, P1B88, P1B8B, P1B8E, P1B91, P1B94, P1B97, P1B9A, P1B9D, P1BA0, P1BA3, P1BA6, P1BA9, P1BAC, P1BAF, P1BB2, P1BB5, P1BB8, P1BBB, P1BBE, P1BC1, P1BC4, P1BC7, P1BCA, P1BCD, P1BD0, P1BD3, P1BD6, P1BD9, P1BDC, P1BDF, P1BE2, P1BE5, P1BE8, P1BEB, P1BEE, P1BF1, P1BF4, P1BF7, P1BFA, P1BFD, P1E02, P1E05
Bundle Name: Open Sense Line Fault
P0B3B, P0B40, P0B45, P0B4A, P0B4F, P0B54, P0B59, P0B5E, P0B63, P0B68, P0B6D, P0B72, P0B77, P0B7C, P0B81, P0B86, P0B8B, P0B90, P0B95, P0B9A, P0B9F, P0BA4, P0BA9, P0BAE, P0BB3, P0BB8, P1B28, P1B29, P1B2A, P1B2B, P1B2C, P1B2D, P1E4C, P1E4D, P1E4E, P1E4F, P1E50, P1E51, P1E52, P1E53, P1E54, P1E55, P1E56, P1E57, P1E58, P1E59, P1E5A, P1E5B, P1E5C, P1E5D, P1E5E, P1E5F, P1E60, P1E61, P1E62, P1E63, P1E64, P1E65, P1E66, P1E67, P1E68, P1E69, P1E6A, P1E6B, P1E6C, P1E6D, P1E6E, P1E6F, P1E70, P1E71, P1E72, P1E73, P1E74, P1E75, P1E76, P1E77, P1E78, P1E79, P1E7A, P1E7B, P1E7C, P1E7D, P1E7E, P1E7F, P1E80, P1E81, P1E82, P1E83, P1E84, P1E86, P1E87, P1E88, P1E89, P1E8A
Bundle Name: Slave Cell Balancing Fault
P1E92, P1E98, P1E9E, P1EA4, P1FC9, P1FCA, P1FCB, P1FCC, P1FCD, P1FCE, P3036, P3041
Bundle Name: Slave Internal Performance Fault
P1E8E, P1E94, P1E9A, P1EA0, P1FBD, P1FBE, P1FBF, P1FC0, P1FC1, P1FC2, P3034, P303F
Bundle Name: Slave Loss of Comm Fault
U2603, U2604, U2605, U2606, U2617, U2618, U2619, U2620, U2621, U2622, U2623, U2624

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP) Sensor A Circuit	P0335	Diagnostic will fail if a crank sensor pulse was not received (from the ECM's replicated crank signal) during a period of time; if crank sensor pulses are received, the diagnostic will pass.	No crankshaft pulses received.	Crank Sync State= No Activity for ≥ 1.40 s	HWIO based crank decode status	= NOT Disable-Crank	Continuous at every 12.5 msec	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Crankshaft Position (CKP) Sensor A Performance	P0336	1. Fail counts will occur if the engine goes out of synchronization repeatedly over a period of time and will pass if the engine stays in synchronization. 2. Diagnostic will fail if synchronization gap is not found in a specified period of time and will pass if the synchronization gap is found.	Time in which 15.00 crank re-synchronizations occur	Crank Sync State transitions to Activity Detected X times in < 10.00 seconds (without seeing "crank in sync")	HWIO based crank decode status	= NOT Disable-Crank	Continuous every 250 msec	Type B, 2 Trips
			No crankshaft synchronization gap found	Crank Sync State = Activity Detected for >= 1.40 s	HWIO based crank decode status	= NOT Disable-Crank	Continuous every 12.5 msec	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Idle Air Control (IAC) System - RPM Too Low	P0506	This DTC sets when the idle speed is lower than the targeted idle speed	Idle Speed	<p>Fail Criteria: Filtered input speed error (desired - actual), is greater than the fail threshold of 91 RPM. Filter coefficient for engine speed = 0.003</p> <p>Pass Criteria: Filtered input speed error (desired - actual), is less than fail threshold 81 . Filter coefficient for engine speed = 0.003</p>	<p>No Active DTCs:</p> <p>No Active DTCs:</p> <p>No Active DTCs:</p> <p>Accelerator pedal position</p> <p>Engine State</p> <p>Vehicle Speed</p> <p>Engine Coolant</p> <p>Commanded RPM Delta</p> <p>Idle Conditons Present</p>	<p>Motor A speed faults: P0A3F, P1B03, P0A40, P0C52, P0C53, P0C5C, P0C5D</p> <p>Motor B speed faults: P0A45, P1B04, P0A46, P0C57, P0C58, P0C61, P0C62</p> <p>Vehicle Speed/TOS sensor faults: P0722, P077B, P215C</p> <p>Not Defaulted & <= 1.00 %</p> <p>Running (not starting or stopping states)</p> <p><= 2 kph</p> <p>>= 60.00 Deg C</p> <p>< 50 RPM</p> <p>>= 10.00 seconds</p>	<p>1 loop execution at 100 ms rate</p> <p>Pass condition met for 10.00 seconds</p>	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Idle Air Control (IAC) System - RPM Too High	P0507	This DTC sets when the idle speed is higher than the targeted idle speed	Idle Speed	<p>Fail Criteria: Filtered input speed error (desired - actual), is less than the fail threshold of -182 RPM. Filter coefficient for engine speed = 0.003</p> <p>Pass Criteria: Filtered input speed error (desired - actual), is greater than fail threshold -172 . Filter coefficient for engine speed = 0.003</p>	<p>No Active DTCs:</p> <p>No Active DTCs:</p> <p>No Active DTCs:</p> <p>Accelerator pedal position</p> <p>Engine State</p> <p>Vehicle Speed</p> <p>Engine Coolant</p> <p>Commanded RPM Delta</p> <p>Idle Conditons Present</p>	<p>Motor A speed faults: P0A3F, P1B03, P0A40, P0C52, P0C53, P0C5C, P0C5D</p> <p>Motor B speed faults: P0A45, P1B04, P0A46, P0C57, P0C58, P0C61, P0C62</p> <p>Vehicle Speed/TOS sensor faults: P0722, P077B, P215C</p> <p>Not Defaulted & <= 1.00 %</p> <p>Running (not starting or stopping states)</p> <p><= 2 kph</p> <p>>= 60.00 Deg C</p> <p>< 25 RPM</p> <p>>= 10.00 seconds</p>	<p>1 loop execution at 100 ms rate</p> <p>Pass condition met for 10.00 seconds</p>	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage Performance	P0561	This diagnostic detects a difference in voltage between the 12V input and the Ignition Run/Crank Voltage. The fault sets when the host controller detects the difference is above the indicated threshold for the indicated time.	Difference between 12V Battery Voltage Input and Ignition Run/Crank Voltage	> 3.00 Volts	Enable Calibration is True Diagnostic System Code Clear Requested Diagnostic System Reset Complete Battery input is present Ignition Run/Crank Voltage 12V Starter Engaged	= 1.00 (1 is Enabled) = False = True = 1.00 (1 is Available) > 6.0 Volts = False	4 seconds out of a 5 seconds window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage Low	P0562	This diagnostic detects low voltage in the vehicle's 12 volt system. The fault sets when the THCP detects supply voltage below the indicated threshold for the indicated time.	Ignition Voltage	≤ 10.00 Volts	Enable Calibration is True 12V Starter Engaged Ignition Run/Crank Voltage Engine Speed	= 1.00 (1 is Enabled) = False > 6.0 Volts ≥ 0.00 RPM	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage High	P0563	This diagnostic detects high voltage in the vehicle's 12 volt system. The fault sets when the host controller detects supply voltage above the indicated threshold for the indicated time.	Ignition Voltage	≥ 16.00 Volts	Enable Calibration is True Ignition Run/Crank Voltage	= 1.00 (1 is Enabled) > 6.0 Volts	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Read Only Memory (ROM)	P0601	This Diagnostic tests ROM (flash) memory in the THCP micro-controller. The test checks that ROM has not changed since it was flashed in the plant. The bytes of ROM in different areas (code, calibration, HW configuration, etc.) are summed and compared to a checksum for that area. The checksum is created when the software is built and does not change over time. The DTC sets when the checksum comparison does not match for the indicated number of times.	Calculated Checksum of the Boot ROM	≠ Expected Checksum	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 5 failures	Type A, 1 Trips
			2nd Processor State of Health ROM fault latched	= TRUE	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	Runs continuously in the background	
			Calculated Checksum of Torque Security Related Calibrations	≠ Expected Checksum	Controller Status (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) = Disable Calibration is False = Enable Calibration is True	= On = False = True = 0 (0 is Enabled) = 1 (1 is Enabled)	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 2 failures	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			ECC Fault detected in Flash memory	= TRUE	Controller Status Power Up Reset AND HWIO BINVDM ECC State AND HWIO ROM Fault Enable Calibration is true	= On = False = False = True = 1 (1 is Enabled)	Greater than 0 failures at controller initialization Runs once at initialization	
			ROM fault Active AND 2nd SOH ROM Fault Latched AND Main SOH ROM Fault Latched	≠ True ≠ True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs in the Background	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Not Programmed	P0602	This Diagnostic checks that the THCP micro-controller has a valid calibration flashed into it. The controller manufacturer flashes a calibration with a particular calibration set to 1. At the vehicle plant the controller is reflashed with a valid calibration that also changes the particular calibration set to 0. The DTC sets when the diagnostic checks that particular calibration and it has a nonzero value.	No Start Calibration is True	= 0 (1 is for No Start Condition)	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at controller initialization and every 1 second there after	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Reset	P0603	This Diagnostic tests the NonVolatile Memory (NVM) in the THCP micro-controller for changes since the last write at power down. The bytes of various NVM sections are summed and compared to checksums for each section that were stored at the last powerdown. The DTC sets when the checksum comparisons do not match.	Static NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	Type A, 1 Trips
			Preserved NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Power Up Reset BINVDM NVM Checksum at power-up	= False ≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	Runs once at controller initialization 3 out of 5 controller initializations for Failure	
			Dynamic NVM checksum at power-up AND Shutdown Finished	≠ Checksum at power-down = TRUE	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Static NVM Error Dynamic NVM Error BINVDM ECC Error	= False = False = False	Enable Calibration is True	= 1 (1 is Enabled)	Runs once at controller initialization	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Random Access Memory (RAM)	P0604	This Diagnostic tests the RAM in the THCP micro-controller. The diagnostic checks that RAM has not changed unexpectedly. Pattern checks are done at initialization where different patterns are written and then read back. The DTC sets if the patterns do not match. Continuous checks are done while the controller is executing code that store the same variables in multiple locations. When those variables are read, a check is done to be sure both locations still match. A DTC sets if the locations do not match for the indicated time.	Secure redundant "Y" variable	≠ Primary "V" variable for greater than 125 ms	Current Time Execution - Time of Last DualStore Error	> 25 ms	Executes in Background loop	Type A, 1 Trips
			HWIO detects an illegal write to Write Protected RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop 1 count to fail	
			2nd Processor State of Health RAM Fault Latched	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop every 1000ms	
			Checksum of PreservedNVM_Region for Main Processor State of Health and 2nd Processor State Of Health	≠ Expected checksum value	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization	
			HWIO detects fault in System RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in Cache RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in eTPU RAM (Timer Processing Unit)	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			Main SOH RAM Fault Latched AND SPI Fault Latched	= 0 = False	(Diagnostic System Code Clear Requested AND Diagnostic System Reset	= False = True	Executes in Background loop every 1000ms	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			AND System RAM Fault Count AND Cache RAM Fault Count AND eTPU RAM Fault Count	= 0 = 0 = 0	Complete) Time Since Last Duel Store Error	> 1,000 ms		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Performance	P0606	<p>This Diagnostic tests all the internal processor subsystems for faults which suggest that the integrity of the processor can not be trusted.</p> <p>Fail Case 1: In case of many faults the THCP microprocessor along with the other microprocessors need to take remedial action to directly take the vehicle to a safe state. This fail case tests at powerdown that the microprocessors can take those remedial actions effectively. Potential failures can include memory, software, processor and Arithmetic Logic Unit (ALU) faults. The diagnostic runs by setting different controller inputs and the outputs are checked in each case across all of the microprocessors . The DTC sets when the outputs are not as expected for the indicated number of tests.</p> <p>Fail Case 2, 3, 4, 5, 6:</p>	<p>Inhibit Path Test Failed</p> <p>Indicates that the Processor is not demonstrating the ability to inhibit the system (take remedial action) during the Inhibit Path Test</p> <p>"2ndFailsToTakeRmdlActn"</p>	>= 3 Failures	<p>HV Batt contactor Staus Available</p> <p>Invertor State</p> <p>HV Batt Voltage</p> <p>HV Contactors</p> <p>12V Batt Voltage</p> <p>Vehicle Speed</p> <p>Motor Faults</p> <p>Motor Speed</p> <p>SRAR Shutdowns</p> <p>SPI Fault</p> <p>RunCrank Active</p> <p>Ram or ROM fault</p> <p>Seed received in wrong order fault</p> <p>Seed/Key Timeout</p> <p>Powermode Off time</p>	<p>= TRUE</p> <p>= Off</p> <p>>= 80.00 V</p> <p>= Closed</p> <p>> 9.50 V</p> <p>< 0.00 kph</p> <p>= FALSE (None active)</p> <p><= 20.00 rpm</p> <p>= FALSE</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>= FALSE (No active P0601, P0604)</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>< 5.00 s</p>	<p>Executes in a 12.5ms loop</p> <p>Detects in 3 key cycles</p>	Type A, 1 Trips
			<p>Key Value</p> <p>Indicates that the Processor received incorrect key values for the associated seed values that it sent out to the secondary processor</p>	≠ expected key value	<p>Number Of Main Processors to monitor</p> <p>IPT status</p> <p>SPI Fault</p>	<p>> 0</p> <p>= Not Running</p> <p>= FALSE (No active P0606)</p>	<p>Executes in a 12.5ms loop</p> <p>Detects in 150ms or two consecutive faulty keys</p>	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>The microprocessors in the TPIM ECU monitor that each of the others is executing code correctly and in a timely manner. These fail cases rely on a seed and key interaction where one micro-controller sends a seed and a second controller runs a predefined set of calculations and responds with a key. The first controller sends a seed and checks that the received key matches its lookup table value for that seed and that it was received in time. The second controller checks that the correct seed value has been received and that is in time. The DTC sets when there is a mismatch of seed or key values or the expected key or seed value is out of order or if the key or seed value has not been received in the indicated time.</p> <p>Fail Case 7, 8, 9: These diagnostics are built into the hardware of the THCP microprocessor by the chip manufacturer. These diagnostics</p>	"2ndRxIncorrectKeys"		Run/Crank Voltage	>= 9.50 V		
			<p>New Seed Update Time</p> <p>Indicates that the Processor did not receive a key value from the secondary processor during the expected time frame "MainDtctdSdKeyTimeout"</p>	> 1.00 sec	<p>Number Of Mains Processors to monitor AND SPI Faults AND Seed/Key Init delay timer AND Run/Crank Voltage OR 12V Battery Voltage</p>	<p>> 0 = FALSE (No active P0606) >= 1.00 s >= 9.50 V > 11 V</p>	<p>Executes in a 12.5ms loop Detects in 1 second</p>	
			<p>Seed sequence</p> <p>Indicates that the Processor received key values in the incorrect order from the secondary processor "MainDtctdSdRxWrongOrder"</p>	≠ expected order	<p>Number Of Mains Processors to monitor AND SPI Faults AND Run/Crank Voltage OR 12V Battery Voltage</p>	<p>> 0 = FALSE (No active P0606) >= 9.50 V > 11 V</p>	<p>0.15 seconds out of a 0.2 seconds window Executes in a 12.5ms loop</p>	
			<p>Program Sequence Watch Seed time Since Seed Change</p> <p>Indicates that the Processor detected that a program Seed was not sending for the Program Sequence Watch "MainSequenceFlt"</p>	> 0.20 ms	Program Sequence Watch Enabled (KaPISD_b_ProgSeqWatchEnbl[x])	= TRUE	Executes in a 50ms loop after controller initialization	
			<p>Program Sequence Watch Fault on a CPU</p> <p>Indicates that the Processor detected that a program was ran out of sequence according to the Program Sequence Watch "MainSequenceFlt"</p>	seed sequence ≠ expected sequence	Program Sequence Watch Enabled (KaPISD_b_ProgSeqWatchEnbl[x])	= TRUE	0.15 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>check the ALU and Configuration registers to ensure there have been no changes. The DTC sets if these registers have changed since the software flash at the vehicle plant. An additional built in diagnostic checks whether the top of the stack memory has changed from initialization at power up. The DTC sets if this section of memory has been detected to have changed for the indicated amount of time.</p> <p>Fail Case 10: This diagnostic checks the analog to digital converter (ADC) in the THCP microprocessor. If the accuracy of the ADC read of a test voltage is greater than the indicated threshold for the indicated amount of time then the DTC sets.</p> <p>Fail Case 11, 12: These diagnostics use microprocessor internal circuitry to detect if there are faults in the RAM or Flash memory. The checks occur at power up and will set</p>	<p>HWIO detects Fault in ALU Test</p> <p>Indicates that the Processor detected an ALU fault in the processor "MainALU_Flt"</p>	= 2 faults in a key cycle	<p>Enabled Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p> <p>= False</p> <p>= False</p>	Runs continuously in 12.5ms loop	
			<p>HWIO detects Fault in Configuration Registry Test</p> <p>Indicates that the Processor detected a Configuration Register fault in the processor "MainCfgRegFlt"</p>	= 2 faults in a key cycle	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p> <p>= False</p> <p>= False</p>	Runs continuously in 12.5ms loop	
			<p>HWIO detects Fault in the Stack Limit Test</p> <p>Indicates that the CPU Stack memory exceeded the limit "MainStackFlt"</p>	= 2 faults since power up	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p>	Runs Continuously in 100ms loop	
			<p>Voltage difference between expected circuit voltage and actual test circuit voltage</p> <p>Indicates that the</p>	> 9 V	<p>Enable Calibration is True AND Run/Crank Voltage</p> <p>(Diagnostic System Code Clear Requested</p>	<p>= 1 (1 is Enabled)</p> <p>>= 7 V</p> <p>= False</p>	<p>0.15 seconds out of a 0.2 seconds window</p> <p>OR</p> <p>A2D Converter Test Error >=</p>	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		the DTC if there are the indicated number of failures in each diagnostic.	Processor detected a problem with the Analog to Digital convertor test circuit "MainADC_Flt"		AND Diagnostic System Reset Complete)	= True	0.20 seconds	
		Fail Case 13: This diagnostic checks the circuitry that transfers data from Flash memory to RAM. When the data transfer is made at startup and periodically there after a set of bytes are included that can be checked. The DTC sets if these bytes in RAM are not equal to the Flash memory.	HWIO detects Fault that the Processor detected a problem with the Flash ECC (error correction code) test circuit "FlashECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3.00 failed cycles out of 10.00 cycles (turns on MIL) 5.00 failed cycles out of 10.00 cycles (shutdown vehicle)	
			HWIO detects Fault that the Processor detected a problem with the RAM ECC (error correction code) test circuit "RAM_ECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3.00 failed cycles out of 10.00 cycles (turns on MIL) 5.00 failed cycles out of 10.00 cycles (shutdown vehicle)	
			HWIO detects Fault in Transfer Test from Flash to RAM OR HWIO detects Fault in the Memory Data From Flash Indicates that the	= TRUE = TRUE	Enable Calibration is True (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1 (1 is Enabled) = False = True	50ms Execution Rate after controller initialization	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Processor detected a problem in the data transfer from Flash memory to RAM memory "DMA_XferTest"					
			First ROM Test Complete AND Processor Performance System Run Time Met AND Processor Integrity Fault Lower AND Processor Integrity Fault Upper	= True = 1 (1 is Enabled) after Controller Initialization = No Fault = No Fault	End of Test in Progress AND Diagnostic End of Trip in Progress AND Inhibit Path Test State	= True = False = Test Aborted OR Test Completed	Executes at the end of every trip	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Torque Performance	P061A	This Diagnostic tests if the regenerative braking function is producing too much torque. Potential failures can include memory, software, processor and ALU faults. If the total output torque, including regenerative torque, is greater than the regenerative braking request plus the maximum output torque allowed or the output torque is greater than the regenerative braking request plus the actual output torque request plus the indicated threshold then the DTC is set.	Calculated Output Torque (To)	> Upper limit of Output Torque (ToMax) plus Regen Torque Request OR > Regen Torque Request plus Output Torque Request plus 363.00 Nm threshold	Ignition Run Crank Security Voltage OR Ignition Run/Crank Voltage AND Enable Calibration is True	>= 9.50 V >= 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Torque Calculation Performance	P061B	Fail Case 1: This Diagnostic tests the calculation of output torque. Potential failures can include memory, software, processor and ALU faults. The primary calculated output torque value is compared to the secondary calculated output torque and if that difference is greater than the indicated threshold for the indicated time the fault is set. The DTC is also set if the regenerative braking minus the indicated calibration is greater than the indicated threshold for greater than the indicated time.	Difference between Immediate Axle Torque command primary and secondary OR Regen Brake Torque Output command minus 0.00 Nm	> 363.00 Nm ≥ 342.00 Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Enable Calibration is True	≥ 9.50 V ≥ 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	Type A, 1 Trips
			Calculated Output Torque (To)	> Max of Drivers Output Torque Request plus 363.00 Nm OR 363.00 Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Enable Calibration is True	≥ 9.50 V ≥ 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	
			Calculated Output Torque (To)	< Min of Drivers Output Torque Request minus 363.00 Nm OR - 363.00 Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Enable Calibration is True	≥ 9.50 V ≥ 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	
		Fail Case 2 This diagnostic tests the calculation of output torque. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated output torque value is greater than the driver's calculated torque request plus the indicated calibration.	[Trans Range State AND Output Torque Command AND Shaped Torque for Sign Diff test] OR [Trans Range State AND Output Torque Command AND Shaped Torque for Sign Diff test]	= Drive ≤ -363.00 Nm ≥ 0Nm = Reverse ≥ 363.00 Nm ≤ 0Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Transient Torque Condition AND (Computed TOS OR ((Computed TOS AND Vehicle Direction Error) OR Vehicle speed rationality)) Enable Calibration is True	≥ 9.50 V ≥ 11.00 V = FALSE ≤ 236.00 rpm > 135.00 rpm = TRUE = TRUE = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 3: This diagnostic tests the calculation of output torque. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated output torque value is less than the driver's calculated torque request minus the indicated calibration. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 4: This diagnostic tests the calculation of output torque request. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated output torque request is less than the indicated threshold and the transmission is in Drive. The fault is also set if the calculated output torque request is</p>	Motor A torque command	> ShortTerm motor A capacity plus 126.00 Nm OR < ShortTerm motor A capacity minus 126.00 Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Enable Calibration is True	>= 9.50 V >= 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	
			Motor B torque command	> ShortTerm motor B capacity plus 118.00 Nm OR < ShortTerm motor B capacity minus 118.00 Nm	Run/Crank Voltage OR Ignition Run/Crank Voltage Enable Calibration is True	>= 9.50 V >= 11.00 V = 0 (0 is Enabled)	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>greater than the indicated threshold and the transmission is in Reverse. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 5: This diagnostic tests the calculation of motor A torque request. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated motor A torque request is greater than the short term motor A capacity plus the indicated threshold. The fault is also set if the calculated motor A torque is less than the motor A capacity minus the indicated threshold. The DTC is set if either fault is present for longer than the indicated time.</p> <p>Fail Case 6: This diagnostic tests the calculation of motor B torque request. Potential failures can include memory, software, processor and ALU faults. The fault is set if the</p>						

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		calculated motor B torque request is greater than the short term motor B capacity plus the indicated threshold. The fault is also set if the calculated motor B torque is less than the motor B capacity minus the indicated threshold. The DTC is set if either fault is present for longer than the indicated time.						

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Performance	P062F	This Diagnostic tests specific areas of nonvolatile memory (NVM). The fault sets If the last write to nonvolatile memory was not successful or if the checksum of static NVM does not agree with the latest summation of that memory area. The NVM write and records the success or not of that write at key off and the success value is read at initialization.	HWIO reports next write to NVM will not succeed OR HWIO reports the assembly calibration integrity check has failed	= True = True	Enable Calibration is True Controller Status	= 1 (1 is Enabled) = Initialization	Runs once at controller initialization	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD1 Actuator Supply Circuit Voltage Low	P0658	This diagnostic reports when a high side driver 1 circuit low fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit low is present or not. HSD 1 Short to Ground Fault Status	=TRUE	Enable Calibration is True HSD 1	= 1 (1 is Enabled) = On	0.13125 seconds out of a 0.15625 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD1 Actuator Supply Circuit Voltage High	P0659	This diagnostic reports when a high side driver 1 circuit high fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit high is present or not. HSD 1 Short to Power Fault Status	=TRUE	Enable Calibration is True	= 1 (1 is Enabled)	0.00625 seconds (1 Loop)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Torque Managment System - Forced Engine Shutdown	P06AF	This THCP Diagnostic checks that the ECM is processing code correctly. The ECM has a main and a secondary processor. As long as the main ECM processor responds to the secondary ECM processor correctly then the correct pattern is sent via CAN message to the THCP. When the ECM does not have correct interaction between its two microprocessors then an incorrect pattern is sent to the THCP and the THCP sets the DTC.	Received pattern from the ECM OR Received malfunction pattern	≠ expected pattern (F, 5, B, D, A, 6, 3, 0) >= 2 counts	Run/Crank Voltage OR Ignition Run/Crank Voltage Run Crank Active Time	>= 9.50 V >= 11.00 V >= 0.10 seconds	0.1 seconds out of a 0.15 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply C Circuit Low	P06E7	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	< 12.00 V	Wakeup Signal	ON	0.32 seconds out of a 0.4 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply C Circuit High	P06E8	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	> 22.00 V	Wakeup Signal	ON	0.32 seconds out of a 0.4 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Performance	P0711	Monitors the performance of Transmission Fluid Temperature (TFT) circuit by comparing the temperature calculated from the resistance vs temp table to an estimated cold soak average temperature or verifying that the temperature calculated from the resistance vs temp table has not latched at a value after a period of time.	Transmission Fluid Temperature Sensor compared to a Cold Soak Average Temperature	\geq (See supporting tables for failure threshold value) Cold Soak Rationality	Rationality Enable Calibration is True Time after init controller Cold Soak Enable Calibration is True Cold Soak Average Temperature Message Cold Soak Average Temperature P0712, P0713, U179A, U0293 TFT temperature	= 1 (1 is Enabled) ≥ 3.00 seconds = 1 (1 is Enabled) = Use Data ≥ -40.00 C NOT Fault Active $-40.00 \leq X \leq 130.00$ C	One diagnostic loop once all enable criteria have been met	Type A, 1 Trips
			Continuous Check for Transmission Fluid Temperature Stuck in Range Transmission Oil Temperature Raw - Previous Transmission Oil Temperature	≤ 0.00 C	Rationality Enable Calibration is True Time after init controller Continuous Rationality Enable Calibration is True Engine Speed Vehicle Speed Transmission Oil Temperature Raw	= 1 (1 is Enabled) ≥ 3.00 seconds = 1 (1 is Enabled) $0.00 \leq X \leq 7,500.00$ RPM for 5.00 seconds ≤ 124.27 MPH for 5.00 seconds $-40.00 \leq X \leq 130.00$ C	≥ 300.00 seconds	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Circuit Low Voltage	P0712	Monitors the Transmission Fluid Temperature (TFT) sensor circuit resistance and reports a low voltage condition if the sensed resistance is below a threshold.	Transmission Fluid Temperature (TFT) circuit resistance	≤ 68.60 ohms (Corresponds to 149 C which is above the operating range of the transmission)	Enable Calibration is True 12V Battery Voltage Ignition Run/Crank Voltage	= 1 (1 is Enabled) > 9.00 for 0.10 seconds > 9.00 for 0.10 seconds	2 seconds out of a 3 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Circuit High Voltage	P0713	Monitors the Transmission Fluid Temperature (TFT) sensor circuit resistance and reports a high voltage condition if the sensed resistance is above a threshold.	Transmission Fluid Temperature (TFT) circuit resistance	$\geq 83,641.00$ ohms (Corresponds to a temperature below -50 C, which is below the operating range of the transmission)	Enable Calibration is True 12V Battery Voltage Ignition Run/Crank Voltage	= 1 (1 is Enabled) > 9.00 for 0.10 seconds > 9.00 for 0.10 seconds	2 seconds out of a 3 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Output Speed (TOS) Sensor Wrong Direction	P0721	The DTC monitors when the TOS direction converted from the TOS sensor output pulse amplitude does not fall within the valid ranges for "Forward" or "Reverse" for a calibrated period of time.	TOS Raw Direction	TOS Direction Raw is not Forward or Reverse	Enable Calibration is True TOS Sample Period TOS Sensor Type	= 1 (1 is Enabled) ≠ 0 = CeTOSR_e_Directional	2.5 seconds out of a 3.125 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit - Direction Error	P077B	The DTC monitors when the TOS direction converted from the TOS sensor output pulse amplitude does not match the TOS direction calculated from the motor A and motor B resolver directions for a calibrated period of time.	Transmission Output Speed Direction Raw	≠ transmission output speed direction calculated from motor A and motor B resolver directions	Enable Calibration is True P0721, P077C, P077D, P215C Hybrid Motor Speed based Estimated Output Speed is Valid Transmission Output Speed and Motor Output Speed Difference Motor Estimated Transmission Output Speed	= 1 (1 is Enabled) NOT Fault Active Calculated based on Stable Speed Equation ≤ 50.00 RPM ≥ 50.00 RPM	0.35 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit Low	P077C	This DTC monitors the transmission output speed sensor signal and reports when the signal voltage is below a calibrated threshold.	Transmission Output Speed Sensor Voltage	< 0.36 Volts	Enable Calibration is True P077D Ignition Run/Crank Voltage 12V Battery Voltage	= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 Volts for 0.00 seconds 9.00 ≤ X ≤ 16.00 V for 0.00 seconds	≥ 0.01 seconds for 36.00 counts at 25 ms	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit High	P077D	This DTC monitors the transmission output speed sensor signal and reports when the signal voltage is above a calibrated threshold.	Transmission Output Speed Sensor Voltage	> 4.25 Volts	Enable Calibration is True P077C Ignition Run/Crank Voltage 12V Battery Voltage	= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 Volts for 0.00 seconds 9.00 ≤ X ≤ 16.00 Volt for 0.00 seconds	≥ 0.01 seconds for 36.00 counts at 25 ms	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 1 Slip	P079A	Monitors clutch 1 slip by comparing the slip speed across the clutch to a slip threshold or comparing the calculated slip energy to an energy threshold.	Clutch 1 Slip Speed	>= 190.00 RPM	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 190.00 kPa > 74.00 Nm =Locked = not faulted =0 =0	Fail Condition met for 0.60 seconds out of 0.80 seconds Retry Count: 3.00	Type A, 1 Trips
			Clutch 1 Energy	>= 8,003.30 J	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 190.00 kPa > 74.00 Nm =Locked = not faulted =0 =0	Instantly once Clutch 1 Energy >= 8,003.30 J Retry Count: 3.00	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 2 Slip	P079B	Monitors clutch 2 slip by comparing the slip speed across the clutch to a slip threshold or comparing the calculated slip energy to an energy threshold.	Clutch 2 Slip Speed	>= 100.00 RPM	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 190.00 kPa > 15.00 Nm =Locked = not faulted =0 =0	Fail Condition met for 2.50 seconds out of 3.33 seconds Retry Count: 3.00	Type A, 1 Trips
			Clutch 2 Energy	>= 5,851.40 J	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 190.00 kPa > 15.00 Nm =Locked = not faulted =0 =0	Instantly once Clutch 1 Energy >= 5,851.40 J Retry Count: 3.00	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 3 Slip	P079C	Monitors clutch 3 slip by comparing slip speed across the clutch to a slip threshold.	Clutch 3 Slip Speed	>= 100.00 RPM	Line Pressure Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 190.00 kPa =Locked = not faulted =0 =0	Fail Condition met for 1.00 seconds out of 1.25 seconds Retry Count: 1.00	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 1 Stuck On	P07A3	Detects if clutch 1 is stuck on by comparing actual clutch 1 slip speed to a desired slip profile or by detecting that slip across the clutch is not above a threshold when slip is expected.	C1 Offgoing Slip Expected	=1	Motor Speed Clutch 1 State	= not faulted = offgoing	Fail condition met for 0.50 seconds out of 0.75 seconds. Retry Count: 3.00	Type A, 1 Trips
			C1 Slip Speed	=< Clutch1FailSlipSpeed (See supporting table)	Clutch Status Shutdown command	=Released =0	Fail condition met for 0.50 seconds out of 0.75 seconds. Retry Count: 3.00	
			C1 Profiled Slip Speed	>= Clutch1ProfiledSlipSpdThd (See supporting table)	Motor Speed	=not faulted	Retry Count: 3.00	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 2 Stuck On	P07A5	Detects if clutch 2 is stuck on by comparing actual clutch 2 slip speed to a desired slip profile or by detecting that slip across the clutch is not above a threshold when slip is expected.	C2 Offgoing Slip Expected	=1	Motor Speed Clutch 2 State	= not faulted =off going	Fail condition met for 0.50 seconds out of 0.75 seconds. Retry Count: 3.00	Type A, 1 Trips
			C2 Slip Speed	=< Clutch2FailSlipSpeed (See supporting table)	Clutch Status Shutdown command	=Released =0	Fail condition met for 0.50 seconds out of 0.75 seconds. Retry Count: 3.00	
			C2 Profiled Slip Speed	>= Clutch2ProfiledSlipSpeedThd (See supporting table)	Motor Speed	= not faulted	Retry Count: 3.00	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 3 (Diode) Stuck	P07A7	Detects if clutch 3 is stuck on by comparing actual clutch 3 slip speed to a desired slip profile.	C3 Slip Speed C3 Profiled Slip Speed	=< Clutch3FailSlipSpeed (See supporting table) >= Clutch3ProfiledSlipSpeedThd (See supporting table)	Clutch Status Shutdown command Motor Speeds	=Released =0 =not faulted	Fail condition met for 0.38 seconds out of 0.50 seconds. Retry Count: 1.00	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit Open	P0960	This DTC sets when the PCSA control circuit has been detected to be open	HWIO circuitry detects if an electrical circuit open is present or not. PCS A Circuit Open Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>=9.00 V and <=16.00V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit Low Voltage	P0962	This DTC sets when the PCSA control circuit has been detected to be shorted to ground	HWIO circuitry detects if an electrical circuit low is present or not. PCS A Circuit Low Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>=9.00 V and <=16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit High Voltage	P0963	This DTC sets when PCS1 has been detected to be shorted to power	HWIO circuitry detects if an electrical circuit high is present or not. PCS A Circuit High Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>=9.00 V and <=16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit Open	P0964	This DTC sets when the PCSB control circuit has been detected to be open	HWIO circuitry detects if an electrical circuit open is present or not PCS B Open Circuit Fault Status	HWIO circuitry detects if an electrical circuit open is present or not. =TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit Low Voltage	P0966	This DTC sets when the PCSB control circuit has been detected to be shorted to ground	HWIO circuitry detects if an electrical circuit low is present or not PCS B Circuit Low Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.075 seconds in a 0.10 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit High Voltage	P0967	This DTC sets when PCSb has been detected to be shorted to power or open circuited	HWIO circuitry detects if an electrical circuit high is present or not. PCS A Circuit High Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit Open	P0968	This DTC sets when the PCSC control circuit has been detected to be open circuit	HWIO circuitry detects if an electrical circuit open is present or not. PCS C Open Circuit Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit Low Voltage	P0970	This DTC sets when the PCSC control circuit has been detected to be shorted to ground	HWIO circuitry detects if an electrical circuit low is present or not. PCS C Circuit Low Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit High Voltage	P0971	This DTC sets when PCSC has been detected to be shorted to power or open circuited.	HWIO circuitry detects if an electrical circuit high is present or not. PCS C Circuit High Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid System Performance	P0AB9	This diagnostic indicates an autostart or autostop attempt has failed or an engine stall has occurred.	Engine Sensed Torque	≤ 0.00 Nm	Commanded Engine Torque Engine State Low Fuel Condition Fuel Level Data Fault Engine Positiong Fault (CAM or Crank) DTC's not Fault Active Number of engine start re-try attempts	> 20.00 Nm = Auto-starting = FALSE = FALSE = FALSE = P16E0 = 2	Diagnostic will set in 15.00 s (runs at 12.5 ms)	Type A, 1 Trips
			Engine Stopping State	= Preparing for Stop OR	Engine State Low Fuel Condition	= Auto-stopping = FALSE	Diagnostic will set in 15.00 s (runs at 12.5 ms)	
			Engine Stopping State	= Disabling Fuel OR	Fuel Level Data Fault Engine Positiong Fault (CAM or Crank)	= FALSE = FALSE		
			Engine Stopping State	= Ramping Down	DTC's not Fault Active	= P16E0		
			Engine Speed	< 300.00 RPM	Engine State Low Fuel Condition Fuel Level Data Fault Engine Positiong Fault (CAM or Crank) DTC's not Fault Active	= Engine Running = FALSE = FALSE = FALSE = P16E0	25.00 RPM * seconds (integrated value) (runs at 12.5ms) (i.e. if RPM is 25.00 below the 300.00 RPM threshold for 1 second, the	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Wheel Slip State	= No Wheel Slip	diagnostic will set, diagnostic will proportionally set faster as RPM dips further below the 300.00 RPM threshold)	
			Engine Speed	< 800.00 AND > 300.00	Engine State Low Fuel Condition Fuel Level Data Fault Engine Positioning Fault (CAM or Crank) DTC's not Fault Active Wheel Slip State	= Engine Running = FALSE = FALSE = FALSE = P16E0 = No Wheel Slip	If the fail conditons are met for 0.50 s	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Phase U Current Low	P0B01	This diagnostic monitors the sensed current on the "U" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the U Phase	< 1.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	RUN > 10.00 ms ≠Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 14.97 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Phase V Current Low	P0B04	This diagnostic monitors the sensed current on the "V" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the V Phase	< 1.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	Run > 10.00 ms ≠Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 14.97 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Phase W Current Low	P0B07	This diagnostic monitors the sensed current on the "W" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the W Phase	< 1.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	RUN > 10.00 ms ≠Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 14.97 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmission Fluid Pump Motor Current High	P0C28	This diagnostic monitors the sensed current on all three phases of the electric motor. The absolute value of the highest current phase value is then compared against a threshold. If the value is above the failure threshold for sufficient time, the diagnostic will fail. This diagnostic implements the use of 2 different fail timers, one fast and one slow. The fast timer has a very short sample window so that the diagnostic will detect a sudden fault, the slower timer has a longer sample window to allow the diagnostic to detect an intermittent fault.	U, V, or W Phase Current Sensor	> 35.00 Amps	Wakeup Signal	On	0.0104 seconds out of a 0.0624 seconds window (x of y) OR 0.0104 seconds out of a 0.104 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid Battery System Discharge Time Too Long	P0C76	Monitors the high voltage bus after contactors open to ensure sufficient drop in voltage occurs	High voltage inverter rationalized voltage after discharge	> 200 volts	Enable calibration is True High voltage main contactor status IF discharge during charging is Not Allowed THEN High voltage charging contactor status	= 1 (1 is Enabled) = OPEN = 0 (0 is Not Allowed) = OPEN	3.5 seconds Diagnostic must run 2 times before failure is reported	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Supply Voltage Circuit 2 Low Voltage	P150D	This diagnostic detects low supply voltage for the circuit 2 path for motor control. If the supply voltage circuit 2 path is below the indicated threshold for the indicated time the DTC is set.	12 volt battery supply circuit 2	< 8.00 Volts	Enable Calibration is True Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1.00 (1 is Enabled) = False = True	2 seconds out of a 2.5 seconds window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Supply Voltage Circuit 1 Low Voltage	P150E	This diagnostic detects low supply voltage for the circuit 1 path for motor control. If the supply voltage circuit 1 path is below the indicated threshold for the indicated time the DTC is set.	12 volt battery supply circuit 1	< 8.00 Volts	Enable Calibration is True Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1.00 (1 is Enabled) = False = True	2 seconds out of a 2.5 seconds window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Regenerative Braking Control Switch A Circuit/Open	P152A	Checks to see if the regen on demand switch is active for an expected amount of time while the IMS is in an expected range. Fail case 1 and fail case 2 must be met to trip this DTC. Regenerative Braking Control Switch A Stuck ON	IMS Position	= TapDwnSwch2_Fail1 Rng	P152A enable calibration	= 1.00 (1 is enabled)	Malfunction criteria met for 600.00 seconds	Type C, No SVS
			Tap Switch Position	=Tap Down	Crank Diagnostic enable criteria met P152D Regen on Demand Switch available	= True NOT Fault active (FA) AND NOT Test Failed This Key On (TFTKO) = 1.00 (1 is available)		
			IMS Position	= TapDwnSwch2_Fail2 Rng	P152A enable calibration	= 1.00 (1 is enabled)	Malfunction criteria met for 600.00 seconds	
			Tap Switch Position	=Tap Up	Crank Diagnostic enable criteria met P152D Regen on Demand Switch available	= True NOT Fault active (FA) AND NOT Test Failed This Key On (TFTKO) = 1.00 (1 is available)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Regenerative Braking Control Switch Signal Message Counter Incorrect	P152C	This diagnostic monitors the signal from the body control module (BCM) to the THCP microprocessor for the regenerative braking switch. Potential failures include the BCM transceiver, the transmission line, the THCP transceiver and the processing in both microprocessors. If the BCM does not increment a counter with each message or fails to send the message in time the fault is set in the THCP.	Tap Up Tap Down Switch Alive Rolling Count Error	> 3 Errors	Enable Calibration is True Enable Calibration is True	= 1 (1 is Enabled) = 1 (1 is Enabled)	10 ms out of 10 ms window	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Regenerative Braking Control Switch A and B Circuit	P152D	This DTC reports when the regen on demand switch position is invalid after an expected period of time.	Regen On Demand Switch position	= Invalid (NOT reported as "TapDwn" or "TapOff")	P152D Enable calibration Regen on Demand Switch available Crank Diagnostic Enable criteria met	= 1.00 (1 is enabled) = 1.00 (1 is available) = True	Malfunction criteria met for 60.00 seconds	Type C, No SVS

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Alive Rolling Count/ Protection Value Fault - Engine Actual Torque Steady State	P15F0	This diagnostic monitors the signal from the engine control module (ECM) to the THCP microprocessor with the engine torque data. Potential failures include the ECM transceiver, the transmission line, the THCP transceiver and the processing in both microprocessors. If the ECM does not increment an Alive Rolling Count (ARC) with each message or fails to send the message in time or fails to calculate the checksum correctly the fault is set in the THCP.	Current ARC value OR Primary signal value	≠ Previous ARC value plus 1 (0-3) ≠ Protection Value	Propulsion System Active Run/Crank Active time AND Run/Crank Voltage OR Ignition Run/Crank Voltage	= TRUE ≥ 0.50 seconds ≥ 9.50 V ≥ 11.00 V	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Alive Rolling Count/ Protection Value Fault - Commanded Axle Torque Predicted	P15F1	This diagnostic monitors the signal from the engine control module (ECM) to the THCP microprocessor with commanded engine torque data. Potential failures include the ECM transceiver, the transmission line, the THCP transceiver and the processing in both microprocessors. If the ECM does not increment a counter with each message or fails to send the message in time or fails to calculate the checksum correctly the fault is set in the THCP.	Current ARC value OR Primary signal value	≠ Previous ARC value plus 1 (0-3) ≠ Protection Value	Run/Crank Active time AND (Run/Crank Voltage OR Ignition Run/Crank Voltage	>= 0.50 seconds >= 9.50 V >= 11.00 V	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Alive Rolling Count/ Protection Value Fault - Contactor Status Signal Circuit	P15FC	This diagnostic monitors the signal from the VICM/BSM (HPCM2) to the THCP microprocessor with contactor status information. Potential failures include the VICM/BSM transceiver, the transmission line, the THCP transceiver and the processing in both microprocessors. If the VICM/BSM does not increment a counter with each message or fails to send the message in time or fails to calculate the checksum correctly the fault is set in the THCP.	Current ARC value OR Primary signal value	≠ Previous ARC value plus 1 (0,1,2,3,0,1,2...) ≠ Protection Value	Ignition Status	= Run or Crank	0.45 seconds out of a 0.5 seconds window Executes every time PE GMLAN msg \$1D8 is received	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Engine Performance - No Torque Detected	P16E0	This diagnostic indicates that the engine is not producing torque	Reported Engine Torque - Sensed Engine Torque	> 50.00 Nm	All Secondary Parameters Listed below must be meet for 2.00 seconds Engine Actual Torque Fault DTC's not Fault Active Engine Start Stop State Engine Torque Command Immediate Engine Sensed Torque Low Fuel Condition Fuel Level Data Fault	= FALSE = U0100 = Engine Running ≥ 50.00 Nm > 0.00 Nm = FALSE = FALSE	3.5 seconds out of a 4 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 2	P16E9	This diagnostic checks that the SPI communication between the THCP and MCP2 is working correctly. Potential failures could be in the microprocessors SPI handling, the transmission line or the microprocessors ability to execute code. The DTC sets if the messages are missing, the counter is not updated, or the SPI handler detects an incorrect checksum.	CRC (Cyclic Redundant Checksum) error on receive Number of missing messages OR Alive Rolling Count (ARC) incremented from previous value (0-3)	=True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V >= 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	Type A, 1 Trips
			HWIO Received Errors AND Receiving Data in Progress	≠ 0 ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V >= 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	
			Number of Missing Received Messages	> 4 messages	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	0.175 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False > 11.00 V >= 9.50 V > 11.00 V		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 1	P16F0	This diagnostic checks that the SPI communication between the THCP and MCP1 is working correctly. Potential failures could be in the microprocessors SPI handling, the transmission line or the microprocessors ability to execute code. The DTC sets if the messages are missing, the counter is not updated, or the SPI handler detects an incorrect checksum in the time indicated.	CRC error on receive Number of missing messages OR Alive Rolling Count (ARC) incremented from previous value (0-3)	=True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	Type A, 1 Trips
			HWIO Received Errors AND Receiving Data in Progress	≠ 0 ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	
			Number of Missing Received Messages	> 4 messages	(Diagnostic System Code Clear Requested AND Diagnostic System Reset	= False = True	0.175 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False > 11.00 V >= 9.50 V > 11.00 V		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Redundant Memory Performance	P16F3	This diagnostic detects RAM faults in real time for those variables that are determined to be safety critical. The DTC sets when the called variable is called and compared to its redundant variable and does not match. There are fail cases for secure vehicle speed, transmission output sensor to wheel speed sensor conversion factor, and the engine torque value.	Rate Limited Secure Vehicle Speed (Re)	≠ Dual Stored Rate Limited Secure Vehicle Speed (Ve)	Run Crank Voltage Enable Calibration is True	>= 11.00 V = 1 (1 is Enabled)	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips
			TOS to Wheel Speed Conversion Factor	>= 1.10 (High & Neu) OR <= 0.10 (High & Neu)	Run Crank Voltage	>= 11.00 V	0.125 seconds out of a 0.2 seconds window	
			TOS to Wheel Speed Conversion Factor	>= 1.10 (4WD Low) OR <= 0.10 (4WD Low)				
			Engine Actual Torque Steady State WOM (Ve)	≠ Dual Stored Engine Actual Torque Steady State WOM (We)	Run Crank Voltage	>= 11.00 V	0.125 seconds out of a 0.2 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Transmissio n Range Control Performance	P16F4	Detects transmission range errors by comparing the Direction IMS switches with the Range IMS information from the THCP.	Valid Range IMS transmission position	≠ Valid Direction IMS transmission position	Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	Type A, 1 Trips
		DTC Fail case 1: Positive transmission ranges that do not match	Valid Range IMS transmission position	≠ Error corrected Direction IMS transmission position	Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
		DTC Fail case 2: Error corrected Direction IMS does not match						
		DTC Fail case 3: Range IMS is between valid transmission positions and Direction IMS is error corrected	Range IMS indicates a transitional state AND Direction IMS has an error corrected transmission position		Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
		DTC Fail case 4: Range IMS is invalid and Direction IMS is error corrected	Range IMS is invalid due to a fault or problem with THCP, AND the Direction IMS has an error corrected transmission position		Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
		DTC Fail case 5: Range IMS is between valid transmission positions and Direction IMS is invalid						
		DTC Fail case 6: Range IMS and Direction IMS are both invalid	Range IMS indicates a transitional state AND Direction IMS is invalid due to a fault or problem with the THCP		Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Range IMS is invalid due to a fault or problem with the THCP, AND the Direction IMS is invalid due to a fault or a problem with the THCP		Run/Crank Voltage	>= 9.50 Volts	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Commanded Range State	P16F6	This diagnostic verifies the calculation of the Transmission Range State. Potential failure modes could be the calculation of range state, range state transitions or the calculation of input torque does not match the range state. The DTC sets if there are mismatches in system equations, or the transmission range state being executed is invalid, or the transmission range state has performed an invalid transition or the input torque can not be rationalized with the range state.	The current Transmission Range State being used is detected to be an invalid value within the current Transmission range State group		Run/Crank Voltage R Ignition Voltage Enable range equation check is True Enable state machine rationality check is True Enable clutch control rationality check is True	>= 11.00 V >= 9.50 V = 1 R is Enabled = 1 R is Enabled = 1 R is Enabled	0.2 seconds out of a 0.2125 seconds window	Type A, 1 Trips
			The current Transmission Range State group being used by the system is an invalid value		Run/Crank Voltage R Ignition Voltage Enable range equation check is True Enable state machine rationality check is True Enable clutch control rationality check is True	>= 11.00 V >= 9.50 Volts = 1 R is Enabled = 1 R is Enabled = 1 R is Enabled	0.2 seconds out of a 0.2125 seconds window	
			The current Transmission Range State has changed, and the change in value is not one of the supported transitions from the previous Transmission Range State		Run/Crank Voltage R Ignition Voltage Enable range equation check is True Enable state machine rationality check is True Enable clutch control rationality check is True	>= 11.00 V >= 9.50 V = 1 R is Enabled = 1 R is Enabled = 1 R is Enabled	0.2 seconds out of a 0.2125 seconds window	
			The Range Equation can not be rationalized against the current Transmission Range State		Run/Crank Voltage R Ignition Voltage Enable range equation check is True	>= 11.00 V >= 9.50 V = 1 R is Enabled	0.2 seconds out of a 0.2125 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Enable state machine rationality check is True Enable clutch control rationality check is True	= 1 <input type="checkbox"/> is Enabled = 1 <input type="checkbox"/> is Enabled		
			The Torque Determination State can not be rationalized against the current Transmission Range State		Run/Crank Voltage <input type="checkbox"/> R Ignition Voltage Enable range equation check is True Enable state machine rationality check is True Enable clutch control rationality check is True	>= 11.00 V >= 9.50 V = 1 <input type="checkbox"/> is Enabled = 1 <input type="checkbox"/> is Enabled = 1 <input type="checkbox"/> is Enabled	0.2 seconds out of a 0.2125 seconds window	
			The Input Torque Optimization State can not be rationalized against the current Transmission Range State		Run/Crank Voltage <input type="checkbox"/> R Ignition Voltage Enable range equation check is True Enable state machine rationality check is True Enable clutch control rationality check is True	>= 11.00 V >= 9.50 V = 1 <input type="checkbox"/> is Enabled = 1 <input type="checkbox"/> is Enabled = 1 <input type="checkbox"/> is Enabled	0.2 seconds out of a 0.2125 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Pressure Control Solenoid Command Incorrect	P16F7	This diagnostic detects whether the solenoids driving the clutches are in the correct states. If a pressure solenoid is commanded off and the electronic feedback indicates it is in the "on" state the DTC sets in the indicated time. If the pressure solenoid is commanded on and the electronic feedback indicates the solenoid is "off" the DTC sets in the indicated time.	Clutch commanded off OR Clutch commanded on	= Clutch State On = Clutch State Off	Direct control of Solenoids AND Direct control of clutches AND Hydraulic default state AND (Run Crank Voltage OR Ignition Voltage)	= Inactive = Inactive = False >= 11.00 V >= 9.50 V	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Overspeed	P179A	This diagnostic monitors the output speed of the high voltage motor. The absolute value of the sensed speed of the motor is compared against a threshold. If the sensed speed is above the fail threshold for sufficient time, the diagnostic will fail.	ABS(Motor Speed)	> 6,500.00 rpm	Wakeup Signal	On	5.00 instances of failure within 10.00 seconds where each failure is counted when failure conditions have been met for 0.0832 seconds out of a 0.1664 seconds window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Clutch 1 Slip Adapt	P179C	Detects an excessive amount of clutch slip adapt from slip intervention	Max clutch 1 capacity reserve adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	10.00 cycles of max clutch capacity reserve adapt being observed	Type B, 2 Trips
			Slip intervention requested without holding the adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	65,535.00 cycles of slip intervention without holding the adapt being observed	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Clutch 2 Slip Adapt	P179D	Detects an excessive amount of clutch slip adapt from slip intervention	Max clutch 2 capacity reserve adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	10.00 cycles of max clutch capacity reserve adapt being observed	Type B, 2 Trips
			Slip intervention requested without holding the adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	65,535.00 cycles of slip intervention without holding the adapt being observed	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Circuit High Voltage	P1824	This DTC Monitors if the IMS P Circuit is Shorted to a high voltage	IMS P Voltage	> 2.49	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	= 1 (1 is Enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Circuit Low Voltage	P182A	This DTC Monitors if the IMS A Circuit is Shorted to a Low Voltage	IMS A Voltage	<= 0.66	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	=1 1 (1 is Enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Circuit Low Voltage	P182B	This DTC Monitors if the IMS B Circuit is Shorted to a Low Voltage	IMS B Voltage	<= 0.66	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Circuit High Voltage	P182C	This DTC Monitors if the IMS B Circuit is Shorted to a high voltage	IMS B Voltage	> 2.49	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	= 1 (1 is Enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Circuit Low Voltage	P182D	This DTC Monitors if the IMS P Circuit is Shorted to a Low Voltage	IMS P Voltage	<= 0.66	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch Invalid Range	P182E	This DTC Monitors if the IMS is Reporting an invalid range, meaning that the position of the IMS cannot be determined from the states of the individual IMS bits.	Converted Directional IMS	= Illegal	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 2.70 seconds in a 3.13 second window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Circuit High Voltage	P182F	This DTC Monitors if the IMS C Circuit is Shorted to a high voltage	IMS C Voltage	> 2.49	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Circuit High Voltage	P1838	This DTC Monitors if the IMS A Circuit is Shorted to a high voltage	IMS A Voltage	> 2.49	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	= 1 (1 is Enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Circuit Low Voltage	P1839	This DTC Monitors if the IMS C Circuit is Shorted to a Low Voltage	IMS C Voltage	<= 0.66	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch S Circuit Low Voltage	P1840	This DTC Monitors if the IMS S Circuit is Shorted to a Low Voltage	IMS S Voltage	<= 0.66	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch S Circuit High Voltage	P1841	This DTC Monitors if the IMS S Circuit is Shorted to a high voltage	IMS S Voltage	> 2.49	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	= 1 (1 is Enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Circuit Short	P18B5	This DTC reports if the monitored an IMS A Circuit voltage is between the max voltage for the valid low range and the min voltage for the valid high range.	IMS A Voltage	> 1.02 Volts and < 1.62 Volts	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Circuit Short	P18B6	This DTC reports if the monitored an IMS B Circuit voltage is between the max voltage for the valid low range and the min voltage for the valid high range.	IMS A Voltage	> 1.02 Volts and < 1.62 Volts	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Circuit Short	P18B7	This DTC reports if the monitored an IMS C Circuit voltage is between the max voltage for the valid low range and the min voltage for the valid high range.	IMS A Voltage	> 1.02 Volts and < 1.62 Volts	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Circuit Short	P18B8	This DTC reports an IMS P Circuit short if the monitored voltage is between the max voltage for the valid low range and the min voltage for the valid high range.	IMS P Voltage	> 1.02 Volts and < 1.62 Volts	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch S Circuit Short	P18B9	This DTC reports if the monitored an IMS S Circuit voltage is between the max voltage for the valid low range and the min voltage for the valid high range.	IMS S Voltage	> 1.02 Volts and < 1.62 Volts	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 1.75 seconds in a 2.00 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Stuck Off	P18BA	This DTC Monitors if the IMS A Circuit is Stuck Off, meaning that the circuit is in the valid low state when it is expected to be in the valid high state.	Converted Directional IMS Directional IMS A	Transitional 30 IMS A has not been observed valid Low	Ignition Voltage	>= 9.0 volts and <= 32.0 volts	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips
					Run/Crank Voltage	> 6.00 volts		
					Enable Calibration is True	= 1 (1 is enabled)		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Stuck Off	P18BC	This DTC Monitors if the IMS C Circuit is Stuck Off, meaning that the circuit is in the valid low state when it is expected to be in the valid high state.	Converted Directional IMS Directional IMS C	Transitional 27 IMS C has not been observed valid Low	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is enabled)	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Stuck On	P18BF	This DTC Monitors if the IMS A Circuit is Stuck On, meaning that the circuit is in the valid high state when it is expected to be in the valid low state.	Converted Directional IMS AND Directional IMS A	Transitional 17 IMS A has not been observed in the valid High state	Ignition Voltage Run/Crank Voltage Enable Calibration is True Converted Directional IMS AND Directional IMS A	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled) =Transitional 2 Has not been observed High in park for 1.50 seconds	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Stuck On	P18C0	This DTC Monitors if the IMS B Circuit is Stuck On, meaning that the circuit is in the valid high state when it is expected to be in the valid low state.	Converted Directional IMS AND Directional IMS B	Drive IMS B has not been observed High	Ignition Voltage Run/Crank Voltage Enable Calibration is True Converted Directional IMS AND Directional IMS B	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled) Drive Has not been observed High in Park for 1.50 seconds.	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Stuck On	P18C2	This DTC Monitors if the IMS P Circuit is Stuck On, meaning that the circuit is in the valid high state when it is expected to be in the valid low state.	Converted Directional IMS AND Directional IMS P	Transitional 24 IMS P as not been observed High	Ignition Voltage Run/Crank Voltage Enable Calibration is True	>= 9.0 volts and <= 32.0 volts > 6.00 volts = 1 (1 is Enabled)	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch S Stuck On	P18C3	This DTC Monitors if the IMS S Circuit is Stuck On, meaning that the circuit is in the valid high state when it is expected to be in the valid low state.	Converted Directional IMS AND Directional IMS S	LowManual IMS S has not been observed High	Ignition Voltage Run/Crank Voltage Converted Directional IMS Enable Calibration is True AND Directional IMS S	>= 9.0 volts and <= 32.0 volts > 6.00 volts =Park = 1 (1 is Enabled) has not been observed High in park for 1.50 seconds	Fail condition met for 2.70 seconds in a 3.13 second window	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Alive Rolling Count/ Protection Value Fault - Regenerativ e Braking Torque Request Circuit	P1B15	This diagnostic monitors the signal from the electronic brake control module (EBCM) to the THCP microprocessor with the regenerative braking torque request data. Potential failures include the EBCM transceiver, the transmission line, the THCP transceiver and the processing of the signal in both microprocessors. If the EBCM does not increment a counter with each message or fails to send the message in timetime or fails to calculate the checksum correctly the fault is set in the THCP. Detect the ARC (Alive Rolling Count) or Protection Value fault by checking the ARC counter and verifying the Protection Value of the Regenerative Braking Torque Request Circuit	Current ARC value OR Primary signal value	≠ Previous ARC value plus 1 (0-3) ≠ Protection Value	Run/Crank Active time AND Run/Crank Voltage OR Ignition Run/Crank Voltage	>= 0.50 seconds >= 9.50 Volts >= 11.00 V	0.1875 seconds out of a 0.25 seconds window Executes every time CE GMLAN msg \$235 is received	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Isolation Sensing Performance	P1E1B	This diagnostic verifies that the high voltage bus positive and negative leg sensors are neither inappropriately high nor low. It compares the sensed battery pack voltage against the high voltage positive and negative leg. If the absolute value of the difference between the sensed battery voltage and the high voltage positive and negative leg sensors is greater than the failure threshold for a sufficient time, the diagnostic will fail.	ABS(Total High Voltage Measured By the Battery Pack - High Voltage Measured from Positive to Ground - High Voltage Measured from Negative to Ground)	>= 70.00 V	No Active DTCs: Controller Initialization Contactors	P1AE8, P1AE9, P1B0B, P1B0C Complete Closed	0.175 seconds out of a 0.2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit Low	P1E1C	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail	Pos mid-pack voltage	< 20.00 Volts	Controller Initialization Run Crank Active Contactors	Complete True Closed	0.7 seconds out of a 1.5 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit High	P1E1D	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Positive to Ground Reading - Total High Voltage Reading from High Voltage Battery	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.5 seconds out of a 1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit Low	P1E1E	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Negative mid-pack voltage	< 20.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.7 seconds out of a 1 seconds window (x o y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit High	P1E1F	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Positive to Ground Reading - Total High Voltage Reading from High Voltage Battery	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.5 seconds out of a 1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage System Isolation Fault	P1E22	This diagnostic monitors the high voltage bus for possible shorts to chassis. The high voltage positive leg is compared to the high voltage negative leg via a ratio. If the ratio falls outside of a specific window for sufficient time, the diagnostic will fail.	Isolation Ratio (Neg mid-pack voltage / Pos mid-pack voltage)	> 4.53 OR < 0.21	No Active DTCs: Controller Initialization	P1AE8, P1AE9, P1AEC Complete	2.5 seconds out of a 5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Calculated Motor Position Performance	P1E29	This diagnostic monitors the auxiliary fluid pump for a loss of control. The calculated motor speed achieved is compared to a threshold. If the achieved speed is lower than the fail threshold for sufficient time, the diagnostic will fail.	Motor Speed Achieved	< -500.00 rpm	Wakeup Signal	ON	5.00 Retries Allowed after failure conditions met for 0.0006 seconds out of a 0.002 seconds window	Type A, 1 Trips
			Rotor Speed (Electrical Radians Per Second)	> 62.80 Rad/S	Wakeup Signal	ON	5.00 Retries Allowed after failure conditions met for 0.0006 seconds out of a 0.002 seconds window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase U Current Sensor Circuit Low	P1E2A	This diagnostic monitors for the "U" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	U Phase current sensor output at highside	< -50.00 Amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase U Current Sensor Circuit High	P1E2B	This diagnostic monitors for the "U" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is above the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output at highside	> 50.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase U Current Sensor Circuit Range/ Performance	P1E2C	This diagnostic monitors the offset that is learned by the phase "U" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	U phase current sensor offset learn value	> 2.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail conditions met 0.10 sec after enable conditions met	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase V Current Sensor Circuit Low	P1E2D	This diagnostic monitors for the "V" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output at highside	< -50.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase V Current Sensor Circuit High	P1E2E	This diagnostic monitors for the "V" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is above the failure threshold for sufficient time, the diagnostic will fail.	V phase Current Sensor output highside	> 50.00	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Phase V Current Sensor Circuit Range/ Performance	P1E2F	This diagnostic monitors the offset that is learned by the phase "V" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	U phase current sensor offset learn value	> 2.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail conditions met 0.10 sec after enable conditions met	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Inverter Temperature Sensor Circuit High	P1E34	This diagnostic monitor for inverter phase "U" temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	PIM Temperature Sensor A	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON ≥ 600.00 s ≥ABS(1.00)Nm	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Inverter Temperatur e Sensor Circuit Low	P1E35	This diagnostic monitor for inverter phase "U" temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	PIM Temperature Sensor A	> 170.00 degrees C	Sensor Exists WakeUp Signal	= 1.00 On	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Inverter Temperature Sensor Circuit Range/ Performance	P1E36	This diagnostic verifies that the high voltage electric motor inverter phase "U" temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated on key up after the vehicle has been off for a certain amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter A Temp- Cold Soak Average Temp)	> 10.00 degrees C	Vehicle off time Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Delay timer after controller initialization	≥ 9.17 hours > -20.00 °C P0AF0 and P0AEF > 5.13 second	0.5 seconds out of a 0.6 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Inverter Over Temperature	P1E37	This diagnostic monitors the inverter phase "U" temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	PIM Phase U Temperature	> 122.00 degrees C	PIM Phase U Temperature	TEMP NORMAL	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Power Supply Circuit/Open	P1E38	This diagnostic monitors the status of the IGBTs. The IGBT module will continuously monitor the supply circuit voltage. When the supply circuit drops below a threshold voltage the module then report out a status of being in a Bias fault. If the Bias fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C Power Supply	Failed (Status Fault Bit)	Inverter State	Initialization Complete	0.002 seconds out of a 0.024 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio ni Fluid Pump Motor Inverter Performance	P1E39	This diagnostic monitors the status of the IGBTs. The IGBT module will continually monitor the IGBTs for a short between the upper and lower phase. The module will then report out a status of being in a DeSat fault. If the DeSat fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C High or Low Side IGBT	DSatFltPending (Status Fault Bit)	Wakeup Signal	ON	0.01 seconds out of a 1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxilliary Transmissio n Fluid Pump Motor Torque Delivered Performance	P1E3A	This diagnostic is a plausibility check of the auxilliary motor speed and torque. Potential failure modes include the motor's ability to maintain a speed and the motor speed sensing circuits. When the difference between commanded auxilliary motor speed and actual auxilliary motor speed is greater than the indicated threshold and the torque is greater than the indicated threshold for longer than the timer threshold, the DTC is set.	(Motor speed using AB pulse from RDC - Motor speed from MCP) AND Motor torque commanded	> 200.00 > 6.50	Diagnostic is enabled AND Motor speed fault active AND Motor control	= 1.00 (1 = Run diagnostic) = False = Normal PWM control	(Motor RPM based) 80 failed revolutions out of 2,500 revolutions multiplied by 5.00 failed retry attempts	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Redundant Drive Motor A Speed Sensing Circuit	P1E4A	This diagnostic is a check of the motor A speed detection circuitry. When the difference between the THCP's motor A speed from the resolver circuit and the MCPA's motor speed from the emulated encoder circuit are greater than the indicated threshold for longer than the timer threshold, the DTC is set.	Difference between Resolver based Motor Speed and Emulated Encoder based Motor Speed	> 400.00 rpm	Enable Calibration is True AND (Run/Crank Voltage OR Ignition Run/Crank Voltage) AND SPI Receive Fault Active	= 1 (1 is Enabled) >= 9.50 Volts >= 11.00 V = FALSE	3.3375 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Redundant Drive Motor B Speed Sensing Circuit	P1E4B	This diagnostic is a check of the motor B speed detection circuitry. When the difference between the THCP's motor B speed from the resolver circuit and the MCPB's motor speed from the emulated encoder circuit are greater than the indicated threshold for longer than the timer threshold, the DTC is set.	Difference between Resolver based Motor Speed and Emulated Encoder based Motor Speed	> 400.00 rpm	Enable Calibration is True AND (Run/Crank Voltage OR Ignition Run/Crank Voltage) AND SPI Receive Fault Active	= 1 (1 is Enabled) >= 9.50 Volts >= 11.00 V = FALSE	3.3375 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Motor Inverter Temperature Sensor Circuit Erratic	P1F00	This diagnostic monitors the inverter phase "U" temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV System Discharge Switch Circuit Performance	P1F63	Voltage drop over a given time is monitored to ensure discharge circuit is performing as expected.	High voltage rationalized inverter voltage delta during discharge switch commanded on time	< 20 volts = 0.1 seconds	Enable calibration is True High voltage inverter rationalized voltage before discharge High voltage inverter rationalized voltage after discharge completes Motor Speeds High voltage main contactor status IF discharge during charging is Not Allowed THEN High voltage charging contactor status	= 1 (1 is Enabled) > 330 Volts < 200 Volts < 200 RPM = OPEN = 0 (0 is Not Allowed) = OPEN	1 Failure	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV System Discharge Switch Circuit Low	P1F64	Monitors the high voltage discharge switch for a circuit low fault	Active discharge circuit open status	HWIO determines if the active discharge resistor is failed open. =TRUE	Enable calibration is True	= 1 (1 is Enabled)	0.125 seconds out of a 0.15 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Hybrid/EV System Discharge Switch Circuit High	P1F65	Monitors the high voltage discharge switch for a circuit high fault	Active discharge circuit high status	HWIO determines if the active discharge resistor is failed high. =TRUE	Enable calibration is True	= 1 (1 is Enabled)	0.125 seconds out of a 0.15 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Vehicle Speed Output Shaft Speed Correlation	P215B	The DTC Monitors if the Difference between the Transmission Output Speed, Output Speed Calculated from the Wheel Speed Sensors, and Output Speed Calculated from the Motor Speeds. The DTC sets if 2 of the 3 vehicle speed sources do not match.	Transmission Output Speed and Output Speed Calculated from the Wheel Speed Sensors and Output Speed Calculated from the Motor Speeds difference	> 12.42 mph	Number of Secured Vehicle Speed Sources	CeVSPI_e_ThreeSrcSystem	0.15 seconds	Type A, 1 Trips
					Secured Vehicle Speed Use Transmission Output Speed	1		
					Secured Vehicle Speed Use Wheel Speed	1		
					Secured Vehicle Speed Use Motor Speed	1	0.15 seconds	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Shaft Speed (OSS) - Wheel Speed Correlation	P215C	The DTC calculates the difference between the output shaft speed measured from the transmission output speed sensor (TOSS) and the output shaft speed calculated from the average of the wheel speed sensors then reports if they differ from each other by a threshold for a calibrated period of time. There is a different set of enable conditions when the TOS calculated from wheel speeds and TOS calculated from motor speeds are above or below a threshold.	Difference between Transmission Output Speed and the Calculated Average of Output Speed from the Motors and Wheel Speed Sensors	≥ 50.00 RPM	Enable Calibration is True OBD Wheel Speed Sensors Driven Wheel Estimated Vehicle Speed Fault Propulsion System Active TOS calculated from Wheel Speeds TOS calculated from Motor Speeds	= 1 (1 is Enabled) True False True ≥ 200.00 RPM ≥ 200.00 RPM	0.23 seconds	Type B, 2 Trips
			Difference between Transmission Output Speed and the Calculated Average of Output Speed from the Motors and Wheel Speed Sensors	≥ 60.00 RPM	Enable Calibration is True OBD Wheel Speed Sensors Driven Wheel Estimated Vehicle Speed Fault Propulsion System Active TOS calculated from Wheel Speeds TOS calculated from Motor Speeds	= 1 (1 is Enabled) True False True ≤ 200.00 RPM ≤ 200.00 RPM	0.23 seconds	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit Low	P2534	Detects a run crank relay open circuit	Runk Crank Line Voltage	≤ 2.0 Volts	Enable Calibration is True CAN Communication ECM Run Crank Active CAN Data Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1 (1 is Enabled) Enabled Available and Active = False = True	Fail condition met for 2.50 seconds in a 5.00 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit High	P2535	Detects a run crank relay short to power	Runk Crank Line Voltage	> 6.0 V	Enable Calibration is True CAN Communication ECM Run Crank Active CAN Data Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1 (1 is True) Enabled Available and False = False = True	Fail condition met for 2.50 seconds in a 5.00 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Accessory Position Circuit Low	P2537	Detects an accessory position circuit open	Accessory	False	P2537 Propulsion System Propulsion System Active Time	Not Test Failed This Key On and Not Test Passed This Key On Active > 0.50 seconds	0.10 seconds	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD2 Actuator Supply Circuit Voltage Low	P2670	This diagnostic reports when a high side driver 2 circuit low fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit low is present or not. HSD 2 Short to Ground Fault Status	=TRUE	Enable Calibration is True HSD 2	= 1 (1 is Enabled) = On	0.13125 seconds out of a 0.15625 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD2 Actuator Supply Circuit Voltage High	P2671	This diagnostic reports when a high side driver 2 circuit high fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit high is present or not. HSD 2 Short to Power Fault Status	=TRUE	Enable Calibration is True	= 1 (1 is Enabled)	0.00625 seconds (1 Loop)	Type B, 2 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit Open	P2718	This DTC sets when the PCSD control circuit has been detected to be open circuit	HWIO circuitry detects if an electrical circuit open is present or not. PCS D Open Circuit Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit Low Voltage	P2720	This DTC sets when the PCSD control circuit has been detected to be open circuit or shorted to power	HWIO circuitry detects if an electrical circuit low is present or not. PCS D Circuit Low Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.03 seconds in a 0.04 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit High Voltage	P2721	This DTC sets when PCSD has been detected to be shorted to battery	HWIO circuitry detects if an electrical circuit high is present or not. PCS D Circuit High Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit Open	P2727	This DTC sets when the PCSE control circuit has been detected to be open circuit	HWIO circuitry detects if an electrical circuit open is present or not. PCS E Open Circuit Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit Low Voltage	P2729	This DTC sets when the PCSE control circuit has been detected to be open circuit or shorted to ground	HWIO circuitry detects if an electrical circuit low is present or not. PCS E Circuit Low Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit High Voltage	P2730	This DTC sets when PCS5 has been detected to be shorted to power	HWIO circuitry detects if an electrical circuit high is present or not. PCS E Circuit High Fault Status	=TRUE	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	>= 9.00 V and <= 16.00 V > = 11 Volts && <= 16 Volts >= 0 RPM && <= 7500 RPM for >= 5 seconds <= 200 mph for >= 5 seconds =1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Performance	P2797	This diagnostic monitors the aux pump performance based on aux pump filtered desired speed and actual speed values.	Difference between desired and actual aux pump speed AND Aux Pump Motor Estimated Temperature	See supporting tables for P2797 failure threshold P2797 Pump Performance Speed Delta Threshold < 165C	Aux Pump Speed Command Run/Crank Voltage	>= 5.00 RPM for 1.00 s > 6.00 volts	Fail Condition met for 3.00 seconds in a 3.75 second window	Type A, 1 Trips
			Difference between desired and actual aux pump speed AND Aux Pump Motor Estimated Temperature	See supporting tables for P2797 failure threshold P2797 Pump Performance Speed Delta Threshold Case 2 > 165C	Aux Pump Speed Command Run/Crank Voltage	>= 5.00 RPM for 1.00 s > 6.00 volts	Fail Condition met for 2.00 seconds in a 2.50 second window	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
DID 76 Calibration Incorrect	P27A7	Detects if the solenoid calibration is incorrect	Solenoid not programmed	=1			Instantly	Type A, 1 Trips
			Solenoid programming falut(stored solenoid type and class configuration calibrations do not match)	=1			Instantly	
			Checksum Mismatch	=1			Instantly	
			Access Decreasing Fault	=1			Instantly	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module Drive Motor Control Performance	P3260	This diagnostic checks that the engine speed and motor torque go below thresholds when the driver shifts to neutral. When the driver shifts to neutral and the vehicle speed is below the shown threshold the vehicle should turn off the engine and reduce the motor torque to near zero Nm. When shifted to neutral, if the engine speed does not fall below the threshold or motor torque is not removed in the shown time then the DTC is set. A second fail case is checked after the above conditions are correct the engine speed and motor torque values are continuously monitored to be sure they stay in range, otherwise the DTC is set.	((Motor A torque AND Ignore Motor A torque) OR (Motor B torque AND Ignore Motor B torque) OR (Engine speed AND Ignore Engine speed))	!< 4.00 Nm = 0.00 (0 = use Motor A torque) !< 1.00 Nm != 1.00 (1 = Do not use Motor B torque) !< 200.00 RPM = 1.00 (0 = use Engine speed)	Vehicle speed AND No motor neutral diagnostic enabled AND Gear position	< 5.00 kph = 1 (1 = Enabled) = CeHSER_e_N1_RngEqn (Neutral)	Timer from shift to neutral to all conditions being met > 33.00 seconds Debounce timer > 125.00 msec	Type A, 1 Trips
			((Motor A torque AND Ignore Motor A torque) OR (Motor B torque AND Ignore Motor B torque) OR (Engine speed AND Ignore Engine speed))	!< 4.00 Nm = 0.00 (0 = use Motor A torque) < 1.00 Nm != 1.00 (1 = do not use Motor B torque) !< 200.00 RPM = 1.00 (0 = use Engine speed)	Case 1 test passed AND Gear position	= CeHSER_e_N1_RngEqn (Neutral)	Debounce timer > 125.00 msec	

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus A Off	U0073	This diagnostic detects that BUS A is off or is non-operational. If the host controller can not transmit on bus A in the indicated time the DTC is set.	Bus off failures exceeds before the sample time is reached	4 counts (equivalent to 0.05 seconds)	General Enable Criteria: U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Ignition voltage Power Mode Off Cycle Enable Criteria: Enable Calibration is True Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active >= 9.50 = run = 1 (1 is Enabled) = Active > 9.50 > 3.00 seconds > 0.1125 seconds	0.05 seconds out of 0.56 seconds	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus B Off	U0074	This diagnostic detects that BUS B is off or is non-operational. If the host controller can not transmit on BUS B in the indicated time the DTC is set.	Bus off failures exceeds before the sample time is reached	4 counts (equivalent to 0.05 seconds)	General Enable Criteria: U0074 Normal CAN transmission on Bus B Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Ignition voltage Power Mode Off Cycle Enable Criteria: Enable Calibration is True Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active >= 9.50 = run = 1 (1 is Enabled) = Active > 9.50 > 3.00 seconds > 0.1125 seconds	0.05 seconds out of 0.56 seconds	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus E Off	U0077	This diagnostic detects that BUS E is off or is non-operational. If the host controller can not transmit on BUS E in the indicated time the DTC is set.	Bus off failures exceeds before the sample time is reached	4 counts (equivalent to 0.05 seconds)	General Enable Criteria: U0077 Normal CAN transmission on Bus E Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Ignition voltage Power Mode Off Cycle Enable Criteria: Enable Calibration is True Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active >= 9.50 = run = 1 (1 is Enabled) = Active > 9.50 > 3.00 seconds > 0.1125 seconds	0.05 seconds out of 0.56 seconds	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with ECM/PCM A	U0100	This diagnostic detects that the engine control module (ECM) has stopped sending messages on Bus A. If ECM message traffic is not received on Bus A by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0AA</p> <p>Message \$0C9</p> <p>Message \$1A3</p> <p>Message \$1AA</p> <p>Message \$1C5</p> <p>Message \$287</p> <p>Message \$3DC</p> <p>Message \$3E9</p> <p>Message \$3FB</p> <p>Message \$4A3</p> <p>Message \$4C1</p> <p>Message \$4C7</p> <p>Message \$4F1</p> <p>Message \$589</p>	<p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0100</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					ECM	Cycle is present on the bus		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Brake System Control Module	U0129	This diagnostic detects that the brake system control module has stopped sending messages. If brake system control module message traffic is not received by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C1</p> <p>Message \$0C5</p> <p>Message \$0D1</p> <p>Message \$0F1</p> <p>Message \$1E9</p> <p>Message \$4E9</p>	<p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0129</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Brake System Control Module	is present on the bus		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Hybrid Powertrain Control Module B	U179A	This diagnostic detects that Hybrid Powertrain Control Module B has stopped sending messages. If Hybrid Powertrain Control Module B message traffic is not received by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$3DD</p> <p>Message \$4CB</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U179A</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					HPCM_B	is present on the bus		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with ECM/PCM A on Bus B	U1818	This diagnostic detects that the engine control module (ECM) has stopped sending messages on Bus B. If ECM message traffic is not received on Bus B by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$091</p> <p>Message \$0A5</p> <p>Message \$184</p> <p>Message \$187</p> <p>Message \$18C</p> <p>Message \$18D</p> <p>Message \$1C2</p> <p>Message \$283</p> <p>Message \$383</p> <p>Message \$489</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U1818</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					ECM	Cycle is present on the bus		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Hybrid Powertrain Control Module B on Bus B	U182D	This diagnostic detects that the Hybrid Powertrain Control Module B has stopped sending messages on Bus B. If Hybrid Powertrain Control Module B message traffic is not received on Bus B by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$18D</p> <p>Message \$1D8</p> <p>Message \$3C5</p> <p>Message \$3D5</p> <p>Message \$3D7</p> <p>Message \$3DA</p> <p>Message \$3DB</p> <p>Message \$3DF</p>	<p>≥ 10.0 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U182D</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Hybrid Powertrain Control Module B (VICM)	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Brake System Control Module on Bus E	U1833	This diagnostic detects that the Brake System Control Module has stopped sending messages on Bus E. If Brake System Control Module message traffic is not received on Bus E by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C1 Rdnt</p> <p>Message \$0C5 Rdnt</p> <p>Message \$235</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 0.50 seconds</p>	<p>General Enable Criteria:</p> <p>U0077</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U1833</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Brake System Control Module	is present on the bus		

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 5 Slip	P079E	Monitors clutch 5 slip by comparing the slip speed across the clutch to a slip threshold or comparing the calculated slip energy to an energy threshold.	Clutch 5 Slip Speed	>= 50.00 RPM	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 350.00 kPa > 50.00 Nm =Locked = not faulted =0 =0	Fail Condition met for 0.80 seconds out of 0.80 seconds Retry Count: 1.00	Type A, 1 Trips
			Clutch 5 Slip Speed Transient	>= 50.00 RPM	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 350.00 kPa > 50.00 Nm =Locked = not faulted =0 =0	Fail Condition met for 0.80 seconds out of 1.00 seconds Retry Count: 1.00	
			Clutch 5 Energy	>= 6,848.00 J	Line Pressure Estimate Clutch Torque Estimate Clutch Status Motor Speeds Wheel Slip Shutdown Command	>= 350.00 kPa > 50.00 Nm =Locked = not faulted =0 =0	Instantly once Clutch 1 Energy >= 6,848.00 J Retry Count: 1.00	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 4 Stuck On	P07A9	Detects if clutch 4 is stuck on by comparing actual clutch 4 slip speed to a desired slip profile or by detecting that slip across the clutch is not above a threshold when slip is expected.	C4 Offgoing Slip Expected	=1	Motor Speed Clutch 4 State	= not faulted =off going	Fail condition met for 1.00 seconds out of 1.25 seconds. Retry Count: 2.00	Type A, 1 Trips
			C4 Slip Speed	=< Clutch4FailSlipSpeed (See supporting table)	Clutch Status Shutdown command	=Released =0	Fail condition met for 1.00 seconds out of 1.25 seconds. Retry Count: 2.00	
			C2 Profiled Slip Speed	>= Clutch4ProfiledSlipSpeedThd (See supporting table)	Motor Speed	= not faulted	Retry Count: 2.00	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Clutch 5 Stuck On	P07AB	Detects if clutch 5 is stuck on by comparing actual clutch 5 slip speed to a desired slip profile or by detecting that slip across the clutch is not above a threshold when slip is expected.	C5 Offgoing Slip Expected	=1	Motor Speed Clutch 5 State	= not faulted =off going	Fail condition met for 2.00 seconds out of 2.68 seconds. Retry Count: 1.00	Type A, 1 Trips
			C5 Slip Speed	=< Clutch5FailSlipSpeed (See supporting table)	Clutch Status Shutdown command	=Released =0	Fail condition met for 2.00 seconds out of 2.68 seconds.	
			C5 Profiled Slip Speed	>= Clutch5ProfiledSlipSpeedThd (See supporting table)	Motor Speed	= not faulted	Retry Count: 1.00	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Transmissio n Direction Range Switch	P16F2	This Diagnostic detects transmission direction errors by reading the states of the Direction IMS switches as well as determining a transmission direction and comparing it to the transmission direction from the primary controls path DTC Fail case 1: No direction match with no IMS failures DTC Fail case 2: Multiple transmission directions with no IMS failures DTC Fail case 3: No direction match with one IMS failure DTC Fail case 4: Multiple transmission directions with one IMS failure DTC Fail case 5: Unable to determine transmission direction	Direction IMS transmission direction from Hardware (P,R,N,D)	≠ transmission direction determined by primary path	Run/Crank Voltage IMS Failure	>= 9.50 Volts = FALSE	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	Type A, 1 Trips
			Direction IMS represents more than one valid transmission direction	= TRUE	Run/Crank Voltage IMS Failure	>= 9.50 Volts = FALSE	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
			Calculated transmission direction after one IMS failure	≠ transmission direction determined by primary path	Run/Crank Voltage One IMS Failure	>= 9.50 Volts = TRUE	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
			Calculated transmission direction after one IMS failure represents more than one valid transmission direction	= TRUE	Run/Crank Voltage One IMS Failure	>= 9.50 Volts = TRUE	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	
			Multiple Direction IMS failures and cannot calculate a transmission direction.	= TRUE	Run/Crank Voltage Multiple IMS Failures	>= 9.50 Volts = TRUE	150.00 ms out of a 200.00 ms window Executes in a 25ms loop	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Clutch 3 Slip Adapt	P179E	Detects an excessive amount of clutch slip adapt from slip intervention	Max clutch 3 capacity reserve adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of max clutch capacity reserve adapt being observed	Type B, 2 Trips
			Slip intervention requested without holding the adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of slip intervention without holding the adapt being observed	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Clutch 4 Slip Adapt	P179F	When a small amount of clutch slip is observed the system can intervene to prevent the slip. This diagnostic detects either an excessive amount of clutch slip adapt from slip intervention once the maximum clutch capacity reserve adapt has been reached or if there are multiple slip intervention requests without the adapt being changed.	Max clutch 2 capacity reserve adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of max clutch capacity reserve adapt being observed	Type B, 2 Trips
			Slip intervention requested without holding the adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of slip intervention without holding the adapt being observed	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Clutch 5 Slip Adapt	P17A0	When a small amount of clutch slip is observed the system can intervene to prevent the slip. This diagnostic detects either an excessive amount of clutch slip adapt from slip intervention once the maximum clutch capacity reserve adapt has been reached or if there are multiple slip intervention requests without the adapt being changed.	Max clutch 2 capacity reserve adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of max clutch capacity reserve adapt being observed	Type B, 2 Trips
			Slip intervention requested without holding the adapt	= 1	Enable Calibration is True Hydraulic System	= 1 (1 is Enabled) = Enabled	100.00 cycles of slip intervention without holding the adapt being observed	

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 R1 Circuit Low Voltage	P181C	The DTC monitors if the IMS R1 circuit is shorted to a low voltage	Converted Directional IMS AND Directional IMS R1	Transitional 17 R1 circuit has not been observed high	Ignition Voltage Converted Directional IMS AND Directional IMS R1	> 9.00 volts Transitional 2 R1 Circuit NOT high for 5.00 seconds	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 R1 Circuit High Voltage	P181D	The DTC monitors if the IMS R1 circuit is shorted to a high voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS R1	Transitional 30 R1 circuit has not been observed low	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 R2 Circuit Low Voltage	P181E	The DTC monitors if the IMS R2 circuit is shorted to a low voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS R2	Drive R2 circuit has not been observed high	Ignition Voltage Converted Directional IM AND Directional IMS R2	> 9.00 volts Park R2 Circuit NOT high for 5.00 seconds	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 R2 Circuit High Voltage	P181F	The DTC monitors if the IMS R2 circuit is shorted to a high voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS R2	Transitional 14 OR Transitional 29 R2 circuit has not been observed low	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 D1 Circuit Low Voltage	P183A	The DTC monitors if the IMS D1 circuit is shorted to a low voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS D1	Transitional 8 OR Transitional 20 D1 circuit has not been observed high	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 D1 Circuit High Voltage	P183B	The DTC monitors if the IMS D1 circuit is shorted to a high voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS D1	Transitional 27 D1 circuit has not been observed low	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 D2 Circuit Low Voltage	P183C	The DTC monitors if the IMS D2 circuit is shorted to a low voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS D2	Transitional 24 D2 circuit has not been observed high	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 D2 Circuit High Voltage	P183D	The DTC monitors if the IMS D2 circuit is shorted to a high voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS D2	Transitional 11 AND Transitional 23 D2 circuit has not been observed low	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 Invalid Range	P183E	The DTC monitors if the IMS is in an invalid range	Converted Directional IMS	Illegal (All Circuits Open)	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 1-2 Correlation	P183F	The DTC monitors if the IMS Direction and Range Correlation is Invalid	Converted Directional IMS	Correlation Fault Neutral (With No IMS Faults the Direction IMS and Range IMS Indicate Different Detent Postions)	Ignition Voltage	> 9.00 volts	1.25 seconds out of a 1.7 seconds window	Type A, 1 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 S Circuit Low Voltage	P184A	The DTC monitors if the IMS S circuit is shorted to a low voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS S	Transitional 9 S circuit has not been observed high	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch 2 S Circuit High Voltage	P184B	The DTC monitors if the IMS S circuit is shorted to a high voltage when the shift lever has been moved.	Converted Directional IMS AND Directional IMS S AND Directional IMS R1	Transitional 26 S circuit has not been observed low R1 circuit has been observed low	Ignition Voltage	> 9.00 volts	2.7 seconds out of a 3.125 seconds window	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Sense Circuit Low Voltage	P1E20	This diagnostic monitors the high voltage bus total voltage which is out of range low. The total sensed voltage is compared against a threshold. If the total sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage	< 30.00 volts	Controller Initialization Run/CrankActive Contactors	Complete True Closed	1.5 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery Voltage Sense Circuit High Voltage	P1E21	This diagnostic monitors the high voltage bus total voltage which is out of range high. The total sensed voltage is compared against a threshold. If the total sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage	> 575.00 volts	Controller Initialization Run/CrankActive	Complete True	1.5 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery System Voltage High	P1E27	This diagnostic monitors the total high voltage system voltage which is too high for the hardware. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage OR High Voltage Hardware Flag	> 445.00 Volts = True	Controller Initialization	Complete	0.004 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Auxiliary Transmissio n Fluid Pump Control Module Hybrid Battery System Voltage	P1E28	This diagnostic monitors the correlation of sensed total high voltage with sum of the mid-pack voltages and the high voltage reported by the battery. If these values are greater than a threshold the diagnostic will set.	ABS(High Voltage Sensor - High Voltage Battery Voltage) OR ABS(High Voltage Battery Voltage - sum of mid-pack voltages)	≥ 40.00 volts ≥ 50.00 volts	No Active DTCs: Controller Initialization Contactors	P1AE8, P1AE9 Complete Closed	0.175 seconds out of a 0.2 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 HPC1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With TCM	U0101	This diagnostic detects that the transmission control module (TCM) has stopped sending messages. If TCM message traffic is not received by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0BD</p> <p>Message \$0C7</p> <p>Message \$1A7</p> <p>Message \$1A8</p> <p>Message \$1A9</p> <p>Message \$1F5</p> <p>Message \$385</p> <p>Message \$4C9</p>	<p>≥ 10.00 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p><u>General Enable Criteria:</u> U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p><u>Ignition Voltage Criteria:</u> Ignition voltage</p> <p>Power Mode</p> <p><u>Off Cycle Enable Criteria:</u> KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0101</p> <p>TCM</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p> <p>> 3.00 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p> <p>is present on the bus</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch1FailSlipSpeed

Description:						
y/x	-50	-30	-24	-17	4	40
1	20	20	20	20	30	30

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch1ProfiledSlipSpdThd

Description:						
y/x	-50	-30	-24	-17	4	40
1	250	250	250	250	175	120

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch2FailSlipSpeed

Description:						
y/x	-50	-30	-24	-17	4	40
1	20	20	20	20	30	30

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch2ProfiledSlipSpeedThd

Description:						
y/x	-50	-30	-24	-17	4	40
1	350	350	350	350	350	250

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch3FailSlipSpeed

Description:						
y/x	-50	-30	-24	-17	4	40
1	20	20	20	20	20	20

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch3ProfiledSlipSpeedThd

Description:						
y/x	-50	-30	-24	-17	4	40
1	200	200	200	200	200	200

Initial Supporting table - Clutch4FailSlipSpeed

Description:

y/x	1	2	3	4	5	6
1	30	30	30	30	30	30

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch4ProfiledSlipSpeedThd

Description:						
y/x	1	2	3	4	5	6
1	350	350	350	350	350	350

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch5FailSlipSpeed

Description:						
y/x	1	2	3	4	5	6
1	30	30	30	30	30	30

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Clutch5ProfiledSlipSpeedThd

Description:

y/x	1	2	3	4	5	6
1	550	550	550	550	550	550

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table - Cold Soak Rationality

Description: Transmission Temp Difference from Cold Soak Average Temperature Based on Transmission Fluid Temperature

y/x	1	2	3	4	5
1	-40	-20	0	20	60
2	15	10	10	10	10

Initial Supporting table - P2797 Pump Performance Speed Delta Threshold

Description:

y/x	-40	-30	-15	50	90	125
1	67	100	500	500	500	500

Initial Supporting table - P2797 Pump Performance Speed Delta Threshold Case 2

Description:

y/x	-40	-30	-15	50	90	125
1	1,000	900	800	700	600	500

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table -TapDwnSwch2_Fail1Rng

Description:

TapDwnSwch2_Fail1Rng - Part 1

y/x	CeTRGR_e_Drive1	CeTRGR_e_Drive2	CeTRGR_e_Drive3	CeTRGR_e_Drive4
1	0	0	0	1

TapDwnSwch2_Fail1Rng - Part 2

y/x	CeTRGR_e_Drive5	CeTRGR_e_Drive6	CeTRGR_e_Drive7	CeTRGR_e_Drive8
1	0	1	0	0

TapDwnSwch2_Fail1Rng - Part 3

y/x	CeTRGR_e_Neutral	CeTRGR_e_Reverse	CeTRGR_e_Park	
1	0	0	0	

18 OBDG01 HPC1 Supporting Tables

Initial Supporting table -TapDwnSwch2_Fail2Rng

Description:

TapDwnSwch2_Fail2Rng - Part 1

y/x	CeTRGR_e_Drive1	CeTRGR_e_Drive2	CeTRGR_e_Drive3	CeTRGR_e_Drive4
1	0	0	0	1

TapDwnSwch2_Fail2Rng - Part 2

y/x	CeTRGR_e_Drive5	CeTRGR_e_Drive6	CeTRGR_e_Drive7	CeTRGR_e_Drive8
1	0	1	0	0

TapDwnSwch2_Fail2Rng - Part 3

y/x	CeTRGR_e_Neutral	CeTRGR_e_Reverse	CeTRGR_e_Park	
1	0	0	0	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage Performance	P0561	This diagnostic detects a difference in voltage between the 12V input and the Ignition Run/Crank Voltage. The fault sets when the host controller detects the difference is above the indicated threshold for the indicated time.	Difference between 12V Battery Voltage Input and Ignition Run/Crank Voltage	> 3.00 Volts	Enable Calibration is True Diagnostic System Code Clear Requested Diagnostic System Reset Complete Battery input is present Ignition Run/Crank Voltage 12V Starter Engaged	= 1.00 (1 is Enabled) = False = True = 1.00 (1 is Available) > 6.0 Volts = False	4 seconds out of a 5 seconds window	Type C, No SVS

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage Low	P0562	This diagnostic detects low voltage in the vehicle's 12 volt system. The fault sets when the THCP detects supply voltage below the indicated threshold for the indicated time.	Ignition Voltage	≤ 10.00 Volts	Enable Calibration is True 12V Starter Engaged Ignition Run/Crank Voltage Engine Speed	= 1.00 (1 is Enabled) = False > 6.0 Volts ≥ 0.00 RPM	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
System Voltage High	P0563	This diagnostic detects high voltage in the vehicle's 12 volt system. The fault sets when the host controller detects supply voltage above the indicated threshold for the indicated time.	Ignition Voltage	≥ 16.00 Volts	Enable Calibration is True Ignition Run/Crank Voltage	= 1.00 (1 is Enabled) > 6.0 Volts	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Read Only Memory (ROM)	P0601	This Diagnostic tests the checksum on ROM (flash) memory. It will fail if any check sum in the boot is incorrect, if any check sum in the calibration is incorrect, or if any check sum in the software is incorrect.	Calculated Checksum of the Boot ROM	≠ Expected Checksum	Ignition Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= Run or Crank ≠ True = False = True	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 5 failures.	Type A, 1 Trips
			Second Processor State of Health ROM fault latched	= TRUE	Ignition Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= Run or Crank ≠ True = False = True	Runs continuously in the background	
			Calculated Checksum of Torque Security Related Calibrations	≠ Expected Checksum	Controller Status (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) = Disable Calibration is False = Enable Calibration is True Ignition Status	= On = False = True = 0 (0 is Enabled) = 1 (1 is Enabled)	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 5 failures.	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			ECC Fault detected in Flash memory	= TRUE	Controller Status Power Up Reset AND HWIO BINVDM ECC State AND HWIO ROM Fault Enable Calibration is true	= On = False = False = True = 1 (1 is Enabled)	Greater than 5 failures at controller initialization Runs once at initialization	
			ROM fault Active AND 2nd SOH ROM Fault Latched AND Main SOH ROM Fault Latched	≠ True ≠ True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs in the Background	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Not Programmed	P0602	This Diagnostic checks that the TCM micro-controller has a valid calibration flashed into it. The controller manufacturer flashes a calibration with a particular calibration set to 1. At the vehicle plant the controller is reflashed with a valid calibration that also changes the particular calibration set to 0. The DTC sets when the diagnostic checks that particular calibration and it has a nonzero value.	No Start Calibration	= 0 (1 is for No Start Condition)	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at controller initialization and every 1 second there after	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Reset	P0603	This Diagnostic tests the NonVolatile Memory (NVM) in the TCM micro-controller for changes since the last write at power down. The bytes of various NVM sections are summed and compared to checksums for each section that were stored at the last powerdown. The DTC sets when the checksum comparisons do not match.	Static NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	Type A, 1 Trips
			Preserved NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Power Up Reset BINVDM NVM Checksum at power-up	= False ≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	Runs once at controller initialization 3 out of 5 controller initializations for Failure	
			Dynamic NVM checksum at power-up AND Shutdown Finished	≠ Checksum at power-down = TRUE	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Static NVM Error Dynamic NVM Error BINVDM ECC Error	= False = False = False	Enable Calibration is True	= 1 (1 is Enabled)	Runs once at controller initialization	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Random Access Memory (RAM) Failure	P0604	This Diagnostic tests the RAM in the TCM micro-controller. The diagnostic checks that RAM has not changed unexpectedly. Pattern checks are done at initialization where different patterns are written and then read back. The DTC sets if the patterns do not match. Continuous checks are done while the controller is executing code that store the same variables in multiple locations. When those variables are read, a check is done to be sure both locations still match. A DTC sets if the locations do not match for the indicated time.	Secure redundant "Y" variable	≠ Primary "V" variable for greater than 175 ms	Current Time Execution - Time of Last DualStore Error	> 25 ms	Executes in Background loop	Type A, 1 Trips
			HWIO detects an illegal write to Write Protected RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop 1 count to fail	
			2nd Processor State of Health RAM Fault Latched	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop every 1000ms	
			Checksum of PreservedNVM_Region for Main Processor State of Health and 2nd Processor State Of Health	≠ Expected checksum value	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization	
			HWIO detects fault in System RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 3 count to fail	
			HWIO detects fault in Cache RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 3 count to fail	
			HWIO detects fault in eTPU RAM (Timer Processing Unit)	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 3 count to fail	
			Main SOH RAM Fault Latched AND SPI Fault Latched	= 0 = False	(Diagnostic System Code Clear Requested AND Diagnostic System Reset	= False = True	Executes in Background loop every 1000ms	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			AND System RAM Fault Count AND Cache RAM Fault Count AND eTPU RAM Fault Count	= 0 = 0 = 0	Complete) Time Since Last Duel Store Error	> 1,000 ms		

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Performance	P0606	This diagnostic tests all internal processor subsystems for faults which suggest that the integrity of the processor cannot be trusted. Fail Case 1,2,3:	New Seed Update Time Indicates that the Processor did not receive a key value from the secondary processor during the expected time frame "MainDtctdSdKeyTimeout"	> 1.00 sec	Number Of Mains Processors to monitor AND SPI Faults AND Seed/Key Init delay timer AND Run/Crank Voltage OR 12V Battery Voltage	> 0 = FALSE (No active P0606) >= 1.00 s >= 9.50 V > 11.00 V	Executes in a 12.5ms loop Detects in 1 second	Type A, 1 Trips
		The microprocessors in the TCM monitor that each of the others is executing code correctly and in a timely manner. These fail cases rely on a seed and key interaction where one micro-controller sends a seed and a second controller runs a predefined set of calculations and responds with a key. The first controller sends a seed and checks that the received key matches	Seed sequence Indicates that the Processor received key values in the incorrect order from the secondary processor "MainDtctdSdRxWrongOrder"	≠ expected order	Number Of Mains Processors to monitor AND SPI Faults AND Run/Crank Voltage OR 12V Battery Voltage	> 0 = FALSE (No active P0606) >= 9.50 V > 11 V	150.00 ms out of a 200.00 ms window Executes in a 12.5ms loop	
			Program Sequence Watch Seed time Since Seed Change Indicates that the Processor detected that a program Seed was not sending for the Program Sequence Watch "MainSequenceFlt"	> 200.00 ms	Program Sequence Watch Enabled (KaPISD_b_ProgSeqWatchEnbl[x])	= TRUE	Executes in a 50ms loop after controller initialization	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>its lookup table value for that seed and that is was received in time. The second controller checks that the correct seed value has been received and that is in time. The DTC sets when there is a mismatch of seed or key values or the expected key or seed value is out of order or if the key or seed value has not been received in the indicated time.</p> <p>Fail Case 4, 5, 6:</p> <p>These diagnostics are built into the hardware of the HMCP microprocessor by the chip manufacturer. These diagnostics check the ALU and Configuration registers to ensure there have been no changes. The DTC sets if these registers have changed since the software flash at the vehicle plant. An additional built in diagnostic checks whether the top of the stack memory has changed from initialization at power up. The DTC sets if this section of memory has been detected to</p>	<p>HWIO detects Fault in ALU Test</p> <p>Indicates that the Processor detected an ALU fault in the processor "MainALU_Flt"</p>	= 2 faults in a key cycle	<p>Enabled Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p> <p>= False</p> <p>= False</p>	Runs continuously in 12.5ms loop	
			<p>HWIO detects Fault in Configuration Registry Test</p> <p>Indicates that the Processor detected a Configuration Register fault in the processor "MainCfgRegFlt"</p>	= 2 faults in a key cycle	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p> <p>= False</p> <p>= False</p>	Runs continuously in 12.5ms loop	
			<p>HWIO detects Fault in the Stack Limit Test</p> <p>Indicates that the CPU Stack memory exceeded the limit "MainStackFlt"</p>	= 2 faults since power up	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p>	Runs Continuously in 100ms loop	
			<p>Voltage difference between expected circuit voltage and actual test circuit voltage</p> <p>Indicates that the</p>	> 9 V	<p>Enable Calibration is True AND Run/Crank Voltage</p> <p>(Diagnostic System Code Clear Requested</p>	<p>= 1 (1 is Enabled)</p> <p>>= 7 V</p> <p>= False</p>	<p>150.00 ms out of a 200.00 ms window</p> <p>OR</p> <p>A2D Converter Test Error >=</p>	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		have changed for the indicated amount of time.	Processor detected a problem with the Analog to Digital convertor test circuit "MainADC_Flt"		AND Diagnostic System Reset Complete)	= True	0.20 seconds	
		Fail Case 7 This diagnostic checks the analog to digital converter (ADC) in the TCM poprocessor. If the accuracy of the ADC read of a test voltage is greater than the indicated threshold for the indicated amount of time then the DTC sets.	HWIO detects Fault that the Processor detected a problem with the Flash ECC (error correction code) test circuit "FlashECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3 failed cycles out of 10 cycles (turns on MIL) 5 failed cycles out of 10 cycles (shutdown vehicle)	
		Fail Case 8 9 These diagnostics use microprocessor internal circuitry to detect if there are faults in the RAM or Flash memory. The checks occur at power up and will set the DTC if there are the indicated number of failures in each diagnostic.	HWIO detects Fault that the Processor detected a problem with the RAM ECC (error correction code) test circuit "RAM_ECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3 failed cycles out of 10 cycles (turns on MIL) 5 failed cycles out of 10 cycles (shutdown vehicle)	
		Fail Case 10: This diagnostic checks the circuitry that transfers data from Flash memory to RAM. When the data transfer is made at startup and periodically there after a set of bytes are included that can be checked. The DTC sets if these bytes in	HWIO detects Fault in Transfer Test from Flash to RAM OR HWIO detects Fault in the Memory Data From Flash Indicates that the Processor detected a problem in the data transfer from Flash memory to RAM memory "DMA_XferTest"	= TRUE = TRUE	Enable Calibration is True (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1 (1 is Enabled) = False = True	50ms Execution Rate after controller initialization	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		RAM are not equal to the Flash memory.	First ROM Test Complete AND Processor Performance System Run Time Met AND Processor Integrity Fault Lower AND Processor Integrity Fault Upper	= True = 1 (1 is Enabled) after Controller Initialization = No Fault = No Fault	End of Test in Progress AND Diagnostic End of Trip in Progress AND Inhibit Path Test State	= True = False = Test Aborted OR Test Completed	Executes at the end of every trip	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Long Term Memory Performance	P062F	This Diagnostic tests specific areas of nonvolatile memory (NVM). The fault sets If the last write to nonvolatile memory was not successful or if the checksum of static NVM does not agree with the latest summation of that memory area. The NVM write and records the success or not of that write at key off and the success value is read at initialization.	HWIO reports next write to NVM will not succeed OR HWIO reports the assembly calibration integrity check has failed	= True = True	Enable Calibration is True Controller Status	= 1 (1 is Enabled) = Initialization	Runs once at controller initialization	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD1 Actuator Supply Circuit Voltage Low	P0658	This diagnostic reports when a high side driver 1 circuit low fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit low is present or not. HSD 1 Short to Ground Fault Status	=TRUE	Enable Calibration is True HSD 1	= 1 (1 is Enabled) = On	0.0375 seconds out of a 15 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD1 Actuator Supply Circuit Voltage High	P0659	This diagnostic reports when a high side driver 1 circuit high fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit high is present or not. HSD 1 Short to Power Fault Status	=TRUE	Enable Calibration is True	= 1 (1 is Enabled)	0.00625 seconds (1 Loop)	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Performance	P0711	Monitors the performance of Transmission Fluid Temperature (TFT) circuit by comparing the temperature calculated from the resistance vs temp table to an estimated cold soak average temperature or verifying that the temperature calculated from the resistance vs temp table has not latched at a value after a period of time.	Transmission Fluid Temperature Sensor compared to a Cold Soak Average Temperature	\geq (See supporting tables for failure threshold value)	Rationality Enable Calibration is True Time after init controller Cold Soak Enable Calibration is True Cold Soak Average Temperature Message Cold Soak Average Temperature P0712, P0713, U179A, U0293 TFT temperature	= 1 (1 is Enabled) ≥ 3.00 seconds = 1 (1 is Enabled) = Use Data ≥ -40.00 C NOT Fault Active $-40.00 \leq X \leq 130.00$ C	One diagnostic loop once all enable criteria have been met	Type A, 1 Trips
			Continuous Check for Transmission Fluid Temperature Stuck in Range Transmission Oil Temperature Raw - Previous Transmission Oil Temperature	≤ 0.00 C	Rationality Enable Calibration is True Time after init controller Continuous Rationality Enable Calibration is True Engine Speed Vehicle Speed Transmission Oil Temperature Raw	= 1 (1 is Enabled) ≥ 3.00 seconds = 1 (1 is Enabled) $0.00 \leq X \leq 8,000.00$ RPM for 0.00 seconds ≤ 185.79 MPH for 0.00 seconds $-40.00 \leq X \leq 130.00$ C	≥ 300.00 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Circuit Low Voltage	P0712	Monitors the Transmission Fluid Temperature (TFT) sensor circuit resistance and reports a low voltage condition if the sensed resistance is below a threshold.	Transmission Fluid Temperature (TFT) circuit resistance	≤ 68.60 ohms (Corresponds to 149 C which is above the operating range of the transmission)	Enable Calibration is True 12V Battery Voltage Ignition Run/Crank Voltage	= 1 (1 is Enabled) > 9.00 for 0.10 seconds > 9.00 for 0.10 seconds	2 seconds out of a 3 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Fluid Temperature (TFT) Sensor Circuit High Voltage	P0713	Monitors the Transmission Fluid Temperature (TFT) sensor circuit resistance and reports a high voltage condition if the sensed resistance is above a threshold.	Transmission Fluid Temperature (TFT) circuit resistance	$\geq 83,641.00$ ohms (Corresponds to a temperature below -50 C, which is below the operating range of the transmission)	Enable Calibration is True 12V Battery Voltage Ignition Run/Crank Voltage	= 1 (1 is Enabled) > 9.00 for 0.10 seconds > 9.00 for 0.10 seconds	2 seconds out of a 3 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Transmission Output Speed (TOS) Sensor Wrong Direction	P0721	The DTC detects incorrect TOS direction.	TOS Raw Direction	TOS Direction Raw is not Forward or Reverse	Enable Calibration is True TOS Sample Period TOS Sensor Type	= 1 (1 is Enabled) ≠ 0 = CeTOSR_e_Directional	3.50 seconds	Type A, 1 Trips
			TOS Raw Direction	TOS Direction Raw is Forward or Reverse	Enable Calibration is True TOS Sample Period TOS Sensor Type	= 1 (1 is Enabled) ≠ 0 = CeTOSR_e_Directional	5.00 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit - Direction Error	P077B	The DTC detects if the Transmission Output Speed Sensor Direction is Incorrect by Comparing with Calculated Direction from Motor Speed Sign	Transmission Output Speed Direction Raw	≠ Motor Direction	Enable Calibration is True P0721, P077C, P077D, P215C Hybrid Motor Speed based Estimated Output Speed is Valid Transmission Output Speed and Motor Output Speed Difference Motor Estimated Transmission Output Speed	= 1 (1 is Enabled) NOT Fault Active Calculated based on Stable Speed Equation ≤ 50.00 RPM ≥ 50.00 RPM	0.35 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit Low	P077C	Monitor to detect a low-voltage fault on the Transmission Output Speed Sensor	Transmission Output Speed Sensor Voltage	< 0.35 Volts	Enable Calibration is True P077D Ignition Run/Crank Voltage 12V Battery Voltage	= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 Volts for 0.00 seconds ≥ 9.00 volts for 0.00 seconds	≥ 0.2000 seconds for 36.00 counts at 25 ms	Type A
			Transmission Output Speed Sensor Voltage Pass Criteria	> 0.36 Volts	Same as FailEnable Calibration is True P077D Ignition Run/Crank Voltage 12V Battery Voltage	Same as Fail= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 volts for 0.00 seconds ≥ 9.00 volts for 0.00 seconds	≥ 1.50 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Speed Sensor Circuit High	P077D	Monitor to detect a high-voltage fault on the Transmission Output Speed Sensor	Transmission Output Speed Sensor Voltage	> 4.25 Volts	Enable Calibration is True P077C Ignition Run/Crank Voltage 12V Battery Voltage	= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 volts for 0.00 seconds ≥ 9.00 volts for 0.00 seconds	≥ 0.2000 seconds for 36.00 counts at 25 ms	Type A
			Transmission Output Speed Sensor Voltage Pass Criteria	< 4.25 Volts	Enable Calibration is True P077C Ignition Run/Crank Voltage 12V Battery Voltage	= 1 (1 is Enabled) NOT Fault Active ≥ 6.00 Volts for 0.00 seconds ≥ 9.00 volts for 0.00 seconds	≥ 1.50 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Upshift Switch Circuit	P0815	Checks to see if the manual tap up circuit is active for an expected amount of time while the IMS is in an expected range. Fail case 1 and fail case 2 must be met to trip this DTC.	IMS Position	= Drive 1, Drive 2, Drive 3, Drive 4, OR Drive 6	P0815 enable calibration P1761 P0836 Crank Diagnostic enable criteria met	= 1.00 (1 is enabled) NOT Fault Active (FA) NOT Fault Active (FA) AND NOT Test failed This Key On (TFTKO) AND NOT Fault Pending (FP) =True	Malfunction Criteria met for 3.00 seconds	Type C, No SVS
			Tap Switch position	= Tap Up				
			IMS Position	= Park, Reverse, Neutral, Drive 5, Drive 7, Drive 8, Drive 9, OR Drive 10	P0815 enable calibration P1761 P0836 Crank Diagnostic enable criteria met	= 1.00 (1 is enabled) NOT Fault Active (FA) NOT Fault Active (FA) AND NOT Test failed This Key On (TFTKO) AND NOT Fault Pending (FP) =True	Malfunction Criteria met for 655.00 seconds	
			Tap Switch position	= Tap Up				

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Downshift Switch Circuit	P0816	Checks to see if the manual tap down circuit is active for an expected amount of time while the IMS is in an expected range. Fail case 1 and fail case 2 must be met to trip this DTC.	IMS Position	= Drive 1, Drive 2, Drive 3, Drive 4, OR Drive 6	P0816 enable calibration P1761 P0836 Crank Diagnostic enable criteria met	= 1.00 (1 is enabled) NOT Fault Active (FA) NOT Fault Active (FA) AND NOT Test failed This Key On (TFTKO) AND NOT Fault Pending (FP) =True	Malfunction criteria met for 3.00 seconds	Type C, No SVS
			Tap Switch position	= Tap Down				
			IMS Position	= Park, Reverse, Neutral, Drive 5, Drive 7, Drive 8, Drive 9, OR Drive 10	P0816 enable calibration P1761 P0836 Crank Diagnostic enable criteria met	= 1.00 (1 is enabled) NOT Fault Active (FA) NOT Fault Active (FA) AND NOT Test failed This Key On (TFTKO) AND NOT Fault Pending (FP) =True	Malfunction criteria met for 655.00 seconds	
			Tap Switch position	= Tap Down				

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Up and Downshift Switch Circuit	P0826	This DTC reports when the tap switch position is invalid after an expected period of time.	Tap Switch Position	=Invalid (NOT reported as "TapUp", "TapDwn" or "TapOff")	P0826 enable calibration P1761 Crank Diagnostic enable criteria met	= 1.00 (1 is enabled) NOT Fault Active (FA) =True	Malfunction criteria met for 8.00 seconds	Type C, No SVS

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit Open	P0960	This DTC sets when the PCSA control circuit has been detected to be open	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts $\geq 0.00 \text{ RPM}$ && $\leq 8,000.00 \text{ RPM}$ for ≥ 0.00 seconds $\leq 250 \text{ mph}$ for ≥ 0.00 seconds $= 1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit Low Voltage	P0962	This DTC sets when the PCSA control circuit has been detected to be shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid A Control Circuit High Voltage	P0963	This DTC sets when PCS1 has been detected to be shorted to power	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit Open	P0964	This DTC sets when the PCSB control circuit has been detected to be open	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	$\geq 11.00 \text{ V}$ and $\leq 32.00 \text{ V}$ $> 11 \text{ Volts} \ \&\& \leq 16 \text{ Volts}$ $\geq 0 \text{ RPM} \ \&\& \leq 7500 \text{ RPM}$ for ≥ 5 seconds $\leq 200 \text{ mph}$ for ≥ 5 seconds $=1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit Low Voltage	P0966	This DTC sets when the PCSB control circuit has been detected to be shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.081 seconds in a 0.10 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid B Control Circuit High Voltage	P0967	This DTC sets when PCSb has been detected to be shorted to power or open circuited	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit Open	P0968	This DTC sets when the PCSC control circuit has been detected to be open circuit	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts $\geq 0.00 \text{ RPM}$ && $\leq 8,000.00 \text{ RPM}$ for ≥ 0.00 seconds $\leq 250 \text{ mph}$ for ≥ 0.00 seconds $= 1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit Low Voltage	P0970	This DTC sets when the PCSC control circuit has been detected to be shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.07 seconds in a 0.09 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid C Control Circuit High Voltage	P0971	This DTC sets when PCSC has been detected to be shorted to power or open circuited.	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Shift Solenoid A Control Circuit Low Voltage	P0973	This DTC sets when the Shift Solenoid A control circuit used for motor cooling has been detected to be shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && $\leq 8,000.00$ RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds $= 1$	Fail condition met for 0.07 seconds in a 0.09 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Shift Solenoid A Control Circuit High Voltage	P0974	This DTC sets when the Shift Solenoid A control circuit used for motor cooling has been detected as shorted to power or open circuit.	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && $\leq 8,000.00$ RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds $= 1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 2	P16E9	This DTC detects intermittent and continuous invalid SPI messages.	Communication Fault on 2nd Processor AND Communcation Fail on 2nd Processor Previous Loop	= True = True	Post Code Clear Diagnostic Disable	= False	12.5ms (One Loop)	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 1	P16F0	This DTC detects intermittent and continuous invalid SPI messages.	Valid Message Not Received Serial Communication Continuous Fail Threshold	= True >= 10.00 counts	Run Crank Low Voltage Crank	>= 9.50 V	125ms (10.00 counts at 12.5ms)	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Control Module Redundant Memory Performance	P16F3	This diagnostic detects RAM faults in real time for those variables that are determined to be safety critical. The DTC sets when the called variable is called and compared to its redundant variable and does not match. There are fail cases for secure vehicle speed, transmission output sensor to wheel speed sensor conversion factor, and the engine torque value.	Rate Limited Secure Vehicle Speed (Re)	≠ Dual Stored Rate Limited Secure Vehicle Speed (Ve)	Run Crank Voltage Enable Calibration is True	>= 11.00 V = 1 (1 is Enabled)	125.00 ms out of a 200.00 ms window	Type A, 1 Trips
			Bus Off Fault for Bus A&B AND Processor Performance System Run Time Met AND Processor Integrity Fault	= False = 1 (1 being Enabled) = False	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Performed on Powertrain Powerdown	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Pressure Control Solenoid Command Incorrect	P16F7	Detects controller faults such that solenoid commands doesn't match with it's expected associated Range State value.	Clutch Rationality Fault OR Clutch Solenoid Current Command Fault	= True = True	Pressure Solenoid Override Command Clutch Override Command Hydrualic Default State Enabled (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank	= False = False = False = False = True >= 11.00 V >= 9.50 V	137.50 ms out of a 200.00 ms window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Clutch Command Incorrect	P16F8	Detects controller fault such that clutch commands match with a known tie up condition for a given clutch configuration.	Clutch Tie Up Rationality Fault	= True	Pressure Solenoid Override Command Clutch Override Command Hydraulic Default State Enabled (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank	= False = False = False = False = True >= 11.00 V >= 9.50 V	137.50 ms out of a 200.00 ms window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Up and Downshift Switch Signal Circuit	P1761	This DTC reports if the tap up tap down switch signal has had an error count greater than a threshold for an expected period of time.	Number of tap up tap down signal rolling count errors	> 3.00	P1761 enable calibration Tap Up Tap Down Switch messages from Platform are equal to the expected value Run Crank Ignition voltage diagnostic conditions met	= 1.00 (1 is enabled) =TRUE =TRUE	Malfunction criteria met for 10.00 seconds	Type C, No SVS

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Range State Command Circuit	P179B	This diagnostic checks for corruption in signals sent over CAN for the Hybrid Range State. The diagnostic will detect the ARC (Alive Rolling Count) or Protection Value fault by checking the ARC and Protection Value of the Hybrid Range State.	Current ARC is not equal to previous ARC + 1 and Primary Value is not equal to protection value	No errors in 1000ms	Run Crank Active Run/Crank Voltage	>= 0.50 sec > 9.50 Volts	137.50 ms out of a 200.00 ms window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Circuit High Voltage	P1824	The DTC monitors if the IMS P Circuit is shorted to a High Voltage	Transmission Direction State PRNDL P Circuit Sensed	PARK Has Not Been Observed Low	P1824 Transmission Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On False > 9.00 volts	2.50 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL P Circuit Has Been Observed Low for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Circuit Low Voltage	P182A	The DTC monitors if the IMS A Circuit is shorted to a Low Voltage	PRNDL State Trans Direction State	Transitional 1 DRIVE	P182A Transmission Direction State Fault Active PRNDL State PRNDL A Circuit Sensed Ignition Voltage	NOT Fault Active OR Failed This Key On False PARK PRNDL A Circuit Has NOT Been Observed High for 1.00 second > 9.00 volts	8.00 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL A Circuit Has Been Observed High for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Circuit Low Voltage	P182B	The DTC monitors if the IMS B Circuit is shorted to a Low Voltage	Transmission Direction State PRNDL B Circuit Sensed	PARK PRNDL B Circuit Has Not Been Observed High	P182B Transmission Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On False > 9.00 volts	2.50 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL B Circuit Has Been Observed High for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch B Circuit High Voltage	P182C	The DTC monitors if the IMS B Circuit is shorted to a High Voltage	PRNDL State Trans Direction State	Transitional 13 DRIVE	P182C PRNDL State PRNDL B Circuit Sensed Trans Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On PARK Has Been Observed High for 1.00 second False > 9.00 volts	8.00 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL B Circuit Has Been Observed Low for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch P Circuit Low Voltage	P182D	The DTC monitors if the IMS P Circuit is shorted to a Low Voltage	PRNDL State Trans Direction State	Transitional 8 DRIVE	P182D PRNDL State PRNDL P Circuit Sensed Trans Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On PARK Has Been Observed Low for 1.00 second False > 9.00 volts	8.00 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL P Circuit Has Been Observed High for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch- Invalid Range	P182E	The DTC monitors if the IMS is in an Invalid Range	PRNDL State	Illegal	P182E Ignition Voltage	NOT Fault Active OR Failed This Key On > 9.00 volts	5.00 seconds Pass Conditions PRNDL State is NOT Illegal for 5.00 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Circuit High Voltage	P182F	The DTC monitors if the IMS C Circuit is shorted to a High Voltage	Transmission Direction State PRNDL C Circuit Sensed	DRIVE Has Not Been Observed Low	P182F Trans Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On False > 9.00 volts	2.50 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL C Circuit Has Been Observed Low for 4.00 seconds + 1.00 count at 6.25ms	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch A Circuit High Voltage	P1838	The DTC monitors if the IMS A Circuit is shorted to a High Voltage	Transmission Direction State	PARK	P1838	NOT Fault Active OR Failed This Key On	2.50 seconds + count at 6.25ms	Type B, 2 Trips
			PRNDL A Circuit Sensed	Has Not Been Observed Low	Trans Direction State Fault Active Ignition Voltage	False > 9.00 volts	Pass Conditions PRNDL A Circuit Has Been Observed Low for 1.59 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Internal Mode Switch C Circuit Low Voltage	P1839	The DTC monitors if the IMS C Circuit is shorted to a Low Voltage	Transmission Direction State PRNDL C Circuit Sensed	PARK PRNDL C Circuit Has Not Been Observed High	P1839 Trans Direction State Fault Active Ignition Voltage	NOT Fault Active OR Failed This Key On False > 9.00 volts	2.50 seconds + 1.00 count at 6.25ms Pass Conditions PRNDL C Circuit Has Been Observed Low for 1.59 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Output Shaft Speed (OSS) - Wheel Speed Correlation	P215C	The DTC Correlates the Transmission Output Speed with the ABS Wheel Speed and Motor Speed to Detect any Failures in the Transmission Output Speed Sensor	Difference between Transmission Output Speed and the Calculated Average of Output Speed from the Motors and Wheel Speed Sensors	≥ 140.00 RPM	Enable Calibration is True OBD Wheel Speed Sensors Driven Wheel Estimated Vehicle Speed Fault Propulsion System Active TOS calculated from Wheel Speeds TOS calculated from Motor Speeds	= 1 (1 is Enabled) True False True ≥ 150.00 RPM ≥ 150.00 RPM	0.20 seconds	Type B, 2 Trips
			Difference between Transmission Output Speed and the Calculated Average of Output Speed from the Motors and Wheel Speed Sensors	≥ 140.00 RPM	Enable Calibration is True OBD Wheel Speed Sensors Driven Wheel Estimated Vehicle Speed Fault Propulsion System Active TOS calculated from Wheel Speeds TOS calculated from Motor Speeds	= 1 (1 is Enabled) True False True ≤ 150.00 RPM ≤ 150.00 RPM	0.20 seconds	
			Difference between Transmission Output Speed and the Calculated Average of Output Speed from the Motors and Wheel Speed Sensors Pass Criteria	≤ 50.00 RPM	Enable Calibration is True OBD Wheel Speed Sensors Driven Wheel Estimated Vehicle Speed Fault Propulsion System Active	= 1 (1 is Enabled) True False True	0.50 seconds	

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit Low	P2534	Detects a run crank relay open circuit	Runk Crank Line Voltage	≤ 2.0 Volts	Enable Calibration is True CAN Communication ECM Run Crank Active CAN Data Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1 (1 is Enabled) Enabled Available and Active = False = True	2.5 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Run/ Start Position Circuit High	P2535	Detects a run crank relay short to power	Runk Crank Line Voltage	> 6.0 V	Enable Calibration is True CAN Communication ECM Run Crank Active CAN Data Diagnostic System Code Clear Requested Diagnostic System Reset Complete	= 1 (1 is True) Enabled Available and False = False = True	2.5 seconds out of a 5 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Ignition Switch Accessory Position Circuit Low	P2537	Detects an accessory position circuit open	Accessory	False	P2537 Propulsion System Propulsion System Active Time	Not Test Failed This Key On and Not Test Passed This Key On Active > 0.50 seconds	0.20 seconds	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD2 Actuator Supply Circuit Voltage Low	P2670	This diagnostic reports when a high side driver 2 circuit low fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit low is present or not. HSD 2 Short to Ground Fault Status	=TRUE	Enable Calibration is True HSD 2	= 1 (1 is Enabled) = On	0.0375 seconds out of a 15 seconds window	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
HSD2 Actuator Supply Circuit Voltage High	P2671	This diagnostic reports when a high side driver 2 circuit high fault is detected by the current supply driver and is reported via HWIO.	HWIO circuitry detects if an electrical circuit high is present or not. HSD 2 Short to Power Fault Status	=TRUE	Enable Calibration is True	= 1 (1 is Enabled)	0.00625 seconds (1 Loop)	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit Open	P2718	This DTC sets when the PCSD control circuit has been detected to be open circuit	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts $\geq 0.00 \text{ RPM}$ && $\leq 8,000.00 \text{ RPM}$ for ≥ 0.00 seconds $\leq 250 \text{ mph}$ for ≥ 0.00 seconds $= 1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit Low Voltage	P2720	This DTC sets when the PCSD control circuit has been detected to be open circuit or shorted to power	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && $\leq 8,000.00$ RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.06 seconds in a 0.07 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid D Control Circuit High Voltage	P2721	This DTC sets when PCSD has been detected to be shorted to battery	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit Open	P2727	This DTC sets when the PCSE control circuit has been detected to be open circuit	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts $\geq 0.00 \text{ RPM}$ && $\leq 8,000.00 \text{ RPM}$ for ≥ 0.00 seconds $\leq 250 \text{ mph}$ for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit Low Voltage	P2729	This DTC sets when the PCSE control circuit has been detected to be open circuit or shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && $\leq 8,000.00$ RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.07 seconds in a 0.09 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid E Control Circuit High Voltage	P2730	This DTC sets when PCSE has been detected to be shorted to power	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid F Control Circuit Open	P2736	This DTC sets when the PCSF control circuit has been detected to be open circuit	Voltage measurement outside of controller specific acceptable range indicates an open circuit Controller specific circuit voltage thresholds are set to meet the following controller specification for an open circuit	$\geq 200 \text{ K } \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts $\geq 0.00 \text{ RPM}$ && $\leq 8,000.00 \text{ RPM}$ for ≥ 0.00 seconds $\leq 250 \text{ mph}$ for ≥ 0.00 seconds $= 1$	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid F Control Circuit Low Voltage	P2738	This DTC sets when the PCSF control circuit has been detected to be open circuit or shorted to ground	Voltage measurement outside of controller specific acceptable range indicates a ground short Controller specific circuit voltage thresholds are set to meet the following controller specification for a ground short	$\leq 0.5 \Omega$ impedance between signal and controller ground	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && $\leq 8,000.00$ RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds $= 1$	Fail condition met for 0.06 seconds in a 0.07 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Pressure Control (PC) Solenoid F Control Circuit High Voltage	P2739	This DTC sets when PCSF has been detected to be shorted to power	Voltage measurement outside of controller specific acceptable range indicates a short to voltage Controller specific circuit voltage thresholds are set to meet the following controller specification for a short to voltage	$\leq 0.5 \Omega$ impedance between signal and controller voltage source	Battery Voltage Ignition voltage Engine Speed Vehicle Speed PropSysActive	≥ 11.00 volts and ≤ 32.00 volts ≥ 9.00 volts ≥ 0.00 RPM && \leq 8,000.00 RPM for ≥ 0.00 seconds ≤ 250 mph for ≥ 0.00 seconds = 1	Fail condition met for 0.30 seconds in a 0.40 second window.	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Communicati on Bus A Off	U0073	This diagnostic detects that BUS A is off or is non-operational. If the host controller can not transmit on bus A in the indicated time the DTC is set.	Bus off failures exceeds before the sample time of is reached	4 counts (equivalent to 0.05 seconds) 0.56 seconds	<u>General Enable Criteria:</u> U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management <u>Ignition Voltage Criteria:</u> Ignition voltage Power Mode <u>Off Cycle Enable Criteria:</u> KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds CAN hardware is bus OFF for	Not Active on Current Key Cycle Enabled Not Active Not Active >= 11.00 or >= 9.50 = run = 1 (1 indicates enabled) = Active > 11.00 > 0.1125 seconds	Diagnostic runs in 12.5 ms loop	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with ECM/PCM A	U0100	This diagnostic detects that the engine control module (ECM) has stopped sending messages on Bus A. If ECM message traffic is not received on Bus A by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0AA</p> <p>Message \$0C9</p> <p>Message \$1A3</p> <p>Message \$287</p> <p>Message \$3E9</p> <p>Message \$4C1</p>	<p>≥ 10.00 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p><u>General Enable Criteria:</u> U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p><u>Ignition Voltage Criteria:</u> Ignition voltage</p> <p>Power Mode</p> <p><u>Off Cycle Enable Criteria:</u> Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0100</p> <p>ECM</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p> <p>is present on the bus</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on With Brake System Control Module	U0129	This diagnostic detects that the brake system control module has stopped sending messages. If brake system control module message traffic is not received by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C1</p> <p>Message \$0C5</p>	<p>≥ 10.0 seconds</p> <p>≥ 10.0 seconds</p>	<p><u>General Enable Criteria:</u> U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p><u>Ignition Voltage Criteria:</u> Ignition voltage</p> <p>Power Mode</p> <p><u>Off Cycle Enable Criteria:</u> Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0129</p> <p>Brake System Control Module</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p> <p>is present on the bus</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type B, 2 Trips

18 OBDG01 TCM - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Lost Communicati on with Hybrid Powertrain Control Module	U0293	This diagnostic detects that the hybrid powertrain control module has stopped sending messages. If hybrid powertrain control module message traffic is not received by the host controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0B9</p> <p>Message \$0BA</p> <p>Message \$0BB</p> <p>Message \$0BC</p> <p>Message \$186</p> <p>Message \$1DF</p> <p>Message \$4A7</p>	<p>≥ 0.50 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 0.50 seconds</p> <p>≥ 10.00 seconds</p>	<p><u>General Enable Criteria:</u> U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p><u>Ignition Voltage Criteria:</u> Ignition voltage</p> <p>Power Mode</p> <p><u>Off Cycle Enable Criteria:</u> Enable Calibration is True</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U0293</p> <p>HCP</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 9.50</p> <p>> 3.0000 seconds</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p> <p>is present on the bus</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply A Circuit Low	P06B1	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	< 12.00 V	Wakeup Signal	ON	0.34 seconds out of a 0.42 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply A Circuit High	P06B2	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	> 22.00 V	Wakeup Signal	ON	0.34 seconds out of a 0.42 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Performance	P0A1B	<p>This Diagnostic tests all the internal processor subsystems for faults which suggest that the integrity of the processor can not be trusted.</p> <p>Fail Case 1:</p> <p>In case of many faults the MCP microprocessor along with the other microprocessors need to take remedial action to directly take the vehicle to a safe state. This fail case tests at powerdown that the microprocessors can take those remedial actions effectively. Potential failures can include memory, software, processor and ALU faults. The diagnostic runs by setting different controller inputs and the outputs are checked in each case across all of the microprocessors . The DTC sets when the outputs are not as expected for the indicated number of tests.</p> <p>Fail Case 2, 3, 4, 5, 6:</p>	<p>Inhibit Path Test Failed</p> <p>Indicates that the Processor is not demonstrating the ability to inhibit the system (take remedial action) during the Inhibit Path Test</p> <p>"2ndFailsToTakeRmdlActn"</p>	>= 3 Failures	<p>HV Batt contactor Staus Available</p> <p>Invertor State</p> <p>HV Batt Voltage</p> <p>HV Contactors</p> <p>12V Batt Voltage</p> <p>Vehicle Speed</p> <p>Motor Faults</p> <p>Motor Speed</p> <p>SRAR Shutdowns</p> <p>SPI Fault</p> <p>RunCrank Active</p> <p>Ram or ROM fault</p> <p>Seed received in wrong order fault</p> <p>Seed/Key Timeout</p> <p>Powermode Off time</p>	<p>= TRUE</p> <p>= Off</p> <p>>= 80.00 V</p> <p>= Closed</p> <p>> 9.50 V</p> <p>< 0.00 kph</p> <p>= FALSE (None active)</p> <p><= 10.00 rpm</p> <p>= FALSE</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>= FALSE (No active P0601, P0604)</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>< 5.00 s</p>	<p>Executes in a 12.5ms loop</p> <p>Increment/ Decrement counter = 3</p>	Type A, 1 Trips
			<p>Key Value</p> <p>Indicates that the Processor received incorrect key values for the associated seed values that it sent out to the secondary processor</p>	≠ expected key value	<p>Number Of Mains Processors to monitor</p> <p>IPT status</p> <p>SPI Fault</p>	<p>> 0</p> <p>= Not Running</p> <p>= FALSE (No active P0606)</p>	<p>Executes in a 12.5ms loop</p> <p>Detects in 150ms or two consecutive faulty keys</p>	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>The microprocessors in the TPIM ECU monitor that each of the others is executing code correctly and in a timely manner. These fail cases rely on a seed and key interaction where one micro-controller sends a seed and a second controller runs a predefined set of calculations and responds with a key. The first controller sends a seed and checks that the received key matches its lookup table value for that seed and that it was received in time. The second controller checks that the correct seed value has been received and that is in time. The DTC sets when there is a mismatch of seed or key values or the expected key or seed value is out of order or if the key or seed value has not been received in the indicated time.</p> <p>Fail Case 7, 8, 9:</p> <p>These diagnostics are built into the hardware of the MCP microprocessor by the</p>	"2ndRxIncorrectKeys"		Run/Crank Voltage	>= 9.50 V		
			<p>New Seed Update Time</p> <p>Indicates that the Processor did not receive a key value from the secondary processor during the expected time frame</p> <p>"MainDtctdSdKeyTimeout"</p>	> 1.00 sec	<p>Number Of Mains Processors to monitor</p> <p>AND</p> <p>SPI Faults</p> <p>AND</p> <p>Seed/Key Init delay timer</p> <p>AND</p> <p>Run/Crank Voltage</p> <p>OR</p> <p>12V Battery Voltage</p>	<p>> 0</p> <p>= FALSE (No active P0606)</p> <p>>= 1.00 s</p> <p>>= 9.50 V</p> <p>> 11 V</p>	<p>Executes in a 12.5ms loop</p> <p>Detects in 1 second</p>	
			<p>Seed sequence</p> <p>Indicates that the Processor received key values in the incorrect order from the secondary processor</p> <p>"MainDtctdSdRxWrongOrder"</p>	≠ expected order	<p>Number Of Mains Processors to monitor</p> <p>AND</p> <p>SPI Faults</p> <p>AND</p> <p>Run/Crank Voltage</p> <p>OR</p> <p>12V Battery Voltage</p>	<p>> 0</p> <p>= FALSE (No active P0606)</p> <p>>= 9.50 V</p> <p>> 11 V</p>	<p>0.15 seconds out of a 0.2 seconds window</p> <p>Executes in a 12.5ms loop</p>	
			<p>Program Sequence Watch Seed time Since Seed Change</p> <p>Indicates that the Processor detected that a program Seed was not sending for the Program Sequence Watch</p> <p>"MainSequenceFit"</p>	> 0.20 ms	Seed Update Key Store Fault Enable is true	= 0 (1 is Enabled)	Executes in a 50ms loop after controller initialization	
			<p>Program Sequence Watch Fault on a CPU</p> <p>Indicates that the Processor detected that a program was ran out of sequence according to the Program Sequence</p>	seed sequence ≠ expected sequence	Program Sequence Watch Enabled (KaPISD_b_ProgSeqWatchEnbl[x])	= TRUE	0.15 seconds out of a 0.2 seconds window	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>chip manufacturer. These diagnostics check the ALU and Configuration registers to ensure there have been no changes. The DTC sets if these reigsters have changed since the software flash at the vehicle plant. An additional built in diagnostic checks whether the top of the stack memory has changed from initialization at power up. The DTC sets if this section of memory has been detected to have changed for the indicated amount of time.</p> <p>Fail Case 10:</p> <p>This diagnostic checks the analog to digital converter (ADC) in the MCP microprocessor. If the accuracy of the ADC read of a test voltage is greater than the indicated threshold for the indicated amount of time then the DTC sets.</p> <p>Fail Case 11, 12:</p> <p>These diagnostics use microprocessor internal</p>	Watch "MainSequenceFlt"					
			HWIO detects Fault in ALU Test	= 2 faults in a key cycle	Enabled Calibration is True	= 1 (1 is Enabled)	Runs continuously in 12.5ms loop	
			Indicates that the Processor detected an ALU fault in the processor "MainALU_Flt"		(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False		
					Run Crank Ignition Low Voltage	≠ True		
					Run Crank Low Voltage Crank	≠ True		
			HWIO detects Fault in Configuration Registry Test	= 2 faults in a key cycle	Enable Calibration is True	= 1 (1 is Enabled)	Runs continuously in 12.5ms loop	
			Indicates that the Processor detected a Configuration Register fault in the processor "MainCfgRegFlt"		(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False		
					Run Crank Ignition Low Voltage	≠ True		
					Run Crank Low Voltage Crank	≠ True		
			HWIO detects Fault in the Stack Limit Test	= 2 faults since power up	Enable Calibration is True	= 1 (1 is Enabled)	Runs Continuously in 100ms loop	
			Indicates that the CPU Stack memory exceeded the limit "MainStackFlt"		(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False		
				voltage diff between real circuit and test circuit	> 16 V	Enable Calibration is True	= 1 (1 is Enabled)	
Run/Crank Voltage	>= 7 V							
			Indicates that the				OR	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>circuitry to detect there are faults in the RAM or Flash memory. The checks occur at power up and will set the DTC if there are the indicated number of failures in each diagnostic.</p> <p>Fail Case 13:</p> <p>This diagnostic checks the circuitry that transfers data from Flash memory to RAM. When the data transfer is made at startup and periodically there after a set of bytes are included that can be checked. The DTC sets if these bytes in RAM are not equal to the Flash memory.</p>	Processor detected a problem with the Analog to Digital convertor test circuit "MainADC_Flt"		(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	<p>= False</p> <p>= True</p>	A2D Converter Test Error >= 0.20 seconds	
			HWIO detects Fault that the Processor detected a problem with the Flash ECC (error correction code) test circuit "FlashECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	<p>= 1 (1 is Enabled)</p> <p>= TRUE</p>	<p>Executes once at every power up reset</p> <p>3.00 failed cycles out of 10.00 cycles (turns on MIL)</p> <p>5.00 failed cycles out of 10.00 cycles (shutdown vehicle)</p>	
			HWIO detects Fault that the Processor detected a problem with the RAM ECC (error correction code) test circuit "RAM_ECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Rest	<p>= 1 (1 is Enabled)</p> <p>= TRUE</p>	<p>Executes once at every power up reset</p> <p>3.00 failed cycles out of 10.00 cycles (turns on MIL)</p> <p>5.00 failed cycles out of 10.00 cycles (shutdown vehicle)</p>	
			<p>HWIO detects Fault in Transfer Test from Flash to RAM</p> <p>OR</p> <p>HWIO detects Fault in the Memory Data From Flash</p>	<p>= TRUE</p> <p>= TRUE</p>	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p>	50ms Execution Rate after controller initialization	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Indicates that the Processor detected a problem in the data transfer from Flash memory to RAM memory "DMA_XferTest"					
			First ROM Test Complete AND Processor Performance System Run Time Met AND Processor Integrity Fault Lower AND Processor Integrity Fault Upper	= True = 1 (1 is Enabled) after Controller Initialization = No Fault = No Fault	End of Test in Progress AND Diagnostic End of Trip in Progress AND Inhibit Path Test State	= True = False = Test Aborted OR Test Completed	Executes at the end of every trip	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit	P0A3F	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit observes the error between the sin and cos signals produced by the operation of the resolver. If the error is below a threshold voltage the circuit will output a status signal indicating a loss of signal. If the loss of signal status is present for a threshold amount of time, the diagnostic will fail.	Amplitude of Sin or Cos Signal	<2.3V	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 s > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit Range/ Performance	P0A40	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit observes the error between the sin and cos signals produced by the operation of the resolver. If the error is above a threshold voltage, the circuit will output a status signal indicating the degradation of signal. If the degradation of signal status is present for a threshold amount of time, the diagnostic will fail.	Sin or Cos Signal	>4.0V	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 s > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U Current Low	P0A5E	This diagnostic monitors the sensed current on the "U" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	ABS(Peak Phase Axis Current on the U phase)	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	RUN > 10.00 ms ≠ Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase V Current Low	P0A61	This diagnostic monitors the sensed current on the "V" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the V phase	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	Run > 10.00 ms ≠ Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase W Current Low	P0A64	This diagnostic monitors the sensed current on the "W" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the W phase	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power State Inverter Voltage Rotor Position Squared Current Comanded	Run > 10.00 ms ≠Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Inverter Performance	P0A78	This diagnostic monitors the status of the IGBTs. The IGBT module will continually monitor the IGBTs for a short between the upper and lower phase. The module will then report out a status of being in a DeSat fault. If the DeSat fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C High or Low Side IGBT	DSatFltPending (Status Fault Bit)	Wakeup Signal	ON	0.002 seconds out of a 1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor A Circuit Range/ Performance	P0AEE	This diagnostic verifies that the high voltage electric motor inverter phase "U" temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated on key up after the vehicle has been off for a certain amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter Phase U Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0AF0 and P0AEF > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor A Circuit Low	P0AEF	This diagnostic monitor for inverter phase U temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase U Temperature Sensor	> 170.00 degrees C	Sensor Exists WakeUp Signal	= 1.00 On	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor A Circuit High	P0AF0	This diagnostic monitor for inverter phase U temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase U Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON ≥ 90.00 s ≥ ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor C Circuit Range/ Performance	P0BD2	This diagnostic verifies that the motor inverter phase V temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated after a specified amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter Phase V Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0BD3 and P0BD4 > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor C Circuit Low	P0BD3	This diagnostic monitor for inverter phase V temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase V Temperature Sensor	> 170.00 degrees C	Sesor Exists WakeUp Signal	= 1.00 ON	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor C Circuit High	P0BD4	This diagnostic monitor for inverter phase V temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase V Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON ≥ 90.00 s ≥ ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor E Circuit Range/ Performance	P0BDC	This diagnostic verifies that the high voltage electric motor inverter phase "W" temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated on key up after the vehicle has been off for a certain amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter Phase W Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0BDD and P0BDE > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor E Circuit Low	P0BDD	This diagnostic monitor for inverter phase W temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase W Temperature Sensor	> 170.00 degrees C	Sesor Exists WakeUp Signal	= 1.00 ON	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor E Circuit High	P0BDE	This diagnostic monitor for inverter phase W temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase W Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON ≥ 90.00 s ≥ ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U Current Sensor Offset Out-of Range	P0BE6	This diagnostic monitors the offset that is learned by the phase "U" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	U phase offset current learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail conditions met 0.10 sec after enable conditions met	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U Current Sensor Circuit Low	P0BE7	This diagnostic monitors for the "U" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U Current Sensor Circuit High	P0BE8	This diagnostic monitors for the "U" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is above the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output highside	> 700.00 amps	Wakeup Signal Enable Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase V Current Sensor Offset Out-of Range	P0BEA	This diagnostic monitors the offset that is learned by the phase "V" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	V phase current sensor offset learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fai conditions met 0.10 Sec after enable conditions met	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase V Current Sensor Circuit Low	P0BEB	This diagnostic monitors for the "V" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	V phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase V Current Sensor Circuit High	P0BEC	This diagnostic monitors for the "V" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is above the failure threshold for sufficient time, the diagnostic will fail.	V phase current Sensor output at highside	> 700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase W Current Sensor Offset Out-of Range	P0BEE	This diagnostic monitors the offset that is learned by the phase "W" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	W phase current sensor offset learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail condititions met 0.10 sec after enable conditoins met	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase W Current Sensor Circuit Low	P0BEF	This diagnostic monitors for the "W" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	W phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase W Current Sensor Circuit High	P0BF0	This diagnostic monitors for the "W" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is above the failure threshold for sufficient time, the diagnostic will fail.	W phase current sensor output at high side	> 700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U- V-W Correlation	P0BFD	This diagnostic monitors the U, V, and W phase currents for balance. The absolute value of the sum of the phase values is compared against a threshold. If the sum is above the failure threshold for sufficient time, the diagnostic will fail.	Sum of U-V-W phase currents	≥ 110.00 amps	Wakeup Signal Run Flag	On = 1.00	0.0032 seconds out of a 0.0038 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Phase U- V-W Current Sensor Overcurrent	P0C01	This diagnostic monitors the sensed current on all three phases of the electric motor. The absolute value of the highest current phase value is then compared against a threshold. If the value is above the failure threshold for sufficient time, the diagnostic will fail. This diagnostic implements the use of 2 different fail timers, one fast and one slow. The fast timer has a very short sample window so that the diagnostic will detect a sudden fault, the slower timer has a longer sample window to allow the diagnostic to detect an intermittent fault.	U, V, or W Phase Current Sensor	> 600.00 amps	Wakeup Signal	On	0.0104 seconds out of a 0.104 seconds window (x of y) OR 0.00416 seconds out of a 0.0208 seconds window (x of y)	Type A, 1 Trips
			D Axis current less than calculated threshold determined by stator temperature listed in supporting table unless the motor temperature reading is faulted, then D Axis current threshold is determined by a default value	D-Axis Current<- 600.00 amps (faulted motor temp value) P0C01 D-Axis Current Thresholds (See supporting tables for expected threshold values for non-faulted motor temperature readings)	Wakeup Signal	On	0.0104 seconds out of a 0.104 seconds window (x of y) OR 0.00416 seconds out of a 0.0208 seconds window (x of y)	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Inverter Power Supply Circuit/Open	P0C0B	This diagnostic monitors the status of the IGBTs. The IGBT module will continuously monitor the supply circuit voltage. When the supply circuit drops below a threshold voltage the module then report out a status of being in a Bias fault. If the Bias fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C Power Supply	Failed (Status Fault Bit)	Inverter State	Initialization Complete	0.002 seconds out of a 0.024 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase U Over Temperature	P0C11	This diagnostic monitors the inverter phase U temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	Inverter Phase U Temperature	> 126.00 degrees C	PIM Phase U Temperature	TEMP NORMAL	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase V Over Temperature	P0C12	This diagnostic monitors the inverter phase V temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	Inverter Phase V Temperature	> 126.00 degrees C	PIM Phase V Temperature	TEMP Normal	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase W Over Temperature	P0C13	This diagnostic monitors the inverter phase W temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	Inverter Phase W Temperature	> 126.00 degrees C	PIM Phase W Temperature	TEMP NORMAL	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Not Learned	P0C17	This diagnostic monitors the initial offset that is learned by the resolver circuit. The diagnostic runs only when there is no previously stored value for the resolver offset. The diagnostic fails when during the learn process either the motor speed is higher than a threshold, the total high voltage bus is below a threshold voltage, the peak to peak current on the motor falls below a threshold, or the learn process takes longer than a threshold time.	Initial Offset Learn Could Not Complete Because: ABS(Motor Speed)	> 50.00 rpm	Key Off	TRUE	0.30 s Learn Time	Type A, 1 Trips
			Initial Offset Learn Could Not Complete Because: Filtered DC	< 200.00 V	Key Off	TRUE	0.30 s Learn Time	
			Initial Offset Learn Could Not Complete Because: ALL phase Current	< 15.00 A	Key Off	TRUE	0.30 s Learn Time	
			Initial Offset Learn Could Not Complete Because: Learn Timer	> 1.40 s	Key Off	TRUE	0.30 s Learn Time	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Torque Delivered Performance	P0C19	This diagnostic is a plausibility check that the motor torque is following the commanded torque. Potential failure modes include the motor's ability to produce torque and the torque calculation path in the microprocessor. When the difference between commanded motor torque and actual motor torque is greater than the indicated threshold for longer than the timer threshold, the DTC is set.	Absolute value of (Commanded torque - Torque Command Slewed)	> 123.00 Nm	DTCs not Fault Active AND DTCs not Fault Active AND Motor Drive State ID AND ((DTCs not Fault Active) OR (Voltage Hazard Active AND Motor Temperature Fault Active))	(P1AF5 or P1B0C or P1B41) (P0A3F or P0A40 or P1B03 or P16EB) = Run P0BFD = True = False	0.1875 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Exceeded Learning Limit	P0C4E	This diagnostic monitors the offset that is learned by the resolver circuit. The diagnostic runs on every key off cycle after the offset learn has completed. Once the offset value has been determined it is compared to a threshold. If the value of the offset is above the fail threshold, the diagnostic will fail. Another way the diagnostic can fail is once the offset learn has completed and the offset value determined, it is then compared against the previously stored offset value. If the absolute value of the difference between the previous offset value and the current offset value is above the failure threshold the diagnostic will fail.	Offset Learn Completes AND ABS(Offset Correction Angle)	> 30.00 degrees	Key Off Offset Learn Status	TRUE Complete	5.00 key off cycles of out of offset angle being out of range	Type A, 1 Trips
			Offset Learn Completes AND ABS(Offset Correction Angle - previously stored value)	> 10.00 degrees	Key Off Offset Learn Status	TRUE Complete	5.00 key off cycles of out of offset angle being out of range	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit A Low	P0C52	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Resolver S13 Circuit Reference Voltage	< 0.50 V	Wakeup Signal	ON	0.525 seconds out of a 0.8375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit A High	P0C53	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range high. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Resolver S13 Circuit Reference Voltage	> 4.50 V	Wakeup Signal	ON	0.2125 seconds out of a 0.3125 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit B Low	P0C5C	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Resolver S24 Circuit Reference Voltage	< 0.50 V	Wakeup Signal	ON	0.525 seconds out of a 0.8375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit B High	P0C5D	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range high. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Resolver S24 Circuit Reference Voltage	> 4.50 V	Wakeup Signal	ON	0.2125 seconds out of a 0.3125 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase U Temperature Sensor Erratic	P190A	This diagnostic monitors the inverter phase U temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase V Temperature Sensor Erratic	P190B	This diagnostic monitors the inverter phase V temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Inverter Phase W Temperature Sensor Erratic	P190C	This diagnostic monitors the inverter phase W temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Not Programmed	P1A4F	This Diagnostic checks that the MCP micro-controller has a valid calibration flashed into it. The controller manufacturer flashes a calibration with a configuration ID. At the vehicle plant the controller is reflashed with a valid configuration ID. The DTC sets when the diagnostic checks the configuration ID and it does not match the correct ID.	MCP Processor Configuration ID	≠ CeMCGR_i_MCP1	None	NA	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Random Access Memory (RAM)	P1A50	This Diagnostic tests the RAM in the MCP micro-controller. The diagnostic checks that RAM has not changed unexpectedly. Pattern checks are done at initialization where different patterns are written and then read back. The DTC sets if the patterns do not match. Continuous checks are done while the controller is executing code that store the same variables in multiple locations. When those variables are read, a check is done to be sure both locations still match. A DTC sets if the locations do not match for the indicated time.	Secure "Y" variable	≠ Primary "V" variable for greater than 125 ms	Current Time Execution - Time of Last DualStore Error	> 25 ms	Executes in Background loop	Type A, 1 Trips
			HWIO detects an illegal write to Write Protected RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop 0 counts to fail	
			2nd Processor State of Health RAM Fault Latched	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop every 1000ms	
			Checksum of PreservedNVM_Region for Main Processor State of Health and 2nd Processor State Of Health	≠ Expected checksum value	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization	
			HWIO detects fault in System RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in Cache RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in eTPU RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			Main SOH RAM Fault Latched AND SPI Fault Latched AND System RAM Fault Count AND Cache RAM Fault Count AND eTPU RAM Fault Count	= 0 = False = 0 = 0 = 0	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) Time Since Last Duel Store Error	= False = True > 1,000 ms	Executes in Background loop every 1000ms	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Read Only Memory (ROM)	P1A51	This Diagnostic tests ROM (flash) memory in the MCP micro-controller. The test checks that ROM has not changed since it was flashed in the plant. The bytes of ROM in different areas (code, calibration, HW configuration, etc.) are summed and compared to a checksum for that area. The DTC sets when the checksum comparison does not match for the indicated number of times.	Calculated Checksum of the Boot ROM	≠ Expected Checksum	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 5 failures	Type A, 1 Trips
			2nd Processor State of Health ROM fault latched	= TRUE	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	Runs continuously in the background	
			Calculated Checksum of Torque Security Related Calibrations	≠ Expected Checksum	Controller Status (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) = Enable Calibration is True = Enable Calibration is True	= On = False = True = 0 (0 is Enabled) = 1 (1 is Enabled)	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 2 failures	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			ECC Fault detected in Flash memory	= TRUE	Controller Status Power Up Reset AND HWIO BINVDM ECC State AND HWIO ROM Fault Enable Calibration is true	= On = False = False = True = 1 (1 is Enabled)	Greater than 5 failures at controller initialization Runs once at initialization	
			ROM fault Active AND 2nd SOH ROM Fault Latched AND Main SOH ROM Fault Latched	≠ True ≠ True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs in the Background	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Long Term Memory Performance	P1ADC	This Diagnostic tests specific areas of nonvolatile memory (NVM). The fault sets if the last write to nonvolatile memory was not successful or if the checksum of static NVM does not agree with the latest summation of that memory area. The DTC sets if the fault is set in the indicated time.	HWIO reports next write to NVM will not succeed OR HWIO reports the assembly calibration integrity check has failed	= True = True	Enable Calibration is True Controller Status	= 1 (1 is Enabled) = Initialization	Runs once at controller initialization	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module System Voltage Low	P1ADE	This diagnostic detects low voltage in the vehicle's 12 volt system. The fault sets when the host controller detects supply voltage below the indicated threshold for the indicated time.	Ignition Voltage	≤ 10.00 Volts	Enable Calibration is True AND 12V Starter Engaged AND Ignition Run/Crank Voltage AND Engine Speed (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1 (1 is Enabled) = False > 6.0 Volts ≥ 0.00 RPM = False = True	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module System Voltage High	P1ADF	This diagnostic detects high voltage in the vehicle's 12 volt system. The fault sets when the host controller detects supply voltage above the indicated threshold for the indicated time.	Ignition Voltage	≥ 16.00 Volts	Enable Calibration is True AND Ignition Run/Crank Voltage (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1.00 (1 is Enabled) > 6.0 Volts = False = True	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Hybrid Battery System Voltage High	P1AEE	This diagnostic monitors the total high voltage system voltage which is too high for the hardware. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage OR High Voltage Hardware Flag	> 450.00 Volts = True	Controller Initialization	Complete	0.01 seconds out of a 0.2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage System Isolation Fault	P1AF0	This diagnostic monitors the high voltage bus for possible shorts to chassis. The high voltage positive leg is compared to the high voltage negative leg via a ratio. If the ratio falls outside of a specific window for sufficient time, the diagnostic will fail.	Isolation Ratio (Neg mid-pack voltage / Pos mid-pack voltage)	> 4.53 OR < 0.21	No Active DTCs: Controller Initialization	P1AE8, P1AE9, P1AEC Complete	2.5 seconds out of a 5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit Low	P1AF4	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Positive mid-pack voltage	< 20.00 Volts	Controller Initialization Run Crank Active Contactors	Complete True Closed	0.7375 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit High	P1AF5	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	Positive mid-pack voltage - High Voltage sensor voltage	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.525 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit Loss of Tracking	P1B03	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit is continually calculating the position of the rotor in degrees. When the error between each sampling of position is greater than 5 degrees the circuit will output a status signal indicating a loss of tracking. If the loss of tracking status is present for a threshold amount of time, the diagnostic will fail.	Internal Tracking Error	>5 Degrees	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit Low	P1B0B	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail	Negative mid-pack voltage	< 20.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.7375 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit High	P1B0C	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Negative to Ground Reading - Total High Voltage Reading from High Voltage Battery	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.525 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Position Sensor Circuit Overspeed	P1B0D	This diagnostic monitors the output speed of the high voltage motor. The absolute value of the sensed speed of the motor is compared against a threshold. If the sensed speed is above the fail threshold for sufficient time, the diagnostic will fail.	ABS(Motor Speed)	> 12,700.00 rpm	Wakeup Signal	On	0.09 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Isolation Sensing Performance	P1B41	This diagnostic verifies that the high voltage bus positive and negative leg sensors are neither inappropriately high nor low. It compares the sensed battery pack voltage against the high voltage positive and negative leg. If the absolute value of the difference between the sensed battery voltage and the high voltage positive and negative leg sensors is greater than the failure threshold for a sufficient time, the diagnostic will fail.	ABS(Total High Voltage Measured By the Battery Pack - High Voltage Measured from Positive to Ground - High Voltage Measured from Negative to Ground)	≥ 70.00 V	No Active DTCs: Controller Initialization Contactors	P1AE8, P1AE9, P1B0B, P1B0C Complete Closed	0.175 seconds out of a 0.2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

[illegible]

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		the electronic current delivery circuits. The fault is set if the difference in current delivered between the primary and secondary paths is greater than the shown threshold. The DTC is set if the fault is present for longer than the indicated time.			TorqCalcPerf Flt counter OR TrqMntr Fault	≠ 0 = TRUE		
			Absolute difference between Issq in primary and secondary path is greater than the threshold value	> 50.00 Amps	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
		Fail Case 6: This diagnostic tests the calculation of the back emf torque in the primary and secondary paths. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated back emf torque in the primary path is different from the secondary calculation path by more than the threshold given. The DTC is set if the fault is present for longer than the indicated time.	Absolute difference between IssCmd Torque in primary and secondary path is greater than the threshold value	> 123.00 Nm	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			Absolute difference between Back emf Torque in primary and secondary path is greater than the threshold value	> 0.015 Nm	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
		Fail Case 7, 8, 9: This diagnostic compares different calculations of Usd and Usq in a primary and a secondary path. Potential failures can include memory,	Absolute difference between Usd Limited in primary and secondary path is greater than the threshold value Or Absolute difference between Usq Limited in primary and secondary	> 0.40 V (for Usd) > 0.40 V (for Usd)	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>software, processor and ALU faults. The fault is set if the calculated differences are greater than the indicated thresholds. The DTC is set if either fault is present for longer than the indicated time.</p> <p>Fail Case 10: This diagnostic tests the primary and secondary input power paths for motor A. Potential failures can include the power input circuits, microprocessor memory, software and calibration, processor and ALU faults. The fault is set if the difference between primary and secondary input power are greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 11: This diagnostic tests the primary and secondary input voltage paths for motor A. Potential failures can include the power input circuits, microprocessor</p>	path is greater than the threshold value					
			UsdLmt Squared plus UsqLmt Squared OR DutyQ Squared plus DutyD Squared AND Duty Squared minus UsLmt Squared OR Perf Squared	<p>> 0.70</p> <p>> 0.70</p> <p>> 0.30</p> <p>> 1.00</p> <p>> 0.10</p> <p>> 0.15</p>	<p>DriveStateID</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			Absolute difference of the Mod Index Square Calcluation for Usd and Usq for Volt Hz mode in primary and secondary paths	> 5.00 V	<p>DriveStateID</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			Difference between Power Input in primary and secondary path is greater than or equal to the threshold value	>= 40,000.00 Watts	<p>DriveStateID</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			Difference between Vdc Adapt in primary and secondary path is greater than or equal to the threshold value	>= 0.07 Volts	<p>DriveStateID</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p>	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		memory, software and calibration, processor and ALU faults. The fault is set if the difference between primary and secondary voltage are greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.			OR TrqMntr Fault	= TRUE		
			Difference between Reactive Power (Qest) in the primary and secondary path is greater than or equal to the threshold value	>= 43,755.40 Watts	DriveStateID TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
		Fail Case 12: This diagnostic tests the primary and secondary reactive power paths for motor A. Potential failures can include the reactive power input circuits, microprocessor memory, software and calibration, processor and ALU faults. The fault is set if the difference between primary and secondary reactive power is greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.	Calculated resolver Mtr Speed difference in the primary and secondary path is greater than the threshold value OR Calculated resolver Mtr Speed difference in the primary and secondary path is greater than the threshold value	> 20,000.00 rpm > 510.00 radians/sec	DriveStateID TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			To Pass: Calculated resolver Mtr Speed AND Calculated Mtr Speed in radians/sec	< 19,000.00 rpm <= 146.00 rad				
		Fail Case 13: This diagnostic tests the primary and secondary resolver motor speed for motor A. The diagnostic tests						

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		the resolver circuits. The fault is set if the difference between primary and secondary motor speed is greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.						

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Long Term Memory Reset	P1EB6	This Diagnostic tests the NonVolatile Memory (NVM) in the MCP micro-controller for changes since the last write at power down. The bytes of various NVM sections are summed and compared to checksums for each section that were stored at the last powerdown. The DTC sets when the checksum comparisons do not match.	Static NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	Type A, 1 Trips
			Preserved NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Power Up Reset	= False	Ignition Status	= Run or Crank	Runs once at controller initialization	
			BINVDM NVM Checksum at power-up	≠ Checksum at power-down	Enable Calibration is True	= 1 (1 is Enabled)	3 out of 5 controller initializations for Failure	
			Dynamic NVM checksum at power-up AND Shutdown Finished	≠ Checksum at power-down = TRUE	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Static NVM Error Dynamic NVM Error BINVDM ECC Error	= False = False = False	Enable Calibration is True	= 1 (1 is Enabled)	Runs once at controller initialization	

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Control Module A Lost Communication With Hybrid Powertrain Control Module B on Bus B	U182E	This diagnostic detects that the Hybrid Powertrain Control Module B has stopped sending messages on Bus B. If Hybrid Powertrain Control Module B message traffic is not received on Bus B by the MCPA controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$1D8</p> <p>Message \$3C5</p> <p>Message \$3D7</p>	<p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl and Ignition Accessory Line and Battery Voltage and General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p> <p>> 0.4000 seconds</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U182E Hybrid Powertrain Control Module B (VICM)	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Control Module A Lost Communicati on With Hybrid Powertrain Control Module	U1845	This diagnostic detects that the Hybrid Powertrain Control Module has stopped sending messages on Bus A. If Hybrid Powertrain Control Module message traffic is not received on Bus A by the MCPA controller in the indicated time the DTC is set.	Message is not received from controller for Message \$1A45	≥ 10.00 seconds	General Enable Criteria: U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management Ignition Voltage Criteria: Ignition voltage Power Mode Off Cycle Enable Criteria: KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line and Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for	Not Active on Current Key Cycle Enabled Not Active Not Active ≥ 9.50 = run = 1 (1 indicates enabled) = Active > 11.00 > 0.4000 seconds	See Threshold Value Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U0293 Hybrid Powertrain Control Module	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Lost Communicati on With Engine Control Module (ECM)/ Powertrain Control Module (PCM)	U1876	This diagnostic detects that the Engine Control Module (ECM/PCM) has stopped sending messages. If ECM/PCM message traffic is not received by the MCPA controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C9</p> <p>Message \$1A3</p> <p>Message \$4C1</p> <p>Message \$4C7</p> <p>Message \$4F1</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type B, 2 Trips

18 OBDG01 MCP1 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U0293 Hybrid Powertrain Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 Motor Control Processor A (MCPA) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Reference Voltage D Circuit Low	P06A4	This diagnostic monitors the PSD Reference Voltage. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time the diagnostic will fail.	Continuous Failure HWIO circuitry detects if an electrical circuit low is present or not. 8.2 volt circuit fault status	<7.9V	Ignition Run/Crank Voltage OR Battery Voltage	> 9.50 > 11.00	0.0875 seconds out of a 0.09375 seconds window	Type A, 1 Trips
			Intermittent Failure HWIO circuitry detects if an electrical circuit low is present or not. 8.2 volt circuit fault status	< 7.9V	Ignition Run/Crank Voltage OR Battery Voltage	> 9.50 > 11.00	0.0875 seconds out of a 0.09375 seconds window	

18 OBDG01 Motor Control Processor A (MCPA) Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Reference Voltage D Circuit High	P06A5	This diagnostic monitors the PSD Reference Voltage. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time the diagnostic will fail.	Continuous Failure HWIO circuitry detects if an electrical circuit low is present or not. 8.2 volt circuit fault status	> 8.5 V	Ignition Run/Crank Voltage OR Battery Voltage	> 9.50 V > 11.00 V	0.0875 seconds out of a 0.09375 seconds window	Type A, 1 Trips
			Intermittent Failure HWIO circuitry detects if an electrical circuit low is present or not. 8.2 volt circuit fault status	> 8.5 V	Ignition Run/Crank Voltage OR Battery Voltage	> 9.50 V > 11.00 V	0.0875 seconds out of a 0.09375 seconds window	

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 1	P16F0	This diagnostic checks that the SPI communication between the Hybrid Control Processor (HMCP) and MCP is working correctly. Potential failures could be in the microprocessor's SPI handling, the transmission line or the microprocessors ability to execute code. The DTC sets if the messages are missing, the counter is not updated, or the SPI handler detects an incorrect checksum in the time indicated.	CRC error on receive Number of missing messages OR Alive Rolling Count (ARC) incremented from previous value (0-3)	=True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	Type A, 1 Trips
			HWIO Received Errors AND Receiving Data in Progress	≠ 0 ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	
			Number of Missing Received Messages	> 4 messages	(Diagnostic System Code Clear Requested AND Diagnostic System Reset	= False = True	0.175 seconds out of a 0.2 seconds window	

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False > 11.00 V >= 9.50 V > 11.00 V		

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor 1 Position Sensor Sense Circuit 1 High Voltage	P1904	This monitor detects when the position speed direction sensor circuit A is shorted high	HWIO circuitry detects if a circuit high is present	> 7.79 V	Low Side Output	ON	0.05 seconds out of a 0.15 seconds window With 10 retries with 0.30 seconds between retry attempts	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor 1 Position Sensor Sense Circuit 2 High Voltage	P1905	This monitor detects when the position speed direction sensor circuit B is shorted high	HWIO circuitry detects if a circuit high is present	> 7.79 V	Low Side Output	ON	0.05 seconds out of a 0.15 seconds window With 10 retries with 0.30 seconds between retry attempts	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor 1 Position Sensor Sense Circuit 1 Low Voltage	P1906	This monitor detects when the position speed direction sensor circuit A is shorted to ground	HWIO circuitry detects if a short to ground is present	< 0.41 V			0.006 seconds out of a 0.01 seconds window With 35 retries	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor 1 Position Sensor Sense Circuit 2 Low Voltage	P1907	This monitor detects when the position speed direction sensor circuit B is shorted to ground	HWIO circuitry detects if a short to ground is present	< 0.41 V			0.006 seconds out of a 0.01 seconds window With 35 retries	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Control Module Hybrid Battery Voltage Sense Circuit High Voltage	P1AE9	This diagnostic monitors the total high voltage for out of range high. The total high voltage is compared against a threshold. If the total high voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage	> 575.00 volts	Controller Initialization Run/CrankActive	Complete True	Failure Conditions met for 1.5 seconds out of a 2 seconds window	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

[illegible]

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "A" Hybrid Battery System Voltage High	P1AEE	This diagnostic monitors the total high voltage system voltage which is too high for the hardware. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage OR High Voltage Hardware Flag	> 445.00 Volts = True	Controller Initialization	Complete	0.004 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Lost Communicati on With Transmissio n Control Module (TCM)	U1849	This diagnostic detects that the Transmission Control Module has stopped sending messages. If Transmission Control Module message traffic is not received by the MCPA controller in the indicated time the DTC is set.	Message is not received from controller for Message \$1F5	≥ 10.00 seconds	<u>General Enable Criteria:</u> U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management <u>Ignition Voltage Criteria:</u> Ignition voltage Power Mode <u>Off Cycle Enable Criteria:</u> KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for U1849 Transmission Control Module	Not Active on Current Key Cycle Enabled Not Active Not Active ≥ 9.50 = run = 0 (1 indicates enabled) = Active > 11.00 > 0.4000 seconds Not Active on Current Key Cycle is present on the bus	See Threshold Value Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 MCP1 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor A Control Module Lost Communicati on With Engine Control Module (ECM)/ Powertrain Control Module (PCM)	U1876	This diagnostic detects that the Engine Control Module (ECM/PCM) has stopped sending messages. If ECM/PCM message traffic is not received by the MCPA controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C9</p> <p>Message \$1A3</p> <p>Message \$4C1</p> <p>Message \$4C7</p> <p>Message \$4F1</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p><u>General Enable Criteria:</u> U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p><u>Ignition Voltage Criteria:</u> Ignition voltage</p> <p>Power Mode</p> <p><u>Off Cycle Enable Criteria:</u> KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line</p> <p>Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p> <p>U1876</p> <p>Engine Control Module</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 0 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p> <p>> 0.4000 seconds</p> <p>Not Active on Current Key Cycle</p> <p>is present on the bus</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type B, 2 Trips

18 OBDG01 MCP1 Supporting Tables

Initial Supporting table - P0C01 D-Axis Current Thresholds

Description: X-Axis is stator temperature, Y-Axis is current threshold for the D-Axis current

y/x	0	50	100	110	120	130	140	150	160	170
1	-485	-485	-485	-485	-485	-485	-485	-485	-485	-485

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Performance	P0A1C	<p>This Diagnostic tests all the internal processor subsystems for faults which suggest that the integrity of the processor can not be trusted.</p> <p>Fail Case 1: In case of many faults the MCP microprocessor along with the other microprocessors need to take remedial action to directly take the vehicle to a safe state. This fail case tests at powerdown that the microprocessors can take those remedial actions effectively. Potential failures can include memory, software, processor and ALU faults. The diagnostic runs by setting different controller inputs and the outputs are checked in each case across all of the microprocessors . The DTC sets when the outputs are not as expected for the indicated number of tests.</p> <p>Fail Case 2, 3, 4, 5, 6: The microprocessors in the TPIM ECU monitor</p>	<p>Inhibit Path Test Failed</p> <p>Indicates that the Processor is not demonstrating the ability to inhibit the system (take remedial action) during the Inhibit Path Test "2ndFailsToTakeRmdlActn "</p>	>= 3 Failures	<p>HV Batt contactor Staus Available</p> <p>Invertor State</p> <p>HV Batt Voltage</p> <p>HV Contactors</p> <p>12V Batt Voltage</p> <p>Vehicle Speed</p> <p>Motor Faults</p> <p>Motor Speed</p> <p>SRAR Shutdowns</p> <p>SPI Fault</p> <p>RunCrank Active</p> <p>Ram or ROM fault</p> <p>Seed received in wrong order fault</p> <p>Seed/Key Timeout</p> <p>Powermode Off time</p>	<p>= TRUE</p> <p>= Off</p> <p>>= 80.00 V</p> <p>= Closed</p> <p>> 9.50 V</p> <p>< 0.00 kph</p> <p>= FALSE (None active)</p> <p><= 10.00 rpm</p> <p>= FALSE</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>= FALSE (No active P0601, P0604)</p> <p>= FALSE (No active P0606)</p> <p>= FALSE</p> <p>< 5.00 s</p>	<p>Executes in a 12.5ms loop</p> <p>Increment/ Decrement counter = 3</p>	Type A, 1 Trips
			<p>Key Value</p> <p>Indicates that the Processor received incorrect key values for the associated seed values that it sent out to the secondary processor "2ndRxIncorrectKeys"</p>		≠ expected key value	<p>Number Of Mains Processors to monitor</p> <p>IPT status</p> <p>SPI Fault</p> <p>Run/Crank Voltage</p>	<p>> 0</p> <p>= Not Running</p> <p>= FALSE (No active P0606)</p> <p>>= 9.50 V</p>	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		that each of the others is executing code correctly and in a timely manner. These fail cases rely on a seed and key interaction where one micro-controller sends a seed and a second controller runs a predefined set of calculations and responds with a key. The first controller sends a seed and checks that the received key matches its lookup table value for that seed and that it was received in time. The second controller checks that the correct seed value has been received and that is in time. The DTC sets when there is a mismatch of seed or key values or the expected key or seed value is out of order or if the key or seed value has not been received in the indicated time.	New Seed Update Time	> 1.00 sec	Number Of Mains Processors to monitor AND SPI Faults AND Seed/Key Init delay timer AND Run/Crank Voltage OR 12V Battery Voltage	> 0 = FALSE (No active P0606) ≥ 1.00 s ≥ 9.50 V > 11 V	Executes in a 12.5ms loop Detects in 1 second	
			Seed sequence	≠ expected order	Number Of Mains Processors to monitor AND SPI Faults AND Run/Crank Voltage OR 12V Battery Voltage	> 0 = FALSE (No active P0606) ≥ 9.50 V > 11 V	0.15 seconds out of a 0.2 seconds window Executes in a 12.5ms loop	
			Program Sequence Watch Seed time Since Seed Change	> 0.20 ms	Seed Update Key Store Fault Enable is true	= 0 (1 is Enabled)	Executes in a 50ms loop after controller initialization	
			Program Sequence Watch Fault on a CPU	seed sequence ≠ expected sequence	Program Sequence Watch Enabled (KaPISD_b_ProgSeqWatc hEnbl[x])	= TRUE	0.15 seconds out of a 0.2 seconds window	
		Fail Case 7, 8, 9: These diagnostics are built into the hardware of the MCP microprocessor by the chip manufacturer. These diagnostics check the ALU and Configuration registers	HWIO detects Fault in	= 2 faults in a key cycle	Enabled Calibration is	= 1 (1 is Enabled)	Runs	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>to ensure there have been no changes. The DTC sets if these registers have changed since the software flash at the vehicle plant. An additional built in diagnostic checks whether the top of the stack memory has changed from initialization at power up. The DTC sets if this section of memory has been detected to have changed for the indicated amount of time.</p> <p>Fail Case 10: This diagnostic checks the analog to digital converter (ADC) in the MCP microprocessor. If the accuracy of the ADC read of a test voltage is greater than the indicated threshold for the indicated amount of time then the DTC sets.</p> <p>Fail Case 11, 12: These diagnostics use microprocessor internal circuitry to detect there are faults in the RAM or Flash memory. The checks occur at power up and will set the DTC if there are the indicated number of</p>	<p>ALU Test</p> <p>Indicates that the Processor detected an ALU fault in the processor "MainALU_Flt"</p>		<p>True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= False</p> <p>= True</p> <p>≠ True</p> <p>≠ True</p>	continuously in 12.5ms loop	
			<p>HWIO detects Fault in Configuration Registry Test</p> <p>Indicates that the Processor detected a Configuration Register fault in the processor "MainCfgRegFlt"</p>	= 2 faults in a key cycle	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) AND Run Crank Ignition Low Voltage AND Run Crank Low Voltage Crank</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p> <p>≠ True</p> <p>≠ True</p>	Runs continuously in 12.5ms loop	
			<p>HWIO detects Fault in the Stack Limit Test</p> <p>Indicates that the CPU Stack memory exceeded the limit "MainStackFlt"</p>	= 2 faults since power up	<p>Enable Calibration is True</p> <p>(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)</p>	<p>= 1 (1 is Enabled)</p> <p>= False</p> <p>= True</p>	Runs Continuously in 100ms loop	
			<p>voltage diff between real circuit and test circuit</p> <p>Indicates that the Processor detected a problem with the Analog to Digital convertor test</p>	> 16 V	<p>Enable Calibration is True AND Run/Crank Voltage</p> <p>(Diagnostic System Code Clear Requested AND</p>	<p>= 1 (1 is Enabled)</p> <p>>= 7 V</p> <p>= False</p>	<p>0.15 seconds out of a 0.2 seconds window</p> <p>OR</p> <p>A2D Converter Test Error >= 0.20 seconds</p>	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		failures in each diagnostic.	circuit "MainADC_Flt"		Diagnostic System Reset Complete)	= True		
		Fail Case 13: This diagnostic checks the circuitry that transfers data from Flash memory to RAM. When the data transfer is made at startup and periodically there after a set of bytes are included that can be checked. The DTC sets if these bytes in RAM are not equal to the Flash memory.	HWIO detects Fault that the Processor detected a problem with the Flash ECC (error correction code) test circuit "FlashECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Reset	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3.00 failed cycles out of 10.00 cycles (turns on MIL) 5.00 failed cycles out of 10.00 cycles (shutdown vehicle)	
			HWIO detects Fault that the Processor detected a problem with the RAM ECC (error correction code) test circuit "RAM_ECC_CktTest"	= TRUE	Enable Calibration is True AND Power-Up Rest	= 1 (1 is Enabled) = TRUE	Executes once at every power up reset 3.00 failed cycles out of 10.00 cycles (turns on MIL) 5.00 failed cycles out of 10.00 cycles (shutdown vehicle)	
			HWIO detects Fault in Transfer Test from Flash to RAM OR HWIO detects Fault in the Memory Data From Flash Indicates that the Processor detected a problem in the data	= TRUE = TRUE	Enable Calibration is True (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1 (1 is Enabled) = False = True	50ms Execution Rate after controller initialization	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			transfer from Flash memory to RAM memory "DMA_XferTest"					
			First ROM Test Complete AND Processor Performance System Run Time Met AND Processor Integrity Fault Lower AND Processor Integrity Fault Upper	= True = 1 (1 is Enabled) after Controller Initialization = No Fault = No Fault	End of Test in Progress AND Diagnostic End of Trip in Progress AND Inhibit Path Test State	= True = False = Test Aborted OR Test Completed	Executes at the end of every trip	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit	P0A45	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit observes the error between the sin and cos signals produced by the operation of the resolver. If the error is below a threshold voltage the circuit will output a status signal indicating a loss of signal. If the loss of signal status is present for a threshold amount of time, the diagnostic will fail.	Amplitude of Sin or Cos Signal	<2.3V	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 s > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit Range/ Performance	P0A46	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit observes the error between the sin and cos signals produced by the operation of the resolver. If the error is above a threshold voltage, the circuit will output a status signal indicating the degradation of signal. If the degradation of signal status is present for a threshold amount of time, the diagnostic will fail.	Sin or Cos Signal	>4.0V	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 s > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor B Circuit Range/ Performance	P0AF3	This diagnostic verifies that the high voltage electric motor inverter phase "U" temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated on key up after the vehicle has been off for a certain amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter A Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0AF4 and P0AF5 > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor B Circuit Low	P0AF4	This diagnostic monitor for inverter phase U temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase U Temperature Sensor	> 170.00 degrees C	Sesor Exists WakeUp Signal	= 1.00 On	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor B Circuit High	P0AF5	This diagnostic monitor for inverter phase U temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	PIM Temperature Sensor A Inverter Phase U Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON >= 90.00 s >=ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor D Circuit Range/ Performance	P0BD7	This diagnostic verifies that the motor inverter phase V temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated after a specified amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter Phase V Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0BD8 and P0BD9 > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor D Circuit Low	P0BD8	This diagnostic monitor for inverter phase V temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase V Temperature Sensor	> 170.00 degrees C	Sesor Exists WakeUp Signal	= 1.00 ON	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor D Circuit High	P0BD9	This diagnostic monitor for inverter phase V temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase V Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON ≥ 90.00 s ≥ ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor F Circuit Range/ Performance	P0BE1	This diagnostic verifies that the high voltage electric motor inverter phase "W" temperature sensor is neither inappropriately high nor low. This diagnostic compares the temperature reading from the sensor to a calculated average temperature of the vehicle. This average temperature is only calculated on key up after the vehicle has been off for a certain amount of time. The absolute value of the sensed temperature minus the calculated average temperature is then compared against a threshold. If the calculated delta between the sensed temperature and the calculated average temperature is above the fail threshold the diagnostic will fail.	ABS(Inverter Phase W Temp- Cold Soak Average Temp)	> 20.00 degrees C	Vehicle off soak timer met Cold Start Average Temperature No Active Power Inverter Temp Out Of Range Faults: Time after controller initialization	= TRUE > -20.00 C P0BE2 and P0BE3 > 5.13 seconds	0.525 seconds out of a 0.625 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor F Circuit Low	P0BE2	This diagnostic monitor for inverter phase W temperature sensor voltage which is out of range low. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase W Temperature Sensor	> 170.00 degrees C	Sesor Exists WakeUp Signal	= 1.00 ON	2.5 seconds out of a 3.5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Inverter Temperature Sensor F Circuit High	P0BE3	This diagnostic monitor for inverter phase W temperature sensor voltage which is out of range high. The temperature sensor this diagnostic is monitoring is a negative temperature coefficient thermistor with a pull up resistor on the sensing board, meaning a high temperature of sensor short to ground will result in a low sensed voltage. After conversion the sensed temperature is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	Inverter Phase W Temperature Sensor	< -50.00 degrees C	Sensor Exists Wakeup Signal Inverter Warmup Time at or above inverter warmup torque	= 1.00 ON >= 90.00 s >=ABS(20.00)Nm	2.625 seconds out of a 3.65 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase U Over Temperature	P0C14	This diagnostic monitors the inverter phase U temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	Inverter Phase U Temperature	> 131.00 degrees C	PIM Phase U Temperature	TEMP NORMAL	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase V Over Temperature	P0C15	This diagnostic monitors the inverter phase V temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	PIM Phase V Temperature	> 131.00 degrees C	PIM Phase V Temperature	TEMP Normal	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase W Over Temperature	P0C16	This diagnostic monitors the inverter phase W temperature for an in-range high temperature condition. The sensed temperature is compared against a threshold. If the sensed temperature is above the failure threshold for a sufficient time, the diagnostic will fail.	PIM Phase W Temperature	> 131.00 degrees C	PIM Phase W Temperature	TEMP NORMAL	1.2 seconds out of a 2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Not Learned	P0C18	This diagnostic monitors the initial offset that is learned by the resolver circuit. The diagnostic runs only when there is no previously stored value for the resolver offset. The diagnostic fails when during the learn process either the motor speed is higher than a threshold, the total high voltage bus is below a threshold voltage, the peak to peak current on the motor falls below a threshold, or the learn process takes longer than a threshold time.	Initial Offset Learn Could Not Complete Because: ABS(Motor Speed)	> 50.00 rpm	Key Off	TRUE	0.30 s Learn Time	Type A, 1 Trips
			Initial Offset Learn Could Not Complete Because: Filtered DC	< 200.00 V	Key Off	TRUE	0.30 s Learn Time	
			Initial Offset Learn Could Not Complete Because: ALL phase Current	< 30.00 A	Key Off	TRUE	0.30 s Learn Time	
			Initial Offset Learn Could Not Complete Because: Learn Timer	> 1.40 s	Key Off	TRUE	0.30 s Learn Time	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Torque Delivered Performance	P0C1A	This diagnostic is a plausibility check that the motor torque is following the commanded torque. Potential failure modes include the motor's ability to produce torque and the torque calculation path in the microprocessor. When the difference between commanded motor torque and actual motor torque is greater than the indicated threshold for longer than the timer threshold, the DTC is set.	Absolute value of (Commanded torque - Torque Command Slewed)	> 132.00 Nm	DTCs not Fault Active AND DTCs not Fault Active AND Motor Drive State ID AND ((DTCs not Fault Active) OR (Voltage Hazard Active AND Motor Temperature Fault Active))	(P1AF5 or P1B0C or P1B41) (P0A3F or P0A40 or P1B03 or P16EB) = Run P0BFD = True = False	0.1875 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Exceeded Learning Limit	P0C4F	This diagnostic monitors the offset that is learned by the resolver circuit. The diagnostic runs on every key off cycle after the offset learn has completed. Once the offset value has been determined it is compared to a threshold. If the value of the offset is above the fail threshold, the diagnostic will fail. Another way the diagnostic can fail is once the offset learn has completed and the offset value determined, it is then compared against the previously stored offset value. If the absolute value of the difference between the previous offset value and the current offset value is above the failure threshold the diagnostic will fail.	Offset Learn Completes AND ABS(Offset Correction Angle)	> 30.00 degrees	Key Off Offset Learn Status	TRUE Complete	5.00 key off cycles of out of offset angle being out of range	Type A, 1 Trips
			Offset Learn Completes AND ABS(Offset Correction Angle - previously stored value)	> 10.00 degrees	Key Off Offset Learn Status	TRUE Complete	5.00 key off cycles of out of offset angle being out of range	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit A Low	P0C57	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Resolver S13 Circuit Reference Voltage	< 0.50 V	Wakeup Signal	ON	0.525 seconds out of a 0.8375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit A High	P0C58	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range high. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Resolver S13 Circuit Reference Voltage	> 4.50 V	Wakeup Signal	ON	0.2125 seconds out of a 0.3125 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit B Low	P0C61	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Resolver S24 Circuit Reference Voltage	< 0.50 V	Wakeup Signal	ON	0.525 seconds out of a 0.8375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit B High	P0C62	This diagnostic monitors the output voltage from the high voltage motor resolver circuit which is out of range high. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Reslover S24 Circuit Reference Voltage	> 4.50 V	Wakeup Signal	ON	0.2125 seconds out of a 0.3125 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase U Temperature Sensor Erratic	P190D	This diagnostic monitors the inverter phase U temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase V Temperature Sensor Erratic	P190E	This diagnostic monitors the inverter phase V temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Inverter Phase W Temperature Sensor Erratic	P190F	This diagnostic monitors the inverter phase W temperature sensor voltage which could be intermittently high, low, or open. A rolling average of sensed temperature readings calculated over a set amount of time is compared against a threshold that has been calculated based on the stator current. If the calculated rolling average is above the calculated fail threshold for sufficient time the, the diagnostic will fail.	A rolling average of temperature readings calculated over 0.38 s this calculation is known as a string length. Temperature readings are taken every .025s.	> an estimated string length calculated based on stator current.	Start-Up Delay	> 0.13 s	1.75 seconds out of a 2.375 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Not Programmed	P1A52	This Diagnostic checks that the MCP micro-controller has a valid calibration flashed into it. The controller manufacturer flashes a calibration with a configuration ID. At the vehicle plant the controller is reflashed with a valid configuration ID. The DTC sets when the diagnostic checks the configuration ID and it does not match the correct ID.	MCP Processor Configuration ID	≠ CeMCGR_i_MCP2	None	NA	0.125 seconds out of a 0.2 seconds window	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Random Access Memory (RAM)	P1A53	This Diagnostic tests the RAM in the MCP micro-controller. The diagnostic checks that RAM has not changed unexpectedly. Pattern checks are done at initialization where different patterns are written and then read back. The DTC sets if the patterns do not match. Continuous checks are done while the controller is executing code that store the same variables in multiple locations. When those variables are read, a check is done to be sure both locations still match. A DTC sets if the locations do not match for the indicated time.	Secure "Y" variable	≠ Primary "V" variable for greater than 125 ms	Current Time Execution - Time of Last DualStore Error	> 25 ms	Executes in Background loop	Type A, 1 Trips
			HWIO detects an illegal write to Write Protected RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop 0 counts to fail	
			2nd Processor State of Health RAM Fault Latched	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Executes in Background loop every 1000ms	
			Checksum of PreservedNVM_Region for Main Processor State of Health and 2nd Processor State Of Health	≠ Expected checksum value	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization	
			HWIO detects fault in System RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in Cache RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			HWIO detects fault in eTPU RAM	= TRUE	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs once at Initialization 1 count to fail	
			Main SOH RAM Fault Latched AND SPI Fault Latched	= 0 = False	(Diagnostic System Code Clear Requested AND Diagnostic System Reset	= False = True	Executes in Background loop every 1000ms	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			AND System RAM Fault Count AND Cache RAM Fault Count AND eTPU RAM Fault Count	= 0 = 0 = 0	Complete) Time Since Last Duel Store Error	> 1,000 ms		

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Read Only Memory (ROM)	P1A54	This Diagnostic tests ROM (flash) memory in the MCP micro-controller. The test checks that ROM has not changed since it was flashed in the plant. The bytes of ROM in different areas (code, calibration, HW configuration, etc.) are summed and compared to a checksum for that area. The DTC sets when the checksum comparison does not match for the indicated number of times.	Calculated Checksum of the Boot ROM	≠ Expected Checksum	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 5 failures	Type A, 1 Trips
			2nd Processor State of Health ROM fault latched	= TRUE	Controller Status ROM Checksum in Progress (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= On ≠ True = False = True	Runs continuously in the background	
			Calculated Checksum of Torque Security Related Calibrations	≠ Expected Checksum	Controller Status (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) = Enable Calibration is True = Enable Calibration is True	= On = False = True = 0 (0 is Enabled) = 1 (1 is Enabled)	1 failure if it occurs during the first ROM test of the ignition cycle otherwise 2 failures	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
			ECC Fault detected in Flash memory	= TRUE	Controller Status Power Up Reset AND HWIO BINVDM ECC State AND HWIO ROM Fault Enable Calibration is true	= On = False = False = True = 1 (1 is Enabled)	Greater than 5 failures at controller initialization Runs once at initialization	
			ROM fault Active AND 2nd SOH ROM Fault Latched AND Main SOH ROM Fault Latched	≠ True ≠ True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	Runs in the Background	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Long Term Memory Performance	P1ADD	This Diagnostic tests specific areas of nonvolatile memory (NVM). The fault sets If the last write to nonvolatile memory was not successful or if the checksum of static NVM does not agree with the latest summation of that memory area. The DTC sets if the fault is set in the indicated time.	HWIO reports next write to NVM will not succeed OR HWIO reports the assembly calibration integrity check has failed	= True = True	Enable Calibration is True Controller Status	= 1 (1 is Enabled) = Initialization	Runs once at controller initialization	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module System Voltage Low	P1AE0	This diagnostic detects low voltage in the vehicle's 12 volt system. The fault sets when the THCP detects supply voltage below the indicated threshold for the indicated time.	Ignition Voltage	≤ 10.00 Volts	Enable Calibration is True AND 12V Starter Engaged AND Ignition Run/Crank Voltage AND Engine Speed (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1.00 (1 is Enabled) = False > 6.0 Volts ≥ 0.00 RPM = False = True	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module System Voltage High	P1AE1	This diagnostic detects high voltage in the vehicle's 12 volt system. The fault sets when the THCP detects supply voltage above the indicated threshold for the indicated time.	Ignition Voltage	≥ 16.00 Volts	Enable Calibration is True AND Ignition Run/Crank Voltage (Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= 1.00 (1 is Enabled) > 6.0 Volts = False = True	5 seconds out of a 6 seconds window	Type C, No SVS

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Hybrid Battery System Voltage High	P1AEF	This diagnostic monitors the total high voltage system voltage which is too high for the hardware. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage OR High Voltage Hardware Flag	> 450.00 Volts = True	Controller Initialization	Complete	0.01 seconds out of a 0.2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage System Isolation Fault	P1AF2	This diagnostic monitors the high voltage bus for possible shorts to chassis. The high voltage positive leg is compared to the high voltage negative leg via a ratio. If the ratio falls outside of a specific window for sufficient time, the diagnostic will fail.	Isolation Ratio (Neg mid-pack voltage / Pos mid-pack voltage)	> 4.53 OR < 0.21	No Active DTCs: Controller Initialization	P1AE8, P1AE9, P1AEC Complete	2.5 seconds out of a 5 seconds window (x of y)	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit Low	P1AF6	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Positive mid-pack voltage	< 20.00 Volts	Controller Initialization Run Crank Active Contactors	Complete True Closed	0.7375 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Isolation Sensor 1 Circuit High	P1AF7	This diagnostic monitors the high voltage bus positive leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	Pos mid-pack voltage - High Voltage sensor voltage	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.525 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit Loss of Tracking	P1B04	This diagnostic monitors the output from the resolver circuit on the high voltage motor. The circuit is continually calculating the position of the rotor in degrees. When the error between each sampling of position is greater than 5 degrees the circuit will output a status signal indicating a loss of tracking. If the loss of tracking status is present for a threshold amount of time, the diagnostic will fail.	Internal Tracking Error	>5 Degrees	Wakeup Signal Resolver Initialization Delay Once Resolver has indicated a fault, a Retry timer is initiated. Retry Timer must be	ON 1.00 > 0.05 s	Failure Conditions Met for 0.20 to 0.40 seconds out of a 2.00 second window	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Circuit Overspeed	P1B0E	This diagnostic monitors the output speed of the high voltage motor. The absolute value of the sensed speed of the motor is compared against a threshold. If the sensed speed is above the fail threshold for sufficient time, the diagnostic will fail.	ABS(Motor Speed)	> 12,700.00 rpm	Wakeup Signal	On	0.09 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Isolation Sensing Performance	P1B42	This diagnostic verifies that the high voltage bus positive and negative leg sensors are neither inappropriately high nor low. It compares the sensed battery pack voltage against the high voltage positive and negative leg. If the absolute value of the difference between the sensed battery voltage and the high voltage positive and negative leg sensors is greater than the failure threshold for a sufficient time, the diagnostic will fail.	ABS(Total High Voltage Measured By the Battery Pack - High Voltage Measured from Positive to Ground - High Voltage Measured from Negative to Ground)	$\geq 70.00 \text{ V}$	No Active DTCs: Controller Initialization Contactors	P1AE8, P1AE9, P1B0B, P1B0C Complete Closed	0.175 seconds out of a 0.2 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit Low	P1B43	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range low. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail	Negative mid-pack voltage	< 20.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.7375 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Isolation Sensor 2 Circuit High	P1B44	This diagnostic monitors the high voltage bus negative leg sensor voltage which is out of range high. The sensed voltage is subtracted from the total voltage. This delta is then compared against a threshold. If the delta is above the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Negative to Ground Reading - Total High Voltage Reading from High Voltage Battery	> 60.00 Volts	Controller Initialization Run/Crank Active Contactors	Complete True Closed	0.525 seconds out of a 1.05 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Torque Calculation Performance	P1E0B	<p>Fail Case 1, 5: This Diagnostic tests the calculation of output torque. Potential failures can include memory, software, processor and ALU faults. The primary calculated output torque value is compared to the secondary calculated output torque and if that difference is greater than the indicated threshold for the indicated time the fault is set.</p> <p>Fail Case 2 This diagnostic tests the calculation of output motor torque. Potential failures can include memory, software, processor and ALU faults. The fault is set if the difference in calculated output motor torque and the secondary output motor torque is greater than the indicated calibration. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 3, 4: This diagnostic tests the electronic current delivery circuits. The</p>	Absolute difference between Torque Achieved in primary and secondary path is greater than the threshold value	> 132.00 Nm	DriveStateID TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	Type A, 1 Trips
			Absolute difference between Torque Commanded in primary and secondary path is greater than the threshold value Abs(Primary - Secondary) OR Absolute difference between Mtr Minimum Short Term Torque Commanded in primary and secondary path is greater than the threshold value Abs(Primary - Secondary) OR Absolute difference between Mtr Maximum Short Term Torque Commanded in primary and secondary path is greater than the threshold value Abs(Primary - Secondary)	> 30.00 Nm > 132.00 Nm > 132.00 Nm	DriveStateID TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			Difference between Issd in primary and secondary path is greater than the threshold value	> 50.00 Amps	DriveStateID TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR	= Run = TRUE = FALSE	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		<p>fault is set if the difference in current delivered between the primary and secondary paths is greater than the shown threshold. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 6: This diagnostic tests the calculation of the back emf torque in the primary and secondary paths. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated back emf torque in the primary path is different from the secondary calculation path by more than the threshold given. The DTC is set if the fault is present for longer than the indicated time.</p> <p>Fail Case 7, 8, 9: This diagnostic compares different calculations of Usd and Usq in a primary and a secondary path. Potential failures can include memory, software, processor and ALU faults. The fault is set if the calculated differences</p>			TorqCalcPerf Flt counter OR TrqMntr Fault	<p>≠ 0</p> <p>= TRUE</p>		
			Absolute difference between Issq in primary and secondary path is greater than the threshold value	> 50.00 Amps	<p>DriveStatelD</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			Absolute difference between IssCmd Torque in primary and secondary path is greater than the threshold value	> 132.00 Nm	<p>DriveStatelD</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			Absolute difference between Back emf Torque in primary and secondary path is greater than the threshold value	> 0.015 Nm	<p>DriveStatelD</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	
			<p>Absolute difference between Usd Limited in primary and secondary path is greater than the threshold value</p> <p>OR</p> <p>Absolute difference between Usq Limited in primary and secondary</p>	<p>> 0.40 V (for Usd)</p> <p>> 0.40 V (for Usd)</p>	<p>DriveStatelD</p> <p>TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault</p>	<p>= Run</p> <p>= TRUE</p> <p>= FALSE</p> <p>≠ 0</p> <p>= TRUE</p>	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		are greater than the indicated thresholds. The DTC is set if either fault is present for longer than the indicated time. Fail Case 10: This diagnostic tests the primary and secondary input power paths for motor A. Potential failures can include the power input circuits, microprocessor memory, software and calibration, processor and ALU faults. The fault is set if the difference between primary and secondary input power are greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.	path is greater than the threshold value					
			UsdLmt Squared plus UsqLmt Squared OR DutyQ Squared plus DutyD Squared AND Duty Squared minus UsLmt Squared OR Perf Squared	> 0.70 > 0.70 > 0.30 > 1.00	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			Absolute difference of the Mod Index Square Calcluation for Usd and Usq for Volt Hz mode in primary and secondary paths	> 5.00 V	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
		Fail Case 11: This diagnostic tests the primary and secondary input voltage paths for motor A. Potential failures can include the power input circuits, microprocessor memory, software and calibration, processor and ALU faults. The fault is set if the difference between	Difference between Power Input in primary and secondary path is greater than or equal to the threshold value	>= 40,000.00 Watts	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			Difference between Vdc Adapt in primary and secondary path is greater than or equal to the threshold value	>= 0.07 Volts	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter	= Run = TRUE = FALSE ≠ 0	0.1875 seconds out of a 0.2 seconds window	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		primary and secondary voltage are greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time. Fail Case 12: This diagnostic tests the primary and secondary reactive power paths for motor A. Potential failures can include the reactive power input circuits, microprocessor memory, software and calibration, processor and ALU faults. The fault is set if the difference between primary and secondary reactive power is greater than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time. Fail Case 13: This diagnostic tests the primary and secondary resolver motor speed for motor A. The diagnostic tests the resolver circuits. The fault is set if the difference between primary and secondary motor speed is greater			OR TrqMntr Fault	= TRUE		
			Difference between Reactive Power (Qest) in the primary and secondary path is greater than or equal to the threshold value	>= 43,755.40 Watts	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			Calculated resolver Mtr Speed difference in the primary and secondary path is greater than the threshold value OR Calculated resolver Mtr Speed difference in the primary and secondary path is greater than the threshold value	> 20,000.00 rpm > 510.00 radians/sec	DriveStatelD TorqCalcPerf Flt Active OR TorqCalcPerf TPTKO OR TorqCalcPerf Flt counter OR TrqMntr Fault	= Run = TRUE = FALSE ≠ 0 = TRUE	0.1875 seconds out of a 0.2 seconds window	
			To Pass: Calculated resolver Mtr Speed AND Calculated Mtr Speed in radians/sec	< 19,000.00 rpm ≤ 146.00 rad				

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
		than the indicated threshold. The DTC is set if the fault is present for longer than the indicated time.						

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Long Term Memory Reset	P1EB7	This Diagnostic tests the NonVolatile Memory (NVM) in the MCP micro-controller for changes since the last write at power down. The bytes of various NVM sections are summed and compared to checksums for each section that were stored at the last powerdown. The DTC sets when the checksum comparisons do not match.	Static NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	Type A, 1 Trips
			Preserved NVM Checksum at power-up	≠ Checksum at power-down	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Power Up Reset	= False	Ignition Status	= Run or Crank	Runs once at controller initialization	
			BINVDM NVM Checksum at power-up	≠ Checksum at power-down	Enable Calibration is True	= 1 (1 is Enabled)	3 out of 5 controller initializations for Failure	
			Dynamic NVM checksum at power-up AND Shutdown Finished	≠ Checksum at power-down = TRUE	Ignition Status Enable Calibration is True	= Run or Crank = 1 (1 is Enabled)	1 failure Runs once at controller initialization	
			Static NVM Error Dynamic NVM Error BINVDM ECC Error	= False = False = False	Enable Calibration is True	= 1 (1 is Enabled)	Runs once at controller initialization	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Control Module B Lost Communication With Hybrid Powertrain Control Module B on Bus B	U182F	This diagnostic detects that the Hybrid Powertrain Control Module B has stopped sending messages on Bus B. If Hybrid Powertrain Control Module B message traffic is not received on Bus B by the MCPB controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$1D8</p> <p>Message \$3C5</p> <p>Message \$3D7</p>	<p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p> <p>≥ 0.5 seconds</p>	<p>General Enable Criteria:</p> <p>U0074</p> <p>Normal CAN transmission on Bus B</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p> <p>> 0.4000 seconds</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U182F Hybrid Powertrain Control Module B (VICM)	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor Control Module B Lost Communication With Hybrid Powertrain Control Module	U1846	This diagnostic detects that the Hybrid Powertrain Control Module has stopped sending messages on Bus A. If Hybrid Powertrain Control Module message traffic is not received on Bus A by the MCPb controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$1A5</p>	≥ 10.00 seconds	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					not active for U1846 Hybrid Powertrain Control Module	> 0.4000 seconds Not Active on Current Key Cycle is present on the bus		

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Lost Communicati on With Engine Control Module (ECM)/ Powertrain Control Module (PCM)	U1879	This diagnostic detects that the Engine Control Module (ECM/PCM) has stopped sending messages. If ECM/PCM message traffic is not received by the MCPB controller in the indicated time the DTC is set.	<p>Message is not received from controller for</p> <p>Message \$0C9</p> <p>Message \$1A3</p> <p>Message \$4C1</p> <p>Message \$4C7</p> <p>Message \$4F1</p>	<p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p> <p>≥ 10.00 seconds</p>	<p>General Enable Criteria:</p> <p>U0073</p> <p>Normal CAN transmission on Bus A</p> <p>Device Control</p> <p>High Voltage Virtual Network Management</p> <p>Ignition Voltage Criteria:</p> <p>Ignition voltage</p> <p>Power Mode</p> <p>Off Cycle Enable Criteria:</p> <p>KeCAND_b_OffKeyCycle DiagEnbl</p> <p>Ignition Accessory Line and Battery Voltage</p> <p>General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds</p> <p>Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for</p>	<p>Not Active on Current Key Cycle</p> <p>Enabled</p> <p>Not Active</p> <p>Not Active</p> <p>≥ 9.50</p> <p>= run</p> <p>= 1 (1 indicates enabled)</p> <p>= Active</p> <p>> 11.00</p> <p>> 0.4000 seconds</p>	<p>See Threshold Value</p> <p>Diagnostic runs in 12.5 ms loop</p>	Type B, 2 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					U1879 Hybrid Powertrain Control Module	Not Active on Current Key Cycle is present on the bus		

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply B Circuit Low	P06B4	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is below the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	< 12.00 V	Wakeup Signal	ON	0.34 seconds out of a 0.42 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Sensor Power Supply B Circuit High	P06B5	This diagnostic monitors the IGBT power supply circuit voltage. The sensed voltage is compared against a threshold. If the sensed voltage is above the failure threshold for sufficient time, the diagnostic will fail.	Scaled 15V IGBT Supply Voltage	> 22.00 V	Wakeup Signal	ON	0.34 seconds out of a 0.42 seconds window (x of y) OR Continuous Fail Time > 0.30 seconds	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U Current Low	P0A67	This diagnostic monitors the sensed current on the "U" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the U phase	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	RUN > 10.00 ms ≠ Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps^2	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase V Current Low	P0A6A	This diagnostic monitors the sensed current on the "V" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the V phase	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power Stage Inverter Voltage Rotor Position Squared Current Comanded	Run > 10.00 ms ≠ Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps ²	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase W Current Low	P0A6D	This diagnostic monitors the sensed current on the "W" phase of the electric motor for an open circuit. When the phase angle of the stator current vector nears its peak, the absolute value of the current is then compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	Peak Phase Axis Current on the W phase	< 9.00 Amps	Drive State Delay Timer Inverter State Inverter Power State Inverter Voltage Rotor Position Squared Current Comanded	Run > 10.00 ms ≠Active Discharge Normal PWM > 50.00 V -30 deg < Phase Axis < +30 deg > 4,900.00 Amps ²	0.4 seconds out of a 0.6 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Inverter Performance	P0A79	This diagnostic monitors the status of the IGBTs. The IGBT module will continually monitor the IGBTs for a short between the upper and lower phase. The module will then report out a status of being in a DeSat fault. If the DeSat fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C High or Low Side IGBT	DSatFltPending (Status Fault Bit)	Wakeup Signal	ON	0.002 seconds out of a 1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U Current Sensor Offset Out-of Range	P0BF2	This diagnostic monitors the offset that is learned by the phase "U" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	U phase offset current learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail conditions met 0.10 sec after enable conditions met	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U Current Sensor Circuit Low	P0BF3	This diagnostic monitors for the "U" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed current is below the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U Current Sensor Circuit High	P0BF4	This diagnostic monitors for the "U" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	U phase current sensor output highside	> 700.00 amps	Wakeup Signal Enable Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase V Current Sensor Offset Out-of Range	P0BF6	This diagnostic monitors the offset that is learned by the phase "V" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	V phase current sensor offset learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fai conditions met 0.10 Sec after enable conditions met	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase V Current Sensor Circuit Low	P0BF7	This diagnostic monitors for the "V" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	V phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase V Current Sensor Circuit High	P0BF8	This diagnostic monitors for the "V" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	V phase current Sensor output at highside	> 700.00	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase W Current Sensor Offset Out-of Range	P0BFA	This diagnostic monitors the offset that is learned by the phase "W" current sensor on the high voltage electric motor. In order to ensure accurate current measurement an offset is calculated when there is no current going through the motor. The offset learn process is conducted on every key crank, the learned offset is then compared against a threshold, if the offset value is larger than the fail threshold the diagnostic will fail.	W phase current sensor offset learn value	> 30.00 amps	Wakeup Signal Delay Timer Motor Faults Inverter Faults	On 0.10 Sec None None	Fail condititions met 0.10 sec after enable conditoins met	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase W Current Sensor Circuit Low	P0BFB	This diagnostic monitors for the "W" phase current sensor voltage which is out of range low. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed temperature is below the failure threshold for sufficient time, the diagnostic will fail.	W phase current sensor output at highside	< -700.00 amps	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase W Current Sensor Circuit High	P0BFC	This diagnostic monitors for the "W" phase current sensor voltage which is out of range high. After the sensor output voltage is converted, the sensed current is compared against a threshold. If the sensed temperature is above the failure threshold for sufficient time, the diagnostic will fail.	W phase current sensor output at high side	> 700.00	Wakeup Signal Run Flag	On = 1.00	0.05 seconds out of a 0.1 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U- V-W Correlation	P0BFE	This diagnostic monitors the U, V, and W phase currents for balance. The absolute value of the sum of the phase values is compared against a threshold. If the sum is above the failure threshold for sufficient time, the diagnostic will fail.	Sum of U-V-W phase currents	≥ 110.00 amps	Wakeup Signal Run Flag	On = 1.00	0.0032 seconds out of a 0.0038 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor "B" Phase U- V-W Current Sensor Overcurrent	P0C04	This diagnostic monitors the sensed current on all three phases of the electric motor. The absolute value of the highest current phase value is then compared against a threshold. If the value is above the failure threshold for sufficient time, the diagnostic will fail. This diagnostic implements the use of 2 different fail timers, one fast and one slow. The fast timer has a very short sample window so that the diagnostic will detect a sudden fault, the slower timer has a longer sample window to allow the diagnostic to detect an intermittent fault.	U, V, or W Phase Current Sensor	> 600.00 amps	Wakeup Signal	On	0.0104 seconds out of a 0.104 seconds window (x of y) OR 0.00416 seconds out of a 0.0208 seconds window (x of y)	Type A, 1 Trips
			D Axis current less than calculated threshold determined by stator temperature listed in supporting table unless the motor temperature reading is faulted, then D Axis current threshold is determined by a default value	D-Axis Current<- 600.00 amps (faulted motor temp value) P0C04 D-Axis Current Thresholds (See supporting tables for expected threshold values for non-faulted motor temperature readings)	Wakeup Signal	On	0.0104 seconds out of a 0.104 seconds window (x of y) OR 0.00416 seconds out of a 0.0208 seconds window (x of y)	

18 OBDG01 MCP2 - Common Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Inverter Power Supply Circuit/Open	P0C0E	This diagnostic monitors the status of the IGBTs. The IGBT module will continuously monitor the supply circuit voltage. When the supply circuit drops below a threshold voltage the module then report out a status of being in a Bias fault. If the Bias fault status is present for sufficient time, the diagnostic will fail.	Phase A, B, or C Power Supply	Failed (Status Fault Bit)	Inverter State	Initialization Complete	0.002 seconds out of a 0.024 seconds window (x of y)	Type A, 1 Trips

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Control Module Serial Peripheral Interface Bus 2	P16E9	This diagnostic checks that the SPI communication between the Transmission & Hybrid Control Processor (HMCP) and MCP is working correctly. Potential failures could be in the microprocessor's SPI handling, the transmission line or the microprocessors ability to execute code. The DTC sets if the messages are missing, the counter is not updated, or the SPI handler detects an incorrect checksum in the time indicated.	CRC error on receive Number of missing messages OR Alive Rolling Count (ARC) incremented from previous value (0-3)	=True ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	Type A, 1 Trips
			HWIO Received Errors AND Receiving Data in Progress	≠ 0 ≠ True	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete) OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False = True = False > 11.00 V ≥ 9.50 V > 11.00 V	0.175 seconds out of a 0.2 seconds window	
			Number of Missing Received Messages	> 4 messages	(Diagnostic System Code Clear Requested AND Diagnostic System Reset Complete)	= False = True	0.175 seconds out of a 0.2 seconds window	

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					OR CAN communication Disabled OR Run Crank In Range Voltage AND Run Crank In Range Security Voltage AND 12V Battery Voltage	= False > 11.00 V >= 9.50 V > 11.00 V		

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Sense Circuit Low Voltage	P1AEA	This diagnostic monitors the total high voltage sense circuit for low voltage. If the total high voltage sense is below the failure threshold for sufficient time, the diagnostic will fail.	High Voltage Sensor Voltage	< 30.00 volts	Controller Initialization Run/CrankActive Contactors	Complete True Closed	Failure Conditions met for 1.5 seconds out of a 2 seconds window	Type A, 1 Trips

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery Voltage Sense Circuit High Voltage	P1AEB	This diagnostic monitors the total high voltage sense circuit for high voltage. If the total high voltage sense is above the failure threshold for sufficient time, the diagnostic will fail.Circuit High monitor of HV output voltage sensor	High Voltage Sensor Voltage	> 575.00 volts	Controller Initialization Run/CrankActive	Complete True	Failure Conditoins met for 1.5 seconds out of a 2 seconds window	Type A, 1 Trips

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Hybrid Battery System Voltage	P1AED	This diagnostic checks correlation of total high voltage with the sum of mid-pack voltages and high voltage read by the HV Battery. If the difference is greater than a failure threshold for sufficient time the diagnostic will fail.	ABS(High Voltage Sensor - High Voltage Battery Voltage)	>= 40.00 volts	No Active DTCs:	P1AE8, P1AE9	Failure conditions met for 0.175 seconds out of a 0.2 seconds window	Type B, 2 Trips
			OR		Controller Initialization	Complete		
			ABS(High Voltage Battery Voltage - sum of mid-pack voltages)	>= 50.00 volts	Contactors	Closed		

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Position Sensor Learn Incorrect	P1B10	This diagnostic monitors the offset that is learned by the resolver circuit. The diagnostic runs on every key off cycle while the offset learn process is in progress. The offset learn process can fail when during the learn process either the motor speed is higher than a threshold, the total high voltage bus is below a threshold voltage, the peak to peak current on the motor falls below a threshold, or the learn process takes longer than a threshold time. If the learn process fails for any one of the aforementioned reasons a counter is increased and compared against a threshold. If the counter exceeds the threshold the diagnostic will fail.	Offset Learn Could Not Complete Because:		Key Off	TRUE	15.00 consecutive key cycles with a 0.30 s Learn Time	Type B, 2 Trips
			ABS(Motor Speed)	> 50.00 rpm				
			Consecutive Key Cycles where the offset learn is unable to complete	> 15.00 cycles				
			Initial Offset Learn Could Not Complete Because:		Key Off	TRUE	15.00 consecutive key cycles with a 0.30 s Learn Time	
			Filtered DC	< 200.00 V				
			Consecutive Key Cycles where the offset learn is unable to complete	> 15.00 cycles				
			Initial Offset Learn Could Not Complete Because:		Key Off	TRUE	15.00 consecutive key cycles with a 0.30 s Learn Time	
			ALL phase Current	< 20.00 A				
			Consecutive Key Cycles where the offset learn is unable to complete	> 15.00 cycles				
			Initial Offset Learn Could Not Complete Because:		Key Off	TRUE	15.00 consecutive key cycles with a 0.30 s Learn Time	
			Learn Timer	> 1.40 s				
			Consecutive Key Cycles where the offset learn is unable to complete	> 15.00 cycles				

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
Drive Motor B Control Module Lost Communicati on With Transmissio n Control Module (TCM)	U1850	This diagnostic detects that the Transmission Control Module has stopped sending messages. If Transmission Control Module message traffic is not received by the MCPB controller in the indicated time the DTC is set.	Message is not received from controller for Message \$1F5	 ≥ 10.00 seconds	<u>General Enable Criteria:</u> U0073 Normal CAN transmission on Bus A Device Control High Voltage Virtual Network Management <u>Ignition Voltage Criteria:</u> Ignition voltage Power Mode <u>Off Cycle Enable Criteria:</u> KeCAND_b_OffKeyCycle DiagEnbl Ignition Accessory Line Battery Voltage General Enable Criteria and either Ignition Voltage Criteria or Off Cycle Enable Criteria met for > 3.0000 seconds Power Mode is in accessory or run or crank and High Voltage Virtual Network Management is not active for U1850	Not Active on Current Key Cycle Enabled Not Active Not Active ≥ 10 = run = 0 (1 indicates enabled) = Active > 11 Not Active on Current Key Cycle	See Threshold Value Diagnostic runs in 12.5 ms loop	Type B, 2 Trips

18 OBDG01 MCP2 - CT6 Unique Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL Illum.
					Transmission Control Module	is present on the bus		

18 OBDG01 MCP2 Supporting Tables

Initial Supporting table - P0C04 D-Axis Current Thresholds

Description: X-Axis is stator temperature, Y-Axis is current threshold for the D-Axis current

y/x	100	140	150	160	170	180	190	200	210	220
1	-804	-676	-565	-517	-517	-517	-517	-517	-517	-517

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
ABS Front Hydraulic Circuit Leak Detected	C05B0	This monitoring checks if the front brake circuit has a leak by comparing the wheels dynamics with the vehicle deceleration.1. A fault is set if wheels dynamics do not match the vehicle deceleration.	The wheels dynamics are not matching the vehicle deceleration	= True	Ignition key AND Antilock brake system OR EBD Braking	= On = Active = Active	1 [Sec]	Type A, 1 Trip
		This monitoring checks for a brake circuit failure at the front axle. A fault is set if the master cylinder pressure is higher than the rear axle pressure.	Pressure of Master cylinder	> Pressure of rear axle	Ignition key AND Pressure at front axle Maintain the brake pedal at a constant force	= On > 5000 Kpa = 3 Sec	0.2 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition On and apply brake pedal with a pressure at front axle higher than 5000 kpa. Maintain the brake pedal with a constant force for 3 seconds and release.					
ABS Pump Motor Calibration Not Learned	C05AE	This monitoring strategy checks if there is a 0V calibration at Sigma Delta Modulator (SDM).The motor measuring units through a SDM require a 0V calibration. The measured SDM 0V calibration values are compared. A fault is set if the measured voltages are outside of a calibrated range.	Raw generator voltage Ugen OR Raw generator voltage Ugen AND Raw voltage drops at hydraulic pump motor relay URdsON OR Raw voltage drops at hydraulic pump motor relay URdsON	< 14 V > 23.8 V < 13 V > 18 V	Ignition key AND System voltage AND Hydraulic pump motor	= On > 6.9 V = Off	3 [Sec]	Type A, 1 Trip
		This monitoring verifies the supply voltage of the return flow pump. A supply undervoltage fault is set if the voltage of the pump motor shunt resistor is below a calibrated threshold or if the voltage of the Motor relay drain voltage is above a calibrated range, which is depending on the system voltage.	Voltage of motor shunt resistor OR Motor relay drain voltage OR Motor relay drain voltage	< 7.5 V > 3 V < 1.5 V	Ignition key AND System voltage AND Hydraulic pump motor	= On > 6.9 V = Off	2 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 18.6 mph and hold the speed for at least 20s					
ABS Pump Motor Control Circuit High	C052D	This monitoring strategy checks if there is a motor interruption or a motor relay short-circuit failure outside a motor actuation. The state of the pump motor is monitored. A fault is set if the motor voltage exceeds a calibrated threshold.	Hydraulic pump motor supply voltage	> 12 V	Hydraulic pump motor	= Off	1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
ABS Pump Motor Performance	C052B	This monitoring strategy checks if the return pump is weak due to a heavy load. A fault is set if the calculated generator voltage is over a calibrated threshold and the measured generator voltage is below the same threshold.	Calculated generator voltage AND Measured generator voltage	> 0.6 V < 0.6 V	System voltage AND Hydraulic pump motor AND Electronic Brake Control Unit state	> 6.9 V = On = Started with hardware reset	0.48 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks the functionality of the hydraulic pump motor path. A fault is set if the voltage drop over the motor relay stays below a calibrated threshold when the motor relay (MR) is switched on.	Voltage drops at hydraulic pump motor relay AND Motor relay switched on	< 2 V = True	System voltage AND Vehicle speed AND Hydraulic pump motor	> 6.9 V > 9.32 mph = Off	5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the hydraulic pump motor can be actuated and if the generated motor voltage is visible to the microcontroller. The pump motor is actuated, and both the analog and digital feedback voltage signals are monitored. A fault is set if the analog or digital pump motor voltage is below a calibrated threshold.	Analog pump motor voltage OR Digital pump motor voltage	< 1.7 V < 1.7 V	Ignition key	= On	5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the motor voltage is incorrect. The Motor Voltage Comparison Test triggers a predetermined number of measurements in normal mode to give the motor voltage comparison monitor the chance to detect failures. To do this, it switches the motor voltage to UBMR (Battery Motor Relay) voltage and compares the analog UBMR voltage read in by the Analog Digital Converter (ADC) with the digital UBMR voltage calculated by the Application Specific Integrated Circuit (ASIC) while the hydraulic pump is not active. A fault is set if the deviation between the UBMR voltage read by the ADC (analog) and the UBMR voltage calculated by the ASIC (digital) exceeds a calibrated threshold.	Motor relay supply line voltage read by ADC (analog) / Motor relay supply line voltage calculated by ASIC (digital)	> 0.25	Ignition key AND Hydraulic pump motor	= On = On	2 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking. Accelerate vehicle to at least 37.3 mph and hold the speed for at least 7s					
ABS Pump Motor Supply Circuit	C052F	This monitoring strategy checks if an interruption of the motor relay voltage supply line has occurred. This can be caused by a defective fuse, a bad or broken car wire harness, or even by very deep undervoltage at the motor relay voltage supply line. A fault is set if the supply line voltage (UBMR) drops below a calibrated threshold.	Motor relay supply voltage	< 1.955 V	Ignition key	= On	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
ABS Pump Motor Supply Voltage "A" Circuit Low	C055B	This monitoring strategy checks if there is a possible inline resistor or undervoltage situation in the motor relay supplier. This is a check to ensure that the Application Specific Integrated Circuit (ASIC) register bit is set whenever there is an MRDSupplyFailure and is not reset throughout the ignition cycle, even if the voltage is recovered. A fault is set if during return flow pump actuation, the motor relay battery voltage drops below a calibrated threshold.	Motor relay voltage / internal supply voltage	< 0.4	Hydraulic pump motor AND Ignition key AND Vehicle speed	= On = On > 23.6 mph	0.01 [Sec]	Special Type C
		This monitoring strategy checks if there are failures on the motor supply line (for example: interruptions of UBMR). An Application Specific Integrated Circuit (ASIC) compares the voltage at UBMR with an internal dependent threshold provided by the hardware. A fault is set if the motor relay supply voltage is below a calibrated threshold.	Motor relay voltage / internal supply voltage	< 0.4	Ignition key	= On	0.2 [Sec]	Special Type C
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5 Sec					
ABS Rear Hydraulic Circuit Leak Detected	C05B1	This monitoring checks if there is a leakage on the rear axle brake circuit.	Calculated leakage based on rear axle pressure sensor AND For a defined number of times	> 0.6 ml/Sec ≥ 3	System voltage AND Actual pressure at rear axle AND Actual pressure at rear axle AND Absolute value of target pressure gradient AND Vehicle Standstill is detected AND Rear axle is in by-wire mode AND (APB State OR APB State)	> 9.6 V > 1000 kPa < 10000 kPa ≤ 200 kPa/sec = True = True = Not initialized = Brake Released	0.15 [Sec]	Type A, 1 Trip
		This monitoring checks for a brake circuit failure at the rear axle. A fault is set if the master cylinder pressure is lower than the rear axle pressure.	Pressure of Master cylinder	< Pressure of rear axle	Ignition key AND Pressure at front axle Maintain the brake pedal at a constant force	= On > 5000 KPa = 3 Sec	0.2 [Sec]	Type A, 1 Trip
		DTC Pass	Turn on ignition. Constant brake pedal application during standstill for at least 3 sec. Check that the brake lights are illuminated or pressure at master cylinder > 500kpa. Release the brake pedal. Wait 5s. Constant brake pedal application during standstill for at least 3 sec. Check that the brake lights are illuminated or pressure at master cylinder > 500kpa. Release the brake pedal.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Brake Assist Information 1 Message Counter Incorrect	C1284	This monitoring strategy checks whether the message is still alive or not. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a counter is incremented within the sending ECU. the counter value is enclosed within the message. The receiving control unit checks whether counters have been incremented. A fault is set if the counter value is not incremented.	Message 0x214 on Bus E counter halted	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the message checksum is correct. The network driver sends and receives all network messages. It also checks if the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a checksum is calculated within the sending ECU. The value of the checksum is enclosed within the message. The receiving control unit calculates the checksum again and compares it with the sent one. A fault is set if the received checksum is different from the calculated checksum.	Checksum of 0x214 on Bus E not correct	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
Brake Assist Information 2 Message Counter Incorrect	C1285	This monitoring strategy checks whether the message is still alive or not. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a counter is incremented within the sending ECU. the counter value is enclosed within the message. The receiving control unit checks whether counters have been incremented. A fault is set if the counter value is not incremented.	Message 0x219 on Bus E counter halted	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the message checksum is correct. The network driver sends and receives all network messages. It also checks if the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a checksum is calculated within the sending ECU. The value of the checksum is enclosed within the message. The receiving control unit calculates the checksum again and compares it with the sent one. A fault is set if the received checksum is different from the calculated checksum.	Checksum of 0x219 on Bus E not correct	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
Brake Blending System Performance	C05AD	This monitoring checks if the vehicle is overbraked, because the actual pressure is much higher than the target pressure in the by-wire circuit.	Actual pressure at rear axle – Target pressure	> threshold curve starting from 1500 kPa to 5000 kPa	Ignition state AND Rear axle target pressure AND Rear axle target pressure signal is valid AND (pressure sensor offset is finished OR valve calibration routine is finished) AND ABS intervention is not active AND Rear axle is in by-wire mode AND (APB State OR APB State)	= On < 9500 kPa = TRUE = TRUE = TRUE = TRUE = TRUE = Not Initialized = Brake Released	0.5 - 1.07 [Sec]	Type A, 1 Trip
		This monitoring checks if the vehicle is underbraked, because the actual pressure is much lower than the target pressure in the by-wire circuit.	Target pressure - Actual pressure at rear axle	> maximum value out of (threshold curve starting from 1500 kPa to 5000 kPa OR 20% of target pressure)	Ignition state AND Rear axle target pressure signal is valid AND (pressure sensor offset is finished OR valve calibration routine is finished) AND ABS intervention is not active AND Rear axle is in by-wire mode AND (APB State OR APB State)	= On = TRUE = TRUE = TRUE = TRUE = TRUE = Not Initialized = Brake Released	0.5 - 1.07 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
			Target pressure - Actual pressure at rear axle	> 800 kPa	Ignition state AND (Target Pressure Gradient AND Target Pressure AND Target Pressure AND For time) AND Rear axle target pressure signal is valid AND (pressure sensor offset is finished OR valve calibration routine is finished) AND ABS intervention is not active AND Rear axle is in by-wire mode AND (APB State OR APB State)	= On < 1000 kPa/s > 400 kPa < 2000 kPa > 1 s = TRUE = TRUE = TRUE = TRUE = Not Initialized = Brake Released	1.07 [sec]	Type A, 1 Trip
		This monitoring checks if the vehicle is overbraked, because the actual master cylinder pressure is much higher than the target pressure or if the master cylinder pressure is much higher than the Rear axle pressure.	Actual Master Cylinder pressure – Target pressure	> threshold curve starting from 1500 kPa to 5000 kPa	Ignition state AND Master cylinder pressure signal is valid AND Rear axle is not in by-wire mode AND Regenerative braking is active AND VolumeShiftBack is not active AND (APB State OR APB State)	= On = TRUE = TRUE = TRUE = TRUE = Not Initialized = Brake Released	0.7 - 1.07 [sec]	Type A, 1 Trip
			Master Cylinder pressure – Rear axle pressure	> threshold curve starting from 1000 kPa to 1800 kPa	Ignition state AND Master cylinder pressure signal is valid AND Rear axle pressure signal is valid AND Rear axle is not in by-wire mode AND Regenerative braking is active AND VolumeShiftBack is not active AND (APB State OR APB State)	= On = TRUE = TRUE = TRUE = TRUE = Not Initialized = Brake Released	1 [sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring checks if the vehicle is underbraked, because the actual pressure at master cylinder is much lower than the target pressure.	Target pressure - Actual Master Cylinder pressure	> maximum value out of (threshold curve starting from 1500 kPa to 5000 kPa OR 20% of target pressure)	Ignition state AND Master cylinder pressure signal is valid AND Rear axle is not in by-wire mode AND Regenerative braking is active AND VolumeShiftBack is not active AND (APB State OR	= On = TRUE = TRUE = TRUE = TRUE = Not Initialized	0.7 - 1.7 [sec]	Type A, 1 Trip
		DTC Pass	Turn on ignition, 1. Wait 5seconds, 2. Drive up to 24.8 mph, 3. Realize a comfortable braking (about 3000 kpa at the rear axle), 4. Hold for 2 seconds and release smooth the brake pedal, 5. Wait 2seconds. Then repeat step 2 to 5 once again.					
Brake Master Cylinder Pressure Sensor 1 Circuit High Voltage	C0572	This monitoring checks if there is a short circuit between the supply voltage line and the pressure sensor signal line by comparing the signal line with the supply voltage line. Normally, the signal line maximum voltage should be lower than the supply voltage. A fault is set, if there is no difference in voltage between the signal line and the supply line.	Signal line voltage / Supply line voltage AND Signal line voltage / Supply line voltage	> 0.95 < 1.05	Ignition key	= On	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Brake Master Cylinder Pressure Sensor 1 Circuit Low Voltage	C0571	This monitoring checks if there is a short circuit between the ground and the pressure sensor signal line by comparing the signal line voltage with the ground. Normally, the signal line has a minimum voltage that is higher than the ground. A fault is set if there is no difference in voltage between the signal line and the ground.	Signal line voltage / Ground voltage AND Signal line voltage / Ground voltage	> 0.95 < 1.05	Ignition key	= On	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Brake Master Cylinder Pressure Sensor 1 Circuit Performance	C0574	This monitoring strategy checks if the offset compensation of the pressure sensor is out of range. The zero-point of the pressure sensor signal is adjusted to compensate for any signal drifts. The offset compensation is only performed when the brake pedal is not applied (corresponding to the pressure sensor zero point). A fault is set if the offset is outside a calibrated range.	Measured pressure OR Measured pressure	> 1500 KPa < -1500 KPa	System voltage AND Brake pedal is pushed AND Acceleration pedal is pushed AND Hydraulic pump motor And Vehicle speed	> 6.9 V = False = True = Off > 4.48 mph	Immediately	Type A, 1 Trip
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5s					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Brake Pressure Sensor "A" Missing Calibration	C0560	This monitoring strategy checks if the pressure sensor at the master cylinder is functioning as expected. A fault is set if the master cylinder pressure sensor test pulse voltage exceeds a calibrated threshold or if it falls below another calibrated threshold.	Master cylinder pressure sensor test pulse voltage OR Master cylinder pressure sensor test pulse voltage	> 110 % < 90 %	Vehicle acceleration AND Actual pressure of Master Cylinder AND Traction Control System AND Vehicle speed AND Anti-Lock Braking System intervention AND Vehicle Dynamics Control AND Hydraulic pump motor	= False < 150 KPa = Off < 9.32 mph = Off = Off = Off	Immediately	Type A, 1 Trip
		DTC Pass	Drive with more than 6.2 mph for more than 60 Sec. without pressing brake pedal and no					
Brake Pressure Sensor "B" Missing Calibration	C059B	This monitoring strategy checks if the rear left pressure sensor is functioning as expected. A fault is set if the master cylinder pressure sensor test pulse voltage exceeds a calibrated threshold. A fault is also set if the test pulse voltage falls below a calibrated threshold.	Rear left pressure sensor testpulse voltage OR Rear left pressure sensor testpulse voltage	> 110 % < 90 %	System Software Offset compensation of pressure sensor completed AND Actual pressure of Master Cylinder AND Traction Control System AND Anti-Lock Braking System intervention AND Vehicle Dynamics Control AND Hydraulic pump motor AND Brake light switch AND Last test pulse AND Vehicle speed OR Throttle control is pushed	= At least once < 150 kPa = Off = Off = Off = Off = Off > 30 Sec < 9.32 mph = True	Immediately	Type A, 1 Trip
		DTC Pass	Drive with more than 6.2 mph for more than 60 Sec. without pressing brake pedal and no stability control active.					
Brake Pressure Sensor / Brake Pedal Position Sensor Correlation	P05FF	This monitoring checks for hydraulic circuit failures. It will check if there is a leakage or a large amount of air in the hydraulic circuit. A fault is set if the pressure sensor value stay at zero while the pedal Travel sensor value is over a threshold. This monitoring checks a pressure sensor plausibility failure. A fault is set if the pressure sensor value is too high compared to the pedal travel sensor value.	PTS signal AND Pressure signal PTS signal AND Pressure signal	> 24 mm = 0 KPa = 0 mm > 25 KPa	Full system mode Full system mode	= On = On	0.2 [Sec] 0.2 [Sec]	Type A, 1 Trip Type A, 1 Trip
		DTC Pass	The brake pedal has to be pressed for more than 1 second (the pressure should reach minimum 3000 kpa).					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Control Module Communication Chassis Expansion CAN Bus Off - Generic	U0077	The CAN (Control Area Network) bus E state is monitored periodically. A fault is set if the bus is in "Bus Off" state.	CAN bus E state	= Bus off	System voltage AND System voltage ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = True ≥ 5 Sec	0.09 [Sec]	Type A, 1 Trip
		This monitoring checks the CAN initialization function has taken too long to finish. The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Ignition key	= On	0.01 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
Control Module Communication High Speed CAN Bus Off - Generic	U0073	The CAN (Control Area Network) bus A state is monitored periodically. A fault is set if the bus is in "Bus Off" state.	CAN bus A state	= Bus off	System voltage AND System voltage ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = True ≥ 5 Sec	0.24 [Sec]	Type A, 1 Trip
		This monitoring checks the CAN initialization function has taken too long to finish. The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Ignition key	= On	0.01 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
Control Module Internal Performance	P0606	This monitoring strategy checks for proper the CPU Compare Module functionality. The software is executed on 2 CPU cores simultaneously instruction by instruction (lock step mode). The output of both cores is compared by the CPU Compare Module. A self test runs at Init to verify the CPU Compare Module is working properly. A fault is set if the self test failed.	Core Compare Module selftest	= failed	System voltage	> 6.9 V	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a Central Processing Unit (CPU) exception. If a CPU exception occurs, normal program execution is no longer allowed (e.g. aborts from privileged modes). A fault is set if a data abortion, a prefetch abortion, or an undefined instruction occurs.	Data abortion occurs OR Prefetch abortion occurs OR Undefined instruction occurs	= True = True = True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the execution of a sensitive process task jitters too much. A fault is set if the real process execution time is greater than its ideal start time increased by a percentage.	The execution time of the internal system process task (non ibooster systems)	> Process Ideal Time + 5% Sec	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring checks the TPSW customer function accessibility area into the RAM. A fault is set if any customer SW variable or function tries to access outside its restricted area.	SW variable or function tries to access outside its restricted area	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the A/D converter reference voltage is out of range. A fault is set if the ADC band gap voltage is outside the allowable range.	Analog Digital Converter voltage OR Analog Digital Converter voltage	< 1.145 V > 1.345 V	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the ECU internal electrical enable line cannot be switched on or off via the software. The electrical enable line is set directly by a microcontroller pin. When the microcontroller port changes, the enable line may take the value set by the microcontroller. If the enable line does not change this means that the ECU enable line has shorted to the ground or to the supply voltage line (3.3V). A fault is set if the ECU internal electrical enable line value is different than the value requested from the software.	The ECU internal electrical enable line cannot be switched ON or OFF by the software	= True	System voltage AND Fail-Safe Logic Test	> 6.9 V = On	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the ECU (Electronic Control Unit) internal hydraulic enable line. A fault is set if the ECU internal electrical enable line either is shorted to ground, is shorted to the supply voltage, or cannot be switched ON or OFF by the software.	ECU internal hydraulic enable line has a short to ground OR ECU internal hydraulic enable line has a short to supply voltage (3.3V) OR The ECU internal hydraulic enable line cannot be switched ON or OFF by the software	= True = True = True	System voltage	> 6.9 V	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the enable line is set properly. After the Fail-Safe Logic Test has finished the ECU (Electronic Control Unit) internal hydraulic and electrical enable lines are monitored. It is expected that the enable lines always stay at a high level. A fault is set if an interruption (an enable line at low level) of the hydraulic or electrical enable line is detected.	ECU internal hydraulic line state For time OR ECU internal electrical line state For time	= low > 0.05 Sec = low > 0.05 Sec	System voltage	> 6.9 V	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the error pin event counter is in range. The monitor pulls the error pin to test the event counter within the system chip. To prevent an electrical shutdown (which would disturb communication) during the provoked error pin event, the electrical decouple bit is set. A fault is set if the error pin event counter does not increment, or if the decouple bit is not reset.	Error pin event counter not incremented	= True	Ignition key	= On	1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a HET exception. A fault is set if a failure is detected in the EEPROM (Electrically Erasable Programmable Read-Only Memory) cell.	Failure detected in register HET	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks for proper of the High End Timer Transfer Unit (HETTU) addressing functionality. When a pointer error is detected, the HETTU state switches to a specific value. A fault is set if the HETTU is in the pointer error state.	High End Timer Transfer Unit Status	= "pointer error"	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks the High End Timer Transfer Unit (HETTU) internal bus. A fault is set if a bus error is detected.	High End Timer Transfer Unit Status	= "bus error"	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks the High End Timer Transfer Unit (HETTU) internal bus. A fault is set if a busy bit error is detected.	High End Timer Transfer Unit Status	= "busy bit error"	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if there was a High End Timer Transfer Unit (HETTU) exception. A fault is set if an exception occurs.	Failure detected in register INT	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks whether any tasks failed to call. A fault is set if a task did not start in the expected time.	Watchdog detects a missing task	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks the feedback of the Fail-Safe Logic Test. The Fail-Safe Logic Test tests whether the system chip switches off the gate actuation of the Booster Master Switch when it detects a missing watchdog trigger. A fault is set if the feedback shows that the valve relay gate is not switched off.	Missing watchdog trigger AND No switched off valve relay gate	= True = True	System voltage	> 6.9 V	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve relay gate actuation is properly switched off via a Serial Peripheral Interface (SPI) command during the Fail-Safe Logic Test. A fault is set if the feedback shows that the valve relay gate is not switched off.	No switch off of the valve relay gate actuation via SPI	= True	System voltage	> 6.9 V	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the watchdog fault counter of the system integrated circuit. A fault is set if the value of this error counter exceeds a threshold.	Error counter	> 3	System voltage AND	> 6.9 V	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the watchdog trigger is received as expected. An incorrect watchdog trigger signal is sent to the system chip watchdog function which increments the watchdog error counter. A fault is set if the watchdog fault counter is not incremented.	Incorrect watchdog data sent to chip	= True	System voltage	> 6.9 V	1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the watchdog trigger is received within a certain time by the system chip. A fault is set if not all watchdog tasks are executed within a certain period of time.	Number of watchdog tasks done	< Number of watchdog tasks	System voltage	> 6.9 V	1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the status of the watchdog. During the initialization test the watchdog status feedback from the system chip is tested against several patterns according to the ongoing sub test. A fault is set if the watchdog status is not as expected.	Watchdog status	≠ expected watchdog status	System voltage	> 6.9 V	1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the status of the watchdog. After the initialization test has finished, the status of the watchdog is continuously monitored. A fault is set if the watchdog status is not as expected.	Watchdog status	≠ expected watchdog status	System voltage	> 6.9 V	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for correct NMI handling. The Error Signal Module is the central module at the microcontroller level; it handles severe microcontroller core failures and peripheral failures, and coordinates the logic tests during start-up. A fault is set if the Non-Maskable Interrupt handler detects a failure during initialization tests.	Non-maskable Interrupt is detected	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if a severe microcontroller core or peripheral failure has occurred. The Error Signal Module (ESM) is the central module at the microcontroller level; it handles severe microcontroller core and peripheral failures. A fault is set when a severe microcontroller core or peripheral failure is detected.	A microcontroller core failure via Error Signal Module is detected OR Peripheral failure via ESM is detected	= True = True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks whether the HET has the proper reference signal frequency. The monitor compares the defined frequency with the actual reference signal frequency, which is calculated by the HET. A fault is set if the difference between the defined frequency and the actual frequency exceeds a threshold.	Absolute(Defined frequency - calculated frequency) / defined frequency	> 0.05	Ignition key	= On	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		<p>This monitoring strategy checks the Serial Peripheral Interface (SPI) functionalities and failures handling of the Application Specific Integrated Circuit (ASIC) used in the system. To do so, the SPI component provides special functions to perform the following tests :</p> <ul style="list-style-type: none"> - reading from/writing to an undefined address EEPROM (Electronically Erasable Programmable Read-Only Memory) cell - writing to a non-writable EEPROM cell - reading a EEPROM cell with a parity failure during transmission - reading a EEPROM cell with a clock failure during transmission <p>For each of these tests, a certain fault response is expected from the ASIC. A fault is set if at least one fault response is not as expected.</p>	<p>No or wrong error response from ASIC while reading from an undefined address register OR No or wrong error response from ASIC while writing to an undefined address register OR No or wrong error response from ASIC while writing to a non-writable register OR No or wrong error response from ASIC while reading a register with a parity error in frame 1 during transmission OR No or wrong error response from ASIC while reading a register with a parity error in frame 2 during transmission OR No or wrong error response from ASIC while reading a register with a clock failure (less clock pulses) during transmission OR No or wrong error response from ASIC while reading a register with a clock failure (more clock pulses) during transmission</p>	<p>= True = True = True = True = True = True = True</p>	System voltage	> 6.9 V	immediately	Type A, 1 Trip
		<p>The monitoring checks the received data by the Application Specific Integrated Circuit (ASIC). The ASIC of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). A fault is set if not all data has been transmitted or received.</p> <p>Parity check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if the calculated parity does not match the parity bit.</p> <p>Bit check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if at least one bit of the actual transmitted data is not equal to the transmit bit in register.</p> <p>Rationality check - The ASICs of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). When ASIC detects a transmission failure, it sends an error frame via the SPI. The monitoring checks the frames transmitted via the SPI. A fault is set if an error frame is transmitted.</p>	<p>Length of received data OR Calculated parity of the received data OR Time out error OR Actual transmitted bits OR Clock failure OR Error frame</p>	<p>≠ length of send data ≠ received parity bit = True ≠ bits in register = True = bits in register</p>	Ignition key	= On	0.001 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a Serial Peripheral Interface (SPI) communication failure. The Application Specific Integrated Circuit (ASIC) of the system is connected to the microcontroller via a SPI. The microcontroller includes hardware monitoring of the ASIC to recognize failures of the necessary input signals. The Monitor reads the results of certain of this hardware monitoring by reading out the ASIC EEPROM (Electronically Erasable Programmable Read-Only Memory) cell via Serial Peripheral Interface. A fault is set if charge pump failure bit, or clock-input-signal failure bit, or internal-oscillator-circuit failure bit is set.	Charge-pump failure bit is set OR Clock-input-signal failure bit is set OR Internal-oscillator-circuit failure bit is set		Ignition key AND First cyclic transmission to the ASICs occurred	= On = True	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage comparators of the Application Specific Integrated Circuit (ASIC). The ASIC has several voltage comparators to monitor the level of different voltage supplies. These comparators are tested at start-up for correct functionality, and the result of the test is stored as a EEPROM (Electronically Erasable Programmable Read-Only Memory) cell value. A fault is set if there is an error flag when the monitor reads the EEPROM cell value.	Error flag is set in a defined register	= True	System voltage	> 6.9 V	Three consecutive ignition cycles	Type A, 1 Trip
		This monitoring strategy checks if there is a Serial Peripheral Interface (SPI) communication failure. The L99H01 Application Specific Integrated Circuit (ASIC) of the system is connected to the microcontroller via a SPI. The microcontroller includes hardware monitoring of the ASIC to recognize failures of the necessary input signals. The Monitor reads the results of certain of this hardware monitoring by reading out the ASIC EEPROM (Electronically Erasable Programmable Read-Only Memory) cell via Serial Peripheral Interface. A fault is set if charge-pump failure bit, or watchdog failure bit, or Thermal failure bit is set.	Charge-pump failure bit is set OR Watchdog failure bit is set OR Thermal failure bit is set	= True = True = True	Ignition key AND First cyclic transmission to the L99H01 ASICs occurred	= On = True	0.005 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a timeout of the Serial Peripheral Interface (SPI) communication to Application Specific Integrated Circuit (ASIC). The Application Specific Integrated Circuit (ASIC) of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). The goal is to monitor the duration of the SPI transmission. A fault is set if the SPI transfer to ASIC is not finished within a defined period.	Duration of SPI transfer to ASIC	> 0.005 Sec	Ignition key AND Cyclic Tasks Started	= On = True	0.01 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		<p>The monitoring checks the received data by the Application Specific Integrated Circuit (ASIC). The ASIC of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). A fault is set if not all data has been transmitted or received.</p> <p>Clock Failure Check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring check for any clock failures.</p> <p>Frame Error Check - The ASICs of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). When ASIC detects a transmission failure, it sends an error frame via the SPI. The monitoring checks the frames transmitted via the SPI. A fault is set if an error frame is transmitted.</p>	<p>Clock failure OR Error frame received</p>	<p>= True ≠ bits in register</p>	<p>Ignition key AND Cyclic Tasks Started</p>	<p>= On = True</p>	<p>0.01 [Sec]</p>	<p>Type A, 1 Trip</p>
		<p>This monitoring strategy checks if there is a timeout of the Serial Peripheral Interface (SPI) communication to Application Specific Integrated Circuit (ASIC). The Application Specific Integrated Circuit (ASIC) of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). The goal is to monitor the duration of the SPI transmission. A fault is set if the SPI transfer to ASIC is not finished within a defined period.</p>	<p>Duration of SPI transfer to ASIC</p>	<p>> 0.005 Sec</p>	<p>System voltage AND Cyclic Tasks Started</p>	<p>> 6.9 V = True</p>	<p>0.05 [Sec]</p>	<p>Type A, 1 Trip</p>

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		<p>The monitoring checks the received data by the Application Specific Integrated Circuit (ASIC). The ASIC of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). A fault is set if not all data has been transmitted or received.</p> <p>Parity check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if the calculated parity does not match the parity bit.</p> <p>Bit check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if at least one bit of the actual transmitted data is not equal to the transmit bit in register.</p> <p>Rationality check - The ASICs of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). When ASIC detects a transmission failure, it sends an error frame via the SPI. The monitoring checks the frames transmitted via the SPI. A fault is set if an error frame is transmitted.</p>	<p>Length of received data OR Calculated parity of the received data OR Clock failure OR Acutal transmitted bits OR Error frame received</p>	<p>≠ length of send data ≠ received parity bit = True ≠ bits in register ≠ bits in register</p>	Ignition key	= On	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for exceptions in Operating System. A fault is set if an exception occurs in the Operating System.	OS-exception occurs	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		Detection of software component internal execution errors	Internal software state type	= Invalid	Ignition key	= On	0.01 [Sec]	Type A, 1 Trip
		This monitoring checks the TPSW-PBC function accessibility area into the RAM. A fault is set if the PBC SW variable or function tries to access outside its restricted area.	PBC SW function stays within its restricted area	= False	Ignition key	= On	0.02 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the Static Random Access Memory (SRAM) and peripheral Random Access Memory (RAM) are initialized or not. The SRAM and peripheral RAM are cleared at power-up. Then This monitoring reads every SRAM and RAM addresses. A fault is set if at least one addresses is not initialized to zero.	At least one RAM or SRAM bit	≠ 0	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks for proper pull-up resistor functionality. It monitors whether the motor relay pull-up (MRPU) switch inside the Application Specific Integrated Circuit (ASIC) is working as expected. A fault is set if the MRPU pin status does not match the selected switch state.	Motor relay pull-up pin status not correct	= True	System voltage AND Hydraulic pump motor	> 6.9 V = Off	0.5 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if a wrong hexfile was flashed in the AECU. The purpose of RTP pins is to do measurement of RAM variables. A fault is set if the RTP Enable pin is stuck to a high.	RTP Enable pin stuck to high	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		The System Mode Manager (SMM) asks in parallel with multiple system modes for the individual modules. To do this, it receives requests from different parts of software which are initialized at the beginning and after a while a valid value is given which is not "init" value. A fault is set if after a while one requester is still in init value.	One requester still in init value for time	> 3.6 Sec	Ignition key	= On	3.6 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the microcontroller stack has over or underflowed. During initialization, stack memory cells are set at the beginning and at the end of the stack area: these Stack memory cells are checked periodically. A fault is set if one of these Stack memory cells has been overwritten.	End-stack word overwritten OR Beginning-stack word overwritten	= True = True	Ignition key	= On	0.04 [Sec]	Type A, 1 Trip
		During system start-up, the time required to configure the application software (ASW) is monitored. A fault is set if the configuration lasts longer than a defined amount of time.	ASW configuration time	> 5 Sec	Ignition key	= On	5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for an unsupported Bootblock and FSW clock configuration in ECU. Within an ECU, the Bootblock allows actualizing the application which is called FSW. A failure is set if the Bootblock and FSW clock settings are different.	Bootblock and FSW clock settings are different	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if an internal fault has occurred in the operating system. A fault is set if software interrupts have occurred but: - the interrupt is invalid. - An interrupt lock release is called without previous lock. - not all interrupts are released.	Software interrupt occurred AND { Invalid interrupt occurred OR Interrupt lock release is called without previous lock OR Not all interrupts are released OR Interrupt lock time }	= True = True = True = True > 0.001 Sec	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if interrupts are properly running. The error signal module is the central module in the microcontroller level. It handles severe microcontroller core failures or peripheral failures, and coordinates the logic tests during start-up. A fault is set if no or not expected non-maskable interrupt occurs during Init tests.	Failure detected during safety logic startup tests	= True	System voltage	> 6.9 V	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the software is properly configured for the hardware. Software version and device identifiers of the Application Specific Integrated Circuit (ASIC) and of the microcontroller are compared with the software version and identifiers of the configuration software. A fault is set if a least one ID or software version does not match.	Received ID of microcontroller is not identical with the ID stored in the software	= True	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		This monitoring checks the valve channels during the freewheeling test. This test consists of splitting up several small pulses to slowly accelerate the pump. The acceleration is slow in order to avoid noise generation. A fault is set if an unused valve channel is detected during the freewheeling test or if the Valve-Driver ASIC (Application Specific Integrated Circuit) activation channel is defective.	Unused valve channel detected OR Valve-Driver-ASIC activation channel defect	= True = True	Ignition key AND FreeWheeling Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This is a monitoring of the Valve-Driver-ASIC (Application Specific Integrated Circuit) freewheeling path, which slowly accelerates the pump to avoid noise generation. A fault is set if the Valve-Driver-ASIC freewheeling path was activated for a longer time period than the maximum freewheeling time.	Valve-Driver-ASIC freewheeling path was activated for longer time than freewheeling time	> 0.03 Sec	Ignition key AND Valve test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve is activated properly. During an activation of all valves, the feedback gate of the Valve-Driver-ASIC (Application Specific Integrated Circuit) shows valve activation although the Hydraulic Enable of the Valve-Driver-ASIC is low with. A fault is set if the feedback duty on (Gate ON) for maximum valve actuation during testing exceeds a calibrated threshold.	Feedback duty on (Gate ON) for maximum actuation of valve under test	= 100 %	Ignition key	= On	0.005 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a pulse width modulation (PWM) failure in all 12 valves. A fault is set if the PWM check sequence is not completed during the duration of the Valve Actuation Register Test (VART).	Pulse width modulation check sequence is not completed during the running period of Valve Actuation Register Test	= True	Ignition key AND PWM Monitor OR Valve Actuation Register Test OR Valve Drift Check	= On = On = On = On	0.005 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the Silent Valve Driver Test (SVDT) results. SVDT is a periodic check that is initiated by the software. The test runs automatically at the Application Specific Integrated Circuit (ASIC), and in case of a positive result, feedback is sent to the software via the SPI (Serial Peripheral Interface) bus. A fault is set if successful feedback is not received from the finished Silent Valve Driver Test (VDT) via the SPI-bus.	Feedback of a successful finished Silent Valve Driver Test via SPI-bus not received	= True	Ignition key	= On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the configuration bits of the Valve-Driver-ASIC register are written correctly. A fault is set if the read data of the Application Specific Integrated Circuit (ASIC) configuration bits do not match with the corresponding written data in ASIC.	Configuration of Valve-Driver-ASIC register not correct	= True	Ignition key AND Hydraulic Enable signal high	= On = True	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the result of the built-in self-test (BIST) is correct. The built-in self-test (BIST) is an internal hardware valve driver test triggered by the software. It checks the functionality of both arithmetic logic units (ALU) of the current controller. Both ALUs are triggered by different patterns. A fault is set if the BIST results are not as expected.	Valve driver BIST result from ALU not as expected	= True	Ignition key AND BuidInSelfTest (BIST)	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the serial high end timer transmission between the microcontroller and the valve driver has failed. A fault is set if a wrong protocol, timing deviation, or lack of data transmission is detected.	SHET protocol wrong OR Timing deviation OR No data transmission	= True = True = True	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the VART (Valve Activation Register Test) detects an error. The internal valve driver activation registers are tested using the VART in order to detect any crosstalk or stuck situations. All the valves are opened and closed sequentially according to a matching test pattern. A valve opening draws a low valve relay current. A fault is set if an open load or under current state is not detected for each valve actuation.	Valve relay voltage / Internal supply voltage OR Valve Current	< 0.33 > 0.1 A	Ignition key	= On	140 [Sec]	Type A, 1 Trip
		This monitoring checks the plausibility of the valve activation state bit. The valve opening draws a low valve relay current. The bit should be set when the valve is off. A fault is set if the bit is set even though the ratio of valve relay output voltage (UVR) to internal supply voltage (UBVR) indicates that the valve is on.	Valve relay voltage / Internal supply voltage AND Valve actuation	> 0.5 = True	Ignition key AND Valve relay supply voltage	= On > 6.9 V	120 [Sec]	Type A, 1 Trip
		This monitoring compares the valve relay output voltage read by the Application Specific Integrated Circuit (ASIC) with the valve relay output voltage read by the Analog to Digital Converter (ADC) in order to check that the valve driver ensures circuit continuity. A fault is set if the difference between the two voltages is above a calibrated threshold	Absolute(measured ASIC voltage - read ADC voltage)	> 0.4 V	Ignition key AND SilentValveDriverTest (SVDT)	= On = On	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if a low ohmic side circuit from the valve voltage (UVR) to the supply voltage (UBVR) occurs during the resistor measurement. During this measurement, the valve relay output voltage should ideally be zero. A fault is set if UVR is higher than a calibrated threshold.	Valve relay output voltage	> 1.26 V	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there are internal and input signal failures of the Application Specific Integrated Circuit (ASIC). The ASIC is connected to the microcontroller by Serial Peripheral Interface (SPI). The monitor reads the results of this hardware monitoring EEPROM (Electrically Erasable Programmable Read-Only Memory) cell using Serial Peripheral Interface. The bits of the EEPROM cell are set by the hardware logic "Voltage-Pre_regulator-Mode". A fault is set if the voltage-pre-regulator-mode failure bit is set.	Voltage-pre-regulator-mode failure bit is set	= True	Ignition key	= On	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if wheel speed signals are correct. The Multiplexer IC inside the EBCU (Electronic Brake Control Unit) handles the EBCU internal transmission of the wheel speed sensor signals of all four wheels. To ensure safe EBCU internal transmission these signals are multiplexed and the multiplexed signal is sent on a separate signal path within EBCU. The Multiplexer IC signal check compares the EBCU internal signals with the multiplexed signal. A fault is set if the wheel speed signals and the multiplexed signal are not identical.	Wheel speed signal and multiplexed wheel speed sensor not identical	= True	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	dependent on vehicle speed	Type A, 1 Trip
		This monitoring strategy checks if the current wheel speed sensor configuration is correct via Serial Peripheral Interface (SPI). The system supports different wheel speed sensor configurations. A fault is set if, for a calibrated duration, there is a mismatch between the current wheel speed sensor mode software configuration (stored in a register) and the hardware configuration.	Mismatch between current WSS Mode software configuration stored in a register and the hardware configuration For time	= True > 0.1 Sec	Ignition key AND First cyclic transmission to ASIC	= On = True	0.1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an hardware defect. The Wheel Speed Sensor (WSS) System Integrated Circuit performs a check of the WSS wirings at System start-up automatically by switching sensor supply lines separately and storing the states of input comparators in a buffer. The buffer content is then evaluated in software. A fault is set if the buffer content shows a physically impossible condition.	Detected wheel speed sensor line condition is physically impossible	= True	System voltage AND Initial wheel speed sensor hardware tests AND Started with Hardware Reset OR Started with Software Reset	> 6.9 V = On = True = True	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking. Accelerate vehicle to at least 18.6 mph and hold the speed for at least 20s.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Control Module Long Term Memory Performance	P062F	This monitoring strategy checks if there is enough available space in the EEPROM (Electronically Erasable Programmable Read-Only Memory) to allocate a data field. A fault is set if the size of the data field is bigger than the amount of available space in EEPROM.	Data field size to allocate	> Available Space	System voltage AND Ignition key	> 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if it is possible to write data in persistent storage. Every write access to non-volatile memory in the EEPROM (Electronically Erasable Programmable Read-Only Memory) is protected by timeout monitoring and data verification after writing. The Persistent Data Manager checks persistent data access in EEPROM. A fault is set if a write operation occurs or if data verification after writing fails.	Writing operation AND Read data different from written data	> 0.025 Sec = True	Ignition key	= On	immediately	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Control Module Long Term Memory Reset	P0603	This monitoring checks the write result at the end of the EEPROM write procedure. A fault is set if a cell is invalid which results to a read back error after writing	Read back error	= True	Ignition key	= On		Type A, 1 Trip
		This monitoring strategy checks if the customer identifier is correct. During initialization, the persistent data manager compare the EEPROM (Electronically Erasable Programmable Read-Only Memory) cell value with the expected customer ID. A fault is set if the expected customer ID does not match the stored customer ID.	Stored customer ID	≠ expected customer ID	System voltage AND Ignition key	> 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the system has not found the enhanced platform software end marker, which is used to help the system find the end of the data. At ignition state, the Persistent Data Manager checks the content of the EEPROM (Electronically Erasable Programmable Read-Only Memory). A fault is set if the enhanced platform software end marker has not been found.	No enhanced platform software end marker in EEPROM	= True	System voltage AND Ignition key	> 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the stored data field size is correct. At ignition state, the Persistent Data Manager checks the content of the EEPROM (Electronically Erasable Programmable Read-Only Memory). A fault is set if a data field size in EEPROM does not match the corresponding data item configuration in the software.	Data field size in the EEPROM	≠ data size configuration in software	Ignition key	= On	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks the reading accessibility of the EEPROM (Electrically Erasable Programmable Read-Only Memory). During initialization, the Persistent Data Manager checks the content of the EEPROM. A fault is set if an access error occurs while reading EEPROM.	Read error occurs OR Not expected Non-Markable Interrupt detected	= True = True	System voltage	> 6.9 V	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM (Electrically Erasable Programmable Read-Only Memory) memory is readable. Besides the management of the electronic stability system the Electronic Brake Control Unit (EBCU) performs various functional checks. Initially and periodically, the memory content is checked by calculating a 64-bit CRC (Cyclic Redundancy Check) value and comparing it with the checksum generated during the software build process. This algorithm checks the complete memory content. A fault is set if it is not possible to read back data from EEPROM or if the data read back from EEPROM is not valid.	EEPROM data cannot be read OR EEPROM data not valid	= True = True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if EEPROM (Electrically Erasable Programmable Read-Only Memory) access is possible. The reference resistor is used to calculate the reference current. A fault is set if it is not possible to load the reference resistor value stored in EEPROM. In this case, the EEPROM value is defective or unreadable.	Cannot load the reference resistor value stored in the EEPROM	= True	Ignition key AND Resistor Measurement Test	= On = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the reference resistor voltage stored in EEPROM (Electrically Erasable Programmable Read-Only Memory) matches the measured resistor voltage. The reference resistor voltage is measured in the factory. A fault is set if the absolute difference between the reference resistor voltage stored in EEPROM and the measured resistor voltage exceeds a calibrated threshold.	Absolute(Reference resistor voltage stored in the EEPROM - Measured resistor voltage)	> 10 %	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitor checks the configuration of the wheel speed sensors after ignition on. The failure is due to a PDM access problem or a wrong value in the wheel speed sensor type. A failure is set if after ignition ON, the configuration of the wheel speed sensor type is not possible.	Wheel speed sensor type configuration possible	= False	Ignition key	= On	immediately	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Control Module Not Programmed	P0602	This monitoring check if the Electronic Brake Control Module (EBCM) has not been programmed with calibration data set. A fault is set if the byte 5 of the internal customer data for each of the 5 calibration modules is equal to ACII D	Byte 5 of the internal customer data for each of the 5 calibration modules is equal to ACII D	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
Control Module Random Access Memory (RAM)	P0604	This monitoring strategy checks the values of a specific RAM area. Furthermore, the address decoder is tested using test patterns to ensure bus integrity. The test writes different patterns at the addresses of this RAM area. Addresses are then read out and a signature for all the readout values is calculated. The original content in RAM is afterwards rewritten. The order of the patterns is chosen so that the signature the multibit and coupling failures can be set during the signature evaluation. A fault is set if a multibit or coupling failure is detected.	Multi-bits failure detected OR Coupling failure detected OR Address decoder test detects an error	= True = True = True	System voltage	> 6.9 V	Immediately	Type A, 1 Trip
		This monitoring strategy checks correct functionality of Random Access Memory (RAM) through a programmable Built In Self Test running in start-up phase.	Memory test fails	= True	Ignition key	= On	Immediately	Type A, 1 Trip
		This monitoring strategy checks if there is a single bit error at RAM. Because of Error Correction Code, RAM single-bit errors are always corrected. A fault is set if the number of bit errors exceeds a threshold.	Number of detected single-bit errors	> 2	Ignition key	= On	Immediately	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Control Module Read Only Memory (ROM)	P0601	This monitoring strategy checks if the CRC (Cyclic Redundancy Check) of Flash EEPROM (Electrically Erasable Programmable Read-Only Memory) is correct. Initially and periodically the complete Flash EEPROM contents are checked by calculating a CRC value and comparing it with the checksum generated during the software build process. A fault is set if a double bit error of Flash EEPROM is detected, or if more than a defined number of single bit errors are detected (otherwise, single bit errors are corrected).	Double bit error detected OR Number of detected single-bit errors	= True > 1	System voltage	> 6.9 V	Immediately , during start-up or respectively after 60 sec for cyclic flash checksum test.	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Ignition Switch - Accessory Position - Circuit Low	P2537	Detects an accessory position circuit open	Accessory .	= False	Propulsion System Active Propulsion System Active Time	= True > 0.5 Sec	0.5 [Sec]	Type B, 2 Trips

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Ignition Switch - Circuit High	P2535	Detects if the Run/Crank input circuit is high	Short to Battery	> 5 V	CAN Communication And ECM Run/Crank Active Data	= Enabled = False	2.5 [Sec]	Type A, 1 Trip
Ignition Switch - Circuit Low	P2534	Detects if the Run/Crank input circuit is low	Short to Ground Or Open Condition	< 2 V = True	CAN Communication And ECM Run/Crank Active Data	= Enabled = Active	2.5 [Sec]	Type A, 1 Trip
Internal Control Module A/D Processing Performance	P060B	This monitoring strategy checks the conversion time of the ADC (Analog Digital Converter). The ADC periodically reads an analog signal and converts it into digital values. Before starting a new conversion, the monitor checks that the previous conversion is finished. A fault is set if the previous conversion is not finished for a number of checks.	Number of times that the previous analog to digital conversion is not finished	> 9	Ignition key	= On	0.003 [Sec]	Type A, 1 Trip
		This monitoring strategy checks proper functionality of ADC self-test. To do this, ADC channels are switched to two predefined internal microcontroller resistors to measure defined (voltage) levels (high and low).The absolute differences between the two measurements are calculated in unit digits. A fault will be set if the difference is greater than a threshold.	Absolute(difference between the two ADC measurements)	> 540 digitSec	Ignition key	= On	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for correct internal Analog Digital Converter (ADC) functionality by comparing the analog motor voltage read in by the ADC with the digital motor voltage calculated by the Application Specific Integrated Circuit (ASIC) while the hydraulic pump is active. A fault is set if the deviation between the hydraulic pump motor voltage read by the ADC (analog) and the hydraulic pump motor voltage calculated by the ASIC (digital) exceeds a calibrated threshold.	Hydraulic pump motor voltage read by ADC (analog)/hydraulic pump motor voltage calculated by ASIC (digital)	> 0.25	Ignition key AND Hydraulic pump motor	= On = On	0.04 [Sec]	Type A, 1 Trip
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5s					
Left Front Inlet Control	C0010	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.		See Disabling DTCs	Not Fault Active		
Left Front Outlet Control	C0011	This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDt). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Front Wheel Speed Sensor Circuit High	C0503	This monitoring strategy checks if there is a shortcut of WSS signal line to the battery.	Voltage of WSS signal line	> 12 V	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Left Front Wheel Speed Sensor Circuit Low	C0502	This monitoring strategy checks for a line failure on the front left wheel speed sensor. In the line monitor, if a failure is detected, ASIC registers are evaluated and the corresponding failures are set. A fault is set if no precise line failure can be determine.	A failure is detected AND Wheel Speed Sensor Current Supply Line Monitoring AND Wheel Speed Sensor Voltage Monitoring AND Wheel Speed Sensor Current Signal Line Monitoring	= True = False = False = False	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the current at the supply line is below a calibrated threshold.	Sensor current at supply line	< 0.16 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Front Wheel Speed Sensor Circuit/Open	C0500	This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the sensor current at the signal line is below a calibrated threshold.	Sensor current at the signal line	< 0.0038 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Front Wheel Speed Sensor Incorrect Component Installed	C0555	This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted at the correct wheel. Since the WSS signals differ for different WSS sensor types, the EBCU (Electronic Brake Control Unit) is able to recognize incorrect WSS placement by evaluating the signal. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the stop pulse is missing for a calibrated period of time.	No stop pulse according to wheel speed sensor protocol detected	= True	Wheel speed sensor test completed AND Ignition key	= True = On	3 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Left Front Wheel Speed Sensor Intermittent/Erratic	C0504	This monitoring strategy checks if the High End Timer Transfer Unit (HETTU) buffer has overflowed. The HETTU buffer stores the time stamp of the wheel speed sensor outputs. This buffer has a status which tells whether the buffer can be used or not. A common PIC (Programmable Interrupt Controller) checks if the HETTU buffer is in the overflow state. In this case the buffer cannot be used because more edges occur on the wheel speed sensor channels than the buffer can store. A fault is set if the HETTU buffer is in the overflow state.	HET TU buffer state	= Overflow	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Front Wheel Speed Sensor Range/Performance	C0501	This monitoring strategy checks if there is a defective wheel speed sensor. A fault is set if the speed of one wheel speed sensor is zero and the other wheel speed sensor speeds are above a calibrated threshold. Additionally the vehicle speed has to be above a calibrated threshold.	Speed of 1 wheel AND Speed of 3 wheels	= 0 mph > 0 mph	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention	= On = False > 11.8 mph > 6.9 V = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed sensors is defective. It can be done after standstill, start-up monitoring at low speed, as well as while driving, start-up monitoring at high speed. The main principle of the start-up monitoring is to compare the speed signal from all four wheels to each other. A fault is set if the speed of the monitored wheel is below a calibrated threshold while the speed of the other wheels is above a calibrated threshold.	FR, RL, RR Wheel speed sensor AND FL Wheel speed sensor	> 7.45 mph = 0 mph	Check at low speed: Initial vehicle speed AND Anti-Lock Braking System intervention AND Traction control system intervention OR Check at high speed: Anti-Lock Braking System intervention AND Traction control system intervention	< 1.8 mph = False = False = False = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed signal is missing due to faulty wheel speed information. A fault is set if the wheel speed signal is missing for a calibrated duration (Δt) and the wheel deceleration is below a calibrated threshold.	No wheel speed signal for a time AND Wheel deceleration	> 0.08 Sec < 300 m/Sec ²	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention AND Hydroplaning detected	= On = False > 26.84 mph > 6.9 V = False = False	0.08 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the wheel speed sensor PWM (Pulse Width Modulation) is functioning correctly. The wheel speed sensor returns a PWM signal with a frequency which is dependent on the vehicle velocity. The vehicle velocity is determined by counting every rising-edge of the signal periodically for a fixed time. A threshold is calculated with the two last rising-edges values to filter a missing edge value due to high deceleration. A fault is set if the number of rising-edges for the next cycle is lower than this calculated threshold. This monitor uses rough road detection to distinguish gaps in the edge cycle signal caused by real faults from those caused by driving on rough roads.	Number of rising-edge per cycle	< Threshold calculated by mean of the two latest edge cycle	Vehicle speed AND Vehicle speed AND Anti-lock Brake System Interventions AND System voltage AND Ignition key	> 6.21 mph < 37.36 mph = False > 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks for a discontinuous wheel speed sensor signal, caused for example by impulse wheel vibration. The vibrations induce additional frequencies to the wheel speed sensor signal. The noise monitoring consists of three checks which lead to a noise fault. The first check evaluates the acceleration of each wheel speed sensor. The second check evaluates the amplitude of the noise events. A weighing factor is calculated according to the noise amplitude value. The third check evaluates the number of edges. A fault is set if two implausible high wheel speed accelerations occur within a calibrated duration, if the wheel speed acceleration is above a calibrated threshold, if the accumulation of the weighted noise amplitude is above a calibrated threshold during the actual driving cycle, or if the number of detected edges increases above a calibrated threshold within a calibrated period of time.	Wheel acceleration AND For a calibrated number of counts For time OR Wheel acceleration AND Accumulation of the weighted noise amplitude in current driving cycle OR Number of detected edges increases from To For time	> 9.81 m/Sec^2 = 2 < 1.2 Sec > 500 m/Sec^2 > 4 < 3 > 5 < 0.005 Sec	System voltage AND Ignition key	> 6.9 V = On	20 [Sec]	Type A, 1 Trip
		This monitoring strategy checks each wheel speed sensor signal for implausibly high wheel speed values. A fault is set if the wheel speed signal value is above a calibrated threshold for a calibrated duration.	Measured wheel speed For time	> 183.9 mph > 5.04 Sec	System voltage AND Ignition key	> 6.9 V = On	5.04 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the difference between the wheel speed sensor signals is within a range. A fault is set if the difference in wheel speed between a single wheel speed sensor and all other wheel speed sensors is above a calibrated threshold. If the vehicle speed is below a calibrated value, the malfunction threshold is a fixed value. If the vehicle speed is above this calibrated value, the malfunction threshold is proportional to the actual vehicle speed.	Difference between maximum and minimum wheel speed for vehicle speed OR Difference between maximum and minimum wheel speed for vehicle speed	> 3.7 mph < 12.4 mph > 6 % > 12.4 mph	Ignition key	= On	72 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted properly. This monitor continuously evaluates continuously the distance between the impulse wheel and the WSS. The WSS evaluates the magnetic flux density to detect an air gap failure. A fault is set if the air gap is too large which is indicated by a magnetic flux density below a calibrated threshold for a calibrated number of wheel rotations.	Magnetic flux density AND for a number of wheel rotations	< 0.0022 T > 5	Ignition key AND Wheel speed sensor test completed	= On = True	0.1 [Sec]	Type A, 1 Trip
		The monitoring checks if the stop pulse from each wheel speed sensor (WSS) is detected. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the Application Specific Integrated Circuit (ASIC) does not detect a stop pulse after some time and if there is no level change on the wheel speed sensor signal for some time.	No stop pulse detected For time OR No level change on signal For time	= True > 0.15 Sec = True > 3.5 Sec	Vehicle speed AND For time AND Wheel speed sensor test completed	< 1.12 mph > 10 Sec = True	3.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the supply voltage of the corresponding wheel speed sensor. Each wheel speed sensor is switched on separately. A fault is set if the sensor supply voltage is below a calibrated threshold during the initial phase.	Sensor supply voltage of the respective wheel speed sensor	< 11 V	Ignition key AND System voltage AND	= On > 6.9 V	0.035 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 37.3 mph and hold the speed for at least 7s					
Left Rear Brake Pressure Sensor Circuit High Voltage	C0576	This monitoring strategy checks if there is a short circuit to the supply voltage in the pressure sensor line. To do this, it compares the signal line voltage with the supply voltage. The signal line maximum voltage should be lower than the supply voltage. A fault is set if there is no difference in voltage between the signal line and the supply line.	Signal line voltage	> 3.3 V	Ignition key	= On	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Left Rear Brake Pressure Sensor Circuit Low Voltage	C0575	This monitoring strategy checks if there is a short circuit to ground in the pressure sensor line. To do this, it compares the signal line voltage with the ground voltage. The signal line minimum voltage should be higher than the ground voltage. A fault is set if there is no difference in voltage between the signal line and the ground.	Signal line voltage	< 0.3 V	Ignition key	= On	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Brake Pressure Sensor Circuit Performance	C0578	This monitoring strategy checks if the offset compensation of the pressure sensor is out of range. The zero-point of the pressure sensor signal is adjusted to compensate for any signal drifts. The offset compensation is only performed when the brake pedal is not applied (corresponding to the pressure sensor zero point). A fault is set if the offset is outside a calibrated range.	Measured pressure OR Measured pressure	> 1500 KPa < -1500 KPa	System voltage AND Brake pedal is pushed AND Acceleration pedal is pushed AND Vehicle speed	> 6.9 V = False = True > 4.47 mph	Immediately	Type A, 1 Trip
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5s					
Left Rear Inlet Control	C0018	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Outlet Control	C0019	This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Wheel Speed Sensor Circuit High	C050F	This monitoring strategy checks if there is a shortcut of WSS signal line to the battery.	Voltage of WSS signal line	> 12 V	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Wheel Speed Sensor Circuit Low	C050E	This monitoring strategy checks for a line failure on the rear left wheel speed sensor. In the line monitor, if a failure is detected, ASIC registers are evaluated and the corresponding failures are set. A fault is set if no precise line failure can be determine.	A failure is detected AND Wheel Speed Sensor Current Supply Line Monitoring AND Wheel Speed Sensor Voltage Monitoring AND Wheel Speed Sensor Current Signal Line Monitoring	= True = False = False = False	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the current at the supply line is below a calibrated threshold.	Sensor current at supply line	< 0.16 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Left Rear Wheel Speed Sensor Circuit/Open	C050C	This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the sensor current at the signal line is below a calibrated threshold.	Sensor current at the signal line	< 0.0038 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Wheel Speed Sensor Incorrect Component Installed	C0557	This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted at the correct wheel. Since the WSS signals differ for different WSS sensor types, the EBCU (Electronic Brake Control Unit) is able to recognize incorrect WSS placement by evaluating the signal. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the stop pulse is missing for a calibrated period of time.	No stop pulse according to wheel speed sensor protocol detected	= True	Wheel speed sensor test completed AND Ignition key	= True = On	3 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Wheel Speed Sensor Intermittent/Erratic	C0510	This monitoring strategy checks if the High End Timer Transfer Unit (HETTU) buffer has overflowed. The HETTU buffer stores the time stamp of the wheel speed sensor outputs. This buffer has a status which tells whether the buffer can be used or not. A common PIC (Programmable Interrupt Controller) checks if the HETTU buffer is in the overflow state. In this case the buffer cannot be used because more edges occur on the wheel speed sensor channels than the buffer can store. A fault is set if the HETTU buffer is in the overflow state.	HET TU buffer state	= Overflow	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Left Rear Wheel Speed Sensor Range/Performance	C050D	This monitoring strategy checks if there is a defective wheel speed sensor. A fault is set if the speed of one wheel speed sensor is zero and the other wheel speed sensor values are above a calibrated threshold. Additionally the vehicle speed has to be above a calibrated threshold.	Speed of 1 wheel AND Speed of 3 wheels	= 0 mph > 0 mph	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention	= On = False > 11.8 mph AND > 6.9 V = False	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the wheel speed sensors is defective. It can be done after standstill, start-up monitoring at low speed, as well as while driving, start-up monitoring at high speed. The main principle of the start-up monitoring is to compare the speed signal from all four wheels to each other. A fault is set if the speed of the monitored wheel is below a calibrated threshold while the speed of the other wheels is above a calibrated threshold.	FR, FL, RR Wheel speed sensor AND RL Wheel speed sensor	> 7.45 mph = 0 mph	Check at low speed: Initial vehicle speed AND Anti-Lock Braking System intervention AND Traction control system intervention OR Check at high speed: Anti-Lock Braking System intervention AND Traction control system intervention	< 1.8 mph = False = False = False = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed signal is missing due to faulty wheel speed information. A fault is set if the wheel speed signal is missing for a calibrated duration (Δt) and the wheel deceleration is below a calibrated threshold.	No wheel speed signal for a time AND Wheel deceleration	> 0.08 Sec < 300 m/Sec ²	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention AND Hydroplaning detected	= On = False > 26.84 mph > 6.9 V = False = False	0.08 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed sensor PWM (Pulse Width Modulation) is functioning correctly. The wheel speed sensor returns a PWM signal with a frequency which is dependent on the vehicle velocity. The vehicle velocity is determined by counting every rising-edge of the signal periodically for a fixed time. A threshold is calculated with the two last rising-edges values to filter a missing edge value due to high deceleration. A fault is set if the number of rising-edges for the next cycle is lower than this calculated threshold. This monitor uses rough road detection to distinguish gaps in the edge cycle signal caused by real faults from those caused by driving on rough roads.	Number of rising-edge per cycle	< Threshold calculated by mean of the two latest edge cycle	Vehicle speed AND Vehicle speed AND Anti-lock Brake System Interventions AND System voltage AND Ignition key	> 6.21 mph < 37.36 mph = False > 6.9 V = On	Immediately	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks for a discontinuous wheel speed sensor signal, caused for example by impulse wheel vibration. The vibrations induce additional frequencies to the wheel speed sensor signal. The noise monitoring consists of three checks which lead to a noise fault. The first check evaluates the acceleration of each wheel speed sensor. The second check evaluates the amplitude of the noise events. A weighing factor is calculated according to the noise amplitude value. The third check evaluates the number of edges. A fault is set if two implausible high wheel speed accelerations occur within a calibrated duration, if the wheel speed acceleration is above a calibrated threshold, if the accumulation of the weighted noise amplitude is above a calibrated threshold during the actual driving cycle, or if the number of detected edges increases above a calibrated threshold within a calibrated period of time.	Wheel acceleration AND For a calibrated number of counts For time OR Wheel acceleration AND Accumulation of the weighted noise amplitude in current driving cycle OR Number of detected edges increases from To For time	> 9.81 m/Sec ² = 2 < 1.2 Sec > 500 m/Sec ² > 4 < 3 > 5 < 0.005 Sec	System voltage AND Ignition key	> 6.9 V = On	20 [Sec]	Type A, 1 Trip
		This monitoring strategy checks each wheel speed sensor signal for implausibly high wheel speed values. A fault is set if the wheel speed signal value is above a calibrated threshold for a calibrated duration.	Measured wheel speed For time	> 183.9 mph > 5.04 Sec	System voltage AND Ignition key	> 6.9 V = On	5.04 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the difference between the wheel speed sensor signals is within a range. A fault is set if the difference in wheel speed between a single wheel speed sensor and all other wheel speed sensors is above a calibrated threshold. If the vehicle speed is below a calibrated value, the malfunction threshold is a fixed value. If the vehicle speed is above this calibrated value, the malfunction threshold is proportional to the actual vehicle speed.	Difference between maximum and minimum wheel speed for vehicle speed OR Difference between maximum and minimum wheel speed for vehicle speed	> 3.7 mph < 12.4 mph > 6 % > 12.4 mph	Ignition key	= On	72 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted properly. This monitor continuously evaluates continuously the distance between the impulse wheel and the WSS. The WSS evaluates the magnetic flux density to detect an air gap failure. A fault is set if the air gap is too large which is indicated by a magnetic flux density below a calibrated threshold for a calibrated number of wheel rotations.	Magnetic flux density AND for a number of wheel rotations	< 0.0022 T > 4	Ignition key AND Wheel speed sensor test completed	= On = True	0.1 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		The monitoring checks if the stop pulse from each wheel speed sensor (WSS) is detected. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the Application Specific Integrated Circuit (ASIC) does not detect a stop pulse after some time and if there is no level change on the wheel speed sensor signal for some time.	No stop pulse detected For time OR No level change on signal For time	= True > 0.15 Sec = True > 3.5 Sec	Vehicle speed AND For time AND Wheel speed sensor test completed	< 1.12 mph > 10 Sec = True	3.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the supply voltage of the corresponding wheel speed sensor. Each wheel speed sensor is switched on separately. A fault is set if the sensor supply voltage is below a calibrated threshold during the initial phase.	Sensor supply voltage of the respective wheel speed sensor	< 11 V	Ignition key AND System voltage AND	= On > 6.9 V	0.035 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 37.3 mph and hold the speed for at least 7s					
Lost Communication with Brake System Control Module B on Chassis Expansion Bus	U179D	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x214 not received on Bus E	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x219 not received on Bus E	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
		DTC Pass	After receiving all monitored messages from the supervised source					
Lost Communication with Engine Control Module	U0100	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1C5 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.5 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1F4 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0xC9 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x4C1 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	1.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x3D3 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1C3 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x2C3 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x4F1 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	2.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1C4 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x3E9 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0xAA not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0xBE not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1A3 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	5 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		DTC Pass	After receiving all monitored messages from the supervised source					
Lost Communication with Hybrid Powertrain Control Module	U0293	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0xD3 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1DF not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1F5 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.5 [Sec]	Type A, 1 Trip
		DTC Pass	After receiving all monitored messages from the supervised source					
Lost Communication with Hybrid Powertrain Control Module B	U179A	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x236 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.5 [Sec]	Type B, 2 Trips
		DTC Pass	After receiving all monitored messages from the supervised source					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Lost Communication with Hybrid Powertrain Control Module on Chassis Expansion CAN Bus	U18B5	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x230 not received on Bus E	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type B, 2 Trips
		DTC Pass	After receiving all monitored messages from the supervised source					
Powertrain Control Module Indicated Requested Torque	C10EA	This monitoring strategy checks if the electric power train response(actual regenerative brake torque) does not correspond to the target regenerative brake torque, or if the signal transmission from the power train ECU (Electronic Control Unit) to the brake system ECU failed. A Fault is set if the electric power train has applied regenerative braking without the request of the brake system ECU.	(Actual regenerative brake torque signal value - Target regenerative brake torque)	> 700 Nm	Full system mode AND Regenerative braking OR Unintended regenerative braking was executed	= On = On = True	0.8 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the electric power train response(actual regenerative brake torque) does not correspond to the target regenerative brake torque, or if the signal transmission from the power train ECU (Electronic Control Unit) to the brake system ECU failed. In case of a braking situation, the ECU calculates the proportion of regenerative brake torque to non-regenerative brake torque. Then the regenerative brake torque must reach the regenerative brake torque request from the ECU. A fault is set if the actual regenerative brake torque provided by the electric power train ECU deviates by more than a certain amount from the target regenerative brake torque requested by the brake system.	(Actual regenerative brake torque signal value - Target regenerative brake torque)	> 700 Nm	Full system mode AND Regenerative braking is being requested OR Response of electricpowertrain does not match request	= On = True = True	0.8 [Sec]	Type A, 1 Trip
		DTC Pass	Turn on ignition. 1. Accelerate moderate to 24.8 mph and Brake to standstill with low deceleration (brake time about 15sec), 2. Accelerate moderate to 24.8 mph and Brake to standstill with middle deceleration (brake time about 7.5sec), 3. Accelerate moderate to 24.8 mph and Brake to standstill with low deceleration (brake time about 15sec), 4. Accelerate moderate to 24.8 mph and Brake to standstill with middle deceleration (brake					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Pump Motor Relay Circuit High	C106B	This monitoring strategy checks if the hydraulic pump has an electrical fault. When the pump is not running. The monitor checks the voltage difference between MRD and MRS voltage and the current across the motor while the pump is activated, A fault is set if the voltage is greater than a calibrated threshold.	During motor actuation. Absolute (Hydraulic pump motor relay drain voltage - hydraulic pump motor relay source voltage)	> 2 V	Ignition key AND Hydraulic pump motor AND System voltage	= On = On > 6.9 V	0.06 [Sec]	Type A, 1 Trip
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5s					
Pump Motor Relay Circuit Low	C106A	This monitoring strategy checks if there is an overload situation on the motor relay during actuation. A fault is set if the hydraulic pump motor relay cannot be switched-through completely. This happens when the voltage between the Motor Relay Drain (MRD) and the Motor Relay Source (MRS) is greater than a calibrated threshold.	During motor actuation. Absolute (Hydraulic pump motor relay drain voltage - hydraulic pump motor relay source voltage)	> 0.5 V	Ignition key AND Hydraulic pump motor AND System voltage	= On = On > 6.9 V	0.06 [Sec]	Type A, 1 Trip
		DTC Pass	Drive off, accelerate up to 37.2 mph and maintain this speed for at least 5s					
Regenerative Braking Axle Torque Achieved Message Counter Incorrect	C1287	This monitoring strategy checks whether the message is still alive or not. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a counter is incremented within the sending ECU. the counter value is enclosed within the message. The receiving control unit checks whether counters have been incremented. A fault is set if the counter value is not incremented.	Message 0x230 on Bus E counter halted	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type B, 2 Trips
		This monitoring strategy checks if the message checksum is correct. The network driver sends and receives all network messages. It also checks if the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a checksum is calculated within the sending ECU. The value of the checksum is enclosed within the message. The receiving control unit calculates the checksum again and compares it with the sent one. A fault is set if the received checksum is different from the calculated checksum.	Checksum of 0x230 on Bus E not correct	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [Sec]	Type B, 2 Trips

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Right Front Inlet Control	C0014	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Front Outlet Control	C0015	This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Front Wheel Speed Sensor Circuit High	C0509	This monitoring strategy checks if there is a shortcut of WSS signal line to the battery.	Voltage of WSS signal line	> 12 V	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Right Front Wheel Speed Sensor Circuit Low	C0508	This monitoring strategy checks for a line failure on the front right wheel speed sensor. In the line monitor, if a failure is detected, ASIC registers are evaluated and the corresponding failures are set. A fault is set if no precise line failure can be determine.	A failure is detected AND Wheel Speed Sensor Current Supply Line Monitoring AND Wheel Speed Sensor Voltage Monitoring AND Wheel Speed Sensor Current Signal Line Monitoring	= True = False = False = False	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the current at the supply line is below a calibrated threshold.	Sensor current at supply line	< 0.16 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Front Wheel Speed Sensor Circuit/Open	C0506	This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the sensor current at the signal line is below a calibrated threshold.	Sensor current at the signal line	< 0.0038 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Front Wheel Speed Sensor Incorrect Component Installed	C0556	This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted at the correct wheel. Since the WSS signals differ for different WSS sensor types, the EBCU (Electronic Brake Control Unit) is able to recognize incorrect WSS placement by evaluating the signal. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the stop pulse is missing for a calibrated period of time.	No stop pulse according to wheel speed sensor protocol detected	= True	Wheel speed sensor test completed AND Ignition key	= True = On	3 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Right Front Wheel Speed Sensor Intermittent/Erratic	C050A	This monitoring strategy checks if the High End Timer Transfer Unit (HETTU) buffer has overflowed. The HETTU buffer stores the time stamp of the wheel speed sensor outputs. This buffer has a status which tells whether the buffer can be used or not. A common PIC (Programmable Interrupt Controller) checks if the HETTU buffer is in the overflow state. In this case the buffer cannot be used because more edges occur on the wheel speed sensor channels than the buffer can store. A fault is set if the HETTU buffer is in the overflow state.	HET TU buffer state	= Overflow	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Front Wheel Speed Sensor Range/Performance	C0507	This monitoring strategy checks if there is a defective wheel speed sensor. A fault is set if the speed of one wheel speed sensor is zero and the other wheel speed sensor values are above a calibrated threshold. Additionally the vehicle speed has to be above a calibrated threshold.	Speed of 1 wheel AND Speed of 3 wheels	= 0 mph > 0 mph	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention	= On = False > 11.8 mph > 6.9 V = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed sensors is defective. It can be done after standstill, start-up monitoring at low speed, as well as while driving, start-up monitoring at high speed. The main principle of the start-up monitoring is to compare the speed signal from all four wheels to each other. A fault is set if the speed of the monitored wheel is below a calibrated threshold while the speed of the other wheels is above a calibrated threshold.	FL, RL, RR Wheel speed sensor AND FR Wheel speed sensor	> 7.45 mph = 0 mph	Check at low speed: Initial vehicle speed AND Anti-Lock Braking System intervention AND Traction control system intervention OR Check at high speed: Anti-Lock Braking System intervention AND Traction control system intervention	< 1.8 mph = False = False = False = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed signal is missing due to faulty wheel speed information. A fault is set if the wheel speed signal is missing for a calibrated duration (Δt) and the wheel deceleration is below a calibrated threshold.	No wheel speed signal for a time AND Wheel deceleration	> 0.08 Sec < 300 m/Sec ²	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention AND Hydroplaning detected	= On = False > 26.84 mph > 6.9 V = False = False	0.08 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the wheel speed sensor PWM (Pulse Width Modulation) is functioning correctly. The wheel speed sensor returns a PWM signal with a frequency which is dependent on the vehicle velocity. The vehicle velocity is determined by counting every rising-edge of the signal periodically for a fixed time. A threshold is calculated with the two last rising-edges values to filter a missing edge value due to high deceleration. A fault is set if the number of rising-edges for the next cycle is lower than this calculated threshold. This monitor uses rough road detection to distinguish gaps in the edge cycle signal caused by real faults from those caused by driving on rough roads.	Number of rising-edge per cycle	< Threshold calculated by mean of the two latest edge cycle	Vehicle speed AND Vehicle speed AND Anti-lock Brake System Interventions AND System voltage AND Ignition key	> 6.21 mph < 37.36 mph = False > 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks for a discontinuous wheel speed sensor signal, caused for example by impulse wheel vibration. The vibrations induce additional frequencies to the wheel speed sensor signal. The noise monitoring consists of three checks which lead to a noise fault. The first check evaluates the acceleration of each wheel speed sensor. The second check evaluates the amplitude of the noise events. A weighing factor is calculated according to the noise amplitude value. The third check evaluates the number of edges. A fault is set if two implausible high wheel speed accelerations occur within a calibrated duration, if the wheel speed acceleration is above a calibrated threshold, if the accumulation of the weighted noise amplitude is above a calibrated threshold during the actual driving cycle, or if the number of detected edges increases above a calibrated threshold within a calibrated period of time.	Wheel acceleration AND For a calibrated number of counts For time OR Wheel acceleration AND Accumulation of the weighted noise amplitude in current driving cycle OR Number of detected edges increases from To For time	> 9.81 m/Sec^2 = 2 < 1.2 Sec > 500 m/Sec^2 > 4 < 3 > 5 < 0.005 Sec	System voltage AND Ignition key	> 6.9 V = On	20 [Sec]	Type A, 1 Trip
		This monitoring strategy checks each wheel speed sensor signal for implausibly high wheel speed values. A fault is set if the wheel speed signal value is above a calibrated threshold for a calibrated duration.	Measured wheel speed For time	> 183.9 mph > 5.04 Sec	System voltage AND Ignition key	> 6.9 V = On	5.04 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the difference between the wheel speed sensor signals is within a range. A fault is set if the difference in wheel speed between a single wheel speed sensor and all other wheel speed sensors is above a calibrated threshold. If the vehicle speed is below a calibrated value, the malfunction threshold is a fixed value. If the vehicle speed is above this calibrated value, the malfunction threshold is proportional to the actual vehicle speed.	Difference between maximum and minimum wheel speed for vehicle speed OR Difference between maximum and minimum wheel speed for vehicle speed	> 3.7 mph < 12.4 mph > 6 % > 12.4 mph	Ignition key	= On	72 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted properly. This monitor continuously evaluates continuously the distance between the impulse wheel and the WSS. The WSS evaluates the magnetic flux density to detect an air gap failure. A fault is set if the air gap is too large which is indicated by a magnetic flux density below a calibrated threshold for a calibrated number of wheel rotations.	Magnetic flux density AND for a number of wheel rotations	< 0.0022 T > 4	Ignition key AND Wheel speed sensor test completed	= On = True	0.1 [Sec]	Type A, 1 Trip
		The monitoring checks if the stop pulse from each wheel speed sensor (WSS) is detected. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the Application Specific Integrated Circuit (ASIC) does not detect a stop pulse after some time and if there is no level change on the wheel speed sensor signal for some time.	No stop pulse detected For time OR No level change on signal For time	= True > 0.15 Sec = True > 3.5 Sec	Vehicle speed AND For time AND Wheel speed sensor test completed	< 1.12 mph > 10 Sec = True	3.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the supply voltage of the corresponding wheel speed sensor. Each wheel speed sensor is switched on separately. A fault is set if the sensor supply voltage is below a calibrated threshold during the initial phase.	Sensor supply voltage of the respective wheel speed sensor	< 11 V	Ignition key AND System voltage AND	= On > 6.9 V	0.035 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 37.3 mph and hold the speed for at least 7s					
Right Rear Inlet Control	C001C	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Rear Outlet Control	C001D	This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2, or if the High Side Switch Line Loss is below a calibrated threshold, for a calibrated number of failed tests.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Rear Wheel Speed Sensor Circuit High	C0515	This monitoring strategy checks if there is a shortcut of WSS signal line to the battery.	Voltage of WSS signal line	> 12 V	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Right Rear Wheel Speed Sensor Circuit Low	C0514	This monitoring strategy checks for a line failure on the rear right wheel speed sensor. In the line monitor, if a failure is detected, ASIC registers are evaluated and the corresponding failures are set. A fault is set if no precise line failure can be determine.	A failure is detected AND Wheel Speed Sensor Current Supply Line Monitoring AND Wheel Speed Sensor Voltage Monitoring AND Wheel Speed Sensor Current Signal Line Monitoring	= True = False = False = False	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the current at the supply line is below a calibrated threshold.	Sensor current at supply line	< 0.16 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Rear Wheel Speed Sensor Circuit/Open	C0512	This monitoring strategy checks if there is an electrical failure in the wheel speed sensors. The sensor current and the sensor voltage are monitored by a comparator circuit in an ASIC (Application Specific Integrated Circuit). A fault is set if the sensor current at the signal line is below a calibrated threshold.	Sensor current at the signal line	< 0.0038 A	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.12 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Rear Wheel Speed Sensor Incorrect Component Installed	C0558	This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted at the correct wheel. Since the WSS signals differ for different WSS sensor types, the EBCU (Electronic Brake Control Unit) is able to recognize incorrect WSS placement by evaluating the signal. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the stop pulse is missing for a calibrated period of time.	No stop pulse according to wheel speed sensor protocol detected	= True	Wheel speed sensor test completed AND Ignition key	= True = On	3 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Right Rear Wheel Speed Sensor Intermittent/Erratic	C0516	This monitoring strategy checks if the High End Timer Transfer Unit (HETTU) buffer has overflowed. The HETTU buffer stores the time stamp of the wheel speed sensor outputs. This buffer has a status which tells whether the buffer can be used or not. A common PIC (Programmable Interrupt Controller) checks if the HETTU buffer is in the overflow state. In this case the buffer cannot be used because more edges occur on the wheel speed sensor channels than the buffer can store. A fault is set if the HETTU buffer is in the overflow state.	HET TU buffer state	= Overflow	Ignition key	= On	0.03 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Right Rear Wheel Speed Sensor Range/Performance	C0513	This monitoring strategy checks if there is a defective wheel speed sensor. A fault is set if the speed of one wheel speed sensor is zero and the other wheel speed sensor values are above a calibrated threshold. Additionally the vehicle speed has to be above a calibrated threshold.	Speed of 1 wheel AND Speed of 3 wheels	= 0 mph > 0 mph	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention	= On = False > 11.8 mph > 6.9 V = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed sensors is defective. It can be done after standstill, start-up monitoring at low speed, as well as while driving, start-up monitoring at high speed. The main principle of the start-up monitoring is to compare the speed signal from all four wheels to each other. A fault is set if the speed of the monitored wheel is below a calibrated threshold while the speed of the other wheels is above a calibrated threshold.	FR, FL, RL Wheel speed sensor AND RR Wheel speed sensor	> 7.45 mph = 0 mph	Check at low speed: Initial vehicle speed AND Anti-Lock Braking System intervention AND Traction control system intervention OR Check at high speed: Anti-Lock Braking System intervention AND Traction control system intervention	< 1.8 mph = False = False = False = False	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the wheel speed signal is missing due to faulty wheel speed information. A fault is set if the wheel speed signal is missing for a calibrated duration (Δt) and the wheel deceleration is below a calibrated threshold.	No wheel speed signal for a time AND Wheel deceleration	> 0.08 Sec < 300 m/Sec ²	Ignition key AND Anti-Lock Braking intervention AND Vehicle speed AND System voltage AND Traction Control System Intervention AND Hydroplaning detected	= On = False > 26.84 mph > 6.9 V = False = False	0.08 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the wheel speed sensor PWM (Pulse Width Modulation) is functioning correctly. The wheel speed sensor returns a PWM signal with a frequency which is dependent on the vehicle velocity. The vehicle velocity is determined by counting every rising-edge of the signal periodically for a fixed time. A threshold is calculated with the two last rising-edges values to filter a missing edge value due to high deceleration. A fault is set if the number of rising-edges for the next cycle is lower than this calculated threshold. This monitor uses rough road detection to distinguish gaps in the edge cycle signal caused by real faults from those caused by driving on rough roads.	Number of rising-edge per cycle	< Threshold calculated by mean of the two latest edge cycle	Vehicle speed AND Vehicle speed AND Anti-lock Brake System Interventions AND System voltage AND Ignition key	> 6.21 mph < 37.36 mph = False > 6.9 V = On	Immediately	Type A, 1 Trip
		This monitoring strategy checks for a discontinuous wheel speed sensor signal, caused for example by impulse wheel vibration. The vibrations induce additional frequencies to the wheel speed sensor signal. The noise monitoring consists of three checks which lead to a noise fault. The first check evaluates the acceleration of each wheel speed sensor. The second check evaluates the amplitude of the noise events. A weighing factor is calculated according to the noise amplitude value. The third check evaluates the number of edges. A fault is set if two implausible high wheel speed accelerations occur within a calibrated duration, if the wheel speed acceleration is above a calibrated threshold, if the accumulation of the weighted noise amplitude is above a calibrated threshold during the actual driving cycle, or if the number of detected edges increases above a calibrated threshold within a calibrated period of time.	Wheel acceleration AND For a calibrated number of counts For time OR Wheel acceleration AND Accumulation of the weighted noise amplitude in current driving cycle OR Number of detected edges increases from To For time	> 9.81 m/Sec^2 = 2 < 1.2 Sec > 500 m/Sec^2 > 4 < 3 > 5 < 0.005 Sec	System voltage AND Ignition key	> 6.9 V = On	20 [Sec]	Type A, 1 Trip
		This monitoring strategy checks each wheel speed sensor signal for implausibly high wheel speed values. A fault is set if the wheel speed signal value is above a calibrated threshold for a calibrated duration.	Measured wheel speed For time	> 183.9 mph > 5.04 Sec	System voltage AND Ignition key	> 6.9 V = On	5.04 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the difference between the wheel speed sensor signals is within a range. A fault is set if the difference in wheel speed between a single wheel speed sensor and all other wheel speed sensors is above a calibrated threshold. If the vehicle speed is below a calibrated value, the malfunction threshold is a fixed value. If the vehicle speed is above this calibrated value, the malfunction threshold is proportional to the actual vehicle speed.	Difference between maximum and minimum wheel speed for vehicle speed OR Difference between maximum and minimum wheel speed for vehicle speed	> 3.7 mph < 12.4 mph > 6 % > 12.4 mph	Ignition key	= On	72 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the Wheel Speed Sensor (WSS) is mounted properly. This monitor continuously evaluates continuously the distance between the impulse wheel and the WSS. The WSS evaluates the magnetic flux density to detect an air gap failure. A fault is set if the air gap is too large which is indicated by a magnetic flux density below a calibrated threshold for a calibrated number of wheel rotations.	Magnetic flux density AND for a number of wheel rotations	< 0.0022 T > 4	Ignition key AND Wheel speed sensor test completed	= On = True	0.1 [Sec]	Type A, 1 Trip
		The monitoring checks if the stop pulse from the Wheel Speed Sensor of each wheel is detected. The intelligent WSS signal provides additional information (air gap) encoded in bits 0-8. Each detection event is followed by a stop pulse. A fault is set if the Application Specific Integrated Circuit (ASIC) does not detect a stop pulse after some time and if there is no level change on the wheel speed sensor signal for some time.	No stop pulse detected For time OR No level change on signal For time	= True > 0.15 Sec = True > 3.5 Sec	Vehicle speed AND For time AND Wheel speed sensor test completed	< 1.12 mph > 10 Sec = True	3.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the supply voltage of the corresponding wheel speed sensor. Each wheel speed sensor is switched on separately. A fault is set if the sensor supply voltage is below a calibrated threshold during the initial phase.	Sensor supply voltage of the respective wheel speed sensor	< 11 V	Ignition key AND System voltage AND	= On > 6.9 V	0.035 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 37.3 mph and hold the speed for at least 7s					
Software Incompatibility With Brake System Control Module "B" - Generic	U031C	This monitoring checks if there is a mismatch between the iBooster compatibility index signal and the current configuration in ESP. A fault is set if the signal "Ebrake Assist Compatibility Index" is received with an incompatible index value.	"Ebrake Assist Compatibility Index" is received with an incompatible index value	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
System Voltage	P0560	This monitoring strategy checks if the resistance in the internal valve supply voltage (UBVR) line is faulty or too high by checking the voltage. A supply line failure is detected during the Valve Activation Supply Line Test (VAST). A fault is set if the ratio of internal valve supply voltage to system voltage is above a calibrated threshold.	Internal valve supply voltage / System voltage	> 0.25	Vehicle speed AND Ignition key AND System voltage	> 9.32 mph = On > 6.9 V	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Accelerate vehicle to at least 18.6 mph and hold the speed for at least 20s					
System Voltage High	P0563	This monitoring checks the system supply voltage. A fault is set if the voltage is greater than a calibrated threshold.	CAN supply voltage	> 17 V	Ignition key	= On	0.09 [Sec]	Type B, 2 Trips
		This monitoring strategy checks if the motor relay is in an overvoltage situation. This protects the hydraulic pump against overvoltage. A fault is set if the supply voltage is above a calibrated threshold.	Voltage at motor relay	> 17 V	System voltage AND Ignition key	> 6.9 V = On	1 [Sec]	Type B, 2 Trips
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
System Voltage Low	P0562	This monitoring strategy checks if Ecu supply voltage is out of range low, which means below the HW (Hardware) switch off threshold but the HW is not switched off for the particular time. A fault is set if the Ecu supply voltage is below a threshold.	Ecu supply voltage	< 4.9 V	Ignition key	= On	0.2 [Sec]	Special Type C
		This monitoring strategy checks if the hydraulic components are in a hard undervoltage situation. A fault is set if the hydraulic supply voltage drops below a calibrated threshold.	Hydraulic supply voltage	< 6.9 V	Ignition key	= On	1 [Sec]	Special Type C
		This monitoring strategy checks the lower functional voltage range of the hydraulic components to ensure full system functionality. A fault is set if the valve voltage or the motor voltage drops below a calibrated threshold.	Valve relay voltage	< 9.4 V	Ignition key	= On	1 [Sec]	Special Type C
		This monitoring checks the system supply voltage. A fault is set if the voltage is less than a calibrated threshold.	CAN supply voltage	< 7.5 V	Ignition key	= On	0.09 [Sec]	Special Type C
		This monitoring strategy checks if there is an undervoltage of the ASIC internal Sigma Delta Modulator (SDM). This monitoring works through an ASIC which measures an undervoltage and indicates an insufficient supply voltage of sigma delta converter to the microcontroller with SPI (Serial Peripheral Interface) protocol. A fault is set if the SDM (Sigma Delta Modulator) supply voltage is below a calibrated threshold.	Sigma delta converter supply voltage	< 5.5 V	Ignition key	= On	0.01 [Sec]	Special Type C

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					
Traction Control Front Isolation Solenoid Valve Circuit	C1590	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a short circuit between valves or a defective coil during the Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2 for a calibrated number of failed tests. A fault is also set if the High Side Switch Line Loss is below a calibrated threshold.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the drift effects in the hardware current controller. The current regulator inside the valve driver returns current feedback for each activated valve. A fault is set if the difference between an activated valve's measured activation (current regulator feedback) and activation calculated from the previous resistor measurement values (current pattern) is above a calibrated threshold.	Comparison of calculated current with measured current AND Comparison of calculated current with measured current	> 20 % < -20 %	Ignition key AND Vehicle speed AND Previous successful resistor measurement AND Valve Drift Check	= On > 9.32 mph = True = active	0.025 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec. Accelerate vehicle to at least 18.6 mph and hold the speed for at least 20s		d			
Traction Control Front Prime Solenoid Valve Circuit	C158F	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	(Current through the valve OR Current through the valve) AND Both for a number of failed tests	> 0.12 A < 0.085 A > 5	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND For a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance AND For a number of times	> 0.2 Of calculated resistance < -0.2 Of calculated resistance > 2	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if there is a short circuit between valves or a defective coil during the Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failure such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2 for a calibrated number of failed tests. A fault is also set if the High Side Switch Line Loss is below a calibrated threshold.	(Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test (VART). A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation AND For a number of times	< 0.005 A > 2	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Traction Control Rear Isolation Solenoid Valve Circuit	C1592	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	Current through valve AND Current through valve AND Both for a number of failed tests	> 0.12 A < 0.085 A	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside of the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND Both for a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance	> 0.2 Of calculated resistance > -0.2 Of calculated resistance	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring checks if there is a short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failures such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDT). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2 for a calibrated number of failed tests. A fault is also set if the High Side Switch Line Loss is below a calibrated threshold_5.	Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test. A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold for a calibrated period of time.	Measured gate actuation during test actuation	< 0.005 A	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Traction Control Rear Prime Solenoid Valve Circuit	C1591	This monitoring strategy checks if the Valve-Driver-ASIC (Application Specific Integrated Circuit) FreeWheeling component is defective. A fault is set if the valve driver freewheeling cannot be switched on or off or if the trigger state is incorrect.	Freewheeling of valve driver cannot be switched OR Trigger state not correct	= True = True	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve actuation corresponds to the expected value. The basic valve monitoring is triggered by the coordinator via the control message. A fault is set if the valve actuation is different from the expected value for a calibrated period of time.	Valve actuation	≠ expected value	Ignition key AND Resistor Measurement Test	= On = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the current through a valve is too high or too low. A fault is set if the valve current is above a calibrated threshold_1 or below a calibrated threshold_2 for a calibrated number of failed tests.	Current through valve AND Current through valve AND Both for a number of failed tests	> 0.12 A < 0.085 A	Ignition key AND Leakage Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage at the output Qx or at the gate to detect if the Valve-Driver-ASIC (Application Specific Integrated Circuit) output driver is not functioning correctly. All PWM (Pulse Width Modulation) signal positive edges are counted, and the low time duration is measured. The resulting value is read out via SPI (Serial Peripheral Interface). The high and low limits of the real PWM signal, which are set by the output driver, are calculated using the measured number of edges and the low time. The calculated high and low limits depend on the activation used. A fault is set if the current activation value is outside the calculated limits.	Measured actuation duty OR Measured actuation duty AND Both for a number of times	< Set Actuation Duty - 20% > Set Actuation Duty + 20% > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring strategy checks if the transistor gates are set properly. Qx is the command sent to the transistor gate which commands the valve motor. The Qx monitor compares the expected value of Qx (the calculated Qx-ON/OFF value which is dependent on the current set valve activation) with the actual value of Qx (Qx-ON/OFF from the valve-related SPI (Serial Peripheral Interface) register) in order to check for correct output driver functionality (gate on/off). A fault is set if the actual Qx value does not match the expected Qx value.	(Measured Gate On Actuation Duty OR Measured Gate Off Actuation Duty) AND Both for a number of failed tests	< 95 % > 5 % > 5	Ignition key AND Resistor Measurement Test AND Leakage Test AND Valve Activation Register Test AND Silent Valve Driver Test	= On = Off = Off = Off = Off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve-related resistor value is out of range during the resistor measurement. This resistor value is calculated by taking the mean of the voltage through the resistor. A fault is set if the valve resistor value is too high or too low.	Comparison of calculated resistance and measured resistance OR Comparison of calculated resistance and measured resistance	> 0.2 Of calculated resistance > -0.2 Of calculated resistance	Ignition key AND Resistor Measurement Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring checks if there is short circuit between valves or a defective coil (due to Valve-Driver-ASIC (Application Specific Integrated Circuit) internal failures such as OpenLoad, UnderCurrent, OverCurrent, OverTemp, PGndLost or DxLost) during the Valve-Driver-ASIC Silent Valve Driver Test (SVDt). A fault is set if the ASIC current or temperature is below a calibrated threshold_1 or above a calibrated threshold_2 for a calibrated number of failed tests. A fault is also set if the High Side Switch Line Loss is below a calibrated threshold_5.	Current at ASIC OR Current at ASIC OR Temperature at ASIC OR Temperature at ASIC OR High Side Switch Line Loss) AND For a number of times	< 0.05 A > 0.14 A < 25 °C > 140 °C < 0.005 A > 2	Ignition key AND Silent Valve Driver Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring checks if the internal valve-driver-ASIC (Application Specific Integrated Circuit) register matches the current actuation during the Valve Actuation Register Test. A fault is set if the measured gate actuation duty during the test actuation exceeds a calibrated threshold.	Measured gate actuation during test actuation	< 0.005 A	Ignition key AND Valve Activation Register Test	= On = On	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the drift effects in the hardware current controller. The current regulator inside the valve driver returns current feedback for each activated valve. A fault is set if the difference between an activated valve's measured activation (current regulator feedback) and activation calculated from the previous resistor measurement values (current pattern) is above a calibrated threshold.	Comparison of calculated current with measured current AND Comparison of calculated current with measured current	> 20 % < - 20 %	Ignition key Vehicle speed AND Previous successful resistor measurement AND Valve Drift Check	= On > 9.32 mph = True = active	0.03 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec. Accelerate vehicle to at least 18.6 mph and hold the speed for at least 20s					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Valve Relay Circuit	C106D	This monitoring strategy checks if the valve relay is correctly activated by comparing the valve relay output voltage (UVR) to the supply voltage (UBVR). The valve relay is typically switched on or off during the Fail-Safe Logic Test (FSLT) to detect if the valve relay has not switched on successfully. A fault is set if the resulting ratio of UVR to UBVR is below a calibrated threshold.	Valve relay output voltage / Valve relay supply voltage	< 0.7	Ignition key AND Fail-Safe Logic Test	= On = On	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the valve relay is correctly activated by comparing the valve relay output voltage (UVR) to the valve relay supply voltage (UBVR). A fault is set if the resulting ratio is below a calibrated threshold which indicates that the valve relay has not switched on successfully.	Valve relay output voltage / Valve relay supply voltage	< 0.7	Ignition key AND Fail-Safe Logic Test is finished AND Valve relay output voltage mid level supply	= On = True = On	0.025 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Valve Relay Circuit High	C1070	This monitoring strategy checks if the valve relay output voltage (UVR) voltage is shorted to the valve relay supply voltage (UBVR), if the valve relay is stuck, or if a missing valve relay watchdog is not detected. Two separate tests check if the valve relay can be switched off. The first test checks if a missing Built In Self Test (BIST) watchdog leads to a switched off valve relay because the hydraulic state "off". The second test checks if the valve-relay-safety-switch detects a missing valve-relay-watchdog, which must lead to a switched off valve relay. During checks, the Fail-Safe Logic Test (FSLT) derives the valve relay status by comparing the valve relay supply voltage to the valve relay voltage. A fault is set if test 1 or 2 detects that the valve relay is still switched on.	Missing BIST watchdog detected OR Valve relay safety switch detects a missing valve relay watchdog	= True = True	Ignition key AND Initial Fail-Safe Logic Test is running	= On = True	0.45 [Sec]	Type A, 1 Trip
		This monitoring checks if there is a short circuit to the valve relay. All hydraulic valves are supplied with power through one relay. This relay is checked for circuit continuity. A fault is set if the valve solenoid high side voltage is above a calibrated threshold, meaning a short circuit to the battery voltage is detected. The threshold depends on the system voltage.	Valve relay solenoid low side voltage	> 4.8 V	Ignition key AND Valve relay enabled AND System voltage	= On = False > 6.9 V	0.2 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
Valve Relay Circuit Low	C106F	This monitoring strategy checks if a valve relay high ohmic short to ground has occurred by comparing the valve relay output voltage (UVR) to the valve relay supply voltage (UBVR). A fault is set if the resulting ratio is below a calibrated threshold which indicates that the valve relay is shorted to ground.	Valve relay output voltage / Valve relay supply voltage	< 0.3	Ignition key AND Valve relay supply voltage	= On > 6.9 V	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a valve relay short to ground by comparing the valve relay output voltage (UVR) to the valve relay supply voltage (UBVR). A fault is set if the resulting ratio is below a calibrated threshold which indicates that the valve relay is shorted to ground.	Valve relay output voltage / Valve relay supply voltage	< 0.10	Ignition key AND Valve relay supply voltage	= On > 5 V	0.04 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Valve Relay Circuit Performance	C106E	This monitoring strategy checks if the supply voltage (UBVR) is too low during evaluation of failsafe logic. During an undervoltage situation, an evaluation of the valve relay safety switch test is not possible. A fault is set if the supply voltage (UBVR) is below a calibrated threshold for a calibrated period of time.	Valve relay supply line voltage For time	< 5 V > 0.5 Sec	Ignition key AND Fail-Safe Logic Test	= On = On	0.5 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Vehicle Speed - Wheel Speed Correlation	P215A	This monitoring strategy checks if the ABS (Anti-lock Brake System) is correctly triggered. Normally, an ABS intervention should be applied for limited time. A fault is set if the system detects an ABS intervention for more than a calibrated period of time.	Anti-lock Brake System intervention for a period of time	> 60 Sec	System voltage AND Electronic Brake Control Unit state	> 6.9 V = Started with hardware reset	60 [Sec]	Type A, 1 Trip
		This monitor checks the wheel speed sensor signals for not plausible or invalid signals. The failure is set if at least three Wheel Speed Sensor (WSS) failure suspicions are set (at the same time). These WSS failure suspicions are set by other wheel speed monitorings.	Wheel Speed Sensor failure suspicions set	> 2	System voltage AND Ignition key	> 6.9 V = On	0.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if whether at one or at several wheels no impulse wheel or impulse wheels with wrong tooth/multiple number or wheels with a different circumference are mounted. Additionally, signal-loss caused by too high airgap between sensor and impulse wheel is detected at least over time; if another plausibility monitoring was not successful. A fault is set if an individual wheel monitor detects a deviation above a calibrated threshold but is not able to identify the faulty wheel speed sensor.	Difference between maximum and minimum wheel speed for vehicle speed OR Difference between maximum and minimum wheel speed for vehicle speed	> 3.7 mph < 12.4 mph > 6 % > 12.4 mph	Ignition key	= On	80 [Sec]	Type A, 1 Trip

18 OBDG01 BSC1 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Require	MIL illum.
		This monitoring checks for wheel speed sensor failures. A suspected wheel speed sensor failure is set if any of the following monitors set a suspected failure flag: noise monitor, slip monitor, dynamic monitor, absent signal monitor or flat tire monitor. If a wheel speed sensor failure has occurred, the Traction Control System (TCS) and the valve drift check are not available. A fault is set if more than one suspected wheel speed sensor failure occur simultaneously.	Number of suspected wheel speed sensor failures in the same time	= 2	Ignition key AND System voltage AND Ignition key	= On > 6.9 V = On	0.1 [Sec]	Type A, 1 Trip
		This monitoring checks for wheel speed sensor failures. A suspected wheel speed sensor failure is set if any of the following monitors set a suspected failure flag: noise monitor, slip monitor, dynamic monitor, absent signal monitor or flat tire monitor. If a wheel speed sensor failure has occurred, the Traction Control System (TCS) and the valve drift check are not available. A fault is set if more than one suspected wheel speed sensor failure occur simultaneously for longer than a calibrated duration.	Number of suspected wheel speed sensor failures in the same time For time	= 2 > 0.5 Sec	Ignition key AND System voltage	= On > 6.9 V	> 0.5 [Sec]	Type A, 1 Trip
		DTC Pass	Drive off and straight ahead with more than 37.2 mph for at least 40s.					
Wheel Speed Sensors Supply Circuit High	C05A3	This monitoring strategy detects wheel speed sensor supply line short to battery by monitoring reverse current.	Reverse current detected on WSS supply line for	> 3.5 Sec	Ignition key	= On	3.5 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 5sec.					
Wheel Speed Sensors Supply Circuit Low	C05A4	This monitoring strategy checks the for an undervoltage situation with the System ASIC internal hardware comparator. This comparator monitors the voltage between the wheel speed sensor (WSS) power supply line and WSS signal line. A fault is set if the voltage between the WSS power supply line and WSS signal line is under the threshold.	voltage between the WSS power supply line and WSS signal line	< 6.7 V	System voltage AND Wheel speed sensor test completed	> 6.9 V = True	0.06 [Sec]	Type A, 1 Trip
		DTC Pass	Turn ignition on and wait for at least 30sec without braking.					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake Booster Internal Power Driver Range/Performance	C0595	This monitoring strategy checks the ability of the Booster Master Switch to be switched correctly. This is done by checking in 3 steps: a) The booster master switch is switched on. After a defined period the test checks if the booster master switch is switched on by evaluating the ratio of Voltage Sensor 2 and Voltage Sensor 1	Voltage Sensor2 / Voltage Sensor1	< 0.88	Software State	= Init	0.015 [Sec]	Type A, 1 Trip
		b) The Booster Master Switch is switched off. After a defined period the Voltage Sensor 2 value is evaluated.	Voltage Sensor2	> 0.88 V	Software State	= Init	0.015 [Sec]	Type A, 1 Trip
		c) The booster master switch is switched on again. After a defined period the test checks if the booster master switch is switched on by evaluating the ratio of Voltage Sensor 2 and Voltage Sensor 1	Voltage Sensor2 / Voltage Sensor1	< 0.88	Software State	= Init	0.015 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Motor "A" Current Sensor Circuit Range/Performance	C0596	This monitoring strategy checks the functionality of the over current detection system by switching the comparator off and on. This is done by setting the pulse width modulated signal to the minimum or maximum pulse ratio. The proper comparator switching is verified by reading back the comparator's output via a feedback line. A fault is set - if the comparator's output does not indicate the correct switch position for the current pulse ratio. - if the voltage at the Booster Master Switch UB6 is not close to zero or to the power supply battery voltage (UBB), depending on the current pulse ratio.	PWM ratio VoltageSensor 2/ VoltageSensor 1 PWM ratio VoltageSensor 2	= maximum < 0.88 = minimum > 0.88 V	Software State BMS control BMS control	= Init = switched on = switched off	0.03 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for over current at the electric motor driver. Current through the motor driver is monitored by hardware and the feedback pin reports if over current has been detected. A fault is set if the feedback pin is at a high level.	Feedback pin level	logical high	Software State	=Init OR Running OR Shutdown	0.03 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake Booster Motor "A" Performance	C0594	This monitoring strategy checks if the movement of electric motor is in proper direction. This is done by: a) Checking if the sign of the target speed matches that of the actual speed. b) Checking the changes in direction of the measured electric motor speed within a period. A counter is incremented each time a change in direction is detected.	Absolute(actual electric motor speed) Or Counter	'< 15 rad/Sec > 7	Software State Absolute(target electric motor speed) Absolute(target electric motor speed)- Absolute(actual electric motor speed)	= Running OR Shutdown > 25 rad/Sec > 15 rad/Sec	0.15 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the oscillation of the i booster motor. A fault is set if the sign of the actual motor speed has changed to often within a short time interval and no change of the sign of the desired speed.	sign of the actual motor speed has changed AND Sign of the desired speed has change	= True = False	Software State AND Brake Light Switch	= Running OR Shutdown = On	0.15 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is an unintended backward rotation of the ESC electric motor. The speed controller monitor detects an unintended backward rotation of the brake booster electric motor. A fault is set if the speed deviation is greater than a threshold.	target electric motor speed - Absolute(actual electric motor speed)	> 40 rad/Sec	Software State target electric motor speed actual electric motor speed	= Running OR Shutdown > 0 rpm ≤ 1 rpm	0.015 [Sec]	Type A, 1 Trip
		DTC PASS	Apply the brake pedal for about 50% for at least 1 sec and then release the brake pedal.					
Brake Booster Motor "A" Phase U-V-W Circuit Low	C0580	This monitoring strategy checks if the gate supply voltage of the electric motor bridge driver is too low. A gate under voltage protection circuit as a part of electric motor driver circuit compares the gate supply voltage of the bridge driver with the power supply of the electric motor. A fault is set if the gate supply voltage is too low compared to the power supply of the electric motor.	Voltage Sensor 2 – Gate supply voltage	> 7 V	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Motor "A" Phase U-V-W Circuit Range/Performance	C0582	This monitoring strategy checks if two or more gate transistors out of six of the B6-bridge are shorted to each over. One high-side transistor and one low-side transistor of different electric motor phases are switched on simultaneously (all 6 combinations will be switched once within one test execution). If two gates are shorted, one transistor switches on unintentionally, leading to a very high current. A fault is set if the current exceeds a threshold.	Current	> 150 A	Software State	= Running OR Shutdown	0.004 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Motor "A" Phase U-V-W Circuit/Open	C057F	This monitoring strategy checks if MOS-FETs of electric motor driver can be controlled and actuate properly. This monitoring strategy checks if MOS-FETs of electric motor driver can be controlled and actuate properly. A fault is set if a low-side transistor is switched on and the PhaseW voltage is in range. Similarly A fault is set if a high-side transistor is switched on and the PhaseW voltage is in range.	low-side transistor PhaseW voltage / Voltage Sensor 2 OR high-side transistor PhaseW voltage / Voltage Sensor 2	switched on ≥ 0.463 switched on ≤ 0.483	Software State electric motor	= Running OR Shutdown = not controlled	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake Booster Motor "A" Phase U-V-W Current High	C0590	This monitoring strategy checks if there is a positive leakage current at the electric motor driver circuit during control. Leakage current at motor driver is monitored during inactivity of half bridge. A fault is set if the leakage current is above a threshold.	Current Sensor	> 20 A	Software State electric motor	= Running OR Shutdown = controlled	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Apply the brake pedal for about 50% for at least 1 sec and then release the brake pedal.					
Brake Booster Motor "A" Phase U-V-W Current Low	C0591	This monitoring strategy checks if the leakage current at the motor is in range low. Leakage current at motor driver is monitored during inactivity of half bridge. A fault is set if the leakage current is below a threshold.	Current Sensor	< -20 A	Software State electric motor	= Running OR Shutdown = controlled	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Apply the brake pedal for about 50% for at least 1 sec and then release the brake pedal.					
Brake Booster Motor "A" Position Sensor Circuit Range/Performance	C058A	This monitoring strategy checks if the RPS1 has a gradient failure. The Electric Motor Speed is equivalent to the gradient of the rotor rotation. A fault is set if the RPS 1 gradient exceeds a threshold.	Absolute(RPS1 gradient)	> 73 °/mSec	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the rationality of the measured electric motor backward stop position. At end of line, the electric motor backward stop position is stored at EEPROM. This monitor compares the measured electric motor backward stop position with the stored electric motor backward stop position. If there electric motor rotates more than a threshold value to move to backward stop position, a mechanical defect should be present. A negative deviation of expected rotation will be detected by PreDriveCheck monitor. A fault is set if the difference between the measured electric motor backward stop position and the stored electric motor backward stop position exceeds a threshold.	Absolute(measured electric motor backward stop position - stored electric motor backward stop position)	> 60 °	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		<p>This monitoring strategy checks for proper eBoost actuator functionality.</p> <p>(a) A command is sent to move the boost body to the backward bound position (housing).</p> <p>(b) Once the backward bound position is reached (when the boost body comes in contact with the housing), a command is sent to move the boost body forwards to the idle position.</p> <p>A fault is set if</p> <p>(a) :</p> <ul style="list-style-type: none"> - the backward position is not reached within a calibrated time, depending of last post drive check. - the electric motor is rotating in the wrong direction with a speed exceeding a threshold. <p>(b):</p> <ul style="list-style-type: none"> - the idle position is not reached within a calibrated time 	<p>Absolute(electric motor speed) electric motor moving direction OR backward bound position OR idle position</p>	<p>> 20 rad/s opposite than controlled</p> <p>not reached</p> <p>not reached</p>	Software State	= Init	3 [sec]	Type A, 1 Trip
		<p>This monitoring strategy checks the rationality of RPS1. The rotor angle is calculated internally in RPS1 IC using the raw values of the X and Y direction of the magnetic field orientation after they are internally corrected (e.g. due to off-center positioning of the sensor chip in the magnetic field).</p> <p>This internal calculation is monitored by an redundant recalculation in eBoost ECU using the transmitted X and Y raw values and correction values delivered by the rotor position sensor 1 IC. Both rotor angles, the RPS1 delivered one and the eBoost calculated one, are compared. A fault is set if the deviation between the recalculated angle and the RPS 1 angle delivered by the rotor position Sensor 1 IC exceeds a threshold.</p>	Absolute(measured RPS1 angle - recalculated angle)	> 7.8 °	Software State	= Running OR Shutdown	0.05 [Sec]	Type A, 1 Trip
		<p>This monitoring strategy checks if vector length of RPS vector does not exceed an upper threshold. A permanent magnet is located at the end of the electric motor shaft. The RPS uses the Giant Magneto Resistance (GMR) principle to measure the X and Y direction of the magnetic field. The rotor position is calculated using these raw values after they are internally corrected (e.g due to off-center positioning of the sensor chip in the magnetic field).</p> <p>At a given temperature, the vector length ($\sqrt{X^2 + Y^2}$) should be constant due to the defined magnetic field. Hence within the calibrated temperature range of -50°C to 150°C the vector length must lie within a defined range. A fault will be set if the calculated vector length is above a threshold.</p>	Calculated vector length	> 20000 digits	Software State	= Running OR Shutdown	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the vector length value from the Rotor Position Sensor (RPS) is in range low. A permanent magnet is located at the end of the brake booster motor shaft. The Rotor Position Sensor (RPS) uses the Giant Magneto Resistance (GMR) principle to measure the X and Y direction of the magnetic field. The rotor position is calculated using these raw values after they are internally corrected (e.g due to off-center positioning of the sensor chip in the magnetic field). At a given temperature, the vector length ($\sqrt{X^2 + Y^2}$) should be constant due to the defined magnetic field. Hence within the calibrated temperature range of -50°C to 150°C the vector length must lie within a defined range. A fault will be set if the calculated vector length is below a threshold.	Calculated vector length	< 3922 digits	Software State	= Running OR Shutdown	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a noise in the RPS1 vector length. By design, the vector length ($\sqrt{X^2 + Y^2}$) is almost constant, but noise or failures on the X, Y or correction values might lead to an oscillation of the vector length. A high pass filter cuts unwanted high frequencies and noise. A fault will be set if the peak amplitude of the oscillation or noise of the RPS1 vector length is greater than a threshold.	Absolute(Noise amplitude)	> 190 digits	Software State	= Running OR Shutdown	0.05 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Rotor Position Sensor Configuration Error	C1277	This monitoring strategy checks if the rotor position sensor IC configuration EEPROM cell is valid. The configuration EEPROM cells of the Rotor Position Sensor (RPS) integrated circuit are monitored to ensure that the original configuration does not change. A fault is set if at least one monitored bit in the rotor position sensor IC configuration EEPROM cells differs from expected value.	Bit value	≠ expected bit value	Software State	= Running OR Shutdown	0.02 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Rotor Position Sensor Message Counter Incorrect	C1276	This monitoring strategy checks if all RPS (Rotor Position Sensor) data are periodically updated. For the raw values, the correction values and the rotor angle, an update-flag within the RPS safety word exists which shows if all these values are periodically updated, not updated or still in the init-state. A fault will be set if the update-flag within the RPS safety word is either "not updated" or "init".	update-flag of RPS safety word OR update-flag of RPS safety word	= NOT_UPDATED = INIT	Software State	= Running OR Shutdown	0.1 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the RPS1 internal clock works properly. The life counter monitoring detects if the internal IC clock is running with the desired frequency. At each clock cycle a counter is incremented in register cell. Between two monitoring tasks, the counter is incremented in a range corresponding to the ratio of clock-frequency to monitoring-frequency. A fault will be set if the counter increment is outside the range.	Counter increment OR Counter increment	< 6 > 24	Software State	= Running OR Shutdown	0.015 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if The Cyclic Redundancy Check (CRC) is correct. A CRC is sent from the Rotor Position Sensor (RPS) IC to the eBoost ECU for all data which is checked by eBoost. A fault is set if the recalculated CRC does not match the received one.	calculated checksum	≠ received checksum	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Booster Rotor Position Sensor Unexpected Reset	C1275	This monitoring strategy checks if there was an unexpected reset at RPS. According to the specification of the Rotor Position Sensor (RPS) chip, the sensor can perform a reset under specific conditions (e.g. under voltage). If a reset happens, the position of the electric motor cannot be calculated anymore. The Hardware Related Software (HSW) checks if a reset of the sensor has happened by monitoring the reset-flag in EEPROM cell. A fault is set if the reset flag is set.	Reset-flag	= 1	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "A" Circuit High	P057D	This monitoring strategy checks if there is a circuit high at BPTS A. The brake pedal travel sensor signal A line monitor detects a short circuit to the supply voltage when no level change is detected for a period and logical signal level is high. A fault is set if there is a circuit high at BPTS A.	BPTS A signal line voltage AND rising or falling edge of BPTS A PWM	> 4.7 V = not detected	Software State	= Running OR Shutdown	0.03 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "A" Circuit Intermittent/Erratic	P057E	This monitoring strategy checks if there is a BPTS A gradient error. This monitoring is detecting the gradient only in backward direction. There is no definition possible, how quick a driver can push the brake pedal. Negative gradient monitoring is used to prevent mechanical defects. A fault is set if the gradient of signal A is out of range.	BPTS A gradient	< -2000 mm/Sec	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "A" Circuit Low	P057C	This monitoring strategy checks if there is a circuit low at BPTS A. The brake pedal travel sensor signal A line monitor detects a short circuit to ground when no level change is detected for a period and logical signal level is low. A fault is set if there is a circuit low at BPTS A.	BPTS A signal line rising or falling edge of BPTS A PWM	< 0.3 V = not detected	Software State	= Running OR Shutdown	0.03 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake Pedal Position Sensor "A" Circuit Range/Performance	P057B	This monitoring strategy checks if BPTS A is out of range high. A fault is set if the BPTS A is above a threshold.	BPTS A	> 47 mm	Software State	= Running OR Shutdown	0.04 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if BPTS A is out of range low. A fault is set if the BPTS A is above a threshold.	BPTS A	< -0.5 mm	Software State	= Running OR Shutdown	0.04 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a BPTS A communication fault. The brake pedal travel sensor module is working with a frequency of 1 kHz. This is done by checking if - the frequency of the Pulse Width Modulated signal is in range. - the duty cycle of the Pulse Width Modulated brake of pedal position sensor A is in range. A fault is set if - the frequency is out of range. - the duty cycle of BPTS A is out of range.	BPTS A PWM frequency OR BPTS A PWM frequency OR BPTS A PWM duty cycle OR BPTS A PWM duty cycle	< 879.3 1/Sec > 1127.17 1/Sec < 7.32 % > 92.83 %	Software State	= Running OR Shutdown	0.1 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "A"/"B" Correlation	P05E0	This monitoring strategy checks if there is a deviation between the two sensor channels. A fault is set if the absolute value of the difference between both signals exceeds a threshold.	Absolute(BPTS A - BPTS B) OR Absolute(BPTS A - BPTS B)	> 1 mm > 0.5 mm	BPTS A signal AND BPTS B signal OR BPTS A signal	> 42 mm > 42 mm ≤ 42 mm	0.5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if zero position of brake pedal is in range. The brake pedal travel sensor provides two separate signals with different transmissions and signal conditionings. This monitor checks if the arithmetic mean of BPTS A and BPTS B when brake pedal is not applied is within a tolerated range. A fault is set if the arithmetic mean of BPTS A and BPTS B is above a threshold.	(BPTS A + BPTS B) / 2 (BPTS A + BPTS B) / 2	> 0.6 mm < 1.5 mm	Software State	= Running OR Shutdown	0.5 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait at least 60 sec with released brake pedal while the brake system and fluid has a temperature of approximately 20C					
Brake Pedal Position Sensor "B" Circuit High	P05DE	This monitoring strategy checks if there is a circuit high at BPTS B. The brake pedal travel sensor signal B line monitor detects a short circuit to the supply voltage when no level change is detected for a period and logical signal level is high. A fault is set if there is a circuit high at BPTS B.	BPTS B signal line rising or falling edge of BPTS B PWM	> 4.7 V = not detected	Software State	= Running OR Shutdown	0.03 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "B" Circuit Intermittent/Erratic	P05DF	This monitoring strategy checks if there is a BPTS B gradient error. This monitoring is detecting the gradient only in backward direction. There is no definition possible, how quick a driver can push the brake pedal. Negative gradient monitoring is used to prevent mechanical defects. A fault is set if the gradient of BPTS B is above a threshold.	BPTS B gradient	< -2000 mm/Sec	Software State	= Running OR Shutdown	0.005 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake Pedal Position Sensor "B" Circuit Low	P05DD	This monitoring strategy checks if there is a circuit low at BPTS B. The brake pedal travel sensor signal B line monitor detects a short circuit to ground when no level change is detected for a period and logical signal level is low. A fault is set if there is a circuit low at BPTS B.	BPTS B signal line rising or falling edge of BPTS B PWM	< 0.3 V = not detected	Software State	= Running OR Shutdown	0.03 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake Pedal Position Sensor "B" Circuit Range/Performance	P05DC	This monitoring strategy checks if BPTS B is out of range high. A fault is set if the BPTS B is above a threshold.	BPTS B	> 47 mm	Software State	= Running OR Shutdown	0.04 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if BPTS B is out of range low. A fault is set if the BPTS B is above a threshold.	BPTS B	< -0.5 mm	Software State	= Running OR Shutdown	0.04 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a BPTS B communication fault. The brake pedal travel sensor module is working with a frequency of 1 kHz. This is done by checking if - the frequency of the Pulse Width Modulated signal is in range. - the duty cycle of the Pulse Width Modulated brake of pedal position sensor A is in range. A fault is set if - the frequency is out of range. - the duty cycle of BPTS B is out of range.	BPTS B PWM frequency OR BPTS B PWM frequency OR BPTS B PWM duty cycle OR BPTS B PWM duty cycle	< 879.3 1/Sec > 1127.17 1/Sec < 7.32 % > 92.83 %	Software State	= Running OR Shutdown	0.1 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Brake System Information 1 Message Counter Incorrect	C1278	This monitoring strategy checks whether the message is still alive or not. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a counter is incremented within the sending ECU. the counter value is enclosed within the message. The receiving control unit checks whether counters have been incremented. A fault is set if the counter value is not incremented.	Message 0x21B on Bus E counter halted	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the message checksum is correct. The network driver sends and receives all network messages. It also checks if the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a checksum is calculated within the sending ECU. The value of the checksum is enclosed within the message. The receiving control unit calculates the checksum again and compares it with the sent one. A fault is set if the received checksum is different from the calculated checksum.	Checksum of 0x21B on Bus E not correct	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.2 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Brake System Information 2 Message Counter Incorrect	C1279	This monitoring strategy checks whether the message is still alive or not. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a counter is incremented within the sending ECU. the counter value is enclosed within the message. The receiving control unit checks whether counters have been incremented. A fault is set if the counter value is not incremented.	Message 0x21E on Bus E counter halted	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the message checksum is correct. The network driver sends and receives all network messages. It also checks if the messages are correct (length, checksum, alive-counter, reception timeout). With each newly sent message a checksum is calculated within the sending ECU. The value of the checksum is enclosed within the message. The receiving control unit calculates the checksum again and compares it with the sent one. A fault is set if the received checksum is different from the calculated checksum.	Checksum of 0x21E on Bus E not correct	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.2 [Sec]	Type A, 1 Trip
Control Module Communication Chassis Expansion CAN Bus Off - Generic	U0077	The CAN (Control Area Network) bus E state is monitored periodically. A fault is set if the bus is in "Bus Off" state.	CAN bus E state	= Bus off	System voltage AND System voltage ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = True ≥ 5 Sec	0.09 [Sec]	Type A, 1 Trip
		This monitoring checks if the CAN initialization function has taken too long to finish . The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Software State	= Init	0.01 [sec]	Type A, 1 Trip
Control Module Communication High Speed CAN Bus Off - Generic	U0073	The CAN (Control Area Network) bus A state is monitored periodically. A fault is set if the bus is in "Bus Off" state.	CAN bus A state	= Bus off	System voltage AND System voltage ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = True ≥ 5 Sec	0.24 [Sec]	Type B, 2 Trips
		This monitoring checks if the CAN initialization function has taken too long to finish . The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Software State	= Init	0.01 [sec]	Type B, 2 Trips

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Control Module Input Power "A" Circuit High	U3502	This monitoring checks the system supply voltage. A fault is set if the voltage is greater than a calibrated threshold.	CAN supply voltage	> 16 V	Software State	= Running	0.09 [Sec]	Type B, 2 Trips
		DTC PASS	Turn ignition on and wait for at least 30sec					
Control Module Input Power "A" Circuit Low	U3501	This monitoring strategy checks if voltage sensor 3 is out of range low, which means below the HW (Hardware) switch off threshold but the HW is not switched off for the particular time. A fault is set if the voltage sensor 3 is below a threshold	Ecu supply voltage	< 4.9 V	Software State	= Running	0.2 [Sec]	Special Type C
		This monitoring checks the system supply voltage. A fault is set if the voltage is less than a calibrated threshold.	CAN supply voltage	< 7.5 V	Software State	= Running	0.09 [Sec]	Special Type C
		DTC PASS	Turn ignition on and wait for at least 30sec					
Control Module Input Power "B" Circuit/Open	U3007	A fault is set if the Voltage Sensor 1 voltage drops below a threshold.	Voltage Sensor 1	< 2 V	Software State	= Running OR Shutdown	0.1 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Control Module Input Power "B" Circuit High	U3506	This monitoring strategy checks the power supply battery (UBB) voltage. A fault is set if the UBB detection voltage is above the voltage limit for an extended period of time.	UBB AND Period of time	> 17 V = 90 Sec	Software State	= Running OR Shutdown	90 [Sec]	Type B, 2 Trips
		This monitoring strategy checks the range of the supply voltage of the complex device driver module. A fault is set if this voltage is above a calibrated threshold.	Complex device motor voltage	> 18 V	Software State	= Running OR Shutdown	1.1 [Sec]	Type B, 2 Trips
		This monitoring strategy checks the power supply battery (UBB) voltage. A fault is set if the performance is reduced due to a voltage UBB above the level 1.	UBB AND Period of time	> 16.5 V = 1.1 Sec	Software State	= Running OR Shutdown	1.1 [Sec]	Type B, 2 Trips
		DTC PASS	Turn ignition on and wait for at least 90sec					
Control Module Input Power "B" Circuit Low	U3505	This monitoring strategy checks if Voltage Sensor 1 is out of range low. A fault is set if the voltage sensor 1 is below a threshold.	Voltage Sensor 1	< 6 V	Software State	= Running OR Shutdown	30 [Sec]	Special Type C
		This monitoring strategy checks the power supply battery (UBB) voltage. A fault is set if the UBB detection voltage is below the voltage limit for an extended period of time.	UBB AND Period of time	< 9.3 V = 90 Sec	Software State	= Running OR Shutdown	90 [Sec]	Special Type C
		This monitoring strategy checks the range of the supply voltage of the complex device driver module. A fault is set if the voltage is less than a threshold.	Complex device motor voltage	< 6 V	Software State	= Running OR Shutdown	0.2 [Sec]	Special Type C

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks the power supply battery (UBB) voltage. A fault is set if the system performance is reduced due to low voltage under level 1.	UBB	< 9.3 V	Software State	= Running OR Shutdown	0.2 [Sec]	Special Type C
		This monitoring strategy checks the power supply battery (UBB) voltage. A fault is set if the system performance is reduced due to low voltage under level 2.	UBB	< 7.5 V	Software State	= Running OR Shutdown	0.2 [Sec]	Special Type C
		DTC PASS	Turn ignition on and wait for at least 90sec					
Control Module Input Power "C" Circuit High	U350A	This monitoring strategy checks if Voltage Sensor 2 is out of range high. A fault is set if the Voltage Sensor 2 is above a threshold.	Voltage Sensor 2	> 19.8 V	Software State AND vehicle speed	= Running OR Shutdown > 4 mph	90 [Sec]	Type A, 1 Trip
		DTC PASS	Drive straight ahead for at least 3.1 mile					
Control Module Input Power "C" Circuit Low	U3509	This monitoring strategy checks if Voltage Sensor 2 is out of range low. A fault is set if the Voltage Sensor 2 is below a threshold.	Voltage Sensor 2	< 6 V	Software State AND vehicle speed	= Running OR Shutdown > 4 mph	90 [Sec]	Type A, 1 Trip
		DTC PASS	Drive straight ahead for at least 3.1 mile					
Control Module Input Power Circuit "A/B" Correlation	U3018	This monitoring checks if the battery power supply (UBB) is not too low compared to the ECU power supply to ensure a reliable switching of the Booster Master Swith. A fault is set if the difference between UBB and UB_ECU is higher than a threshold	UBB - UB_ECU	> 7 V	Software State	= Init OR Running OR Shutdown	0.01 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the battery can provide enough power to the system. The central coordinator component in Electric Brake Booster Control Module is used to coordinate some initial tests and specific cyclic Electric Brake Booster Control Module Monitoring which depends on each other. A prerequisite for all initial tests except for the failsafe logic handler test is a sufficient Electric Brake Booster Control Module Power Supply Battery UBB. If the voltage is too low, the coordinator tests are delayed. During initial phase, all tests must be done once. If the initial phase takes too long, an undervoltage situation is given. A fault is set if any tests are initially delayed.	UBB OR [UBB_ECU AND UBB-UBB_ECU] OR [UBB_ECU AND UBB-UBB_ECU]	< 6 V > 8.5 V > 3.5 V ≤ 8.5 V > 1.5 V	Software state	= Init	0.5 [sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Control Module Input Power Circuit "B/C" Correlation	U3019	This monitoring strategy checks Voltage divider drift between the booster circuit supply line (Voltage Sensor 1) and the Motor Driver supply line (Voltage Sensor 2). A fault is set if the ratio of Voltage Sensor 1 and Voltage Sensor 2 is outside a range.	Voltage Sensor 2/Voltage Sensor 1	> 1.321	Software State	= Running OR Shutdown	2 [Sec]	Type A, 1 Trip
			OR Voltage Sensor 2/Voltage Sensor 1	< 0.766				
		DTC PASS	Turn ignition on and wait for at least 5sec					

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Control Module Internal Performance	P0606	This monitoring strategy checks the proper functionality of the CPU Compare Module. The software is executed on 2 CPU cores simultaneously instruction by instruction (lock step mode). The output of both cores is compared by the CPU Compare Module. A self test runs at Init to verify that the CPU Compare Module is working properly. A fault will be set if the selftest failed.	Core Compare Module selftest	= failed	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if there is a CPU exception. A fault is set if a data abort, a prefetch abort, or an undefined instruction occurs.	Data abort occurs OR Prefetch abort occurs OR Undefined instruction occurs	= True = True = True	Software State	= Init OR Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks if the execution of a sensitive process task jitters too much. A fault is set if the real process execution time is greater than its ideal start time increased by a percentage.	The execution time of the internal system process task (ibooster systems)	> Ideal Time + 10% s	Software State	= Init OR Running OR Shutdown	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the reference voltage of A/D-converter is out of range. A fault is set if the bandgap voltage of the ADC is outside the allowable range.	Analog Digital Converter bandgap voltage OR Analog Digital Converter bandgap voltage	< 1145 V > 1345 V	Software State	= Init OR Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy tests whether the system chip detects a missing watchdog trigger. At Initialization, the safety controller switches off the BMS. At switched off the BMS, a watchdog trigger is expected. If this trigger is missed, A fault is set. A fault is set if BMS switched off does not set a watchdog trigger.	Watchdog trigger AND BMS gate	missed not switched off	Software State	= Init	1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the motor driver circuit is able to be switched off and on. The electric motor driver switching (on/off) is tested by the microcontroller and the safety controllers to detect any short-circuit or interruption of the enable signal line. A fault is set if the electric motor driver is not properly switched off and on.	(Command sent : AND Motor Driver) OR (Command sent : AND Motor Driver)	switch off enabled switch on disabled	Software State	= Init	1 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the error pin event counter is in range. The monitor pulls the error pin to test the event counter within the system chip. To prevent an electrical shutdown (which would disturb communication) during the provoked error pin event, the electrical decouple bit is set. A fault is set if the error pin event counter does not increment, or if the decouple bit is not reset.	Error pin event counter not incremented	= True	Software State	= Running	1 [sec]	Type A, 1 Trip
		This monitoring strategy checks if there is a High End Timer (HET) exception. A fault is set if a failure is detected in the EEPROM cell.	Failure detected in register of High End Timer	= True	Software State	= Init OR Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks for proper of the High End Timer Transfer Unit (HETTU) addressing functionality. When a pointer error is detected, the HETTU state switches to a specific value. A fault is set if the HETTU is in the pointer error state.	High End Timer Transfer Unit Status	= "pointer error"	Software State	= Init OR Running OR Shutdown	Immediately	Type A, 1 Trip
		This monitoring strategy checks the High End Timer Transfer Unit (HETTU) internal bus. A fault is set if a bus error is detected.	High End Timer Transfer Unit Status	= "bus error"	Software State	= Init OR Running OR Shutdown	Immediately	Type A, 1 Trip
		This monitoring strategy checks the High End Timer Transfer Unit (HETTU) internal bus. A fault is set if a bus error is detected.	High End Timer Transfer Unit Status	= "busy bit error"	Software State	= Init OR Running OR Shutdown	Immediately	Type A, 1 Trip
		This monitoring strategy checks if there was a High End Timer Transfer Unit (HETTU) exception. A fault is set if an exception occurs.	Failure detected in register INT	= True	Software State	= Running	Immediately	Type A, 1 Trip
		This monitoring strategy checks if the eBoost internal motor driver enable signal line or the electrical enable signal line are in logical low. It is expected that the enable signal lines always stay at a high voltage level (except when the SW intends a different state). A fault is set if at least one of the pins reports a logical low.	Pin level of Motor Driver enable line OR Pin level of electrical enable line	= 0 (logical low) = 0 (logical low)	Software State AND failsafe logic test	= Running OR Shutdown = Finished	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if there was a task failed to call. A fault will be set if a task did not start in the expected time.	Watchdog detects a missing task	= True	Software State	= Init OR Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks the system integrated circuit watchdog fault counter. A fault is set if this error counter exceeds a threshold.	Error counter	> 3	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks if the watchdog trigger is received as expected. An incorrect watchdog trigger signal is sent to the system chip watchdog function, which increments the watchdog error counter. A fault is set if the watchdog fault counter is not incremented.	Incorrect watchdog data sent to chip	= True	Software State	= Running OR Shutdown	1 [sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if all possible watchdog triggers are received within a certain time by the system chip. A fault will be set if not all watchdog tasks are done in a certain period.	Number of watchdog tasks done	< Number of watchdog tasks	Software State	= Running OR Shutdown	0.45 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the status of the watchdog. During the initialization test the watchdog status feedback from the system chip is tested against several patterns according to the ongoing sub test. A fault is set if the watchdog status is not as expected.	Watchdog status	≠ expected watchdog status	Software State	= Running OR Shutdown	1 [sec]	Type A, 1 Trip
		This monitoring strategy checks the status of the watchdog. After the Init test has finished, the status of the watchdog respectively the safety logic is being continuous Monitored. A fault will be set if the status is not as expected.	Watchdog status	≠ expected watchdog status	Software State	= Running OR Shutdown	0.05 [Sec]	Type A, 1 Trip
		This monitoring strategy checks correct handling of NMI. The Error Signal Module is the central module at the microcontroller level; it handles severe microcontroller core failures or peripheral failures, and coordinates the logic tests during start-up. A fault is set if the Non-Maskable Interrupt handler detects a failure During Init tests.	Non-Maskable Interrupt occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if a severe microcontroller core or peripheral failure occurred. The Error Signal Module (ESM) is the central module at the microcontroller level; it handles severe microcontroller core or peripheral failures. A fault is set when severe microcontroller core or peripheral failures occurred.	A microcontroller core failure via Error Signal Module is detected OR Peripheral failure via ESM is detected	= True = True	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks whether the HET has the proper reference signal frequency. The monitor compares the defined frequency with the actual reference signal frequency, which is calculated by the HET. A fault is set if the difference between the defined frequency and the actual frequency exceeds a threshold.	Absolute(Defined frequency - calculated frequency) / defined frequency	> 0.05	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		<p>This monitoring strategy tests the Serial Peripheral Interface (SPI) functionality and failure handling of the Application Specific Integrated Circuits (ASIC) used in the system. To do so, the SPI component provides special functions to perform the following tests :</p> <ul style="list-style-type: none"> - reading from/writing to an undefined address EEPROM cell - writing to a non-writable EEPROM cell - reading a EEPROM cell with a parity failure during transmission - reading a EEPROM cell with a clock failure during transmission <p>For each of these tests, a certain fault response is expected from the ASIC. A fault is set if at least one fault response does not match the expected one.</p>	<p>No or wrong fault response from ASIC while reading from an undefined address register</p> <p>OR</p> <p>No or wrong fault response from ASIC while writing to an undefined address register</p> <p>OR</p> <p>No or wrong fault response from ASIC while writing to a non-writable register</p> <p>OR</p> <p>No or wrong fault response from ASIC while reading a register with a parity error in frame 1 during transmission</p> <p>OR</p> <p>No or wrong fault response from ASIC while reading a register with a parity error in frame 2 during transmission</p> <p>OR</p> <p>No or wrong fault response from ASIC while reading a register with a clock failure (less clock pulses) during transmission</p> <p>OR</p> <p>No or wrong fault response from ASIC while reading a register with a clock failure (more clock pulses) during transmission</p>	<p>= True</p> <p>= True</p> <p>= True</p> <p>= True</p> <p>= True</p> <p>= True</p> <p>= True</p>	Software State	= Init	immediately	Type A, 1 Trip
		<p>The monitoring checks the received data by the Application Specific Integrated Circuit (ASIC). The ASIC of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). A fault is set if not all data has been transmitted or received.</p> <p>Parity check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if the calculated parity does not match the parity bit.</p> <p>Bit check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if at least one bit of the actual transmitted data is not equal to the transmit bit in register.</p> <p>Rationality check - The ASICs of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). When ASIC detects a transmission failure, it sends an error frame via the SPI. The monitoring checks the frames transmitted via the SPI. A fault is set if a wrong frame is transmitted.</p>	<p>Length of received data</p> <p>OR</p> <p>Calculated parity of the received data</p> <p>OR</p> <p>Time out error</p> <p>OR</p> <p>Actual transmitted bits</p> <p>OR</p> <p>Clock failure</p> <p>OR</p> <p>Data received</p>	<p>≠ length of send data</p> <p>≠ received parity bit</p> <p>= True</p> <p>≠ bits in register</p> <p>= True</p> <p>≠ bits in register</p>	Software State	= Init OR Running	0.001 [sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if there is a Serial Peripheral Interface (SPI) communication failure. The Application Specific Integrated Circuits (ASIC) of the system are connected to the microcontroller via a SPI. The microcontroller includes hardware Monitoring of the ASIC to recognize failures of the necessary input signals. The Monitor reads the results of certain of this hardware Monitoring by reading out the ASIC EEPROM cell via Serial Peripheral Interface. A fault is set if charge-pump failure bit, or clock-input-signal failure bit, or internal-oscillator-circuit failure bit is set.	Charge-pump failure bit is set OR Clock-input-signal failure bit is set OR Internal-oscillator-circuit failure bit is set	= True = True = True	Software State	= Init	0.2 [Sec]	Type A, 1 Trip
		This monitoring strategy checks the voltage comparators of the ASIC. The Application Specific Integrated Circuit (ASIC) has several voltage comparators to monitor the level of different voltage supplies. These comparators are tested at start-up for correct functionality, and the result of the test is stored as a EEPROM cell value. A fault is set if there is an error flag when the monitor reads the EEPROM cell value.	Error flag is set in a defined register	= True	Software State	= Init	Three consecutive ignition cycles	Type A, 1 Trip
		This monitoring strategy checks if there is a timeout of the Serial Peripheral Interface (SPI) communication to Application Specific Integrated Circuit (ASIC). The Application Specific Integrated Circuit (ASIC) of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). The goal is to monitor the duration of the SPI transmission. A fault is set if the SPI transfer to ASIC is not finished within a defined period.	Duration of SPI transfer to ASIC	> 0.005 Sec	Software State	= Init	0.05 [Sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		<p>The monitoring checks the received data by the Application Specific Integrated Circuit (ASIC). The ASIC of the system is connected to the microcontroller via a Serial Peripheral Interface (SPI). A fault is set if not all data has been transmitted or received.</p> <p>Parity check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if the calculated parity does not match the parity bit.</p> <p>Bit check - The ASIC of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). The monitoring checks the received data by the ASIC. A fault is set if at least one bit of the actual transmitted data is not equal to the transmit bit in register.</p> <p>Rationality check - The ASICs of the system is connected to the microcontroller via a serial Peripheral Interface (SPI). When ASIC detects a transmission failure, it sends an error frame via the SPI. The monitoring checks the frames transmitted via the SPI. A fault is set if an error frame is transmitted.</p>	<p>Length of received data OR Calculated parity of the received data OR Clock failure OR Actual transmitted bits OR Error frame received</p>	<p>≠ length of send data ≠ received parity bit = True ≠ bits in register ≠ bits in register</p>	Software State	= Init OR Running OR Shutdown	0.05 [sec]	Type A, 1 Trip
		This monitoring strategy checks if there was an exception in Operating System. A fault is set if an exception occurs in the Operating System.	OS-exception occurs	= True	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks if the Static Random Access Memory (SRAM) and peripheral Random Access Memory (RAM) are initialized or not. The SRAM and peripheral RAM are cleared at power-up. Then this Monitoring reads every SRAM and RAM addresses. A fault will be set if at least one adresse is not initialized to zero.	At least one RAM or SRAM bit	≠ 0	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if a wrong hexfile was flashed in the AECU. The purpose of RTP pins is to do measurement of RAM variables. A fault is set if the RTP Enable pin is stuck to a high.	RTP Enable pin stuck to high	= True	Software State	= Init	Immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		The System Mode Manager (SMM) asks in parallel with multiple system modes for the individual modules. To do this, it receives requests from different parts of software which are initialized at the beginning and after a while a valid value is given which is not "init" value. A fault is set if after a while one requester is still in init value.	One requester still in init value for time	> 3.6 Sec	Software State	= Running	3.6 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if the microcontroller stack has over or underflowed. During initialization, stack memory cells are set at the beginning and at the end of the stack area: these Stack memory cells are checked periodically. A fault is set if one of these Stack memory cells has been overwritten.	End-stack word overwritten OR Beginning-stack word overwritten	= True = True	Software State	= Init	0.04 [sec]	Type A, 1 Trip
		This monitoring strategy checks the time to configure the Application Software, during the system startup. A fault will be set if it lasts longer than a defined period.	ASW configuration time	> 5 Sec	Software State	= Init	5 [Sec]	Type A, 1 Trip
		This monitoring strategy checks for an unsupported Bootblock and FSW clock configuration in ECU. Within an ECU, the Bootblock allows actualizing the application which is called FSW. A failure is set if the Bootblock and FSW clock settings are different.	Bootblock and FSW clock settings are different	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring strategy checks if an internal fault has occurred in the operating system. A fault is set if software interrupts have occurred but: - the interrupt is invalid. - An interrupt lock release is called without previous lock. - not all interrupts are released.	Software interrupt occurred AND { Invalid interrupt occurred OR Interrupt lock release is called without previous lock OR Not all interrupts are released OR Interrupt lock time }	= True = True = True = True > 0.001 Sec	Software State	= Init OR Running OR Shutdown	Immediately	Type A, 1 Trip
		This monitoring strategy checks if interrupts are properly running. The error signal module is the central module in the microcontroller level. It handles severe microcontroller core failures or peripheral failures, and coordinates the logic tests during start-up. A fault is set if no or not expected non-maskable interrupt occurs during Init tests.	Failure detected during safety logic startup tests	= True	System voltage	> 6.9 V	Immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the software is properly configured for the hardware. Software version and device identifiers of the Application Specific Integrated Circuit (ASIC) and of the microcontroller are compared with the software version and identifiers of the configuration software. A fault is set if a least one ID or software version does not match.	Received ID of microcontroller is not identical with the ID stored in the software	= True	Software State	Init	0.03 [sec]	Type A, 1 Trip
		This monitoring strategy checks if there are internal and input signal failures of the Application Specific Integrated Circuit (ASIC). The ASIC is connected to the microcontroller by Serial Peripheral Interface (SPI). The monitor reads the results of this hardware monitoring EEPROM cell using Serial Peripheral Interface. The bits of the EEPROM cell are set by the hardware logic "Voltage-Pre_regulator-Mode". A fault is set if the voltage-pre-regulator-mode failure bit is set.	Voltage-pre-regulator-mode failure bit is set	= True	Software State	= Running OR Shutdown	0.2 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 30sec					
Control Module Long Term Memory Performance	P062F	This monitoring checks for a plausible EEPROM ceel defect. A fault is set if the "gap lap adjust" correction factor can not be read from the EEPROM	Gap lap adjust correction factor can not be read	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring strategy checks for a plausible EEPROM cell defect. A fault is set if the update of the plant Jump-In Gain adjustment failed.	Update of Plant Jump-In Gain Adjustment failed	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring strategy checks if there is enough available space in the EEPROM (Electronically Erasable Programmable Read-Only Memory) to allocate a data field. A fault is set if the size of the data field is bigger than the amount of available space in EEPROM.	Data field size to allocate	> Available Space	Software State	= Init OR Running OR Shutdown	immediately	Type A, 1 Trip
		This monitoring strategy checks if it is possible to write data in persistent storage. Every write access to non-volatile memory in the EEPROM (Electronically Erasable Programmable Read-Only Memory) is protected by timeout monitoring and data verification after writing. The Persistent Data Manager checks persistent data access in EEPROM. A fault is set if a write operation occurs or if data verification after writing fails.	Writing operation	> 0.025 Sec	Software State	= Running	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy check if the the Master Cylinder pressure sensor offset can be written. A fault is set if the value can not be written in the EEPROM during postrun	write failure occurred	= True	Software State	= Shutdown	immediately	Type A, 1 Trip
		This monitoring checks if there is no write failure during the system shutdown phase. A fault is set if values can not be written in the EEPROM during postrun	write failure occurred	= True	Software State	= Shutdown	0.02 [Sec]	Type A, 1 Trip
		This monitoring checks the CAN initialization function has taken too long to finish . The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Software State	= Running	0.02 [Sec]	Type A, 1 Trip
		This monitoring checks the CAN initialization function has taken too long to finish . The access to message Ram by the CAN-Core is handle through a message interface register. In each cycle a CAN register bit is checked to determine if the bit is set. A fault is set if the loop lasts longer than a threshold	Number of CAN cycles	> 1000	Software State	= Running	0.02 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Control Module Long Term Memory Reset	P0603	This monitoring cheks for a plausible EEPROM cell defect. A fault is set if the regenerative braking counter value can not be read from the EEPROM	Regenerative braking counter value can not be read	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring checks for a plausible EEPROM cell defect. A fault is set if the delta dead volume of the Pression-Volume (pV) characteristics can not be read from the EEPROM	Delta dead volume of the pV characteristics can not be read	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring cheks for a plausible EEPROM cell defect. A fault is set if the Pressure-Volume characteristics correction factor can not be read from the EEPROM.	Pressure-Volume characteristics correction factor can not be read	= True	Software State	= Init	Immediately	Type A, 1 Trip
		This monitoring strategy checks the stored value of Elektric Motor idle position. The rotor idle position is written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault will be set if the stored value of the "Motor_IdlePositionTravel" could not be read from EEPROM cell.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if there is no calibration of electric motor idle position. The rotor idle position is written to a EEPROM cell of an EEPROM at end of production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the stored Electric Motor angle at the lower end stop position can be read. The brake booster electric motor angle at the lower end stop position is measured and written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This Monitoring checks that one value of the eBoost basic Init conditions is available. The brake booster motor angle at backwards bound is measured and written to an EEPROM cell at end of production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if there is a reading problem of the EEPROM. The plunger release position is written to an EEPROM cell of an EEPROM at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if data in EEPROM is empty. The plunger release position is written to a EEPROM cell the end of production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the customer identifier is correct. At Init, the persistent data manager checks the mismatch of the EEPROM cell value and expected customer ID. A fault is set if the expected customer ID does not match with the stored customer ID.	Stored customer ID	≠ expected customer ID	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the system do not find the enhanced platform software end marker which is use to help the system to find the end of data. At ignition state the Persistent Data Manager checks the content of the EEPROM. A fault is set if the enhanced platform software end marker has not been found.	No enhanced platform software end marker in EEPROM	= True	Software State	= Init	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks the stored data field size is correct. At Ignition State, the Persistent Data Manager checks the content of the EEPROM. A fault is set if a data field size in EEPROM does not match data item configuration in software.	Data field size in the EEPROM	≠ data size configuration in software	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks the reading accessibility of the EEPROM. At Init, the Persistent Data Manager checks the content of the EEPROM. A fault is set if an access error occurs while reading the EEPROM.	Read error occurs OR Not expected Non-Markable Interrupt detected	= True = True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if a stored BPTS value can be read. The BPTS detects the position of the brake pedal. Before providing proper values, the BPTS has to be calibrated using calibration values stored in an EEPROM cell. This EEPROM cell is read during the eBoost initialization state. A fault is set if a read failure occurs.	read failure occurred	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the calibrations value of the Brake Pedal Travel Sensor (BPTS) is empty. The BPTS provides two separate signals with different transmissions and signal conditionings. Each signal is calibrated at end of production line, and calibration values are written to a cell of an EEPROM. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the calibrated position value can be read. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in an EEPROM cell. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the calibrated offset value can be read. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in an EEPROM cell. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the calibrated offset value is empty. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in a EEPROM cell in an EEPROM memory. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the calibrated value can be read. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in an EEPROM cell in an EEPROM memory. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the calibrated offset value can be read. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in an EEPROM cell. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the calibrations value is empty. The Brake Pedal Travel Sensor (BPTS) detects the position of the brake pedal. Before providing proper values, it has to be calibrated by using calibration values stored in an EEPROM cell. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks the compensation of the 1, 2, 6 or 8 order of RPS signal. A fault is set if the compensation of 1, 2, 6 or 8 order of RPS signal is not working due to a lack of informations of the EEPROM.	Lack of information of the EEPROM for RPS	= True	Software State	= Init	0.005 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if a stored value of RPS x-value offset could be read. The correction value for the X raw signal of the Rotor Position Sensor (RPS) is written to an EEPROM cell at end of production line. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the offset of the X-value of RPS is empty. The correction value for the X raw signal of the Rotor Position Sensor (RPS) is written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if a stored value of RPS y value offset could be read. The correction value for the Y raw signal of the Rotor Position Sensor (RPS) is written to an EEPROM cell at end of production line. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the offset of the Y-value of RPS is empty. The correction value for the Y raw signal of the Rotor Position Sensor (RPS) is written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if a stored value of RPS synchronicity could be read. The amplitude synchronicity of the X and Y raw values of the Rotor Position Sensor (RPS) is written to an EEPROM cell at end of production line. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the EEPROM cell which contains the offset of the X-value of RPS is empty. The amplitude synchronicity of the X and Y raw values of the Rotor Position Sensor (RPS) are written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the Rotor Position Sensor (RPS) offset can be read. The RPS offset is written to an EEPROM cell at end of production line. This EEPROM cell is read at Init State. A fault is set if a read failure occurs.	Read failure occurs	= True	Software State	= Init	immediately	Type A, 1 Trip
		This monitoring strategy checks if the EEPROM cell which contains the offset of the RPS is empty. The rotor idle position is written to an EEPROM cell at the end of the production line. This EEPROM cell is read at Ignition State. A fault is set if the EEPROM cell is empty.	Register is empty	= True	Software State	= Init	immediately	Type A, 1 Trip
		DTC PASS	Turn ignition off and wait at least 90 sec, turn ignition on and wait 5sec					
Control Module Random Access Memory (RAM)	P0604	This monitoring strategy checks the values of a specific RAM area. Furthermore, the address decoder is tested using test patterns to ensure bus integrity. The test writes different patterns at the addresses of this RAM area. Addresses are then read out and a signature for all the readout values is calculated. The original content in RAM is afterwards rewritten. The order of the patterns is chosen so that the signature the multibit and coupling failures can be set during the signature evaluation. A fault is set if a multibit or coupling failure is detected.	Multi-bits failure detected OR Coupling failure detected OR Address decoder test detects an error	= True = True = True	System voltage	> 6.9 V	Immediately	Type A, 1 Trip
		This monitoring strategy checks correct functionality of Random Access Memory (RAM). A programmable Built In Self Test runs in start-up phase. It is a test implemented in hardware, triggered and evaluated in software. A fault is set if the memory test detects a failure.	Memory test detects a fault	= True	Software State	= Init	Immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if there is a single bit error at RAM. Because of Error Correction Code, RAM single-bit errors are always corrected. A fault will be set if the number of bit errors exceeds a threshold.	Number of detected single-bit errors	> 2	Software State	= Running OR Shutdown	immediately	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Control Module Read Only Memory (ROM)	P0601	This monitoring strategy checks the correct CRC of Flash EEPROM. Initially and cyclically the complete Flash EEPROM contents is checked by calculating a CRC value and comparing it with the checksum generated during the software build process. A fault is set if a double bit error of Flash EEPROM is detected, or if more than a number of single bit errors are detected (otherwise single bit errors are corrected).	Double bit error detected OR Number of detected single bit errors	= True > 1	Software State	= Init OR Running OR Shutdown	immediately During Startup or respectively after 60 sec for cyclic flash checksum test.	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Extended Brake Pedal Travel	C0075	This monitoring strategy checks if the differential stroke is in range. Due to a mechanical coupling of the boost body and the pedal travel sensor, the differential stroke can only have defined range. A fault is set if the differential stroke exceeds the range.	brake pedal stroke - boost body stroke	< - 5.0 mm	Software State	= Running OR Shutdown	0.04 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Ignition Switch - Accessory Position - Circuit Low	P2537	Detects an accessory position circuit open	Accessory	= False	Propulsion System Active Propulsion System Active Time	= True > 0.5 Sec	0.5 [sec]	Type B, 2 Trips
Ignition Switch - Circuit High	P2535	Detects if the Run/Crank input circuit is high	Short to Battery	> 5 V	CAN Communication And ECM Run/Crank Active Data	= Enabled = False	2.5 [sec]	Type A, 1 Trip
Ignition Switch - Circuit Low	P2534	Detects if the Run/Crank input circuit is low	Short to Ground Or Open Condition	< 2 V = True	CAN Communication And ECM Run/Crank Active Data	= Enabled = Active	2.5 [sec]	Type A, 1 Trip
Internal Control Module A/D Processing Performance	P060B	This monitoring strategy checks the conversion time of the ADC (Analog Digital Converter). The ADC periodically reads an analog signal and converts it into digital values. Before starting a new conversion, the monitor checks that the previous conversion is finished. A fault is set if the previous conversion is not finished for a number of checks.	number of conversions which could not be finished in time	> 9	Software State	= Running	0.003 [sec]	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks proper functionality of ADC self-test. To do this, ADC channels are switched to two predefined internal microcontroller resistors to measure defined (voltage) levels (high and low). The absolute differences between the two measurements are calculated in unit digits. A fault will be set if the difference is greater than a threshold.	Absolute(difference between the two ADC measurements)	> 540 digits	Software State	= Running	0.2 [sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Lost Communication with Brake System Control Module on Bus E	U1833	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x21B not received on Bus E	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x21E not received on Bus E	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
Lost Communication With ECM/PCM "A"	U0100	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0xC9 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.25 [sec]	Type B, 2 Trips
		This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x4C1 not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	1.25 [sec]	Type B, 2 Trips

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
Lost Communication With Hybrid Powertrain Control Module	U0293	This monitoring strategy checks if no messages are sent. The network driver has to send and receive all network messages. At the same time it has to check that the messages are correct (length, checksum, alive-counter, reception timeout). The diagnostic performs a Time out check. A fault is set if no message is received within a defined amount of time.	0x1DF not received on Bus A	= True	System voltage AND System voltage AND Bus Off Fault Active ECU is sending/receiving on CAN AND ECU Power Mode transition diagnostic enable delay timer	> 7.5 V < 16 V = False = True ≥ 5 Sec	0.1 [Sec]	Type A, 1 Trip
Sensor Reference Voltage "A" Circuit Range/Performance	P06A6	This monitoring strategy checks if the BPTS supply voltage is in range. The Brake Booster Electronic Control Unit (ECU) evaluates the supply voltage of the brake pedal position sensors. A fault is set if the supply voltage is outside of a certain range.	BPTS supply voltage OR BPTS supply voltage	< 4.68 V > 5.32 V	Software State	= Init OR Running OR Shutdown	0.06 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Sensor Reference Voltage "B" Circuit Range/Performance	P06A7	This monitoring strategy checks if the RPS1 supply voltage is in range. Periodically the RPS1 IC transmits a safety word together with raw values. The voltage-flag of the RPS1 safety word indicates either one of the following errors (failure modes cannot be distinguished): • Under voltage error • Over voltage error • Open circuit A fault is set if the voltage-flag of the RPS1 safety word is set.	voltage-flag of RPS1 safety word set	= True	Software State	= Running OR Shutdown	0.02 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
Sensor Reference Voltage A Circuit Low	P0642	This monitoring strategy checks if the BPTS supply under voltage. A fault is set if BPTS under voltage is caused by Voltage Sensor3 under voltage.	BPTS supply voltage AND Voltage Sensor3	< 4.68 V < 5.6 V	Software State	= Running OR Shutdown	0.06 [Sec]	Type A, 1 Trip
		DTC PASS	Turn ignition on and wait for at least 5sec					
System Configuration Error	C1449	This monitoring strategy checks if the calibrated idle position can be reached at the end of BPTS calibration routine at end of production line.	Idle position not reached	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if all written BPTS calibration values can be read at the end of production line.	read failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the BPTS calibration routine has been completed at the end of production line	Calibration routine aborted	= True	Software State	= Diag	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring checks if the pre drive check is missed at the end of the production line	Pre drive check missed	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if measured value for idle position at OES calibration routine can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if measured electric motor angle value at OES calibration routine can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the measured value of punger release position at OES calibration routine can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the BPTS hysteresis value can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the BPTS1 offset based on mounting position can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the BPTS2 offset based on mounting position can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the calibration value of BPTS1 has been written at the end of production line.	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the calibration value of BPTS2 has been written at the end of production line.	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the RPS1 X value offset can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip
		This monitoring strategy checks if the offset Y value of RPS1 can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip

18 OBDG01 BSC2 Summary Tables

Component/ System	Fault Code	Monitor Strategy Description	Malfunction Criteria	Threshold Value	Secondary Parameters	Enable Conditions	Time Required	MIL illum.
		This monitoring strategy checks if the synchronicity value of RPS1 can be written. A fault is set if the value can not be written in the EEPROM at the end of the production line	write failure occurred	= True	Software State	= Diag	immediately	Type A, 1 Trip