

**Mode \$06 data definitions for  
2003 Cadillac CTS w/ 3.2L LA3**

<b>Test ID (hex)</b>	<b>Type of Test Limit (see footnote on last page) and Comp ID (hex)</b>	<b>Description</b>	<b>Decimal Range</b>	<b>Hex Range</b>
<b>Enhanced Evaporative Emission System Monitor</b>				
05	0C	Rough leakage test	0 to 3276.75 seconds	0000 to FFFF
05	0D	Leakage flow test small leakage	0 to 2.6214 m <sup>3</sup> /h	0000 to FFFF
05	8A	Purge Valve Stuck Open	- 32.0143 to 32.0143 hPa	0000 to FFFF
05	8B	Canister Vent Valve Stuck Closed	- 32.0143 to 32.0143 hPa	0000 to FFFF
05	11	Canister Vent Valve Stuck Open	0 to 3276.75 seconds	0000 to FFFF
05	12	Fuel Tank Pressure Sensor not responding	0 to 3276.75 seconds	0000 to FFFF
05	13	Gross Leak	0 to 3276.75 seconds	0000 to FFFF
05	94	Purge Valve Stuck Closed	-32.0143 to 32.0143 hPa	0000 to FFFF
<b>Catalyst Efficiency Monitor</b>				
01	05	Catalyst Oxygen Storage Factor - Bank 1	0 to 1 factor	00 to FF
01	06	Catalyst Oxygen Storage Factor - Bank 2	0 to 1 factor	00 to FF
<b>Thermostat Monitor</b>				
09	0A	Thermostat Monitoring - difference - Model versus Actual	0 to 191.25 °C	0000 to FFFF

**Mode \$06 data definitions for  
2003 Cadillac CTS w/ 3.2L LA3**

Test ID (hex)	Type of Test Limit <i>(see footnote on last page)</i> and Comp ID (hex)	Description	Decimal Range	Hex Range
<p>footnote:</p> <p>bit 7:</p> <p>Most significant bit indicates type of test limit, where:</p> <p>0 - test limit is maximum value - test fails if test value is greater than this value</p> <p>1 - test limit is minimum value - test fails if test value is less than this value</p> <p>If the test result should be within a range of values, two messages will be returned, one with the maximum value and one with the minimum value.</p> <p>bit 6 - bit 0</p> <p>Component ID - manufacturer defined - necessary when multiple components or systems are present on the vehicle and have the same definition of test ID.</p>				