

Vehicle Identification Number

Technician (Print Name)

Dealer/BAC Code

Deliciencies mast be called to Service Mariage	ment's attention. Inspect, perform, verify proper operation	
tial Preparation:	Road Test:	Special Inspection Items
Leave door edge protection and other	ODOMETER:	Engine – Vehicles with 2.0 (LTG) and 3.6
shipping/storage materials on until	Before After	(LGX) are equipped with Stop/Start. For further information see Doc ID 4069102
customer delivery	Before, during and after this test, check all	(Stop/Start Description and Operation.
Adjust tires to pressures specified on the	standard equipment, options and accessories	□ Initial Prep – Slowly remove the protective film
Certification/Tire Label. Do NOT relearn	for proper operation, as applicable.	from the Bose speakers, to avoid damaging
the Tire Pressure Monitoring System.	Drive on a legal roadway with road conditions	the speaker grille or emblem.
Record adjusted results.	permitting. Evaluate the following:	☐ Interior — Place cleaning cloth (from loose shipped parts) in Integrated Center Stack
mperature:°F °C	☐ Check Automatic Transmission Shift lock	behind the faceplate (if equipped). Otherwise,
es: LF RF LR RR	control	place in glove box.
Spare (if equipped)	☐ Check electronic steering column lock	□ <u>Interior</u> – Reprogram the HMI Module (Radio
Install loose shipped parts and all	(PEPS vehicles only) (if equipped)	RPO IO5/IO6) with the latest software
accessories (torque as needed)	Remote start (if equipped)	available. Refer to latest TSB 16-NA-042 for applicable vehicle builds.
	☐ Engine Performance: Cold start, idle	☐ Interior — If equipped with Adaptive Froward
erior:	quality	Lighting RPO T4F access personalization
Power mirrors (if equipped)	☐ Forward Collision Alert, Front and Rear	menu for vehicle settings/lighting and enable
Seats, all: Check material, operation and	Parking Assist, Lane Departure Warning,	this feature.
hat removable seats are properly secured	Side Blind Zone Alert, Lane Change Alert,	☐ Interior – Set the LKA (Lane Keep Assist)
Seat belts, all: material, operation, routing		button left of the steering column lower IP to the off position.
and latches	Rear Cross Traffic Alert, Safety Seat Alert,	Exterior – It is recommended a non-alkaline
Displays, gauges, interior and exterior	Rear Vision Camera (if equipped)	solution be used for washing the Bright
ghts	Front and rear HVAC system controls,	Aluminum Moldings. If a cleaning solution
erior:	blower(s), heater, A/C, front defroster and	greater than 11.0 pH is used the dealer MUST:
Doors, locks, all keys/fobs and keyless	rear defogger	Prewash the vehicle to bring molding to room
entry system	☐ Electronic compass for function. Set to	temperature. Apply cleaning solution out of the sunlight at room temperature. Rinse
Check child safety door/window locks are	correct zone and calibrate (if equipped)	moldings with clean water within 5 minutes of
n normal (unlocked) position (if equipped)	□ Regular and steering wheel controls for	application of cleaning solution.
	radio, CD, MP3, XM, RSA, RSE and NAV	☐ Trunk - Place the tow eye hook in the upper
Fit/Function removable top/panel	(if equipped)	right corner of the molded tray.
convertible top (if equipped)	☐ Steering wheel – center position	Final Inspection & Preparation:
Fit/function/retention of parts such as	 Steering for leads, pulls, vibration at idle, 	Perform just prior to delivery.
numpers, moldings, grille, emblems, doors,	vibration while driving	 Interior: Remove protective coverings.
deck lid, hood, fuel door and cap, tailgate,	□ Wipers, delay, RainSense and washers,	Clean as required: seats, headliner, kick
iftgate and hatches, sunroof (if equipped) Check antenna mast installation	front and rear (if equipped)	panels, carpets, console, instrument panel,
Check antenna mast installation	□ Brakes for noise, pulls, vibration or	moldings and hard trim
ler Hood:	shudder at both high and low speeds	 Install and secure the floor mat retainers
Remote hood release, latch and hood	 Unusual wind noise 	to the carpet side retainers (if equipped)
safety latch	 Unusual noise/vibration/squeak/rattle 	☐ Check heated/cooled seats/steering wheel
Check condition and charge 12V battery	 Cruise/adaptive cruise (if equipped) 	(if equipped)
using PDI Mode on the EL-50313 battery	 Transfer case operation, all ranges (if 	 Set NAV to correct region (if required)
tester/charger (Midtronics GR8). Attach	equipped)	 Exterior wash and dry, preferably by hand
print out to repair order. See TSB 03-06-	 Transmission shifter, clutch, noise, shift 	or touchless car wash to avoid paint
03-004 for additional information.	smoothness	scratches; check for water leaks
Hoses, lines, cables and wire attachments	 Engine performance: Hot start, idle quality 	☐ Check paint finish for dents, dings, chips,
are free of kinks and clear of any	 Check for MIL, SES, SVS, and any 	scratches, or blemishes. Repair.
moving/hot parts	warning lights	□ Reset fuel economy readings
Hoses, clamps, pipes, fittings, seals, and	OnStar: Verify Hot Spot (if equipped)	☐ Set clock/calendar to local time
gaskets for seepage and proper	□ Varify OnStar indicator light is groon	☐ Using a clean cloth, clean the wiper
connection	☐ Verify OnStar indicator light is green	blades using GM Optikleen windshield
Fluid levels: Add as required	☐ Wi-Fi® broadcast check – Press the	washer solvent
·	OnStar "Voice Command" button and say	☐ Thoroughly clean all glass surfaces, use
der Vehicle:	"Wi-Fi® Settings"	plain water on interior glass
/isually inspect underbody; check all fluid	Using the information on the screen	☐ Recheck tire pressures (Including spare, if
systems for leaks	connect a device, using a Wi-Fi® enabled	equipped) and 12V battery condition
Brake/fuel lines secured in clips	device (e.g. smartphone), verify that you	
	can connect to vehicle's Hot Spot	(using EL50313 battery tester/charger PDI
	Note: You do not need to press the Blue OnStar button.	Mode)
	The Demo message will continue to play during each ignition cycle until a customer purchases the vehicle and an Online Enrollment	☐ Check Investigate Vehicle History (IVH)
	is submitted by the selling Dealer.	for required field actions. All open field action
	·	must be completed prior to vehicle delivery

Date