Vehicle Identification Number

Dealer/BAC Code

Demove writtwetches iswelm, asl		Repair Order #
Remove wristwatches, jewelry, cell phones, etc., and cover belt buckles to prevent damage to the vehicle. Deficiencies must be called to Service Management's attention. Inspect, perform, verify proper operation, assembly, fit and routing of the following.		
Initial Preparation:	Road Test: ODOMETER: Before After	Initial Preparation - 'Transport Mode On' may display on the DIC or the red battery light may flash. To turn the Mode Off, start engine, activate hazard flashers, press brake pedal, then press & hold the Start/Stop button or turn the ignition key to the crank position for 15 seconds. Interior - Reprogram the HMI Module (Radio RPO IO5/IO6) with the latest software available. Refer to latest TSB 16-NA-042 for applicable vehicle builds. Exterior - Inspect surfaces for white cloudy spots. Refer to latest TSB 16-NA-220 for examples and correction action. Road Test - Verify operation of all the ESS 1 & ESS 2 Safety features (if equipped). Final Inspection & Prep - Use a non-alkaline solution for washing the Bright Aluminum Moldings. Do Not wash the vehicle until PIC5779 has been reviewed. Final Inspection & Prep - Due to normal daily & seasonal temperature changes, tire pressures MUST be rechecked at the time of delivery. Consult Tire Loading Label Recommended Cold Tire Inflation Pressure. Final Inspection & Preparation: Perform just prior to delivery. Interior: Remove protective coverings. Clean as required: seats, headliner, kick panels, carpets, console, instrument panemoldings and hard trim Install and secure the floor mat retainers the carpet side retainers (if equipped) Check heated/cooled seats/steering whee (if equipped) Set NAV to correct region (if required) Exterior wash and dry, preferably by hand or touchless car wash to avoid paint scratches; check for water leaks Check paint finish for dents, dings, chips, scratches, or blemishes. Repair. Reset fuel economy readings Set clock/calendar to local time Using a clean cloth, clean the wiper blade using GM Optikleen windshield washer solvent Thoroughly clean all glass surfaces, use plain water on interior glass Recheck tire pressures (Including spare, i equipped) and 12V battery condition (using EL50313 battery tester/charger PD Mode) Check Investigate Vehicle History (IVH) for required field actions. All open field action must be complete
	an Online Enrollment is submitted by the selling Dealer.	

Technician (Print Name)

Service Manager (Signature)

File With Repair Order

Date

011217 r1.5

Certification: I certify that this Pre-Delivery Inspection has been completed by: