Vehicle Identification Number

Dealer/BAC Code

Stock #_____ Repair Order #_

Remove wristwatches, jewelry, cel	Il phones, etc., and cover belt buckles to	prevent damage to the vehicle.
Deficiencies must be called to Service Manager	ment's attention. Inspect, perform, verify proper operatio	n, assembly, fit and routing of the following.
Initial Preparation: □ Leave door edge protection and other shipping/storage materials on until customer delivery □ Adjust tires to pressures specified on the Certification/Tire Label. Do NOT relearn the Tire Pressure Monitoring System. Record adjusted results. Temperature:°F °C Tires: LF RF LR RR Spare (if equipped) □ Install loose shipped parts and all accessories (torque as needed) Interior: □ Power mirrors (if equipped) □ Seats, all: Check material, operation and that removable seats are properly secured □ Seat belts, all: material, operation, routing and latches	Road Test: ODOMETER: Before After Before, during and after this test, check all standard equipment, options and accessories for proper operation, as applicable. Drive on a legal roadway with road conditions permitting. Evaluate the following: Check Automatic Transmission Shift lock control Check electronic steering column lock (PEPS vehicles only) (if equipped) Remote start (if equipped) Engine Performance: Cold start, idle quality Forward Collision Alert, Front and Rear Parking Assist, Lane Departure Warning, Side Blind Zone Alert, Lane Change Alert, Rear Cross Traffic Alert, Safety Seat Alert,	Special Inspection Items Initial Prep – The vehicle may be shipped in Transport Mode. Refer to latest TSB 11-08-49-001 to disable the Transport Mode. NOTE – The battery is located in the trunk. The EL-50313 battery tester/charger (Midtronics GR8) must be used to check the condition of the battery. Interior – Remove the door sill plate protective film. Interior – The passenger side Instrument Panel insert is an embroidered microfiber fabric. Refer to Owner's Manual page 10-79 for cleaning instructions Exterior – Do Not leave Protective Shipping Film in place for more than 6 months from date of mfr. If staining is present when removed refer to latest TSB 05-08-51-001. Exterior – Set the tire pressure to 36 PSI front & 36 PSI rear. Refer to latest bulletin PI1084. Verify RPO KTI is inflator kit and RPO QSB has full size spare. Under Vehicle – Remove the rear brake disc protection covers. Refer to latest bulletin PI1084. Road Test – Verify the function, alignment &
□ Displays, gauges, interior and exterior	Rear Vision Camera (if equipped) Front and rear HVAC system controls,	visibility of the Head-Up Display (HUD). Final Inspection & Preparation:
Exterior: Doors, locks, all keys/fobs and keyless entry system Check child safety door/window locks are in normal (unlocked) position (if equipped) Fit/Function removable top/panel convertible top (if equipped) Fit/function/retention of parts such as bumpers, moldings, grille, emblems, doors, deck lid, hood, fuel door and cap, tailgate, liftgate and hatches, sunroof (if equipped) Check antenna mast installation Under Hood: Remote hood release, latch and hood safety latch Check condition and charge 12V battery using PDI Mode on the EL-50313 battery tester/charger (Midtronics GR8). Attach print out to repair order. See TSB 03-06-03-004 for additional information. Hoses, lines, cables and wire attachments are free of kinks and clear of any moving/hot parts Hoses, clamps, pipes, fittings, seals, and gaskets for seepage and proper connection Fluid levels: Add as required Under Vehicle: Visually inspect underbody; check all fluid systems for leaks Brake/fuel lines secured in clips	blower(s), heater, A/C, front defroster and rear defogger Electronic compass for function. Set to correct zone and calibrate (if equipped) Regular and steering wheel controls for radio, CD, MP3, XM, RSA, RSE and NAV (if equipped) Steering wheel – center position Steering for leads, pulls, vibration at idle, vibration while driving Wipers, delay, RainSense and washers, front and rear (if equipped) Brakes for noise, pulls, vibration or shudder at both high and low speeds Unusual wind noise Unusual vind noise Unusual noise/vibration/squeak/rattle Cruise/adaptive cruise (if equipped) Transfer case operation, all ranges (if equipped) Transmission shifter, clutch, noise, shift smoothness Engine performance: Hot start, idle quality Check for MIL, SES, SVS, and any warning lights OnStar: Verify Hot Spot (if equipped) Verify OnStar indicator light is green Wi-Fi® broadcast check – Press the OnStar "Voice Command" button and say "Wi-Fi® Settings" Using the information on the screen connect a device, using a Wi-Fi® enabled device (e.g. smartphone), verify that you can connect to vehicle's Hot Spot Note: You do not need to press the Blue OnStar button. The Demo message will continue to play during each ignition cycle until a customer purchases the vehicle and an Online Enrollment is submitted by the selling Dealer.	Perform just prior to delivery. Interior: Remove protective coverings. Clean as required: seats, headliner, kick panels, carpets, console, instrument panel moldings and hard trim Install/secure the floor mat retainers to the carpet side retainers (if equipped) Check heated/cooled seats/steering wheel (if equipped) Set NAV to correct region (if required) Exterior wash and dry, preferably by hand or touchless car wash to avoid paint scratches; check for water leaks Check paint finish for dents, dings, chips, scratches, or blemishes. Repair. Reset fuel economy readings Set clock/calendar to local time Using a clean cloth, clean the wiper blades using GM Optikleen windshield washer solvent Thoroughly clean all glass surfaces, use plain water on interior glass Recheck tire pressures (Including spare, if equipped) and 12V battery condition (using EL50313 battery tester/charger PDI Mode) Check Investigate Vehicle History (IVH) for required field actions. All open field actions must be completed prior to vehicle delivery
Certification: I certify that this Pre-Delivery Insp	ection has been completed by:	
Technician (Print Name)	ervice Manager (Signature)	Date

File With Repair Order

112116 r1.6