

Certification: I certify that this Pre-Delivery Inspection has been completed by:

Service Manager (Signature)

Technician (Print Name)

Vehicle Identification Number

Dealer/BAC Code

		Repair Order #
Remove wristwatches, jewelry, ce	II phones, etc., and cover belt buckles to	prevent damage to the vehicle.
Deficiencies must be called to Service Manage	ment's attention. Inspect, perform, verify proper operatio	n, assembly, fit and routing of the following.
Initial Preparation:	Road Test:	
Leave door edge protection and other	ODOMETER:	Special Inspection Items Initial Preparation – "Transport Mode On' may
shipping/storage materials on until	Before After	display on the DIC or the red battery light may
customer delivery	Before, during and after this test, check all	flash. To turn the mode off, refer to latest TSB
☐ Adjust tires to pressures specified on the	standard equipment, options and accessories	11-08-49-001.
Certification/Tire Label. Do NOT relearn	for proper operation, as applicable.	<ul> <li>Initial Preparation – Ensure all GM Accessories have been installed. Examples: Cargo hooks, roof</li> </ul>
the Tire Pressure Monitoring System.	Drive on a legal roadway with road conditions	cross rails, etc. Refer to Accessory Installation
Record adjusted results.	permitting. Evaluate the following:	Manual in SI.
Temperature:°F °C	☐ Check Automatic Transmission Shift lock	□ <u>Interior</u> – Place cleaning cloth (from loose shipped
Tires: LF RF LR RR	control	parts) in Integrated Center Stack behind the faceplate (if equipped). Otherwise, place in glove
Spare (if equipped)	☐ Check electronic steering column lock	box.
☐ Install loose shipped parts and all	(PEPS vehicles only) (if equipped)	□ Interior – Reprogram the HMI Module (Radio RPO
accessories (torque as needed)	□ Remote start (if equipped)	IO5/IO6) with the latest software available. Refer to
Interior:	☐ Engine Performance: Cold start, idle	latest TSB 16-NA-042 for applicable vehicle builds.  Exterior – Place capless fuel funnel in rear cargo
□ Power mirrors (if equipped)	quality	sysyem (from loose shipped parts).
□ Seats, all: Check material, operation and	□ Forward Collision Alert, Front and Rear	□ Exterior – Install the side door latch plate covers
that removable seats are properly secured	Parking Assist, Lane Departure Warning,	on Denali models. Refer to latest bulletin PIT5259.  Note – Vehicles in dealer inventory need to be
☐ Seat belts, all: material, operation, routing	Side Blind Zone Alert, Lane Change Alert,	properly maintained for a quality delivery. Refer to
and latches	Rear Cross Traffic Alert, Safety Seat Alert,	latest TSB 09-00-89-002.
☐ Displays, gauges, interior and exterior	Rear Vision Camera (if equipped)	□ <u>Final Inspection &amp; Prep</u> – Restore Radio to
lights	☐ Front and rear HVAC system controls,	Factory settings. In the settings menu, Select Restore Radio Settings. A screen displays stating
Exterior:	blower(s), heater, A/C, front defroster and	all personalized radio settings will be restored back
□ Doors, locks, all keys/fobs and keyless	rear defogger	to the factory.
entry system	☐ Electronic compass for function. Set to	Final Inspection & Prep – Due to normal daily &
☐ Check child safety door/window locks are	correct zone and calibrate (if equipped)  Regular and steering wheel controls for	seasonal temperature changes, tire pressures MUST be rechecked at time of delivery. Consult
in normal (unlocked) position (if equipped)	radio, CD, MP3, XM, RSA, RSE and NAV	Tire Loading Label Recommended Cold Tire
☐ Fit/Function removable top/panel	(if equipped)	Inflation Pressure.
convertible top (if equipped)	☐ Steering wheel – center position	Final Inspection & Preparation:
☐ Fit/function/retention of parts such as	☐ Steering for leads, pulls, vibration at idle,	Perform just prior to delivery.
bumpers, moldings, grille, emblems, doors,	vibration while driving	Interior: Remove protective coverings.
deck lid, hood, fuel door and cap, tailgate,	□ Wipers, delay, RainSense and washers,	Clean as required: seats, headliner, kick
liftgate and hatches, sunroof (if equipped)	front and rear (if equipped)	panels, carpets, console, instrument pane
<ul> <li>Check antenna mast installation</li> </ul>	<ul> <li>Brakes for noise, pulls, vibration or</li> </ul>	moldings and hard trim
<u>Under Hood</u> :	shudder at both high and low speeds	<ul> <li>Install and secure the floor mat retainers t</li> </ul>
<ul> <li>Remote hood release, latch and hood</li> </ul>	☐ Unusual wind noise	the carpet side retainers (if equipped)
safety latch	Unusual noise/vibration/squeak/rattle	☐ Check heated/cooled seats/steering whee
☐ Check condition and charge 12V battery	☐ Cruise/adaptive cruise (if equipped)	(if equipped)  ☐ Set NAV to correct region (if required)
using <b>PDI Mode</b> on the EL-50313 battery	☐ Transfer case operation, all ranges (if	<ul><li>Set NAV to correct region (in required)</li><li>Exterior wash and dry, preferably by hand</li></ul>
tester/charger (Midtronics GR8). Attach	equipped)  Transmission shifter, clutch, noise, shift	or touchless car wash to avoid paint
print out to repair order. See TSB 03-06- 03-004 for additional information.	smoothness	scratches; check for water leaks
☐ Hoses, lines, cables and wire attachments	☐ Engine performance: Hot start, idle quality	☐ Check paint finish for dents, dings, chips,
are free of kinks and clear of any	☐ Check for MIL, SES, SVS, and any	scratches, or blemishes. Repair.
moving/hot parts	warning lights	□ Reset fuel economy readings
☐ Hoses, clamps, pipes, fittings, seals, and	OnStar: Verify Hot Spot (if equipped)	☐ Set clock/calendar to local time
gaskets for seepage and proper	□ Verify OnStar indicator light is green	<ul> <li>Using a clean cloth, clean the wiper blade</li> </ul>
connection	☐ Wi-Fi® broadcast check – Press the	using GM Optikleen windshield washer
☐ Fluid levels: Add as required	OnStar "Voice Command" button and say	solvent
Under Vehicle:	"Wi-Fi® Settings"	☐ Thoroughly clean all glass surfaces, use
☐ Visually inspect underbody; check all fluid	☐ Using the information on the screen	plain water on interior glass
systems for leaks	connect a device, using a Wi-Fi® enabled	Recheck tire pressures (Including spare, i
☐ Brake/fuel lines secured in clips	device (e.g. smartphone), verify that you	equipped) and 12V battery condition
	can connect to vehicle's Hot Spot	(using EL50313 battery tester/charger <b>PD</b>
	Note: You do not need to press the Blue OnStar button.	Mode)  Chock Investigate Vehicle History (IVH) for
	The Demo message will continue to play during each	<ul> <li>Check Investigate Vehicle History (IVH) for required field actions. All open field action</li> </ul>
	ignition cycle until a customer purchases the vehicle and an Online Enrollment is submitted by the selling Dealer.	must be completed prior to vehicle delivery
	a S Enforment is submitted by the sening bedief.	soc so completed prior to volitor delivery