

2017 CTS-V Sedan (RPO IO5 & IO6)

Pre-Delivery Inspection Form

Dealer/BAC Code

Vehicle Identification Number

_ Repair Order #_ Stock #___ Remove wristwatches, jewelry, cell phones, etc., and cover belt buckles to prevent damage to the vehicle.

nitial Preparation:	Road Test and other ODOMETI		Special Inspection Items Initial Prep – Remove the yellow Transit
Leave door edge protection a			Blocks from the front springs. Place the transit
shipping/storage materials or customer delivery		After ring and after this test, check all	blocks, tow eye, and roadside fuel funnel in the
Adjust tires to pressures spec		quipment, options and accessories	molded storage bin under the trunk closeout
Certification/Tire Label. Do N		operation, as applicable.	panel. Initial Prep – Remove the Transit Block Sticker
the Tire Pressure Monitoring		legal roadway with road conditions	Initial Prep – Remove the Transit Block Sticker from the driver's door window.
Record adjusted results.		Evaluate the following:	☐ Interior – Slowly remove the protective film
remperature:°F °C	•	•	from the Bose speakers to avoid damaging the
•	U Check	Automatic Transmission Shift lock	speaker grille or emblem. Initial Prep – Remove the protective film from
	RR control	alastas ais ataunin a saluman la al-	the Supercharger cover.
Spare (if equipped)		electronic steering column lock	□ <u>Interior</u> − Place cleaning cloth (from loose
Install loose shipped parts an		vehicles only) (if equipped)	shipped parts) in Integrated Center Stack
accessories (torque as neede		e start (if equipped)	behind the faceplate.
<u>nterior:</u>		Performance: Cold start, idle	 Interior – Set the LKA (Lane Keep Assist) button on the center stack to the off position.
Power mirrors (if equipped)	quality □ Forwar	d Callisian Mart Front and Boar	□ Interior – Remove and discard the red cap on
Seats, all: Check material, op	Dorling	d Collision Alert, Front and Rear	the Performance Data Recorder (PDR) that is
that removable seats are prop		Assist, Lane Departure Warning,	located behind the inside rearview mirror.
Seat belts, all: material, opera		ind Zone Alert, Lane Change Alert,	Exterior – Use a non-alkaline solution to wash
and latches		ross Traffic Alert, Safety Seat Alert,	the Bright Aluminum Moldings. Do NOT wash the vehicle until latest bulletin PIC5779 has
 Displays, gauges, interior and 		ision Camera (if equipped)	been reviewed.
lights		nd rear HVAC system controls,	□ Exterior – Vehicles equipped with the Carbon
Exterior:		s), heater, A/C, front defroster and	Fiber Package (RPO CFZ) DO NOT come with
□ Doors, locks, all keys/fobs an	rear de nd keyless □ Electro	nic compass for function. Set to	front tire air deflector kits in the loose shipped parts by design. Do not order a front tire
entry system	- = =	zone and calibrate (if equipped)	deflector kit for vehicles equipped with CFZ.
☐ Check child safety door/wind		r and steering wheel controls for	Final Inspection & Preparation:
in normal (unlocked) position		CD, MP3, XM, RSA, RSE and NAV	Perform just prior to delivery.
☐ Fit/Function removable top/pa			☐ Interior: Remove protective coverings.
convertible top (if equipped)	(• 9 • · ·	g wheel – center position	Clean as required: seats, headliner, kick
☐ Fit/function/retention of parts		g for leads, pulls, vibration at idle,	panels, carpets, console, instrument pane
bumpers, moldings, grille, en		n while driving	moldings and hard trim
deck lid, hood, fuel door and	. "	, delay, RainSense and washers,	Install and secure the floor mat retainers to
liftgate and hatches, sunroof		nd rear (if equipped)	the carpet side retainers (if equipped)
Check antenna mast installat		for noise, pulls, vibration or	□ Check heated/cooled seats/steering whee
Jnder Hood:		er at both high and low speeds	(if equipped)
Remote hood release, latch a		al wind noise	 Set NAV to correct region (if required)
safety latch	411G 1100G	al noise/vibration/squeak/rattle	 Exterior wash and dry. Check for water
 Check condition and charge 		adaptive cruise (if equipped)	leaks
using PDI Mode on the EL-50		er case operation, all ranges (if	 Check paint finish for dents, dings, chips,
tester/charger (Midtronics GF			scratches, or blemishes. Repair.
print out to repair order. See		nission shifter, clutch, noise, shift	 Reset fuel economy readings
03-004 for additional information			 Set clock/calendar to local time
☐ Hoses, lines, cables and wire		performance: Hot start, idle quality	 Using a clean cloth, clean the wiper blade
are free of kinks and clear of	_ ^ '	for MIL, SES, SVS, and any	using GM Optikleen windshield washer
moving/hot parts	warning		fluid, if necessary
☐ Hoses, clamps, pipes, fittings	s. seals. and OnStar: V	erify Hot Spot (if equipped)	☐ Thoroughly clean all glass surfaces, use
gaskets for seepage and proj		OnStar indicator light is green	plain water on interior glass
connection	_ voiny v	broadcast check – Press the	 Recheck tire pressures (Including spare, if
Fluid levels: Add as required		"Voice Command" button and say	equipped) and 12V battery condition
•		Settings"	(using EL50313 battery tester/charger PD
Jnder Vehicle:		he information on the screen	Mode)
 Visually inspect underbody; or leaks 		t a device, using a Wi-Fi® enabled	☐ Check Investigate Vehicle History (IVH) fo
systems for leaks		(e.g. smartphone), verify that you	required field actions. All open field action
☐ Brake/fuel lines secured in cli	F ~	nnect to vehicle's Hot Spot	must be completed prior to vehicle deliver
		not need to press the Blue OnStar button.	
		nessage will continue to play during each	
		until a customer purchases the vehicle and	

Technician (Print Name) Service Manager (Signature) Date File With Repair Order 052417 r1.3

Page 1 of 1

Certification: I certify that this Pre-Delivery Inspection has been completed by: