

Pre-Delivery Inspection Form

RR

Vehicle Identification Number

Dealer/BAC Code

Repair Order #

Remove wristwatches, jewelry, cell phones, etc., and cover belt buckles to prevent damage to the vehicle

Deficiencies must be called to Service Management's attention. Inspect, perform, verify proper operation, a

Initial Preparation:

- □ Leave door edge protection and other shipping/storage materials on until customer delivery
- □ Adjust tires to pressures specified on the Certification/Tire Label. Do NOT relearn the Tire Pressure Monitoring System. Record adjusted results. °C

Temperature: °F

- Tires: LF RF LR
- Spare _ _ (if equipped)
- Install loose shipped parts and all accessories (torque as needed)
- Interior:
- □ Power mirrors (if equipped)
- Seats, all: Check material and operation of all features
- □ Check that removable seats are properly secured
- Check all accessory power outlets and AC inverter (if equipped)
- □ Seat belts, all: material, operation, routing and latches
- Displays, gauges, interior and exterior liahts
- □ Center stack and steering wheel controls for infotainment/ radio and NAV (if equipped)
- □ HVAC system controls, blower, heater, A/C, defroster and rear defogger
- Rear HVAC Control function (if equipped)
- Check heated/cooled seats/steering wheel (if equipped)

Exterior:

- Doors, locks, all keys/fobs and keyless entry system
- Check child safety door/window locks are in normal (unlocked) position
- □ Fit/Function removable top/panel convertible top (if equipped)
- □ Fit/function/retention of parts such as bumpers, moldings, grille, emblems, doors, deck lid, hood, fuel door and cap, tailgate, liftgate and hatches, sunroof (if equipped)
- Check antenna mast installation

Under Hood:

- Remote hood release, latch and hood safety latch
- Check condition and charge 12V battery using PDI Mode on the EL-50313 battery tester/charger (Midtronics GR8). Attach print out to repair order. See TSB 03-06-03-004 for additional information.
- Hoses, lines, cables and wire attachments are free of kinks and clear of any moving/hot parts
- Hoses, clamps, pipes, fittings, seals, and gaskets for seepage and proper retention
- Fluid levels: Add as required
- Certification: I certify that this Pre-Delivery Inspection has been completed by:

- Visually inspect underbody; check all fluid systems for leaks
- Brake/fuel lines secured in clips

Road Test:

ODOMETER:

Before After

Before, during and after this test, check all standard equipment, options and accessories for proper operation, as applicable. Drive on a legal roadway with road conditions permitting. Evaluate the following:

- Check Automatic Transmission Shift lock control and shifter operation
- Check electronic steering column lock
- (PEPS vehicles only) (if equipped) Remote start (if equipped)
- □ Engine Performance: Cold start, idle quality
- □ Safety Systems: Front and Rear Parking Assist, Lane Departure Warning, Side Blind Zone Alert, Lane Change Alert, Rear Cross Traffic Alert, Safety Alert Seat, Camera Vision Systems (if equipped)
- Electronic compass for function.
- Steering wheel center position
- Steering for leads, pulls, vibration at idle, vibration while driving
- □ Wipers, delay, RainSense and washers, front and rear (if equipped)
- Brakes for noise, pulls, vibration or shudder at both high and low speeds
- Unusual wind noise
- Unusual noise/vibration/squeak/rattle
- Cruise/adaptive cruise (if equipped)
- Transfer case operation, all ranges (if equipped)
- Manual Transmission shifter, clutch, noise, shift smoothness
- Automatic Transmission shift performance
- Automatic Park Assist for operation (if (baggiupe
- Verify AutoStop/Start operation during Road Test
- Engine performance: Hot start, idle quality
- Check for warning lights and messages
- OnStar:
- Verify OnStar indicator light is green
- □ Connect a Wi-Fi® enabled device (e.g. smartphone) to the vehicle and verify that you can connect to vehicle's Hot Spot. If you can't connect to the Hot Spot, refer to the latest version of TSB 16-NA-239 for steps to enable it.

Note: The Demo message will continue to play during each ignition cycle until a customer purchases the vehicle and an Online Enrollment is submitted by the selling Dealer.

prevent damage to the vehicle.		
assembly, fit and routing of the following.		
	Special Inspection Items Engine – Vehicles with 2.0 (LTG) and 3.6 (LGX) are equipped with Stop/Start. For further	
	information see Doc ID 4069102 (Stop/Start	
	Description and Operation. <u>Initial Prep</u> – Slowly remove the protective film from the Bose speakers, to avoid damaging the	
	speaker grille or emblem.	
	Interior – Place cleaning cloth (from loose shipped parts) in Integrated Center Stack behind the faceplate (if equipped). Otherwise, place in glove	
	box. Interior – If equipped with Adaptive Froward	
	Lighting RPO T4F access personalization menu for vehicle settings/lighting and enable this feature.	
	Interior – Set the LKA (Lane Keep Assist) button left of the steering column lower IP to the off	
_	position.	
	<u>Infotainment</u> – Press the User icon on the CUE home screen and sign in as a Guest. Connect a smart phone via USB and verify you can make a	
	phone call and listen to music.	
	Infotainment – If vehicle has RPO IOT (Navigation), ensure that the Nav SD card that is	
	located beneath the USB hub in the armrest	
	console is inserted correctly and is functional. Infotainment – Go to the Collection icon on the	
	CUE screen, Verify that there are apps available to download.	
	Exterior – It is recommended a non-alkaline	
	solution be used for washing the Bright Aluminum Moldings. If a cleaning solution greater than 11.0	
	pH is used the dealer MUST : Prewash the vehicle	
	to bring molding to room temperature. Apply	
	cleaning solution out of the sunlight at room temperature. Rinse moldings with clean water	
	within 5 minutes of application of cleaning solution.	
	Trunk - Place the tow eye hook and roadside fuel	
	funnel in the upper right corner of the molded	
	storage bin under the trunk close out panel.	
	nal Inspection & Preparation:	
-e	rform just prior to delivery.	
	Interior: Remove protective coverings.	
	Clean as required: seats, headliner, kick	
	panels, carpets, console, instrument panel	¥,
	moldings and hard trim	
	Install and secure the floor mat retainers to	С
	the carpet side retainers (if equipped)	
	Exterior wash and dry. Check for water leaks	
	Check paint finish for dents, dings, chips,	
	scratches, or blemishes.	
	Reset fuel economy readings	
	Set clock/calendar to local time	

- Set clock/calendar to local time
- Using a clean cloth, clean the wiper blades using GM Optikleen windshield washer fluid, if necessary
- □ Thoroughly clean all glass surfaces, use plain water on interior glass
- Recheck tire pressures (Including spare, if equipped) and 12V battery condition (using EL50313 battery tester/charger PDI Mode)
- Check Investigate Vehicle History (IVH) for required field actions. All open field actions must be completed prior to vehicle delivery

Technician (Print Name)

Service Manager (Signature) File With Repair Order

F

Stock #

adillac