

## 2018 ATS Sedan **Pre-Delivery Inspection Form**

Hoses, clamps, pipes, fittings, seals, and gaskets for seepage and proper retention

Certification: I certify that this Pre-Delivery Inspection has been completed by:

□ Fluid levels: Add as required

	Vehicle Identification Number	Dealer/BAC Code		
		Stock #		Repair Order #
	Remove wristwatches, iewelry, cel	I phones, etc., and cover belt buckles to		
			-	_
		nent's attention. Inspect, perform, verify proper operation	ı, as	sembly, ht and routing of the following.
	tial Preparation:	Under Vehicle:		Special Inspection Items
	Leave door edge protection and other	☐ Visually inspect underbody; check all fluid		Engine – Vehicles with 2.0 (LTG) and 3.6 (LGX)
	shipping/storage materials on until	systems for leaks		are equipped with Stop/Start. For further information see Doc ID 4069102 (Stop/Start
	customer delivery	☐ Brake/fuel lines secured in clips		Description and Operation.
	Adjust tires to pressures specified on the	Road Test:		Initial Prep – Slowly remove the protective film
	Certification/Tire Label. Do NOT relearn	ODOMETER:		from the Bose speakers, to avoid damaging the speaker grille or emblem.
	the Tire Pressure Monitoring System.	Before After		<u>Interior</u> – Place cleaning cloth (from loose shipped
т.	Record adjusted results.  mperature: °F °C	Before, during and after this test, check all		parts) in Integrated Center Stack behind the
		standard equipment, options and accessories for proper operation, as applicable.		faceplate (if equipped). Otherwise, place in glove box.
	es: LF RF LR RR	Drive on a legal roadway with road conditions		Interior - If equipped with Adaptive Froward
	Spare (if equipped)	permitting. Evaluate the following:		Lighting RPO T4F access personalization menu for vehicle settings/lighting and enable this feature.
	Install loose shipped parts and all			Interior – Set the LKA (Lane Keep Assist) button
	accessories (torque as needed)	☐ Check Automatic Transmission Shift lock		left of the steering column lower IP to the off
	erior:	control and shifter operation		position.
	Power mirrors (if equipped)	□ Check electronic steering column lock		Infotainment – Press the User icon on the CUE home screen and sign in as a Guest. Connect a
	Seats, all: Check material and operation of	(PEPS vehicles only) (if equipped)		smart phone via USB and verify you can make a
	all features	Remote start (if equipped)		phone call and listen to music.
	Check that removable seats are properly	☐ Engine Performance: Cold start, idle		Infotainment – If vehicle has RPO IOT (Navigation), ensure that the Nav SD card that is
	secured	quality		located beneath the USB hub in the armrest
Ш	Check all accessory power outlets and AC	□ Safety Systems:Front and Rear Parking		console is inserted correctly and is functional.
	inverter (if equipped)	Assist, Lane Departure Warning, Side		Infotainment – Go to the Collection icon on the CUE screen, Verify that there are apps available to
Ш	Seat belts, all: material, operation, routing	Blind Zone Alert, Lane Change Alert, Rear		download.
	and latches	Cross Traffic Alert, Safety Alert Seat,		Exterior – It is recommended a non-alkaline
Ш	Displays, gauges, interior and exterior lights	Camera Vision Systems (if equipped)  Electronic compass for function.		solution be used for washing the Bright Aluminum Moldings. If a cleaning solution greater than 11.0
	Center stack and steering wheel controls	☐ Steering wheel – center position		pH is used the dealer <b>MUST</b> : Prewash the vehicle
	for infotainment/ radio and NAV (if	☐ Steering wheel — center position ☐ Steering for leads, pulls, vibration at idle,		to bring molding to room temperature. Apply
	equipped)	vibration while driving		cleaning solution out of the sunlight at room temperature. Rinse moldings with clean water
П	HVAC system controls, blower, heater,	☐ Wipers, delay, RainSense and washers,		within 5 minutes of application of cleaning solution.
	A/C, defroster and rear defogger	front and rear (if equipped)		<u>Trunk</u> – Place the tow eye hook in the upper right corner of the molded tray.
	Rear HVAC Control function (if equipped)	☐ Brakes for noise, pulls, vibration or shudder	Fi	nal Inspection & Preparation:
	Check heated/cooled seats/steering wheel	at both high and low speeds	_	erform just prior to delivery.
	(if equipped)	☐ Unusual wind noise		Interior: Remove protective coverings.
	terior:	<ul> <li>Unusual noise/vibration/squeak/rattle</li> </ul>		Clean as required: seats, headliner, kick
	Doors, locks, all keys/fobs and keyless	☐ Cruise/adaptive cruise (if equipped)		panels, carpets, console, instrument panel
	entry system	☐ Transfer case operation, all ranges (if		moldings and hard trim
	Check child safety door/window locks are	equipped)		Install and secure the floor mat retainers to
	in normal (unlocked) position	☐ Manual Transmission shifter, clutch, noise,		the carpet side retainers (if equipped)
	Fit/Function removable top/panel	shift smoothness		Exterior wash and dry. Check for water
	convertible top (if equipped) Fit/function/retention of parts such as	☐ Automatic Transmission shift performance		leaks
	bumpers, moldings, grille, emblems, doors,	<ul> <li>Automatic Park Assist for operation (if equipped)</li> </ul>		
	deck lid, hood, fuel door and cap, tailgate,	□ Verify AutoStop/Start operation during		scratches, or blemishes.
	liftgate and hatches, sunroof (if equipped)	Road Test		Reset fuel economy readings
	Check antenna mast installation	☐ Engine performance: Hot start, idle quality		Set clock/calendar to local time
	der Hood:	☐ Check for warning lights and messages		Using a clean cloth, clean the wiper blades using GM Optikleen windshield washer
_	Remote hood release, latch and hood	OnStar:		fluid, if necessary
	safety latch	☐ Verify OnStar indicator light is green		Thoroughly clean all glass surfaces, use
	Check condition and charge 12V battery	☐ Connect a Wi-Fi® enabled device (e.g.		plain water on interior glass
	using <b>PDI Mode</b> on the EL-50313 battery	smartphone) to the vehicle and verify that	П	Recheck tire pressures (Including spare, if
	tester/charger (Midtronics GR8). Attach	you can connect to vehicle's Hot Spot. If		equipped) and 12V battery condition
	print out to repair order. See TSB 03-06-	you can't connect to the Hot Spot, refer to		(using EL50313 battery tester/charger <b>PDI</b>
	03-004 for additional information.	the latest version of TSB 16-NA-239 for		Mode)
	Hoses, lines, cables and wire attachments	steps to enable it.		Check Investigate Vehicle History (IVH) for
	are free of kinks and clear of any	<u>Note:</u> The Demo message will continue to play during each		required field actions. All open field actions
	moving/hot parts	ignition cycle until a customer purchases the vehicle and		must be completed prior to vehicle delivery

Technician (Print Name) Service Manager (Signature) Date

an Online Enrollment is submitted by the selling Dealer.

must be completed prior to vehicle delivery