

2018 Silverado HD **CHEVROLET** Pre-Delivery Inspection Form

Vehicle Identification Number

Dealer/BAC Code

Stock #_____ Repair Order #_

053017 r1.0

Page 1 of 1

Remove wristwatches, jewelry, cell phones, etc., and cover belt buckles to prevent damage to the vehicle.		
Deficiencies must be called to Service Mana	gement's attention. Inspect, perform, verify proper operatio	n, assembly, fit and routing of the following.
Initial Preparation: □ Leave door edge protection and other shipping/storage materials on until customer delivery □ Adjust tires to pressures specified on the Certification/Tire Label. Do NOT relearn the Tire Pressure Monitoring System. Record adjusted results. Temperature:°F °C Tires: LF RF LR RR Spare (if equipped) Install loose shipped parts and all accessories (torque as needed) Interior: Power mirrors (if equipped) Seats, all: Check material and operation of all features Check all accessory power outlets and AC inverter (if equipped) Seat belts, all: material, operation, routing and latches Displays, gauges, interior and exterior lights Center stack and steering wheel controls for infotainment/ radio and NAV (if equipped) HVAC system controls, blower, heater, A/C, defroster and rear defogger Check heated/cooled seats/steering wheel (if equipped) Exterior: □ Doors, locks, all keys/fobs and keyless entry system Check child safety door/window locks are in normal (unlocked) position Fit/Function removable top/panel convertible top (if equipped) Fit/function/retention of parts such as bumpers, moldings, grille, emblems, door deck lid, hood, fuel door and cap, tailgate, liftgate and hatches, sunroof (if equipped) Check antenna mast installation Under Hood: Remote hood release, latch and hood safety latch Check condition and charge 12V battery using PDI Mode on the EL-50313 battery tester/charger (Midtronics GR8). Attach print out to repair order. See TSB 03-06-03-004 for additional information. Hoses, lines, cables and wire attachments are free of kinks and clear of any moving/hot parts	Under Vehicle: Visually inspect underbody; check all fluid systems for leaks Brake/fuel lines secured in clips Road Test: ODOMETER: Before After Before, during and after this test, check all standard equipment, options and accessories for proper operation, as applicable. Drive on a legal roadway with road conditions permitting. Evaluate the following: Check Automatic Transmission Shift lock control and shifter operation Check electronic steering column lock (PEPS vehicles only) (if equipped) Remote start (if equipped) Braine Performance: Cold start, idle quality Safety Systems:Front and Rear Parking Assist, Lane Departure Warning, Side Blind Zone Alert, Lane Change Alert, Rear Cross Traffic Alert, Safety Alert Seat, Camera Vision Systems (if equipped) Electronic compass for function Steering wheel – center position Steering for leads, pulls, vibration at idle, vibration while driving Wipers, delay, RainSense and washers, front and rear (if equipped) Brakes for noise, pulls, vibration or shudder at both high and low speeds Unusual wind noise Unusual moise/vibration/squeak/rattle Cruise/adaptive cruise (if equipped) Transfer case operation, all ranges (if equipped) Automatic Transmission shift performance Automatic Park Assist for operation (if equipped) Engine performance: Hot start, idle quality Check for warning lights and messages OnStar: Verify OnStar indicator light is green Connect a Wi-Fi® enabled device (e.g. smartphone) to the vehicle and verify that you can't connect to the Hot Spot, refer to the latest version of TSB 16-NA-239 for steps to enable if	Special Inspection Items Preparation - "Transport Mode On" may display on the DIC or the red battery light may flash. To turn the mode off, start the engine, activate hazard flashers, press brake pedal and turn the ignition key to the crank position for 15 seconds. Initial Prep - Ensure all GM accessories are installed. Examples: cargo lamps, running boards, cargo hooks. Refer to accessory installation manual in SI - Dual Rear Wheel Vehicles Only. Install valve stem extensions on vehicles with Chrome Trim Skins (RPO Q9A). Note - Vehicles built with SEO 8S3, Backup Alarm. The backup alarm must be connected during PDI, refer to latest bulletin PIT5386 for instructions. Interior - Place cleaning cloth (from loose shipped parts) in Integrated Center Stack behind the faceplate (if equipped). Otherwise, place in glove box. Final Inspection & Prep - Vehicles built with Duramax Diesel engines (RPOs L5P) only. Diesel Exhaust Fluid (DEF) MUST be filled at the time of Pre-Delivery Inspection up to 9.5L (2.5 gallons). Refer to the Duramax Diesel Owner Manual supplement. Final Inspection & Prep - CNG Fuel System (RPO: LC8) Check operation and functionality of CNG system during road test. "DO NOT remove any CNG stickers or placards. Final Inspection & Preparation: Perform just prior to delivery. Interior: Remove protective coverings. Clean as required: seats, headliner, kick panels, carpets, console, instrument panel moldings and hard trim Secure floor mat retainers to the carpet side retainers (if equipped). Do Not stack mats. See warning in TSB 10-08-110-001 Exterior wash and dry. Check for water leaks Check paint finish for dents, dings, chips, scratches, or blemishes. Reset fuel economy readings Set clock/calendar to local time Using a clean cloth, clean the wiper blades using GM Optikleen windshield washer fluid, if necessary Thoroughly clean all glass surfaces, use plain water on interior glass Recheck tire pressures (Including spare, if equipped) and 12V battery condition (using EL50313 battery tester/charger PDI
	ignition cycle until a customer purchases the vehicle and	Mode)
Certification: I certify that this Pre-Delivery In Technician (Print Name)	spection has been completed by: Service Manager (Signature)	Date

File With Repair Order